

Document Title	Acceptance Test Specification of RTE
<b>Document Owner</b>	AUTOSAR
<b>Document Responsibility</b>	AUTOSAR
<b>Document Identification No</b>	634
Document Classification	Auxiliary

<b>Document Status</b>	Final
Part of AUTOSAR Standard	Acceptance Tests for Classic Platform
Part of Standard Release	1.2.0

	Document Change History					
Date						
2016-12-15	1.2.0	AUTOSAR Release Management	<ul> <li>Checked and adapted to Classic Platform Release 4.2.2</li> <li>Added test suites for RS_BRF_01416 – RTE NvDataHandling</li> <li>Added testcases for Rte Client Server Communication (ATS_RTE_00864 and ATS_RTE_00852)</li> <li>Updated testcases for Sender-receiver communication (ATS_RTE_00654, ATS_RTE_00698 and ATS_RTE_00689)</li> </ul>			
2015-10-31	1.1.0	AUTOSAR Release Management	<ul> <li>Adaptations needed to test Classic Platform R3.2 are no more maintained. Please refer to Classic Platform Acceptance Tests R1.0.0.</li> <li>Added test cases for         <ul> <li>Sender-receiver communication</li> <li>Scheduling (ATS_RTE_00694 &amp; ATS_RTE_00707)</li> <li>Miscellaneous features (IRV, Enhanced modes, Ports, Pim, CData, Prm APIs)</li> </ul> </li> <li>Checked and adapted to Classic Platform Release 4.2.1</li> <li>Formalization of the point of control and observation for actions and expected results</li> <li>Formal changes</li> </ul>			
2014-07-30	1.0.0	AUTOSAR Release Management	Initial release			



#### **Disclaimer**

This specification and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the specification.

The material contained in this specification is protected by copyright and other types of Intellectual Property Rights. The commercial exploitation of the material contained in this specification requires a license to such Intellectual Property Rights.

This specification may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the specification may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The AUTOSAR specifications have been developed for automotive applications only. They have neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

#### Advice for users

AUTOSAR specifications may contain exemplary items (exemplary reference models, "use cases", and/or references to exemplary technical solutions, devices, processes or software).

Any such exemplary items are contained in the specifications for illustration purposes only, and they themselves are not part of the AUTOSAR Standard. Neither their presence in such specifications, nor any later documentation of AUTOSAR conformance of products actually implementing such exemplary items, imply that intellectual property rights covering such exemplary items are licensed under the same rules as applicable to the AUTOSAR Standard.



## **Table of Contents**

1	Acron	yms and abbreviations	10
2	Scope	9	11
3	RS_B	RF_01312 - Rte Client Server Communication	12
	3.1 Ge	eneral Test Objective and Approach	12
	3.1.1	Test System	
	3.1.2	Test Configuration	
	3.1.3	Test Case Design	29
	3.2 Re	e-usable Test Steps	29
		est Cases	
	3.3.1	[ATS_RTE_00052] Test synchronous server call for n:1 intra-ECU	
	0.0.1	Client-Server communication	
	3.3.2	[ATS_RTE_00054] Test intra-ECU C-S with operations of 2 ports	
		mapped on one runnable (synchronous server call)	31
	3.3.3	[ATS_RTE_00055] Test asynchronous server call for 1:1 intra-ECU	
		Client-Server communication	33
	3.3.4	[ATS_RTE_00056] Test asynchronous server call for n:1 intra-ECU	
		Client-Server communication	
	3.3.5	[ATS_RTE_00057] Test intra-ECU C-S with operations of 2 ports	
		mapped on one runnable (asynchronous server call)	
	3.3.6	[ATS_RTE_00058] Test intra-ECU Client-Server communication with	
	0.07	timeout (asynchronous server call)	38
	3.3.7	[ATS_RTE_00059] Test asynchronous server call for 1:1 inter-ECU Client-Server communication	40
	3.3.8	[ATS_RTE_00060] Test asynchronous server call for n:1 inter-ECU	40
	3.3.0	Client-Server communication	<b>4</b> 1
	3.3.9	[ATS_RTE_00061] Test inter-ECU C-S with operations of 2 ports	71
	0.0.0	mapped on one runnable (remote clients)	43
	3.3.10	[ATS_RTE_00062] Test n:1 inter-ECU Client-Server communication	
		with queue overflow	
	3.3.11	[ATS_RTE_00063] Test inter-ECU Client-Server communication with	
		timeout (synchronous server call)	46
	3.3.12	[ATS_RTE_00064] Test inter-ECU Client-Server communication with	
		timeout (asynchronous server call)	48
	3.3.13	[ATS_RTE_00065] Test inter/intra-ECU C-S with operations of 2 ports	
	0.0.4.4	mapped on one runnable	
		[ATS_RTE_00071] Test n:1 inter-ECU Client-Server communication	
	2 2 4 5	(remote clients)	51
	3.3.13	array on client side	
	3 3 16	[ATS_RTE_00142] Test inter-ECU Client-Server communication -	
	5.5.10	array on server side	
	3.3.17	[ATS_RTE_00206] Test intra-ECU Client-Server communication -	5-7
	3.3	independence of operations	
	3.3.18	[ATS_RTE_00242] Test concurrent activation of server (runnable not	
		mapped to task)	



	3.3.19	[ATS_RTE_00249] Test concurrent activation of server (runnable	
	2 2 20	mapped to task)	
	3.3.20	Client-Server communication for INOUT Argument	
	3.3.21	[ATS_RTE_00852] Test asynchronous server call for 1:1 intra-ECU	
	0.0.2	Client-Server communication for INOUT Argument	
4	DC D	RF_01320 & RS_BRF_01328 – Rte SWC scheduling and activation from	
4		RF_01320 & RS_BRF_01326	
		eneral Test Objective and Approach	
		Test System	
		Test Configuration	
	4.1.3	Test Case Design	
		e-usable Test Steps	
2		est Cases	
	4.3.1	[ATS_RTE_00116] Test Behavior of runnables activated by "General"	
	4 2 2	Events [ATS_RTE_00117] Test Runnables activated by Trigger Events	
	4.3.2 4.3.3	- , , , , , , , , , , , , , , , , , , ,	
	4.0.0	[A10_K12_00110] rest Kullilables activated from 6/1X confinding attention	
	4.3.4	[ATS_RTE_00119] Test Runnables activated from C/S communication	
	4.3.5	[ATS_RTE_00121] Test Runnable activated by Mode Switchs	
	4.3.6	[ATS_RTE_00132] Test Runnable activated by Multiple Events	
	4.3.7	[ATS_RTE_00694] Waking Up A Runnable From WaitPoint On	
	4 2 0	Occurrence Of ModeSwitchedAckEvent	
	4.3.8	[ATS_RTE_00707] MinimumStartInterval For A Runnable Entity	
5	RS_B	RF_01376 - Rte Data Conversion	. 83
Ę	5.1 Ge	eneral Test Objective and Approach	. 83
	5.1.1	Test System	. 83
	5.1.2	Test Configuration	. 86
	5.1.3	Test Case Design	. 91
Ę	5.2 Re	e-usable Test Steps	. 91
Ę		est Cases'	
	5.3.1	[ATS_RTE_00145] Test Intra-ECU C/S argument rescaling -	
		ClientServerInterfaceMapping Linear Scaling	
	5.3.2	[ATS_RTE_00146] Test Intra-ECU S/R dataelements rescaling -	
		Linear Scaling different units	. 93
	5.3.3	[ATS_RTE_00149] Test Intra-ECU C/S argument rescaling -	
	E 2 1	ClientServerInterfaceMapping Texttable to Texttable	
	5.3.4	[ATS_RTE_00150] Test Intra-ECU C/S argument rescaling - ClientServerInterfaceMapping Linear Scaling different units	
	5.3.5	[ATS_RTE_00151] Test Intra-ECU C/Sargument rescaling - C/S	
	2.0.0	ApplicationErrorMapping	
	5.3.6	[ATS_RTE_00154] Test intra-ECU C/S argument rescaling -	
		Composite Types (Structure)	. 98
	5.3.7	[ATS_RTE_00158] Test intra-ECU C/S argument rescaling -	
		Composite Type (Array)	. 99



	5.3.8		
	5.3.9	Mixed Linear scaled and texttable	100 -
		Linear Scaled conversion	102
	5.3.10	[ATS_RTE_00162] Test intra-ECU S/R dataelements rescaling	-
	5044	Composite Types (Structure)	
	5.3.11	[ATS_RTE_00163] Test intra-ECU S/R dataelements rescaling	
	5312	Composite Types (Array)	104
	0.0.12	texttable to texttable	
	5.3.13	[ATS_RTE_00165] Test Inter-ECU NetworkRepresentations	-
		Transmitting ECU DatatTypePolicy : Override	106
	5.3.14	[ATS_RTE_00166] Test Inter-ECU NetworkRepresentations	
	- 0 4-	Transmitting ECU DatatTypePolicy : FromComSpec	
	5.3.15	[ATS_RTE_00167] Test Inter-ECU NetworkRepresentations	
	E 2 16	Receiving ECU DatatTypePolicy : Override	
	5.5.10	Receiving ECU DatatTypePolicy : FromComSpec	
	5.3.17	[ATS_RTE_00169] Test Intra-ECU Range Checks - SR Unqueued	
	5.3.18	ignore[ATS_RTE_00170] Test Inter-ECU Range Checks - Sender Side	Э
		ISignalProps = invalid	113
	5.3.19	[ATS_RTE_00175] Test Intra-ECU Range Checks - SR queued	d
	E 2 20	saturate	
	5.3.20	[ATS_RTE_00176] Test Inter-ECU Range Checks - Receiver Side ISignalProps = invalid	
^	DO D	9	
6	_	RF_01304/RS_BRF_01352 – Rte Sender Receiver Communication	
6		eneral Test Objective and Approach	
		Test System	
		Test Configuration	
		e-usable Test Steps	
О		st Cases	
	6.3.1 6.3.2	[ATS_RTE_00009] Implicit write and read / data – intra-ECU	
	6.3.3	[ATS_RTE_00010] Explicit write and read / data = Intra-ECO	
	6.3.4	[ATS_RTE_00011] Send and receive / event = intra-200	
	6.3.5	[ATS_RTE_00013] Explicit write / data – inter-ECU	
	6.3.6	[ATS_RTE_00014] Send / events – inter-ECU	
	6.3.7	[ATS_RTE_00015] Implicit read / data – inter-ECU	
	6.3.8	[ATS_RTE_00016] Explicit read / data – inter-ECU	
	6.3.9	[ATS_RTE_00017] Receive / events – inter-ECU	
		[ATS_RTE_00018] 1:n reception from inter-ECU	
		[ATS_RTE_00019] 1:n transmission to intra-ECU and inter-ECU	149
	<b>6212</b>	IATS RTF 000201 Init value. Never received status, and valid 1 to 1	)
	6.3.12	[ATS_RTE_00020] Init value, Never received status, and valid 1 to 2 write	



6.3.14	[ATS_RTE_00634] Explicit Nonqueued Inter-ECU Rte_Write For DataElement Of Primitive Data Type When Com Service Is Not Available
6.3.15	[ATS_RTE_00635] Explicit Nonqueued Inter-ECU Rte_Write For DataElement With Array Data Type
6.3.16	[ATS_RTE_00636] Explicit Nonqueued Inter-ECU Rte_Write For DataElement With Record Data Type
6.3.17	[ATS_RTE_00637] Explicit Nonqueued Inter-ECU Rte_Read For DataElement Of Primitive Data Type
6.3.18	[ATS_RTE_00638] Explicit Nonqueued Inter-ECU Rte_Read For DataElement With Array Data Type
6.3.19	[ATS_RTE_00639] Explicit Nonqueued Inter-ECU Rte_Read For DataElement With Record Data Type
6.3.20	[ATS_RTE_00640] Explicit Queued Inter-ECU Rte_Send For DataElement Of Variable-length Arrays Of Bytes
6.3.21	[ATS_RTE_00641] Explicit Queued Inter-ECU Rte_Receive For DataElement Of Variable-Length Arrays Of Bytes
6.3.22	[ATS_RTE_00642] Explicit Nonqueued Intra-Partition Data Invalidation When Attribute 'HandleInvalid = Keep' And
6.3.23	'HandleNeverReceived = False' Or Undefined
6.3.24	'HandleNeverReceived = True'
6.3.25	[ATS_RTE_00645] Explicit Nonqueued Inter-ECU Data Invalidation On Sender Side For DataElement Of Primitive Data Type
6.3.26	[ATS_RTE_00646] Explicit Nonqueued Inter-ECU Data Invalidation On Sender Side For DataElement With Array Data Type
6.3.27	[ATS_RTE_00647] Explicit Nonqueued Inter-ECU Data Invalidation On Sender Side For DataElement With Record Data Type
6.3.28	[ATS_RTE_00648] Explicit Nonqueued Inter-ECU Data Invalidation On Receiver Side When Attribute 'HandleInvalid = Keep' For
6.3.29	DataElement Of Primitive Data Type
6.3.30	DataElement Of Primitive Data Type
6.3.31	DataeElement With Array Data Type
6.3.32	DataElement With Record Data Type
6.3.33	DataElement With Array Data Type



6.3.34	[ATS_RTE_00654] Explicit Nonqueued Inter-ECU
	TransmissionAcknowledgementRequest For DataElement Of
	Primitive Data Type (Without WaitPoint)
6.3.35	[ATS_RTE_00655] Explicit Nonqueued inter-ECU
	TransmissionAcknowledgementRequest For DataElement Of
	Primitive Data Type (With WaitPoint)
6 3 36	[ATS_RTE_00656] Explicit Nonqueued Inter-ECU Transmission error
0.5.50	
	notification For DataElement Of Primitive Data Type (Without
0 0 07	WaitPoint)
6.3.37	[ATS_RTE_00657] Explicit Nonqueued Inter-ECU Transmission error
	notification For DataElement Of Primitive Data Type (With WaitPoint) 184
6.3.38	[ATS_RTE_00658] Explicit Nonqueued Inter-ECU
	TransmissionAcknowledgementRequest timeout notification (Without
	WaitPoint, Primitive Data Type)
6.3.39	[ATS_RTE_00659] Explicit Nonqueued Inter-ECU
	TransmissionAcknowledgementRequest timeout notification (With
	WaitPoint, Primitive Data Type)
6.3.40	[ATS_RTE_00660] Explicit Nonqueued Inter-ECU Reception On
	AliveTimeout Expiry For DataElement Of Primitive Data Type
6.3.41	[ATS_RTE_00661] Explicit Nonqueued Inter-ECU
	TransmissionAcknowledgementRequest For DataElement With Array
	Data Type (Without WaitPoint)
6342	[ATS_RTE_00662] Explicit Nonqueued Inter-ECU
0.0.72	TransmissionAcknowledgementRequest For DataElement With
	Record Data Type (Without WaitPoint)
6313	[ATS_RTE_00663] Explicit Nonqueued Inter-ECU
0.5.45	
	TransmissionAcknowledgementRequest For DataElement WIth Array
6 2 44	Data Type (With WaitPoint)
6.3.44	[ATS_RTE_00664] Explicit Nonqueued Inter-ECU
	TransmissionAcknowledgementRequest For DataElement With
004=	Record Data Type (With WaitPoint)
6.3.45	[ATS_RTE_00665] Explicit Nonqueued Inter-ECU Transmission Error
	Notification For DataElement With Array Data Type (Without
	WaitPoint)
6.3.46	[ATS_RTÉ_00666] Explicit Nonqueued Inter-ECU Transmission Error
	Notification For DataElement With Record Data Type (Without
	WaitPoint)
6.3.47	[ATS_RTE_00667] Explicit Nonqueued inter-ECU Transmission error
	notification For DataElement With Array Data Type (With WaitPoint) . 197
6.3.48	[ATS_RTE_00668] Explicit Nonqueued inter-ECU Transmission error
	notification For DataElement With Record Data Type (With WaitPoint)199
6.3.49	[ATS_RTE_00669] Explicit Nonqueued Inter-ECÚ
	TransmissionAcknowledgementRequest Timeout Notification (Without
	WaitPoint, Array Data Type)
6.3.50	[ATS_RTE_00670] Explicit Nonqueued Inter-ECU
3.3.00	TransmissionAcknowledgementRequest Timeout Notification (Without
6351	WaitPoint, Record Data Type)
0.5.51	
	TransmissionAcknowledgementRequest timeout notification (With
	WaitPoint, Array Data Type)



6.3	3.52	[ATS_RTE_00672]	Explicit	Nonque	ued inter	r-ECU
		TransmissionAckno	owledgementReq	uest timeou	ut notification	(With
		WaitPoint, Record	Data Type)			204
6.3	3.53	[ATS_RTE_00673]				
		AliveTimeout Expir				
6.3	3.54	[ATS_RTE_00674]	,	,	7.1	
		AliveTimeout Expir				
6.3	3.55	[ATS_RTE_00675]				
		[ATS_RTE_00676]				
		[ATS_RTE_00677]				
•		Rte_Receive		•		
6.3	3 58	[ATS_RTE_00678]	Oueued Inter-F0	:II Transmis	sion With Succ	essful
0.0	0.00	Acknowledgement	Request	o manomio	olon min odoo	211
6.3	3 59	[ATS_RTE_00679]				
0.0	0.00	212	Quodod Intol 20	o manomio.	Sion Enor Hour	oation
6 1	3 60	[ATS_RTE_00680]	Oueued Inter-EC	IIRte Rece	eive For DataFlo	ement
0.0	5.00	Of Primitive Data T				
6 '	3 61	[ATS_RTE_00681]				
0.	3.01	With Array Data Ty				
6 '	3 62	[ATS_RTE_00682]	•			
0.	3.02	With Record Data				
6 '	2 62	[ATS_RTE_00683]	<b>7</b> I			
		[ATS_RTE_00684]				
0.	3.03	[ATS_RTE_00685] Communication Us				
6 '	2 66		_			
0	3.00	[ATS_RTE_00686] Transmission	Rie_ireeuback	API FUNCTIO	namy For Succ	220
6 '	2 67	[ATS_RTE_00687]				
0	3.07					
6 1	2 60	Transmission Error				
0	3.00	[ATS_RTE_00688]				
6.4	2 60	Transmission Ackn				
		[ATS_RTE_00689]				
٥.٠	3.70	[ATS_RTE_00690]	•			
<u> </u>	24	AliveTimeout				220
		[ATS_RTE_00695]				
		[ATS_RTE_00696]				
		[ATS_RTE_00697]				
		[ATS_RTE_00698]				
		[ATS_RTE_00699]				
		[ATS_RTE_00700]				
6.3	3.77	[ATS_RTE_00701]	Filter 'oneEvery	1' Configured	d	234
R	S_B	RF_01416_NvDatal	Handling			237
7.1		eneral Test Objective	_			
	1.1	Test System				
		Test Configuration				
	1.2	Test Case Design.				
		· ·				
7.2		-usable Test Steps				
7.3	Te	st Cases				262

7



	7.3.1	[ATS_RTE_01237] Implicit Write Access to NvDataElements PrimitiveData Type of Write Immediate Block	
	7.3.2	[ATS_RTE_01252] Explicit Write Access to NvDataElements	-
	7.3.3	Composite type (Array) of Write Cyclic Block	-
	7.3.4	[ATS_RTE_01253] Explicit Write Access to NvDataElements Boolean to BitField Type of Write Cyclic Block	-
	7.3.5	[ATS_RTE_01254] Explicit Write Access to NvDataElements Primitive Data Type of Write At Shutdown Block	-
	7.3.6	[ATS_RTE_01255] Write Optimization if useCRCCompMechanism i	S
	7.3.7	[ATS_RTE_01284] Implicit Read Access of Ram Block from Multiple SWC's	е
	7.3.8	[ATS_RTE_01285] Explicit Read Access of Nv Data Elements from Multiple SWC's	n
	7.3.9	[ATS_RTE_01261] NvMNotification and InitNotifyCallback using ClientServer Interface	g
		[ATS_RTE_01262] Initialization of RAMBlock with Initivalue of VDP [ATS_RTE_01263] Rejection of NvM_WriteBlock by NvM	. 285
		BlockProtection is enabled by SWC	. 287
	1.3.12	is False	_
8	Miscel	llaneous features	. 291
	8.1 Ge	eneral Test Objective and Approach	. 291
		Test System	
		Test Configuration	
	8.2 Re	e-usable Test Steps	. 292
		est Cases	
	8.3.1	[ATS_RTE_00691] InterRunnableVariables With Explicit Behavior	. 292
	8.3.2	[ATS_RTE_00692] InterRunnableVariables With Implicit Behavior	. 293
	8.3.3	[ATS_RTE_00693] Enhanced Rte_Mode API Functionality	
	8.3.4	[ATS_RTE_00702] Ports APIs Functionality	
	8.3.5	[ATS_RTE_00703] Rte_Prm API Functionality	
	8.3.6	[ATS_RTE_00704] Rte_CData API For sharedParameter	
	8.3.7	[ATS_RTE_00705] Rte_CData API For perInstanceParameter	
	8.3.8	[ATS_RTE_00706] Rte_Pim API Functionality	. 301



## 1 Acronyms and abbreviations

Abbreviation / Acronym:	Description:	
AT	Acceptance Test	
CAN	Controller Area Network	
ECU	Electronic Control Unit	
LT	Lower Tester	
NM	Network Management	
PCO	Point of Control and Observation	
PDU	Protocol Data Unit	
RfC	Request for Change	
Rx	Reception	
SUT	System Under Test	
SWC	Software Component	
TCP	Test Coordination Procedures	
Tx	Transmission	
UT	Upper Tester	



## 2 Scope

The following test cases are used to verify the correct behavior of all the RTE features.

Each test case documents for which releases of the AUTOSAR software specification it can be used:

- When test cases are known to be applicable for a release, this is mentioned in the "AUTOSAR Releases" field of the test case specifications.
   You can find a summary of the applicability of all test cases to the software specification releases in the "AUTOSAR\_TR\_ATSReleaseApplicability" document.
- When test cases are known to require adaptations (in their configuration requirements or test sequences), this is mentioned in the "Needed Adaptation to other Releases" field of the test case specifications.




## 3 RS BRF 01312 - Rte Client Server Communication

## 3.1 General Test Objective and Approach

This Test Specification covers the Client Server feature of the RTE as described in the AUTOSAR Feature [RS\_BRF\_01312].

The tests use a test bench environment and embedded Software Components that use the feature.

This test specification document has been established to cover the following features:




This specification gives the description of required tests environments (test bench, uses case, arxml files) and detailed tests cases for executing tests.

#### 3.1.1 Test System

#### 3.1.1.1 Overview on Architecture

In order to cover the required features / sub-features coverage, the environment has been separated in several use cases.






The test system architecture consists of Test Bench that executes only test sequencer and gives action requests through Test Coordination Procedures to embedded SWCs.

The location of SWC Clients and Server depends on the selected use case. The requirements for ECU Extract are described individually for each Use Case.

### 3.1.1.1.1 Use case UC01.01: Client-Server communication Intra-ECU


For this use case, the intention is to cover all intra-ECU communication (synchronous or asynchronous calls) inside an ECU.



## 3.1.1.1.2 Use case UC01.02.01: Client-Server communication Inter-ECU distant server

For this use case, the objective is to test the communication features of Clients to distant server as defined below:






In this use case, the test bench simulates the communication from clients to server.

## 3.1.1.1.3 Use case UC01.02.02: Client-Server communication Inter-ECU local server

For this use case, the objective is to test the communication features of Clients to local server and from distant clients to local server as defined below:



In this use case, the test bench simulates the communication from local server to distant clients.

### 3.1.1.2 Specific Requirements

Not Applicable

#### 3.1.1.3 Test Coordination Requirements

Not Applicable



## 3.1.2 Test Configuration

This section describes sets of requirements on configuration.

These sets are later referenced by test cases.

No configuration files are provided. They need to be developed when the test suite is implemented.

## 3.1.2.1 Required ECU Extract of System Description Files

## 3.1.2.1.1 Generic SWC description

The SWC description has been established to cover all use cases. Only the mapping of com signals and ECU Extract is specific.

The SWC requirements are described below:

#### 3.1.2.1.1.1 ClientServerInterfaces

Name	Operation	Arguments type
PrimitiveData_IF	Write	uint8 Data : IN
	Read	uint8 Data : OUT
	ReadWrite	uint8 Data : INOUT
Repeat_IF	Repeat	uint8 Data : IN
		uint8 Data : OUT
	RepeatArray	uint8[3] Data : IN
		uint8[3] Data : OUT
Reentrant_IF	Reentrant	uint8 Data : IN

### 3.1.2.1.1.2 SWC Tester\_Client\_1

SWC Name	SWC Name Tester Client 4				
SWC Name	Tester_Client_1				
	Name	Client1A			
	Туре	RPortPrototype			
	Interface	PrimitiveData_IF			
	Requirements				
PORTS					
	Name	ne Reentrant1			
	Туре	RPortPrototype			
	Interface	Reentrant_IF			
	Requirements				
	Name	RUN_Client1			
	Requirements				
RUNNABLE ENTITIES		Name	sscp_Read1A		
	ServerCallPoints	Туре	SynchronousServerCallPoint		
		Access to	Client1A (Read operation)		



Requirements	
Name	sscp_Write1A
Туре	SynchronousServerCallPoint
Access to	Client1A (Write operation)
Requirements	
Name	sscp_ReadWrite1A
Туре	SynchronousServerCallPoint
Access to	Client1A (Read and Write operation)
Requirements	
Name	sscp_Reentrant1
Туре	SynchronousServerCallPoint
Access to	Reentrant1 (Reentrant operation)
Requirements	

3.1.2.1.1.3 SWC Tester\_Client\_2

SWC Name	Tester_Client_2		
	Name	Client2A	
	Туре	RPortPrototype	
	Interface	PrimitiveData_IF	
	Requirements		
	Name	Client2B	
PORTS	Туре	RPortPrototype	
FORTS	Interface	PrimitiveData_IF	
	Requirements		
	Name	Client2C	
	Туре	RPortPrototype	
	Interface	PrimitiveData_IF	
	Requirements		
	Name	RUN_Client2	
	Requirements		



		Name	ascp_Read2A
		Туре	AsynchronousServerCallPoint
		Access to	Client2A (Read operation)
		Requirements	
		Name	ascp_Write2A
		Туре	AsynchronousServerCallPoint
		Access to	Client2A (Write operation)
		Requirements	
		Name	ascp_ReadWrite2A
		Туре	AsynchronousServerCallPoint
		Access to	Client2A (ReadWrite operation)
	Comres Coll Delinte	Requirements	
	ServerCallPoints		
		Name	ascp_Read2B
		Туре	AsynchronousServerCallPoint
RUNNABL		Access to	Client2B (Read operation)
E ENTITIES		Requirements	
		Name	ascp_Write2B
		Туре	AsynchronousServerCallPoint
		Access to	Client2B (Write operation)
		Requirements	
		Name	ascp_Write2C
		Туре	AsynchronousServerCallPoint
		Access to	Client2C (Write operation)
		Requirements	
	Name	RUN_Results2	
	Requirements	(ASCRE_Read/ ASCRE_Read/ ASCRE_Write2	erverCallReturnsEvents 2A, ASCRE_Write2A, /rite2A, ASCRE_Read2B, B) which refer to ascrp_Read2A, ascrp_ReadWrite2A,
	AsynchronousServerCallResultP -	Name	ascrp_Read2A
	oint	Туре	AsynchronousServerCallResultP oint



Access to	ascp_Read2A
Requirement s	
Name	ascrp_Write2A
Туре	AsynchronousServerCallResultP oint
Access to	ascp_Write2A
Requirement s	
Name	ascrp_ReadWrite2A
Туре	AsynchronousServerCallResultP oint
Access to	ascp_ReadWrite2A
Requirement s	
Name	ascrp_Read2B
Туре	AsynchronousServerCallResultP oint
Access to	ascp_Read2B
Requirement s	
Name	ascrp_Write2B
Туре	AsynchronousServerCallResultP oint
Access to	ascp_Write2B
Requirement s	



3.1.2.1.1.4 SWC Tester_Client_3					
SWC Name	Tester_Client_3				
	Name	Client3A			
	Туре	RPortPrototype			
	Interface	PrimitiveData_IF	-		
	Requirements				
	Name	Client3B			
PORTS	Туре	RPortPrototype			
PURIS	Interface	PrimitiveData_IF	=		
	Requirements				
	Name	Reentrant3			
	Туре	RPortPrototype			
	Interface	Reentrant_IF			
	Requirements				
	Name	RUN_Client3			
-	Requirements				
		Name	sscp_Read3A		
		Туре	SynchronousServerCallPoint		
		Access to	Client3A (Read operation)		
		Requirements			
		Name	sscp_Write3A		
		Туре	SynchronousServerCallPoint		
RUNNABLE		Access to	Client3A (Write operation)		
ENTITIES		Requirements			
	ServerCallPoint				
		Name	sscp_Read3B		
		Туре	SynchronousServerCallPoint		
		Access to	Client3A (Read operation)		
		Requirements			
		Name	sscp_Write3B		
		Туре	SynchronousServerCallPoint		
		Access to	Client3A (Write operation)		



Requiremen	ts
Name	sscp_Reentrant3
Туре	SynchronousServerCallPoint
Access to	Reentrant3 (Reentrant operation)
Requiremen	ts

3.1.2.1.1.5 SWC Tester Client 4

	ester_Client_4				
SWC Name	Tester_Client_4				
	Name		Repeat4		
	Туре				
	Interface				
	Requirements				
	Name	Client4B			
	Туре	RPortPrototype			
	Interface	PrimitiveData_IF			
	Requirements				
	Name	RUN_Client4			
	Requirements				
		Name	sscp_Repeat4		
		Туре	SynchronousServerCallPoint		
		Access to	Repeat4 (Repeat operation)		
		Requirements			
RUNNABLE		Name	sscp_RepeatArray4		
ENTITIES	ServerCallAccesspoint	Туре	SynchronousServerCallPoint		
	Server GanAccesspoint	Access to	Repeat4 (RepeatArray operation)		
		Requirements			
		Name	sscp_Write4B		
		Туре	SynchronousServerCallPoint		
		Access to	Client4B (Write operation)		
		Requirements			

## 3.1.2.1.1.6 SWC Tester\_Server



SWC Name	Tester_Server		
	Nam	ıe	ServerA
	Тур	е	PPortPrototype
	Interfa	ace	PrimitiveData_IF
	Requirer	nents	
	Name		ServerB
	Туре		PPortPrototype
	Interfa		PrimitiveData_IF
	Requirer	ments	
PORTS			
	Nam _		RepeatS
	Тур		PPortPrototype
	Interfa		Repeat_IF
	Requirer	nents	
	Nom	2	ReentrantS
	Name		PPortPrototype
	Type Interface		Reentrant_IF
	Requirer		ixeentan_n
	oquii o		
	Name	serverRead	
	Requirements	canBeInvokedConcurrently=false	
	Requirements	send back da	ta from global variable written by serverWrite
		Name	OIE_ReadA
		Туре	OperationInvokedEvent
			Port: ServerA Operation: Read
		Requiremen	
RUNNABLE	Started by Event	Troquironion	
ENTITIES		Name	OIE_ReadB
		Туре	OperationInvokedEvent
			Port: ServerB
			Operation: Read
		Requiremen	ts
	Name	serverWrite	
	Requirements	canBeInvokedConcurrently=false store received data in global variable (see serverRead)	



Started by Event  Name OIE_WriteB Type OperationInvokedEvent Port: ServerA Operation: Write  Requirements  Name OIE_WriteB Type Operation: Write Requirements  Name ServerReentrant CanBeInvokedConcurrently=true  Name OIE_Reentrant Type OperationInvokedEvent Port: Reentrant Type OperationInvokedEvent Port: Reentrant Requirements  Name OIE_Reentrant Requirements  Name OIE_Reentrant Type OperationInvokedEvent Port: Reentrant Requirements  Name OIE_Repeat Requirements  Name OIE_Repeat Type OperationInvokedEvent Port: RepeatS Operation: Repeat Requirements  Name OIE_Repeat Requirements  Name OIE_RepeatArray Requirements  Name OIE_RepeatArray Type OperationInvokedEvent Port: RepeatS Operation: RepeatArray Type OperationInvokedEvent Port: RepeatS Operation: RepeatArray Type Operation RepeatArray Type Operation RepeatArray Type Operation RepeatArray Requirements  Name OIE_RepeatArray Type Operation RepeatArray Type Operation RepeatArray Type Operation RepeatArray Requirements  Name ServerReadWrite Requirements				
Started by Event    Requirements		Name	OIE_WriteA	
Started by Event    Requirements   Name   OIE_WriteB		Туре		
Name   OIE_WriteB				
Name   OIE_WriteB			Operation: Write	
Name   OIE_WriteB		Requirements		
Type OperationInvokedEvent Port: ServerB Operation: Write  Requirements  Name serverReentrant CanBeInvokedConcurrently=true  Name OIE_Reentrant Type OperationInvokedEvent Port: ReentrantS Operation: Reentrant  Requirements  Name ServerRepeat  Requirements  Name OIE_Repeat  Type OperationInvokedEvent  Port: Reentrant  Requirements  Name OIE_Repeat  Type OperationInvokedEvent  Port: RepeatS Operation: Repeat  Requirements  Name ServerRepeatArray  Requirements  Name OIE_Repeat  Requirements  Name ServerRepeatArray  Requirements  Name OIE_RepeatArray  Type OperationInvokedEvent  Port: RepeatArray  Requirements  Name OIE_RepeatArray  Type OperationInvokedEvent  Port: RepeatS Operation: RepeatArray  Type OperationInvokedEvent  Port: RepeatS Operation: RepeatArray  Requirements  Name ServerRepeatArray  Requirements  Name ServerRepeatArray  Type OperationInvokedEvent  Port: RepeatS Operation: RepeatArray  Requirements  Name ServerRepeatArray  Requirements	Event			
Port: ServerB		Name	OIE_WriteB	
Name   ServerReentrant		Туре	OperationInvokedEvent	
Name   ServerReentrant			Port: ServerB	
Name   ServerReentrant			Operation: Write	
Name   OIE_Reentrant		Requirements		
Name   OIE_Reentrant				
Name   OIE_Reentrant	Name	serverReentrant		
Type	Requirements	canBelnvokedCo	oncurrently=true	
Port: ReentrantS   Operation: Reentrant		Name	OIE_Reentrant	
Name   ServerRepeat		Туре	OperationInvokedEvent	
Name   ServerRepeat			Port: ReentrantS	
Name   ServerRepeat	_,_,		Operation: Reentrant	
Name   OIE_Repeat		Requirements		
Name   OIE_Repeat				
Name   OIE_Repeat				
Started by Event  Type OperationInvokedEvent Port: RepeatS Operation: Repeat  Requirements  Name ServerRepeatArray  Requirements Copy IN parameter to the OUT parameter  Name OIE_RepeatArray  Type OperationInvokedEvent Port: RepeatS Operation: RepeatArray  Requirements  Name Port: RepeatS Operation: RepeatArray  Requirements  Name ServerReadWrite	Name	serverRepeat		
Type   OperationInvokedEvent	Requirements	Copy IN parame	eter to the OUT parameter	
Port: RepeatS   Operation: Repeat		Name	OIE_Repeat	
Name   ServerRepeatArray	Started by	Туре	OperationInvokedEvent	
Requirements	Event		Port: RepeatS	
Name   serverRepeatArray			Operation: Repeat	
Requirements   Copy IN parameter to the OUT parameter		Requirements		
Requirements   Copy IN parameter to the OUT parameter				
Name     OIE_RepeatArray       Type     OperationInvokedEvent       Port: RepeatS     Operation: RepeatArray       Requirements     Name	Name	serverRepeatArı	ray	
Type OperationInvokedEvent Port: RepeatS Operation: RepeatArray  Requirements  Name serverReadWrite	Requirements	Copy IN parame	eter to the OUT parameter	
Port: RepeatS Operation: RepeatArray  Requirements  Name serverReadWrite		Name	OIE_RepeatArray	
Port: RepeatS Operation: RepeatArray  Requirements  Name serverReadWrite	Event	Туре	OperationInvokedEvent	
Requirements  Name serverReadWrite			Port: RepeatS	
Name serverReadWrite			Operation: RepeatArray	
		Requirements		
Requirements canBeInvokedConcurrently=false	Name	serverReadWrite	9	
	Requirements	Requirements canBeInvokedConcurrently=false		



# Acceptance Test Specification of RTE AUTOSAR TC Release 1.2.0

		XOR The receive the result into IN	ed data (INOUT parameter) with 0xFF and copy OUT parameter
		Name	OIE_ReadWrite
	Event	Туре	OperationInvokedEvent
	Event		Port: ServerA Operation: ReadWrite
	-	Requirements	



### 3.1.2.1.2 Use case UC01.01: intra-ECU Client-Server communication

The objective of the use case 1 is to test the Client-Server <u>intra-ECU</u> communication. This means that for this configuration, all SWC Clients and server are located in the SUT as described in the figure below:

#### 3.1.2.1.2.1 Use case UC01.01: intra-ECU Client-Server communication

The objective of the use case 1 is to test the Client-Server <u>intra-ECU</u> communication. This means that for this configuration, all SWC Clients and server are located in the SUT as described in the figure below:

For this use case, all the SW-Cs are mapped to the SUT ECU.




Figure 1: UC01.01: intra-ECU Client-Server communication

Some tests cases use Exclusive Area to not rely on OsTasks relative priorities.

The allocation of runnables to tasks is implementation specific.



## 3.1.2.1.3 Use case UC01.02.01: inter-ECU Client-Server communication – remote server

The objective of the use case 2.1 is to test the Client-Server <u>inter-ECU</u> communication <u>with distant server</u>. This means that for this configuration, only the SWC Tester\_Client\_1 and Tester\_Client\_2 are mapped on SUT.




Figure 2: UC01.02.01: inter-ECU Client-Server communication - remote server

The following frames are used for the inter-ECU communication between clients and servers:

Frame	Description	Tx ECU	Rx ECU
WRITE_A_REQ	Contain the callSignal for the call of operation Write on ServerA.  It includes the following signals:  • clientId (uint8)  • sequenceCounter (uint8)  • the IN parameter of the Write operation (uint8)	SUT	TestBench
WRITE_A_RES	Contain the returnSignal for the result of operation Write on ServerA  It includes the following signals:  • clientId (uint8)  • sequenceCounter (uint8)	TestBench	SUT



	the return value (uint8)		
READ_A_REQ	Contain the callSignal for the call of operation Read on ServerA	SUT	TestBench
	operation Read on ServerA		
	It includes the following signals:		
	clientId (uint8)		
	sequenceCounter (uint8)		
READ_A_RES	Contain the returnSignal for the result of	TestBench	SUT
	operation Read on ServerA		
	It includes the following signals:		
	clientId (uint8)		
	sequenceCounter (uint8)		
	<ul><li>the read value (uint8)</li></ul>		
	the return value (uint8)		
REPEATARRAY	Contain the callSignal for the call of	TestBench	SUT
_REQ	operation RepeatArray on ServerRepeat		
	It includes the following signals:		
	clientId (uint8)		
	sequenceCounter (uint8)		
	3 bytes for IN value (3 uint8 array)		
	elements)		
REPEATARRAY	Contain the returnSignal for the result of	TestBench	SUT
_RES	operation RepeatArray on ServerA		
	It is alredge the following signals:		
	It includes the following signals:		
	clientId (uint8)		
	sequenceCounter (uint8)		
	3 bytes fort the OUT value (3 uint8 array)		
	elements)		
	<ul> <li>the return value (uint8)</li> </ul>		



## 3.1.2.1.4 Use case UC01.02.02: inter-ECU Client-Server communication – remote clients

The objective of the use case 2.2 is to test the Client-Server <u>inter-ECU</u> communication <u>with local server</u>. This means that for this configuration, only the SWC Tester\_Client\_1, Tester\_Client\_2 and Tester\_Server are mapped on SUT.




Figure 3: UC01.02.01: inter-ECU Client-Server communication - remote clients

The following frames are used for the inter-ECU communication between clients and servers:

Frame	Description	Tx ECU	Rx ECU
WRITE_A_REQ	Contain the callSignal for the call of operation Write on ServerA.  It includes the following signals:  • clientId (uint8)  • sequenceCounter (uint8)  • the IN parameter of the Write operation (uint8)	TestBench	SUT
WRITE_A_RES	Contain the returnSignal for the result of operation Write on ServerA  It includes the following signals:  • clientId (uint8)  • sequenceCounter (uint8)  • the return value (uint8)	SUT	TestBench



READ_A_REQ	Contain the callSignal for the call of operation Read on ServerA	TestBench	SUT
	It includes the following signals:		
	clientId (uint8)		
	sequenceCounter (uint8)		
READ_A_RES	Contain the returnSignal for the result of	SUT	TestBench
	operation Read on ServerA		
	It includes the following signals:		
	clientId (uint8)		
	sequenceCounter (uint8)		
	the read value (uint8)		
	the return value (uint8)		
REPEATARRAY	Contain the callSignal for the call of	TestBench	SUT
_REQ	operation RepeatArray on ServerRepeat		
	It includes the following signals:		
	clientId (uint8)		
	sequenceCounter (uint8)		
	3 bytes for IN value (3 uint8 array)		
	elements)		
REPEATARRAY _RES	Contain the returnSignal for the result of operation RepeatArray on ServerA	SUT	TestBench
	It includes the following signals:		
	clientId (uint8)		
	sequenceCounter (uint8)		
	3 bytes fort the OUT value (3 uint8 array)		
	elements)		
DEDEATA DD AV	the return value (uint8)		
REPEATARRAY _REQ	Contain the callSignal for the call of operation Repeat on ServerRepeat	TestBench	SUT
	·		
	It includes the following signals:		
	clientId (uint8)		
	<ul> <li>sequenceCounter (uint8)</li> </ul>		
DEDEAT DES	• the IN value (uint8)	OLUT	T. (5)
REPEAT_RES	Contain the returnSignal for the result of	SUT	TestBench
	operation Repeat on ServerA		
	It includes the following signals:		
	clientId (uint8)		
	sequenceCounter (uint8)		
	the OUT value (uint8)		
	<ul> <li>the return value (uint8)</li> </ul>		



## 3.1.2.2 Required ECU Configuration Description Files

There are no generic requirements on ECU Configuration files. Individual test cases may have specific requirements on the RTE configuration.

## 3.1.2.3 Required Software Component Description Files

Requirements on Software Component Description files are provided in the section 3.1.2.1 Required ECU Extract of System Description Files, together with the connections of the different components.

### 3.1.2.4 Mandatory vs. Customizable Parts

Not Applicable.

### 3.1.3 Test Case Design

Not Applicable.

## 3.2 Re-usable Test Steps

Not Applicable



## 3.3 Test Cases

## 3.3.1 [ATS\_RTE\_00052] Test synchronous server call for n:1 intra-ECU Client-Server communication

Test Objective	Toet evechronous conver call for	n:1 intra ECI	I Client-Server communication
	Test synchronous server call for I		
ID	ATS_RTE_00052	Releases	3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00002		
Trace to SWS Item	RTE: SWS_Rte_02527 RTE: SWS_Rte_04515 RTE: SWS_Rte_04516 RTE: SWS_Rte_04519		
Requirements / Reference to Test Environment	UC01.01		
Configuration Parameters	See UC01.01 in chapter 3.1.2 Test Configuration.  This test case uses:  Tester_Client_1  * port Client1A  * runnable RUN_Client1 (sscp_Read1A, sscp_Write1A)  Tester_Client_3  * port Client3A  * runnable RUN_Client3 (sscp_Write3A)  Tester_Server  * port ServerA  * runnable serverRead  * runnable serverWrite  Client1A and Client3A connected to ServerA.  ServerA triggers serverRead (resp. serverWrite) for the Read (resp. Write)		
Summary	operation.  The goal of this test is to check the behavior of synchronous server calls in case of n:1 Intra-ECU Client-Server communication.  2 clients connected to the same server are invoking (synchronous server call) successively the same operation of the server.  The Test Manager checks that the operations are handled correctly.		
Needed Adaptation to other Releases		_	
Pre-conditions	None		
Main Test Execu	ution		
Test Steps			Pass Criteria
Step 1	[CP]		
	start RUN_Client1, RUN_Client3		



Step 2	[RUN <run_client1>]</run_client1>	[RUN <run_client1>]</run_client1>
	execute Rte_Call_Client1A_Write(DataValue1)	Rte_Call returns RTE_E_OK
Step 3	[RUN <run_client3>]</run_client3>	[RUN <run_client3>]</run_client3>
	execute Rte_Call_Client3A_Write(DataValue2)	Rte_Call returns RTE_E_OK
Step 4	[RUN <run_client1>]</run_client1>	[RUN <run_client1>]</run_client1>
	execute Rte_Call_Client1A_Read	Rte_Call returns RTE_E_OK, data returned is DataValue2
Step 5	[CP]	
	terminate RUN_Client1, RUN_Client3	
Post- conditions	None	

# 3.3.2 [ATS\_RTE\_00054] Test intra-ECU C-S with operations of 2 ports mapped on one runnable (synchronous server call)

Test Objective	Test intra-ECU C-S with operations of 2 ports mapped on one runnable (synchronous server call)			
ID	ATS_RTE_00054	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2	
Affected Modules	RTE	State	reviewed	
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00002			
Trace to SWS Item	RTE: SWS_Rte_04520 RTE: SWS_Rte_04522 RTE: SWS_Rte_08001 RTE: SWS_Rte_08002	RTE: SWS_Rte_04522 RTE: SWS_Rte_08001		
Requirements / Reference to Test Environment	UC01.01			
Configuration Parameters	See UC01.01 in chapter 3.1.2 Test Configuration.  This test case uses:  Tester_Client_1  To port Client1A  To runnable RUN_Client1 (sscp_Write1A)  Tester_Client_3  To port Client3B  Trunnable RUN_Client3 (sscp_Write3B)  Tester_Client_4  To port Client4B  To runnable RUN_Client4 (sscp_Write4B)  Tester_Server  To port ServerA  To port ServerA  To port ServerB			



	* runnable serverWrite			
	Client1A connected to ServerA.	Client1A connected to ServerA.		
	Client3B and Client4B connected to Serv	Client3B and Client4B connected to ServerB.		
	Both ServerA and ServerB triggers serverWrite when the Write operation is invoked. ServerComSpec.queueLength set to 2 on both ServerA and ServerB for operation			
	Write. serverWrite has its canBeInvokedConcurrently attribute set to false			
Summary	The goal of this test is to check the behav	The goal of this test is to check the behavior of synchronous server calls when 2 operations are mapped on the same runnable entity (on server side).		
		the clients are connected to the server on 2 ports (server side) start the same server		
	The server has a queue length (ServerCoports.	omSpec.queueLength) set to 2 on both		
	It needs to be ensured that the first reque is issued (see HINT below).	ests are not processed before the third one		
	The Test Manager checks that the first 2 server in the requested sequence, and the RTE_E_LIMIT error.			
	HINT: For example, the clients runnables can be mapped to tasks with the following relative priorities:			
	Prio RUN_Client4 <prio run_client1<="" run_client3<prio="" th=""></prio>			
	The Task containing the Test Manager should have a priority higher than Clients			
	The Task containing the Server should ha	ave a lower priority than Clients		
Needed Adaptation to other Releases	6			
Pre-conditions	None			
Main Test Exec	cution			
Test Steps		Pass Criteria		
Step 1	[CP]			
	start RUN_Client1, RUN_Client3, RUN_Client4			
Step 2	[RUN <run_client1>]</run_client1>	[RUN <run_client1>]</run_client1>		
		L		
040	execute Rte_Call_Client1A_Write	Rte_Call returns RTE_E_OK		
Step 3	[RUN <run_client3>]</run_client3>	[RUN <run_client3>]</run_client3>		
	execute Rte_Call_Client3B_Write	Rte_Call returns RTE_E_OK		
Step 4	[RUN <run_client4>]</run_client4>	[RUN <run_client4>]</run_client4>		
	execute Rte_Call_Client4B_Write	Rte_Call returns RTE_E_LIMIT		
Step 5	[CP]			
	ľ ·			



	terminate RUN_Client1, RUN_Client3, RUN_Client4	
Post- conditions	None	

## 3.3.3 [ATS\_RTE\_00055] Test asynchronous server call for 1:1 intra-ECU Client-Server communication

Test Objective	Test asynchronous server call fo	or 1·1 intra-F0	CU Client-Server communication
ID			
ID	ATS_RTE_00055	Releases	3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
	ATR: ATR_ATR_00001		
Trace to SWS Item	RTE: SWS_Rte_03771		
Requirements / Reference to Test Environment	UC01.01		
Configuration Parameters	See UC01.01 in chapter 3.1.2 To This test case uses: Tester_Client_2 * port Client2A * runnable RUN_Client2 (ascp_f * runnable RUN_Results2 (ascrp ASCRE_Write2A)  Tester_Server * port ServerA * runnable serverRead * runnable serverWrite  Client2A connected to ServerA.	Read2A, ascp	
Summary	The goal of this test is to check to 1:1 intra-ECU Client-Server come. This test involves communication. The Tester_Client_2 SW-C calls. The Test Manager checks that a operations succeed (data is write.)	munication.  n between Teal  the local ser  asynchronous  ten and read	ester_Client_2 and Tester_Server.  ever for the Read and Write operations.  server calls for the Read and Write correctly) and that an gered to start a runnable of the client.
Needed Adaptation to other Releases	_		
Pre-conditions	None		
Main Test Execu			



Test Steps		Pass Criteria
Step 1	[CP]	
	atort DUNI ClientO	
Step 2	start RUN_Client2 [RUN <run client2="">]</run>	IDIAN (DIA) Clion42: 1
Step 2	[RON <ron_client2>]</ron_client2>	[RUN <run_client2>]</run_client2>
	execute Rte_Call_Client2A_Read	Rte_Call returns RTE_E_OK
Step 3	[CP]	[RUN <run_results2>]</run_results2>
	MAIT 400	www.ablabaabaaaaaaaaba
	WAIT 100ms	runnable has been started by AsynchronousServerCallReturnsEvent
Step 4	[RUN <run_results2>]</run_results2>	[RUN <run_results2>]</run_results2>
·		
	execute Rte_Result_Client2A_Read	Rte_Result returns RTE_E_OK, data
Ston F	IDUN DUN Cliento 1	returned is DataValueInit
Step 5	[RUN <run_client2>]</run_client2>	[RUN <run_client2>]</run_client2>
	execute	Rte_Call returns RTE_E_OK
	Rte_Call_Client2A_Write(DataValue1)	
Step 6	[CP]	[RUN <run_results2>]</run_results2>
	WAIT 100ms	runnable has been started by an
		AsynchronousServerCallReturnsEvent
Step 7	[RUN <run_results2>]</run_results2>	[RUN <run_results2>]</run_results2>
	execute Rte_Result_Client2A_Write	Rte_Result returns RTE_E_OK
Step 8	[RUN <run client2="">]</run>	[RUN <run client2="">]</run>
Otop o	[NONANON_OHOM22]	[Nortalitation   Internation   Internation
	execute Rte_Call_Client2A_Read	Rte_Call returns RTE_E_OK
Step 9	[CP]	[RUN <run_results2>]</run_results2>
	M/AIT 100mg	ruppable has been started by an
	WAIT 100ms	runnable has been started by an AsynchronousServerCallReturnsEvent
Step 10	[RUN <run_results2>]</run_results2>	[RUN <run_results2>]</run_results2>
	execute Rte_Result_Client2A_Read	Rte_Result returns RTE_E_OK, data returned is DataValue1
Post-	None	returned is Data value i
conditions	I VOLIG	

# 3.3.4 [ATS\_RTE\_00056] Test asynchronous server call for n:1 intra-ECU Client-Server communication

Test Objective	Test asynchronous server call for n:1 intra-ECU Client-Server communication		
ID	ATS_RTE_00056 AUTOSAR Releases 3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2		
Affected Modules	RTE	State	reviewed
Trace to Requirement	ATR: ATR_ATR_00001		



on Acceptance	
Test Document	
Item	RTE: SWS_Rte_02527 RTE: SWS_Rte_02528 RTE: SWS_Rte_03773 RTE: SWS_Rte_04520
Requirements /	UC01.01
Reference to Test	
Environment	
Configuration Parameters	See UC01.01 in chapter 3.1.2 Test Configuration.
	This test case uses: Tester_Client_2
	* port Client2A
	* port Client2C
	* runnable RUN_Client2 (ascp_Read2A, ascp_Write2A, ascp_Write2C) * runnable RUN_Results2 (ascrp_Read2A, ASCRE_Read2A, ascrp_Write2A, ASCRE_Write2A, ascrp_Write2C, ASCRE_Write2C)
	Tester_Server
	* port ServerA * runnable serverRead
	* runnable serverWrite
	Client2A and Client2C connected to ServerA.
	In addition, the system is configured so that the first Write request is not processed before the second one is issued.
	For example: * serverRead, serverWrite are mapped to tasks * serverRead and serverWrite are configured to run inside the same exclusive area EA1
	* RUN_Client2 can enter this exclusive area EA1 (i.e. the RTE is configured to use the same OS object to implement the exclusive area of the server and client SW-C) * ServerA has a ServerComSpec for operation Write with queueLength 1
Summary	The goal of this test is to check the behavior of asynchronous server calls in case of n:1 intra ECU Client-Server communication.
	This test involves communication between Tester_Client_2 and Tester_Server.
	The Tester_Client_2 SWC calls the local server for Write operations on 2 different ports, both connected to the same server port.
	The Server has a queueLength = 1.
	The system is configured in such way that the first request is not processed before the second one is issued. The 2 requests as thus considered 'simultaneous'.
	The Test Manager shall check that the first asynchronous server call for the first operation succeeds (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.
	The Test Manager shall check that the second (simultaneous) asynchronous server call for the Write operation (on the other port) results in a RTE_E_LIMIT error.



	HINT: To allow this behavior, the 2 simultaneous Client call to server operation should be				
	encapsulated in an ExclusiveArea EA1 that is also used by the server. In this case,				
	the server will not execute before call of the	e 2 successive requests.			
Needed Adaptation to other Releases					
Pre-conditions	None				
Main Test Execution					
Test Steps		Pass Criteria			
Step 1	[CP]				
	start RUN_Client2				
Step 2	[RUN <run_client2>]</run_client2>	[RUN <run_client2>]</run_client2>			
	execute Rte_Enter to enter EA1, execute Rte_Call_Client2A_Write	Rte_Call returns RTE_E_OK			
Step 3	[RUN <run_client2>]</run_client2>	[RUN <run_client2>]</run_client2>			
	execute Rte_Call_Client2A_Read	Rte_Call returns RTE_E_OK			
Step 4	[RUN <run_client2>]</run_client2>	[RUN <run_client2>]</run_client2>			
	execute Rte_Call_Client2C_Write execute Rte_Exit to exit EA1	Rte_Call returns RTE_E_OK			
Step 5	[RUN <run_results2>]</run_results2>	[RUN <run_results2>]</run_results2>			
	execute Rte_Result_Client2A_Write	Rte_Result returns RTE_E_OK			
Step 6	[RUN <run_results2>]</run_results2>	[RUN <run_results2>]</run_results2>			
	execute Rte_Result_Client2A_Read	Rte_Result returns RTE_E_OK Read data is equal to the data written in step 2			
Step 7	[RUN <run_results2>]</run_results2>	[RUN <run_results2>]</run_results2>			
	execute Rte_Result_Client2C_Write	Rte_Result returns RTE_E_LIMIT			
Step 8	[CP]				
	terminate RUN_Client2, RUN_Results2				
Post- conditions	None				

# 3.3.5 [ATS\_RTE\_00057] Test intra-ECU C-S with operations of 2 ports mapped on one runnable (asynchronous server call)

•	Test intra-ECU C-S with operations of 2 ports mapped on one runnable (asynchronous server call)		
ID		AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed



T 4-	ATD ATD ATD AGGG		
Trace to Requirement	ATR: ATR_ATR_00001		
on Acceptance			
Test Document			
Trace to SWS	RTE: SWS_Rte_04520		
ltem	RTE: SWS_Rte_04522		
	RTE: SWS_Rte_08001 RTE: SWS_Rte_08002		
Requirements /			
Reference	0001.01		
to Test			
Environment			
Configuration	See UC01.01 in chapter 3.1.2 Test Configura	tion.	
Parameters	This test sees upon		
	This test case uses: Tester_Client_2		
	* port Client2A		
	* runnable RUN_Client2 (ascp_Read2A, ascp		
	* runnable RUN_Results2 (ascrp_Read2A, A	SCRE_Read2A, ascrp_Read2B,	
	ASCRE_Read2B)		
	Tester_Server		
	* port ServerA		
	* port ServerB		
	* runnable serverRead		
	Client2A connected to ServerA.		
	Client2B connected to ServerB.		
	Both ServerA and ServerB triggers serverRead when the Read operation is		
	invoked. ServerComSpec.queueLength set to 1 on both ServerA and ServerB for operation		
	Read.	in ServerA and ServerB for operation	
	serverRead has its canBeInvokedConcurrently attribute set to false		
	The server/system has to be designed/configuencessed before the second request is issue		
Summary	The goal of this test is to check the behavior of		
	operations are mapped on the same runnable		
	In this case, the server shall implement a sing	gle queue for the 2 operations	
	(ServerComSpecs.queueLength = 1).		
	The test manager has to ensure that the succ	ressive calls of the Read operation on	
	2 ports are issued before the first one is proce		
	The test manager checks that the first reques request results in a RTE_E_LIMIT error.	t is handled correctly and the second	
Needed			
Adaptation to			
other Releases			
Pre-conditions			
Main Test Execu		<b>-</b>	
Test Steps		Pass Criteria	
Step 1	[CP]		
	start RUN_Client2		
	J.S. 1 1 10 1 _ 0 110 11/2	<u>I</u>	



Step 2	[RUN <run_client2>]</run_client2>	[RUN <run_client2>]</run_client2>
	execute Rte_Call_Client2A_Read	Rte_Call returns RTE_E_OK
Step 3	[RUN <run_client2>]</run_client2>	[RUN <run_client2>]</run_client2>
	execute Rte_Call_Client2B_Read	Rte_Call returns RTE_E_OK
Step 4	[CP]	[RUN <run_results2>]</run_results2>
	WAIT 100ms	runnable has been started by AsynchronousServerCallReturnsEvent
Step 5	[RUN <run_results2>]</run_results2>	[RUN <run_results2>]</run_results2>
	execute Rte_Result_Client2A_Read	Rte_Result returns RTE_E_OK
Step 6	[RUN <run_results2>]</run_results2>	[RUN <run_results2>]</run_results2>
	execute Rte_Result_Client2B_Read	Rte_Result returns RTE_E_LIMIT
Post- conditions	None	

# 3.3.6 [ATS\_RTE\_00058] Test intra-ECU Client-Server communication with timeout (asynchronous server call)

Test Objective	Test intra-ECU Client-Server communication with timeout (asynchronous server call)		
ID	ATS_RTE_00058	AUTOSAR Releases	3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00001		
Trace to SWS Item	RTE: SWS_Rte_03764 RTE: SWS_Rte_03765 RTE: SWS_Rte_03766 RTE: SWS_Rte_03770 RTE: SWS_Rte_03771		
Requirements / Reference to Test Environment	UC01.01		
Configuration Parameters	See UC01.01 in chapter 3.1.2 Test Configuration.  This test case uses: Tester_Client_2 * port Client2A * runnable RUN_Client2 (ascp_Write2A) * runnable RUN_Results2 (ascrp_Write2A, ASCRE_Write2A)  Tester_Server * port ServerA * runnable serverWrite		



	Client2A connected to ServerA.		
	In addition		
	* Tester_Client_2 has a TriggerPort, accessi * One Runnable RUN_BlockingProcess is sta		
	ExternalTriggeredOccurredEvent from Trigge		
	Execution time of RUN_BlockingProcess hig	her than 10ms	
	* ascp_Write2A configured with timeout = 10		
Summary	references the AsynchronousServerCallRetu The goal of this test case is to check the RTE	-	
Summary	asynchronous server call for an intra-ECU C		
	This test uses Tester_Client_2, which calls a	server of Tester_Server.	
	This test is developed in a way that a timeou	t occurs.	
	The test manager checks that a RTE_E_TIM	IEOUT error is provided to the client.	
	HINT: In order to check the timeout monitoring of the RTE, this test case uses (in addition to the client and server) one external runnable that is triggered by Tester_Client_2 (ExternalTrigger). This external runnable has a higher priority than the server runnable, the client is mapped to a task with a higher priority than the external runnable. The execution time of the external runnable should be at least equal to the configured timeout.		
Needed			
Adaptation to other Releases			
Pre-conditions	None		
Main Test Exec	ution		
Test Steps		Pass Criteria	
Step 1	[CP]		
	starts RUN_Client2		
Step 2	[RUN <run_client2>]</run_client2>	[RUN <run_client2>]</run_client2>	
	execute Rte_Call_Client2A_Write execute Rte_Trigger to trigger execution of RUN_BlockingProcess	Rte_Call returns RTE_E_OK	
Step 3	[CP]	[RUN <run_results2>]</run_results2>	
	WAIT 100ms	runnable has been started by AsynchronousServerCallReturnsEvent	
Step 4	[RUN <run_results2>]</run_results2>	[RUN <run_results2>]</run_results2>	
	execute Rte_Result_Client2A_Write	Rte_Result returns RTE_E_TIMEOUT	
Post- conditions	None		



### 3.3.7 [ATS\_RTE\_00059] Test asynchronous server call for 1:1 inter-ECU Client-Server communication

Test Objective	Test asynchronous server call for 1:1 inter-ECU Client-Server communication			
ID	ATS_RTE_00059	AUTOSAR Releases	3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2	
Affected	RTE	State	reviewed	
Modules	СОМ			
Trace to	ATR: ATR_ATR_00001			
Requirement on Acceptance				
Test Document				
Trace to SWS				
Item				
Requirements / Reference to Test Environment	UC01.02.01			
Configuration Parameters	See UC01.02.01 in chapter 3.1.2	Test Config	uration.	
raiameters	This test case uses: Tester_Client_2 * port Client2A * runnable RUN_Client2 (ascp_Read2A, ascp_Write2A) * runnable RUN_Results2 (ascrp_Read2A, ASCRE_Read2A)  Write request for Client2A transmitted on frame WRITE_A_REQ (includes IN			
	parameter, clientId, sequenceCounter) Write result for Client2A transmitted on frame WRITE_A_RES (includes return value, clientId, sequenceCounter) Read request for Client2A transmitted on frame READ_A_REQ (includes IN parameter, clientId, sequenceCounter) Read result for Client2A transmitted on frame READ_A_RES (includes return value, OUT parameter, clientId, sequenceCounter)			
Summary	The goal of this test is to check the behavior of asynchronous server calls in case of 1:1 inter-ECU Client-Server communication.			
	This test involves communication between Tester_Client_2 and a remote server (on test bench)			
	Tester_Client_2 calls asynchrono the remote server.	ously the Wri	te (IN parameter) operation of	
	The test manager checks that the request (including the IN parameter) is correctly transmitted on a bus.			
	Then, Tester_Client_2 calls asynchronously the Read operation of the remote server.			
	The test manager checks that			
	<ul> <li>the Read request is corre</li> <li>the results of the Read o to Tester_Client_2 (Rte_</li> </ul>	peration, trar	nsmitted on a bus, is correctly provided	



Needed Adaptation to		
other Releases		
	None	
Main Test Execu	ıtion	
Test Steps		Pass Criteria
Step 1	[CP]	
	start RUN_Client2	
Step 2	[RUN <run_client2>]</run_client2>	[RUN <run_client2>]</run_client2>
	execute Rte_Call_Client2A_Write(DataValue1)	Rte_Call returns RTE_E_OK
Step 3	[CP]	[LT]
	WAIT 100ms	frame WRITE_A_REQ with DataValue1 has been transmitted by SUT
Step 4	[RUN <run_client2>]</run_client2>	[RUN <run_client2>]</run_client2>
	execute Rte_Call_Client2A_Read	Rte_Call returns RTE_E_OK
Step 5	[CP]	[LT]
	WAIT 100ms	frame READ_A_REQ has been transmitted by SUT
Step 6	[LT]	
	send frame READ_A_RES with DataValue1 as OUT parameter, RTE_E_OK as return value, and both clientId/sequenceCounter as received in step 5	
Step 7	[CP]	
-	WAIT 100ms	
Step 8	[RUN <run_results2>]</run_results2>	[RUN <run_results2>]</run_results2>
	execute Rte_Result_Client2A_Read	Rte_Result returns RTE_E_OK Returned data value is equal to DataValue1
Post- conditions	None	

## 3.3.8 [ATS\_RTE\_00060] Test asynchronous server call for n:1 inter-ECU Client-Server communication

Test Objective	Test asynchronous server call for n:1 inter-ECU Client-Server communication		
ID	ATS_RTE_00060 AUTOSAR		
Affected Modules	RTE, COM	State	reviewed



	I	1		
Trace to Requirement	ATR: ATR_ATR_00001			
on Acceptance				
Test Document				
_	RTE: SWS_Rte_02649			
Item	RTE: SWS_Rte_02651			
Requirements / Reference	UC01.02.01			
to Test				
Environment				
Configuration	See UC01.02.01 in chapter 3.1.2 Test Config	uration.		
Parameters	This took ages were			
	This test case uses: Tester_Client_2			
	* port Client2A			
	* port Client2B			
	* runnable RUN_Client2 (ascp_Write2A, ascr	_ ,		
	* runnable RUN_Results2 (ascrp_Write2A, A ASCRE_Write2A)	SCRE_write2A, ascrp_write2A,		
	_ ,			
	The Write requests on the 2 ports are mappe			
	example both Client2A and Client2B are conidentifiers.	nected to serverA), with different client		
	The results of the Write requests on the 2 poi	rts are mapped to the frame		
	WRITE_A_RES.			
Summary	The goal of this test is to check the behavior	of asynchronous server calls in case of		
	n:1 inter-ECU Client-Server communication.			
	This test involves 2 clients (Tester_Client_2 with ports Client2A and Client2B),			
	which are using asynchronous calls to a remo			
	example Tester_Server).	`		
	L			
	The 2 clients perform simultaneous requests to the server.			
	Frames are sent from the test bench to provide a successful answer to the first			
	request, and an RTE_E_LIMIT error to the second one.			
	The test manager checks that the requests are correctly transmitted on a bus and that the results are correctly provided to the callers.			
Needed	and the results are serrestly provided to the sancre.			
Adaptation to				
other Releases				
	Pre-conditions None			
Main Test Execu	ution			
Test Steps	Lan.	Pass Criteria		
Step 1	[CP]			
	start RUN_Client2			
Step 2	[RUN <run_client2>]</run_client2>	[RUN <run_client2>]</run_client2>		
	_			
	execute Rte_Call_Client2A_Write	Rte_Call returns RTE_E_OK		
Step 3		[LT]		
		from MAITE A DEO is transpositional		
		frame WRITE_A_REQ is transmitted on <bus></bus>		
		OII \Duo/		



Step 4	[RUN <run_client2>]</run_client2>	[RUN <run_client2>]</run_client2>
	execute Rte_Call_Client2B_Write	Rte_Call returns RTE_E_OK
Step 5		[LT]
		frame WRITE_A_REQ is transmitted on <bus> (clientId differs from step 3)</bus>
Step 6	[LT]	
	send frame WRITE_A_RES with the clientId and sequenceCounter received in step 3 and return value RTE_E_OK	
Step 7	[LT]	
	send frame WRITE_A_RES with the clientId and sequenceCounter received in step 5 and return value RTE_E_LIMIT	
Step 8	[CP]	[RUN <run_results2>]</run_results2>
	WAIT 100ms	runnable has been started by AsynchronousServerCallReturnsEvent
Step 9	[RUN <run_results2>]</run_results2>	[RUN <run_results2>]</run_results2>
	execute Rte_Result_Client2A_Write	Rte_Result returns RTE_E_OK
Step 10	[RUN <run_results2>]</run_results2>	[RUN <run_results2>]</run_results2>
	execute Rte_Result_Client2B_Write	Rte_Result returns RTE_E_LIMIT
Post- conditions	None	

# 3.3.9 [ATS\_RTE\_00061] Test inter-ECU C-S with operations of 2 ports mapped on one runnable (remote clients)

Test inter-ECU C-S with operations of 2 ports mapped on one runnable (remote clients)		
		3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2
RTE COM	State	reviewed
ATR: ATR_ATR_00001		
RTE: SWS_Rte_03769		
UC01.02.02		
See UC01.02.02 in chapter 3.1.2 Test Configuration.  This test case uses:		
	Clients)  ATS_RTE_00061  RTE COM  ATR: ATR_ATR_00001  RTE: SWS_Rte_03769  UC01.02.02	AUTOSAR   Releases



	L .		
	Tester_Server * port ServerA		
	* port ServerB		
	* runnable serverWrite (invoked by the Write operation on both ports)		
	frames WRITE_A_REQ, WRITE_A_RES, WRITE_B_REQ, WRITE_B_RES		
	The server/system shall be implemented/conf request is not fully processed before the seco		
Summary	The goal of this test is to check the behavior of inter-ECU Client-Server communication when 2 operations are mapped on the same runnable entity (on server side).		
	2 server ports are mapped to the same server remote clients.	r runnable, and are connected to	
	The servers are configured with a ServerCom	Spec.queueLength = 1.	
	The Test Manager sends requests on the bus request is handled correctly and the second reerror.		
Needed Adaptation to other Releases			
Pre-conditions	None		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[CP]		
	Send frame WRITE_A_REQ with value DataValue1, a clientId and sequenceCounter		
Step 2	[CP]		
	Send frame WRITE_B_REQ with value DataValue2, a clientId (different from the one of step 1), and a sequenceCounter		
Step 3	. ,	[RUN <serverwrite>]</serverwrite>	
	WAIT 100ms	serverWrite has been started once by an OperationInvokedEvent and received the value DataValue1	
Step 4		[LT]	
		WRITE_A_RES has been sent by SUT with return value RTE_E_OK and clientId/sequenceCounter as in step 1	
		WRITE_B_RES has been sent by SUT with return value RTE_E_LIMIT and clientId/sequenceCounter as in step 2	
Post- conditions	None		



#### 3.3.10 [ATS\_RTE\_00062] Test n:1 inter-ECU Client-Server communication with queue overflow

Test Objective	Test n:1 inter-ECU Client-Server	communicat	ion with queue overflow
ID	ATS_RTE_00062		3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2
	A13_K1E_00002	Releases	0.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE, COM	State	reviewed
	ATR: ATR_ATR_00002	=	-
Requirement			
on Acceptance Test Document			
	RTE: SWS_Rte_04520		
	RTE: SWS_Rte_08002		
Requirements / Reference to Test Environment			
Configuration	See UC01.02.02 in chapter 3.1.2	Test Config	uration.
Parameters	This test case uses:		
	Tester_Client_1		
	* port Client1A		
	* runnable RUN_Client1 (sscp_R	ead1A)	
	Tester_Server		
	* port ServerA		
	* runnable serverRead		
	frames READ_A_REQ, READ_A_RES		
	In addition:		
	For ServerA: ServerComSpec.queueLength = 2		
	Client1A connected to ServerA. The server/system is implemented/configured so that the first (local) request is not		
	fully processed before the 2 other requests are issued.		
Summary	The goal of this test is to check the behavior of n:1 inter-ECU, including the queue overflow.		
	In this test case, multiple clients in	nvoke the sa	ame operation of a server
	a local client (synchronous servei		and operation of a server.
	2 remote clients (frames sent by t	he test man	ager, for example by Tester_Client_3
	and Tester_Client_4 running on a	nother AUT	OSAR ECU)
	The server is configured with Ser	verComSpe	c.queueLength = 2
	The test manager checks that the first remote request is processed successfully and the second request receives an RTE_E_LIMIT error.		
Needed			
Adaptation to other Releases			
Pre-conditions	None		
Main Test Execu			
Test Steps			Pass Criteria
•	[CP]		



	start RUN_Client1	
Step 2	[RUN <run_client1>]</run_client1>	
	execute Rte_Call_Client1A_Read (blocking call)	
Step 3	[LT]	
	send frame READ_A_REQ with first clientId	
Step 4	[LT]	
	send frame READ_A_REQ with second clientId	
Step 5	[CP]	[RUN <run_client1>]</run_client1>
	WAIT 100ms	Rte_Call has finished its execution, has returned RTE_E_OK and returned the value provided by the server
Step 6		[LT]
		2 READ_A_RES frames have been transmitted:
		<ul> <li>one with the clienId/sequenceCounter of step 3, a return value set to RTE_E_OK and the value provided by the server</li> <li>the other one with the clientId/sequenceCounter of step 4, and a return value set to RTE_E_LIMIT</li> </ul>
Post- conditions	None	

### 3.3.11 [ATS\_RTE\_00063] Test inter-ECU Client-Server communication with timeout (synchronous server call)

Test Objective	Test inter-ECU Client-Server com	nmunication	with timeout (synchronous server call)
ID		AUTOSAR Releases	3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE, COM	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00002		
Trace to SWS Item	RTE: SWS_Rte_03763		
Requirements / Reference	UC01.02.01		



to Test Environment					
Configuration	See UC01.02.01 in chapter 3.1.2 Test Configuration.				
Parameters					
	Tester_Client_1				
	* port Client1A				
	* runnable RUN_Client1 (sscp_Read1A)				
	frame READ_A_REQ				
	In addition: A timeout is configured on the sscp_Read1A	: 10ms			
Summary	The goal of this test case is to check the beh				
	communication when a timeout occurs and the call.	ne client uses a synchronous server			
	For this test case, the server is on the test be	ench, the client (Tester_Client_1)			
	performs a synchronous call to the server.	. , = = ,			
	The test bench does not provide a response	within 20ms.			
	The test manager checks that the client rece	ives an RTE_E_TIMEOUT error.			
	The client is able to perform another request	to the server afterwards.			
Needed					
Adaptation to other Releases					
Pre-conditions					
Main Test Exec					
Test Steps		Pass Criteria			
Step 1	[CP]				
	start RUN_Client1				
Step 2	[RUN <run_client1>]</run_client1>	[LT]			
	execute Rte_Call_Client1A_Read	frame READ_A_REQ is transmitted on <bus></bus>			
Step 3	[CP]				
	WAIT 00				
	WAIT 20ms (test bench remains silent on <bus> during</bus>				
	that time)				
Step 4	[LT]				
	send frame READ A RES with the same				
	clientId and sequenceCounter as in step 2 with value DataValue1				
Step 5	with value Data value i	[RUN <run_client1>]</run_client1>			
Olep 3					
		Rte_Call returns RTE_E_TIMEOUT			
Step 6	[RUN <run_client1>]</run_client1>	[LT]			
	Land to Discoult Office (4A) Book	from a DEAD. A DEO is to a service to			
	execute Rte_Call_Client1A_Read	frame READ_A_REQ is transmitted on <bus> (same clientId, but different</bus>			



Step 7	[LT]	[RUN <run_client1>]</run_client1>		
		Rte_Call returns RTE_E_OK with value DataValue2		
Post- conditions	None			

### 3.3.12 [ATS\_RTE\_00064] Test inter-ECU Client-Server communication with timeout (asynchronous server call)

Took Objective	Objective Test inter-ECU Client-Server communication with timeout (asynchronous server			
l est Objective	call)			
ID		Releases	3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2	
Affected Modules	RTE, COM	State	reviewed	
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00001			
Trace to SWS Item	RTE: SWS_Rte_03763 RTE: SWS_Rte_03765 RTE: SWS_Rte_03772 RTE: SWS_Rte_03773			
Requirements / Reference to Test Environment	UC01.02.01			
	See UC01.02.01 in chapter 3.1.2 Test Configuration.  This test case uses: Tester_Client_2 * port Client2A * runnable RUN_Client2 (ascp_Read2A) * runnable RUN_Results2 (ascrp_Read2A, ASCRE_Read2A)  frame READ_A_REQ  In addition: A timeout is configured on ascp_Read2A: 10ms			
Summary	communication when a timeout or call.  For this test case, the server is or performs an asynchronous call to The test bench does not provide a The test manager checks that the	al of this test case is to check the behavior of inter-ECU Client-Server nication when a timeout occurs and the client uses an asynchronous server test case, the server is on the test bench, the client (Tester_Client_2) as an asynchronous call to the server. It bench does not provide a response within 20ms.  It manager checks that the client receives an RTE_E_TIMEOUT error.  The sent is able to perform another request to the server afterwards		



Needed Adaptation to		
other Releases		
Pre-conditions		
Main Test Execu	ution	
Test Steps		Pass Criteria
Step 1	[CP] start RUN_Client2	
Step 2	[RUN <run_client2>]</run_client2>	[LT]
	execute Rte_Call_Client2A_Read	frame READ_A_REQ transmitted on <bus></bus>
Step 3	[CP]	[RUN <run_results2>]</run_results2>
	WAIT 20ms (test bench remains silent during that time)	runnable has been started by an AsynchronousServerReturnsEvent
Step 4	[RUN <run_results2>]</run_results2>	[RUN <run_results2>]</run_results2>
	execute Rte_Result_Client2A_Read	Rte_Result returns RTE_E_TIMEOUT
Step 5	[LT]	
	send frame READ_A_RES with the same clientId and sequenceCounter as in step 2 with value DataValue1	
Step 6	[RUN <run_client2>]</run_client2>	[LT]
	execute Rte_Call_Client2A_Read	frame READ_A_REQ is transmitted on <bus> (same clientId, but different sequenceCounter than in step 2)</bus>
Step 7	[LT]	[RUN <run_results2>]</run_results2>
	send frame READ_A_RES with the same clientId and sequenceCounter as in step 6 with value DataValue2	runnable has been started by an AsynchronousServerCallReturnsEvent
Step 8	[RUN <run_results2>]</run_results2>	[RUN <run_results2>]</run_results2>
	execute Rte_Result_Client2A_Read	Rte_Result returns RTE_E_OK with value DataValue2
Post- conditions	None	

## 3.3.13 [ATS\_RTE\_00065] Test inter/intra-ECU C-S with operations of 2 ports mapped on one runnable

Test Objective	Test inter/intra-ECU C-S with operations of 2 ports mapped on one runnable			
ID		AUTOSAR Releases	3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2	
Affected Modules	RTE, COM	State	reviewed	



_				
	ATR: ATR_ATR_00001			
Requirement on Acceptance				
Test Document				
	RTE: SWS_Rte_08002			
Item				
Requirements /	UC01.02.02			
Reference				
to Test				
Environment	0 - 11004 00 00 is also 4 0 Test 0 - 1"			
Configuration Parameters	See UC01.02.02 in chapter 3.1.2 Test Config	uration.		
raiailleteis	This test case uses:			
	Tester_Client_1			
	* port Client1A			
	* runnable RUN_Client1 (sscp_Write1A)			
	Tester_Client_2			
	* port Client2B			
	* runnable RUN_Client2 (ascp_Write2B)			
	Tester_Server			
	* port ServerA * port ServerB			
	* runnable serverRead (invoked by the Write	operation on both ports)		
	Tallitable server read (inverted by the vinter	operation on both porter		
	frames $WRITE\_A\_REQ$ , $WRITE\_A\_RES$ for t	he inter-ECU communication to		
	ServerA (operation Write)			
	frames WRITE_B_REQ, WRITE_B_RES for the inter-ECU communication to ServerB (operation Write)			
	Client1A connected to ServerA Client2B connected to ServerB			
	The server/system shall be implemented/conf are fully processed before all requests are iss			
	The goal of this test is to check the behavior of 2 operations are mapped on the same runnablare both local and remote.			
	2 server ports are mapped to the same server runnable, and are connected to remote and local clients.			
	The servers are configured with a ServerCom	Spec.queueLength = 2.		
	The test manager sends requests on the bus, 2 requests are handled correctly and the subs			
Needed Adaptation to other Releases				
Pre-conditions	None			
Main Test Execu	ution			
Test Steps		Pass Criteria		
•	[CP]			
	I	l		



	start RUN_Client2	
Step 2	[RUN <run_client2>]</run_client2>	[RUN <run_client2>]</run_client2>
	execute Rte_Call_Client2A_Write	Rte_Call returns RTE_E_OK
Step 3	[LT]	
	send frame WRITE_B_REQ	
Step 4	[LT]	
	send frame WRITE_A_REQ	
Step 6	[CP]	[LT]
	WAIT 100ms	frame WRITE_B_RES has been transmitted with clientId and sequenceCounter from step 3, and return value RTE_E_OK
		frame WRITE_A_RES has been transmitted with clientId and sequenceCounter from step 4, and return value RTE_E_LIMIT
Step 7	-	[RUN <run_results2>]</run_results2>
		runnable has been started by AsynchronousServerCallReturnsEvent
Step 8	[RUN <run_results2>]</run_results2>	[RUN <run_results2>]</run_results2>
	execute Rte_Result_Client2A_Write	Rte_Result returns RTE_E_OK
Step 9	[CP]	
	terminate RUN_Client2 and RUN_Results2	
Post- conditions	None	

### 3.3.14 [ATS\_RTE\_00071] Test n:1 inter-ECU Client-Server communication (remote clients)

Test Objective	Test n:1 inter-ECU Client-Server communication (remote clients)		
ID	ATS_RTE_00071	AUTOSAR Releases	3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE, COM	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00001		
Trace to SWS Item			
Requirements / Reference to Test Environment	UC01.02.02		



Configuration Parameters	See UC01.02.02 in chapter 3.1.2 Test Configuration.			
rarameters	This test case uses: Tester_Server * port RepeatS * runnable serverRepeat, which repeats its IN parameter into its OUT parameter			
	frames REPEAT_REQ, REPEAT_RES			
	In addition:			
	For ServerRepeat: ServerComSpec.queueLe	ngth >= 3		
Summary	The goal of this test is to check the behavior of invoked by remote clients.			
	The server is located on the SUT. It repeats in received in its IN parameter.	n its OUT parameter the value		
	3 requests (with 3 different IN parameter valu (clientId1, clientId2).	es) are sent by 2 different clients		
	The test manager checks that each request rerepeated)	eceives the correct response (value is		
Needed Adaptation to other Releases				
Pre-conditions	None			
Main Test Exec	ution			
Test Steps		Pass Criteria		
Step 1	[LT]	•		
·	j ·			
	send frames:			
	<ul> <li>REPEAT_REQ with clientId1,</li> </ul>			
	sequenceCounter=1, IN			
	<ul><li>parameter=DataValue1</li><li>REPEAT_REQ with clientId2,</li></ul>			
	sequenceCounter=1, IN			
	parameter=DataValue2			
	<ul> <li>REPEAT_REQ with clientId1, sequenceCounter=2, IN</li> </ul>			
	parameter=DataValue3			
Step 2	[CP]	[RUN <serverrepeat>]</serverrepeat>		
	WAIT 100ms	runnable has been started 3 times, with IN parameter successively DataValue1, DataValue2, DataValue3		
Step 3		[LT]		
Otep 3		r,		
		The following frames have been transmitted by SUT on <bus>:</bus>		
		<ul> <li>REPEAT_RES with clientId1, sequenceCounter=1, OUT parameter=DataValue1, return=RTE_E_OK</li> </ul>		
		TOTHER LE LIK		



		•	REPEAT_RES with clientId2, sequenceCounter=1, OUT parameter=DataValue2, return=RTE_E_OK REPEAT_RES with clientId1, sequenceCounter=2, OUT parameter=DataValue3, return=RTE_E_OK
Post- conditions	None		

### 3.3.15 [ATS\_RTE\_00141] Test inter-ECU Client-Server communication - array on client side

Test Objective	Test inter-ECU Client-Server communication - array on client side		
ID	ATS_RTE_00141	AUTOSAR Releases	3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE, COM	State	reviewed
Trace to Requiremen t on Acceptance Test Document	ATR: ATR_ATR_00001		
Trace to SWS Item	RTE: SWS_Rte_08761		
Requiremen ts / Reference to Test Environmen t	UC01.02.01		
on	See UC01.05 in chapter 3.1.2 Test Configuration.  This test case uses: Tester_Client_4 * port Repeat4 * runnable RUN_Client4 (sscp_RepeatArray4)		
	frame REPEATARRAY_REQ, which include a clientId, a sequenceCounter and the 3 uint8 values of the array frame REPEATARRAY_RES, which include a clientId, a sequenceCounter, the 3 uint8 values of the array, and a return value  The client serializer concatenate clientId, sequenceCounter, and the 3 array values as uint8 signals The client deserializer extracts in the byte stream: clientId, sequenceCounter, array[0], array[1], array[2], return value in this order (each value is a uint8)		
Summary	The goal of this test is to check the serialization (resp. deserialization) by a client of an array IN (resp. OUT) parameter in case of remote server invocation.		



	The client, on SUT, invokes a server with an array IN parameter.		
	The test manager checks that the IN parameter is correctly serialized in uint8 signals in the transmitted frame.		
	The test manager sends back the same data in a response frame and checks that the client receives the correct array values.		
Needed Adaptation to other Releases			
Pre- conditions	None		
Main Test Ex	recution		
Test Steps		Pass Criteria	
Step 1	[CP]		
	start RUN_Client4		
Step 2	[RUN <run_client4>]</run_client4>	[LT]	
	ArrayIn[0]=0x55 ArrayIn[1]=0xAA ArrayIn[2]=0x55 execute	frame REPEATARRAY_REQ is transmitted with byte stream: [clientId,sequenceCounter,0x55,0xAA, 0x55]	
	Rte_Call_Repeat4_RepeatArray(&ArrayIn[0], &ArrayOut[0])		
Step 3	[LT]	[RUN <run_client4>]</run_client4>	
	send frame REPEATARRAY_RES with byte stream: [clientId,sequenceCounter,0x55,0xAA,0x55,RTE _E_OK]	Rte_Call returns RTE_E_OK and provides the following array:  ArrayOut[0]=0x55  ArrayOut[1]=0xAA  ArrayOut[2]=0x55	
Post- conditions	None		

### 3.3.16 [ATS\_RTE\_00142] Test inter-ECU Client-Server communication - array on server side

Test Objective	Test inter-ECU Client-Server communication - array on server side			
ID	ATS_RTE_00142	AUTOSA R Releases	3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2	
Affected Modules	RTE, COM	State	reviewed	
Trace to Requiremen t on Acceptance				



_			
Test Document			
	DTE: 0140 Dt- 00700		
Trace to SWS Item	RTE: SWS_Rte_08762		
Requiremen	UC01.02.02		
ts/	3 3 3 1 3 2 3 3		
Reference			
to Test			
Environmen			
Configurati	See UC01.02.02 in chapter 3.1.2 Test	Configuration	
on	1000 0001.02.02 in onapter 0.1.2 1000	Configuration.	
Parameters	This test case uses:		
	Tester_Server		
	* port RepeatS		
	* runnable repeatArray		
	frame REPEATARRAY REQ, which in	clude a clientId, a sequenceCounter and the 3	
	uint8 values of the array	·	
		clude a clientId, a sequenceCounter, the 3 uint8	
	values of the array, and a return value		
Summary		ialization (resp. deserialization) by a server of an	
	array in (resp. OUT) parameter in case	e of server invocation by a remote client.	
	The test manager sends a frame to inv	roke the server	
	The lest manager sends a frame to inv	oke the server.	
	It checks that the server is executed and received the correct IN parameter, and then		
	checks that the server's response is correctly transmitted on the bus.		
Needed			
Adaptation			
to other Releases			
Pre-	None		
conditions	None		
Main Test Ex	recution		
Test Steps		Pass Criteria	
	[LT]		
	-		
	send frame REPEATARRAY_REQ		
	with byte stream:		
	[clientId,sequenceCounter,0x55,0xAA,0x55]		
Step 2	[CP]	[RUN <serverrepeatarray>]</serverrepeatarray>	
otop Z	[	[NOTE SOLVE IN OPERIOR IT REST.	
	WAIT 100ms	runnable has been started by	
		OperationInvokedEvent and received IN	
		parameter [0xAA,0x55,0xAA]	
Step 3	[RUN <serverrepeatarray>]</serverrepeatarray>	[LT]	
	copy IN parameter into OUT	frame REPEATARRAY_RES is transmitted with	
	parameter and return RTE_E_OK	byte stream: [clientId,sequenceCounter,0xAA,0x55,0xAA,RTE	
		[clientid,sequenceCounter,0xAA,0x55,0xAA,RTET _E_OK]	
Post-	None		
conditions			



### 3.3.17 [ATS\_RTE\_00206] Test intra-ECU Client-Server communication - independence of operations

Test Objective	Test intra-ECU Client-Server comm	nunication -	independence of operations
ID		AUTOSAR Releases	3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules		State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00001		
Trace to SWS Item	RTE: SWS_Rte_04517 RTE: SWS_Rte_04518		
Requirements / Reference to Test Environment	UC01.01		
Configuration Parameters	See UC01.01 in chapter 3.1.2 Test Configuration.  This test case uses: Tester_Client_1 * port Client1A * runnable RUN_Client1 (sscp_Read1A)  Tester_Client_2 * port Client2A * runnable RUN_Client2 (ascp_Write2A)  Tester_Server * port ServerA * runnable serverRead * runnable serverWrite		
Summary	Client1A and Client2A connected to ServerA.  The goal of this test case is to check that operations of a server can be invoked independently.  Tester_Client_1 invokes the Write operation (synchronous server call).  Tester_Client_2 invokes the Read operation (asynchronous server call).  The test manager check that both invocations succeed and give the appropriate result.		
Needed Adaptation to other Releases			
Pre-conditions			
Main Test Exec	ution		
Test Steps			Pass Criteria
Step 1	[CP] start RUN_Client1, RUN_Client2		
56 of 302	,		Document ID 634: AUTOSAR ATS RT



Step 2	[RUN <run_client2>]</run_client2>	[RUN <run_client2>]</run_client2>
	execute Rte_Call_Client2A_Write(DataValue1)	Rte_Call returns RTE_E_OK
Step 3	[RUN <run_client1>]</run_client1>	[RUN <run_client1>]</run_client1>
		Rte_Call returns RTE_E_OK and data returned in DataValue1
Step 4	[CP]	
	terminate RUN_Client1, RUN_Client2	
Post- conditions	None	

## 3.3.18 [ATS\_RTE\_00242] Test concurrent activation of server (runnable not mapped to task)

	ı		1
Test Objective	Test concurrent activation of serv	•	
ID		AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00002		
Trace to SWS Item	RTE: SWS_Rte_03523		
Requirements / Reference to Test Environment	UC01.01		
Configuration Parameters	See UC01.01 in chapter 3.1.2 Test Configuration.  This test case uses: Tester_Client_1 * port Reentrant1 * runnable RUN_Client1 (sscp_Reentrant1)  Tester_Client_3 * port Reentrant3 * runnable RUN_Client3 (sscp_Reentrant3)  Tester_Server * port ReentrantS * runnable serverReentrant, canBeInvokedConcurrently=true  Reentrant1 and Reentrant3 connected to ReentrantS.  serverReentrant is not mapped to a task The serverReentrant/system shall be implemented/configured in such way that the request of Tester_Client_1 is being processed when the request of Tester_Client_3		



Summary	The goal of this test case is to check the support of the RTE for servers that canBeInvokedConcurrently when they are not mapped to a task (i.e. direct function call).  In this test case, the Tester_Client_1 and Tester_Client_3 will call simultaneously the server operation Reentrant (the request from Tester_Client_3 is issued while the Tester_Client_1 request is processed).		
	The test manager checks that the requests of Tester_Client_1 and Tester_Client_3 are handled correctly.		
	HINT: The server could for example trigger the execution of RUN_Client3 depending on its parameter, and RUN_Client3 can be mapped to a task with an higher priority or the server could change its duration based on the its parameter.		
Needed Adaptation to other Releases			
Pre-conditions			
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[CP]		
	start RUN_Client1		
Step 2	[RUN <run_client1>] execute</run_client1>		
Step 3	Rte_Call_Reentrant1_Reentrant(0x55)		
элер э	[CP] start RUN_Client3 before the end of the server execution		
Step 4	[RUN <run_client3>]</run_client3>	[RUN <serverreentrant>]</serverreentrant>	
	execute Rte_Call_Reentrant3_Reentrant(0xAA)	runnable has been started twice with parameters 0x55 and 0xAA. 2 instances of the runnable have been executed simultaneously.	
Step 5		[RUN <run_client1>] Rte_Call returns RTE_E_OK</run_client1>	
Step 6		[RUN <run_client3>]</run_client3>	
otep 0		Rte_Call returns RTE_E_OK	
Post- conditions			

## 3.3.19 [ATS\_RTE\_00249] Test concurrent activation of server (runnable mapped to task)

Test Objective	Test concurrent activation of server (runnable mapped to task)			
ID	ATS_RTE_00249 AUTOSAR 3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2			
		Releases		



Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00002		
Trace to SWS Item			
Requirements / Reference to Test Environment	UC01.01		
Configuration Parameters	request of Tester_Client_1 is beir is issued.	eentrant1) eentrant3) eelnvokedCo ected to Ree ask I be implemen	entrantS.  ented/configured in such way that the d when the request of Tester_Client_3
Summary	the server operation Reentrant (the Tester_Client_1 request is procest that the are handled correctly.  HINT: The server could for example the server could be server could for example the server could for example the se	they are many they are many at_1 and Testine request from the requests of the pole, depending to a task with the results of the testine requests of the request of the requests of the request	apped to a task.  ster_Client_3 will call simultaneously rom Tester_Client_3 is issued while the  f Tester_Client_1 and Tester_Client_3  ng on its parameter, trigger the with an higher priority or the server
Needed Adaptation to other Releases			
Pre-conditions	None		
Main Test Execu	ution		
Test Steps			Pass Criteria
Step 1	[CP]		
	start RUN_Client1		



Step 2	[RUN <run_client1>]</run_client1>	
	execute Rte_Call_Reentrant1_Reentrant(0x55)	
Step 3	[CP]	
	start RUN_Client3 before the end of the server execution	
Step 4	[RUN <run_client3>]</run_client3>	[RUN <serverreentrant>]</serverreentrant>
	execute Rte_Call_Reentrant3_Reentrant(0xAA)	runnable has been started twice with parameters 0x55 and 0xAA.
Step 5		[RUN <run_client1>]</run_client1>
		Rte_Call returns RTE_E_OK
Step 6		[RUN <run_client3>]</run_client3>
		Rte_Call returns RTE_E_OK
Post- conditions	None	

### 3.3.20 [ATS\_RTE\_00846] Test synchronous server call for 1:1 intra-ECU Client-Server communication for INOUT Argument

Test Objective	Test synchronous server call for 1:1 intra-ECU Client-Server communication for INOUT Argument		
ID	ATS_RTE_00846	AUTOSAR Releases	3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00002		
Item	RTE: SWS_Rte_01020 RTE: SWS_Rte_01102 RTE: SWS_Rte_01104 RTE: SWS_Rte_01166 RTE: SWS_Rte_01293		
Requirements / Reference to Test Environment	UC01.01		
Configuration Parameters	See UC01.01 in chapter 3.1.2 Test Configuration.  This test case uses: Tester_Client_1 * port Client1A * runnable RUN_Client1 (sscp_ReadWrite1A) Tester_Server * port ServerA * runnable serverReadWrite		




	Client1A connected to ServerA.		
	ServerA triggers serverReadWrite.		
Summary	The goal of this test is to check the behavior of synchronous server call in case of 1:1 Intra-ECU Client-Server communication for INOUT argument.		
	In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter.		
	The Test Manager checks that the operation	ns are handled correctly.	
Needed Adaptation to other Releases	None		
Pre-conditions	None		
Main Test Execu	ution		
Test Steps	Pass Criteria		
Step 1	[CP]		
	r., 1		
	start RUN_Client1		
Step 2		[RUN <run_client1>]</run_client1>	
Step 2	start RUN_Client1	[RUN <run_client1>]  Rte_Call returns RTE_E_OK, data returned is 0xAA</run_client1>	
Step 2 Step 3	start RUN_Client1  [RUN <run_client1>]  set data to 0x55 and execute</run_client1>	Rte_Call returns RTE_E_OK, data	
·	start RUN_Client1  [RUN <run_client1>]  set data to 0x55 and execute  Rte_Call_Client1A_ReadWrite(&amp;data)</run_client1>	Rte_Call returns RTE_E_OK, data	

# 3.3.21 [ATS\_RTE\_00852] Test asynchronous server call for 1:1 intra-ECU Client-Server communication for INOUT Argument

Test Objective	Test asynchronous server call for 1:1 intra-ECU Client-Server communication for INOUT Argument		
ID		AUTOSAR Releases	3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01020 RTE: SWS_Rte_01102 RTE: SWS_Rte_01104 RTE: SWS_Rte_01111 RTE: SWS_Rte_01112 RTE: SWS_Rte_01166 RTE: SWS_Rte_01294 RTE: SWS_Rte_01296		



See UC01.01 in chapter 3.1.2 Test Configuration.  Parameters  This test case uses:     Tester_Client_2     *port Client2A     *runnable RUN_Client2 (ascp_ReadWrite2A)     *runnable RUN_Results2 (ascrp_ReadWrite2A, ASCRE_ReadWrite2A)  Tester_Server     *port ServerA     *runnable serverReadWrite  Client2A connected to ServerA.  ServerA triggers serverReadWrite.  Summary  The goal of this test is to check the behavior of asynchronous server calls in case of 1:1 intra-ECU Client-Server communication for an operation which has INOUT argument  This test involves communication between Tester_Client_2 and Tester_Server.  The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  None  None  Main Test Execution  Test Steps  Pass Criteria  [CP]  start RUN_Client2  [RUN <run_client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Rte_Call returns RTE_E_OK</run_client2>		L			
to Test Environment  Configuration Parameters  See UC01.01 in chapter 3.1.2 Test Configuration.  This test case uses:     Tester Client 2     * port Client2A     * runnable RUN_Client2 (ascrp_ReadWrite2A)     * runnable RUN_Results2 (ascrp_ReadWrite2A)     Tester_Server     * port ServerA     * runnable serverReadWrite  Client2A connected to ServerA. ServerA triggers serverReadWrite.  Summary  The goal of this test is to check the behavior of asynchronous server calls in case of 1:1 intra-ECU Client-Server communication for an operation which has INOUT argument  This test involves communication between Tester_Client_2 and Tester_Server.  The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rie_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  None  Adaptation to other Releases  Pre-conditions  None  Main Test Execution  Test Steps  Pass Criteria  [CP]  start RUN_Client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  [CP]  WAIT 100ms  Pass Criteria  Rte_Call returns RTE_E_OK execute Rte_Call_Client2A_ReadWrite(data)  [RUN <run_results2>]  RUN<run_results2>]  RUN<run_results2>]  RUN<run_results2>]  RUN<run_results2>]</run_results2></run_results2></run_results2></run_results2></run_results2>		UC01.01	UC01.01		
Environment  Configuration Parameters  See UC01.01 in chapter 3.1.2 Test Configuration.  This test case uses: Tester_Client_2 * port Client2A * runnable RUN_Client2 (ascp_ReadWrite2A) * runnable RUN_Results2 (ascrp_ReadWrite2A) Tester_Server * port ServerA * runnable serverReadWrite  Client2A connected to ServerA. ServerA triggers serverReadWrite.  Summary  The goal of this test is to check the behavior of asynchronous server calls in case of 1:1 intra-ECU Client-Server communication for an operation which has INOUT argument This test involves communication between Tester_Client_2 and Tester_Server.  The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rie_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  None  Main Test Execution Test Steps  Pass Criteria  [CP]  start RUN_Client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  [CP]  WAIT 100ms  Pass Criteria  [RUN <run_results2>]  [RUN<run_results2>]  [RUN<run_results2>]  [RUN<run_results2>]  Rte_Result returns RTE_E_OK, data</run_results2></run_results2></run_results2></run_results2>					
This test case uses: Tester_Client_2 port Client2A * runnable RUN_Client2 (ascp_ReadWrite2A) * runnable RUN_Results2 (ascrp_ReadWrite2A) * runnable RUN_Results2 (ascrp_ReadWrite2A, ASCRE_ReadWrite2A)  Tester_Server port ServerA * runnable serverReadWrite  Client2A connected to ServerA.  ServerA triggers serverReadWrite.  Summary  The goal of this test is to check the behavior of asynchronous server calls in case of 1:1 intra=ECU Client-Server communication for an operation which has INOUT argument  This test involves communication between Tester_Client_2 and Tester_Server.  The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  None  Adaptation to other Releases  Pre-conditions  None  Main Test Execution  Test Steps  Pass Criteria  [CP]  start RUN_Client2  [RUN <run_client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  [CP]  WAIT 100ms  Regults2&gt;]  Run_Run_Results2&gt;]  runnable has been started by AsynchronousServerCallReturnsEvent  Rte_Result returns RTE_E_OK, data</run_client2>	Environment				
This test case uses: Tester Client 2 port Client2A runnable RUN_Client2 (ascp_ReadWrite2A) runnable RUN_Results2 (ascrp_ReadWrite2A) Tester_Server port ServerA runnable serverReadWrite  Client2A connected to ServerA. ServerA triggers serverReadWrite.  The goal of this test is to check the behavior of asynchronous server calls in case of 1:1 intra-ECU Client-Server communication for an operation which has INOUT argument  This test involves communication between Tester_Client_2 and Tester_Server.  The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  None Adaptation to other Releases Pre-conditions   None Main Test Execution  Test Steps   Pass Criteria  [CP]   RUN-RUN_Client2>]   RUN-RUN_Client2>]   Re_Call returns RTE_E_OK   Re_Call returns RTE_E_OK   Run-Run_Results2>]   Run-Run_Resul	Configuration	See UC01.01 in chapter 3.1.2 Test Configura	tion.		
Tester_Client_2  ' port Client2A  ' runnable RUN_Client2 (ascp_ReadWrite2A)  ' runnable RUN_Results2 (ascrp_ReadWrite2A, ASCRE_ReadWrite2A)  Tester_Server  ' port ServerA  ' runnable serverReadWrite  Client2A connected to ServerA.  ServerA triggers serverReadWrite.  Summary  The goal of this test is to check the behavior of asynchronous server calls in case of 1:1 intra-ECU Client-Server communication for an operation which has INOUT argument  This test involves communication between Tester_Client_2 and Tester_Server.  The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  None  Adaptation to other Releases  Pre-conditions  None  Main Test Execution  Test Steps  Res Criteria  [CP]  start RUN_Client2  Step 1  [CP]  start RUN_Client2  [RUN <run_client2>]  Re_Call returns RTE_E_OK  AsynchronousServerCallReturnsEvent  [RUN<run_results2>]  runnable has been started by AsynchronousServerCallReturnsEvent  Re_Result returns RTE_E_OK, data</run_results2></run_client2>	Parameters	L.,			
* port Client2A * runnable RUN_Client2 (ascp_ReadWrite2A) * runnable RUN_Results2 (ascrp_ReadWrite2A) * runnable RUN_Results2 (ascrp_ReadWrite2A, ASCRE_ReadWrite2A)  Tester_Server * port ServerA * runnable serverReadWrite  Client2A connected to ServerA.  ServerA triggers serverReadWrite.  Summary  The goal of this test is to check the behavior of asynchronous server calls in case of 1:1 intra_ECU Client-Server communication for an operation which has INOUT argument  This test involves communication between Tester_Client_2 and Tester_Server.  The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  None  Adaptation to other Releases  Pre-conditions   None  Main Test Execution  Test Steps   Pass Criteria  [CP]  start RUN_Client2>]   IRUN <run_client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Trunnable has been started by AsynchronousServerCallReturnsEvent  Step 4   IRUN<run_results2>]   IRUN<run_results2>]  Rte_Result returns RTE_E_OK, data</run_results2></run_results2></run_client2>					
' runnable RUN_Results2 (ascp_ReadWrite2A) ' runnable RUN_Results2 (ascrp_ReadWrite2A, ASCRE_ReadWrite2A)  Tester_Server ' port ServerA ' runnable serverReadWrite  Client2A connected to ServerA.  ServerA triggers serverReadWrite.  Summary  The goal of this test is to check the behavior of asynchronous server calls in case of 1:1 intra-ECU Client-Server communication for an operation which has INOUT argument  This test involves communication between Tester_Client_2 and Tester_Server.  The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  Needed Adaptation to other Releases  Pre-conditions None  Main Test Execution  Test Steps  Pass Criteria  [CP]  start RUN_Client2  Step 1  [CP]  start RUN_Client2  [RUN-RUN_Client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Step 3  [CP]  WAIT 100ms  RUN-Results2>]  runnable has been started by AsynchronousServerCallReturnsEvent  [RUN-RUN_Results2>]  execute  Rte_Result returns RTE_E_OK, data					
Tester_Server  † port ServerA  † runnable serverReadWrite  Client2A connected to ServerA.  ServerA triggers serverReadWrite.  The goal of this test is to check the behavior of asynchronous server calls in case of 1:1 intra-ECU client-Server communication for an operation which has INOUT argument  This test involves communication between Tester_Client_2 and Tester_Server.  The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  None  Adaptation to other Releases  Pre-conditions  None  Main Test Execution  Test Steps  Pass Criteria  [CP]  start RUN_Client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  [CP]  walt 100ms  Repaired to start and read correctly and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  None  Main Test Execution  Test Steps  Pass Criteria  [CP]  start RUN_Client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Rte_Call returns RTE_E_OK  AsynchronousServerCallReturnsEvent  RUN-RUN_Results2>]  runnable has been started by AsynchronousServerCallReturnsEvent  RUN-RUN_Results2>]  execute  Rte_Result returns RTE_E_OK, data		* runnable RUN_Client2 (ascp_ReadWrite2A)			
* port ServerA * runnable serverReadWrite  Client2A connected to ServerA.  ServerA triggers serverReadWrite.  The goal of this test is to check the behavior of asynchronous server calls in case of 1:1 intra-ECU Client-Server communication for an operation which has INOUT argument  This test involves communication between Tester_Client_2 and Tester_Server.  The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  None  Adaptation to other Releases  Pre-conditions  None  Main Test Execution  Test Steps  [CP]  start RUN_Client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  [CP]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  [CP]  WAIT 100ms  Funnable has been started by AsynchronousServerCallReturnsEvent  Step 4  [RUN <run_results2>]  execute  Rte_Result returns RTE_E_OK, data</run_results2>		* runnable RUN_Results2 (ascrp_ReadWrite2	2A, ASCRE_ReadWrite2A)		
* runnable serverReadWrite Client2A connected to ServerA. ServerA triggers serverReadWrite.  The goal of this test is to check the behavior of asynchronous server calls in case of 1:1 intra-ECU Client-Server communication for an operation which has INOUT argument  This test involves communication between Tester_Client_2 and Tester_Server.  The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  Needed Adaptation to other Releases Pre-conditions None Main Test Execution  Test Steps  Pass Criteria  [CP]  start RUN_Client2  Step 1  [CP]  start RUN_Client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Rte_Call returns RTE_E_OK  execute Rte_Call_Client2A_ReadWrite(data)  Step 3  [CP]  WAIT 100ms  runnable has been started by AsynchronousServerCallReturnsEvent  Step 4  [RUN <run_results2>]  execute  Rte_Result returns RTE_E_OK, data</run_results2>					
Client2A connected to ServerA.  ServerA triggers serverReadWrite.  The goal of this test is to check the behavior of asynchronous server calls in case of 1:1 intra-ECU Client-Server communication for an operation which has INOUT argument  This test involves communication between Tester_Client_2 and Tester_Server.  The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  None  Main Test Execution  Test Steps  Pass Criteria  ICP]  start RUN_Client2  Step 1 [CP]  start RUN_Client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Rte_Call returns RTE_E_OK  execute Rte_Call_Client2A_ReadWrite(data)  Step 3 [CP]  WAIT 100ms  runnable has been started by AsynchronousServerCallReturnsEvent  Step 4 [RUN <run_results2>]  execute  Rte_Result returns RTE_E_OK, data</run_results2>					
ServerA triggers serverReadWrite.  Summary  The goal of this test is to check the behavior of asynchronous server calls in case of 1:1 intra-ECU Client-Server communication for an operation which has INOUT argument  This test involves communication between Tester_Client_2 and Tester_Server.  The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  Needed Adaptation to other Releases  Pre-conditions None  Main Test Execution  Test Steps  Pass Criteria  [CP]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Step 2  [RUN <run_client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Step 3  [CP]  WAIT 100ms  runnable has been started by AsynchronousServerCallReturnsEvent  Step 4  [RUN<run_results2>]  execute  Rte_Result returns RTE_E_OK, data</run_results2></run_client2>		* runnable serverReadWrite			
The goal of this test is to check the behavior of asynchronous server calls in case of 1:1 intra-ECU Client-Server communication for an operation which has INOUT argument  This test involves communication between Tester_Client_2 and Tester_Server.  The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  Needed Adaptation to other Releases  Pre-conditions  None  Main Test Execution  Test Steps  Pass Criteria  [CP]  start RUN_Client2  [RUN <run_client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Step 3  [CP]  WAIT 100ms  [RUN<run_results2>]  runnable has been started by AsynchronousServerCallReturnsEvent  [RUN<run_results2>]  execute  Rte_Result returns RTE_E_OK, data</run_results2></run_results2></run_client2>		Client2A connected to ServerA.			
1:1 intra-ECU Client-Server communication for an operation which has INOUT argument  This test involves communication between Tester_Client_2 and Tester_Server.  The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  None  None  Main Test Execution  Test Steps  Pass Criteria  Step 1  [CP]  start RUN_Client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Rte_Call returns RTE_E_OK  EXECUTE RUN <run_results2>]  runnable has been started by AsynchronousServerCallReturnsEvent  [RUN<run_results2>]  [RUN<run_results2>]  [RUN<run_results2>]  [RUN<run_results2>]  Rte_Result returns RTE_E_OK, data</run_results2></run_results2></run_results2></run_results2></run_results2>		ServerA triggers serverReadWrite.			
The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.  In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  None  Main Test Execution  Test Steps  Pass Criteria  Step 1  [CP]  start RUN_Client2  Step 2  [RUN <run_client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  [CP]  WAIT 100ms  RunN<run_results2>]  WAIT 100ms  Step 4  [RUN<run_results2>]  [RUN<run_results2>]  [RUN<run_results2>]  [RUN<run_results2>]  [RUN<run_results2>]  [RUN<run_results2>]  [RUN<run_results2>]  [RUN<run_results2>]</run_results2></run_results2></run_results2></run_results2></run_results2></run_results2></run_results2></run_results2></run_results2></run_client2>	Summary	1:1 intra-ECU Client-Server communication for an operation which has INOUT			
In this testcase it is checked if the server receives the input value provided by the client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  None  None  Main Test Execution  Test Steps  Pass Criteria  Step 1  [CP]  start RUN_Client2  Step 2  [RUN <run_client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Step 3  [CP]  WAIT 100ms  Run_Results2&gt;]  runnable has been started by AsynchronousServerCallReturnsEvent [RUN<run_results2>]  [RUN<run_results2>]  execute  Rte_Result returns RTE_E_OK, data</run_results2></run_results2></run_client2>		This test involves communication between Te	ester_Client_2 and Tester_Server.		
client and also the server updates the new data value to the client as part of INOUT parameter of the Rte_Result API.  The Test Manager checks that asynchronous server calls for the ReadWrite operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  None  Main Test Execution  Test Steps  Pass Criteria  [CP]  start RUN_Client2  Step 2  [RUN <run_client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Step 3  [CP]  WAIT 100ms  Results2&gt;]  runnable has been started by AsynchronousServerCallReturnsEvent  [RUN<run_results2>]  execute  Rte_Result returns RTE_E_OK, data</run_results2></run_client2>		The Tester_Client_2 SW-C calls the local server for the ReadWrite operation.			
operation succeed (data is written and read correctly) and that an AsynchronousServerCallReturnsEvent is triggered to start a runnable of the client.  Needed Adaptation to other Releases Pre-conditions None  Main Test Execution  Test Steps Pass Criteria  [CP]  start RUN_Client2  [RUN <run_client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Step 3  [CP]  WAIT 100ms  Run<run_results2>]  wait runnable has been started by AsynchronousServerCallReturnsEvent  [RUN<run_results2>]  [RUN<run_results2>]</run_results2></run_results2></run_results2></run_results2></run_results2></run_results2></run_results2></run_results2></run_results2></run_results2></run_results2></run_results2></run_results2></run_client2>		client and also the server updates the new data value to the client as part of INOUT			
Adaptation to other Releases  Pre-conditions None  Main Test Execution  Test Steps Pass Criteria  Step 1 [CP] start RUN_Client2  Step 2 [RUN <run_client2>] set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Step 3 [CP] WAIT 100ms  Test Steps Pass Criteria  Rte_Call returns RTE_E_OK ReadWrite(data)  Rte_Call returns RTE_E_OK ReadWrite(data)  Funnable has been started by AsynchronousServerCallReturnsEvent  Step 4 [RUN<run_results2>] execute Rte_Result returns RTE_E_OK, data</run_results2></run_client2>		operation succeed (data is written and read correctly) and that an			
Pre-conditions       None         Main Test Execution       Pass Criteria         Test Steps       Pass Criteria         Step 1       [CP]       [RUN <run_client2>]         set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)       Rte_Call returns RTE_E_OK         Step 3       [CP]       [RUN<run_results2>]         WAIT 100ms       runnable has been started by AsynchronousServerCallReturnsEvent         Step 4       [RUN<run_results2>]       [RUN<run_results2>]         execute       Rte_Result returns RTE_E_OK, data</run_results2></run_results2></run_results2></run_client2>	Needed Adaptation to	None			
Main Test Execution  Test Steps Pass Criteria  Step 1 [CP]  start RUN_Client2  Step 2 [RUN <run_client2>] [RUN<run_client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Step 3 [CP] [RUN<run_results2>]  WAIT 100ms runnable has been started by AsynchronousServerCallReturnsEvent  Step 4 [RUN<run_results2>] [RUN<run_results2>]  execute Rte_Result returns RTE_E_OK, data</run_results2></run_results2></run_results2></run_client2></run_client2>	other Releases				
Test Steps Step 1  [CP]  start RUN_Client2  Step 2  [RUN <run_client2>]  set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Step 3  [CP]  WAIT 100ms  Rte_Call returns RTE_E_OK  [RUN<run_results2>]  WAIT 100ms  runnable has been started by AsynchronousServerCallReturnsEvent  Step 4  [RUN<run_results2>]  execute  Rte_Result returns RTE_E_OK, data</run_results2></run_results2></run_client2>	Pre-conditions	None			
Step 1 [CP] start RUN_Client2  Step 2 [RUN <run_client2>] [RUN<run_client2>] set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Step 3 [CP] [RUN<run_results2>] WAIT 100ms runnable has been started by AsynchronousServerCallReturnsEvent  Step 4 [RUN<run_results2>] [RUN<run_results2>] execute Rte_Result returns RTE_E_OK, data</run_results2></run_results2></run_results2></run_client2></run_client2>	Main Test Execu	ution			
start RUN_Client2  Step 2	Test Steps		Pass Criteria		
Step 2	Step 1	[CP]			
Step 2		start PLIN Client?			
set data to 0x55 and execute Rte_Call_Client2A_ReadWrite(data)  Step 3 [CP] [RUN <run_results2>]  WAIT 100ms runnable has been started by AsynchronousServerCallReturnsEvent  Step 4 [RUN<run_results2>] [RUN<run_results2>]  execute Rte_Result returns RTE_E_OK</run_results2></run_results2></run_results2>	Stop 2		IDLIN - DLIN Cliont2>1		
execute Rte_Call_Client2A_ReadWrite(data)  Step 3	Step 2				
CP   [RUN <run_results2>]   WAIT 100ms   runnable has been started by AsynchronousServerCallReturnsEvent   Step 4   [RUN<run_results2>]   [RUN<run_results2>]     execute   Rte_Result returns RTE_E_OK, data</run_results2></run_results2></run_results2>		set data to 0x55 and	Rte_Call returns RTE_E_OK		
WAIT 100ms  runnable has been started by AsynchronousServerCallReturnsEvent  [RUN <run_results2>]  [RUN<run_results2>]  execute  Rte_Result returns RTE_E_OK, data</run_results2></run_results2>		execute Rte_Call_Client2A_ReadWrite(data)			
AsynchronousServerCallReturnsEvent  Step 4 [RUN <run_results2>] [RUN<run_results2>]  execute Rte_Result returns RTE_E_OK, data</run_results2></run_results2>	Step 3	[CP]	[RUN <run_results2>]</run_results2>		
Step 4 [RUN <run_results2>] [RUN<run_results2>]  execute Rte_Result returns RTE_E_OK, data</run_results2></run_results2>		WAIT 100ms			
execute Rte_Result returns RTE_E_OK, data	Stop 4	[DIINZDIIN Posults2>1			
	Step 4	[NONSKON_RESUITS2>]	[NOINSKOIN_RESUITSZ>]		





Post-	Maria
Post-	None
conditions	
oonaniono	




# 4 RS\_BRF\_01320 & RS\_BRF\_01328 – Rte SWC scheduling and activation from events

#### 4.1 General Test Objective and Approach


This test suite intends to cover the RTE SWC scheduling and activation from events features. As Acceptance Tests intends to cover ICC1 scope, this test suite has limited scope of tests cases (**not focusing on the underlying OS features**).

The contents of these features are detailed below:



#### 4.1.1 Test System

#### 4.1.1.1 Overview on Architecture



The test system architecture consists of one test bench and a System Under Test.

#### 4.1.1.2 Specific Requirements

none



#### 4.1.2 Test Configuration

This section describes sets of requirements on configuration.

These sets are later referenced by test cases.

No configuration files are provided. They need to be developed when the test suite is implemented.


#### 4.1.2.1 Required ECU Extract of System Description Files

In order to cover the required features, the requirements for configuration have been split in uses cases:

#### 4.1.2.1.1 Use case 02.01: General Events activated runnables

This use case consists in verifying the 3 general events behavior:

Use Case 1 : Runnables activated by General Events



S

No other additional requirement for ECU Extract required.




#### 4.1.2.1.2 Use case 02.02: Runnables activated by Trigger Events

This use case consists in applications which use triggers:

- InternalTriggerOccurredEvent
- ExternalTriggerOccurredEvent
- Queuing of Triggers

Use Case 2 : Runnables activated by TriggerEvents



This test case uses 2 SWC located on SUT.


No external CAN frame defined.

Hint: RteTriggerSourceQueueLength shall be configured >= 2 for the ExternalTrigger

### 4.1.2.1.3 Use case 02.03: Runnables activated by Sender-Receiver related events



Use Case 3: Runnables activated by S/R Events




This use case intends to cover Sender-Receiver related events.

#### 4.1.2.1.4 Use case 02.04: Runnables activated by Client-Server related events



Use Case 4: Runnables activated by C/S Events




This use case intends to cover Client-Server related Events.



#### 4.1.2.1.5 Use case 02.05: Runnables activated by Mode Switch related events

This use case intends to cover the ModeSwitch Activated runnables:




#### This Test case will use:

- ModeDeclarationGroup:
  - MODE\_1 (Init Value)
  - o MODE\_2
  - o MODE\_3
- One SwcModeManager:
  - o Run\_MSAE is activated consecutively to a ModeSwitchedAckEvent
- OneSwcModeUser:
  - Run\_OnEnter\_Mode2 is activated when entering in MODE\_2
  - Run\_OnExit\_Mode2 is activated when exiting MODE\_2
  - Run OnTransition is activated when transition to MODE 2
  - Runnable\_Triggered:
    - Activated by TiminEvent 100ms
    - ModeDisablingDependency when entering in MODE\_3



#### 4.1.2.1.6 Use case 02.06: Runnable activated by Multiple Events



This use case intends to cover runnable activation by multiple events and check the activation reason at each runnable activation.

The Runnable will check the ActivationReason (DRE1, DRE2 or Timing-Event).

To avoid ICC3 parameters:

- Use a SenderRunnable connected to Port1 & Port2
- Sender SWC and Receiver runsInsideExclusiveArea EA1

#### 4.1.2.2 Required ECU Configuration Description Files

There are no generic requirements on ECU Configuration files. Individual test cases may have specific requirements on the RTE configuration.

#### 4.1.2.3 Required Software Component Description Files

Requirements on on Software Component Description files are provided in the section 4.1.2.1 Required ECU Extract of System Description Files, together with the connections of the different components.

#### 4.1.2.4 Mandatory vs. Customizable Parts

Not Applicable

#### 4.1.3 Test Case Design

Not Applicable



### 4.2 Re-usable Test Steps

Not Applicable

#### 4.3 Test Cases

### 4.3.1 [ATS\_RTE\_00116] Test Behavior of runnables activated by "General" Events

Test Objective	Test Behavior of runnables activated by "General" Events		
ID	ATS_RTE_00116	AUTOSAR Releases	4.1.1 4.2.1 4.2.2
Affected Modules	RTE, OS	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00022		
Trace to SWS Item	RTE: SWS_Rte_01126 RTE: SWS_Rte_01130 RTE: SWS_Rte_01131 RTE: SWS_Rte_01132 RTE: SWS_Rte_02202 RTE: SWS_Rte_06728 RTE: SWS_Rte_06748 RTE: SWS_Rte_06761 RTE: SWS_Rte_07177		
Requirements / Reference to Test Environment	Use case 02.01: Runnabl	es activated on gend	eral events
Configuration Parameters	1 Runnable activated by BackgroundEvent (Background Task) 1 Runnable with TimingEvent Runnable (100ms) 1 Runnable with InitEvent  Hint: The test case relies on a background task to be activated. The test environment has to ensure that such task can be activated (ECU is not kept busy for other processes not related to this test case)		
Summary	This test case checks that :  InitEvent Runnable is activated after initialization  TimingEvent is activated every 100ms (timing measurement)  BackgroundEvent runnable is activated when the ECU is not busy (in the background task)		
Needed Adaptation to	Needed Adaptation for Release [4.0.3]		
other Releases	Configuration: [low]	InitEvents are not av	
	Test Steps: [low]	The associated test	steps shall be removed
Pre-conditions	Pre-conditions ECU powered off		
Main Test Execu	ution		



Test Steps		Pass Criteria
Step 1	[CP]	[swc]
	Power On ECU	InitEvent associted runnable has
	WAIT 50ms	been activated after initialization
Step 2	[SWC]	[SWC]
		BackgroundEvent associated runnable has been activated
		(note: future activation can be ignored)
Step 3	[CP]	[SWC]
	WAIT 125ms	TimingEvent associated runnable has been activated.
Step 4	[swc]	
	save TimeStamp1=GetTimeStamp() when TimingEvent associated runnable is activated	
Step 5	[CP]	[swc]
	WAIT 125ms	TimingEvent associated runnable has been activated.
Step 6	[SWC]	[swc]
	save TimeStamp2=GetTimeStamp() when TimeStamp2-TimeStamp1 = TimingEvent associated runnable is activated (+/- 1ms)	
Post- conditions	none	

### 4.3.2 [ATS\_RTE\_00117] Test Runnables activated by Trigger Events

Test Objective	Test Runnables activated by Trigger Events		
ID	ATS_RTE_00117	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE, OS	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00022		
ltem	RTE: SWS_Rte_07087 RTE: SWS_Rte_07090 RTE: SWS_Rte_07207 RTE: SWS_Rte_07208 RTE: SWS_Rte_07212 RTE: SWS_Rte_07213 RTE: SWS_Rte_07543		
Requirements / Reference to Test Environment	Use case 02.02 : Runnables activated by Trigger Event		



Configuration Parameters	1 SWC with 2 runnables : 1 ExternalTrigger Provided Port interface	
	A runnable Run_Emitter which is identified wi	th:
	one InternalTriggeringPoint InternalTrigger	
	one ExternalTriggeringPoint ExternalTrigger A runnable Run_Receiver which is activated b referencing InternalTrigger	by an InternalTriggerOccurredEvent
	1 SWC with 1 runnable, Run_B, activated by 1 ExternalTrigger RequiredPort interface, con 1 ExternalTrigger Provided Port interface with	nected to the first SWC
	Hint: RteTriggerSourceQueueLength shall be ExternalTrigger	configured >= 2 for the
Summary	This test case intends to check the behavior of	of Runnables activated by:
	- ExternalTriggerOccurredEvent	
	- InternalTriggerOccurredEvent	
	This test will also cover the queuing of trigger	S.
Needed Adaptation to other Releases		
Pre-conditions	ECU powered off	
Main Test Execu	ution	
Test Steps		Pass Criteria
Step 1	[CP]	
	Power ON ECU	
Step 2	[CP]	
	Start Run_Emitter	
Step 3	[RUN <run_emitter>]</run_emitter>	[RUN <run_b>]</run_b>
	Call Rte_Trigger() for ExternalTriggerOccurredEvent.	Run_B has been activated
Step 4	[RUN <run_emitter>]</run_emitter>	[RUN <run_receiver>]</run_receiver>
	Trig InternalTrigger by calling Rte_IrTrigger()	Run_Receiver has been activated
Step 5	[RUN <run_emitter>]</run_emitter>	[RUN <run_b>]</run_b>
Post-	Trig twice ExternalTrigger by calling twice Rte_Trigger()	Run_B has been activated twice

## 4.3.3 [ATS\_RTE\_00118] Test Runnables activated from S/R communication

Test Objective	Test Runnables activated from S/R communication



	T		
ID	ATS_RTE_00118	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00022		
Trace to SWS Item	RTE: SWS_Rte_01135 RTE: SWS_Rte_01137 RTE: SWS_Rte_01359		
Requirements / Reference to Test Environment	Use case 02.03 : Runnables activ	vated by S/R	communication
Configuration Parameters	1 runnable Run_Data_ReceiveEr ExternalReceiverPort ExternalReceiverPort dataelemen Hint: It is expected that the systen * Run_DataReceived, Run_Send after their activation (which is trig	verPort ctivated by E ror activated nt mapped to m is configur Ack, Run_W gered from F	VriteCompletedEvent  DataReceivedEvent on ReceiverPort I by DataReceiveErrorEvent on o an incoming BUS signal red such that VriteAck will be executed less than 1ms
Summary	The goal of this test case is to cover the runnable activations following S/R communication.  The following Events are checked:  - DataReceivedEvent Runnable activation - DataWriteCompletedEvent Runnable activation - DataReceiveErrorEvent Runnable activation - DataSendCompletedEvent Runnable activation  The test generates each event kind and then checks if the runnable has been activated		
Needed Adaptation to other Releases			
Pre-conditions	ECU Powered off		
Main Test Execu	ution		
Test Steps			Pass Criteria
Step 1	[CP]		
Step 2	Power ON ECU [CP]		



	Start Run_Sender	
Step 3	[RUN <run_sender>]</run_sender>	[RUN <run_datareceived>]</run_datareceived>
	Send Data on SenderPort interface by calling Rte_Send()	Run_DataReceived has been activated by DataReceivedEvent
	WAIT 1ms	
Step 4		[RUN <run_sendack>]</run_sendack>
		Run_SendAck has been activated by DataSendCompletedEvent
Step 5	[CP]	
	WAIT 1ms	
Step 6	[RUN <run_sender>]</run_sender>	[RUN <run_writeack>]</run_writeack>
	Write data on WritePort interface (Rte_IWrite())	Run_WriteAck has been activated by DataWriteCompletedEvent
	WAIT 1ms	
Step 7	[CP]	
	WAIT 1ms	
Step 8	[LT]	
	Send Data on Bus corresponding to dataElement in ExtSenderPort with invalid value	
Step 9	[CP]	[RUN <run_receiveerror>]</run_receiveerror>
	WAIT 100ms	Run_ReceiveError has been activated by DataReceiveErrorEvent
Post- conditions	none	

## 4.3.4 [ATS\_RTE\_00119] Test Runnables activated from C/S communication

Test Objective	Test Runnables activated from C/S communication		
ID		AUTOSAR Releases	3.2.1 3.2.2 4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00022		
Trace to SWS Item			
Requirements / Reference to Test Environment	Use case 02.04: Runnables activ	ated by C/S	



Configuration Parameters	1 SWC Client 1 runnable Run_Client with 2 SynchronousSe operation2) and one AsynchronousServerCal 1 runnable Run_AsyncClient activated by an 1 SWC Server 1 runnable Run_Sync with attribute CanBelov	llPoint (operation3) AsynchronousServerCallReturnsEvent
	activated by OperationInvokedEvent (operation 1 runnable Run_direct with attribute CanBeIn activated by an OperationInvokedEvent (oper 1 runnable run_asyncServer activated by OperationInvokedEvent (oper 1 runnable run_asyncServer activated by OperationInvokedEvent (oper 1 runnable run_asyncServer activated by OperationInvokedEvent (operationInvokedEvent (operationI	vokedConcurrently set to TRUE ration2)
Summary	The following activations will be tested:	
	<ul> <li>1 Server Runnable with canBelnvokedConc OperationInvokedEvent triggered by a synchr</li> <li>1 Server Runnable with canBelnvokedConc OperationInvokedEvent triggered by a synchr</li> <li>1 Server Runnable activated by an Operationasynchronous client</li> <li>1 Runnable activated by AsynchronousServ</li> <li>The test will activate each event and check if consecutively.</li> </ul>	ronous client currently=TRUE activated by an ronous client onInvokedEvent triggered by an rerCallReturnsEvent
Needed Adaptation to other Releases		
Pre-conditions	ECU Powered off	
Main Test Exec	ution	
Test Steps		Pass Criteria
Step 1	[CP] Power ON ECU	
Step 2	[CP]	
Otop 2	Start RUN_Client	
Step 3	[RUN <run_client>]</run_client>	
Cton 4	Call operation operation1()	TRUM Pour come 1
Step 4	[CP]	[RUN <run_sync>]</run_sync>
	WAIT 1ms	Run_Sync has been activated by the OperationInvokedEvent
Step 5	[RUN <run_client>]</run_client>	[RUN <run_direct>]</run_direct>
	Call operation operation2()	Run_direct has been immediately activated
Step 6	[RUN <run_client>]</run_client>	
	Call operation operation3()	
Step 7	[CP]	[RUN <run_asyncserver>]</run_asyncserver>
	WAIT 1ms	Run_asyncServer has been activated by OperationInvokedEvent



Step 8	[RUN <run_asyncclient>]</run_asyncclient>
	Run_AsyncClient has been activated by AsynchronousServerCallReturnsEvent
Post- conditions	none

### 4.3.5 [ATS\_RTE\_00121] Test Runnable activated by Mode Switchs

Test Objective	Test Runnable activated by Mode	Switchs	
ID	ATS_RTE_00121	AUTOSAR Releases	4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00022		
Trace to SWS Item	RTE: SWS_Rte_02512 RTE: SWS_Rte_02758 RTE: SWS_Rte_06771		
Requirements / Reference to Test Environment	Use Case 02.05 : Mode Switch related events		
Parameters	A mode switch interface {MODE_1, MODE_2, MODE_3} with initial mode = MODE_1  An atomic software component with a required port prototype typed by this nterface.  A runnable activated on mode transition 'SwcModeSwitchEvent' (on transition from MODE_1 to MODE_2),  A runnable activated on mode transition 'SwcModeSwitchEvent' (on enter in MODE_2),  A runnable activated on mode transition 'SwcModeSwitchEvent' (on exit MODE_2),  A runnable triggered on TimingEvent but disabled in MODE_3 with a ModeDisablingDependency  An atomic software component with a provider port prototype typed by this nterface.  A runnable activated on ModeSwitchedAckEvent  A runnable activated on SwcModeManagerErrorEvent		
Summary	The goal of this test case is to check the correct activation of runnables after the following events:  - SwcModeManagerErrorEvent - SwcModeSwitchEvent - ModeSwitchedAckEvent - ModeDisablindDependency  A SWC will request a Mode Change through a ModeSwitch interface, then the Mode Manager will generate a SwcModeSwitchEvent. Check the activation of the runnables by the SwcModeSwitchEvent and the ModeSwitchedAckEvent.		



	Then restart the operation, generate a SwcModeManagerErrorEvent and check activation of the runnable.		
	Hint: to check the activation of a runnable, the runnable can wrap a counter increased at each activation and publised through a sender/receiver interface.		
Needed Adaptation to	Needed Adaptation for Release [4.0.3]		
other Releases	Configuration: [Low] ModeManagerError	Event is not available.	
	Test Steps: [Low] The associated test	steps shall be removed	
Pre-conditions	ECU Powered off		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[CP]		
	Power ON ECU		
Step 2	[SWC]  Call ModeSwitch interface to request mode switch to MODE_2	[SWC] Runnable activated on transition from MODE_1 to MODE_2 has been called Runnable activated on entering MODE_2 has been called Runnable activated on ModeSwitchedAckEvent has been called	
Step 3	[swc]	[SWC]	
	Call ModeSwitch interfacte to request mode change to MODE_3	Runnable activated on exiting MODE_2 has been called	
Step 4	[CP]	[swc]	
	Wait 10 times the period of the TimingEvent	The runnable activated on TimingEvent has not been called during that time	
Step 5	[CP]	[SWC]	
	Call ModeSwitch Interface with an UnknownMode (not MODE_1, MODE_2 or MODE_3 values)	Runnable activated on SwcModeManagerErrorEvent has been called	
Post- conditions	none		

### 4.3.6 [ATS\_RTE\_00132] Test Runnable activated by Multiple Events

Test Objective	Test Runnable activated by Multip	ole Events	
ID		AUTOSAR Releases	4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed



	T		
Trace to	ATR: ATR_ATR_00022		
Requirement			
on Acceptance Test Document			
Trace to SWS	RTE: SWS_Rte_01126		
Item	RTE: SWS_Rte_03520		
	RTE: SWS_Rte_03524		
	RTE: SWS_Rte_08051		
	RTE: SWS_Rte_08054		
	RTE: SWS_Rte_08055		
	RTE: SWS_Rte_08060		
	Use Case 02.06: Runnab	le activated by Multip	ole Events
Reference to Test			
Environment			
Configuration	1 runnable in a SWC sen	dor	
Parameters			ndPoints on 2 different Ports.
			veArea (EA1) as receiverRunnable
	-> 1 dataSendPoint to po		,
	-> 1 dataSendPoint to po	rt SenderPort2	
	4	- (-   -	
	1 receiverRunnable activation	ated with by 2 DataR	eceivedEvents (DRE1, DRE2) and a
	Firming⊑vent (100ms)		
	The receiverRunnable ru	nsInsideExclusiveAre	ea EA1
	The receiverRunnable en		
			d to the 3 different events
	DRE1 occurs when receind DRE2 occurs when receind the contract of the contract		
Summary			of Runnable activation by multiple
Summary	events.	test the KTE leature	of Kurinable activation by multiple
		will be activated by	both a TimingEvent and a
	DataReceivedEvent	,	3
	The test Manager will sta		
			cally at the period configured in
	TimingEvent (100ms).The	en, Send data from 1	est Framework.
	The Test manager will se	lloot at apply took pat	ivation the ActivationReason (DRE1,
	DRE2 or TimingEvent)	medi ai eadii lask adi	ivation the Activationiceason (DICL),
Needed	Needed Adaptation for	Release [4 0 3]	
Adaptation to	rtoodod /tdaptation for	1101010	
other Releases	Configuration: [low]		
	Coringulation [1011]		on feature is new in R4.1.1, this part
	Test Steps: [low]	of test shall be remo	ved to be compatible with R4.0.3.
		IL.	
Pre-conditions	ECU Powered off		
Main Test Execu			
Test Steps			Pass Criteria
Step 1	[CP]		
	Power ON ECU		
Step 2	[CP]		[RUN <receiverrunnable>]</receiverrunnable>
			_



		receiverRunnable has been activated and Rte_ActivatingEvent corresponds to TimingEvent
Step 3	[CP]	[RUN <receiverrunnable>]</receiverrunnable>
	WAIT 100ms	receiverRunnable has been activated and Rte_ActivatingEvent corresponds to TimingEvent
Step 4	[RUN <senderrunnable>]</senderrunnable>	[RUN <receiverrunnable>]</receiverrunnable>
	Send Data on SenderPort1 (Rte_Send() API).	receiverRunnable has been activated and Rte_ActivatingEvent corresponds to DRE1
Step 5	[RUN <senderrunnable>]</senderrunnable>	[RUN <receiverrunnable>]</receiverrunnable>
	Sand Data on Sandar Part 2 (Pta. Sand () API)	receiverRunnable has been activated
	l	and Rte_ActivatingEvent corresponds to DRE2
Step 6	l	and Rte_ActivatingEvent corresponds
Step 6	[RUN <senderrunnable>]</senderrunnable>	and Rte_ActivatingEvent corresponds to DRE2  [RUN <receiverrunnable>]  receiverRunnable has been activated and Rte_ActivatingEvent corresponds</receiverrunnable>

## 4.3.7 [ATS\_RTE\_00694] Waking Up A Runnable From WaitPoint On Occurrence Of ModeSwitchedAckEvent

Test Objective	Waking Up A Runnable From WaitPoint On Occurrence Of ModeSwitchedAckEvent		
-	ATS_RTE_00694	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on			
Acceptance Test			
	RTE: SWS_Rte_02628		
	RTE: SWS_Rte_02629 RTE: SWS_Rte_02631 RTE: SWS_Rte_02632		
	RTE: SWS_Rte_02660 RTE: SWS_Rte_02667 RTE: SWS_Rte_02674		
	RTE: SWS_Rte_02676 RTE: SWS_Rte_02725 RTE: SWS_Rte_02729		
Requirements / Reference			



to Test Environment			
Configuration Parameters	A ModeDeclarationGroup MDG_TC69 with  * 2 ModeDeclarations: InitMode=0 StartMode=1  * initialMode=InitMode  A SW-C with  * A PPortPrototype which - is typed with a ModeSwitchInterface with a ModeDeclarationGroupPrototype with type=MDG_TC69 - has a ModeSwitchSenderComSpec with a ModeSwitchedAckRequest  * An RPortPrototype which - is typed by the same ModeSwitchInterface - is connected with the previous PPortPrototype  * RunnableEntity_TC69 to execute the test sequence - with a modeSwitchPoint which references the ModeDeclarationGroupPrototype of		
	the PPortPrototype - with a modeAccessPoint which references the ModeDeclarationGroupPrototype of the RPortPrototype - with a waitPoint which references a ModeSwitchedAckEvent that in turn references the ModeDeclarationGroupPrototype of the PPortPrototype		
Summary	This test case verifies that whenever ModeSwitchedAckEvent occurs the RTE shall wake up a runnable from WaitPoint (blocking Rte_SwitchAck API).		
Needed Adaptation to other Releases			
	DUT shall be initialized EcuM module shall be in RUN state		
	Main Test Execution		
Test Steps		Pass Criteria	
	[RUN <runnableentity_tc69>] Invoke Rte_Mode.</runnableentity_tc69>	[RUN <runnableentity_tc69>] Rte_Mode returns RTE_MODE_MDG_69_InitMode.</runnableentity_tc69>	
	[RUN <runnableentity_tc69>] Invoke Rte_Switch(RTE_MODE_MDG_TC69_StartMode).</runnableentity_tc69>	[RUN <runnableentity_tc69>] Rte_Switch returns RTE_E_OK.</runnableentity_tc69>	
Step 3	[RUN <runnableentity_tc69>] Invoke Rte_SwitchAck.</runnableentity_tc69>	[RUN <runnableentity_tc69>] Rte_SwitchAck returns RTE_E_TRANSMIT_ACK.</runnableentity_tc69>	
Post- conditions	NONE		

### 4.3.8 [ATS\_RTE\_00707] MinimumStartInterval For A Runnable Entity

Test Objective	MinimumStartInterval For A Runnable Entity		
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			



Trace to SWS	RTE: SWS_Rte_02697		
Item			
Requirements / Reference			
to Test			
Environment Configuration	SW-C		
Parameters	* PPortPrototype - VariableDataPrototype_TC103_0, primitive data type, swImplPolicy standard * PPortPrototype - VariableDataPrototype_TC103_1, primitive data type, swImplPolicy standard * RunnableEntity_T103_0 - dataWriteAccess referencing VariableDataPrototype_TC103_0		
	<ul> <li>started by TimingEvent (period=100ms)</li> <li>minimumStartInterval=50ms</li> <li>RunnableEntity_T103_1</li> <li>dataWriteAccess referencing VariableDataF</li> <li>started by a TimingEvent (period=100ms)</li> <li>minimumStartInterval=150ms</li> </ul>	Prototype_TC103_1	
	Communication matrix * Signal_TC103_0 - mapped to VariableDataPrototype_TC103_0 - transmitted by the ECU * ISignalIPdu_TC103_0 - configured with an EventControlledTiming - Signal_TC103_0 mapped to ISignalIPdu_TC103_0, transferProperty triggered		
	* Signal_TC103_1 - mapped to VariableDataPrototype_TC103_1 - transmitted by the ECU * ISignalIPdu_TC103_1 - configured with an EventControlledTiming - Signal_TC103_1 mapped to ISignalIPdu_TC103_1, with transferProp		
Summary	In the below test case a runnable entity RunnableEntity_TC103_0 is configured with minimum start interval as 50ms and RunnableEntity_TC103_1 with a minimum start interval of 150ms.  The 3 RunnableEntities are mapped to the same periodic task.  The RunnableEntities send different dataElements which trigger the transmission of different frames used to monitor the periodicity of each RunnableEntity.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu			
Test Steps	l	Pass Criteria	
Step 1	[LT] Observe time between consecutive frames for ISignallPdu_TC103_0.	[LT] The time between consecutive frames for ISignallPdu_TC103_0 is lower than 150ms.	
Step 2	[LT] Observe time between consecutive frames for ISignallPdu_TC103_1.	[LT] The time between consecutive frames for ISignallPdu_TC103_1 is between 150ms and 250ms.	
Post- conditions	NONE		



### 5 RS BRF 01376 - Rte Data Conversion

### 5.1 General Test Objective and Approach

This document intends to cover the RTE Data Conversion feature (AUTOSAR Feature [RS\_BRF\_01376]).

The sub-features to cover are described below:


- → DataTypes : RTE calculates numerical representation
- → Port InterfaceElement Mapping and Data Conversion:
  - Port Interface Element Mapping:
    - Client-Server Interface Elements
    - Sender-Receiver Interface Elements
  - o Data Conversions:
    - Linear Data Scaling
    - TextTable to TextTable
    - Mixed Linear scaled and TextTable to Mixed Linear scale and TextTable
    - Identical Conversion
    - Composite Representations
  - Network Representations
  - o Range Checks During Runtime

These features intend to automatically convert by generated RTE a type 1 to a type 2.

#### 5.1.1 Test System

#### 5.1.1.1 Overview on Architecture

#### 5.1.1.1.1 Use Case 03.01: Intra-ECU Data conversion for C/S interfaces




The test system architecture consists of 2 SWCs on the SUT:



- One SwC Tester\_Client
- One SwC Tester\_Server

Because the intention of these tests cases is to validate types, the used types and computation methods will be described in each test case.

#### 5.1.1.1.2 Use Case 03.02: Intra-ECU Data conversion for S/R interfaces



The test system architecture consists of 2 SWCs on the SUT:

- One SwC Sender
- One SwC Receiver

Because the intention of these tests cases is to validate types, the used types and computation methods will be described in each test case.


The intention of each test case will be to cover the automatic rescaling at port feature (TextTable to TextTable, Linear scale, ...).

#### 5.1.1.1.3 Use Case 03.03: Inter-ECU Network Representations

Use Case 3.1: Sender on SUT




Use case 3.1: inter-ECU Network Representations on S/R Interface



Use case 3.2: Sender on Test Bench

Use case 3.2: inter-ECU Network Representations on S/R Interface



The test system architecture consists of 2 SWCs:

- One SwC Sender
- One SwC Receiver

On Use case 3.1, the Sender is located on SUT.



On Use case 3.2, the Sender is located on TestBench

#### 5.1.1.2 Specific Requirements

None

#### 5.1.2 Test Configuration

This section describes sets of requirements on configuration.

These sets are later referenced by test cases.

No configuration files are provided. They need to be developed when the test suite is implemented.

#### 5.1.2.1 Required ECU Extract of System Description Files

The required ECU Extract files depend on the use case:

#### 5.1.2.1.1 Use case 03.01: intra-ECU C/S data conversion

Use Case 1 : Intra-ECU Communication C/S



Tests cases will use the following types, computation methods and port interface mapping:

	ClientType/CompuMethod	ServerType/CompuMeth	PortArgumentMappin
test case	application data type	od	g
ATS_RTE_0015			
0	km.h-1	m.s-1	
			0300 -> 0300
			SensorError ->
	0300 km.h-1	0300 km.h-1	UnknownSpeedValue
ATS_RTE_0016	350 -> SensorError	400 ->	SignalNotAvailable ->
0	351 -> SignalNotAvailable	UnknownSpeedValue	UnknownSpeedValue
	LowerLimit : 0	LowerLimit :200	
	UpperLimit : 100	UpperLimit : 1200	
ATS_RTE_0014	Unit m.s-1	Unit m.s-1	
5	IntoPhy : identical	PhyToInt = 10*Phy + 200	



	WheelSpeed4		
	Left_front : uint16;	WheelSpeed2	WheelSpeed4.left_fron
	Left_rear:uint16;	{	t -> WheelSpeed2.left
	Right_front : uint16;	Left: uint16;	WheelSpeed4.right_fro
ATS_RTE_0015	Right_Rear: uint16;	Right : uint16;	nt ->
4	}	}	WheelSpeed2.right
			SenderArray[0] ->
			ReceiverArray[4]
			SenderArray[1] ->
			ReceiverArray[5]
			SenderArray[2] ->
			ReceiverArray[6]
ATS_RTE_0015			SenderArray[3] ->
8	SenderArray [4] of uint8	ReceiverArray [8] of uint8	ReceiverArray[7]
	Enum:		TextTableMapping:
	CLIENTO,	Enum:	CLIENTO -> SERVERO
	CLIENT1,	SERVERO,	CLIENT1 -> SERVER2
ATS_RTE_0014	CLIENT2,	SERVER1,	CLIENT2 -> SERVER1
9	CLIENT3	SERVER2	CLIENT3 -> SERVER2

#### 5.1.2.1.2 Use case 03.02: intra-ECU S/R data conversion

Use Case 2 : Intra-ECU Communication S/R



Tests cases will use the following types, computation methods and port interface mapping:

	SenderType/CompuMethod	ReceiverType/CompuMet	
test case	application data type	hod	DataElementMapping
ATS_RTE_			
00146	km.h-1	m.s-1	



			0300 -> 0300
			SensorError ->
	0300 km.h-1	0300 km.h-1	UnknownSpeedValue
ATS RTE	350 -> SensorError	400 ->	SignalNotAvailable ->
00160	351 -> SignalNotAvailable	UnknownSpeedValue	UnknownSpeedValue
00100	331 / Signalitor (Vallable	ommownspeed value	O TIKITO WITS PECCA VALUE
	LowerLimit : 0	LowerLimit :200	
	UpperLimit : 100	UpperLimit : 1200	
ATS_RTE_	Unit m.s-1	Unit m.s-1	
00161	IntoPhy : identical	PhyToInt = 10*Phy + 200	
	WheelSpeed4		
	{		WheelSpeed4.left_fro
	Left_front : uint16;	WheelSpeed2	nt ->
	Left_rear:uint16;	<b>{</b>	WheelSpeed2.left
	Right_front : uint16;	Left: uint16;	WheelSpeed4.right_fr
ATS_RTE_	Right_Rear: uint16;	Right : uint16;	ont ->
00162	}	}	WheelSpeed2.right
			SenderArray[0] ->
			ReceiverArray[4]
			SenderArray[1] ->
			ReceiverArray[5]
			SenderArray[2] ->
			ReceiverArray[6]
ATS_RTE_			SenderArray[3] ->
00163	SenderArray [4] of uint8	ReceiverArray [8] of uint8	ReceiverArray[7]
			TextTableMapping:
			SenderValue0 ->
			ReceiverValue0
			SenderValue1 ->
			ReceiverValue2
	Enum:	Enum:	SenderValue2 ->
	SenderValue0, SenderValue1,	ReceiverValue0,	ReceiverValue1
ATS_RTE_	SenderValue2,	ReceiverValue1,	SenderValue3 ->
00164	SenderValue3	ReceiverValue2	ReceiverValue2

Each test case will ensure that the conversion have been done properly inside the generated RTE.

There are no specific requirements for these tests cases regarding the runnables and events.



#### 5.1.2.1.3 Use case 03.03: Inter-ECU Network Representations

Tests cases will use the following types, computation methods and port interface mapping:

test case	Sender Type /compuMethod	Network Representation
ATS_RTE_	T_VoltageAtSender uint16	
00165/AT	FixPoint Representation with	T_VoltageOnNetwork uint8
S_RTE_00	Offset: 0	FixPoint Representation with
166	LSB = $2^{-2}$	Offset = 0.5 and LSB = 2 <sup>-1</sup>

test case	Receiver Type /compuMethod	Network Representation
ATS_RTE_	T_VoltageAtReceiver uint16	
00167/AT	FixPoint Representation with	T_VoltageOnNetwork uint8
S_RTE_00	Offset: 2	FixPoint Representation with
168	LSB = $2^{-3}$	Offset = 0.5 and LSB = 2 <sup>-1</sup>

#### 5.1.2.1.4 Use case 03.04: Intra-ECU Range Checks


The Use case 4 intends to cover the range checks intra-ECU.

This use case will reuse the SWC requirements described for Use Case 2.



### 5.1.2.1.5 Use case 03.05: Inter-ECU Range Checks


Use case 5.1: inter-ECU Range Checks Receiver on SUT



test case	Sender Type	Signals
		1 ISignal uint16
ATS_RTE_		INVALID_VALUE = 0xFFFF
00170	uint16	HandleOutOfRange = Invalid



### Use case 5.2: inter-ECU Range Checks Sender on SUT



test case	Receiver Type	Signals
		1   Signal uint16
ATS_RTE_		INVALID_VALUE = 0xFFFF
00176	uint16	HandleOutOfRange = Invalid

#### 5.1.2.2 Required ECU Configuration Description Files

No specific configuration requirements for ECU Configuration files as they can be derived from EcuExtract.

#### **5.1.2.3 Required Software Component Description Files**

Requirements on on Software Component Description files are provided in the section 5.1.2.1 Required ECU Extract of System Description Files, together with the connections of the different components.

#### 5.1.2.4 Mandatory vs. Customizable Parts

Not Applicable.

#### 5.1.3 Test Case Design

Not Applicable.

### 5.2 Re-usable Test Steps

Not Applicable.



### 5.3 Test Cases

# 5.3.1 [ATS\_RTE\_00145] Test Intra-ECU C/S argument rescaling - ClientServerInterfaceMapping Linear Scaling

Test Objective	Test Intra-ECU C/S argument rescaling - ClientServerInterfaceMapping Linear		
	Scaling	====	1,001,4,41,001
ID	ATS_RTE_00145	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00028		
Trace to SWS Item	RTE: SWS_Rte_03818 RTE: SWS_Rte_03819 RTE: SWS_Rte_03829		
Requirements / Reference to Test Environment	Use Case 03.01 : Intra-ECU C/S	Communica	tion
Configuration Parameters	1 SWC Client The Operation uses parameter with ClientType LowerLimit = 0, UpperLimit = 100 ComputationMethod : PhytoInt : identical 1 SWC Server The Operation uses parameter with ServerType LowerLimit = 200, UpperLimit = 1200 Computation Method: PhyToInt : Linear (10*x+200) Both are using uint32 types 1 ClientServerInterfaceMapping maps the client to the server		
Summary	The Test Manager starts the Client, which calls the server The Test Manager checks that server was invoked with the converted values.		
Needed Adaptation to other Releases			
Pre-conditions	None		
Main Test Execu	ution		
Test Steps			Pass Criteria
Step 1	[CP] start Tester_Client_1		
Step 2	[SWC <tester_client_1>]</tester_client_1>		[SWC <tester_server>]</tester_server>
	invoke the operation (Rte_call) wi	ith	server has been invoked with converted argument value 200
Step 3	[SWC <tester_client_1>] invoke the operation (Rte_call) wi argument value 100</tester_client_1>	ith	[SWC <tester_server>] server has been invoked with converted argument value 1200</tester_server>
Step 5	[CP]		
	terminate Tester_Client_1		



Post-	None
conditions	

# 5.3.2 [ATS\_RTE\_00146] Test Intra-ECU S/R dataelements rescaling - Linear Scaling different units

Task Obits of	Task listes FOLLO/D Jacobs (		Lineau Carlina different de la
	Test Intra-ECU S/R dataelements		
ID	ATS_RTE_00146	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00028		
Trace to SWS Item	RTE: SWS_Rte_03829 RTE: SWS_Rte_03832		
Requirements / Reference to Test Environment	Use Case 03.02 : Intra-ECU Com	munication (	Units conversion
Configuration Parameters	1 SWC Sender 1 Port interface with DataElement uint32 type unit km.h-1 1 SWC Receiver 1 Port interface with DataElement uint32 type unit m.s-1		
Summary	For different values, the Test Manager starts the sender, which sends a data in km.h^-1. Then the Test Manager starts the receiver and checks that it received with the converted value.		
Needed Adaptation to other Releases			
Pre-conditions	None		
Main Test Execu	ution		
Test Steps			Pass Criteria
Step 1	[CP]		
Stop 2	start SWC_Sender		
Step 2	[SWC <swc_sender>] send data value 0 (km.h-1)</swc_sender>		
Step 3	[CP] start SWC_Receiver		[SWC <swc_receiver>] data value 0 (m.s-1) has been</swc_receiver>
			received
Step 4	[SWC <swc_sender>]</swc_sender>		
	send data value 1 (km.h-1)		<u> </u>
Step 5	[CP]		[SWC <swc_receiver>]</swc_receiver>
	start SWC_Receiver		



		data value 0 (m.s-1) has been received
Step 6	[SWC <swc_sender>]</swc_sender>	
	send data value 10 (km.h-1)	
Step 7	[CP]	[SWC <swc_receiver>]</swc_receiver>
	start SWC_Receiver	data value 3 (m.s-1) has been received
Step 8	[SWC <swc_sender>]</swc_sender>	
	send data value 100 (km.h-1)	
Step 9	[CP]	[SWC <swc_receiver>]</swc_receiver>
	start SWC_Receiver	data value 28 (m.s-1) has been received
Step 10	[SWC <swc_sender>]</swc_sender>	
	send data value 200 (km.h-1)	
Step 11	[CP]	[SWC <swc_receiver>]</swc_receiver>
	start SWC_Receiver	data value 56 (m.s-1) has been received
Step 12	[SWC <swc_sender>]</swc_sender>	
	send data value 300 (km.h-1)	
Step 13	[CP]	[SWC <swc_receiver>]</swc_receiver>
	start SWC_Receiver	data value 83 (m.s-1) has been received
Post- conditions	None	

# 5.3.3 [ATS\_RTE\_00149] Test Intra-ECU C/S argument rescaling - ClientServerInterfaceMapping Texttable to Texttable

Test Objective	Test Intra-ECU C/S argument rescaling - ClientServerInterfaceMapping Texttable to Texttable		
ID		AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00028		
	RTE: SWS_Rte_03818 RTE: SWS_Rte_03830		
Requirements / Reference to Test Environment	Use case 03.01: C/S Communication		



	1		
Configuration Parameters	1 SWC Client with ENUM parameter:		
rarameters	enum {CLIENT0,CLIENT1,CLIENT2, CLIENT3}		
	1 SWC Server with ENUM parameter		
	enum {SERVER2, SERVER1, SERVER0}		
	TextTableMapping: CLIENT0 -> SERVER0 CLIENT1 -> SERVER2 CLIENT2 -> SERVER1 CLIENT3 -> SERVER2		
Summary	The Test Manager starts the Client, which invokes a server operation with CLIENT0, then CLIENT1, then CLIENT2, then CLIENT3 values. The Test Manager checks that server has received the converted argument value on the following sequence: SERVER0, SERVER2, SERVER1, SERVER2		
Needed Adaptation to other Releases			
Pre-conditions	None		
Main Test Exec	ution		
Test Steps		Pass Criteria	
root otopo		i doo oritoria	
Step 1	[CP]	- acc criteria	
Step 1	start SWC_Client		
-		[SWC <swc_server>]</swc_server>	
Step 1	start SWC_Client		
Step 1	start SWC_Client  [SWC <swc_client>]  invoke operation (Rte_call) with argument</swc_client>	[SWC <swc_server>] server has been invoked with</swc_server>	
Step 1 Step 2	start SWC_Client  [SWC <swc_client>]  invoke operation (Rte_call) with argument value CLIENT0  [SWC<swc_client>]  invoke operation (Rte_call) with argument</swc_client></swc_client>	[SWC <swc_server>] server has been invoked with argument value SERVER0 [SWC<swc_server>] server has been invoked with</swc_server></swc_server>	
Step 1 Step 2	start SWC_Client  [SWC <swc_client>]  invoke operation (Rte_call) with argument value CLIENT0  [SWC<swc_client>]</swc_client></swc_client>	[SWC <swc_server>] server has been invoked with argument value SERVER0 [SWC<swc_server>]</swc_server></swc_server>	
Step 1 Step 2 Step 3	start SWC_Client  [SWC <swc_client>]  invoke operation (Rte_call) with argument value CLIENT0  [SWC<swc_client>]  invoke operation (Rte_call) with argument value CLIENT1</swc_client></swc_client>	[SWC <swc_server>] server has been invoked with argument value SERVER0 [SWC<swc_server>] server has been invoked with argument value SERVER2</swc_server></swc_server>	
Step 1 Step 2 Step 3	start SWC_Client  [SWC <swc_client>]  invoke operation (Rte_call) with argument value CLIENT0  [SWC<swc_client>]  invoke operation (Rte_call) with argument value CLIENT1  [SWC<swc_client>]  invoke operation (Rte_call) with argument value CLIENT1</swc_client></swc_client></swc_client>	[SWC <swc_server>] server has been invoked with argument value SERVER0 [SWC<swc_server>] server has been invoked with argument value SERVER2 [SWC<swc_server>] server has been invoked with</swc_server></swc_server></swc_server>	
Step 1 Step 2 Step 3 Step 4	start SWC_Client  [SWC <swc_client>]  invoke operation (Rte_call) with argument value CLIENT0  [SWC<swc_client>]  invoke operation (Rte_call) with argument value CLIENT1  [SWC<swc_client>]  invoke operation (Rte_call) with argument value CLIENT1</swc_client></swc_client></swc_client>	[SWC <swc_server>] server has been invoked with argument value SERVER0 [SWC<swc_server>] server has been invoked with argument value SERVER2 [SWC<swc_server>] server has been invoked with argument value SERVER1</swc_server></swc_server></swc_server>	
Step 1 Step 2 Step 3 Step 4	start SWC_Client  [SWC <swc_client>]  invoke operation (Rte_call) with argument value CLIENT0  [SWC<swc_client>]  invoke operation (Rte_call) with argument value CLIENT1  [SWC<swc_client>]  invoke operation (Rte_call) with argument value CLIENT2  [SWC<swc_client>]  invoke operation (Rte_call) with argument value CLIENT2</swc_client></swc_client></swc_client></swc_client>	[SWC <swc_server>] server has been invoked with argument value SERVER0 [SWC<swc_server>] server has been invoked with argument value SERVER2 [SWC<swc_server>] server has been invoked with argument value SERVER1 [SWC<swc_server>] server has been invoked with argument value SERVER1 [SWC<swc_server>] server has been invoked with</swc_server></swc_server></swc_server></swc_server></swc_server>	
Step 1 Step 2 Step 3 Step 4	start SWC_Client  [SWC <swc_client>]  invoke operation (Rte_call) with argument value CLIENT0  [SWC<swc_client>]  invoke operation (Rte_call) with argument value CLIENT1  [SWC<swc_client>]  invoke operation (Rte_call) with argument value CLIENT2  [SWC<swc_client>]  invoke operation (Rte_call) with argument value CLIENT2  [swc<swc_client>]  invoke operation (Rte_call) with argument value CLIENT3</swc_client></swc_client></swc_client></swc_client></swc_client>	[SWC <swc_server>] server has been invoked with argument value SERVER0 [SWC<swc_server>] server has been invoked with argument value SERVER2 [SWC<swc_server>] server has been invoked with argument value SERVER1 [SWC<swc_server>] server has been invoked with argument value SERVER1 [SWC<swc_server>] server has been invoked with</swc_server></swc_server></swc_server></swc_server></swc_server>	
Step 1 Step 2 Step 3 Step 4	start SWC_Client  [SWC <swc_client>]  invoke operation (Rte_call) with argument value CLIENT0  [SWC<swc_client>]  invoke operation (Rte_call) with argument value CLIENT1  [SWC<swc_client>]  invoke operation (Rte_call) with argument value CLIENT2  [SWC<swc_client>]  invoke operation (Rte_call) with argument value CLIENT2  [SWC<swc_client>]  invoke operation (Rte_call) with argument value CLIENT3  [CP]</swc_client></swc_client></swc_client></swc_client></swc_client>	[SWC <swc_server>] server has been invoked with argument value SERVER0 [SWC<swc_server>] server has been invoked with argument value SERVER2 [SWC<swc_server>] server has been invoked with argument value SERVER1 [SWC<swc_server>] server has been invoked with argument value SERVER1 [SWC<swc_server>] server has been invoked with</swc_server></swc_server></swc_server></swc_server></swc_server>	



# 5.3.4 [ATS\_RTE\_00150] Test Intra-ECU C/S argument rescaling - ClientServerInterfaceMapping Linear Scaling different units

	L		
Test Objective	Test Intra-ECU C/S argument reso	caling - Clie	ntServerInterfaceMapping Linear
	Scaling different units	ALITO SAS	1.0014.4.44.0.44.5.5
ID		AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00028		
Trace to SWS Item	RTE: SWS_Rte_03818 RTE: SWS_Rte_03829		
Requirements / Reference to Test Environment	Use case 03.01 : C/S		
Configuration Parameters	1 Client using parameter in m.s-1	unit (SI)	
	1 Server using km.h-1 unit (with associated CompuMethod defined in arxml for m.s- 1 to km.h-1 conversion)		
Summary	The Client calls the operation usir	ng paramete	er in m.s-1 unit (SI)
	The test shall validate that the conversion is perfectly handled in the RTE generated code: the server is invoked using parameter in km.h-1 unit		
Needed Adaptation to other Releases			
Pre-conditions	None		
Main Test Execu	ution		
Test Steps			Pass Criteria
Step 1	[CP]		
	start SWC_Client		
Step 2	[SWC <swc_client>]</swc_client>		[SWC <swc_server>]</swc_server>
	invoke operation (Rte_Call) with a value 0 (m.s-1)	rgument	server has been invoked with argument value 0 (km.h-1)
Step 3	[SWC <swc_client>]</swc_client>		[SWC <swc_server>]</swc_server>
	invoke operation (Rte_Call) with a value 1 (m.s-1)	rgument	server has been invoked with argument value 4 (km.h-1)
Step 4	[SWC <swc_client>]</swc_client>		[SWC <swc_server>]</swc_server>
	invoke operation (Rte_Call) with a value 10 (m.s-1)	rgument	server has been invoked with argument value 36 (km.h-1)
Step 5	[SWC <swc_client>]</swc_client>		[SWC <swc_server>]</swc_server>
	invoke operation (Rte_Call) with a value 30 (m.s-1)	rgument	server has been invoked with argument value 108 (km.h-1)



Step 6	[SWC <swc_client>]</swc_client>	[SWC <swc_server>]</swc_server>
	invoke operation (Rte_Call) with argument value 60 (m.s-1)	server has been invoked with argument value 216 (km.h-1)
Step 8	[SWC <swc_client>]</swc_client>	[SWC <swc_server>]</swc_server>
	invoke operation (Rte_Call) with argument value 85 (m.s-1)	server has been invoked with argument value 306 (km.h-1)
Step 9	[CP]	
	terminate SWC_Client	
Post- conditions	None	

# 5.3.5 [ATS\_RTE\_00151] Test Intra-ECU C/Sargument rescaling - C/S ApplicationErrorMapping

Test Objective	Test Intra-ECU C/Sargun	nent rescaling - C/S	ApplicationErrorMapping
ID	ATS_RTE_00151	AUTOSAR Releases	4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00028		
Item	RTE: SWS_Rte_07925 RTE: SWS_Rte_07926		
Requirements / Reference to Test Environment	Use case 03.01 : C/S		
Configuration Parameters	1 SWC Client Interface: Std_ReturnType DataWriteError (uint8 DATA) The error codes for the client are: ERRORCODE2: 2 ERRORCODE63: 63 On the server side only ERRORCODE2 is handled. ClientServerApplicationErrorMapping: Mapping ERRORCODE63 -> ERRORCODE2		
Summary	This test case validates the C/S Application Error Mapping feature provided by the RTE.  For this test case, server returns ERRORCODE2 value for error occured ERRORCODE63.		
Needed Adaptation to	Needed Adaptation for	Release [4.0.3]	
other Releases	Configuration: [n/a] Test Steps: [n/a]	Client-server applica	ation Error Mapping not supported.
Pre-conditions	None		
Main Test Execu	ution		



Test Steps		Pass Criteria
Step 1	[CP]	
	Start SWC_Client	
Step 2	[SWC <swc_client>]</swc_client>	[SWC <swc_server>]</swc_server>
	Call DataWriteError operation	server has been invoked
Step 3	[SWC <swc_server>]</swc_server>	[SWC <swc_client>]</swc_client>
	Cause an error and return ERRORCODE2	client has received the ERRORCODE63 return value.
Post- conditions	None	

# 5.3.6 [ATS\_RTE\_00154] Test intra-ECU C/S argument rescaling - Composite Types (Structure)

	ı		
	Test intra-ECU C/S argument rescaling - Composite Types (Structure)		
ID	ATS_RTE_00154	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00028		
Trace to SWS Item	RTE: SWS_Rte_03860 RTE: SWS_Rte_07038		
Requirements / Reference to Test Environment	Use Case 03.01 : Intra-ECU C/S Communication		
	1 SWC Client with argument Composite Type: WheelSpeed4 { left_front : uint16; right_front : uint16; left_rear : uint16; right_rear : uint16; } 1 SWC Server with following type: WheelSpeed2 { left: unit16; right: uint16; } 1 DataPrototypeMapping with SubElementMappings WheelSpeed4.left_front -> WheelSpeed2.left; WheelSpeed4.right_front -> WheelSpeed2.right;		
Summary	The client calls an operation with an argument as a structure with 4 fields  The Test Manager shall check that server is invoked with the correct argument: a structure with 2 fields.		



Needed Adaptation to other Releases		
Pre-conditions	None	
Main Test Execu	ution	
Test Steps		Pass Criteria
Step 1	[CP]	
	start SWC_Client	
Step 2	[SWC <swc_client>]</swc_client>	[SWC <swc_server>]</swc_server>
	invoke operation with composite data: WheelSpeed4.left_front = 0x55AA WheelSpeed4.right_front = 0xAA55 WheelSpeed4.left_rear = 0x5A5A WheelSpeed4.right_rear = 0xA5A5	server has been invoked with composite data: WheelSpeed2.left = 0x55AA WheelSpeed2.right = 0xAA55
Step 3	[CP] terminate SWC_Client	
Post- conditions	None	

# 5.3.7 [ATS\_RTE\_00158] Test intra-ECU C/S argument rescaling - Composite Type (Array)

Test Objective	Test intra-ECU C/S argument rescaling - Composite Type (Array)		
ID	ATS_RTE_00158	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00028		
	RTE: SWS_Rte_03860 RTE: SWS_Rte_07038		
Requirements / Reference to Test Environment	Use case 03.01 : C/S		
	1 SWC Client with Composite Array Type argument ClientArray[4] of uint8 1 SWC Server with Composite Array Type argument ServerArray[8] of uint8 1 DataPrototypeMapping with SubElementMappings ClientArray [0] -> ServerArray[4] ClientArray [1] -> ServerArray[5] ClientArray [2] -> ServerArray[6] ClientArray [3] -> ServerArray[7]		
	Test Manager starts the Client which call the server with the ClientArray argument: ClientArray[0]=0x55 ClientArray[1]=0xAA		



	ClientArray[2]=0x55 ClientArray[3]=0xAA  Test Manager checks that the server is invoked with the ServerArray argument ServerArray[4] = 0x55 ServerArray[5] = 0xAA ServerArray[6] = 0x55 ServerArray[7] = 0xAA	
Needed		
Adaptation to other Releases		
	None	
Main Test Execu	ution	
Test Steps		Pass Criteria
Step 1	[CP] start SWC_Client	
Step 2	[SWC <swc_client>] invoke operation with array argument: ClientArray[0]=0x55 ClientArray[1]=0xAA ClientArray[2]=0x55 ClientArray[3]=0xAA</swc_client>	[SWC <swc_server>] server has been invoked with array argument: ServerArray[4] = 0x55 ServerArray[5] = 0xAA ServerArray[6] = 0x55 ServerArray[7] = 0xAA</swc_server>
Step 3	[CP] terminate SWC_Client	
Post- conditions	None	

## 5.3.8 [ATS\_RTE\_00160] Test intra-ECU S/R dataelements rescaling - Mixed Linear scaled and texttable

Test Objective	Test intra-ECU S/R dataelements rescaling - Mixed Linear scaled and texttable		
ID	ATS_RTE_00160	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00028		
	RTE: SWS_Rte_03815 RTE: SWS_Rte_03816 RTE: SWS_Rte_03832 RTE: SWS_Rte_03855		
Requirements / Reference to Test Environment	use Case 03.02: Intra-ECU S/R Communication		
Configuration Parameters	1 SWC Sender Sender Type: SpeedSensorType with SCALE_LINEAR_AND_TEXTTABLE CompuMethod:		



	values linear 0300		
	value 350 -> SensorError value 351 -> SignalNotAvailable		
	units: km.h-1		
	1 SWC Receiver Receiver Type:		
	SpeedType with SCALE_LINEAR_AND_TEXTTABLE		
	CompuMethod:		
	values linear 0350		
	value 400 -> UnknowSpeedValue		
	units: km.h-1 DataPrototypeMapping betwe	en those AutosarDataPrototypes with	
	TextTableMappings	IV (- I )	
	value 350 (SensorError)-> 400 (UnknownSp value 351 (SignalNotAvailable) -> 400 (Unki		
	Value 331 (SignaliNotAvaliable) -> 400 (Offici	lowi13peed value)	
	Both types are based on uint16		
Summary	The test shall validate that the conversion is	perfectly handled in the RTE generated	
	code for different values:		
	1. Send the value 150 and check that Recei	ver receives the value 150 in	
	Speeddataelement	at Danairea anni ea tha eale	
	<ol><li>Send the value SensorError and check th UnknownSpeedValue</li></ol>	at Receiver receives the value	
	3. Send the value SignalNotAvailable and ch	neck that Receiver receives the value	
	UnknownSpeedValue	icon that reconver receives the value	
Needed			
Adaptation to			
Adaptation to			
other Releases			
other Releases	None		
other Releases			
other Releases Pre-conditions		Pass Criteria	
other Releases Pre-conditions Main Test Exec		Pass Criteria	
other Releases Pre-conditions Main Test Exec Test Steps	ution	Pass Criteria	
other Releases Pre-conditions Main Test Exec Test Steps	ution	Pass Criteria	
other Releases Pre-conditions Main Test Exec Test Steps	[CP]	Pass Criteria  [SWC <swc_receiver>]</swc_receiver>	
other Releases Pre-conditions Main Test Executes Test Steps Step 1	[CP] start SWC_Sender		
other Releases Pre-conditions Main Test Executes Test Steps Step 1	[CP] start SWC_Sender		
other Releases Pre-conditions Main Test Executes Test Steps Step 1	[CP] start SWC_Sender [SWC <swc_sender>]</swc_sender>	[SWC <swc_receiver>]</swc_receiver>	
other Releases Pre-conditions Main Test Executes Test Steps Step 1	[CP] start SWC_Sender [SWC <swc_sender>]</swc_sender>	[SWC <swc_receiver>] receiver has received data value 150</swc_receiver>	
other Releases Pre-conditions Main Test Executes Test Steps Step 1 Step 2	tion  [CP]  start SWC_Sender  [SWC <swc_sender>]  send (Rte_Write) value 150 (km.h-1)</swc_sender>	[SWC <swc_receiver>] receiver has received data value 150 (km.h-1)</swc_receiver>	
other Releases Pre-conditions Main Test Executes Test Steps Step 1 Step 2	tion  [CP]  start SWC_Sender  [SWC <swc_sender>]  send (Rte_Write) value 150 (km.h-1)</swc_sender>	[SWC <swc_receiver>]  receiver has received data value 150 (km.h-1)  [SWC<swc_receiver>]  receiver has received data value 400</swc_receiver></swc_receiver>	
other Releases Pre-conditions Main Test Executes Test Steps Step 1 Step 2	[CP] start SWC_Sender [SWC <swc_sender>] send (Rte_Write) value 150 (km.h-1) [SWC<swc_sender>]</swc_sender></swc_sender>	[SWC <swc_receiver>] receiver has received data value 150 (km.h-1) [SWC<swc_receiver>]</swc_receiver></swc_receiver>	
other Releases Pre-conditions Main Test Executes Test Steps Step 1 Step 2	[CP] start SWC_Sender [SWC <swc_sender>] send (Rte_Write) value 150 (km.h-1) [SWC<swc_sender>]</swc_sender></swc_sender>	[SWC <swc_receiver>]  receiver has received data value 150 (km.h-1)  [SWC<swc_receiver>]  receiver has received data value 400</swc_receiver></swc_receiver>	
other Releases Pre-conditions Main Test Executes Test Steps Step 1 Step 2 Step 3	[CP] start SWC_Sender [SWC <swc_sender>] send (Rte_Write) value 150 (km.h-1)  [SWC<swc_sender>] send (Rte_Write) value 350 (SensorError)  [SWC<swc_sender>]</swc_sender></swc_sender></swc_sender>	[SWC <swc_receiver>] receiver has received data value 150 (km.h-1) [SWC<swc_receiver>] receiver has received data value 400 (UnknownSpeedValue) [SWC<swc_receiver>]</swc_receiver></swc_receiver></swc_receiver>	
other Releases Pre-conditions Main Test Executes Test Steps Step 1 Step 2 Step 3	[CP] start SWC_Sender [SWC <swc_sender>] send (Rte_Write) value 150 (km.h-1)  [SWC<swc_sender>] send (Rte_Write) value 350 (SensorError)  [SWC<swc_sender>] send (Rte_Write) value 351</swc_sender></swc_sender></swc_sender>	[SWC <swc_receiver>]  receiver has received data value 150 (km.h-1)  [SWC<swc_receiver>]  receiver has received data value 400 (UnknownSpeedValue)  [SWC<swc_receiver>]  receiver has received data value 400</swc_receiver></swc_receiver></swc_receiver>	
other Releases Pre-conditions Main Test Executes Test Steps Step 1  Step 2  Step 3	[CP] start SWC_Sender [SWC <swc_sender>] send (Rte_Write) value 150 (km.h-1)  [SWC<swc_sender>] send (Rte_Write) value 350 (SensorError)  [SWC<swc_sender>] send (Rte_Write) value 351 (SignalNotAvailable)</swc_sender></swc_sender></swc_sender>	[SWC <swc_receiver>] receiver has received data value 150 (km.h-1) [SWC<swc_receiver>] receiver has received data value 400 (UnknownSpeedValue) [SWC<swc_receiver>]</swc_receiver></swc_receiver></swc_receiver>	
other Releases Pre-conditions Main Test Executes Test Steps Step 1 Step 2 Step 3	[CP] start SWC_Sender [SWC <swc_sender>] send (Rte_Write) value 150 (km.h-1)  [SWC<swc_sender>] send (Rte_Write) value 350 (SensorError)  [SWC<swc_sender>] send (Rte_Write) value 351</swc_sender></swc_sender></swc_sender>	[SWC <swc_receiver>]  receiver has received data value 150 (km.h-1)  [SWC<swc_receiver>]  receiver has received data value 400 (UnknownSpeedValue)  [SWC<swc_receiver>]  receiver has received data value 400</swc_receiver></swc_receiver></swc_receiver>	
other Releases Pre-conditions Main Test Executes Test Steps Step 1  Step 2  Step 3	[CP] start SWC_Sender [SWC <swc_sender>] send (Rte_Write) value 150 (km.h-1)  [SWC<swc_sender>] send (Rte_Write) value 350 (SensorError)  [SWC<swc_sender>] send (Rte_Write) value 351 (SignalNotAvailable)  [CP]</swc_sender></swc_sender></swc_sender>	[SWC <swc_receiver>]  receiver has received data value 150 (km.h-1)  [SWC<swc_receiver>]  receiver has received data value 400 (UnknownSpeedValue)  [SWC<swc_receiver>]  receiver has received data value 400</swc_receiver></swc_receiver></swc_receiver>	
other Releases Pre-conditions Main Test Exect Test Steps Step 1  Step 2  Step 3  Step 4	[CP] start SWC_Sender [SWC <swc_sender>] send (Rte_Write) value 150 (km.h-1)  [SWC<swc_sender>] send (Rte_Write) value 350 (SensorError)  [SWC<swc_sender>] send (Rte_Write) value 351 (SignalNotAvailable)</swc_sender></swc_sender></swc_sender>	[SWC <swc_receiver>]  receiver has received data value 150 (km.h-1)  [SWC<swc_receiver>]  receiver has received data value 400 (UnknownSpeedValue)  [SWC<swc_receiver>]  receiver has received data value 400</swc_receiver></swc_receiver></swc_receiver>	
other Releases Pre-conditions Main Test Executes Test Steps Step 1  Step 2  Step 3	[CP] start SWC_Sender [SWC <swc_sender>] send (Rte_Write) value 150 (km.h-1)  [SWC<swc_sender>] send (Rte_Write) value 350 (SensorError)  [SWC<swc_sender>] send (Rte_Write) value 351 (SignalNotAvailable)  [CP]</swc_sender></swc_sender></swc_sender>	[SWC <swc_receiver>]  receiver has received data value 150 (km.h-1)  [SWC<swc_receiver>]  receiver has received data value 400 (UnknownSpeedValue)  [SWC<swc_receiver>]  receiver has received data value 400</swc_receiver></swc_receiver></swc_receiver>	



#### 5.3.9 [ATS\_RTE\_00161] Test intra-ECU S/R dataelements rescaling - Linear Scaled conversion

Test Objective	Test intra-ECU S/R dataelements	rescaling -	Linear Scaled conversion
ID	ATS_RTE_00161	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00028		
Trace to SWS Item	RTE: SWS_Rte_03815 RTE: SWS_Rte_03829		
Requirements / Reference to Test Environment	Use case 03.02: Intra-ECU Comr	nunication S	s/R
Configuration Parameters	1 SWC Sender with SenderReceiverInterface dataElement typed with SenderType LowerLimit = 0, UpperLimit = 100 ComputationMethod : PhytoInt : identical 1 SWC Receiver with dataElement typed with ReceiverType LowerLimit = 200, UpperLimit = 1200 Computation Method: PhyToInt : Linear (10*x+200) 1 DataPrototypeMapping between those AutosarDataPrototypes Both types are based on uint32		
Summary Needed	Computation Method: PhyToInt: Linear (10*x+200)  For different values, a value is sent from SWC_Sender and SWC_Receiver checks it received the converted value.		
Adaptation to other Releases			
Pre-conditions	None		
Main Test Execu	ution		
Test Steps	l-a		Pass Criteria
Step 1	[CP] start SWC_Sender		
Step 2	[SWC <swc_sender>] send (Rte_Write) DataWrite with</swc_sender>	data value 0	[SWC <swc_receiver>] receiver has received converted data value 200</swc_receiver>
Step 3	[SWC <swc_sender>] send (Rte_Write) DataWrite with (</swc_sender>	data value	[SWC <swc_receiver>] receiver has received converted data value 1200</swc_receiver>
Step 5	[CP] terminate SWC_Sender		value 1200
	tominate OVVO_Oender		l



Post-	None
conditions	

# 5.3.10 [ATS\_RTE\_00162] Test intra-ECU S/R dataelements rescaling - Composite Types (Structure)

Test Objective	Test intra-ECU S/R dataelements	rescaling -	Composite Types (Structure)
ID	ATS_RTE_00162	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00028	-	
ltem	RTE: SWS_Rte_03815 RTE: SWS_Rte_03816 RTE: SWS_Rte_03860 RTE: SWS_Rte_07091 RTE: SWS_Rte_07092 RTE: SWS_Rte_07099		
Requirements / Reference to Test Environment	Use case 03.02 : S/R		
Parameters	1 SWC Sender with a Sender into WheelSpeed4 { left_front : uint16; left_rear : unit16; right_front : uint16; right_rear : uint16; } 1 SWC receiver with the following WheelSpeed2 { left : uint16; right : uint16; } Mapping: WheelSpeed4.left_front -> Wheel WheelSpeed4.right_front -> Wheel Speed4.right_front -> Wheel Speed4.right_fro	g interface: Speed2.left	ıht
Summary	This test case validates the feature provided by the RTE of sender-receiver dataelements mapping of Composite types like C structures.  The Test Manager shall check that CompositeData has been converted correctly by the RTE on the receiver side.		
Needed Adaptation to other Releases			
	None		
Main Test Execution			
Test Steps			Pass Criteria



Step 1	[CP]	
	start SWC_Sender	
Step 2	[SWC <swc_sender>]</swc_sender>	[SWC <swc_receiver>]</swc_receiver>
	send (Rte_Write) composite data: WheelSpeed4.left_front = 0x55AA WheelSpeed4.right_front = 0xAA55 WheelSpeed4.left_rear = 0x5A5A WheelSpeed4.right_rear = 0xA5A5	receiver has received composite data: WheelSpeed2.left = 0x55AA WheelSpeed2.right = 0xAA55
Step 3	[CP]	
	terminate SWC_Sender	
Post- conditions	None	

# 5.3.11 [ATS\_RTE\_00163] Test intra-ECU S/R dataelements rescaling - Composite Types (Array)

Test Objective	Test intra-ECU S/R dataelements rescaling - Composite Types (Array)		
ID	ATS_RTE_00163	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00028		
Trace to SWS Item	RTE: SWS_Rte_03815 RTE: SWS_Rte_03816 RTE: SWS_Rte_03860 RTE: SWS_Rte_07091 RTE: SWS_Rte_07092 RTE: SWS_Rte_07099		
Requirements / Reference to Test Environment	Use case 03.02: S/R		
Configuration Parameters	A SWC sender Array uint8 SenderArray[4] A Receiver Array uint8 ReceiverArray[8]  Using SubElementMappings, the array elements are mapped as follows: SenderArray[0] -> ReceiverArray[4] SenderArray[1] -> ReceiverArray[5] SenderArray[2] -> ReceiverArray[6] SenderArray[3] -> ReceiverArray[7]		
Summary	The sender runnable sends the following array  SenderArray[0]=0x55  SenderArray[1]=0xAA  SenderArray[2]=0x55  SenderArray[3]=0xAA		



	Test Manager checks that the receiver runnable receives an array with  ReceiverArray[4] = 0x55  ReceiverArray[5] = 0xAA  ReceiverArray[6] = 0x55  ReceiverArray[7] = 0xAA			
Needed Adaptation to other Releases				
Pre-conditions	None			
Main Test Execu	Main Test Execution			
Test Steps		Pass Criteria		
Step 1	[CP] start SWC_Sender			
Step 2	[SWC <swc_sender>] send array: SenderArray[0]=0x55 SenderArray[1]=0xAA SenderArray[2]=0x55 SenderArray[3]=0xAA</swc_sender>	[SWC <swc_receiver>] the following array has been received: ReceiverArray[4] = 0x55 ReceiverArray[5] = 0xAA ReceiverArray[6] = 0x55 ReceiverArray[7] = 0xAA</swc_receiver>		
Step 3	[CP] terminate SWC_Sender			
Post- conditions	None			

## 5.3.12 [ATS\_RTE\_00164] Test intra-ECU S/R dataelements rescaling - texttable to texttable

Test Objective	Test intra-ECU S/R dataelements rescaling - texttable to texttable		
ID		AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00028		
Item	RTE: SWS_Rte_03815 RTE: SWS_Rte_03816 RTE: SWS_Rte_03830 RTE: SWS_Rte_03833		
Requirements / Reference to Test Environment	Use case 03.02 : S/R		
Configuration Parameters	1 SWC Sender with ENUM parameter: enum		



		-	
	{SenderValue0,SenderValue1,SenderValue2 1 SWC Receiver with ENUM parameter enum	,SenderValue3}	
	{ReceiverValue2, ReceiverValue1, ReceiverValue0} TextTableMapping :		
	SenderValue0 -> ReceiverValue0		
	SenderValue1 -> ReceiverValue2		
	SenderValue2 -> ReceiverValue1 SenderValue3 -> ReceiverValue2		
Summary	Test Manager starts the SWC Sender		
Guillillary	rest Manager starts the 5000 Sender		
	Sender sends to Receiver SenderValue0, the then SenderValue3 values.	en SenderValue1, then SenderValue2,	
	Receiver checks that it has received the conv	verted value on the following sequence:	
	ReceiverValue0, ReceiverValue2, ReceiverV	alue1, ReceiverValue2	
Needed Adaptation to other Releases			
Pre-conditions	None		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[CP]		
	start SWC_Sender		
Step 2	[SWC <swc_sender>]</swc_sender>	[SWC <swc_receiver>]</swc_receiver>	
		Davida Walas Olas Isaa saasi a I	
Ctor 2	send value SenderValue0	ReceiverValue0 has been received	
Step 3	[SWC <swc_sender>]</swc_sender>	[SWC <swc_receiver>]</swc_receiver>	
	send value SenderValue1	ReceiverValue2 has been received	
Step 4	[SWC <swc_sender>]</swc_sender>	[SWC <swc_receiver>]</swc_receiver>	
	send value SenderValue2	ReceiverValue1 has been received	
Step 5	[SWC <swc_sender>]</swc_sender>	[SWC <swc_receiver>]</swc_receiver>	
	send value SenderValue3	ReceiverValue2 has been received	
Step 6	[CP]		
	,		
	terminate SWC_Sender		
Post- conditions	None		

# 5.3.13 [ATS\_RTE\_00165] Test Inter-ECU NetworkRepresentations - Transmitting ECU DatatTypePolicy : Override

•	Test Inter-ECU NetworkRepresentations - Transmitting ECU DatatTypePolicy : Override		
ID		AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2



Affected	DTE COM	Ctata				
Affected Modules	RTE, COM	State	reviewed			
Trace to	ATR: ATR_ATR_00027					
Requirement						
on Acceptance						
Test Document						
Trace to SWS Item	RTE: SWS_Rte_03827					
Requirements / Reference to Test Environment	Use Case 03.03: Inter-ECU Network Representations					
Configuration	SWC. Sender sends a dataeleme	SWC_Sender sends a dataelement of a sint16 type t_VoltageAtSender				
Parameters	OVVO_Genuer Serius a uataerement or a sint to type t_voltageAtSenuer					
	SenderPort representation called s					
	Physical Representation called p					
	CompuMethod					
	InternalToPhysical : p=(0+1*s)/4					
	PhysicalToInternal : s=4p					
	NetworkRepresentation (called n)					
	CompuMethod					
	InternalToPhysical : p=(1+n)/2					
	PhysicalToInternal : n=2p-1					
Summary	For this test case, the SWC_Send	der is located	d on the SUT Side.			
	L					
	The SWC_Receiver is located on	the Test be	nch side			
	The Test Bench shall check that t					
	The Test Bench shall check that t received correctly and has been o					
Needed						
Adaptation to						
Adaptation to other Releases	received correctly and has been o					
Adaptation to other Releases Pre-conditions	received correctly and has been o					
Adaptation to other Releases	received correctly and has been o					
Adaptation to other Releases Pre-conditions	received correctly and has been o					
Adaptation to other Releases Pre-conditions Main Test Execu	received correctly and has been o		defined.			
Adaptation to other Releases Pre-conditions Main Test ExecuTest Steps	received correctly and has been of the control of t		defined.			
Adaptation to other Releases Pre-conditions Main Test ExecuTest Steps	received correctly and has been of the control of t		defined.			
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1	received correctly and has been on the None  ution  [CP]  start SWC_Sender	converted as	Pass Criteria			
Adaptation to other Releases Pre-conditions Main Test ExecuTest Steps	received correctly and has been on the last seem of the l	converted as	defined.			
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1	None  [CP]  start SWC_Sender [SWC <swc_sender>]</swc_sender>	converted as	Pass Criteria  [LT]			
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1	received correctly and has been on the None  ution  [CP]  start SWC_Sender	converted as	Pass Criteria			
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1 Step 2	None  [CP]  start SWC_Sender  [SWC <swc_sender>]  send a data value 0</swc_sender>	converted as	Pass Criteria  [LT]  data value -1 (=(0/2)-1) has been received			
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1	None  [CP]  start SWC_Sender [SWC <swc_sender>]</swc_sender>	converted as	Pass Criteria  [LT]  data value -1 (=(0/2)-1) has been			
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1 Step 2	None  Ition  [CP]  start SWC_Sender  [SWC <swc_sender>]  send a data value 0  [SWC<swc_sender>]</swc_sender></swc_sender>	converted as	Pass Criteria  [LT]  data value -1 (=(0/2)-1) has been received [LT]			
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1 Step 2	None  [CP]  start SWC_Sender  [SWC <swc_sender>]  send a data value 0</swc_sender>	converted as	Pass Criteria  [LT]  data value -1 (=(0/2)-1) has been received [LT]  data value 4 (=(10/2)-1) has been			
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1  Step 2  Step 3	None  ICP]  start SWC_Sender  [SWC <swc_sender>]  send a data value 0  [SWC<swc_sender>]  send a data value 10</swc_sender></swc_sender>	converted as	Pass Criteria  [LT]  data value -1 (=(0/2)-1) has been received  [LT]  data value 4 (=(10/2)-1) has been received			
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1 Step 2	None  Ition  [CP]  start SWC_Sender  [SWC <swc_sender>]  send a data value 0  [SWC<swc_sender>]</swc_sender></swc_sender>	converted as	Pass Criteria  [LT]  data value -1 (=(0/2)-1) has been received [LT]  data value 4 (=(10/2)-1) has been			
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1  Step 2  Step 3	None Ition  [CP] start SWC_Sender [SWC <swc_sender>] send a data value 0  [SWC<swc_sender>] send a data value 10</swc_sender></swc_sender>	converted as	Pass Criteria  [LT]  data value -1 (=(0/2)-1) has been received  [LT]  data value 4 (=(10/2)-1) has been received  [LT]			
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1  Step 2  Step 3	None  ICP]  start SWC_Sender  [SWC <swc_sender>]  send a data value 0  [SWC<swc_sender>]  send a data value 10</swc_sender></swc_sender>	converted as	Pass Criteria  [LT]  data value -1 (=(0/2)-1) has been received  [LT]  data value 4 (=(10/2)-1) has been received  [LT]  data value 4 (=(10/2)-1) has been received  [LT]  data value 49 (=(100/2)-1) has been			
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1  Step 2  Step 3	None  Ition  [CP]  start SWC_Sender  [SWC <swc_sender>]  send a data value 0  [SWC<swc_sender>]  send a data value 10  [SWC<swc_sender>]  send a data value 10</swc_sender></swc_sender></swc_sender>	converted as	Pass Criteria  [LT]  data value -1 (=(0/2)-1) has been received  [LT]  data value 4 (=(10/2)-1) has been received  [LT]			
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1  Step 2  Step 3	None Ition  [CP] start SWC_Sender [SWC <swc_sender>] send a data value 0  [SWC<swc_sender>] send a data value 10</swc_sender></swc_sender>	converted as	Pass Criteria  [LT]  data value -1 (=(0/2)-1) has been received  [LT]  data value 4 (=(10/2)-1) has been received  [LT]  data value 4 (=(10/2)-1) has been received  [LT]  data value 49 (=(100/2)-1) has been			
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1  Step 2  Step 3	None  Ition  [CP]  start SWC_Sender  [SWC <swc_sender>]  send a data value 0  [SWC<swc_sender>]  send a data value 10  [SWC<swc_sender>]  send a data value 10</swc_sender></swc_sender></swc_sender>	converted as	Pass Criteria  [LT]  data value -1 (=(0/2)-1) has been received  [LT]  data value 4 (=(10/2)-1) has been received  [LT]  data value 49 (=(100/2)-1) has been received			



Post-	ht
rusi-	None
conditions	

# 5.3.14 [ATS\_RTE\_00166] Test Inter-ECU NetworkRepresentations - Transmitting ECU DatatTypePolicy : FromComSpec

T ( OL ' ('	Tarther FOUND AT Decree of the Country of the Count					
Test Objective	Test Inter-ECU NetworkRepresentations - Transmitting ECU DatatTypePolicy : FromComSpec					
ID	ATS_RTE_00166	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2			
Affected Modules	RTE	State	reviewed			
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00027					
Trace to SWS Item	RTE: SWS_Rte_06737					
Requirements / Reference to Test Environment	Use Case 03.03: inter-ECU Network Representations					
Configuration Parameters	SWC_Sender sends a dataelement of a sint16 type t_VoltageAtSender					
	SenderPort representation called s Physical Representation called p CompuMethod InternalToPhysical: p=(0+1*s)/4 PhysicalToInternal: s=4p  NetworkRepresentation (called n) CompuMethod InternalToPhysical: p=(1+n)/2 PhysicalToInternal: n=2p-1 EcuC Justification: This networkRepresentation is defined in the SenderComSpec of SWC_Sender and on the SenderComSpec of SwcB and the corresponding ISignal is defined					
Summary	This test case validates the data conversion over the network from Transmitting ECU side.  This test case consist in sending the data value on the port and check that the data has been received on the Test Bench side with the correct value regarding the network representation defined.					
Needed Adaptation to other Releases						
Pre-conditions						
	Main Test Execution					
Test Steps	L		Pass Criteria			
Step 1	[CP]					
	start SWC_Sender					



Step 2	[SWC <swc_sender>]</swc_sender>	[LT]
	send a data value 0	data value -1 has been received
Step 3	[SWC <swc_sender>]</swc_sender>	[LT]
	send a data value 10	data value 4 (=(10/2)-1) has been received
Step 4	[SWC <swc_sender>]</swc_sender>	[LT]
	send a data value 100	data value 49 (=(100/2)-1) has been received
Step 5	[CP]	
	terminate SWC_Sender	
Post- conditions	None	

# 5.3.15 [ATS\_RTE\_00167] Test Inter-ECU NetworkRepresentations - Receiving ECU DatatTypePolicy : Override

Test Objective	Test Inter-ECU NetworkRepresentations - Receiving ECU DatatTypePolicy : Override		
ID	ATS_RTE_00167	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE, COM	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00027		
Trace to SWS Item	RTE: SWS_Rte_03828		
Requirements / Reference to Test Environment	Use case 03.03: Inter-ECU Network representations		
Configuration Parameters	SwcB receives a dataelement of a sint16 type t_VoltageAtReceiver  ReceiverPort representation called r Physical Representation called p CompuMethod InternalToPhysical: p=(16+r)/8 PhysicalToInternal: r=8p-16  NetworkRepresentation (called n) CompuMethod InternalToPhysical: p=(1+n)/2 PhysicalToInternal: n=2p-1 EcuC Justification:  DataTypePolicy = Override		
Summary	This test case validates the Data receiver side when ISignal DataT		of Network transmitted data on the set to Override.



	For this test case, the SwcA is located on the Test Bench Side.  The SwcB is located on the SUT side.  The Test Bench shall check that transmitted data over the network have been received and converted correctly by the RTE.		
Needed Adaptation to other Releases			
Pre-conditions	None		
Main Test Exec	ution		
Test Steps		Pass Criteria	
Step 1	[CP] start SWC_Receiver		
Step 2	[LT] sends a data value -1 on network	[SWC <swc_receiver>] data value -16 (=-1*4-12) has been received</swc_receiver>	
Step 3	[LT] send a data value 4 on network	[SWC <swc_receiver>] data value 4 (=4*4-12) has been received</swc_receiver>	
Step 4	[LT] send a data value 49 on network	[SWC <swc_receiver>] data value 184 (=49*4-12) has been received</swc_receiver>	
Step 5	[CP] terminate SWC_Receiver		
Post- conditions	None		

# 5.3.16 [ATS\_RTE\_00168] Test Inter-ECU NetworkRepresentations - Receiving ECU DatatTypePolicy : FromComSpec

Test Objective	Test Inter-ECU NetworkRepresentations - Receiving ECU DatatTypePolicy : FromComSpec			
ID		AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2	
Affected Modules	RTE State reviewed			
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00027			
Trace to SWS Item	RTE: SWS_Rte_06738			
Requirements / Reference	Use case 03.03: Inter-ECU Network Representations			



to Test			
Environment			
Configuration Parameters	SwcB receives a dataelement of a sint16 ty	/pe t_VoltageAtReceiver	
	ReceiverPort representation called r		
	Physical Representation called p		
	CompuMethod		
	InternalToPhysical: p=(16+r)/8		
	PhysicalToInternal : r=8p-16		
	NetworkRepresentation (called n)		
	CompuMethod		
	InternalToPhysical : p=(1+n)/2 PhysicalToInternal : n=2p-1		
	EcuC Justification:		
	DataTypePolicy = FromComSpec		
Summary	This test case validates the data conversio side.	n over the network from Receiving ECU	
	Side.		
	This test case consist in sending the data v	value by the test bench and check that	
	the data has been received on the SUT sid		
	network representation defined.		
Needed			
Adaptation to other Releases			
Pre-conditions	None		
Main Test Exec	ution		
Test Steps		Pass Criteria	
Step 1	[CP]		
	start SWC_Receiver		
Step 2	[LT]	[SWC <swc_receiver>]</swc_receiver>	
	send a data value -1 on network	data value -16 (=4*0-12) has been	
_		received	
IO1 A	r:		
Step 3	[LT]	[SWC <swc_receiver>]</swc_receiver>	
Step 3	[LT] send a data value 4 on network	[SWC <swc_receiver>] data value 4 (=4*4-12) has been</swc_receiver>	
·	send a data value 4 on network	[SWC <swc_receiver>] data value 4 (=4*4-12) has been received</swc_receiver>	
Step 3 Step 4		[SWC <swc_receiver>] data value 4 (=4*4-12) has been</swc_receiver>	
Step 4	send a data value 4 on network  [LT] send a data value 49 on network	[SWC <swc_receiver>] data value 4 (=4*4-12) has been received</swc_receiver>	
·	send a data value 4 on network	[SWC <swc_receiver>]  data value 4 (=4*4-12) has been received  [SWC<swc_receiver>]  data value 184 (=49*4-12) has been</swc_receiver></swc_receiver>	
Step 4	send a data value 4 on network  [LT] send a data value 49 on network	[SWC <swc_receiver>]  data value 4 (=4*4-12) has been received  [SWC<swc_receiver>]  data value 184 (=49*4-12) has been</swc_receiver></swc_receiver>	
Step 4	send a data value 4 on network  [LT] send a data value 49 on network  [CP]	[SWC <swc_receiver>]  data value 4 (=4*4-12) has been received  [SWC<swc_receiver>]  data value 184 (=49*4-12) has been</swc_receiver></swc_receiver>	

# 5.3.17 [ATS\_RTE\_00169] Test Intra-ECU Range Checks - SR Unqueued ignore

Test Objective	Test Intra-ECU Range Checks - SR Unqueued ignore



ID	ATS_RTE_00169	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00029		
Trace to SWS Item	RTE: SWS_Rte_03839 RTE: SWS_Rte_03845 RTE: SWS_Rte_08026 RTE: SWS_Rte_08028		
Requirements / Reference to Test Environment	Use case 03.04: Range checks intra-ECU		
Configuration Parameters	SUT has 2 SWC Data Element Type defined with: uint16 LowerLimit: 0 UpperLimit: 100 SwcA with SenderPort with UnqueuedSenderComSpec defined with HandleOutOfRange = Ignore SwcB with ReceiverPort with UnqueuedReceiverComSpec defined with handleOutOfRange = ignore		
Summary	This test will send different values has been saturated to the defined		that received data on the receiver side (100).
Needed Adaptation to other Releases			
Pre-conditions	None		
Main Test Execu	ution		
Test Steps			Pass Criteria
Step 1	[CP] start SWC_Sender		
Step 2	 [SWC <swc_sender>]</swc_sender>		[SWC <swc_receiver>]</swc_receiver>
	send data value 100		data value 100 has been received
Step 3	[SWC <swc_sender>]</swc_sender>		[SWC <swc_receiver>]</swc_receiver>
	send data value 101		no data has been received
			hint: scheduling must be controlled so that enough time is given to receive a data (as in step 2)
Step 4	[SWC <swc_sender>]</swc_sender>		[SWC <swc_receiver>]</swc_receiver>
	send data value 200		no data has been received
			hint: scheduling must be controlled so that enough time is given to receive a data (as in step 2)
Step 5	[CP]		
	terminate SWC_Sender		



Post-	ht
rusi-	None
conditions	

# 5.3.18 [ATS\_RTE\_00170] Test Inter-ECU Range Checks - Sender Side ISignalProps = invalid

		_	
Test Objective	Test Inter-ECU Range Checks - S		
ID	ATS_RTE_00170	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE, COM	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00029		
Trace to SWS Item	RTE: SWS_Rte_08033		
Requirements / Reference to Test Environment	Use Case 03.05: Range Checks Inter-ECU		
Configuration Parameters	1 SWC Sender on the SUT 1 SenderPort with data element uint16 LowerLimit: 0 Upperlimit: 100 (these limits should be defined on the networkRepresentationProps of the ISignal (SWS_Rte_08042), not on the dataElement) 1 ISignal uint16 networkRepresentationProps with invalidValue INVALID_VALUE: 0xFFFF ISignalProps with handleOutOfRange = hnvalid		
Summary	The Test case will send different SWC Sender, the INVALID_VAL		eck that for data outof range on the ed by SWC Receiver.
Needed Adaptation to other Releases			
Pre-conditions	None		
Main Test Execu	ution		
Test Steps			Pass Criteria
Step 1	[CP] start SWC_Sender		
Step 2	[SWC <swc_sender>] send data value 100</swc_sender>		[LT] data value 100 has been received
Step 3	[SWC <swc_sender>] send data value 101</swc_sender>		[LT]  data value INVALID_VALUE has been received
Step 4	[CP] terminate SWC_Sender		peen received
Post- conditions	None		



## 5.3.19 [ATS\_RTE\_00175] Test Intra-ECU Range Checks - SR queued saturate

Test Objective	Test Intra-ECU Range Checks	- SR queued s	saturate	
ID	ATS_RTE_00175	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2	
Affected Modules	RTE	State	reviewed	
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00029	•		
Trace to SWS Item	RTE: SWS_Rte_03840 RTE: SWS_Rte_08026			
Requirements / Reference to Test Environment	Use case 03.04: Intra-ECU Range checks			
Configuration Parameters	SUT has 2 SWC Data Element Type defined with: uint16 isQueued=true LowerLimit: 0 UpperLimit: 100 SwcA with SenderPort with QueuedSenderComSpec defined with HandleOutOfRange = saturate SwcB with ReceiverPort with QueuedReceiverComSpec defined with handleOutOfRange = saturate			
Summary	This test will send different values and check that received data on the receiver side has been saturated to the defined UpperLimit (100).			
Needed Adaptation to other Releases				
Pre-conditions	None			
Main Test Exec	ution			
Test Steps			Pass Criteria	
Step 1	[CP] start SWC_Sender			
Step 2	[SWC <swc_sender>] send (Rte_Send) data value 99 send (Rte_Send) data value 10 send (Rte_Send) data value 10</swc_sender>	00		
Step 3	[CP] Wait SWC_Receiver activation		[SWC <swc_receiver>] data value 99 has been received (Rte_Receive)</swc_receiver>	
Step 4	[CP] Wait SWC_Receiver activation		[SWC <swc_receiver>] data value 100 has been received (Rte_Receive)</swc_receiver>	
Step 5	[CP] Wait SWC_Receiver activation		[SWC <swc_receiver>] data value 100 has been received</swc_receiver>	



Step 6	[CP]	
	terminate SWC_Sender	
Post-	None	
conditions		

# 5.3.20 [ATS\_RTE\_00176] Test Inter-ECU Range Checks - Receiver Side ISignalProps = invalid

_	<u> </u>		
Test Objective	Test Inter-ECU Range Checks - Receiver Side ISignalProps = invalid		
ID	ATS_RTE_00176	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE, COM	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00029		
Trace to SWS Item	RTE: SWS_Rte_08037		
Requirements / Reference to Test Environment	Use case 03.05: Inter-ECU Rang	e Checks	
Configuration Parameters	1 SWC Receiver on the SUT 1 ReceiverPort with data element uint16 LowerLimit: 0 Upperlimit: 100 1 (these limits should be defined on the networkRepresentationProps of the ISignal (SWS_Rte_08042), not on the dataElement) ISignal uint16 networkRepresentationProps with invalidValue INVALID_VALUE: 0xFFFF and iSignalProps with handleOutOfRange = invalid		
Summary	This test sends a ISignal on the CAN Bus from the Test Bench to SUT.  The ISignal value is out of range (200)  Check that on receiver side, the received value is INVALID_VALUE.		
Needed Adaptation to other Releases			
Pre-conditions	None		
Main Test Execu	ıtion		
Test Steps			Pass Criteria
Step 1	[CP] start SWC_Receiver		
Step 2	[LT] send signal with value 100 on net	work	[SWC <swc_receiver>] data value 100 has been received (Rte_Read) Rte_Read returns RTE_E_OK</swc_receiver>



Step 3	[LT]	[SWC <swc_receiver>]</swc_receiver>
	send signal with value 101 on network	data value INVALID_VALUE has been received (Rte_Read)
		Rte_Read returns RTE_E_OK
Step 5	[CP]	
	terminate SWC_Receiver	
Post- conditions	None	



# 6 RS\_BRF\_01304/RS\_BRF\_01352 - Rte Sender Receiver Communication

### 6.1 General Test Objective and Approach

The "RTE 1:n Sender Receiver" features are tested by sending and receiving data via SW-Cs' ports or via the bus, and then checking if the data that has been transmitted or received correctly and with the appropriate timing.

#### 6.1.1 Test System

#### 6.1.1.1 Overview on Architecture

The basic test setup is depicted in Figure 4, corresponding to the test of the "1:n Sender Receiver" features, that can be refined depending on the communication pattern (intra-ECU or inter-ECU) and the number of receivers (1:1 or 1:2) required to execute the test case.




Figure 4: Basic test setup

It can be refined as follows:



#### 6.1.1.1.1 1:1 intra-ECU test cases




Figure 5: Test Setup for an Intra-ECU test

1:1 intra-ECU test cases require two SWCs as Upper Testers. The Control SWC is responsible for the transmission of data on a provide port, while the Observation SWC is responsible for the reception of data on a require port.



#### 6.1.1.1.2 1:1 Inter-ECU test cases




Figure 6: Test Setup for Inter-ECU Test

1:1 inter-ECU test cases require a SWC as Upper Tester. This SWC performs transmission of data on a provide port and the correct behavior of the "RTE Sender Receiver" features is verified by the Lower Tester which observes the bus transporting the data. The SWC is also responsible for the reception of data transmitted on the bus.



#### 6.1.1.1.3 1:2 reception from inter ECU test cases




Figure 7: Test Setup for 1:2 Inter-ECU Test

1:2 reception from inter-ECU test cases require two SWCs as Upper Testers. These SWCs perform on their require ports the reception of data received by the ECU via the bus.



#### 6.1.1.1.4 1:2 transmission to intra-ECU & inter-ECU test cases




Figure 8: Test Setup for 1:2 Transmission Test

1:2 transmission to intra-ECU & inter-ECU test cases require two SWCs as Upper Testers. The Control SWC performs on a provide port transmission of data that is made available to the other SWC and on the bus. The Observation SWC performs a reception of data on the provide port while the Lower Tester receives the data via the bus.

#### 6.1.1.2 Specific Requirements

Test cases with inter-ECU communication pattern require a "Bus simulation" as Lower Tester. It is used to simulate the reception and the transmission of messages by other ECUs.

In inter-ECU test cases, the bus must be able to transmit any messages from Lower Tester to the Observation SWC and from the Control SWC to the Lower Tester. Test cases implicitly suppose that when a message is sent on the bus, this message is effectively transmitted by the bus.

#### **6.1.1.3 Test Coordination Requirements**

Test Coordination Procedures are needed to synchronize the runnables of the Control SWC and of the Observation SWC in intra-ECU test cases.



TCPs are also needed to collect the test results of the SWCs and the Bus simulation at one central place in order to derive the test verdict.

It is up to the test system designer/implementer to define that "central place" and to design/implement the test coordination functionality.

#### 6.1.2 Test Configuration

This section describes sets of requirements on configuration.

These sets are later referenced by test cases.

No configuration files are provided. They need to be developed when the test suite is implemented.

#### 6.1.2.1 Required ECU Extract of System Description Files

A single ECU Extract is needed as input for the test cases described in this document.

#### 6.1.2.1.1 EcuFlatView

This element includes:

- The ECUFlatView composition;
- The instances of the Atomic Software Components included in the SUT Ecu:
  - o ControlSWC
  - Observation1SWC
  - o Observation2SWC

with their ports and their connections.

A RootSwCompositionPrototype pointing to this ECU flat view must also be included in the ECU Extract.

#### 6.1.2.1.2 SoftwareComponent Description

The description of all the Atomic Software Components included in the SUT Ecu, with their interfaces, datatypes, internal behavior and implementation must be included.(see section 6.1.2.3)

#### 6.1.2.1.3 Topology

This section includes:

- The instance of the SUT Ecu, with a Communication Controller to make communication possible with the Test System;
- The Communication Cluster with a physical channel used by the SUT Ecu instance.

#### 6.1.2.1.4 Communication

To describe the communication characteristics between the SUT Ecu and the Test system, for each test case the following elements must be included:

- two System Signals for the two directions of communication (from SUT Ecu to the Test System and viceversa);
- two ISignal, each mapped to one of the defined System Signal;



- two IPdu, each mapped to one of the defined ISignals;
- two Frames, each mapped to one of the defined IPdu During the implementation phase, it can choose to reuse some of these elements.

#### 6.1.2.1.5 Mappings

The Ecu Extract also includes the following mappings:

- software components to SUT Ecu mapping;
- data to System Signals mapping.

Data are to be mapped to the system signals according to their direction of communication

#### 6.1.2.2 Required ECU Configuration Specifications

There are no generic requirements on ECU Configuration files. Individual test cases may have specific requirements on the RTE configuration.

#### 6.1.2.3 Required Software Component Specifications

#### Types:

Name	Туре	
TYP_ExchangedData	<implementer choice=""></implementer>	

#### Interfaces:

Name	Data Element	Туре	SwImplPolicy
IF_ExchangedData	DE_ExchangedData	TYP_ExchangedData	standard
	DE_ExchangedEvent	TYP_ExchangedData	queued

#### SWCs:

SWC Name	ControlSWC	
	Name	PP_SendData
	Туре	PPortPrototype
	Interface	IF_ExchangedData
	ComSpecs	NonqueuedSenderComSpec for dataElement DE_ExchangedData, with initValue Value_Init_Send.
	Requirements	
PORTS		
	Name	PP_SendEvent
	Туре	PPortPrototype
	Interface	IF_ExchangedData
	ComSpecs	QueuedSenderComSpec for dataElement DE_ExchangedEvent.
	Requirements	
	Name	RUN_Ctrl



	Requirements	Executed in the same task as RUN_Obs2_1 and RUN_Obs2_2.	
		Name	VDP_ImplWrite
		Туре	DataWriteAccess
	VariableDataPrototype	Access to	PP_SendData/ IF_ExchangedData/ DE_ExchangedData
		Requirements	Belongs to the same coherency group as RUN_Obs2_1/ VDP_ImplRead2 and RUN_Obs2_2/ VDP_ImplRead2_2
RUNNABLE			
ENTITIES		Name	VDP_ExplWrite
		Туре	DataSendPoint
		Access to	PP_SendData/ IF_ExchangedData/ DE_ExchangedData
		Requirements	
		Name	VDP_Send
		Туре	DataSendPoint
		Access to	PP_SendEvent/ IF_ExchangedData/ DE_ExchangedEvent
		Requirements	

SWC Name	Observation1SWC		
	Name	RP_ReceiveData1	
	Туре	RPortPrototype	
	Interface	IF_ExchangedData	
	ComSpecs	NonqueuedReceiverComSpec for dataElement DE_ExchangedData, with initValue Value_Init_Send.	
	Requirements		
PORTS			
	Name	RP_ReceiveEvent1	
	Туре	RPortPrototype	
	Interface	IF_ExchangedEvent	
	Queuing attribute	QueuedReceiverComSpec for dataElement DE_ExchangedEvent, with queueLength = 2.	
	Init value		



	Requirements			
	Name	RUN_Obs1		
	Requirements			
		Name	VDP_ImplRead1	
		Туре	DataReadAccess	
		Access to	RP_ReceiveData1/ IF_ExchangedData/ DE_ExchangedData	
	VariableDataPrototype	Requirements		
		Name	VDP_ExplRead1	
RUNNABLE		Туре	DataReceivePoint	
ENTITIES		Access to	RP_ReceiveData1/ IF_ExchangedData/ DE_ExchangedData	
		Requirements	Non blocking	
		Name	VDP_Receive1	
		Туре	DataReceivePoint	
		Access to	RP_ReceiveEvent1/ IF_ExchangedData/ DE_ExchangedEvent	
		Requirements	Non blocking	

SWC Name	Observation2SWC			
	Name	RP_ReceiveData2		
	Туре	RPortPrototype		
	Interface	IF_ExchangedData		
PORTS	ComSpecs	NonqueuedReceiverComSpec for dataElement DE_ExchangedData, with initValue Value_Init_Receive2, and with attribute handleNeverReceived set to TRUE.		
	Requirements			
	Name	RUN_Obs2_1		
	Requirements	Executed in the same task as RUN_Obs2_2 and RUN_Ctrl.		
RUNNABLE	VariableDataPrototype	Name	VDP_ImplRead2_1	
ENTITIES		Туре	DataReadAccess	
		Access to	RP_ReceiveData2/ IF_ExchangedData/ DE_ExchangedData	



		Requirements	Belongs to the same coherency group as RUN_Obs2_2/ VDP_ImplRead2_2 and RUN_Ctrl/ VDP_ImplWrite
		Name	VDP_ExplRead2_1
		Туре	DataReceivePoint
		Access to	RP_ReceiveData2/ IF_ExchangedData/ DE_ExchangedData
		Requirements	Non blocking
	Name	RUN_Obs2_2	
Rec	quirements	Executed in the same task as RUN_Obs2_1 and RUN_Ctrl.	
		Name	VDP_ImplRead2_2
		Туре	DataReadAccess
		Access to	RP_ReceiveData2/ IF_ExchangedData/ DE_ExchangedData
Variable	eDataPrototype	Requirements	Belongs to the same coherency group as RUN_Obs2_1/VDP_ImplRead2_1 and RUN_Ctrl/VDP_ImplWrite

SWC Name	LowerTesterSWC	
	Name	PP_BusSendData
	Туре	PPortPrototype
	Interface	IF_ExchangedData
	ComSpecs	NonqueuedSenderComSpec for dataElement DE_ExchangedData, with initValue Value_Init_BusSend.
DODTE	Requirements	
PORTS		
	Name	RP_BusReceiveData
	Туре	RPortPrototype
	Interface	IF_ExchangedData
	ComSpecs	NonqueuedReceiverComSpec for dataElement DE_ExchangedData, with initValue Value_Init_BusReceive.



	Requirements		
		<u> </u>	
Name P		PP_BusSendEvent	
	Туре	PPortPrototype	
	Interface	IF_ExchangedData	
	ComSpecs	QueuedSenderComS DE_ExchangedEvent	
	Requirements		
	Name	RP_BusReceiveEven	t
	Туре	RPortPrototype	
	Interface	IF_ExchangedData	
	ComSpecs		Spec for dataElement , with queueLength = 2.
	Requirements		
	Name	RUN_LowerTester	
	Requirements		
		Name	VDP_BusWrite
		Туре	DataSendPoint OR DataWriteAccess
		Access to	PP_BusSendData/ IF_ExchangedData/ DE_ExchangedData
		Requirements	
		Name	VDP_BusRead
RUNNABLE ENTITIES	VariableDataPrototype	Туре	DataReceivePoint OR DataReadAccess
		Access to	RP_BusSendData/ IF_ExchangedData/ DE_ExchangedData
		Requirements	
		Name	VDP_BusSend
		Туре	DataSendPoint
		Access to	PP_BusSendEvent/ IF_ExchangedData/ DE_ExchangedEvent
		Requirements	



Name	VDP_BusReceive
Туре	DataReceivePoint
Access to	RP_BusReceiveEvent/ IF_ExchangedData/ DE_ExchangedEvent
Requirements	

#### 6.1.2.4 Mandatory vs. Customizable Parts

In the configuration set, the definition of the queuing attribute of the port must not be changed.

However, the definition of the type of TYP\_Exchanged data along with the init values for all ports as well as the values used in the test cases can be adjusted to the user needs.

### 6.1.3 Test Case Data Types

Test cases are configurable in order to better match requirements from users. They are abstracted from the data types and the values to be sent.

Different data sets can be used to better match user coverage needs. Data sets are defined using equivalence classes method to have a better coverage, as for example, data sets to transmit 8 bits data, 64 bits data, X bits data where X > maximum length of data on the bus (e.g. >8 bytes for CAN)...

List of parameters used by the test cases

Name	Type	Definition	Requirements
Value_Send1	TYP_ExchangedData	First data to	
		transmit.	
Value_Send2	TYP_ExchangedData	Second data to	
		transmit.	
Value_Send3	TYP_ExchangedData	Third data to	
		transmit.	
Value_Init_Send	TYP_ExchangedData	Initial value of	
		Control SWC's	
		port	
Value_Init_Receive1	TYP_ExchangedData	Initial value of	
		observation 1	All data are
		SWC's port	different.
Value_Init_Receive2	TYP_ExchangedData	Initial value of	
		observation 2	
		SWC's port	
Value_Init_BusSend	TYP_ExchangedData	Initial value of	
		Lower Tester's	
		transmission	
		port	
Value_Init_BusReceive	TYP_ExchangedData	Initial value of	
		Lower Tester's	
		reception port	



Timing_MsgOnBus	<user choice=""></user>	Period during	Must be greater
		which an actor	than the time
		waits between	require for a
		two actions.	message to
			appear at least
			once on the bus.

## **Examples of test case data sets:**

#### Test Case Data Set 1

Parameter	Value
TYP_ExchangedData	Unsigned integer 8 bits
Value_Send1	0x5A
Value_Send2	0x96
Value_Send3	0x56
Value_Init_Send	0x7B
Value_Init_Receive1	0xBD
Value_Init_Receive2	0xEB
Value_Init_BusSend	0xE7
Value_Init_BusReceive	0x7D

#### Test Case Data Set 2

Parameter	Value
TYP_ExchangedData	Float 64
Value_Send1	0x0569A65A
Value_Send2	0x2A965A96
Value_Send3	0xA956A956
Value_Init_Send	0xB7BDED7B
Value_Init_Receive1	0x9EDB7EBD
Value_Init_Receive2	0x3BE7D7EB
Value_Init_BusSend	0x1E7BDBE7
Value_Init_BusReceive	0xBEDB7E7D

#### Test Case Data Set 3 – For testing values greater than size limit of CAN messages

Parameter	Value
TYP_ExchangedData	Array Implementation Data Type :
	unsigned integer 8bits[9]
Value_Send1	0x5A965695A
Value_Send2	0x59A965A96
Value_Send3	0x9A956A956
Value_Init_Send	0xEB7BDED7B
Value_Init_Receive1	0x79EDB7EBD
Value_Init_Receive2	0x3BE73D7EB
Value_Init_BusSend	0xDE7EBDBE7
Value_Init_BusReceive	0xBEDBD7E7D



# 6.2 Re-usable Test Steps

None.

### 6.3 Test Cases

## 6.3.1 [ATS\_RTE\_00009] Implicit write and read / data - intra-ECU

Test Objective	Implicit write and read / data – intra-ECU		
ID	ATS_RTE_00009	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00020 ATR: ATR_ATR_00022 ATR: ATR_ATR_00023		
Trace to SWS Item	RTE: SWS_Rte_03571 RTE: SWS_Rte_03573 RTE: SWS_Rte_03744		
Requirements / Reference to Test Environment	ControlSWC and Observation1SWC are required.  The ports ControlSWC.PP_SendData and Observation1SWC.RP_ReceiveData1 are connected.		
Configuration Parameters	Parameters: - Value_Send1 - Value_Send2 - Value_Send3  I-PDU Transmission Mode Timing: EventControlledTiming		
	Implicit read access and implicit write access do not belong to the same coherency group.		
	Hint: The TCPs in Main3 and Main5 require the OS and RTE to be configured such that RUN_Obs1 can preempt RUN_Ctrl. This means in particular that the OS task executing the runnable entity ControlSWC.RUN_Ctrl shall be preemptable. The TCP can be implemented for example with a pair of waitpoints (e.g. RUN_Ctrl send an event which activates RUN_Obs1, and waits with a blocking Rte_Receive that RUN_Obs1 produce another event).		
Summary	Verify that data element with "data" semantics (not queued) written by a sender SWC in an implicit way is read by another receiver SWC running on the same ECU in an implicit way.		
	Ensure implicit semantics is correctly implemented.		
	Test Description:		
	Control starts, does an implicit wr is suspended and Observation st		ovide port then its execution
	Observation starts and reads its rone written by Control. Observation		Data read is the init value and not the es.



	Control resumes, performs two implicit writes and terminates.	
Na a da d	Observation starts and reads the last data written by Observation.	
Needed Adaptation to other Releases		
Pre-conditions	No other runnables than RUN_Ctrl performs a execution of the test case	a write to RP_ReceiveData1 during the
Main Test Execu	ution	
Test Steps		Pass Criteria
Step 1	[CP]	
	RUN_Ctrl starts	
Step 2	[RUN <run_ctrl>]</run_ctrl>	
	RUN_Ctrl executes Rte_IWrite on VDP_ImplWrite with value Value_Send1.	
	[SWS_Rte_03744]	
Step 3	[CP]	
	RUN_Ctrl is suspended. [SWS_Rte_03571]	
	RUN_Obs1 starts	
Step 4	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>
	RUN_Obs1 executes Rte_IRead on VDP_ImpIRead1.	Read data is initial value  Value_Init_Receive1.  [SWS_Rte_03571]
Step 5	[CP]	
	RUN_Obs1 terminates.	
	RUN_Ctrl is resumed	
Step 6	[RUN <run_ctrl>]</run_ctrl>	
	RUN_Ctrl executes Rte_IWrite on VDP_ImplWrite with value Value_Send2. [SWS_Rte_03573]	
Step 7	[RUN <run_ctrl>]</run_ctrl>	
	RUN_Ctrl executes Rte_IWrite on VDP_ImplWrite with value Value_Send3. [SWS_Rte_03573]	
Step 8	[RUN <run_ctrl>]</run_ctrl>	
	RUN_Ctrl terminates. [SWS_Rte_03571]	
Step 9	[CP]	
	DUNI Ohad starts	
Stop 10	RUN_Obs1 starts.	FRUNZBUN Obetst
Step 10	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>



	RUN_Obs1 executes Rte_IRead from VDP_ImpIRead1.	Read data is <i>Value_Send3.</i>
		[SWS_Rte_03571], [SWS_Rte_03573]
Step 11	[RUN <run_obs1>]</run_obs1>	
	RUN_Obs1 terminates	
Post- conditions	Run_Ctrl and Run_Obs are terminated	

# 6.3.2 [ATS\_RTE\_00010] Explicit write and read / data – intra-ECU

Test Objective	Explicit write and read / data – intra-ECU		
ID	ATS_RTE_00010	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
	ATR: ATR_ATR_00020 ATR: ATR_ATR_00022 ATR: ATR_ATR_00023		
Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01091 RTE: SWS_Rte_02635 RTE: SWS_Rte_06011 RTE: SWS_Rte_06016		
Requirements / Reference to Test Environment	Required SWC: ControlSWC and Observation1SWC. Test Environment architecture: (see 1:1 intra-ECU test cases) port ControlSWC.PP_SendData connected to port Observation1SWC.RP_ReceiveData1.		
	Parameters used:  • Value_Send1  • Value_Send2  I-PDU Transmission Mode Timing: EventControlledTiming  Hint: The TCPs in Main3 and Main5 require the OS and RTE to be configured such that RUN_Obs1 can preempt RUN_Ctrl. This means in particular that the OS task executing the runnable entity ControlSWC.RUN_Ctrl shall be preemptable. The TCP can be implemented for example with a pair of waitpoints (e.g. RUN_Ctrl send an event which activates RUN_Obs1, and waits with a blocking Rte_Receive that RUN_Obs1 produce another event).		
Summary	Verify that data element with "data" semantics (not queued) written by a sender SWC in an explicit way is read by another receiver SWC running on the same ECU in an explicit way.  Ensure explicit semantics is correctly implemented.  Test description:  Control starts, does an explicit write with Value_Send1 on the provided port then its execution is suspended and Observation starts.		



	Observation reads its required port. Data read is not the init value but the one written by Control. Observation terminates.		
	Control resumes, performs another explicit write with Value_Send2 and terminates		
	Observation starts and reads the last data writhe new value written by Control. Observation		
Needed Adaptation to other Releases			
	Pre 1: The ControlSWC runnable contains the corresponding DataSendPoint. Pre 2: No other runnables than RUN_Ctrl performs a write to RP_ReceiveData1 during the execution of the test case. Pre 3: RTE_Read call is non-blocking (i.e. Observation1SWC contains DataReceivePoint referencing the DataElementPrototype for which the API is being generated, but no WaitPoint referencing the DataReceivePoint),		
Main Test Exec	ution		
Test Steps		Pass Criteria	
Step 1	[CP]  RUN_Ctrl starts.		
Step 2	[RUN <run_ctrl>]</run_ctrl>		
•	RUN_Ctrl executes Rte_Write on VDP_ExplWrite with value Value_Send1.  [SWS_Rte_01071], [SWS_Rte_06016]		
Step 3	[CP]		
	RUN_Ctrl is suspended after Rte_Write [SWS_Rte_02635]  RUN_Obs1 starts.		
Step 4	[RUN <run_obs1>]</run_obs1>	[RUN <run obs1="">]</run>	
Step 4	[RUN <run_uds1>]</run_uds1>	[KUN <kun_ods1>]</kun_ods1>	
	RUN_Obs1 executes Rte_Read on VDP_ExplRead1. [SWS_Rte_01091], [SWS_Rte_06011]	Read data is the value <i>Value_Send1</i> .	
Step 5	[CP]		
	RUN_Obs1 terminates.		
	RUN_Ctrl is resumed		
Step 6	[RUN <run_ctrl>]</run_ctrl>		
	RUN_Ctrl executes Rte_Write on VDP_ExplWrite with value Value_Send2. [SWS_Rte_01071], [WS_Rte_06016]		
Step 7	[RUN <run_ctrl>]</run_ctrl>		
	RUN_Ctrl terminates.		
Step 8	[CP]		
	RUN_Obs1 starts.		



Step 9	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>
	RUN_Obs1 executes Rte_Read on VDP_ExplRead1. [SWS_Rte_01091], [SWS_Rte_06011]	Read data is the value Value_Send2.
Step 10	[RUN <run_obs1>]</run_obs1>	
	RUN_Obs1 terminates	
Post- conditions	Run_Ctrl and Run_Obs terminated	

## 6.3.3 [ATS\_RTE\_00011] Send and receive / event - intra-ECU

Test Objective	Send and receive / event – intra-ECU		
ID	ATS_RTE_00011	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
on Acceptance Test Document	ATR: ATR_ATR_00020 ATR: ATR_ATR_00022 ATR: ATR_ATR_00023		
Trace to SWS Item	RTE: SWS_Rte_01072 RTE: SWS_Rte_01092 RTE: SWS_Rte_02633		
Requirements / Reference to Test Environment	Required SWC: ControlSWC and Observation1SWC. Test Environment architecture: (see 1:1 intra-ECU test cases) port ControlSWC.PP_SendEvent connected to port Observation1SWC.RP_ReceiveEvent1.		
Configuration Parameters	Parameters used:  • Value_Send1  • Value_Send2  • Value_Send3		
Summary	I-PDU Transmission Mode Timing: EventControlledTiming  Verify that two different data elements with "event" semantics (queued) sent one after the other by a sender SWC are received in the same order by another receiver SWC running on the same ECU.  Test Desciption  Control starts, sends three events then it terminates.  The third event will be discarded as queue is full (queue length set to 2).  Observation starts and asks for the reception of a first event from its required port. Event value is the first one send by Control.  Observation asks for the reception of a second event from its required port. Event value is the second one sent by Control.  Observation asks for the reception of a third event from its required port. No more events have been received.		



Noodod		
Needed Adaptation to		
other Releases		
Pre-conditions	None	
Main Test Execu	ution	
Test Steps		Pass Criteria
Step 1	[CP]	
	RUN_Ctrl starts.	
Step 2	[RUN <run_ctrl>]</run_ctrl>	
	RUN_Ctrl executes Rte_Send on VDP_Send with value Value_Send1.	
Ctom 2	[SWS_Rte_01072], [SWS_Rte_02633]	
Step 3	[RUN <run_ctrl>]</run_ctrl>	
	RUN_Ctrl executes Rte_Send on VDP_Send with value Value_Send2.	
	[SWS_Rte_01072], [SWS_Rte_02633]	
Step 4	[RUN <run_ctrl>]</run_ctrl>	[RUN <run_ctrl>]</run_ctrl>
		RTE_Send returns RTE_E_LIMIT, the event Value_send3 has been discarded as queue is full (queue length set to 2).
Step 5	[RUN <run_ctrl>]</run_ctrl>	,
otep o		
	RUN_Ctrl terminates	
Step 6	[CP]	
_	RUN_Obs1 is started	
Step 7	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>
	RUN_Obs1 executes Rte_Receive on VDP_Receive1.	Event read is <i>Value_Send1</i> .
	[SWS_Rte_01092]	
Step 8	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>
	RUN_Obs1 executes Rte_Receive on VDP_Receive1.	Event read is <i>Value_Send2.</i>
	[SWS_Rte_01092]	
Step 9	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>
	VDP_Receive1.	Status returned is RTE_E_NO_DATA.
	[SWS_Rte_01092]	
Step 10	[RUN <run_obs1>]</run_obs1>	



	RUN_Obs1 terminates	
Post- conditions	Run_Ctrl and Run_Obs terminated	

# 6.3.4 [ATS\_RTE\_00012] Implicit write / data – inter-ECU

ATS_RTE_00012  ATS_RTE_00012  AUTOSAR Releases  A.0.3 4.1.1 4.2.1 4.2.2  Releases  Trace to Requirement on Acceptance Test Document  Trace to SWS Item  RTE: SWS_Rte_03571 RTE: SWS_Rte_03573  Requirements / Reference to Test Environment  The ports ControlSWC.PP_SendData and LowerTesterSWC.RP_BusReceiveData are connected.  Bus tool to emulate ECU executing LowerTesterSWC.	Test Objective	Implicit write / data – inter-ECU		
Affected Modules Trace to Requirement on Acceptance Test Document Trace to SWS Item RTE: SWS_Rte_03571 RTE: SWS_Rte_03573 Requirements / RTE: SWS_Rte_03573 Requirements / Reference to Test				
Trace to Requirement on Acceptance Test Document  Trace to SWS Item RTE: SWS_Rte_03571 RTE: SWS_Rte_03573  Requirements / Reference to Test Environment  The ports ControlSWC.PP_SendData and LowerTesterSWC.RP_BusReceiveData are connected.  Bus tool to emulate ECU executing LowerTesterSWC.  Parameters  Parameters  - Value_Send1 - Value_Send2	ID	ATS_RTE_00012		4.0.3 4.1.1 4.2.1 4.2.2
Requirement on Acceptance Test Document  Trace to SWS Item RTE: SWS_Rte_03571 RTE: SWS_Rte_03573  Requirements / ControlSWC and LowerTesterSWC are required.  Reference to Test The ports ControlSWC.PP_SendData and LowerTesterSWC.RP_BusReceiveData are connected.  Bus tool to emulate ECU executing LowerTesterSWC.  Configuration Parameters Parameters - Value_Send1 - Value_Send2	Affected Modules	RTE	State	reviewed
RTE: SWS_Rte_03573  Requirements / ControlSWC and LowerTesterSWC are required.  Reference to Test	Trace to Requirement on Acceptance Test Document			
Reference to Test Environment  Bus tool to emulate ECU executing LowerTesterSWC.  Parameters  Parameters  The ports ControlSWC.PP_SendData and LowerTesterSWC.RP_BusReceiveData are connected.  Bus tool to emulate ECU executing LowerTesterSWC.  Parameters: - Value_Send1 - Value_Send2	Trace to SWS Item			
- Value_Send1 - Value_Send2	Requirements / Reference to Test Environment	The ports ControlSWC.PP_SendData and LowerTesterSWC.RP_BusReceiveData are connected.		
I-PDU Transmission Mode Timing: - CyclicTiming (cycle time shorter than Timing_MsgOnBus)  Implicit read access and implicit write access do not belong to the same coherenc group.	Configuration Parameters	<ul> <li>Value_Send1</li> <li>Value_Send2</li> <li>Timing_MsgOnBus</li> <li>I-PDU Transmission Mode Timing:</li> <li>CyclicTiming (cycle time shorter than Timing_MsgOnBus)</li> <li>Implicit read access and implicit write access do not belong to the same coherency</li> </ul>		
bus if an implicit write is realized by a sender SWC connected to another receiver SWC running on a different ECU.  Test Description  Lower Tester is started and checks the bus.  Control starts, does an implicit write on its provide port and waits for a given amound time. During this time, Lower Tester must not detect any message from Control with the written data.  Control does a second implicit write with a different value and waits for a given	Summary	Verify that a data element with "data" semantic (not queued) is transmitted on the bus if an implicit write is realized by a sender SWC connected to another receiver SWC running on a different ECU.  Test Description  Lower Tester is started and checks the bus.  Control starts, does an implicit write on its provide port and waits for a given amount of time. During this time, Lower Tester must not detect any message from Control with the written data.  Control does a second implicit write with a different value and waits for a given amount of time. During this time, Lower Tester must not detect any message from Control containing the latest written data.  Control terminates and Lower Tester must detect a message from Control		
Needed	Needed Adaptation to			



	No other runnables than RUN_Ctrl performs a write to RP_BusReceiveData during the execution of the test case.		
Main Test Execution			
Test Steps		Pass Criteria	
Step 1	[CP]		
	Lower Tester starts.		
Step 2	[CP]		
	RUN Ctrl starts.		
Step 3	[RUN <run_ctrl>]</run_ctrl>		
	RUN_Ctrl executes Rte_IWrite on		
	VDP_ImplWrite with value Value_Send1. [SWS_Rte_03573]		
Step 4	[RUN <run_ctrl>]</run_ctrl>	[LT]	
	l	L	
	WAIT for <i>Timing_MsgOnBus</i> ms	WHILE WAITING, no message from RUN_Ctrl with data Value_Send1	
		found on the bus.	
Step 5	[RUN <run_ctrl>]</run_ctrl>		
	DIAL OLI DI DALLI		
	RUN_Ctrl executes Rte_IWrite on VDP_ImplWrite with value Value_Send2.		
	[SWS_Rte_03573]		
Step 6	[LT]		
	Lower Tester reads the bus for a message		
	from RUN_Ctrl containing value		
	Value_Send2.		
Step 7	[RUN <run_ctrl>]</run_ctrl>		
	RUN_Ctrl terminates.		
Step 8	[CP]		
	WAIT for <i>Timing_MsgOnBus</i> ms.	L	
Step 9		[LT]	
		A message from RUN_Ctrl containing	
		value Value_Send2 was available on	
		the bus.	
		[SWS_Rte_03571],	
		[SWS_Rte_03573]	
Post-	RUN_Ctrl is terminated		
conditions			

# 6.3.5 [ATS\_RTE\_00013] Explicit write / data – inter-ECU



ID	ATS_RTE_00013	AUTOSAR	4.0.3 4.1.1 4.2.1 4.2.2
		Releases	
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00020		
Trace to SWS Item	RTE: SWS_Rte_01071		
Requirements / Reference to Test Environment	ControlSWC and LowerTesterSWC are required.  The ports ControlSWC.PP_SendData and LowerTesterSWC.RP_BusReceiveData are connected.		
	Bus tool to emulate ECU executir	ng LowerTes	sterSWC.
Configuration Parameters	Parameters: - Value_Send1 - Value_Send2 - Timing_MsgOnBus  I-PDU Transmission Mode Timing: - EventControlledTiming - CyclicTiming (cycle time shorter than Timing_MsgOnBus)		
Summary	Verify that a data element with "data" semantics (not queued) is transmitted on the bus if an explicit write is realized by a sender SWC connected to another receiver SWC running on a different ECU.  Test Description  Lower Tester is started and checks the bus.  Control starts, does an explicit write on its provide port and waits for a given amount of time. During this time, Lower Tester must detect a message from Control containing the latest written data.  Control does a second explicit write with a different value and terminates. Lower Tester must detect a message from Control containing the latest written data		
Needed Adaptation to other Releases	restorment detect a message nom control containing the latest written data		
Pre-conditions	No other runnables than RUN_Ctrl performs a write to RP_BusReceiveData during the execution of the test case.		
Main Test Execu			
Test Steps	Pass Criteria		
Step 1	[CP]		
	Lower Tester starts.		
Step 2	[CP]  RUN_Ctrl starts.		
Step 3	[RUN <run_ctrl>]  RUN_Ctrl executes Rte_Write on VDP_ExplWrite with value Value</run_ctrl>		



Step 4	[RUN <run_ctrl>]</run_ctrl>	[LT]
	WAIT for <i>Timing_MsgOnBus</i> ms.	WHILE WAITING, a message from RUN_Ctrl containing value Value_Send1 is available on the bus.
Step 5	[RUN <run_ctrl>]</run_ctrl>	
	RUN_Ctrl executes Rte_Write on VDP_ExplWrite with value Value_Send2.	
Step 6	[SWS_Rte_01071]	
Step 0	[21]	
	Lower Tester reads the bus for a message from RUN_Ctrl containing value Value_Send2.	
Step 7	[RUN <run_ctrl>]</run_ctrl>	
	RUN_Ctrl terminates.	
Step 8	[CP]	
	WAIT for <i>Timing_MsgOnBus</i> ms.	
Step 9		[LT]
		A message from <i>RUN_Ctrl</i> containing value <i>Value_Send2</i> was available on the bus.
Post-	RUN_Ctrl is terminated	
conditions		

## 6.3.6 [ATS\_RTE\_00014] Send / events - inter-ECU

Test Objective	Send / events – inter-ECU		
ID	ATS_RTE_00014	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00020		
Trace to SWS Item	RTE: SWS_Rte_01072 RTE: SWS_Rte_07827		
Requirements / Reference to Test Environment	ControlSWC and LowerTesterSWC are required.  The ports ControlSWC.PP_SendEvent and LowerTesterSWC.RP_BusReceiveEvent are connected.  Bus tool to emulate ECU executing LowerTesterSWC.		
Configuration Parameters	Parameters: - Value_Send1 - Timing_MsgOnBus		



	I-PDU Transmission Mode Timing: - EventControlledTiming		
	- CyclicTiming (cycle time shorter than Timing_MsgOnBus)		
Summary	Verify that a data element with "event" semantic (queued) is transmitted on the bus if a send is realized by a sender SWC connected to another receiver SWC running on a different ECU		
	Test Description  Control starts, performs a send of an event then terminates.		
	Lower Tester must detect a message from Control containing the latest written event.		
Needed Adaptation to other Releases			
Pre-conditions	No other runnables than RUN_Ctrl performs a the execution of the test case.	a write to RP_BusReceiveEvent during	
Main Test Exec	ution		
Test Steps		Pass Criteria	
Step 1	[CP]		
	Lower Tester starts		
Step 2	[CP]		
	RUN_Ctrl starts		
Step 3	[RUN <run_ctrl>]</run_ctrl>		
	RUN_Ctrl executes Rte_Send on VDP_Send with value Value_Send1.		
Step 4	[LT]		
	Lower Tester reads the bus for a message from RUN_Ctrl containing value Value_Send1.		
Step 5	[RUN <run_ctrl>]</run_ctrl>		
	RUN_Ctrl terminates.		
Step 6	[CP]		
	WAIT for <i>Timing_MsgOnBus</i> ms.		
Step 7		[LT]	
		A message from <i>RUN_Ctrl</i> containing value <i>Value_Send1</i> was available on the bus.	
Post- conditions	RUN_Ctrl is terminated		

# 6.3.7 [ATS\_RTE\_00015] Implicit read / data – inter-ECU

Test Objective	Implicit read / data – inter-ECU



ID	ATS_RTE_00015	AUTOSAR	4.0.3 4.1.1 4.2.1 4.2.2
	/110_1112_00010	Releases	1.0.0  1.1.1  1.2.1  1.2.2
Affected Modules	RTE	State	reviewed
Trace to	ATR: ATR_ATR_00020	-	
Requirement on Acceptance			
Test Document			
Trace to SWS Item	RTE: SWS_Rte_06011		
Reference	Observation1SWC and LowerTesterSWC are required.		
to Test Environment	The ports Observation1SWC.RP_ReceiveData1 and LowerTesterSWC.PP_BusSendData are connected.		
	Bus tool to emulate ECU executir	ng sender S\	NC.
Configuration Parameters	Parameters: - Value_Send1 - Value_Send2 - Value_Send3 - Timing_MsgOnBus		
	I-PDU Transmission Mode Timing: - EventControlledTiming - CyclicTiming (cycle time shorter than Timing_MsgOnBus)		
	Implicit read access and implicit v group.	vrite access	do not belong to the same coherency
Summary	Verify that a data element with "data" semantic transmitted via the bus is read by one receiver SWC performing implicit reception if the receiver SWC is connected to another sender SWC running on a different ECU.		
	Ensure implicit semantic is correctly implemented.		
	Test Description		
	Observation starts and waits for a given amount of time. During this time Lower Tester send a message on the bus to Observation containing a first data.		
	After the wait, Observation performs an implicit read. Data read is init value.		
Needed	Observation then terminates.		
Adaptation to other Releases			
Pre-conditions	No other runnables than RUN_LowerTester performs a write to RP_ReceiveData1 during the execution of the test case.		
Main Test Execu			
Test Steps			Pass Criteria
Step 1	[CP]		
	RUN_Obs1 starts.		
Step 2	[RUN <run_obs1>]</run_obs1>		



	L=	1
	WAIT till <i>Lower Tester</i> performs step Main 3.	
	WHILE WAITING, DO nothing	
Step 3	[LT]	
	Lower Tester sends on the bus a message to RP_ReceiveData1 with Value_Send1.	
Step 4	[RUN <run_obs1>]</run_obs1>	
	WAIT for <i>Timing_MsgOnBus</i> ms.	
	WHILE WAITING, DO nothing	
Step 5	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>
	RUN_Obs1 executes Rte_IRead on VDP_ImplRead1.	Data read is Value_Init_Receive1.
Step 6	[RUN <run_obs1>]</run_obs1>	
	RUN_Obs1 terminates	
Step 7		
	Lower Tester sends on the bus a message to RP_ReceiveData1 with Value_Send2.	
Step 8	[LT]	
	WAIT for <i>Timing_MsgOnBus</i> ms.	
	WHILE WAITING, DO nothing	
Step 9	[LT]	
	Lower Tester sends on the bus a message to RP_ReceiveData1 with Value_Send3.	
Step 10	[CP]	
	WAIT for <i>Timing_MsgOnBus</i> ms.	
	WHILE WAITING, DO nothing	
Step 11	[CP]  RUN_Obs1 starts.	
Step 12	_	[RUN <run_obs1>]</run_obs1>
	RUN_Obs1 executes Rte_IRead on	Data read is <i>Value_Send3</i> .
Stop 42	VDP_ImplRead1.	
Step 13	[RUN <run_obs1>]</run_obs1>	
	RUN_Obs1 terminates.	
Post- conditions	RUN_Obs1 is terminated	



## 6.3.8 [ATS\_RTE\_00016] Explicit read / data - inter-ECU

Took Ohiostine	Evaligit rood / data : :-t ECU			
-	Explicit read / data – inter-ECU			
ID	ATS_RTE_00016	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2	
Affected Modules	RTE	State	reviewed	
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00020			
Trace to SWS Item	RTE: SWS_Rte_01091			
Requirements / Reference to Test Environment	Observation1SWC and LowerTesterSWC are required.  The ports Observation1SWC.RP_ReceiveData1 and LowerTesterSWC.PP_BusSendData are connected.			
	Bus tool to emulate ECU executing sender SWC.			
Configuration Parameters	Parameters: - Value_Send1 - Value_Send2 - Value_Send3 - Timing_MsgOnBus			
	I-PDU Transmission Mode Timing: - EventControlledTiming - CyclicTiming (cycle time shorter than Timing_MsgOnBus)			
Summary	Verify that a data element with "data" semantic transmitted via the bus is read by one receiver SWC performing explicit reception if the receiver SWC is connected to another sender SWC running on a different ECU.			
	Ensure explicit semantic is correctly implemented.			
	Test Description			
	Observation starts and waits for Lower Tester to send a message on the bus to Observation containing a first data.			
	After the wait, Observation performs an explicit read. Data read is the latest value send by Lower tester.  Observation then terminates.			
	Observation starts, does an expli value send by Lower tester.	cit read on it	s require port. Data read is the latest	
	Observation waits for Lower Test Observation containing two differ		vo messages on the bus to	
	After the wait, Observation perfor send by Lower tester.	ms an explic	cit read. Data read is the latest value	
Needed Adaptation to other Releases				



Pre-conditions No other runnables than RUN_LowerTester performs a write to RP_ReceiveData1 during the execution of the test case.				
Main Test Execution				
Test Steps		Pass Criteria		
Step 1	[CP]			
	RUN_Obs1 starts.			
Step 2	[RUN <run_obs1>] WAIT till Lower Tester performs step Main 3.</run_obs1>			
	WHILE WAITING, DO nothing			
Step 3	[LT]			
	Lower Tester sends on the bus a message to RP_ReceiveData1 with Value_Send1.			
Step 4	[RUN <run_obs1>]</run_obs1>			
	WAIT for <i>Timing_MsgOnBus</i> ms.			
	WHILE WAITING, DO nothing			
Step 5	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>		
	RUN_Obs1 executes Rte_Read on VDP_ExplRead1	Data read is <i>Value_Send1</i>		
Step 6	[RUN <run_obs1>]</run_obs1>			
	RUN_Obs1 terminates			
Step 7	[CP]			
	RUN_Obs1 starts.			
Step 8	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>		
	RUN_Obs1 executes Rte_Read on VDP_ExplRead1	Data read is <i>Value_Send1.</i>		
Step 9	[RUN <run_obs1>]</run_obs1>			
	WAIT till Lower Tester performs step Main 12.			
	WHILE WAITING, DO nothing			
Step 10	[LT]			
	Lower Tester sends on the bus a message to RP_ReceiveData1 with Value_Send2.			
Step 11	[LT]			
	WAIT for <i>Timing_MsgOnBus</i> ms.			
	WHILE WAITING, DO nothing			
Step 12	[LT]			



	Lower Tester sends on the bus a message to RP_ReceiveData1 with Value_Send3.	
Step 13	[RUN <run_obs1>]</run_obs1>	
	WAIT for <i>Timing_MsgOnBus</i> ms.	
	WHILE WAITING, DO nothing	
Step 14	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>
	RUN_Obs1 executes Rte_Read on VDP_ExplRead1	Data read is <i>Value_Send3</i> .
Step 15	[RUN <run_obs1>]</run_obs1>	
	RUN_Obs1 terminates.	
Post- conditions	RUN_Obs1 is terminated	

#### 6.3.9 [ATS\_RTE\_00017] Receive / events - inter-ECU

Test Objective	Receive / events – inter-ECU		
ID	ATS_RTE_00017	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00020		
Trace to SWS Item	RTE: SWS_Rte_01092		
Requirements / Reference to Test Environment	Observation1SWC and LowerTesterSWC are required.  The ports Observation1SWC.RP_ReceiveEvent1 and LowerTesterSWC.PP_BusSendEvent are connected.  Bus tool to emulate ECU executing sender SWC.		
Configuration Parameters	Parameters: - Value_Send1 - Value_Send2 - Value_Send3 - Timing_MsgOnBus  I-PDU Transmission Mode Timing: - EventControlledTiming - CyclicTiming (cycle time shorter than Timing_MsgOnBus)		
Summary	Verify that two data elements with "event" semantic (queued) transmitted on the bus one after another are read in the same order by a receiver SWC connected to another sender SWC running on a different ECU.  Test Description:		



	Lower Tester sends three messages on the bus to Observation with different event values.		
	The third event will be discarded as queue is full (queue length set to 2).  Observation starts and asks for the reception of a first event from its require port.  Event value is the first one send by Lower Tester.		
	Observation asks for the reception of a secon value is the second one send by Lower Teste		
	Observation asks for the reception of a third e event has been received.	event from its require port. No more	
Needed Adaptation to other Releases			
Pre-conditions	No other runnables than RUN_LowerTester p during the execution of the test case	erforms a write to RP_ReceiveEvent1	
Main Test Exec	ution		
Test Steps		Pass Criteria	
Step 1	[LT]		
	Lower Tester sends on the bus a message to RP_ReceiveEvent1 with Value_Send1.		
Step 2	[LT]		
	WAIT for <i>Timing_MsgOnBus</i> ms.		
	WHILE WAITING, DO nothing		
Step 3	[LT]		
	Lower Tester sends on the bus a message to RP_ReceiveEvent1 with Value_Send2.		
Step 4	[LT]		
	WAIT for <i>Timing_MsgOnBus</i> ms.		
	WHILE WAITING, DO nothing		
Step 5	[LT]		
	Lower Tester sends on the bus a message to RP_ReceiveEvent1 with Value_Send3.		
Step 6	[LT]		
	WAIT for <i>Timing_MsgOnBus</i> ms.		
	WHILE WAITING, DO nothing		
Step 7	[CP]		
	RUN_Obs1 is started		
Step 8	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>	
	RUN_Obs1 executes Rte_Receive on VDP_Receive1.	Data read is <i>Value_Send1.</i>	



Step 9	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>
	RUN_Obs1 executes Rte_Receive on VDP_Receive1.	Data read is <i>Value_Send</i> 2.
Step 10	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>
	RUN_Obs1 executes Rte_Receive on VDP_Receive1.	Status returned is RTE_E_NO_DATA
Step 11	[RUN <run_obs1>]</run_obs1>	
	RUN_Obs1 terminates	
Post- conditions	RUN_Obs1 is terminated	

#### 6.3.10 [ATS\_RTE\_00018] 1:n reception from inter-ECU

Test Objective	1:n reception from inter-ECU		
ID	ATS_RTE_00018	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00020 ATR: ATR_ATR_00022		
Trace to SWS Item			
Requirements / Reference to Test Environment	Observation1SWC, Observation2SWC and LowerTesterSWC are required.  The ports Observation1SWC.RP_ReceiveData1 and LowerTesterSWC.PP_BusSendData are connected.  The ports Observation2SWC.RP_ReceiveData2 and LowerTesterSWC.PP_BusSendData are connected.		
Configuration Parameters	Bus tool to emulate ECU executing sender SWC.  Parameters: - Value_Send1 - Timing_MsgOnBus  I-PDU Transmission Mode Timing: - EventControlledTiming - CyclicTiming (cycle time shorter than Timing_MsgOnBus)		
Summary	Ensure that a data received from the bus is read by two different receiver SWCs running on the same ECU and connected to the same sender SWC running on another ECU.  Test Description:  Lower Tester to send a message on the bus to Observations containing a first data.  Both Observations start again and perform a read on their require port. Data read are the value send by Lower Tester.		



	T		
	It is recommended that Observations use a different read method, <i>ie.</i> one uses explicit read and the other one implicit read.		
Needed	explicit read and the other one implicit read.		
Adaptation to			
other Releases			
Pre-conditions	No other runnables than RUN_LowerTester p	erforms a write to RP_ReceiveData1	
Main Test Exec	during the execution of the test case		
Test Steps	ution	Pass Criteria	
Step 1	[LT]	rass Cilleria	
Olep 1	[E-1]		
	Lower Tester sends on the bus a message to		
	RP_ReceiveData1 with Value_Send1.		
Step 2	[CP]		
	WAIT for <i>Timing_MsgOnBus</i> ms.		
	WAIT for Timing_wayOnbus ms.		
	WHILE WAITING, DO nothing		
Step 3	[CP]		
	DIM OF ALL ALL		
Cton 4	RUN_Obs1 is started	TRUN RUN Ob 4. 1	
Step 4	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>	
	RUN_Obs1 reads its port RP_ReceiveData1.	Data read is <i>Value Send1</i>	
	- ' -	_	
	(landementer obside whether read is explicit		
	(Implementer choice whether read is explicit or implicit:		
	RUN_Obs1 executes Rte_Read on		
	VDP_ExplRead1.		
	OR		
	RUN_Obs1 executes Rte_IRead on		
	VDP_implRead1.		
	b		
Step 5	[RUN <run_obs1>]</run_obs1>		
	RUN_Obs1 terminates		
Step 6	[CP]		
	RUN_Obs2_1 is started		
Step 7	[RUN <run_obs2_1>]</run_obs2_1>	[RUN <run_obs2_1>]</run_obs2_1>	
		[	
	RUN_Obs2.1 reads its port	Data read is <i>Value_Send1</i>	
	RP_ReceiveData2.		



	(Implementer choice whether read is explicit or implicit:	
	RUN_Obs2_1 executes Rte_Read on VDP_ExplRead2_1.	
	OR	
	RUN_Obs2_1 executes Rte_IRead on VDP_ImplRead2_1.	
	)	
Step 8	[RUN <run_obs2_1>]</run_obs2_1>	
	RUN_Obs2_1 terminates	
Post- conditions	Run_Obs1 and RUN_Obs2.1 are terminated	

#### 6.3.11 [ATS\_RTE\_00019] 1:n transmission to intra-ECU and inter-ECU

Test Objective	1:n transmission to intra-ECU and inter-ECU		
ID	ATS_RTE_00019	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Requirement on Acceptance Test Document	ATR: ATR_ATR_00020 ATR: ATR_ATR_00022		
Trace to SWS Item			
Reference to Test Environment	ControlSWC, Observation1SWC and LowerTesterSWC are required.  The ports Observation1SWC.RP_ReceiveData1 and ControlSWC.PP_SendData are connected.  The ports LowerTesterSWC.PP_BusReceiveData and ControlSWC.PP_SendData are connected.  Bus tool to emulate ECU executing sender SWC.		
Configuration Parameters	Parameters: - Value_Send1 - Timing_MsgOnBus  I-PDU Transmission Mode Timing: - EventControlledTiming		
Summary		e same ECU	connected to two different receiver I and on another ECU is correctly vide port then terminates.



	Observation start, performs a read on its require port. Data read is the value send by Control.		
	Lower Tester must detect a message from Control containing the written data		
Needed Adaptation to other Releases			
Pre-conditions	No other runnables than RUN_Ctrl performs a RP_BusReceiveData during the execution of		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[CP]		
	RUN_Ctrl starts.		
Step 2	[RUN <run_ctrl>]</run_ctrl>		
	RUN_Ctrl writes its port PP_SendData value Value_Send1.		
	(Implementer choice whether write is explicit or implicit:		
	RUN_Ctrl executes Rte_Write on VDP_ExplWrite.		
	OR		
	RUN_Ctrl executes Rte_IWrite on VDP_ImplWrite.		
	b		
Step 3	[RUN <run_ctrl>]</run_ctrl>		
	RUN_Ctrl terminates		
Step 4	[CP]		
	RUN_Obs1 is started		
Step 5	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>	
	RUN_Obs1 reads its port RP_ReceiveData1.	Data read is <i>Value_Send1</i>	
	(Implementer choice whether read is explicit or implicit:		
	RUN_Obs1 executes Rte_Read on VDP_ExplRead1.		
	OR		



	RUN_Obs1 executes Rte_IRead on VDP_impIRead1.	
Step 6	[RUN <run_obs1>]  RUN Obs1 terminates</run_obs1>	
Step 7	[ <b>CP]</b> WAIT for <i>Timing_MsgOnBus</i> ms	[LT]  WHILE WAITING, a message from  RUN_Ctrl containing value  Value_Send1 is available on the bus.
Post- conditions	RUN_Ctrl and RUN_Obs1 are terminated.	

#### 6.3.12 [ATS\_RTE\_00020] Init value, Never received status, and valid 1 to 2 write

	1		
	Init value, Never received status, and valid 1 to 2 write		
ID	ATS_RTE_00020	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Requirement	ATR: ATR_ATR_00020 ATR: ATR_ATR_00022 ATR: ATR_ATR_00026  RTE: SWS_Rte_06010		
Item	RTE: SWS_Rte_07644		
Requirements / Reference to Test Environment	ControlSWC, Observation1SWC and Observation2SWC are required.  The ports Observation1SWC.RP_ReceiveData1 and ControlSWC.PP_SendData are connected.  The ports Observation2SWC.RP_ReceiveData2 and ControlSWC.PP_SendData are connected.		
Configuration Parameters	Parameters: - Value_Send1 I-PDU Transmission Mode Timing: - EventControlledTiming		
Summary	Verify that when a valid init value is configured and no data have been transmitted then two receiver SWCs connected to the same sender SWC, performing respectively an implicit reception and an explicit reception, will read the init value and get the status NEVER_RECEIVED.  Then when the sender SWC performs a write with a valid data, two receiver SWCs connected to the sender SWC, performing respectively an implicit reception and an explicit reception, will read the transmitted data.  Test Description  Both Observations start, perform a read and their require ports. Data read are the initial values. Both Observations then terminate.		



	Control starts, does a write on its provide port then terminates.	
	Both Observations start again and perform a read on their require port. Data read are the value send by Control.	
Needed Adaptation to other Releases		
Pre-conditions	No other runnables than RUN_Ctrl performs a ReceiveData2 during the execution of the test	
Main Test Execu	!	
Test Steps		Pass Criteria
Step 1	[CP]	
	RUN_Obs1 starts	
Step 2	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>
	RUN_Obs1 executes Rte_IRead on VDP_ImplRead1	Data read is Value_Init_Receive1
Step 3	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>
	RUN_Obs1 executes Rte_IStatus on VDP_ImplRead1	Status returned is  RTE_E_NEVER_RECEIVED
Step 4	[RUN <run_obs1>]</run_obs1>	
01 5	Run_Obs1 terminates	
Step 5	[CP]	
	RUN_Obs2_1 starts	
Step 6	[RUN <run_obs2_1>]</run_obs2_1>	[RUN <run_obs2_1>]</run_obs2_1>
	RUN_Obs2_1 executes Rte_Read on VDP_ExpIRead2_1.	Data read is Value_Init_Receive2.
		Status returned is RTE_E_NEVER_RECEIVED
Step 7	[RUN <run_obs2_1>]</run_obs2_1>	
	DUN Obes 1 terminates	
Step 8	RUN_Obs2_1 terminates [CP]	
Otep 0	[6,1]	
	RUN_Ctrl starts	
Step 9	[RUN <run_ctrl>]</run_ctrl>	
	RUN_Ctrl writes its port PP_SendData value Value_Send1.	
	(Implementer choice whether write is explicit or implicit:	
	RUN_Ctrl executes Rte_Write on VDP_ExplWrite.	
	l .	



	OR	1
	RUN_Ctrl executes Rte_IWrite on VDP_ImplWrite.	
Step 10	[RUN <run_ctrl>]</run_ctrl>	
·	RUN_Ctrl terminates	
Step 11	[CP]	
	RUN_Obs1 starts	
Step 12	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>
	RUN_Obs1 executes Rte_IRead on VDP_ImplRead1	Data read is Value_Send1
Step 13	[RUN <run_obs1>]</run_obs1>	
	Run_Obs1 terminates	
Step 14	[CP]	
	RUN_Obs2_1 starts.	
Step 15	[RUN <run_obs2_1>]</run_obs2_1>	[RUN <run_obs2_1>]</run_obs2_1>
	RUN_Obs2_1 executes Rte_Read on VDP_ExplRead2_1.	Data read is Value_Send1
Step 16	[RUN <run_obs2_1>]</run_obs2_1>	
	RUN_Obs2_1 terminates	
Post- conditions	Run_Ctrl, Run_Obs1 and RUN_Obs2.1 are terminated	

#### 6.3.13 [ATS\_RTE\_00021] Implicit write and read in coherency group

Test Objective	Implicit write and read in coherency group		
ID	ATS_RTE_00021	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
	ATR: ATR_ATR_00020 ATR: ATR_ATR_00022		
	RTE: SWS_Rte_07063 RTE: SWS_Rte_07066		
Requirements / Reference to Test Environment	ControlSWC, Observation1SWC and Observation2SWC are required.  The ports Observation1SWC. RP_ReceiveData1 and ControlSWC.RUN_Ctrl.PP_SendData are connected. The ports Observation2SWC.RP_ReceiveData2 and ControlSWC.RUN_Ctrl.PP_SendData are connected.		



	ControlSWC.Run_Ctrl, Observation2SWC.Ru Observation2SWC.Run_Obs2.2 are executed Order of execution in the OS task is Observat ControlSWC.Run_Ctrl, then Observation2SW Their DataWriteAccess and DataReadAccess Observation1WSC.Run_Obs1 does not belon Hint: The sequence of the test steps require that RUN_Obs1 can preempt RUN_Ctrl. This executing the runnable entity ControlSWC.RU TCP can be implemented for example with a pan event which activates RUN_Obs1, an	I in the same OS task. ion2SWC.Run_Obs2.1, then C.Run_Obs2.2. belong to the same coherency group. g to previous coherency group. he OS and RTE to be configured such means in particular that the OS task JN_Ctrl shall be preemptable. The	
O a meli mu maeti a m			
Configuration Parameters	Parameters: - Value_Send1		
	I-PDU Transmission Mode Timing: - EventControlledTiming		
Summary	Ensure coherency group are correctly support	ted by implicit communication	
	Test description		
	Observation 1 starts, performs a read on its re Observation 1 terminates.	equire port. Data read is initial value.	
	First runnable entity of Observation 2 starts, performs a read on its require port. Data read is initial value. Runnable entity terminates.		
	Control starts, performs a write on its provide port then terminates.		
	Observation 1 starts again, performs a read on its require port. Data read is value written by Control. Observation 1 terminates.		
	The task executing the coherency group is still running.		
	Second runnable entity of Observation 2 starts, performs a read on its require port. Data read is initial value. Runnable entity terminates.		
	The task executing the coherency group is no	t terminated.	
	First runnable entity of Observation 2 starts again, performs a read on its require port. Data read is value written by Control. Runnable entity terminates.		
	Second runnable entity of Observation 2 starts again, performs a read on its require port. Data read is value written by Control. Runnable entity terminates.		
Needed Adaptation to other Releases			
Pre-conditions	No other runnables than RUN_Ctrl performs a write to RP_ReceiveData1 and RP_ReceiveData2 during the execution of the test case		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[CP]		
	RUN_Obs1 starts.		



Step 2	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>
	RUN_Obs1 executes Rte_IRead on	Data read is Value_Init_Receive1
04 0	VDP_ExplRead1.	
Step 3	[RUN <run_obs1>]</run_obs1>	
	RUN_Obs1 terminates	
Step 4	[CP]	
	RUN_Obs2_1 starts	
Step 5	[RUN <run_obs2_1>]</run_obs2_1>	[RUN <run_obs2_1>]</run_obs2_1>
	RUN_Obs2_1 executes Rte_IRead on	Data read is Value_Init_Receive2.
	VDP_implRead2.1.	[SWS_Rte_07063]
Step 6	[RUN <run_obs2_1>]</run_obs2_1>	
	RUN_Obs2_1 terminates	
Step 7	[CP]	
	RUN_Ctrl starts.	
Step 8	[RUN <run_ctrl>]</run_ctrl>	
	RUN_Ctrl executes Rte_IWrite on	
	VDP_ImplWrite.	
Step 9	[RUN <run_ctrl>]</run_ctrl>	
	RUN_Ctrl terminates	
Step 10	[CP]	
	RUN_Obs1 starts	
Step 11	[RUN <run_obs1>]</run_obs1>	[RUN <run_obs1>]</run_obs1>
	RUN_Obs1 executes Rte_IRead on	Data read is <i>Value_Send1</i> .
Otom 40	VDP_implRead1.	
Step 12	[RUN <run_obs1>]</run_obs1>	
	RUN_Obs1 terminates	
Step 13	[CP]	
	RUN_Obs2_2 starts	
Step 14	[RUN <run_obs2_2>]</run_obs2_2>	[RUN <run_obs2_2>]</run_obs2_2>
	RUN_Obs2_2 executes Rte_IRead on	Data read is Value_Init_Receive2.
	VDP_ImplRead2_2.	[SIMS Bto 07062]
		[SWS_Rte_07063], [SWS_Rte_07066]
Step 15	[RUN <run_obs2_2>]</run_obs2_2>	
	RUN_Obs2_2 terminates	
Step 16	[CP]	
	RUN_Obs2_1 starts	
		-



Step 17	[RUN <run_obs2_1>]</run_obs2_1>	[RUN <run_obs2_1>]</run_obs2_1>
	RUN_Obs2_1 executes Rte_IRead on VDP_ImplRead2	Data read is <i>Value_Send1</i>
Step 18	[RUN <run_obs2_1>]</run_obs2_1>	
	RUN_Obs2_1 terminates	
Step 19	[CP]	
	RUN_Obs2_2 starts	
Step 20	[RUN <run_obs2_2>]</run_obs2_2>	[RUN <run_obs2_2>]</run_obs2_2>
	RUN_Obs2.2 reads its port RP_ReceiveData2.	Data read is <i>Value_Send1</i>
	(Implementer choice whether read is explicit or implicit:	
	RUN_Obs2_2 executes Rte_Read on VDP_ExplRead2_2.	
	OR	
	RUN_Obs2_2 executes Rte_IRead on VDP_ImplRead2_2.	
Step 21	[RUN <run_obs2_2>]</run_obs2_2>	
	RUN_Obs2_2 terminates	
Post- conditions	None	

### 6.3.14 [ATS\_RTE\_00634] Explicit Nonqueued Inter-ECU Rte\_Write For DataElement Of Primitive Data Type When Com Service Is Not Available

	Explicit Nonqueued Inter-ECU Rte_Write For DataElement Of Primitive Data Type When Com Service Is Not Available		
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01280 RTE: SWS_Rte_04505 RTE: SWS_Rte_06011		



	RTE: SWS_Rte_06023 RTE: SWS_Rte_07822		
	RTE: SWS_Rte_07824		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * a PPortPrototype to send - VariableDataPrototype_TC4 typed with a primitive data type with swImplPolicy 'standard'  * a RunnableEntity to execute the test sequence with - with a dataSendPoint which references VariableDataPrototype_TC4  A communication matrix with  * Signal_TC4 - mapped to VariableDataPrototype_TC4 - transmitted by the ECU  * ISignalIPdu_TC4 - configured with an EventControlledTiming - Signal_TC4 mapped to ISignalIPdu_TC4 with transferProperty triggered  * ISignalIPduGroup_TC4 which references ISignalIPdu_TC4  * ISignalIPduGroup_TC4 which references ISignalIPdu_TC4		
Summary	This test case verifies the explicit inter-ECU communication when the IPduGroup used to send a dataElement is not started.  In a RunnableEntity Rte_Write is called which causes a transmission request (in case of inter-ECU communication by invoking the Com_SendSignal API). Since the IPduGroup is not started the Com_SendSignal API returns  COM_SERVICE_NOT_AVAILABLE and in turn Rte_Write returns  RTE_E_COM_STOPPED.		
Needed Adaptation to other Releases			
Pre-conditions	ISignallPduGroup_TC4 shall be in stopped mode		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[SWC] Invoke Rte_Write for VariableDataPrototype_TC4 with valid data.	[SWC] Rte_Write returns RTE_E_COM_STOPPED.	
Post- conditions	NONE		

### 6.3.15 [ATS\_RTE\_00635] Explicit Nonqueued Inter-ECU Rte\_Write For DataElement With Array Data Type

Test Objective	Explicit Nonqueued Inter-ECU Rte_Write For DataElement With Array Data Type		
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			



Tropo to CMC	DTE: CWC Dtc 04074	1	
Trace to SWS Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01280		
iteiii	RTE: SWS_Rte_04526		
	RTE: SWS_Rte_04527		
	RTE: SWS_Rte_05081		
	RTE: SWS_Rte_06011		
	RTE: SWS_Rte_07820 RTE: SWS_Rte_07824		
Poquiromento /	K1E. 5W5_Kte_0/624		
Requirements / Reference			
to Test			
Environment			
	A SW-C with		
Parameters	* a PPortPrototype to send		
	<ul> <li>VariableDataPrototype_TC5array typed with 'standard'</li> </ul>	n an array data type with swimpiPolicy	
	* a RunnableEntity to execute the test seque	nce	
	- with a dataSendPoint which references Vari		
	A communication matrix with		
	* SignalGroup_TC5array		
	- mapped to VariableDataPrototype_TC5arra	у	
	- transmitted by the ECU		
	* ISignallPdu_TC5array		
	- configured with an EventControlledTiming	Ddy TCForrow with transferDranarty	
	<ul> <li>SignalGroup_TC5array mapped to ISignalIPdu_TC5array with transferProperty triggered</li> </ul>		
Summary	This test case verifies the explicit inter-ECU communication for a dataElement with		
	array data type.		
	Explicit inter-ECU sender-receiver communication shall be initiated to send valid data. Rte_Write will invoke Com_UpdateShadowSignal API for each element in the		
	array and then it invokes Com_SendSignalGroup API to cause transmission. The		
	frame is then observed on the bus.	cup / ii / to cauce ii an emiceiem / me	
Needed			
Adaptation to			
other Releases			
	ComM channel shall be in COMM_FULL_CO	MMUNICATION mode	
Main Test Execu	ition	b 0 " 1	
Test Steps	rowo	Pass Criteria	
Step 1	[SWC] Invoke Rte Write for	[SWC] Rte_Write returns RTE_E_OK.	
	VariableDataPrototype_TC5array with valid	INTE_VVIITE TETUTIS KTE_E_OK.	
	data.		
Step 2	-	[LT]	
		The frame with ISignalIPdu_TC5array	
		has been seen on the bus with the	
		values of the different subElements of VariableDataPrototype_TC5array	
Post-	NONE	vanabieDatar Tototype_Tobaliay	
conditions	INCINE		
oonanions			



### 6.3.16 [ATS\_RTE\_00636] Explicit Nonqueued Inter-ECU Rte\_Write For DataElement With Record Data Type

Test Objective	Explicit Nonqueued Inter-ECU Rte	_Write For	DataElement With Record Data Type
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01280 RTE: SWS_Rte_04526 RTE: SWS_Rte_04527 RTE: SWS_Rte_05081 RTE: SWS_Rte_06011 RTE: SWS_Rte_07820 RTE: SWS_Rte_07824		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * a PPortPrototype to send  - VariableDataPrototype_TC5record typed with a record data type with swImplPolicy  'standard'  * a RunnableEntity to execute the test sequence  - with a dataSendPoint which references VariableDataPrototype_TC5record  A communication matrix with  * SignalGroup_TC5record  - mapped to VariableDataPrototype_TC5record  - transmitted by the ECU  * ISignalIPdu_TC5record  - configured with an EventControlledTiming  - SignalGroup_TC5record mapped to ISignalIPdu_TC5record with transferProperty triggered		
Summary	This test case verifies the explicit inter-ECU communication for a dataElement with record data type.  Explicit inter-ECU sender-receiver communication shall be initiated to send valid data. Rte_Write will invoke Com_UpdateShadowSignal API for each element in the record and then it invokes Com_SendSignalGroup API to cause transmission. The frame is then observed on the bus.		
Needed Adaptation to other Releases			
Pre-conditions	ComM channel shall be in COMM	_FULL_CO	MMUNICATION mode
Main Test Execu	ution		lo a committe
Test Steps	ISMUC1		Pass Criteria
Step 1	[SWC] Invoke Rte_Write for VariableDataPrototype_TC5record data.	d with valid	[SWC] Rte_Write returns RTE_E_OK.
Step 2	-		[LT] The frame with ISignalIPdu_TC5 has



		been seen on the bus with the values of the different subElements of VariableDataPrototype_TC5record
Post- conditions	NONE	

### 6.3.17 [ATS\_RTE\_00637] Explicit Nonqueued Inter-ECU Rte\_Read For DataElement Of Primitive Data Type

	le		B : E :
Test Objective	· · · · · · · · · · · · · · · · · · ·		DataElement Of Primitive Data Type
ID	ATS_RTE_00637	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01289 RTE: SWS_Rte_01292 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_04505 RTE: SWS_Rte_06011		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * an RPortPrototype to receive  - VariableDataPrototype_TC6 typed with a primitive data type with swImplPolicy  'standard'  * RunnableEntity_DRE  - started by a DataReceivedEvent on reception of VariableDataPrototype_TC6  - with a dataReceivePointByArgument which references  VariableDataPrototype_TC6  A communication matrix with  * Signal_TC6  - mapped to VariableDataPrototype_TC6  - received by the ECU		
Summary			inter-ECU communication: a runnable it can read the data received in the
Needed Adaptation to other Releases			
Pre-conditions	ComM channel shall be in COMN	1_FULL_CO	MMUNICATION mode
Main Test Execution			
Test Steps			Pass Criteria
Step 1	[LT] Transmit a frame with Signal_TC	6.	[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>



	Invoke the Rte_Read API to read VariableDataPrototype_TC6.	[RUN <runnableentity_dre>] Rte_Read returns RTE_E_OK. The data received has the same value as sent in the frame.</runnableentity_dre>
Post- conditions	NONE	

### 6.3.18 [ATS\_RTE\_00638] Explicit Nonqueued Inter-ECU Rte\_Read For DataElement With Array Data Type

Test Objective	Explicit Nangueued Inter ECLL Pt	o Pood For	Data Floment With Array Data Type
-			DataElement With Array Data Type
ID	ATS_RTE_00638	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01135 RTE: SWS_Rte_01289 RTE: SWS_Rte_01292 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_04527 RTE: SWS_Rte_05081 RTE: SWS_Rte_06011		
Requirements / Reference to Test Environment			
Configuration Parameters	'standard'  * RunnableEntity_DRE  - started by a DataReceivedEven  - with a dataReceivePointByArgu VariableDataPrototype_TC7array  A communication matrix with  * SignalGroup_TC7array  - mapped to VariableDataPrototy  - received by the ECU	t on reception ment which in the second seco	у
Summary			communication: a runnable can be read the array data received from the
Needed Adaptation to other Releases			
Pre-conditions	ComM channel shall be in COMN	/_FULL_CO	MMUNICATION mode
Main Test Execu	ution		



Test Steps		Pass Criteria
Step 1	[LT] Transmit frame withSignalGroup_TC7array.	[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>
Step 2	[RUN <runnableentity_dre>] Invoke the Rte_Read API to read VariableDataPrototype_TC7array.</runnableentity_dre>	[RUN <runnableentity_dre>] Rte_Read returns RTE_E_OK. The data received has the same values as sent in the frame.</runnableentity_dre>
Post- conditions	NONE	

### 6.3.19 [ATS\_RTE\_00639] Explicit Nonqueued Inter-ECU Rte\_Read For DataElement With Record Data Type

Test Objective	Explicit Nonqueued Inter-ECU Rt	e_Read For	DataElement With Record Data Type
ID	ATS_RTE_00639	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01135 RTE: SWS_Rte_01289 RTE: SWS_Rte_01292 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_04527 RTE: SWS_Rte_05081 RTE: SWS_Rte_06011		
Requirements / Reference to Test Environment			
Parameters	A SWC with  * An RPortPrototype to receive - VariableDataPrototype_TC7rece 'standard'  * RunnableEntity_DRE - started by a DataReceivedEven' VariableDataPrototype_TC7recor - with a dataReceivePointByArgul VariableDataPrototype_TC7recor  A communication matrix with  * SignalGroup_TC7record - mapped to VariableDataPrototype_received by the ECU	t on receptio d ment which i d	references
Summary	This test case verifies the explicit		ommunication: a runnable can be read the record data received from the



Needed Adaptation to other Releases			
Pre-conditions	ComM channel shall be in COMM_FULL	_COMMUNICATION mode	
Main Test Execu	ution		
Test Steps	Pass Criteria		
Step 1	[LT] Transmit frame with SignalGroup_TC7record.	[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>	
Step 2	[RUN <runnableentity_dre>] Invoke the Rte_Read API to read VariableDataPrototype_TC7record.</runnableentity_dre>	[RUN <runnableentity_dre>] Rte_Read returns RTE_E_OK. The data received has the same values as sent in the frame.</runnableentity_dre>	
Post- conditions	NONE		

### 6.3.20 [ATS\_RTE\_00640] Explicit Queued Inter-ECU Rte\_Send For DataElement Of Variable-length Arrays Of Bytes

Test Objective	Explicit Queued Inter-ECU Rte_Send For DataElement Of Variable-length Arrays Of Bytes		
ID	ATS_RTE_00640	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01072 RTE: SWS_Rte_01281 RTE: SWS_Rte_04526 RTE: SWS_Rte_05081 RTE: SWS_Rte_06011 RTE: SWS_Rte_07817 RTE: SWS_Rte_07821 RTE: SWS_Rte_07825		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * a PPortPrototype to send - VariableDataPrototype_TC8 typ set to variableSize maxNumberO  * a RunnableEntity to execute the - with a dataSendPoint which refe  A communication matrix with  * SignalGroup_TC8 - with dynamicLength = TRUE - mapped to VariableDataPrototy  * ISignalIPdu_TC8	fElements > test sequererences Varia	nce



	- SignalGroup_TC8 mapped to ISignalIPdu_TC8 with transferProperty triggered - configured with an EventControlledTiming		
Summary	This test case verifies the explicit queued inter-ECU communication for variable-length array of bytes.  The dataElement is sent with Rte_Send and it has to be transmitted on the bus with the right length.		
Needed Adaptation to other Releases			
Pre-conditions	ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	Main Test Execution		
Test Steps		Pass Criteria	
Step 1	[SWC] Invoke Rte_Send on VariableDataPrototype_TC8 with an array of 2 bytes and the length set to 2.	[SWC] Rte_Send returns RTE_E_OK.	
Step 2	-	[LT] The frame containing ISignallPdu_TC8 is transmitted on the bus with the 2 bytes matching the values sent in step 1.	
Post- conditions	NONE		

### 6.3.21 [ATS\_RTE\_00641] Explicit Queued Inter-ECU Rte\_Receive For DataElement Of Variable-Length Arrays Of Bytes

	Explicit Queued Inter-ECU Rte_Receive For DataElement Of Variable-Length Arrays Of Bytes		
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01092 RTE: SWS_Rte_01135 RTE: SWS_Rte_01288 RTE: SWS_Rte_02598 RTE: SWS_Rte_06011 RTE: SWS_Rte_07814 RTE: SWS_Rte_07817		
Requirements / Reference to Test Environment			
Parameters	A SW-C with  * an RPortPrototype to receive - VariableDataPrototype_TC9 typ set to variableSize maxNumberO  * RunnableEntity_DRE		amic length array (arraySizeSemantics 2) with swImplPolicy 'queued'



	<ul> <li>started by a DataReceivedEvent on reception</li> <li>with a dataReceivePointByArgument which is VariableDataPrototype_TC9</li> <li>A communication matrix with</li> <li>* SignalGroup_TC9</li> <li>mapped to VariableDataPrototype_TC9</li> <li>dynamicLength = TRUE</li> </ul>		
Summary	This test case verifies that the reception of da activates an associated DRE runnable and the applications through the Rte_Receive API.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execution			
Test Steps		Pass Criteria	
Step 1	[LT] transmit frame withSignal_TC9Rx.	[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>	
Step 2	[RUN <runnableentity_dre>] Invoke the Rte_Receive API to read variable length data received on VariableDataPrototype_TC9.</runnableentity_dre>	[RUN <runnableentity_dre>] Rte_Receive returns RTE_E_OK. The data received has the same value and length as sent in the frame.</runnableentity_dre>	
Post- conditions	NONE		

## 6.3.22 [ATS\_RTE\_00642] Explicit Nonqueued Intra-Partition Data Invalidation When Attribute 'HandleInvalid = Keep' And 'HandleNeverReceived = False' Or Undefined

	Explicit Nonqueued Intra-Partition Data Invalidation When Attribute 'HandleInvalid = Keep' And 'HandleNeverReceived = False' Or Undefined		
ID	ATS_RTE_00642	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01091 RTE: SWS_Rte_01206 RTE: SWS_Rte_01207 RTE: SWS_Rte_01282 RTE: SWS_Rte_01289 RTE: SWS_Rte_02626 RTE: SWS_Rte_05030 RTE: SWS_Rte_06011 RTE: SWS_Rte_07396 RTE: SWS_Rte_08005 RTE: SWS_Rte_08008		



Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * A PPortPrototype which - sends VariableDataPrototype_TC10 with the same value as initValue and invalidValue (Ex: 0xAA) with swImplPolicy 'standard' - is typed by a SenderReceiverInterface with an invalidationPolicy for VariableDataPrototype_TC10 (handleInvalid = keep)  * An RPortPrototype to receive VariableDataPrototype_TC10 - NonqueuedReceiverComSpec with handleNeverReceived = FALSE - connected with the previous PPortPrototype  * A RunnableEntity to execute the test sequence - with a dataReceivePointByArgument which references VariableDataPrototype_TC10 - with a dataSendPoint which references VariableDataPrototype_TC10		
Summary	If the initValue of a nonqueued dataElement equals the invalidValue and handleInvalid is set to keep and the handleNeverReceived is set to FALSE or not defined then data read shall be returned as invalid and should provide the invalidValue until the first reception of the dataElement.  If a dataElement has been invalidated in case of Intra-partition communication and the attribute handleInvalid is set to keep – the query of the value shall return the invalid value.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state		
Main Test Execu	ution		
Test Steps	rower	Pass Criteria	
Step 1	[SWC] Invoke Rte_Read to read the dataElement VariableDataPrototype_TC10.	[SWC] Rte_Read returns RTE_E_INVALID and provides the invalidValue.	
Step 2	[SWC] Invoke Rte_Invalidate to invalidate the dataElement VariableDataPrototype_TC10.	[SWC] Rte_Invalidate returns RTE_E_OK indicating invalidation successful.	
Step 3	[SWC] Invoke Rte_Read to read the dataElement VariableDataPrototype_TC10.	[SWC] Rte_Read returns RTE_E_INVALID and provides the invalidValue.	
Post- conditions	NONE		

## 6.3.23 [ATS\_RTE\_00643] Explicit Nonqueued Intra-Partition Data Invalidation When Attribute 'HandleInvalid = Keep' And 'HandleNeverReceived = True'

	Explicit Nonqueued Intra-Partition Data Invalidation When Attribute 'HandleInvalid = Keep' And 'HandleNeverReceived = True'		
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed



<b>-</b>	Т		
Trace to			
Requirement on Acceptance			
Test Document			
Trace to SWS	RTE: SWS_Rte_01091		
Item	RTE: SWS_Rte_01093		
	RTE: SWS_Rte_01206		
	RTE: SWS_Rte_01207		
	RTE: SWS_Rte_01282		
	RTE: SWS_Rte_01289 RTE: SWS_Rte_02626		
	RTE: SWS_Rte_02020 RTE: SWS_Rte_05030		
	RTE: SWS_Rte_06011		
	RTE: SWS_Rte_07382		
	RTE: SWS_Rte_07396		
	RTE: SWS_Rte_07643		
	RTE: SWS_Rte_08009		
Requirements / Reference			
to Test			
Environment			
	A SWC with		
Parameters	* a PPortPrototype to send		
	<ul> <li>VariableDataPrototype_TC11 with the same</li> </ul>	value as initValue and invalidValue	
	(Ex: 0xAA) with swImplPolicy 'standard'		
	- SenderReceiverInterface with an invalidation		
	VariableDataPrototype_TC11 (handleInvalid =		
	* An RPortPrototype to receive VariableDataPrototype_TC11 - NonqueuedReceiverComSpec with handleNeverReceived = TRUE		
	- connected with the previous PPortPrototype		
	* A RunnableEntity to execute the test sequence		
	- with a dataReceivePointByArgument which	references	
	VariableDataPrototype_TC11 - with a dataSendPoint which references Variation	abla Data Prototypa TC11	
C		* 1 =	
Summary	If the initValue of a nonqueued dataElement equals the invalidValue and handleInvalid is set to TRUE the RTE		
	API Rte_Read should return RTE_E_NEVER		
	dataElement. In this case Rte_Read shall pro		
	If a data element has been invalidated in case		
	the attribute handleInvalid is set to keep – the	query of the value shall return the	
	invalidValue.		
Needed			
Adaptation to other Releases			
	DUT shall be initialized		
. To conditions	EcuM module shall be in RUN state		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[SWC]	[SWC]	
	Invoke Rte_Read API to explicitly read the	Rte_Read returns	
		RTE_E_NEVER_RECEIVED	
		(indicating that no data has been	
		received due to system start) and	
Ston 0	[0](0]	provides the initValue.	
Step 2	[SWC] Invoke Rte_Invalidate API to invalidate the	[SWC] Rte_Invalidate returns RTE_E_OK	
		indicating invalidation successful.	
	data_iomont variableDatal lototype_1011.	maisaning invalidation odooosidi.	



	Invoke Rte_Read API to explicitly read the	[SWC] Rte_Read returns RTE_E_INVALID and provides the invalidValue.
Post- conditions	NONE	

### 6.3.24 [ATS\_RTE\_00644] Explicit Nonqueued Intra-Partition Data Invalidation When Attribute 'Handleinvalid = Replace'

Test Objective	Explicit Nonqueued Intra-Partition Data Invalidation When Attribute 'Handleinvalid = Replace'		
ID	ATS_RTE_00644	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01206 RTE: SWS_Rte_01207 RTE: SWS_Rte_01282 RTE: SWS_Rte_01289 RTE: SWS_Rte_05049 RTE: SWS_Rte_06011 RTE: SWS_Rte_07396		
Requirements / Reference to Test Environment			
Configuration Parameters	A SWC with  * a PPortPrototype to send  - VariableDataPrototype_TC12 with different values as initValue (Ex: 0x12) and invalidValue (Ex: 0xAA) with swImplPolicy 'standard'  - SenderReceiverInterface with an invalidationPolicy for VariableDataPrototype_TC12 (handleInvalid = replace)  * an RPortPrototype to receive VariableDataPrototype_TC12  - NonqueuedReceiverComSpec with handleNeverReceived = FALSE  - connected with the previous PPortPrototype  * A RunnableEntity to execute the test sequence  - with a dataReceivePointByArgument which references  VariableDataPrototype_TC12  - with a dataSendPoint which references VariableDataPrototype_TC12		
Summary	If a dataElement has been received invalidated in case of intra-partition communication and the attribute handleInvalid is set to replace – RTE shall perform the "invalid value substitution" with the initValue. Then the reception will be handled as if a valid value would have been received.		
Needed Adaptation to other Releases			



Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode	
Main Test Execu	ution	
Test Steps		Pass Criteria
Step 1	<u> </u>	[SWC] Rte_Read returns RTE_E_OK and provides the initValue.
Step 2	[SWC] Invoke Rte_Invalidate API to invalidate the dataElement VariableDataPrototype_TC12.	[SWC] Rte_Invalidate returns RTE_E_OK indicating invalidation successful.
Step 3	[SWC] Invoke Rte_Read API to explicit read the dataElement VariableDataPrototype_TC12.	[SWC] Rte_Read returns RTE_E_OK and provides initValue.
Post- conditions	NONE	

### 6.3.25 [ATS\_RTE\_00645] Explicit Nonqueued Inter-ECU Data Invalidation On Sender Side For DataElement Of Primitive Data Type

	Explicit Nonqueued Inter-ECU Data Invalidation On Sender Side For DataElement Of Primitive Data Type		
ID	ATS_RTE_00645	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Item	RTE: SWS_Rte_01206 RTE: SWS_Rte_01207 RTE: SWS_Rte_01231 RTE: SWS_Rte_01282 RTE: SWS_Rte_04505		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * a PPortPrototype which - sends VariableDataPrototype_TC13 typed with a primitive data type with different values as initValue (Ex: 0x12) and invalidValue (Ex: 0xAA) with swImplPolicy 'standard' - is typed by a SenderReceiverInterface with an invalidationPolicy for VariableDataPrototype_TC13  A communication matrix with  * Signal_TC13 - mapped to VariableDataPrototype_TC13 - transmitted by the ECU		
Summary	In case of inter-ECU communication if the application SW-C has to invalidate a data element of primitive type then it calls the Rte_Invalidate API which in turn will trigger the emission of a signal with the invalidValue.		



Needed Adaptation to other Releases		
Pre-conditions	DUT shall be initialized  EcuM module shall be in RUN state  ComM channel shall be in COMM FULL COMMUNICATION mode	
Main Test Execu	ıtion	
Test Steps		Pass Criteria
Step 1	[SWC] Invoke Rte_Invalidate API to invalidate the dataElement VariableDataPrototype_TC13.	[SWC] Rte_Invalidate returns RTE_E_OK.
Step 2	-	[LT] Signal "Signal_TC13" with configured invalidValue has been observed on the bus
Post- conditions	NONE	

### 6.3.26 [ATS\_RTE\_00646] Explicit Nonqueued Inter-ECU Data Invalidation On Sender Side For DataElement With Array Data Type

Test Objective	Explicit Nonqueued Inter-ECU Data Invalidation On Sender Side For DataElement With Array Data Type		
ID	ATS_RTE_00646	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01206 RTE: SWS_Rte_01207 RTE: SWS_Rte_01282 RTE: SWS_Rte_05024 RTE: SWS_Rte_05063 RTE: SWS_Rte_05081		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * a PPortPrototype which - sends VariableDataPrototype_TC14array, typed with an array data type, with different values as initValue (Ex: all subElements = 0x05) and invalidValue (Ex: all subElements = 0xAA), with swImplPolicy 'standard', - is typed by a SenderReceiverInterface with an invalidationPolicy for VariableDataPrototype_TC14array  A communication matrix with  * SignalGroup_TC14array - mapped to VariableDataPrototype_TC14array - transmitted by the ECU		



Summary	In case of inter-ECU communication if the application SW-C has to invalidate a data element with array type then it calls Rte_Invalidate API which in turn will trigger the emission of a signal with the invalidValue.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	Main Test Execution		
Test Steps	Pass Criteria		
Step 1	[SWC] Invoke Rte_Invalidate API to invalidate the array dataElement VariableDataPrototype_TC14array.	[SWC] Rte_Invalidate returns RTE_E_OK indicating invalidation of data.	
Step 2	-	[LT] Signal SignalGroup_TC14array with invalidValue has been observed on the bus	
Post- conditions	None		

### 6.3.27 [ATS\_RTE\_00647] Explicit Nonqueued Inter-ECU Data Invalidation On Sender Side For DataElement With Record Data Type

	Explicit Nonqueued Inter-ECU Data Invalidation On Sender Side For DataElement With Record Data Type		
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01206 RTE: SWS_Rte_01207 RTE: SWS_Rte_01282 RTE: SWS_Rte_05024 RTE: SWS_Rte_05063 RTE: SWS_Rte_05081		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * a PPortPrototype which - sends VariableDataPrototype_TC14record, typed with a record data type, with different values as initValue (Ex: all subElements = 0x05) and invalidValue (Ex: all subElements = 0xAA), with swImplPolicy 'standard', - is typed by a SenderReceiverInterface with an invalidationPolicy for VariableDataPrototype_TC14record  A communication matrix with		



	* SignalGroup_TC14record - mapped to VariableDataPrototype_TC14record - transmitted by the ECU	
Summary	In case of inter-ECU communication if the application SW-C has to invalidate a data element with record type then it calls Rte_Invalidate API which in turn will trigger the emission of a signal with the invalidValue.	
Needed Adaptation to other Releases		
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode	
Main Test Execu	ution	
Test Steps		Pass Criteria
Step 1	[SWC] Invoke Rte_Invalidate API to invalidate the record dataElement VariableDataPrototype_TC14record.	[SWC] Rte_Invalidate returns RTE_E_OK indicating invalidation of data.
Step 2	-	[LT] Signal SignalGroup_TC14record with invalidValue has been observed on the bus
Post- conditions	None	•

# 6.3.28 [ATS\_RTE\_00648] Explicit Nonqueued Inter-ECU Data Invalidation On Receiver Side When Attribute 'HandleInvalid = Keep' For DataElement Of Primitive Data Type

Test Objective	Explicit Nonqueued Inter-ECU Data Invalidation On Receiver Side When Attribute 'HandleInvalid = Keep' For DataElement Of Primitive Data Type		
ID	ATS_RTE_00648	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01135 RTE: SWS_Rte_01289 RTE: SWS_Rte_01292 RTE: SWS_Rte_01359 RTE: SWS_Rte_02626 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_05026 RTE: SWS_Rte_05026 RTE: SWS_Rte_06011		
Requirements / Reference			



to Test		
Environment		
Configuration Parameters	A SW-C with  * an RPortPrototype which receives - VariableDataPrototype_TC15 typed with a primitive data type with an invalidValue (Ex: 0xAA) with swImplPolicy 'standard' - SenderReceiverInterface with an invalidationPolicy for VariableDataPrototype_TC15 (handleInvalid = keep)  * RunnableEntity_DRE - started by a DataReceivedEvent on reception of VariableDataPrototype_TC15 - with a dataReceivePointByArgument which references VariableDataPrototype_TC15  * RunnableEntity_DRError - started by a DataReceiveErrorEvent which references VariableDataPrototype_TC15 - with a dataReceivePointByArgument which references VariableDataPrototype_TC15 - with a dataReceivePointByArgument which references VariableDataPrototype_TC15	
	A communication matrix with  * Signal_TC15 - mapped to VariableDataPrototype_TC15 - received by the ECU	
Summary	If a dataElement has been received invalidated in case of inter-ECU communication and the attribute handleInvalid is set to keep for all receiving software components – the query of the value shall return the received value together with an indication of the invalid status i.e. the return value of Rte_Read shall be RTE_E_INVALID.  If a data element has been received invalidated in case of inter-ECU communication and if a DataReceiveErrorEvent is configured for the associated dataElement then the RTE shall activate the runnable "RunnableEntity_DRError" when a signal with invalid value is received.	
Needed Adaptation to other Releases		
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode	
Main Test Execu	ution	
Test Steps		Pass Criteria
Step 1	[LT] Transmit a frame with Signal_TC15.	[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>
Step 2	[RUN <runnableentity_dre>] Invoke Rte_Read inside to read dataElement VariableDataPrototype_TC15.</runnableentity_dre>	provides the value as sent by LT in step 1.
·	[LT] Transmit a frame with invalid data sent on Signal_TC15.	[RUN <runnableentity_drerror>] RunnableEntity_DRError is invoked.</runnableentity_drerror>
Step 4	[RUN <runnableentity_drerror>] Invoke Rte_Read to read dataElement VariableDataPrototype_TC15.</runnableentity_drerror>	[RUN <runnableentity_drerror>] Rte_Read returns RTE_E_INVALID and provides the value as sent by LT in step 3.</runnableentity_drerror>
Post- conditions	NONE	



# 6.3.29 [ATS\_RTE\_00649] Explicit Nonqueued Inter-ECU Data Invalidation On Receiver Side When Attribute 'HandleInvalid = Replace' For DataElement Of Primitive Data Type

Test Objective	Explicit Nonqueued Inter-ECU Data Invalidation On Receiver Side When Attribute		
rest Objective	'HandleInvalid = Replace' For DataElement Of Primitive Data Type		
ID	ATS_RTE_00649		4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01135 RTE: SWS_Rte_01289 RTE: SWS_Rte_01292 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_05048 RTE: SWS_Rte_06011		
Requirements / Reference to Test Environment			
Parameters	A SW-C with  * an RPortPrototype which receives - VariableDataPrototype_TC16 typed with a primitive data type with different values as initValue (Ex: 0x05) and invalidValue (Ex: 0xAA) with swImplPolicy 'standard' - SenderReceiverInterface with an invalidationPolicy for VariableDataPrototype_TC16 (handleInvalid = replace)  * RunnableEntity_DRE - started by a DataReceivedEvent on reception of VariableDataPrototype_TC16 - with a dataReceivePointByArgument which references VariableDataPrototype_TC16  A communication matrix with  * Signal_TC16 - mapped to VariableDataPrototype_TC16 - received by the ECU		
·	If a data element has been received invalidated in case of Inter-ECU communication and the attribute handle Invalid is set to replace for all receiving software components – COM shall be configured to perform the "invalid value substitution" with the initValue. Then the reception will be handled as if a valid value would have been received. i.e. activation of Runnable Entity using the data received event.		
Needed Adaptation to other Releases			
	DUT shall be initialized EcuM module shall be in RUN sta ComM channel shall be in COMM		MMUNICATION mode
Main Test Execu	ıtion		
Test Steps			Pass Criteria



Step 1	[LT] Transmit a frame with a valid value onSignal_TC16.	[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>
Step 2		[RUN <runnableentity_dre>] Rte_Read returns RTE_E_OK and provides the value as sent by LT in step 1.</runnableentity_dre>
	[LT] Transmit a frame with invalidValue onSignal_TC16.	[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>
Step 4	<u> </u>	[RUN <runnableentity_dre>] Rte_Read returns RTE_E_OK and provides the initValue.</runnableentity_dre>
Post- conditions	NONE	

# 6.3.30 [ATS\_RTE\_00650] Explicit Nonqueued Inter-ECU Data Invalidation On Receiver Side When Attribute 'HandleInvalid = Keep' For DataeElement With Array Data Type

Test Objective	Explicit Nonqueued Inter-ECU Data Invalidation On Receiver Side When Attribute 'HandleInvalid = Keep' For DataeElement With Array Data Type		
ID	ATS_RTE_00650	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01091 RTE: SWS_Rte_01289 RTE: SWS_Rte_01359 RTE: SWS_Rte_02626 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_04527 RTE: SWS_Rte_05026 RTE: SWS_Rte_05026 RTE: SWS_Rte_05081 RTE: SWS_Rte_06011 RTE: SWS_Rte_07396 RTE: SWS_Rte_08405		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * an RPortPrototype which receives  - VariableDataPrototype_TC17array typed with an array data type with different values as initValue (Ex: all subElements = 0x05) and invalidValue (Ex: all subElements = 0xAA) with swImplPolicy 'standard'  - SenderReceiverInterface with an invalidationPolicy for VariableDataPrototype_TC17array (handleInvalid = keep)  * RunnableEntity_DRError		



Post- conditions	NONE			
Step 2	[RUN <runnableentity_drerror>] Invoke Rte_Read to read the dataElement VariableDataPrototype_TC17array.</runnableentity_drerror>	[RUN <runnableentity_drerror>] Rte_Read returns RTE_E_INVALID and provides the invalidValue.</runnableentity_drerror>		
Step 1	[LT] Transmit a frame with invalidValue onSignalGroup_TC17array.	[RUN <runnableentity_drerror>] RunnableEntity_DRError is invoked.</runnableentity_drerror>		
Test Steps		Pass Criteria		
Main Test Execu	Main Test Execution			
	DUT shall be initialized  EcuM module shall be in RUN state  ComM channel shall be in COMM_FULL_COMMUNICATION mode			
Needed Adaptation to other Releases				
Summary	This test case verifies the explicit inter-ECU d array data type on receiver side when the attr			
	- started by a DataReceiveErrorEvent which r VariableDataPrototype_TC17array - with a dataReceivePointByArgument which r VariableDataPrototype_TC17array A communication matrix with * SignalGroup_TC17array - mapped to VariableDataPrototype_TC17array - received by the ECU	references		

## 6.3.31 [ATS\_RTE\_00651] Explicit Nonqueued Inter-ECU Data Invalidation On Receiver Side When Attribute 'HandleInvalid = Keep' For DataElement With Record Data Type

Test Objective	Explicit Nonqueued Inter-ECU Data Invalidation On Receiver Side When Attribute 'HandleInvalid = Keep' For DataElement With Record Data Type		
ID	ATS_RTE_00651	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01091 RTE: SWS_Rte_01289 RTE: SWS_Rte_01359 RTE: SWS_Rte_02626 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_04527 RTE: SWS_Rte_05026 RTE: SWS_Rte_05081 RTE: SWS_Rte_06011 RTE: SWS_Rte_07396 RTE: SWS_Rte_08405		



Requirements / Reference to Test Environment				
Configuration Parameters	A SW-C with  * an RPortPrototype which receives  - VariableDataPrototype_TC17record typed with a record data type with different values as initValue (Ex: all subElements = 0x05) and invalidValue (Ex: all subElements = 0xAA) with swImplPolicy 'standard'  - SenderReceiverInterface with an invalidationPolicy for VariableDataPrototype_TC17record (handleInvalid = keep)  * RunnableEntity_DRError  - started by a DataReceiveErrorEvent which references VariableDataPrototype_TC17record  - with a dataReceivePointByArgument which references VariableDataPrototype_TC17record  A communication matrix with  * SignalGroup_TC17record  - mapped to VariableDataPrototype_TC17record  - received by the ECU			
Summary	This test case verifies the explicit inter-ECU data invalidation for a dataElement with record data type on receiver side when the attribute handleInvalid is set as keep.			
Needed Adaptation to other Releases				
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode			
	Main Test Execution			
Test Steps	Pass Criteria			
Step 1	[LT] Transmit a frame with invalidValue onSignalGroup_TC17record.	[RUN <runnableentity_drerror>] RunnableEntity_DRError is invoked.</runnableentity_drerror>		
Step 2	[RUN <runnableentity_drerror>] Invoke Rte_Read to read the dataElement VariableDataPrototype_TC17record.</runnableentity_drerror>	[RUN <runnableentity_drerror>] Rte_Read returns RTE_E_INVALID and provides the invalidValue.</runnableentity_drerror>		
Post- conditions	NONE			

## 6.3.32 [ATS\_RTE\_00652] Explicit Nonqueued Inter-ECU Data Invalidation On Receiver Side For Attribute 'HandleInvalid = Replace' For DataElement With Array Data Type

	Explicit Nonqueued Inter-ECU Data Invalidation On Receiver Side For Attribute  'HandleInvalid = Replace' For DataElement With Array Data Type			
ID	ATS_RTE_00652			
Affected Modules	RTE	State	reviewed	
Trace to Requirement on Acceptance Test Document				



ltem	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01135 RTE: SWS_Rte_01289 RTE: SWS_Rte_04505 RTE: SWS_Rte_04527 RTE: SWS_Rte_05048		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * an RPortPrototype which receives - VariableDataPrototype_TC18array typed w values as initValue (Ex: all subElements = 0x subElements = 0xAA) with swImplPolicy 'sta - SenderReceiverInterface with an invalidation VariableDataPrototype_TC18array (handleIn  * RunnableEntity_DRE - started by a DataReceivedEvent on recepti VariableDataPrototype_TC18array - with a dataReceivePointByArgument which VariableDataPrototype_TC18array  A communication matrix with  * SignalGroup_TC18array - mapped to VariableDataPrototype_TC18ar - received by the ECU	x05) and invalidValue (Ex: all ndard' onPolicy for nvalid = replace) ion of references	
Summary	If a dataElement with array type has been received invalidated in case of inter-ECU communication and the attribute handleInvalid is set to replace for all receiving software components – COM shall be configured to perform the "invalid value substitution" with the initValue. The reception will be handled as if a valid value would have been received i.e. activation of RunnableEntity using the DataReceivedEvent.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[LT] Transmit a frame with invalid value on SignalGroup_TC18array.	[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>	
Step 2	[RUN <runnableentity_dre>] Invoke Rte_Read to read the dataElement VariableDataPrototype_TC18array.</runnableentity_dre>	[RUN <runnableentity_dre>] Rte_Read returns RTE_E_OK and provides the initValue.</runnableentity_dre>	
Post- conditions	NONE		



## 6.3.33 [ATS\_RTE\_00653] Explicit Nonqueued Inter-ECU Data Invalidation On Receiver Side For Attribute 'HandleInvalid = Replace' For DataElement With Record Data Type

Test Objective	Explicit Nonguound Inter ECLI De	sto Involidati	on On Bossiyar Sida For Attributa
rest Objective	Explicit Nonqueued Inter-ECU Data Invalidation On Receiver Side For Attribute  'HandleInvalid = Replace' For DataElement With Record Data Type		
ID	ATS_RTE_00653		4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Item	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01135 RTE: SWS_Rte_01289 RTE: SWS_Rte_04505 RTE: SWS_Rte_04527 RTE: SWS_Rte_05048		
Requirements / Reference to Test Environment			
Parameters	A SW-C with  * an RPortPrototype which receives - VariableDataPrototype_TC18record typed with a record data type with different values as initValue (Ex: all subElements = 0x05) and invalidValue (Ex: all subElements = 0xAA) with swImplPolicy 'standard' - SenderReceiverInterface with an invalidationPolicy for VariableDataPrototype_TC18record (handleInvalid = replace) * RunnableEntity_DRE - started by a DataReceivedEvent on reception of VariableDataPrototype_TC18record - with a dataReceivePointByArgument which references VariableDataPrototype_TC18record  A communication matrix with * SignalGroup_TC18record - mapped to VariableDataPrototype_TC18record - received by the ECU		
	If a dataElement with record type has been received invalidated in case of inter- ECU communication and the attribute handleInvalid is set to replace for all receiving software components – COM shall be configured to perform the "invalid value substitution" with the initValue. The reception will be handled as if a valid value would have been received i.e. activation of RunnableEntity using the DataReceivedEvent.		
Needed Adaptation to other Releases			
	DUT shall be initialized  EcuM module shall be in RUN state  ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	Main Test Execution		
Test Steps			Pass Criteria



		[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>
	Invoke Rte_Read to read the dataElement	[RUN <runnableentity_dre>] Rte_Read returns RTE_E_OK and provides the initValue.</runnableentity_dre>
Post- conditions	NONE	

# 6.3.34 [ATS\_RTE\_00654] Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest For DataElement Of Primitive Data Type (Without WaitPoint)

Test Objective	Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest For DataElement Of Primitive Data Type (Without WaitPoint)		
ID	ATS_RTE_00654	•	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01084 RTE: SWS_Rte_01086 RTE: SWS_Rte_01137 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01285 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_03531 RTE: SWS_Rte_04505 RTE: SWS_Rte_04505 RTE: SWS_Rte_06011 RTE: SWS_Rte_06023 RTE: SWS_Rte_07820 RTE: SWS_Rte_07824		
Requirements / Reference to Test Environment			
Configuration Parameters	* RunnableEntity_TC19 to initiate - with a dataSendPoint which refe * RunnableEntity_TxAck - with a dataSendPoint which refe	pec with a Ti the test sec grences Varia	ransmissionAcknowledgementRequest quence ableDataPrototype_TC19



	A communication matrix with  * Signal_TC19 - mapped to VariableDataPrototype_TC19  * ISignalIPdu_TC19 - Signal_TC19 mapped to ISignalIPdu_TC19 - configured with an EventControlledTiming - transmitted by the ECU		
Summary	To verify explicit nonqueued inter-ECU Trans activation of a runnable when a Transmissior configured for a dataElement with a primitive	nAcknowledgementRequest is	
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized  EcuM module shall be in RUN state  ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[RUN <runnableentity_tc19>] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC19.</runnableentity_tc19>	[RUN <runnableentity_tc19>] Rte_Feedback returns RTE_E_TRANSMIT_ACK.</runnableentity_tc19>	
Step 2	[RUN <runnableentity_tc19>] Invoke Rte_Write API to write the dataElement VariableDataPrototype_TC19.</runnableentity_tc19>	[RUN <runnableentity_tc19>] Rte_Write returns RTE_E_OK.</runnableentity_tc19>	
Step 3	-	[RUN <runnableentity_txack>] RunnableEntity_TxAck is invoked.</runnableentity_txack>	
Step 4	[RUN <runnableentity_txack>] Invoke Rte_Feedback API for the dataElement VariableDataPrototype_TC19.</runnableentity_txack>	[RUN <runnableentity_txack>] Rte_Feedback returns RTE_E_TRANSMIT_ACK.</runnableentity_txack>	
Post- conditions	NONE		

## 6.3.35 [ATS\_RTE\_00655] Explicit Nonqueued inter-ECU TransmissionAcknowledgementRequest For DataElement Of Primitive Data Type (With WaitPoint)

Test Objective	Explicit Nonqueued inter-ECU TransmissionAcknowledgementRequest For DataElement Of Primitive Data Type (With WaitPoint)		
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01284 RTE: SWS_Rte_01286		



	I		
	RTE: SWS_Rte_03532 RTE: SWS_Rte_04505 RTE: SWS_Rte_06011 RTE: SWS_Rte_06023 RTE: SWS_Rte_07820 RTE: SWS_Rte_07824		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * a PPortPrototype which  - sends VariableDataPrototype_TC20 typed by a primitive data type with swlmplPolicy 'standard'  - has a NonqueuedSenderComSpec with a TransmissionAcknowledgementRequest  * a RunnableEntity to execute the test sequence  - with a dataSendPoint which references VariableDataPrototype_TC20  - with a WaitPoint that references a DataSendCompletedEvent which references the previous dataSendPoint  A communication matrix with  * Signal_TC20  - mapped to VariableDataPrototype_TC20  * ISignallPdu_TC20  - Signal_TC20 mapped to ISignallPdu_TC20 with transferProperty triggered  - configured with an EventControlledTiming		
Summary	This test case verifies the explicit nonqueued inter-ECU TransmissionAcknowledgementRequest and the wake up of category 2 runnables from a WaitPoint as a result of successful transmission for a primitive data type.		
Needed Adaptation to other Releases			
	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode		
	ain Test Execution		
Test Steps	laa.	Pass Criteria	
Step 1	[SWC] Invoke Rte_Write to write the dataElement VariableDataPrototype_TC20.	[SWC] Rte_Write returns RTE_E_OK.	
Step 2	[SWC] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC20.	[SWC] Rte_Feedback returns RTE_E_TRANSMIT_ACK.	
Post- conditions	NONE		

### 6.3.36 [ATS\_RTE\_00656] Explicit Nonqueued Inter-ECU Transmission error notification For DataElement Of Primitive Data Type (Without WaitPoint)

•	Explicit Nonqueued Inter-ECU Transmission error notification For DataElement Of Primitive Data Type (Without WaitPoint)		
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2



Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01137 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01285 RTE: SWS_Rte_04505 RTE: SWS_Rte_06011 RTE: SWS_Rte_06023 RTE: SWS_Rte_07636 RTE: SWS_Rte_07822 RTE: SWS_Rte_07824		
Requirements / Reference to Test Environment			
Configuration Parameters	* RunnableEntity_TC21 to initiate - with a dataSendPoint which refe * RunnableEntity_TxErr - with a dataSendPoint which refe	pec with a Ti the test seq erences Varia erences Varia devent which pe_TC21 IPdu_TC21 ledTiming	ransmissionAcknowledgementRequest Juence ableDataPrototype_TC21 ableDataPrototype_TC21 ch references this dataSendPoint and
Summary	an application SW-C calls 'Rte_Fo acknowledgement status of the tr IpduGroup containing Signal_TC2	eedback' AP ansmission t 21Tx is in St successful tr	to the caller (SW-C). In case of op mode the transmission will be ansmission due to stopping of COM
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN sta ISignallPduGroup_TC21 shall be		mode.
Main Test Execu	ution		
Test Steps			Pass Criteria



	[RUN <runnableentity_tc21>] Invoke Rte_Write to write the dataElement VariableDataPrototype_TC21.</runnableentity_tc21>	[RUN <runnableentity_tc21>] Rte_Write returns RTE_E_COM_STOPPED.</runnableentity_tc21>
Step 2	-	[RUN <runnableentity_txerr>] RunnableEntity_TxErr is invoked.</runnableentity_txerr>
	[RUN <runnableentity_txerr>] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC21.</runnableentity_txerr>	[RUN <runnableentity_txerr>] Rte_Feedback returns RTE_E_COM_STOPPED.</runnableentity_txerr>
Post- conditions	NONE	

## 6.3.37 [ATS\_RTE\_00657] Explicit Nonqueued Inter-ECU Transmission error notification For DataElement Of Primitive Data Type (With WaitPoint)

Test Objective	Explicit Nonqueued Inter-ECU Transmission error notification For DataElement Of Primitive Data Type (With WaitPoint)		
ID	• • • • • • • • • • • • • • • • • • • •	,	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01137 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01284 RTE: SWS_Rte_04505 RTE: SWS_Rte_06011 RTE: SWS_Rte_07636 RTE: SWS_Rte_07822 RTE: SWS_Rte_07824		
Requirements / Reference to Test Environment			
Configuration Parameters	* a RunnableEntity to execute the - with a dataSendPoint which refe	pec with a To test sequer erences Varia a DataSend nt's timeout equest's time	ransmissionAcknowledgementRequest nce ableDataPrototype_TC22dCompletedEvent which references the equal to the above



	- Signal_TC22 mapped to ISignallPdu_TC22 with transferProperty triggered - configured with an EventControlledTiming - transmitted by the ECU * ISignallPduGroup_TC22 which references ISignallPdu_TC22		
	This test case is executed when the relevant I-PDU group is stopped. In such case Rte_Write and the following Rte_Feedback return RTE_E_COM_STOPPED without blocking.		
Needed Adaptation to other Releases			
	DUT shall be initialized EcuM module shall be in RUN state ISignallPduGroup_TC21 shall be in stopped mode.		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[SWC] Invoke Rte_Write to write the dataElement VariableDataPrototype_TC22.	[SWC] Rte_Write returns RTE_E_COM_STOPPED.	
Step 2	[SWC] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC22.	[SWC] Rte_Feedback returns RTE_E_COM_STOPPED.	
Post- conditions	NONE		

## 6.3.38 [ATS\_RTE\_00658] Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest timeout notification (Without WaitPoint, Primitive Data Type)

Test Objective	Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest timeout notification (Without WaitPoint, Primitive Data Type)		
ID	ATS_RTE_00658	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01137 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01285 RTE: SWS_Rte_01286 RTE: SWS_Rte_03754 RTE: SWS_Rte_03757 RTE: SWS_Rte_03757 RTE: SWS_Rte_04505 RTE: SWS_Rte_06011 RTE: SWS_Rte_06023 RTE: SWS_Rte_07637 RTE: SWS_Rte_07820 RTE: SWS_Rte_07824		



Requirements / Reference to Test Environment	A SW C with		
Configuration Parameters	A SW-C with  * a PPortPrototype which - sends VariableDataPrototype_TC23 typed by a primitive data type with swlmplPolicy 'standard' - has a NonqueuedSenderComSpec with a TransmissionAcknowledgementRequest with timeout value > 0  * RunnableEntity_TC23 to initiate the test sequence - with a dataSendPoint which references VariableDataPrototype_TC23  * RunnableEntity_TxTOut - with a dataSendPoint which references VariableDataPrototype_TC23 - started by a DataSendCompletedEvent which references this dataSendPoint and is not referenced by a WaitPoint  A communication matrix with  * Signal_TC23 - mapped to VariableDataPrototype_TC23  * ISignallPdu_TC23 - Signal_TC23 mapped to ISignallPdu_TC23 with transferProperty triggered - configured with an EventControlledTiming		
	- transmitted by the ECU		
Summary	This test case verifies that the RTE should support activation of a runnable when a COM callback for TransmissionAcknowledgementRequest timeout notification is invoked by COM and Rte_Feedback API should return RTE_E_TIMEOUT when TransmissionAcknowledgementRequest timeout notification is received from COM.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[RUN <runnableentity_tc23>] Invoke Rte_Write to write the dataElement VariableDataPrototype_TC23.</runnableentity_tc23>	[RUN <runnableentity_tc23>] Rte_Write returns RTE_E_OK.</runnableentity_tc23>	
Step 2	_	[RUN <runnableentity_txtout>] RunnableEntity_TxTOut is invoked.</runnableentity_txtout>	
Step 3	[RUN <runnableentity_txtout>] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC23.</runnableentity_txtout>	[RUN <runnableentity_txtout>] Rte_Feedback returns RTE_E_TIMEOUT.</runnableentity_txtout>	
Post- conditions	NONE		

# 6.3.39 [ATS\_RTE\_00659] Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest timeout notification (With WaitPoint, Primitive Data Type)

Test Objective	Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest timeout
	notification (With WaitPoint, Primitive Data Type)



			1
ID	ATS_RTE_00659	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01284 RTE: SWS_Rte_03532 RTE: SWS_Rte_04505 RTE: SWS_Rte_06023 RTE: SWS_Rte_07637 RTE: SWS_Rte_07820 RTE: SWS_Rte_07824		
Requirements / Reference to Test Environment			
Parameters	with timeout value > 0 * a RunnableEntity to execute the - with a dataSendPoint which refe	test sequer erences Varia a DataSend nt's timeout equest's time	ransmissionAcknowledgementRequest nce ableDataPrototype_TC24 dCompletedEvent which references the equal to the above eout)
	This test case verifies that if a callback for TransmissionAcknowledgementRequest timeout notification is configured then the RTE should support to wake up category 2 runnables from a WaitPoint as a result of COM callback for TransmissionAcknowledgementRequest timeout (Rte_Feedback does not stay blocked).		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN sta ComM channel shall be in COMM		MMUNICATION mode
Main Test Execu	ıtion		
Test Steps			Pass Criteria



•		[SWC] Rte_Write returns RTE_E_OK.
•	Invoke Rte_Feedback for the dataElement	[SWC] Rte_Feedback returns RTE_E_TIMEOUT.
Post- conditions	NONE	

### 6.3.40 [ATS\_RTE\_00660] Explicit Nonqueued Inter-ECU Reception On AliveTimeout Expiry For DataElement Of Primitive Data Type

Test Objective	Explicit Nonqueued Inter-ECU Reception On AliveTimeout Expiry For DataElement Of Primitive Data Type		
ID	ATS_RTE_00660	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01135 RTE: SWS_Rte_01289 RTE: SWS_Rte_01292 RTE: SWS_Rte_01359 RTE: SWS_Rte_02703 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_05022		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * an RPortPrototype to receive  - VariableDataPrototype_TC25 typed with a primitive data type with swImplPolicy  'standard'  - NonqueuedReceiverComSpec with aliveTimeout > 0 and handleTimeout = none  * RunnableEntity_DRE  - started by a DataReceivedEvent on reception of VariableDataPrototype_TC25  - with a dataReceivePointByArgument which references  VariableDataPrototype_TC25  * RunnableEntity_AliveTOut  - started by a DataReceiveErrorEvent which references  VariableDataPrototype_TC25  - with a dataReceivePointByArgument which references  VariableDataPrototype_TC25  - with a dataReceivePointByArgument which references  VariableDataPrototype_TC25  - mapped to VariableDataPrototype_TC25  - mapped to VariableDataPrototype_TC25  - received by the ECU		



Summary	This test case verifies that the RTE supports the activation of a runnable when a signal reception timeout occurs.	
Needed Adaptation to other Releases		
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode	
Main Test Execu	ution	
Test Steps		Pass Criteria
Step 1	[LT] Transmit a frame periodically with Signal_TC25.	[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>
Step 2	[RUN <runnableentity_dre>] Invoke Rte_Read to read the dataElement VariableDataPrototype_TC25.</runnableentity_dre>	[RUN <runnableentity_dre>] Rte_Read returns RTE_E_OK and provides the value sent periodically.</runnableentity_dre>
Step 3	[LT] Stop sending frame containing Signal_TC25 for more than the configured aliveTimeout.	[RUN <runnableentity_alivetout>] RunnableEntity_AliveTOut is invoked.</runnableentity_alivetout>
Step 4	[RUN <runnableentity_alivetout>] Invoke Rte_Read to read the dataElement VariableDataPrototype_TC25.</runnableentity_alivetout>	[RUN <runnableentity_alivetout>] Rte_Read returns RTE_E_MAX_AGE_EXCEEDED and provides the last value sent periodically (step 1).</runnableentity_alivetout>
Post- conditions	NONE	

# 6.3.41 [ATS\_RTE\_00661] Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest For DataElement With Array Data Type (Without WaitPoint)

Test Objective	Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest For DataElement With Array Data Type (Without WaitPoint)		
ID	ATS_RTE_00661	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01086 RTE: SWS_Rte_01137 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01285 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_04526 RTE: SWS_Rte_04527		



	RTE: SWS_Rte_06011 RTE: SWS_Rte_07820		
	RTE: SWS_Rte_07824		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * a PPortPrototype which - sends VariableDataPrototype_TC26array typed by an array data type with swlmplPolicy 'standard' - has a NonqueuedSenderComSpec with a TransmissionAcknowledgementRequest * RunnableEntity_TC26array to initiate the test sequence - with a dataSendPoint which references VariableDataPrototype_TC26array * RunnableEntity_TxAck - with a dataSendPoint which references VariableDataPrototype_TC26array - started by a DataSendCompletedEvent which references this dataSendPoint and is not referenced by a WaitPoint  A communication matrix with * SignalGroup_TC26array - mapped to VariableDataPrototype_TC26array * ISignallPdu_TC26array - SignalGroup_TC26array mapped to ISignallPdu_TC26array with transferProperty triggered - configured with an EventControlledTiming		
Summary	- transmitted by the ECU  This test case verifies the explicit nonqueued inter-ECU  TransmissionAcknowledgementRequest and activation of a runnable on a  DataSendCompletedEvent for a dataElement with an array type.		
Needed Adaptation to other Releases	·	, ,,	
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	ution		
Test Steps	I	Pass Criteria	
Step 1	[RUN <runnableentity_tc26array>] Invoke Rte_Write to write the dataElement VariableDataPrototype_TC26array.</runnableentity_tc26array>	[RUN <runnableentity_tc26array>] Rte_Write returns RTE_E_OK.</runnableentity_tc26array>	
Step 2	-	[RUN <runnableentity_txack>] RunnableEntity_TxAck is invoked.</runnableentity_txack>	
Step 3	[RUN <runnableentity_txack>] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC26array.</runnableentity_txack>	[RUN <runnableentity_txack>] Rte_Feedback returns RTE_E_TRANSMIT_ACK.</runnableentity_txack>	
Post- conditions	NONE		



# 6.3.42 [ATS\_RTE\_00662] Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest For DataElement With Record Data Type (Without WaitPoint)

Test Objective	Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest For		
	DataElement With Record Data	<u> </u>	· ·
ID	ATS_RTE_00662	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01086 RTE: SWS_Rte_01137 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01285 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_03531 RTE: SWS_Rte_04526 RTE: SWS_Rte_04527 RTE: SWS_Rte_06011 RTE: SWS_Rte_07820 RTE: SWS_Rte_07824		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * a PPortPrototype which - sends VariableDataPrototype_TC26record typed by a record data type with swlmplPolicy 'standard' - has a NonqueuedSenderComSpec with a TransmissionAcknowledgementRequest * RunnableEntity_TC26record to initiate the test sequence - with a dataSendPoint which references VariableDataPrototype_TC26record * RunnableEntity_TxAck - with a dataSendPoint which references VariableDataPrototype_TC26record - started by a DataSendCompletedEvent which references this dataSendPoint and is not referenced by a WaitPoint  A communication matrix with		
	* SignalGroup_TC26record - mapped to VariableDataPrototy * ISignalIPdu_TC26record - SignalGroup_TC26record mappetransferProperty triggered - configured with an EventContro - transmitted by the ECU This test case verifies the explicit	ped to ISigna lledTiming nonqueued	nllPdu_TC26record with
	TransmissionAcknowledgementF DataSendCompletedEvent for a	Request and	activation of a runnable on a



Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[RUN <runnableentity_tc26record>] Invoke Rte_Write to write the dataElement VariableDataPrototype_TC26record.</runnableentity_tc26record>	[RUN <runnableentity_tc26record>] Rte_Write returns RTE_E_OK.</runnableentity_tc26record>	
Step 2	-	[RUN <runnableentity_txack>] RunnableEntity_TxAck is invoked.</runnableentity_txack>	
Step 3	[RUN <runnableentity_txack>] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC26record.</runnableentity_txack>	[RUN <runnableentity_txack>] Rte_Feedback returns RTE_E_TRANSMIT_ACK.</runnableentity_txack>	
Post- conditions	NONE		

#### 6.3.43 [ATS\_RTE\_00663] Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest For DataElement With Array Data Type (With WaitPoint)

Test Objective	Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest For DataElement WIth Array Data Type (With WaitPoint)		
ID	ATS_RTE_00663	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01086 RTE: SWS_Rte_01137 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01284 RTE: SWS_Rte_03532 RTE: SWS_Rte_04526 RTE: SWS_Rte_04527 RTE: SWS_Rte_06011 RTE: SWS_Rte_07820 RTE: SWS_Rte_07824		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with * a PPortPrototype which		



	<ul> <li>sends VariableDataPrototype_TC27array typed by an array data type with swlmplPolicy 'standard'</li> <li>has a NonqueuedSenderComSpec with a TransmissionAcknowledgementRequest * a RunnableEntity to execute the test sequence</li> <li>with a dataSendPoint which references VariableDataPrototype_TC27array</li> <li>with a WaitPoint that references a DataSendCompletedEvent which references the previous dataSendPoint</li> </ul>		
	A communication matrix with  * SignalGroup_TC27array  - mapped to VariableDataPrototype_TC27array  * ISignalIPdu_TC27array  - SignalGroup_TC27array mapped to ISignalIPdu_TC27array with transferProperty triggered  - configured with an EventControlledTiming  - transmitted by the ECU		
Summary	This test case verifies the explicit nonqueued inter-ECU TransmissionAcknowledgementRequest and to wake up category 2 runnables from a WaitPoint as a result of successful transmission of an array.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[SWC] Invoke Rte_Write to write the dataElement VariableDataPrototype_TC27array.	[SWC] Rte_Write returns RTE_E_OK.	
Step 2	[SWC] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC27array.	[SWC] Rte_Feedback returns RTE_E_TRANSMIT_ACK.	
Post- conditions	NONE		

#### 6.3.44 [ATS\_RTE\_00664] Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest For DataElement With Record Data Type (With WaitPoint)

_	Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest For DataElement With Record Data Type (With WaitPoint)		
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01086		



Requirements /	RTE: SWS_Rte_01137 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01284 RTE: SWS_Rte_03532 RTE: SWS_Rte_04526 RTE: SWS_Rte_04527 RTE: SWS_Rte_06011 RTE: SWS_Rte_07820 RTE: SWS_Rte_07824		
Reference			
to Test			
Environment			
Configuration Parameters	A SW-C with  * a PPortPrototype which - sends VariableDataPrototype_TC27record typed by a record data type with swlmplPolicy 'standard' - has a NonqueuedSenderComSpec with a TransmissionAcknowledgementRequest * a RunnableEntity to execute the test sequence - with a dataSendPoint which references VariableDataPrototype_TC27record - with a WaitPoint that references a DataSendCompletedEvent which references the previous dataSendPoint  A communication matrix with  * SignalGroup_TC27record		
Summary	- mapped to VariableDataPrototype_TC27record  * ISignalIPdu_TC27record  - SignalGroup_TC27record mapped to ISignalIPdu_TC27record with transferProperty triggered  - configured with an EventControlledTiming - transmitted by the ECU		
	This test case verifies the explicit nonqueued inter-ECU TransmissionAcknowledgementRequest and to wake up category 2 runnables from a WaitPoint as a result of successful transmission of a record.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	Main Test Execution		
Test Steps		Pass Criteria	
Step 1	[SWC] Invoke Rte_Write to write the dataElement VariableDataPrototype_TC27record.	[SWC] Rte_Write returns RTE_E_OK.	
Step 2	[SWC] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC27record.	[SWC] Rte_Feedback returns RTE_E_TRANSMIT_ACK.	
Post- conditions	NONE		



### 6.3.45 [ATS\_RTE\_00665] Explicit Nonqueued Inter-ECU Transmission Error Notification For DataElement With Array Data Type (Without WaitPoint)

	Explicit Nonqueued Inter-ECU T With Array Data Type (Without V		Error Notification For DataElement
ID	ATS_RTE_00665	,	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01285 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_04526 RTE: SWS_Rte_04527 RTE: SWS_Rte_04527 RTE: SWS_Rte_06011 RTE: SWS_Rte_07636 RTE: SWS_Rte_07822 RTE: SWS_Rte_07824		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * a PPortPrototype which - sends VariableDataPrototype_TC28array typed by an array data type with swImplPolicy 'standard' - has a NonqueuedSenderComSpec with a TransmissionAcknowledgementRequest * RunnableEntity_TC28array to initiate the test sequence - with a dataSendPoint which references VariableDataPrototype_TC28array * RunnableEntity_TxErr - with a dataSendPoint which references VariableDataPrototype_TC28array - started by a DataSendCompletedEvent which references this dataSendPoint and is not referenced by a WaitPoint		
	A communication matrix with  * SignalGroup_TC28array  - mapped to VariableDataPrototy  * ISignalIPdu_TC28array  - SignalGroup_TC28array mapper  triggered  - configured with an EventControl  - transmitted by the ECU  * ISignalIPduGroup_TC28array in	ed to ISignall	Pdu_TC28array with transferProperty
Summary	an application SW-C calls 'Rte_F acknowledgement status of the t	Feedback' AF ransmission	



Needed Adaptation to other Releases		
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM shall be in COMM_NO_COMMUNICA	TION mode
Main Test Execu	ution	
Test Steps		Pass Criteria
•	[RUN <runnableentity_tc28array>] Invoke Rte_Write to write the dataElement VariableDataPrototype_TC28array.</runnableentity_tc28array>	[RUN <runnableentity_tc28array>] Rte_Write returns RTE_E_COM_STOPPED.</runnableentity_tc28array>
Step 2	-	[RUN <runnableentity_txerr>] RunnableEntity_TxErr is invoked.</runnableentity_txerr>
Step 3	[RUN <runnableentity_txerr>] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC28array.</runnableentity_txerr>	[RUN <runnableentity_txerr>] Rte_Feedback returns RTE_E_COM_STOPPED.</runnableentity_txerr>
Post- conditions	NONE	

### 6.3.46 [ATS\_RTE\_00666] Explicit Nonqueued Inter-ECU Transmission Error Notification For DataElement With Record Data Type (Without WaitPoint)

Test Objective	Explicit Nonqueued Inter-ECU Transmission Error Notification For DataElement With Record Data Type (Without WaitPoint)		
ID	ATS_RTE_00666		4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01285 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_04526 RTE: SWS_Rte_04527 RTE: SWS_Rte_04527 RTE: SWS_Rte_06011 RTE: SWS_Rte_07636 RTE: SWS_Rte_07822 RTE: SWS_Rte_07824		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * a PPortPrototype which  - sends VariableDataPrototype_T swImplPolicy 'standard'	C28record t	yped by a record data type with



	<ul> <li>has a NonqueuedSenderComSpec with a T</li> <li>RunnableEntity_TC28record to initiate the t</li> <li>with a dataSendPoint which references Var</li> <li>RunnableEntity_TxErr</li> <li>with a dataSendPoint which references Var</li> <li>started by a DataSendCompletedEvent whi</li> <li>is not referenced by a WaitPoint</li> <li>A communication matrix with</li> <li>SignalGroup_TC28record</li> </ul>	est sequence iableDataPrototype_TC28record iableDataPrototype_TC28record
	<ul> <li>mapped to VariableDataPrototype_TC28red</li> <li>ISignalIPdu_TC28record</li> <li>SignalGroup_TC28record mapped to ISignatransferProperty triggered</li> <li>configured with an EventControlledTiming</li> <li>transmitted by the ECU</li> <li>ISignalIPduGroup_TC28record which refere</li> </ul>	allPdu_TC28record with
Summary	This test case verifies that in case of explicit Sender-Receiver communication when an application SW-C calls 'Rte_Feedback' API RTE should provide the acknowledgement status of the transmission to the caller (SW-C). This test case forces a failure of the transmission by stopping the relevant I-PDU group.	
Needed Adaptation to other Releases		
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM shall be in COMM_NO_COMMUNICA	ATION mode
Main Test Execu	ution	
Test Steps		Pass Criteria
Step 1	[RUN <runnableentity_tc28record>] Invoke Rte_Write to write the dataElement VariableDataPrototype_TC28record.</runnableentity_tc28record>	[RUN <runnableentity_tc28record>] Rte_Write returns RTE_E_COM_STOPPED.</runnableentity_tc28record>
Step 2	-	[RUN <runnableentity_txerr>] RunnableEntity_TxErr is invoked.</runnableentity_txerr>
Step 3	[RUN <runnableentity_txerr>] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC28record.</runnableentity_txerr>	[RUN <runnableentity_txerr>] Rte_Feedback returns RTE_E_COM_STOPPED.</runnableentity_txerr>
Post- conditions	NONE	

## 6.3.47 [ATS\_RTE\_00667] Explicit Nonqueued inter-ECU Transmission error notification For DataElement With Array Data Type (With WaitPoint)

	Explicit Nonqueued inter-ECU Transmission error notification For DataElement With Array Data Type (With WaitPoint)		
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			



ltem	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01284 RTE: SWS_Rte_04526 RTE: SWS_Rte_04527 RTE: SWS_Rte_06011 RTE: SWS_Rte_07636 RTE: SWS_Rte_07822 RTE: SWS_Rte_07824	
Requirements / Reference to Test Environment		
Parameters	A SW-C with  * a PPortPrototype which - sends VariableDataPrototype_TC29array ty swImplPolicy 'standard' - has a NonqueuedSenderComSpec with a T * a RunnableEntity to execute the test sequer - with a dataSendPoint which references Vari - with a WaitPoint that references a DataSend previous dataSendPoint  A communication matrix with * SignalGroup_TC29array - mapped to VariableDataPrototype_TC29array * ISignalIPdu_TC29array - SignalGroup_TC29array mapped to ISignalI triggered - configured with an EventControlledTiming - transmitted by the ECU * ISignalIPduGroup_TC29array which reference	ransmissionAcknowledgementRequest nce ableDataPrototype_TC29array dCompletedEvent which references the ay
Summary	This test case is executed when the relevant Rte_Write and the following Rte_Feedback reblocking.	I-PDU group is stopped. In such case
Needed Adaptation to other Releases		
	DUT shall be initialized EcuM module shall be in RUN state ComM shall be in COMM_NO_COMMUNICA ISignallPduGroup_TC29array shall be in stop	
Main Test Execu	ution	
Test Steps		Pass Criteria
Step 1	[SWC] Invoke Rte_Write API to write the dataElement VariableDataPrototype_TC29array.	[SWC] Rte_Write returns RTE_E_COM_STOPPED.
Step 2	[SWC] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC29array.	[RTE] Rte_Feedback returns RTE_E_COM_STOPPED.
Post- conditions	NONE	



### 6.3.48 [ATS\_RTE\_00668] Explicit Nonqueued inter-ECU Transmission error notification For DataElement With Record Data Type (With WaitPoint)

Test Objective	Explicit Nonqueued inter-ECU Tra Record Data Type (With WaitPoir		error notification For DataElement With
ID	ATS_RTE_00668		4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01284 RTE: SWS_Rte_04526 RTE: SWS_Rte_04527 RTE: SWS_Rte_06011 RTE: SWS_Rte_07636 RTE: SWS_Rte_07822 RTE: SWS_Rte_07824		
Requirements / Reference to Test Environment			
Configuration Parameters	* a RunnableEntity to execute the - with a dataSendPoint which refe	pec with a Ti test sequer erences Varia	ransmissionAcknowledgementRequest nce
	* SignalGroup_TC29record - mapped to VariableDataPrototy  * ISignalIPdu_TC29record - SignalGroup_TC29record mapp transferProperty triggered - configured with an EventControl - transmitted by the ECU * ISignalIPduGroup_TC29record	ed to ISigna lledTiming which refere	IIPdu_TC29record with
Summary			I-PDU group is stopped. In such case sturn RTE_E_COM_STOPPED without
Needed Adaptation to other Releases			



Pre-conditions	DUT shall be initialized  EcuM module shall be in RUN state  ComM shall be in COMM_NO_COMMUNICATION state  ISignallPduGroup_TC29record shall be in stopped mode.	
Main Test Execu	ution	
Test Steps	Pass Criteria	
	[SWC] Invoke Rte_Write API to write the dataElement VariableDataPrototype_TC29record.	[SWC] Rte_Write returns RTE_E_COM_STOPPED.
Step 2	[SWC] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC29record.	[RTE] Rte_Feedback returns RTE_E_COM_STOPPED.
Post- conditions	NONE	

# 6.3.49 [ATS\_RTE\_00669] Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest Timeout Notification (Without WaitPoint, Array Data Type)

Test Objective	Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest Timeout Notification (Without WaitPoint, Array Data Type)		
ID	ATS_RTE_00669	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01137 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01285 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_06011 RTE: SWS_Rte_07637 RTE: SWS_Rte_07820		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * a PPortPrototype which - sends VariableDataPrototype_T swImplPolicy 'standard' - has a NonqueuedSenderComS  with timeout value > 0  * RunnableEntity_TC30array to ir - with a dataSendPoint which refe	pec with a Tr	ransmissionAcknowledgementRequest



	* RunnableEntity_TxTOut - with a dataSendPoint which references Vari - started by a DataSendCompletedEvent which is not referenced by a WaitPoint  A communication matrix with * SignalGroup_TC30array - mapped to VariableDataPrototype_TC30arr * ISignalIPdu_TC30array - SignalGroup_TC30array mapped to ISignall triggered - configured with an EventControlledTiming - transmitted by the ECU	ch references this dataSendPoint and
Summary	This test case verifies that the RTE should support activation of a runnable when a COM callback for TransmissionAcknowledgementRequest timeout notification is invoked by COM and Rte_Feedback API should return RTE_E_TIMEOUT when TransmissionAcknowledgementRequest timeout notification is received from COM.	
Needed Adaptation to other Releases		
Pre-conditions	DUT shall be initialized  EcuM module shall be in RUN state  ComM channel shall be in COMM_FULL_COMMUNICATION mode	
Main Test Execu	ution	
Test Steps		Pass Criteria
Step 1	[RUN <runnableentity_tc30array>] Invoke Rte_Write to write the dataElement VariableDataPrototype_TC30array.</runnableentity_tc30array>	[RUN <runnableentity_tc30array>] Rte_Write returns RTE_E_OK.</runnableentity_tc30array>
Step 2	-	[RUN <runnableentity_txtout>] RunnableEntity_TxTOut is invoked.</runnableentity_txtout>
Step 3	[RUN <runnableentity_txtout>] Invoke Rte_Feedback API for the dataElement VariableDataPrototype_TC30array.</runnableentity_txtout>	[RUN <runnableentity_txtout>] Rte_Feedback returns RTE_E_TIMEOUT.</runnableentity_txtout>
Post- conditions	NONE	

## 6.3.50 [ATS\_RTE\_00670] Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest Timeout Notification (Without WaitPoint, Record Data Type)

	Explicit Nonqueued Inter-ECU TransmissionAcknowledgementRequest Timeout Notification (Without WaitPoint, Record Data Type)		
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080		



Requirements /	RTE: SWS_Rte_01083 RTE: SWS_Rte_01137 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01285 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_06011 RTE: SWS_Rte_07637 RTE: SWS_Rte_07820	
Reference to Test Environment		
Configuration Parameters	A SW-C with  * a PPortPrototype which - sends VariableDataPrototype_TC30record tswImplPolicy 'standard' - has a NonqueuedSenderComSpec with a Twith timeout value > 0  * RunnableEntity_TC30record to initiate the test with a dataSendPoint which references Variates and Point With Point Poin	ransmissionAcknowledgementRequest est sequence ableDataPrototype_TC30record ableDataPrototype_TC30record ch references this dataSendPoint and
Summary	This test case verifies that the RTE should support activation of a runnable when a COM callback for TransmissionAcknowledgementRequest timeout notification is invoked by COM and Rte_Feedback API should return RTE_E_TIMEOUT when TransmissionAcknowledgementRequest timeout notification is received from COM.	
Needed Adaptation to other Releases		
	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_CO	MMUNICATION mode
Main Test Execu	ution	
Test Steps		Pass Criteria
Step 1	[RUN <runnableentity_tc30record>] Invoke Rte_Write to write the dataElement VariableDataPrototype_TC30record.</runnableentity_tc30record>	[RUN <runnableentity_tc30record>] Rte_Write returns RTE_E_OK.</runnableentity_tc30record>
Step 2	-	[RUN <runnableentity_txtout>] RunnableEntity_TxTOut is invoked.</runnableentity_txtout>
Step 3	[RUN <runnableentity_txtout>] Invoke Rte_Feedback API for the dataElement VariableDataPrototype_TC30record.</runnableentity_txtout>	[RUN <runnableentity_txtout>] Rte_Feedback returns RTE_E_TIMEOUT.</runnableentity_txtout>



Post-	NONE
conditions	

# 6.3.51 [ATS\_RTE\_00671] Explicit Nonqueued inter-ECU TransmissionAcknowledgementRequest timeout notification (With WaitPoint, Array Data Type)

	Explicit Nonqueued inter-ECU TransmissionAcknowledgementRequest timeout notification (With WaitPoint, Array Data Type)		
	ATS_RTE_00671		4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01284 RTE: SWS_Rte_03532 RTE: SWS_Rte_06011 RTE: SWS_Rte_07637 RTE: SWS_Rte_07820		
Requirements / Reference to Test Environment			
Parameters	with timeout value > 0 * a RunnableEntity to execute the - with a dataSendPoint which refe - with a WaitPoint that references previous dataSendPoint (WaitPoi TransmissionAcknowledgementR A communication matrix with * SignalGroup_TC31array - mapped to VariableDataPrototy * ISignalIPdu_TC31array	test sequer trences Varia a DataSend nt's timeout equest's time	ransmissionAcknowledgementRequest nce ableDataPrototype_TC31array dCompletedEvent which references the equal to the above neout)
Summary		hen the RTE	ansmissionAcknowledgementRequest E should support to wake up category OM callback for



	TransmissionAcknowledgementRequest timeout (Rte_Feedback does not stay blocked).		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_CO		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[SWC] Invoke Rte_Write to write the dataElement VariableDataPrototype_TC31array.	[SWC] Rte_Write returns RTE_E_OK.	
Step 2	[SWC] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC31array.	[SWC] Rte_Feedback returns RTE_E_TIMEOUT.	
Post- conditions	NONE		

# 6.3.52 [ATS\_RTE\_00672] Explicit Nonqueued inter-ECU TransmissionAcknowledgementRequest timeout notification (With WaitPoint, Record Data Type)

	Explicit Nonqueued inter-ECU TransmissionAcknowledgementRequest timeout notification (With WaitPoint, Record Data Type)		
ID	ATS_RTE_00672	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01071 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01280 RTE: SWS_Rte_01283 RTE: SWS_Rte_01284 RTE: SWS_Rte_03532 RTE: SWS_Rte_06011 RTE: SWS_Rte_07637 RTE: SWS_Rte_07820		
Requirements / Reference to Test Environment	1 12 12		
Configuration Parameters	A SW-C with  * a PPortPrototype which  - sends VariableDataPrototype_T swImplPolicy 'standard'  - has a NonqueuedSenderComS  with timeout value > 0		yped by a record data type with ransmissionAcknowledgementRequest



		-	
	* a RunnableEntity to execute the test sequence - with a dataSendPoint which references VariableDataPrototype_TC31record - with a WaitPoint that references a DataSendCompletedEvent which references the previous dataSendPoint (WaitPoint's timeout equal to the above TransmissionAcknowledgementRequest's timeout)		
	A communication matrix with  * SignalGroup_TC31record  - mapped to VariableDataPrototype_TC31record  * ISignalIPdu_TC31record  - SignalGroup_TC31record mapped to ISignalIPdu_TC31record with transferProperty triggered  - configured with an EventControlledTiming  - transmitted by the ECU		
Summary	This test case verifies that if a callback for TransmissionAcknowledgementRequest timeout notification is configured then the RTE should support to wake up category 2 runnables from a WaitPoint as a result of COM callback for TransmissionAcknowledgementRequest timeout (Rte_Feedback does not stay blocked).		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized  EcuM module shall be in RUN state  ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[SWC] Invoke Rte_Write to write the dataElement VariableDataPrototype_TC31record.	[SWC] Rte_Write returns RTE_E_OK.	
Step 2	[SWC] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC31record.	[SWC] Rte_Feedback returns RTE_E_TIMEOUT.	
Post- conditions	NONE		

## 6.3.53 [ATS\_RTE\_00673] Explicit Nonqueued Inter-ECU Reception On AliveTimeout Expiry For DataElement With Array Data Type

	Explicit Nonqueued Inter-ECU Reception On AliveTimeout Expiry For DataElement With Array Data Type		
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01135 RTE: SWS_Rte_01289 RTE: SWS_Rte_01292		



	DTE: CWC Dtc 04050		
	RTE: SWS_Rte_01359 RTE: SWS_Rte_02703		
	RTE: SWS_Rte_02703		
	RTE: SWS_Rte_03531		
	RTE: SWS_Rte_05022		
Requirements /			
Reference			
to Test			
Environment			
Configuration	A SW-C with		
Parameters	* an RPortPrototype to receive		
	- VariableDataPrototype_TC32array typed wi	th an array data type with swImplPolicy	
	standard' with an initValue (e.g. all subElements = 0x05)		
	<ul> <li>NonqueuedReceiverComSpec with aliveTim</li> </ul>	neout > 0 and handleTimeoutType =	
	replace		
	* RunnableEntity_DRE		
	<ul> <li>started by a DataReceivedEvent on reception</li> <li>VariableDataPrototype_TC32array</li> </ul>	on or	
	- with a dataReceivePointByArgument which	references	
	VariableDataPrototype_TC32array	references	
	* RunnableEntity_AliveTOut		
	- started by a DataReceiveErrorEvent which i	references	
	VariableDataPrototype_TC32array		
	- with a dataReceivePointByArgument which	references	
	VariableDataPrototype_TC32array		
	A communication matrix with		
	A communication matrix with * SignalGroup_TC32array		
	- mapped to VariableDataPrototype_TC32arr	av	
	- received by the ECU	a,	
Summary	This test case verifies that the RTE supports the activation of a runnable when a		
,	signal group reception timeout occurs.		
Needed			
Adaptation to			
other Releases			
Pre-conditions	DUT shall be initialized		
	EcuM module shall be in RUN state		
	ComM channel shall be in COMM_FULL_CO	MMUNICATION mode	
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[LT]	[RUN <runnableentity_dre>]</runnableentity_dre>	
•	Transmit a frame with	RunnableEntity_DRE is invoked.	
	SignalGroup_TC32array.	·	
Step 2	[RUN <runnableentity_dre>]</runnableentity_dre>	[RUN <runnableentity_dre>]</runnableentity_dre>	
	Invoke Rte_Read to read the dataElement	Rte_Read returns RTE_E_OK and	
	VariableDataPrototype_TC32array.	provides the value sent periodically.	
Step 3	[LT]	[RUN <runnableentity_alivetout>]</runnableentity_alivetout>	
	Stop sending frame containing	RunnableEntity_AliveTOut is invoked.	
	SignalGroup_TC32array for more than		
	configured aliveTimeout.		
Step 4	[RUN <runnableentity_alivetout>]</runnableentity_alivetout>	[RUN <runnableentity_alivetout>]</runnableentity_alivetout>	
	Invoke Rte_Read to read the dataElement	Rte_Read returns	
	VariableDataPrototype_TC32array.	RTE_E_MAX_AGE_EXCEEDED and provides the initValue.	
Post	NONE	provides the initivalue.	
Post- conditions	NONE		
Conditions			



### 6.3.54 [ATS\_RTE\_00674] Explicit Nonqueued Inter-ECU Reception On AliveTimeout Expiry For DataElement With Record Data Type

Test Objective		eception On	AliveTimeout Expiry For DataElement
	With Record Data Type	1	1
ID	ATS_RTE_00674	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01135 RTE: SWS_Rte_01289 RTE: SWS_Rte_01292 RTE: SWS_Rte_01359 RTE: SWS_Rte_02703 RTE: SWS_Rte_02530 RTE: SWS_Rte_03531 RTE: SWS_Rte_05022		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * an RPortPrototype to receive - VariableDataPrototype_TC32record typed with a record data type with swlmplPolicy 'standard' with an initValue (e.g. all subElements = 0x05) - NonqueuedReceiverComSpec with aliveTimeout > 0 and handleTimeout = replace * RunnableEntity_DRE - started by a DataReceivedEvent on reception of VariableDataPrototype_TC32record - with a dataReceivePointByArgument which references VariableDataPrototype_TC32record * RunnableEntity_AliveTOut - started by a DataReceiveErrorEvent which references VariableDataPrototype_TC32record - with a dataReceivePointByArgument which references VariableDataPrototype_TC32record - with a dataReceivePointByArgument which references VariableDataPrototype_TC32record  A communication matrix with * SignalGroup_TC32record - mapped to VariableDataPrototype_TC32record		
Summary Needed	This test case verifies that the RTE supports the activation of a runnable when a signal group reception timeout occurs.		
Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN st ComM channel shall be in COMI		MMUNICATION mode



Main Test Execution		
Test Steps		Pass Criteria
Step 1	[LT] Transmit a frame with SignalGroup_TC32record.	[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>
Step 2	[RUN <runnableentity_dre>] Invoke Rte_Read to read the dataElement VariableDataPrototype_TC32record.</runnableentity_dre>	[RUN <runnableentity_dre>] Rte_Read returns RTE_E_OK and provides the value sent periodically.</runnableentity_dre>
Step 3	[LT] Stop sending frame containing SignalGroup_TC32record for more than configured aliveTimeout.	[RUN <runnableentity_alivetout>] RunnableEntity_AliveTOut is invoked.</runnableentity_alivetout>
Step 4	[RUN <runnableentity_alivetout>] Invoke Rte_Read to read the dataElement VariableDataPrototype_TC32record.</runnableentity_alivetout>	[RUN <runnableentity_alivetout>] Rte_Read returns RTE_E_MAX_AGE_EXCEEDED and provides the initValue.</runnableentity_alivetout>
Post- conditions	NONE	

#### 6.3.55 [ATS\_RTE\_00675] Explicit Nonqueued Intra-Partition Rte\_DRead

Test Objective	Explicit Nonqueued Intra-Partitior	Rte_DRead	d
ID	ATS_RTE_00675	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01280 RTE: SWS_Rte_07394 RTE: SWS_Rte_07395 RTE: SWS_Rte_07820		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * A PPortPrototype to send - VariableDataPrototype_TC33 typed by a primitive data type with swImplPolicy 'standard'  * An RPortPrototype to receive VariableDataPrototype_TC33 - connected with the previous PPortPrototype  * A RunnableEntity to execute the test sequence - with a dataReceivePointByValue which references VariableDataPrototype_TC33 - with a dataSendPoint which references VariableDataPrototype_TC33		
Summary	A dataElement is written and later read using Rte_DRead. The data read shall be same as the data written.		
Needed Adaptation to other Releases			



Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state	
Main Test Exec	ution	
Test Steps		Pass Criteria
Step 1	[SWC] Invoke Rte_Write.	[SWC] Rte_Write returns RTE_E_OK.
Step 2	[SWC] Invoke Rte_DRead.	[SWC] Rte_DRead returns the data which was written in step 1.
Post- conditions	NONE	

#### 6.3.56 [ATS\_RTE\_00676] Explicit Nonqueued Inter-ECU Rte\_DRead

Toot Objective	Evaligit Nanguaged Inter ECH Dto. DDood		
	Explicit Nonqueued Inter-ECU Rte_DRead		
ID	ATS_RTE_00676	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01135 RTE: SWS_Rte_01292 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_04505 RTE: SWS_Rte_06011 RTE: SWS_Rte_07394 RTE: SWS_Rte_07395		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * A RPortPrototype to receive - VariableDataPrototype_TC34 typed by a primitive data type with swImplPolicy 'standard'  * RunnableEntity_DRE - started by a DataReceivedEvent on reception of VariableDataPrototype_TC34 - with a dataReceivePointByValue which references VariableDataPrototype_TC34  A communication matrix with  * Signal_TC34 - mapped to VariableDataPrototype_TC34 - received by the ECU		
Summary	A signal is sent on the bus which VariableDataPrototype associate checks that the data read is the s	d to the sign	al with an Rte_DRead API. The test
Needed Adaptation to other Releases			



	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode	
Main Test Execu	ution	
Test Steps	Pass Criteria	
Step 1	[LT] Transmit a frame with Signal_TC34.	[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>
Step 2	[RUN <runnableentity_dre>] Invoke Rte_DRead.</runnableentity_dre>	[RUN <runnableentity_dre>] Rte_DRead returns the data which was sent in step 1.</runnableentity_dre>
Post- conditions	NONE	

#### 6.3.57 [ATS\_RTE\_00677] Queued Intra-partition Rte\_Send And Rte\_Receive

	Queued Intra-partition Rte_Send		
ID	ATS_RTE_00677	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01072 RTE: SWS_Rte_01092 RTE: SWS_Rte_01094 RTE: SWS_Rte_01281 RTE: SWS_Rte_01288 RTE: SWS_Rte_02633 RTE: SWS_Rte_06011 RTE: SWS_Rte_07673		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * A PPortPrototype to send - VariableDataPrototype_TC35 typed by a primitive data type with swImplPolicy 'queued'  * An RPortPrototype to receive VariableDataPrototype_TC35 - connected with the previous PPortPrototype  * A RunnableEntity to execute the test sequence - with a dataReceivePointByArgument which references VariableDataPrototype_TC35 - with a dataSendPoint which references VariableDataPrototype_TC35		
Summary	The test checks the behaviour of Rte_Receive before any event was sent and checks that an event can be sent and received correctly.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN sta	ate	



Main Test Exe	Main Test Execution		
Test Steps		Pass Criteria	
Step 1	[SWC] Invoke Rte_Receive for the dataElement VariableDataPrototype_TC35.	[RTE] Rte_Receive returns RTE_E_NO_DATA and does not change the buffer provided as argument.	
Step 2	[SWC] Invoke Rte_Send for the dataElement VariableDataPrototype_TC35.	[SWC] Rte_Send returns RTE_E_OK.	
Step 3	[SWC] Invoke Rte_Receive for the dataElement VariableDataPrototype_TC35.	[SWC] Rte_Receive returns RTE_E_OK and provides the data (event) sent in step 2.	
Post- conditions	NONE		

#### 6.3.58 [ATS\_RTE\_00678] Queued Inter-ECU Transmission With Successful Acknowledgement Request

Test Objective	Queued Inter-ECU Transmission With Successful Acknowledgement Request		
ID	ATS_RTE_00678	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01072 RTE: SWS_Rte_01083 RTE: SWS_Rte_01086 RTE: SWS_Rte_01137 RTE: SWS_Rte_01281 RTE: SWS_Rte_01283 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_06011		
Requirements / Reference to Test Environment			
Configuration Parameters	<ul> <li>* RunnableEntity_TC36 to initiate</li> <li>- with a dataSendPoint which refe</li> <li>* RunnableEntity_TxAck</li> <li>- with a dataSendPoint which refe</li> </ul>	with a Trans the test seq erences Varia	smissionAcknowledgementRequest luence ableDataPrototype_TC36



	A communication matrix with  * Signal_TC36 - mapped to VariableDataPrototype_TC36  * ISignalIPdu_TC36 - Signal_TC36 mapped to ISignalIPdu_TC36 with transferProperty triggered - configured with an EventControlledTiming - transmitted by the ECU		
Summary	The test checks that the acknowledgment of an event (queued) inter-ECU transmission can activate a runnable and that the Rte_Feedback API provides the acknowledgement status.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[RUN <runnableentity_tc36>] Invoke Rte_Send for the dataElement VariableDataPrototype_TC36.</runnableentity_tc36>	[RUN <runnableentity_tc36>] Rte_Send returns RTE_E_OK.</runnableentity_tc36>	
Step 2	-	[LT] Signal_TC36 within the respective frame is observed on the bus.	
Step 3	-	[RUN <runnableentity_txack>] RunnableEntity_TxAck is invoked.</runnableentity_txack>	
Step 4	[RUN <runnableentity_txack>] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC36.</runnableentity_txack>	[RUN <runnableentity_txack>] Rte_Feedback returns RTE_E_TRANSMIT_ACK.</runnableentity_txack>	
Post- conditions	NONE		

#### 6.3.59 [ATS\_RTE\_00679] Queued Inter-ECU Transmission Error Notification

Test Objective	Queued Inter-ECU Transmission Error Notification		
ID	ATS_RTE_00679	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Item	RTE: SWS_Rte_01072 RTE: SWS_Rte_01080 RTE: SWS_Rte_01083 RTE: SWS_Rte_01137 RTE: SWS_Rte_01281 RTE: SWS_Rte_01283 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_06011 RTE: SWS_Rte_07636		



Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * a PPortPrototype which - sends VariableDataPrototype_TC37 typed by a primitive data type with swlmplPolicy 'queued' - has a QueuedSenderComSpec with a TransmissionAcknowledgementRequest * RunnableEntity_TC37 to initiate the test sequence - with a dataSendPoint which references VariableDataPrototype_TC37  * RunnableEntity_TxErr - with a dataSendPoint which references VariableDataPrototype_TC37 - started by a DataSendCompletedEvent which references this dataSendPoint and is not referenced by a WaitPoint  A communication matrix with * Signal_TC37 - mapped to VariableDataPrototype_TC37 * ISignallPdu_TC37 - Signal_TC37 mapped to ISignallPdu_TC37 with transferProperty triggered - configured with an EventControlledTiming - transmitted by the ECU		
Summary	The test is executed in COMM_NO_COMMUNICATION mode to trigger a transmission failure. The test checks that transmission error of event can activate a runnable and that the Rte_Feedback API provides the error status RTE_E_COM_STOPPED.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM shall be in COMM_NO_COMMUNICATION mode		
Main Test Execu	ution		
Test Steps	IDIN D. LLE W. TOOL !	Pass Criteria	
Step 1	[RUN <runnableentity_tc37>] Invoke Rte_Send for the dataElement VariableDataPrototype_TC37.</runnableentity_tc37>	[RUN <runnableentity_tc37>] Rte_Send returns RTE_E_COM_STOPPED.</runnableentity_tc37>	
Step 2	-	[RUN <runnableentity_txerr>] RunnableEntity_TxAck is invoked.</runnableentity_txerr>	
Step 3	[RUN <runnableentity_txerr>] Invoke Rte_Feedback for the dataElement VariableDataPrototype_TC37.</runnableentity_txerr>	[RUN <runnableentity_txerr>] Rte_Feedback returns RTE_E_COM_STOPPED.</runnableentity_txerr>	
Post- conditions	NONE		

## 6.3.60 [ATS\_RTE\_00680] Queued Inter-ECU Rte\_Receive For DataElement Of Primitive Data Type

Test Objective	Queued Inter-ECU Rte_Receive For DataElement Of Primitive Data Type		
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed



Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01092 RTE: SWS_Rte_01135 RTE: SWS_Rte_01292 RTE: SWS_Rte_02598 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_04505 RTE: SWS_Rte_06011		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * an RPortPrototype which receives - VariableDataPrototype_TC38 typed by a pri 'queued'  * RunnableEntity_DRE - started by a DataReceivedEvent on receptic - with a dataReceivePointByArgument which VariableDataPrototype_TC38  A communication matrix with  * Signal_TC38 - mapped to VariableDataPrototype_TC38 - received by the ECU	on of VariableDataPrototype_TC38	
Summary	The test checks that in case of successful reception of a dataElement of primitive data type in a queued inter-ECU communication a DataReceivedEvent can activate a RunnableEntity and the Rte_Receive API provides the received event.		
Needed Adaptation to other Releases			
	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	ition		
Test Steps		Pass Criteria	
	[LT] Transmit frame withSignal_TC38.	[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>	
Step 2	[RUN <runnableentity_dre>] Invoke the Rte_Receive API for the dataElement VariableDataPrototype_TC38.</runnableentity_dre>	[RUN <runnableentity_dre>] Rte_Receive returns RTE_E_OK and provides the data sent in Signal_TC38.</runnableentity_dre>	
Post- conditions	NONE		

#### 6.3.61 [ATS\_RTE\_00681] Queued Inter-ECU Rte\_Receive For DataElement With Array Data Type

Test Objective	Queued Inter-ECU Rte_Receive For DataElement With Array Data Type



		Т	
ID	ATS_RTE_00681	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01092 RTE: SWS_Rte_01135 RTE: SWS_Rte_01292 RTE: SWS_Rte_02598 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_04527 RTE: SWS_Rte_06011		
Requirements / Reference to Test Environment			
Configuration Parameters	'queued'  * RunnableEntity_DRE  - started by a DataReceivedEven VariableDataPrototype_TC39arra  - with a dataReceivePointByArgu VariableDataPrototype_TC39arra  A communication matrix with  * SignalGroup_TC39array  - mapped to VariableDataPrototy  - received by the ECU	t on reception  t on reception  ment which  y  pe_TC39arra	references ay
Summary	The test checks that in case of successful reception of a dataElement with array data type in a queued inter-ECU communication a DataReceivedEvent can activate a RunnableEntity and the Rte_Receive API provides the received event.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN sta ComM channel shall be in COMM		MMUNICATION mode
Main Test Execu	ution		
Test Steps			Pass Criteria
Step 1	[LT] Transmit frame with SignalGroup_TC39array.		[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>
Step 2	[RUN <runnableentity_dre>] Invoke Rte_Receive for the dataE VariableDataPrototype_TC39arra</runnableentity_dre>		[RUN <runnableentity_dre>] Rte_Receive returns RTE_E_OK and provides the data sent in SignalGroup_TC39array.</runnableentity_dre>
Post- conditions	NONE		



#### 6.3.62 [ATS\_RTE\_00682] Queued Inter-ECU Rte\_Receive For DataElement With Record Data Type

	Ia a		
	Queued Inter-ECU Rte_Receive For DataElement With Record Data Type		
ID	ATS_RTE_00682	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
	RTE: SWS_Rte_01092 RTE: SWS_Rte_01135 RTE: SWS_Rte_01292 RTE: SWS_Rte_02598 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_04527 RTE: SWS_Rte_06011		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * an RPortPrototype which receives  - VariableDataPrototype_TC39record typed by a record data type with swImplPolicy 'queued'  * RunnableEntity_DRE  - started by a DataReceivedEvent on reception of VariableDataPrototype_TC39record  - with a dataReceivePointByArgument which references VariableDataPrototype_TC39record  A communication matrix with  * SignalGroup_TC39record  - mapped to VariableDataPrototype_TC39record  - received by the ECU		
Summary	The test checks that in case of successful reception of a dataElement with record data type in a queued inter-ECU communication a DataReceivedEvent can activate a RunnableEntity and the Rte_Receive API provides the received event.		
Needed Adaptation to other Releases	- ,		
	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	ution		
Test Steps			Pass Criteria
Step 1	[LT] Transmit frame with SignalGroup_TC39record.		[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>
Step 2	[RUN <runnableentity_dre>] Invoke Rte_Receive for the dataE VariableDataPrototype_TC39reco</runnableentity_dre>		[RUN <runnableentity_dre>] Rte_Receive returns RTE_E_OK and provides the data sent in SignalGroup_TC39record.</runnableentity_dre>



Post-	NONE
conditions	

## 6.3.63 [ATS\_RTE\_00683] Inter-ECU Rte\_IsUpdated API Functionality

Test Objective	Inter-ECU Rte_IsUpdated API Functionality		
ID	ATS_RTE_00683	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01135 RTE: SWS_Rte_01289 RTE: SWS_Rte_01292 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_07385 RTE: SWS_Rte_07386 RTE: SWS_Rte_07390 RTE: SWS_Rte_07391 RTE: SWS_Rte_07392		
Requirements / Reference to Test Environment	RTE: SWS_Rte_07393		
Configuration Parameters	A SW-C with  * an RPortPrototype which receives - VariableDataPrototype_TC41 typed by a primitive data type with swImplPolicy 'standard' - NonqueuedReceiverComSpec with enableUpdate = TRUE  * RunnableEntity_TC41 to initiate the test sequence - with a dataReceivePointByArgument which references VariableDataPrototype_TC41  * RunnableEntity_DRE - started by a DataReceivedEvent on reception of VariableDataPrototype_TC41 - with a dataReceivePointByArgument which references VariableDataPrototype_TC41  A communication matrix with  * Signal_TC41 - mapped to VariableDataPrototype_TC41 - received by the ECU		
Summary	This test checks that after reception of a signal configured for an inter-ECU reception with the enableUpdate attribute set to TRUE the corresponding enable flag is provided by the Rte_IsUpdated API and that subsequent calls to Rte_IsUpdated without signal reception return FALSE.		
Needed Adaptation to other Releases			



Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[RUN <runnableentity_tc41>] Invoke Rte_IsUpdated for the dataElement VariableDataPrototype_TC41.</runnableentity_tc41>	[RUN <runnableentity_tc41>] Rte_IsUpdated returns FALSE</runnableentity_tc41>	
Step 2	[LT] Transmit a frame with Signal_TC41.	[RUN <runnableentity_dre>] RunnableEntity_DRE is invoked.</runnableentity_dre>	
Step 3	[RUN <runnableentity_dre>] Invoke Rte_IsUpdated for the dataElement VariableDataPrototype_TC41.</runnableentity_dre>	[RUN <runnableentity_dre>] Rte_IsUpdated returns TRUE.</runnableentity_dre>	
Step 4	[RUN <runnableentity_dre>] Invoke Rte_Read for the dataElement VariableDataPrototype_TC41.</runnableentity_dre>	[RUN <runnableentity_dre>] Rte_Read returns RTE_E_OK and provides the Signal_TC41 value sent in step 2.</runnableentity_dre>	
Step 5	[RUN <runnableentity_dre>] Invoke Rte_IsUpdated for the dataElement VariableDataPrototype_TC41.</runnableentity_dre>	[RUN <runnableentity_dre>] Rte_IsUpdated returns FALSE.</runnableentity_dre>	
Post- conditions	NONE		

# 6.3.64 [ATS\_RTE\_00684] Intra-Partition Rte\_IsUpdated API Functionality

Test Objective	Intra-Partition Rte_IsUpdated API Functionality		
ID	ATS_RTE_00684	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01071 RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01280 RTE: SWS_Rte_01289 RTE: SWS_Rte_06011 RTE: SWS_Rte_07385 RTE: SWS_Rte_07386 RTE: SWS_Rte_07390 RTE: SWS_Rte_07391 RTE: SWS_Rte_07392 RTE: SWS_Rte_07393 RTE: SWS_Rte_07820		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with * A PPortPrototype to send - VariableDataPrototype_TC42 typed by a primitive data type with swImplPolicy		



	'standard'  * An RPortPrototype to receive VariableDataPrototype_TC42  - connected with the previous PPortPrototype  - NonqueuedReceiverComSpec with enableUpdate = TRUE  * A RunnableEntity to execute the test sequence  - with a dataReceivePointByArgument which references  VariableDataPrototype_TC42  - with a dataSendPoint which references VariableDataPrototype_TC42		
Summary	To verify setting of update flag of the dataElements configured with the "enableUpdate" attribute in case explicit nonqueued intra-partition reception (Rte_Read).  This test checks that in case of intra-partition communication with the enableUpdate set to TRUE on the receiver side after transmission of a dataElement the corresponding enable flag is provided by the Rte_IsUpdated API and that subsequent calls to Rte_IsUpdated without transmission of the DataElement return FALSE.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state		
Main Test Execu	ution		
Test Steps	Pass Criteria		
Step 1	[SWC] Invoke Rte_IsUpdated for the dataElement VariableDataPrototype_TC42.	[SWC] Rte_IsUpdated returns FALSE.	
Step 2	[SWC] Invoke Rte_Write for the dataElement VariableDataPrototype_TC42.	[SWC] Rte_Write returns RTE_E_OK.	
Step 3	[SWC] Invoke Rte_IsUpdated for the dataElement VariableDataPrototype_TC42.	[SWC] Rte_IsUpdated returns TRUE.	
Step 4	[SWC] Invoke Rte_Read for the dataElement VariableDataPrototype_TC42.	[SWC] Rte_Read returns RTE_E_OK and provides the value written in step 1.	
Step 5	[SWC] Invoke Rte_IsUpdated for the dataElement VariableDataPrototype_TC42.	[SWC] Rte_IsUpdated returns FALSE.	
Post- conditions	NONE		

# 6.3.65 [ATS\_RTE\_00685] Implicit Write For Intra-Partition Sender Receiver Communication Using Rte\_IWriteRef API

_	Implicit Write For Intra-Partition Sender Receiver Communication Using Rte_IWriteRef API		
ID	ATS_RTE_00685		
Affected Modules	RTE	State	reviewed
Trace to Requirement			



	1		
on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01301 RTE: SWS_Rte_03741		
item	RTE: SWS_Rte_05741 RTE: SWS_Rte_05509		
	RTE: SWS_Rte_05510		
	RTE: SWS_Rte_05511		
	RTE: SWS_Rte_06004		
	RTE: SWS_Rte_06011		
Requirements / Reference to Test Environment			
Configuration	A SW-C with		
Parameters	* A PPortPrototype to send		
	- VariableDataPrototype_TC45 with swImplP		
	* An RPortPrototype to receive VariableDataF		
	<ul><li>connected with the previous PPortPrototype</li><li>RunnableEntity_TC45 to execute the test se</li></ul>		
	- with a dataReadAccess which references V		
	- with a dataWriteAccess which references Va		
Summary	This test case verifies implicit intra-partition S		
Summary			
	Rte_IWriteRef API to write the value into the dataElement and Rte_IRead to read the value written into the dataElement.		
Needed			
Adaptation to			
other Releases			
Pre-conditions	DUT shall be initialized		
	EcuM module shall be in RUN state		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[RUN <runnableentity_tc45>]</runnableentity_tc45>	-	
	Invoke Rte IWriteRef to write the		
	dataElement VariableDataPrototype_TC45.		
	Write some data (Ex:0x20) in the buffer		
	provided by Rte_IWriteRef.		
Step 2	[RUN <runnableentity_tc45>]</runnableentity_tc45>	-	
	Return to exit from this		
	RunnableEntity_TC45 execution-instance.		
Step 3	[CP]	[RUN <runnableentity_tc45>]</runnableentity_tc45>	
	Wait for the next execution-instance of	RunnableEntity_TC45 is invoked	
	RunnableEntity_TC45.		
Step 4	[RUN <runnableentity_tc45>]</runnableentity_tc45>	[RUN <runnableentity_tc45>]</runnableentity_tc45>	
	Invoke Rte_IRead to read the dataElement	Rte_IRead returns the data which	
	VariableDataPrototype_TC45.	was written in step 1 (Ex: 0x20).	
Post-	NONE		
	NONE		
conditions	I TOTAL		

# 6.3.66 [ATS\_RTE\_00686] Rte\_IFeedback API Functionality For Successful Transmission

Test Objective Rte_IFeedback API Functionality For Successful Transmission
----------------------------------------------------------------------------



ID	ATS_RTE_00686	AUTOSAR	4.0.3 4.2.1 4.2.2
		Releases	• •
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01302 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_03744 RTE: SWS_Rte_03746 RTE: SWS_Rte_04505 RTE: SWS_Rte_04505 RTE: SWS_Rte_07367 RTE: SWS_Rte_07376 RTE: SWS_Rte_07379 RTE: SWS_Rte_07647 RTE: SWS_Rte_07648		
Requirements / Reference to Test Environment			
	A SW-C with  * a PPortPrototype which - sends VariableDataPrototype_TC49 typed by a primitive data type with swlmplPolicy 'standard' - has a QueuedSenderComSpec with a TransmissionAcknowledgementRequest * RunnableEntity_TC49 to initiate the test sequence - with a dataWriteAccess which references VariableDataPrototype_TC49 * RunnableEntity_IFeedBackTC49 - with a dataWriteAccess which references VariableDataPrototype_TC49 - started by a DataWriteCompletedEvent which references this dataWriteAccess  A communication matrix with * Signal_TC49 - mapped to VariableDataPrototype_TC49 * ISignallPdu_TC49 - Signal_TC49 mapped to ISignallPdu_TC49 with transferProperty triggered - configured with an EventControlledTiming - transmitted by the ECU		
	The test checks that after a succ	ggered and	smission with Rte_IWrite a the Rte_IFeedback provides access to
Needed Adaptation to other Releases			
conditions	DUT shall be initialized EcuM module shall be in RUN s ComM channel shall be in COM		OMMUNICATION mode
Main Test Exec	cution		
Test Steps			Pass Criteria



	[RUN <runnableentity_tc49>] Invoke Rte_IWrite to write the dataElement VariableDataPrototype_TC49.</runnableentity_tc49>	-
	Return to exit from this	[LT] A frame with Signal_TC49 is observed on the bus with the value written in step 1.
Step 3		[RUN <runnableentity_ifeedbacktc49>] RunnableEntity_IFeedBackTC49 is invoked.</runnableentity_ifeedbacktc49>
	Invoke Rte_IFeedback for the dataElement	[RUN <runnableentity_ifeedbacktc49>] Rte_IFeedback returns RTE_E_TRANSMIT_ACK.</runnableentity_ifeedbacktc49>
Post- conditions	NONE	

# 6.3.67 [ATS\_RTE\_00687] Rte\_IFeedback API Functionality For Transmission Error

Test Objective	Rte_IFeedback API Functionalit	y For Trans	mission Error
ID	ATS_RTE_00687	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on			
Acceptance Test			
Document	DTE OWO DU 04000		
ltem	RTE: SWS_Rte_01302 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_03744 RTE: SWS_Rte_03746 RTE: SWS_Rte_04505 RTE: SWS_Rte_07367 RTE: SWS_Rte_07375 RTE: SWS_Rte_07379 RTE: SWS_Rte_07647 RTE: SWS_Rte_07647 RTE: SWS_Rte_07648		
/ Reference to Test Environment			
Configuration Parameters	* a PPortPrototype which - sends VariableDataPrototype_ swlmplPolicy 'standard' - has a QueuedSenderComSpeet * RunnableEntity_TC50 to initiat - with a dataWriteAccess which * RunnableEntity_IFeedBackTC - with a dataWriteAccess which	c with a Tra e the test so references ' 50 references '	nsmissionAcknowledgementRequest equence VariableDataPrototype_TC50



	A communication matrix with  * Signal_TC50 - mapped to VariableDataPrototype_TC50  * ISignalIPdu_TC50 - Signal_TC50 mapped to ISignalIPdu_TC5 - configured with an EventControlledTiming - transmitted by the ECU		
Summary	The test checks that after a failed transmission (due to COMM_NO_COMMUNICATION mode) with Rte_IWrite a DataWriteCompletedEvent is triggered and the Rte_IFeedback provides access to the transmission error.		
Needed Adaptation to other Releases			
Pre- conditions	DUT shall be initialized EcuM module shall be in RUN state ComM shall be in COMM_NO_COMMUNICATION mode		
Main Test Exec	cution		
Test Steps		Pass Criteria	
Step 1	[RUN <runnableentity_tc50>] Invoke Rte_IWrite to write the dataElement VariableDataPrototype_TC50.</runnableentity_tc50>	-	
Step 2	[RUN <runnableentity_tc50>] Return to exit from this RunnableEntity_TC50 execution-instance.</runnableentity_tc50>	[RUN <runnableentity_ifeedbacktc50>] RunnableEntity_IFeedBackTC50 is invoked.</runnableentity_ifeedbacktc50>	
Step 3	Invoke Rte_IFeedback for the dataElement	[RUN <runnableentity_ifeedbacktc50>] Rte_IFeedback returns RTE_E_COM_STOPPED.</runnableentity_ifeedbacktc50>	
Post- conditions	NONE		

# 6.3.68 [ATS\_RTE\_00688] Rte\_IFeedback API Functionality For Transmission Acknowledgement Timeout

Test Objective	Rte_IFeedback API Functionality For Transmission Acknowledgement Timeout		
ID	ATS_RTE_00688	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01302 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531 RTE: SWS_Rte_03744 RTE: SWS_Rte_03746 RTE: SWS_Rte_04505 RTE: SWS_Rte_07367 RTE: SWS_Rte_07379 RTE: SWS_Rte_07647 RTE: SWS_Rte_07648		



	RTE: SWS_Rte_07650		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * a PPortPrototype which - sends VariableDataPrototype_TC51 typed by a primitive data type with swImplPolicy 'standard' - has a NonqueuedSenderComSpec with a TransmissionAcknowledgementRequest with timeout value > 0  * RunnableEntity_TC51 to initiate the test sequence - with a dataWriteAccess which references VariableDataPrototype_TC51  * RunnableEntity_TxTOut - with a dataWriteAccess which references VariableDataPrototype_TC51 - started by a DataWriteCompletedEvent which references this dataWriteAccess  A communication matrix with  * Signal_TC51 - mapped to VariableDataPrototype_TC51  * ISignallPdu_TC51 - Signal_TC51 mapped to ISignallPdu_TC51 with transferProperty triggered - configured with an EventControlledTiming - transmitted by the ECU		
Summary	The test checks that after a failure to transmit data on time with Rte_IWrite a DataWriteCompletedEvent is triggered and the Rte_IFeedback provides access to the transmission error.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_COMMUNICATION mode		
Main Test Execu	ution		
Test Steps	TOUR DE LES CONTROLS	Pass Criteria	
Step 1	[RUN <runnableentity_tc51>] Invoke Rte_IWrite to write the dataElement VariableDataPrototype_TC51.</runnableentity_tc51>		
Step 2	-	[RUN <runnableentity_txtout>] RunnableEntity_TxTOut is invoked</runnableentity_txtout>	
Step 3	[RUN <runnableentity_txtout>] Invoke Rte_IFeedback for the dataElement VariableDataPrototype_TC51.</runnableentity_txtout>	[RUN <runnableentity_txtout>] Rte_IFeedback returns RTE_E_TIMEOUT.</runnableentity_txtout>	
Post- conditions	NONE		

## 6.3.69 [ATS\_RTE\_00689] Data Invalidation For Implicit Communication

Test Objective	Data Invalidation For Implicit Communication		
ID	ATS_RTE_00689		
Affected Modules	RTE	State	reviewed



Trace to Requirement			
on Acceptance			
Test Document			
Trace to SWS	RTE: SWS_Rte_01301		
Item	RTE: SWS_Rte_01302		
	RTE: SWS_Rte_02599 RTE: SWS_Rte_02600		
	RTE: SWS_Rte_02603		
	RTE: SWS_Rte_03741		
	RTE: SWS_Rte_03744 RTE: SWS_Rte_03746		
	RTE: SWS_Rte_03800		
	RTE: SWS_Rte_03801		
	RTE: SWS_Rte_06004		
Requirements /	RTE: SWS_Rte_06011		
Reference			
to Test			
Environment			
Configuration Parameters	A SW-C with		
Parameters	* A PPortPrototype to send - sends VariableDataPrototype_TC54 with sw	vImplPolicy 'standard'	
	- is typed by a SenderReceiverInterface with		
	VariableDataPrototype_TC54 (handleInvalid		
	* An RPortPrototype to receive VariableDatal - connected with the previous PPortPrototype		
	* RunnableEntity_TC54 to execute the test se		
	- with a dataReadAccess which references VariableDataPrototype_TC54		
	- with a dataWriteAccess which references VariableDataPrototype_TC54		
Summary	The test invalidates a dataElement using the Rte_IInvalidate API and checks that		
	the access to the status in another execution-instance using the Rte_IStatus API after a successful transmission with Rte_IWrite		
Needed			
Adaptation to other Releases			
	DUT shall be initialized		
	EcuM module shall be in RUN state		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[RUN <runnableentity_tc54>]</runnableentity_tc54>	ŀ	
	Invoke Rte_IWrite to write the dataElement VariableDataPrototype_TC54.		
Step 2	[RUN <runnableentity_tc54>]</runnableentity_tc54>	-	
- 40.0	Return to exit from this		
	RunnableEntity_TC54 execution-instance.		
Step 3	[CP]	[RUN <runnableentity_tc54>]</runnableentity_tc54>	
	Wait for the next execution-instance of RunnableEntity_TC54.	RunnableEntity_TC54 is invoked.	
Step 4	[RUN <runnableentity_tc54>]</runnableentity_tc54>	-	
	Invoke Rte_IInvalidate for the dataElement		
	VariableDataPrototype_TC54.		
Step 5	[RUN <runnableentity_tc54>] Invoke Rte_IStatus for the dataElement</runnableentity_tc54>	[RUN <runnableentity_tc54>] Rte_IStatus returns RTE_E_OK.</runnableentity_tc54>	
	VariableDataPrototype_TC54.	Nie_iolalus ieluiiis Nie_e_ON.	
	71 =		



Step 6	[RUN <runnableentity_tc54>] Return to exit from this RunnableEntity_TC54 execution-instance.</runnableentity_tc54>	-
Step 7	[CP] Wait for the next execution-instance of RunnableEntity_TC54.	[RUN <runnableentity_tc54>] RunnableEntity_TC54 is invoked.</runnableentity_tc54>
Step 8	[RUN <runnableentity_tc54>] Invoke Rte_IRead for the dataElement VariableDataPrototype_TC54.</runnableentity_tc54>	[RUN <runnableentity_tc54>] Rte_IRead should read the configured invalid value.</runnableentity_tc54>
Step 9	[RUN <runnableentity_tc54>] Invoke Rte_IStatus for the dataElement VariableDataPrototype_TC54.</runnableentity_tc54>	[RUN <runnableentity_tc54>] Rte_IStatus returns RTE_E_INVALID.</runnableentity_tc54>
Post- conditions	NONE	

# 6.3.70 [ATS\_RTE\_00690] Implicit Sender Receiver Communication On AliveTimeout

Test Objective	Implicit Sender Receiver Communication On AliveTimeout		
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01359 RTE: SWS_Rte_02599 RTE: SWS_Rte_02600 RTE: SWS_Rte_02604 RTE: SWS_Rte_03530 RTE: SWS_Rte_03531		
Requirement s / Reference to Test Environment			
	A SW-C with  * an RPortPrototype which - receives VariableDataPrototype_TC55 typed by a primitive data type with swImplPolicy 'standard' - has a NonqueuedReceiverComSpec with aliveTimeout >0  * RunnableEntity_TC55AliveTimeOut - started by a DataReceiveErrorEvent which references VariableDataPrototype_TC55 - with a dataReadAccess which references VariableDataPrototype_TC55  A communication matrix with  * Signal_TC55 - mapped to VariableDataPrototype_TC55 - received by the ECU		



	This test case uses an inter-ECU communication where the communication is stopped for a longer time than the configured aliveTimeout. The test case verifies that this triggers a DataReceiveErrorEvent and that Rte_IStatus indicates a RTE_E_MAX_AGE_EXCEEDED status.		
Needed Adaptation to other Releases			
conditions	DUT shall be initialized EcuM module shall be in RUN state ComM channel shall be in COMM_FULL_C LT shall transmit a frame with Signal_TC55		
Main Test Exe	cution		
Test Steps		Pass Criteria	
Step 1		[RUN <runnableentity_tc55alivetimeout>] RunnableEntity_TC55AliveTimeOut is invoked.</runnableentity_tc55alivetimeout>	
Step 2	[RUN <runnableentity_tc55alivetimeout &gt;] Invoke Rte_IStatus for the dataElement VariableDataPrototype_TC55.</runnableentity_tc55alivetimeout 	[RUN <runnableentity_tc55alivetimeout &gt;] Rte_IStatus returns RTE_E_MAX_AGE_EXCEEDED.</runnableentity_tc55alivetimeout 	
Post- conditions	NONE		

# 6.3.71 [ATS\_RTE\_00695] Filter 'never' Configured

	Filter 'never' Configured		
Objective ID	ATS_RTE_00695	AUTOSAR	4.0.3 4.2.1 4.2.2
i D	A13_K1E_00095	Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to		-	
Requirement			
on Acceptance			
Test			
Document			
Trace to SWS	RTE: SWS_Rte_01091		
	RTE: SWS_Rte_01093		
	RTE: SWS_Rte_01289		
	RTE: SWS_Rte_02516		
	RTE: SWS_Rte_02517		
	RTE: SWS_Rte_05500		
	RTE: SWS_Rte_05503		
	RTE: SWS_Rte_08077		
	RTE: SWS_Rte_08079		
Requirements			
/ Reference			
to Test			
Environment			
Configuration	A SW-C with		
Parameters	* A PPortPrototype which		



	<ul> <li>sends VariableDataPrototype_TC85 with swImplPolicy 'standard'</li> <li>* RPortPrototypeFilter which</li> <li>receives VariableDataPrototype_TC85 with initValue 0x10</li> <li>is connected with the previous PPortPrototype</li> <li>has a NonqueuedReceiverComSpec configured with filter: dataFilterType=never</li> <li>* RPortPrototypeNoFilter which</li> <li>receives VariableDataPrototype_TC85 with initValue 0x11</li> <li>is connected with the previous PPortPrototype</li> <li>has a NonqueuedReceiverComSpec configured without filter</li> <li>* A RunnableEntity to execute the test sequence</li> <li>with a dataReceivePointByArgument which references VariableDataPrototype_TC85</li> </ul>	
	<ul> <li>with a dataSendPoint which references VariableDataPrototype_T</li> </ul>	
Summary	The test writes some data on a dataElement and reads it on a port never. The test checks that the data read is the initValue.	with a filter set to
Needed Adaptation to other Releases		
	DUT shall be initialized EcuM module shall be in RUN state	
Main Test Exe	cution	
Test Steps		Pass Criteria
	Rte_Read_RPortPrototypeFilter_VariableDataPrototype_TC85.	[SWC] Rte_Read returns RTE_E_OK and provides the initValue 0x10.
	Rte_Read_RPortPrototypeNoFilter_VariableDataPrototype_TC85.	[SWC] Rte_Read returns RTE_E_OK and provides the initValue 0x11.
Step 3		[SWC] Rte_Write returns RTE_E_OK.
	Invoke Rte_Read_RPortPrototypeFilter_VariableDataPrototype_TC85.	[SWC] Rte_Read returns RTE_E_OK and provides the initValue 0x10.
	Rte_Read_RPortPrototypeNoFilter_VariableDataPrototype_TC85.	[SWC] Rte_Read returns RTE_E_OK and provides the value 0x55.
Post- conditions	NONE	

# 6.3.72 [ATS\_RTE\_00696] Filter 'maskedNewEqualsX' Configured

Test Objective	Filter 'maskedNewEqualsX' Configured		
ID	ATS_RTE_00696	AUTOSAR	4.0.3 4.2.1 4.2.2
		Releases	



Acc t - I	DTE	01-1-	
Affected Modules	RTE	State	reviewed
Trace to			
Requirement			
on Acceptance			
Test Document			
Trace to SWS	RTE: SWS_Rte_01091		
Item	RTE: SWS_Rte_01093		
	RTE: SWS_Rte_01289		
	RTE: SWS_Rte_05503		
Requirements /			
Reference to Test			
Environment			
	A SIM C with		
Configuration Parameters	A SW-C with * A PPortPrototype which		
raiailleteis	- sends VariableDataPrototype_T	C86 with sw	vlmnlPolicy 'standard'
	* An RPortPrototype which	OOO WILLI OV	willipii ciicy standard
	- receives VariableDataPrototype	_TC86 with	initValue (Ex: 0x10)
	- is connected with the previous F		
	<ul> <li>has a NonqueuedReceiverCom</li> </ul>		
	dataFilterType=maskedNewEqua		
	* A RunnableEntity to execute the		
	<ul> <li>with a dataReceivePointByArgu</li> <li>VariableDataPrototype_TC86</li> </ul>	nent which	references
	- with a dataSendPoint which refe	rences Vari	ableDataPrototyne TC86
	User defined data:	TOTIOGS Vari	abiebatai iototype_i ooo
	Data_1 = Ex: 0x55 (does not mat	ch the filter)	
	Data $_2$ = Ex: 0x50 (matches the	ilter)	
Summary	The test writes some data on a dataElement and reads it on a port with a filter set to		
	maskedNewEqualsX. The test checks that the reception filter was correctly applied		
			nd another one which does not match.
Needed			
Adaptation to			
Adaptation to other Releases	by sending one value which matc		
Adaptation to other Releases Pre-conditions	by sending one value which mate	h the filter a	
Adaptation to other Releases Pre-conditions	by sending one value which mato DUT shall be initialized EcuM module shall be in RUN sta	h the filter a	
Adaptation to other Releases Pre-conditions Main Test Execu	by sending one value which mato DUT shall be initialized EcuM module shall be in RUN sta	h the filter a	nd another one which does not match.
Adaptation to other Releases Pre-conditions Main Test ExecuTest Steps	by sending one value which mate DUT shall be initialized EcuM module shall be in RUN sta	h the filter a	nd another one which does not match.  Pass Criteria
Adaptation to other Releases Pre-conditions Main Test Execu	by sending one value which mate  DUT shall be initialized  EcuM module shall be in RUN sta  ition  [SWC]	h the filter a	Pass Criteria [SWC]
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1	by sending one value which mate  DUT shall be initialized  EcuM module shall be in RUN sta  Ition  [SWC]  Invoke Rte_Write to write Data_1	h the filter a	Pass Criteria [SWC] Rte_Write returns RTE_E_OK.
Adaptation to other Releases Pre-conditions Main Test ExecuTest Steps	DUT shall be initialized EcuM module shall be in RUN station  [SWC] Invoke Rte_Write to write Data_1 [SWC]	h the filter a	Pass Criteria [SWC] Rte_Write returns RTE_E_OK. [SWC]
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1	by sending one value which mate  DUT shall be initialized  EcuM module shall be in RUN sta  Ition  [SWC]  Invoke Rte_Write to write Data_1	h the filter a	Pass Criteria [SWC] Rte_Write returns RTE_E_OK. [SWC] Rte_Read returns RTE_E_OK and
Adaptation to other Releases Pre-conditions  Main Test Executes Step 1  Step 2	DUT shall be initialized EcuM module shall be in RUN station  [SWC] Invoke Rte_Write to write Data_1 [SWC] Invoke Rte_Read.	h the filter a	Pass Criteria [SWC] Rte_Write returns RTE_E_OK. [SWC] Rte_Read returns RTE_E_OK and provides the InitValue.
Adaptation to other Releases Pre-conditions Main Test Executes Test Steps Step 1	DUT shall be initialized EcuM module shall be in RUN station  [SWC] Invoke Rte_Write to write Data_1 [SWC] Invoke Rte_Read.	h the filter a	Pass Criteria [SWC] Rte_Write returns RTE_E_OK. [SWC] Rte_Read returns RTE_E_OK and provides the InitValue. [SWC]
Adaptation to other Releases Pre-conditions  Main Test Executes Test Steps Step 1  Step 2  Step 3	DUT shall be initialized EcuM module shall be in RUN station  [SWC] Invoke Rte_Write to write Data_1 [SWC] Invoke Rte_Read.  [SWC] Invoke Rte_Read.	h the filter a	Pass Criteria  [SWC] Rte_Write returns RTE_E_OK.  [SWC] Rte_Read returns RTE_E_OK and provides the InitValue.  [SWC] Rte_Write returns RTE_E_OK.
Adaptation to other Releases Pre-conditions  Main Test Executes Step 1  Step 2	DUT shall be initialized EcuM module shall be in RUN station  [SWC] Invoke Rte_Write to write Data_1 [SWC] Invoke Rte_Read.  [SWC] Invoke Rte_Write to write Data_1 [SWC] Invoke Rte_Read.	h the filter a	Pass Criteria  [SWC] Rte_Write returns RTE_E_OK.  [SWC] Rte_Read returns RTE_E_OK and provides the InitValue.  [SWC] Rte_Write returns RTE_E_OK.
Adaptation to other Releases Pre-conditions  Main Test Executes Test Steps Step 1  Step 2  Step 3	DUT shall be initialized EcuM module shall be in RUN station  [SWC] Invoke Rte_Write to write Data_1 [SWC] Invoke Rte_Read.  [SWC] Invoke Rte_Read.	h the filter a	Pass Criteria  [SWC] Rte_Write returns RTE_E_OK.  [SWC] Rte_Read returns RTE_E_OK and provides the InitValue.  [SWC] Rte_Write returns RTE_E_OK.
Adaptation to other Releases Pre-conditions  Main Test Executes Steps Step 1  Step 2  Step 3  Step 4	DUT shall be initialized EcuM module shall be in RUN state  Ition  [SWC] Invoke Rte_Write to write Data_1 [SWC] Invoke Rte_Read.  [SWC] Invoke Rte_Write to write Data_2 [SWC] Invoke Rte_Write to write Data_2 [SWC] Invoke Rte_Write to write Data_2	h the filter a	Pass Criteria [SWC] Rte_Write returns RTE_E_OK. [SWC] Rte_Read returns RTE_E_OK and provides the InitValue. [SWC] Rte_Write returns RTE_E_OK and provides the RTE_E_OK. [SWC] Rte_Write returns RTE_E_OK.
Adaptation to other Releases Pre-conditions  Main Test Executes Test Steps Step 1  Step 2  Step 3	DUT shall be initialized EcuM module shall be in RUN station  [SWC] Invoke Rte_Write to write Data_1 [SWC] Invoke Rte_Read.  [SWC] Invoke Rte_Write to write Data_1 [SWC] Invoke Rte_Read.	h the filter a	Pass Criteria  [SWC] Rte_Write returns RTE_E_OK.  [SWC] Rte_Read returns RTE_E_OK and provides the InitValue.  [SWC] Rte_Write returns RTE_E_OK.
Adaptation to other Releases Pre-conditions  Main Test Executes Steps Step 1  Step 2  Step 3  Step 4  Step 5	DUT shall be initialized EcuM module shall be in RUN state  Ition  [SWC] Invoke Rte_Write to write Data_1 [SWC] Invoke Rte_Read.  [SWC] Invoke Rte_Write to write Data_2 [SWC] Invoke Rte_Write to write Data_2 [SWC] Invoke Rte_Write to write Data_2 [SWC] Invoke Rte_Read.	h the filter a	Pass Criteria  [SWC] Rte_Write returns RTE_E_OK.  [SWC] Rte_Read returns RTE_E_OK and provides the InitValue.  [SWC] Rte_Write returns RTE_E_OK and provides Teturns RTE_E_OK.  [SWC] Rte_Write returns RTE_E_OK.  [SWC] Rte_Read returns RTE_E_OK and provides Data_2.  [SWC] Rte_Write returns RTE_E_OK.
Adaptation to other Releases Pre-conditions  Main Test Executes Steps Step 1  Step 2  Step 3  Step 4	DUT shall be initialized EcuM module shall be in RUN sta  Ition  [SWC] Invoke Rte_Write to write Data_1  [SWC] Invoke Rte_Read.  [SWC] Invoke Rte_Write to write Data_2  [SWC] Invoke Rte_Write to write Data_2  [SWC] Invoke Rte_Write to write Data_2  [SWC]  [SWC] Invoke Rte_Read.	h the filter a	Pass Criteria  [SWC] Rte_Write returns RTE_E_OK.  [SWC] Rte_Read returns RTE_E_OK and provides the InitValue.  [SWC] Rte_Write returns RTE_E_OK and provides Teturns RTE_E_OK.  [SWC] Rte_Write returns RTE_E_OK and provides Data_2.  [SWC] Rte_Write returns RTE_E_OK and provides Data_2.
Adaptation to other Releases Pre-conditions  Main Test Executes Steps Step 1  Step 2  Step 3  Step 4  Step 5	DUT shall be initialized EcuM module shall be in RUN sta  Ition  [SWC] Invoke Rte_Write to write Data_1 [SWC] Invoke Rte_Read.  [SWC] Invoke Rte_Write to write Data_2 [SWC] Invoke Rte_Write to write Data_2 [SWC] Invoke Rte_Read.	h the filter a	Pass Criteria  [SWC] Rte_Write returns RTE_E_OK.  [SWC] Rte_Read returns RTE_E_OK and provides the InitValue.  [SWC] Rte_Write returns RTE_E_OK.  [SWC] Rte_Write returns RTE_E_OK.  [SWC] Rte_Read returns RTE_E_OK and provides Data_2.  [SWC] Rte_Write returns RTE_E_OK.
Adaptation to other Releases Pre-conditions  Main Test Executes Steps Step 1  Step 2  Step 3  Step 4  Step 5  Step 6	DUT shall be initialized EcuM module shall be in RUN sta  Ition  [SWC] Invoke Rte_Write to write Data_1 [SWC] Invoke Rte_Read.  [SWC] Invoke Rte_Write to write Data_2 [SWC] Invoke Rte_Write to write Data_2 [SWC] Invoke Rte_Read.	h the filter a	Pass Criteria [SWC] Rte_Write returns RTE_E_OK. [SWC] Rte_Read returns RTE_E_OK and provides the InitValue. [SWC] Rte_Write returns RTE_E_OK. [SWC] Rte_Write returns RTE_E_OK. [SWC] Rte_Read returns RTE_E_OK and provides Data_2. [SWC] Rte_Write returns RTE_E_OK and provides Data_2. [SWC] Rte_Write returns RTE_E_OK.
Adaptation to other Releases Pre-conditions  Main Test Executes Steps Step 1  Step 2  Step 3  Step 4  Step 5  Step 6	DUT shall be initialized EcuM module shall be in RUN station  [SWC] Invoke Rte_Write to write Data_1  [SWC] Invoke Rte_Read.  [SWC] Invoke Rte_Write to write Data_2  [SWC] Invoke Rte_Write to write Data_1  [SWC] Invoke Rte_Read.	h the filter a	Pass Criteria [SWC] Rte_Write returns RTE_E_OK. [SWC] Rte_Read returns RTE_E_OK and provides the InitValue. [SWC] Rte_Write returns RTE_E_OK. [SWC] Rte_Write returns RTE_E_OK. [SWC] Rte_Read returns RTE_E_OK and provides Data_2. [SWC] Rte_Write returns RTE_E_OK and provides Data_2. [SWC] Rte_Write returns RTE_E_OK.



# 6.3.73 [ATS\_RTE\_00697] Filter 'maskedNewDiffersX' Configured

Toot Objective	Filter (monked Nov Different) Configured			
_	Filter 'maskedNewDiffersX' Confi	Ī	4 0 014 0 414 0 0	
ID	ATS_RTE_00697	AUTOSAR Releases	4.0.3 4.2.1 4.2.2	
Affected Modules	RTE	State	reviewed	
Trace to Requirement on Acceptance Test Document				
Trace to SWS Item	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01289 RTE: SWS_Rte_05503			
Requirements / Reference to Test Environment				
Configuration Parameters	A SW-C with  * A PPortPrototype which - sends VariableDataPrototype_TC87 with swImplPolicy 'standard'  * An RPortPrototype which - receives VariableDataPrototype_TC87 with initValue (Ex: 0x10) - is connected with the previous PPortPrototype - has a NonqueuedReceiverComSpec configured with filter: dataFilterType=maskedNewDiffersX mask=Ex. 0x0F x=Ex. 0x05  * A RunnableEntity to execute the test sequence - with a dataReceivePointByArgument which references VariableDataPrototype_TC87 - with a dataSendPoint which references VariableDataPrototype_TC87 User defined data:Data_1 = Ex: 0x55 (does not match the filter)			
Summary	The test writes some data on a dataElement and reads it on a port with a filter set to maskedNewDiffersX. The test checks that the reception filter was correctly applied by sending one value which match the filter and another one which does not match.			
Needed Adaptation to other Releases				
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN sta	ate		
Main Test Execu	ution			
Test Steps			Pass Criteria	
Step 1	[SWC] Invoke Rte_Write to write Data_1		[SWC] Rte_Write returns RTE_E_OK.	
Step 2	[SWC] Invoke Rte_Read.		[SWC] Rte_Read returns RTE_E_OK and provides the initValue.	
Step 3	[SWC] Invoke Rte_Write to write Data_2		[SWC] Rte_Write returns RTE_E_OK.	
Step 4	[SWC] Invoke Rte_Read.		[SWC] Rte_Read returns RTE_E_OK and provides Data_2.	



Post-	NONE
conditions	

## 6.3.74 [ATS\_RTE\_00698] Filter 'maskedNewDiffersMaskedOld' Configured

Test Objective	Filter 'maskedNewDiffersMaskedOld' Configured			
ID	ATS_RTE_00698		4.0.3 4.2.1 4.2.2	
Affected Modules	RTE	State	reviewed	
Trace to Requirement on Acceptance Test Document				
Trace to SWS Item	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01289 RTE: SWS_Rte_05503			
Requirements / Reference to Test Environment				
Configuration Parameters	A SW-C with  * A PPortPrototype which - sends VariableDataPrototype_TC88 with swImplPolicy 'standard'  * An RPortPrototype which - receives VariableDataPrototype_TC88 with initValue (0x11) - is connected with the previous PPortPrototype - has a NonqueuedReceiverComSpec configured with filter: dataFilterType= maskedNewDiffersMaskedOld mask=Ex. 0x0F  * A RunnableEntity to execute the test sequence - with a dataReceivePointByArgument which references VariableDataPrototype_TC88 - with a dataSendPoint which references VariableDataPrototype_TC88			
Summary	The test writes some data on a dataElement and reads it on a port with a filter set to maskedNewDiffersMaskedOld. The test checks that the reception filter was correctly applied by sending one value which match the filter and another one which does not match. Another data is sent at the end that does not match the filter but would have matched in case the previous value was accepted.			
Needed Adaptation to other Releases				
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state			
Main Test Execu	ution			
Test Steps			Pass Criteria	
Step 1	[SWC] Invoke Rte_Write to write 0x21.		[SWC] Rte_Write returns RTE_E_OK.	
Step 2	[SWC] Invoke Rte_Read.		[SWC] Rte_Read returns RTE_E_OK and provides the value 0x11.	
Step 3	[SWC] Invoke Rte_Write to write 0x22.		[SWC] Rte_Write returns RTE_E_OK.	



Step 4	[SWC] Invoke Rte_Read.	[SWC] Rte_Read returns RTE_E_OK and provides the value 0x22.
Step 5	[SWC] Invoke Rte_Write to write 0x32.	[SWC] Rte_Write returns RTE_E_OK.
Step 6	[SWC] Invoke Rte_Read.	[SWC] Rte_Read returns RTE_E_OK and provides the value 0x22.
Post- conditions	NONE	

# 6.3.75 [ATS\_RTE\_00699] Filter 'newlsWithin' Configured

Test Objective	Filter 'newlsWithin' Configured			
ID	ATS_RTE_00699	AUTOSAR Releases	4.0.3 4.2.1 4.2.2	
Affected Modules	RTE	State	reviewed	
Trace to Requirement on Acceptance Test Document				
Item	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01289 RTE: SWS_Rte_05503			
Requirements / Reference to Test Environment				
Configuration Parameters	A SW-C with  * A PPortPrototype which - sends VariableDataPrototype_TC89 with swImplPolicy 'standard'  * An RPortPrototype which - receives VariableDataPrototype_TC89 with initValue (Ex: 0x10) - is connected with the previous PPortPrototype - has a NonqueuedReceiverComSpec configured with filter: dataFilterType=newlsWithin min=Ex. 0x10 max=Ex. 0x50  * A RunnableEntity to execute the test sequence - with a dataReceivePointByArgument which references VariableDataPrototype_TC89 - with a dataSendPoint which references VariableDataPrototype_TC89 User defined data: Data_1 = Ex: 0x64 (does not match the filter) Data_2 = Ex: 0x15 (matches the filter – min value) Data_4 = Ex: 0x50 (matches the filter – max value)			
Summary	The test writes some data on a dataElement and reads it on a port with a filter set to newlsWithin. The test checks that the reception filter was correctly applied by sending one value which match the filter and another one which does not match.			
Needed Adaptation to other Releases				



Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state			
Main Test Execu	ution			
Test Steps		Pass Criteria		
Step 1	[SWC] Invoke Rte_Write to write Data_1.	[SWC] Rte_Write returns RTE_E_OK.		
Step 2	[SWC] Invoke Rte_Read.	[SWC] Rte_Read returns RTE_E_OK and provides the initValue.		
Step 3	[SWC] Invoke Rte_Write to write Data_2.	[SWC] Rte_Write returns RTE_E_OK.		
Step 4	[SWC] Invoke Rte_Read.	[SWC] Rte_Read returns RTE_E_OK and provides Data_2.		
Step 5	[SWC] Invoke Rte_Write to write Data_3.	[SWC] Rte_Write returns RTE_E_OK.		
Step 6	[SWC] Invoke Rte_Read.	[SWC] Rte_Read returns RTE_E_OK and provides Data_3.		
Step 7	[SWC] Invoke Rte_Write to write Data_4.	[SWC] Rte_Write returns RTE_E_OK.		
Step 8	[SWC] Invoke Rte_Read.	[SWC] Rte_Read returns RTE_E_OK and provides Data_4.		
Post- conditions	NONE			

# 6.3.76 [ATS\_RTE\_00700] Filter 'newlsOutside' Configured

Test Objective	Filter 'newlsOutside' Configured		
ID	ATS_RTE_00700	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
ltem	RTE: SWS_Rte_01091 RTE: SWS_Rte_01093 RTE: SWS_Rte_01289 RTE: SWS_Rte_05503		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * A PPortPrototype which - sends VariableDataPrototype_T  * An RPortPrototype which - receives VariableDataPrototype - is connected with the previous F - has a NonqueuedReceiverCom	_TC90 with i	initValue (Ex: 0x09) pe




	dataFilterType=newlsOutside min=Ex. 0x10 max=Ex. 0x50  * A RunnableEntity to execute the test sequence - with a dataReceivePointByArgument which references VariableDataPrototype_TC90 - with a dataSendPoint which references VariableDataPrototype_TC90 User defined data: Data_1 = Ex: 0x15 (does not match the filter) Data_2 = Ex: 0x64 (matches the filter) Data_1 = Ex: 0x10 (does not match the filter – min value) Data_2 = Ex: 0x50 (does not match the filter – max value)			
Summary	The test writes some data on a dataElement newlsOutside. The test checks that the recep sending one value which match the filter and	otion filter was correctly applied by		
Needed Adaptation to other Releases				
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state			
Main Test Execu	ution			
Test Steps		Pass Criteria		
Step 1	[SWC] Invoke Rte_Write to write Data_1.	[SWC] Rte_Write return RTE_E_OK.		
Step 2	[SWC] Invoke Rte_Read.	[SWC] Rte_Read return RTE_E_OK and provides the initValue.		
Step 3	[SWC] Invoke Rte_Write to send Data_2.	[SWC] Rte_Write return RTE_E_OK.		
Step 4	[SWC] Invoke Rte_Read.	[SWC] Rte_Read returns RTE_E_OK and provides Data_2.		
Step 5	[SWC] [SWC] Invoke Rte_Write to send Data_3. Rte_Write return RTE_E_OK.			
Step 6	[SWC] [SWC] Invoke Rte_Read. Rte_Read returns RTE_E_OK and provides Data_2.			
Step 7	[SWC] [SWC] Invoke Rte_Write to send Data_4. Rte_Write return RTE_E_OK.			
Step 8	[SWC] [SWC] Invoke Rte_Read. Rte_Read returns RTE_E_OK and provides Data_2.			
Post- conditions	NONE			

## 6.3.77 [ATS\_RTE\_00701] Filter 'oneEveryN' Configured

Test Objective	Filter 'oneEveryN' Configured		
ID			4.0.3 4.2.1 4.2.2
		Releases	
Affected	RTE	State	reviewed
Modules			
Trace to			
Requirement			



• .	T				
on Acceptance Test Document					
	RTE: SWS_Rte_01091				
Item	RTE: SWS_Rte_01093				
	RTE: SWS_Rte_01289				
	RTE: SWS_Rte_05503				
Requirements /					
Reference					
to Test Environment					
	A SW-C with				
Configuration Parameters	* A PPortPrototype which				
i didiliciois	- sends VariableDataPrototype_TC91 wi	ith swImplPolicy 'standard'			
	* An RPortPrototype which	, , , , , , , , , , , , , , , , , , ,			
	- receives VariableDataPrototype_TC91				
	- is connected with the previous PPortPr				
	<ul> <li>has a NonqueuedReceiverComSpec of dataFilterType=oneEveryN offset=2 peri</li> </ul>	0			
	* A RunnableEntity to execute the test se				
	- with a dataReceivePointByArgument w				
	VariableDataPrototype_TC91				
	<ul> <li>with a dataSendPoint which references</li> </ul>	77 —			
Summary		nent and reads it on a port with a filter set to			
	oneEveryN. The test checks that the rec				
Noodod	sending one value which match the litter	and another one which does not match.			
Needed Adaptation to					
other Releases					
Pre-conditions	DUT shall be initialized				
	EcuM module shall be in RUN state				
Main Test Execu	ution				
Test Steps		Pass Criteria			
Step 1	[SWC]	[SWC]			
	Invoke Rte_Write to write value 1.	Rte_Write returns RTE_E_OK.			
Step 2	[SWC]	[SWC]			
	Invoke Rte_Read	Rte_Read returns RTE_E_OK and			
-		provides the initValue.			
Step 3	[SWC]	[SWC]			
01 4	Invoke Rte_Write to write value 2.	Rte_Write returns RTE_E_OK.			
Step 4	[SWC] Invoke Rte_Read	[SWC] Rte_Read returns RTE_E_OK and			
	IIIVOKE IXIE_IXEAU	provides the value 2.			
Step 5	[SWC]	[SWC]			
5.0p 0	Invoke Rte_Write to write value 3.	Rte_Write returns RTE_E_OK.			
Step 6	[SWC] [SWC]				
	Invoke Rte_Read Rte_Read returns RTE_E_OK a				
		provides the value 2.			
Step 7	[SWC]	[SWC]			
	Invoke Rte_Write to write value 4.	Rte_Write returns RTE_E_OK.			
Step 8	[SWC]	[SWC]			
	Invoke Rte_Read Rte_Read returns RTE_E_Ok				
		provides the value 2.			
	l-a a.				
Step 9	[SWC] Invoke Rte_Write to write value 5.	[SWC] Rte_Write returns RTE_E_OK.			





•	Invoke Rte_Read	[SWC] Rte_Read returns RTE_E_OK and provides the value 5.
Post- conditions	NONE	




## 7 RS\_BRF\_01416\_NvDataHandling

### 7.1 General Test Objective and Approach

This Test Specification covers the NvDataHandling via RTE as described in the AUTOSAR Feature [RS\_BRF\_01416].


The tests use a test bench environment and embedded Software Components that use the feature.

This test specification document has been established to cover the following features:



#### 7.1.1 Test System

#### 7.1.1.1 Overview on Architecture





The test system architecture requires three SWC's as upper testers and one NvBlockSoftwareComponent.

One is the Control\_SWC and other two are Observation\_SWC1 and Observation\_SWC2. Observation\_SWC1 and Observation\_SWC2 is used to read NvBlockSoftwareComponent data elements to validate the data received in NvBlockSoftwareComponent from Control\_SWC.

Four NvBlockDescriptor is configured in NvBlockSoftwareComponent for different Writing Strategies.

The test cases are derived based on below use cases.

#### UC05.01: NvData Access from SWC

Writing of data to Nv Block and Reading it from Nv Block for different data types from SWC both implicitly and explicitly.

#### UC05.02 : NvData Writing Strategies

Four Different Writing Strategies are there to write NV Block.

- 1. StoreCyclic: NvM\_WriteBlock will be invoked in next periodic activity when it is configured as True for respective Block Descriptor.
- 2. StoreImmediate: NvM\_WriteBlock will be invoked by Rte immediately when it is configured as True for respective Block Descriptor.
- StoreAtShudown: Rte will invoke NvM\_SetRamBlockStatus for respective Block Descriptor. NvM\_WriteAll will be called by EcuM at the time of shutdown to write Nv Blocks
- 4. StoreEmergency: CDD will invoke NvM\_WriteBlock for respective Block Descriptor. This scenario is not handled in RTE and it is not tested in ATS.

#### Uc05.03: Optimization of Write Operations to Nv Memory


If data is not changed from previous Nv Block Write, NvM will not invoke Write to the lower layers. The below parameters should be configured as True.

- 1. calcRamBlockCrc should be True
- 2. useCRCCompMechanism should be True

#### Sender/Receiver Communication

S/R Communication is used for data conversion from Control\_SWC to NvBlockSwComponent






#### Client-Server Communication

JobEndNotification from NvM is indicated to Control\_SWC, Observation\_SWC1 and Observation\_SWC2 via C/S Interface.

Observation\_SWC1 will invoke NvM\_ReadBlock() for NvBlockDescriptor1, NvBlockDescriptor2, NvBlockDescriptor3 which is configured as Immediate, Cyclic, Cyclic and Shutdown, to read the data written in Nv Block via C/S Interface.

Control\_SWC will invoke NvM\_WriteBlock() for NvBlockDescriptor4 which is not configured for any of the writing strategies and Observation\_SWC1 will invoke NvM\_ReadBlock() for the same.





#### 7.1.1.2 Specific Requirements

NvBlockDescriptor should be configured in NvBlockSoftwareComponentType to provide RAM Block to SWC and the data copied in RAM Block should be stored in NVRAM Block based on different Writing Strategies.

#### 7.1.1.3 Test Coordination Requirements

Test Coordination Procedures are needed to synchronize the runnables of the SWC and of the NvBlockSoftwareComponentType in test cases.

TCPs are also needed to collect the test results of the SWCs and the Bus simulation at one central place in order to derive the test verdict.

It is up to the test system designer/implementer to define that "central place" and to design/implement the test coordination functionality.

#### 7.1.2 Test Configuration

Key Configuration Parameters details are provided in individual testcases. .

#### 7.1.2.1 Required ECU Extract of System Description Files

None.

#### 7.1.2.2 Required ECU Configuration Description Files

The NVRAM block associated to NvBlockDescriptors needs to be configured with below values.



NvMBlockUseSyncMechanism should be configured as True.

NvMWriteRamBlockToNvCallback and NvMReadRamBlockFromNvCallback should be configured.

## 7.1.2.3 Required Software Component Description Files

#### 7.1.2.3.1 SWC Control SWC

7.1.2.3.1 SWC CC	Control_SWC		
	Name	PP_SendData1	
	Туре	PPortPrototype	
	Interface	IF_ExchangedData1	
	ComSpecs	NvProvideComSpec for dataElement VDP_Nv1	
	Requirements	Compu Method : Identical	
	Name	PP_SendData2	
	Туре	PPortPrototype	
	Interface	IF_ExchangedData2	
	ComSpecs	NvProvideComSpec for Array VDP_Nv2	
	Requirements	Compu Method : Identical	
	Name	PP_SendData3	
	Туре	PPortPrototype	
PORTS	Interface	IF_ExchangedData3	
	ComSpecs	NvProvideComSpec for Structure VDP_ImplWrite2 Record { App_Data1 : uint16 App_Data2 : uint16 App_Data3 : uint16 App_Data4 : uint16 }	
	Requirements		
	Name	PP_SendData4	
	Туре	PPortPrototype	
	Interface	IF_ExchangedData4	
	ComSpecs	NvProvideComSpec for Boolean Element VDP_ExplWrite2 App_Boolean_Data	
Requirements Compu Method : TEXTTABLE		Compu Method : TEXTTABLE	



	Name PP_SendData5			
	Туре	PPortPrototype		
	Interface	IF_ExchangedData5		
	ComSpecs	NvProvideComSpec for data Element VDP_Nv5		
	Requirements	Compu Method : Ider	ntica	al
	Name	PP_SendData6		
	Туре	PPortPrototype		
	Interface	IF_ExchangedData5		
	ComSpecs	NvProvideComSpec VDP_Nv6	for (	data Element
	Requirements	Compu Method : Ider	ntica	al
	Name	Run_Ctrl_1		
	Requirements	Executed in the same task as Run_Obs1_1 and Run_Obs2_1		
		Name	VI	DP_Nv1
		Туре	Da	ataWriteAccess1
	VariableDataPrototype	Access to	PP_SendData1/ IF_ExchangedData1/ App_Data5	
		Requirements  Requirements  Requirements  Run_Obs1_1/VDP_Nv1 and Run_Obs2_1/VDP_Nv1 , Compu Method : Identical		
5111114515				
RUNNABLE ENTITIES	Name	Run_Ctrl_2		
	Requirements	Executed in the same Run_Obs2_2	e ta	sk as Run_Obs1_2 and
		Name		VDP_Nv2
		Туре		DataSendPoint1
	VariableDataPrototype	Access to		PP_SendData2/ IF_ExchangedData2/ App_Array[4]: uint16
		Requirements		Belongs to the same coherency group as Run_Obs1_2/ VDP_Nv2 and Run_Obs2_2/VDP_Nv2 Compu Method : Identical



	Name	Run_Ctrl_3	
	Requirements	None	
	VariableDataPrototype	Name	VDP_ImplWrite2
		Туре	DataWriteAccess2
		Access to	PP_SendData3/ IF_ExchangedData3/ Record{App_Data1: uint16 App_Data2: uint16 App_Data3: uint16
			App_Data4 : uint16 }
		Requirements	None
	Name	Run_Ctrl_4	
	Requirements	None	
		Name	VDP_ExplWrite2
		Туре	DataSendPoint2
	VariableDataPrototype	Access to	PP_SendData4/ IF_ExchangedData4/ App_Boolean_Data
		Requirements	Compu Method : TEXTTABLE
	Name	Run_Ctrl_5	
	Requirements	None	
		Name	VDP_Nv5
		Туре	DataSendPoint3
	VariableDataPrototype	Access to	PP_SendData5/ IF_ExchangedData5/ App_Data6 : uint16
		Requirements	Compu Method : Identical
	Name	Run_Ctrl_6	
	Requirements	None	
		Name	VDP_Nv6
		Туре	DataSendPoint4
	VariableDataPrototype	Access to	PP_SendData6/ IF_ExchangedData6/ App_Data7 : uint16
		Requirements	Compu Method : Identical



7.1.2.3.2 SWC NvBlockSoftwareComponentType

SWC Name	· ·	ockSoftwareComponentType  NvBlockSoftwareComponentType		
	Name	NvBlockDescriptor1		
	Requirements	NvBlockNeeds supportDirtyFlag – True storeImmediate - True		
	Name	NvBlockDataMapping1		
	ComSpecs	Refer PR_ReceiveData1		
	Requirements	WrittenReadNvData, NvRamBlockElement: Nv_Data4		
	Name	NvBlockDataMapping3		
	ComSpecs	Refer PR_ReceiveData3		
	Requirements	WrittenReadNvData, NvRamBlockElement; Nv_Record{ Nv_Data1 : uint16 Nv_Data2 :		
	requirements	uint16 }		
	Name	NvBlockDescriptor2		
NvBlockDescriptor	Requirements	NvBlockNeeds supportDirtyFlag – True storeCyclic – True cyclicWritingPeriod – 10seconds useCRCCompMechanism - True		
	Name	NvBlockDataMapping2		
	ComSpecs	Refer PR_ReceiveData2		
	Requirements	WrittenReadNvData, NvRamBlockElement; Nv_Array[4]		
	Name	NvBlockDescriptor3		
	Requirements	NvBlockNeeds supportDirtyFlag – True storeCyclic – True cyclicWritingPeriod – 10 seconds storeAtShutdown – True useAutoValidationAtShudown - True		
	Name	NvBlockDataMapping4		
	ComSpecs	Refer PR_ReceiveData4		
	Requirements	WrittenReadNvData, NvRamBlockElement: Nv_Data3_Bitfield : uint8		



	Name	NvBlockDataMapping5
	ComSpecs	Refer PR_ReceiveData5
	Requirements	WrittenReadNvData, NvRamBlockElement Nv_Data5
	Name	NvBlockDescriptor4
	Requirements	supportDirtyFlag – False
	Name	NvBlockDataMapping6
	ComSpecs	Refer PR_ReceiveData6
	Requirements	WrittenReadNvData, NvRamBlockElement Nv_Data6
	Name	PR_ReceiveData1
	Туре	PRPortPrototype
	Interface	IF_ExchangedData1
	ComSpecs	NvProvideComSpec and NvRequireComSpec for data element  VDP_Nv1 : App_Data5
	Requirements	(ApplicationPrimitiveDataType)  Compu Method : Identical
	Requirements	Compa Metrica : Identical
	Name	PR_ReceiveData1Event
	Туре	Data Received Event
	Reference	Start on Event, Target Data Element
	Name	PR_ReceiveData2
PORTS	Туре	PRPortPrototype
	Interface	IF_ExchangedData2
	ComSpecs	NvProvideComSpec and NvRequireComSpec for Array VDP_Nv2 : App_Array[4] (ApplicationArrayDataType)
	Requirements	Compu Method : Identical
	Name	PR_TimingData2Event
	Name Type	PR_TimingData2Event Timing Event
	Туре	Timing Event



Туре	PRPortPrototype	
Interface	IF_ExchangedData3	
ComSpecs	NvProvideComSpec and NvRequireComSpec for Structure Nv_Record { Nv_Data1 : uint16	
Requirements		
Name	PR_ReceiveData3Event	
Туре	Data Received Event	
Reference	Start on Event, Target Data Element	
Name	PR_ReceiveData4	
Туре	PRPortPrototype	
Interface	IF_ExchangedData4	
ComSpecs	NvProvideComSpec and NvRequireComSpec for Bitfield Nv_Data3_Bitfield : uint8	
Requirements	Compu Method : TEXTTABLE  Mapping : 3 <sup>rd</sup> bit needs to be set/reset in  Nv_data3_Bitfield.	
Name	PR_TimingData4Event	
Туре	Timing Event	
Reference	Start on Event, Event Reference, Timing Period	
Reference	Start Sir Event, Event reasonable, Timing Ferred	
Name	PR ReceiveData5	
Туре	PRPortPrototype	
Interface	IF_ExchangedData5	
ComSpecs	NvProvideComSpec and NvRequireComSpec for Primitive Data Type  VDP_Nv5 : App_Data6 (ApplicationPrimitiveDataType)	
Requirements	Compu Method : Identical	
Name	PR_TimingData5Event	
Туре	Timing Event	
Reference	Start on Event, Event Reference, Timing Reference	



	Name PR_ReceiveData6			
	Туре	PRPortPrototype		
	Interface	IF_ExchangedData6		
	ComSpecs	NvProvideComSpec and NvRequireComSpec for Primitive Data Type VDP_Nv6 : App_Data7 (ApplicationPrimitiveDataType)		
	Requirements	Compu Method : Ident	ical	
	Name	Run_NvM_WriteBlock		
	Requirements	None		
		Name	VDP_Nv1, VDP_Nv3	
		VDP InitValue	VDP_Nv1 = 0x190	
		Туре		
	VariableDataPrototype	Access to	PR_ReceiveData1/ IF_ExchangedData1/ Nv_Data4, PR_ReceiveData3/ IF_ExchangedData3/ Nv_Record	
RUNNABLE ENTITIES		Requirements	DataTypeMapping: App_Data5: uint32 Record {App_Data1: uint16 App_Data2: uint16 App_Data3: uint16 App_Data4: uint16	
	Name	Run_NvM_WriteBlock	_2	
	Requirements	None		
		Name	VDP_Nv2	
		Туре		
	VariableDataPrototype	Access to	PR_ReceiveData2/ IF_ExchangedData2/ Nv_Array,	
		Requirements	DataTypeMapping : App_Array[4] : uint16	
	Name	Run_NvM_WriteBlock_3		
	Requirements	None	VOD N. 1	
	VariableDataPrototype	Name	VDP_Nv4	



		Туре	
		Access to	PR_ReceiveData4/ IF_ExchangedData4/ Nv_Data3_Bitfield
		Requirements	
	Name	Run_WriteBlock_5	
	Requirements	None	
		Name	VDP_Nv5
		Туре	
VariableDataPrototype	Access to	PR_ReceiveData5/ IF_ExchangedData5/ Nv_Data5	
		Requirements	

## 7.1.2.3.3 SWC Observation\_SWC1

SWC Name	Observation_SWC1		
	Name	RP_ObserveData1	
	Туре	RPortPrototype	
	Interface	IF_ExchangedData1	
	ComSpecs	NvRequireComSpec for data element Nv_Data4 : uint32	
	Name	RP_ObserveData2	
	Туре	RPortPrototype	
	Interface	IF_ExchangedData2	
	ComSpecs	NvRequireComSpec for Array Nv_Array[4]: uint16	
PORTS			
	Name	RP_ObserveData3	
	Туре	RPortPrototype	
	Interface	IF_ExchangedData3	
	ComSpecs	NvRequireComSpec for Structure Nv_Record { Nv_Data1 : uint16 Nv_Data2 : uint16 }	
	Name	RP_ObserveData4	
	Туре	RPortPrototype	
	Interface	IF_ExchangedData4	
	ComSpecs	NvRequireComSpec for Bitfield	



		Nv_Data3_Bitfield : uint8		
	Requirements	Compu Method : TEXTTABLE  Mapping : App_Boolean_Data is set/reset 3rd bit of Nv_Data3_Bitfield in RAMBlock		
	Name	RP_ObserveData5		
	Туре	RPortPrototype		
	Interface	IF_ExchangedData5		
	ComSpecs	NvRequireComSpec for Nv_Data5 : uint16	or data Element	
	Requirements	Compu Method : Identi	ical	
	Name	RP_ObserveData8		
	Туре	RPortPrototype		
	Interface	IF_ExchangedData6		
	ComSpecs	NvRequireComSpec for data Element Nv_Data6 : uint16		
	Requirements	Compu Method : Identical		
	Name	Run_Obs1_1		
	Requirements	Executed in the same task as Run_Ctrl_1 and Run_Obs2_1		
	VariableDataPrototype .	Name	VDP_Nv1	
		Туре	DataReadAccess1	
		Access to	RP_ObserveData1/ IF_ExchangedData1/ Nv_Data4	
RUNNABLE		Requirements	Belongs to the same coherency group as Run_Ctrl_1 and Run_Obs2_1	
ENTITIES				
	Name	Run_Obs1_2		
	Requirements	None		
		Name	VDP_Nv2	
		Туре	DataReceivePoint1	
	VariableDataPrototype	Access to	RP_ObserveData2/ IF_ExchangedData2/ Nv_Array[4]	
		Requirements		



	Name	Run_Obs1_3		
	Requirements	None		
	VariableDataPrototype _	Name	VDP_Nv3	
		Туре	DataReadAccess2	
		Access to	RP_ObserveData3/ IF_ExchangedData3/ Nv_Record	
		Requirements	Belongs to the same coherency group as Run_Ctrl_3 and Run_Obs2_3/	
	Name	Run_Obs1_4		
	Requirements	None		
		Name	VDP_Nv4	
		Туре	DataReceivePoint2	
	VariableDataPrototype	Access to	RP_ObserveData4/ IF_ExchangedData4/ Bitfield data Nv_Data3_Bitfield	
		Requirements		
	Name	Run_Obs1_5		
	Requirements	None		
		Name	VDP_Nv5	
		Туре	DataReceivePoint3	
	VariableDataPrototype	Access to	RP_ObserveData5/ IF_ExchangedData5/ Nv_Data5	
		Requirements		
	Name	Run_Obs1_6		
	Requirements	None		
		Name	VDP_Nv6	
		Туре	DataReceivePoint3	
	VariableDataPrototype	Access to	RP_ObserveData5/ IF_ExchangedData5/ Nv_Data5	
		Requirements		

## 7.1.2.3.4 SWC Observation\_SWC2

SWC Name	Observation_SWC2
----------	------------------



	Name	RP_ObserveData6		
	Туре	RPortPrototype		
	Interface	IF_ExchangedData1		
	ComSpecs	NvRequireComSpec fo Nv_Data4	or data element	
	Requirements	None		
DODTS				
PORTS	Name	RP_ObserveData7		
	Туре	RPortPrototype		
	Interface	IF_ExchangedData2		
	ComSpecs	NvRequireComSpec fo Nv_Array[4]	or ArrayElement	
	Requirements	None		
	Name	Run_Obs2_1		
	Requirements	Executed in the same task as Run_Ctrl_1 and Run_Obs1_1		
	VariableDataPrototype	Name	VDP_Nv1	
		Туре	DataReadAccess1	
		Access to	RP_ObserveData6/ IF_ExchangedData2/ Nv_Data4	
		Requirements	Belongs to the same coherency group as Run_Ctrl_1 and Run_Obs1_1	
RUNNABLE				
ENTITIES	Name	Run_Obs2_2		
	Requirements	None		
		Name	VDP_Nv2	
		Type DataReceivePoint1		
		Access to	RP_ObserveData7/ IF_ExchangedData2/ Nv_Array[4]	
	VariableDataPrototype	Requirements	Belongs to the same coherency group as Run_Ctrl_2 and Run_Obs1_2	
			1	



SWC Name	Control_SWC				
	Name	Ctrl	_RestoreBlockD	efaults	_Client_1
	Туре	RP	ortPrototype		
	Interface	Res	storeBlockDefau	lts	
	Name	Ctrl	_JobFinished_1		
	Туре	PPo	ortPrototype		
	Interface	Job	JobFinished		
	Name	Ctrl	Ctrl_WriteBlock_1		
	Туре	RP	ortPrototype		
	Interface	Wri	teBlock		
PORTS					
	Name	Ctrl	_SetBlockProtec	ction_1	
	Туре	RP	ortPrototype		
	Interface	Set	BlockProtection		
	Name	Ctrl_GetErrorStatus_2			
	Туре	RPortPrototype			
	Interface	Get	ErrorStatus		
		•			
	Name	Ctrl	_WriteBlock_4		
	Туре	RP	ortPrototype		
	Interface	Wri	teBlock_4		
	Name	Rur	n_Ctrl_RestoreB	lockDe	faults_1
	Requirements	Nor		ı	
RUNNABLE			Name	•	_RestoreBlock
ENTITIES			Туре	-	hronousServerCallPoint
	Servercall points		Access to		RestoreBlockDefaults_Client_1
		R	equirements	None	
	Name		Run_Ctrl_JobF	inished	<u>t</u>
	Requirements		None		
			Access to		Ctrl_JobFinished_1
		Requirements None		None	
			D 0:1111	DI :	
	Name		Run_Ctrl_Write	Block_	_1



	Requirements	None	
		Name	sscp_WriteBlock
		Туре	SynchronousServerCallPoint
	Servercall points	Access to	Ctrl_WriteBlock_1
		Requirements	None
	Name	Run_Ctrl_SetBlockPro	tection_1
	Requirements	None	
		Name	sscp_SetBlockProtection
		Туре	SynchronousServerCallPoint
	Servercall points	Access to	Ctrl_SetBlockProtection_1
		Requirements	None
	Name	Run_Ctrl_GetErrorStatus_2	
	Requirements	None	
		Name	sscp_GetErrorStatus
		Туре	SynchronousServerCallPoint
	Servercall points	Access to	Ctrl_GetErrorStatus_2
		Requirements	None
	Name	Run_Ctrl_WriteBlock_	4
	Requirements	None	
		Name	sscp_WriteBlock
		Туре	SynchronousServerCallPoint
	Servercall points	Access to	Ctrl_WriteBlock_4
		Requirements	None

SWC Name	NvBlockSwComponentType		
	Name	Nv_RestoreBlockDefaults_1	
	Type PPortPrototype Interface Nv_RestoreBlockDefaults_1  Name Nv_JobFinished_1  Type RPortPrototype		
PORTS			
	Interface Nv_JobFinished_1		
	Name Nv_JobFinished_1_Obs1		



Туре	RPortPrototype	
Interface	Nv_JobFinished_1_Obs1	
Name	Nv_WriteBlock_1	
Туре	PPortPrototype	
Interface	Nv_WriteBlock_1	
Name	Nv_SetBlockProtection_1	
Туре	PPortPrototype	
Interface	Nv_SetBlockProtection_1	
Name	Nv_ReadBlock_1	
Туре	PPortPrototype	
Interface	Nv_ReadBlock_1	
Name	Nv_ReadBlock_2	
Туре	PPortPrototype	
Interface	Nv_ReadBlock_2	
Name	Nv_ReadBlock_3	
Туре	PPortPrototype	
Interface	Nv_ReadBlock_3	
Name	Nv_JobFinished_2	
Туре	RPortPrototype	
Interface	Nv_JobFinished_2	
Name	Nv_JobFinished_3	
Туре	RPortPrototype	
Interface	Nv_JobFinished_3	
Name	Nv_GetErrorStatus_2	
Туре	PPortPrototype	
Interface	Nv_GetErrorStatus_2	
Name	Nv_WriteBlock_4	
Туре	PPortPrototype	
Interface	Nv_WriteBlock_4	



	Name	Nv	_JobFinished_4_Obs1	
	Туре	RF	PortPrototype	
	Interface	Nv	_JobFinished_4_Obs1	
	Name		OperationInvokeEvent	_RestoreBlockDefaults
	Runnable Entity		Run_Nv_RestoreBlockDefaults_1	
			Access to	Nv_RestoreBlockDefaults_1
			Requirements	None
	Name		OperationInvokedEver	t_Nvm_SetBlockProtection
	Runnable Entity		Run_Nv_SetBlockProt	_
			Access to	Nv_SetBlockProtection_1
			Requirements	None
	Name		OperationInvokeEvent_WriteBlock	
	Runnable Entity	Run_Nv_WriteBlock_1		T
			Access to	Nv_WriteBlock_1
			Requirements	None
	Name		OperationInvokeEvent	PoadBlock 1
Operation	Runnable Entity		Run_Nv_ReadBlock_1	
Invoked Event	,		Access to Nv_ReadBlock_1	
			Requirements	None None
	Name		OperationInvokeEvent	_ReadBlock_2
	Runnable Entity		Run Nv ReadBlock 2	
			Access to	Nv_ReadBlock_2
			Requirements	None
	Name		OperationInvokeEvent	_ReadBlock_3
	Runnable Entity		Run_Nv_ReadBlock_3	
			Access to	Nv_ReadBlock_3
			Requirements	None
	Name		OperationInvokeEvent	_GetErrorStatus_2
	Runnable Entity		Run_Nv_GetErrorState	
			Access to	Nv_GetErrorStatus_2



	Requirements	None
Name	OperationInvokeEvent_	_WriteBlock_4
Runnable Entity	Run_Nv_WriteBlock_4	
	Access to	Nv_WriteBlock_4
	Requirements	None

SWC Name	Observation_SWC1		
	Name	Obs1_ReadBlock_1	
	Туре	RPortPrototype	
	Interface	ReadBlock_1	
	Name	Obs1_ReadBlock_2	
	Туре	RPortPrototype	
	Interface	ReadBlock_2	
	Name	Obs1_ReadBlock_3	
	Туре	RPortPrototype	
	Interface	ReadBlock_1	
	Name	Obs1_JobFinished_1	
PORTS	Туре	PPortPrototype	
	Interface	JobFinished_1	
	Name	Obs1_JobFinished_2	
	Туре	PPortPrototype	
	Interface	JobFinished_2	
	Name	Obs1_JobFinished_3	
	Туре	PPortPrototype	
	Interface	JobFinished_3	
	Name	Obs1_JobFinished_4	
	Туре	PPortPrototype	
	Interface	JobFinished_4	
Operation	Name	OperationInvokedEvent_Obs	
Invoked Event	Runnable Entity	Run_Obs1_JobFinished_1	
256 of 302	<del></del>	Document ID 634: AUTOSAR ATS RT	



		Access to	Obs1_JobFinished_1
		Requirements	None
	Name	OperationInvokedEvent_Obs1_2	
	Runnable Entity	Run_Obs1_JobFinished_2	
		Access to	Obs1_JobFinished_2
		Requirements	None
	Name	OperationInvokedE <sup>1</sup>	vent_Obs1_3
	Runnable Entity	Run_Obs1_JobFini	shed_3
		Access to	Obs1_JobFinished_3
		Requirements	None
	Name	Run_Obs1_ReadBl	ock_1
	Requirements	None	D 101 1 4
		Name	sscp_ReadBlock_1
		Туре	SynchronousServerCallPoir
	Servercall points	Access to	Obs1_ReadBlock_1 None
		REGULITEMENTS	
		Requirements	Notice
	Namo		
	Name Requirements	Run_Obs1_ReadBl	
	Name Requirements	Run_Obs1_ReadBl	ock_2
RUNNABLE		Run_Obs1_ReadBl None Name	ock_2 sscp_ReadBlock_2
RUNNABLE ENTITIES	Requirements	Run_Obs1_ReadBl	sscp_ReadBlock_2 SynchronousServerCallPoir
		Run_Obs1_ReadBl None Name Type Access to	sscp_ReadBlock_2 SynchronousServerCallPoir Obs1_ReadBlock_2
	Requirements	Run_Obs1_ReadBl None Name Type	sscp_ReadBlock_2 SynchronousServerCallPoir Obs1_ReadBlock_2
	Requirements	Run_Obs1_ReadBl None Name Type Access to	sscp_ReadBlock_2 SynchronousServerCallPoir Obs1_ReadBlock_2 None
	Requirements  Servercall points	Run_Obs1_ReadBl None  Name Type Access to Requirements	sscp_ReadBlock_2 SynchronousServerCallPoir Obs1_ReadBlock_2 None
	Requirements  Servercall points  Name	Run_Obs1_ReadBl None  Name Type Access to Requirements  Run_Obs1_ReadBl	sscp_ReadBlock_2 SynchronousServerCallPoir Obs1_ReadBlock_2 None
	Requirements  Servercall points  Name	Run_Obs1_ReadBl None  Name Type Access to Requirements  Run_Obs1_ReadBl None	sscp_ReadBlock_2 SynchronousServerCallPoir Obs1_ReadBlock_2 None
	Requirements  Servercall points  Name	Run_Obs1_ReadBl None  Name Type Access to Requirements  Run_Obs1_ReadBl None  Name	sscp_ReadBlock_2 SynchronousServerCallPoir Obs1_ReadBlock_2 None ock_3 sscp_ReadBlock_3
	Requirements  Servercall points  Name  Requirements	Run_Obs1_ReadBl None  Name Type Access to Requirements  Run_Obs1_ReadBl None  Name Type	sscp_ReadBlock_2 SynchronousServerCallPoir Obs1_ReadBlock_2 None  sck_3 sscp_ReadBlock_3 synchronousServerCallPoir Obs1_ReadBlock_3 SynchronousServerCallPoir
	Requirements  Servercall points  Name  Requirements	Run_Obs1_ReadBl None  Name Type Access to Requirements  Run_Obs1_ReadBl None  Name Type Access to	sscp_ReadBlock_2 SynchronousServerCallPoir Obs1_ReadBlock_2 None  sck_3 sscp_ReadBlock_3 synchronousServerCallPoir Obs1_ReadBlock_3 SynchronousServerCallPoir
	Requirements  Servercall points  Name  Requirements	Run_Obs1_ReadBl None  Name Type Access to Requirements  Run_Obs1_ReadBl None  Name Type Access to	sscp_ReadBlock_2 SynchronousServerCallPoir Obs1_ReadBlock_2 None  sscp_ReadBlock_3 sscp_ReadBlock_3 SynchronousServerCallPoir Obs1_ReadBlock_3 None
Operation	Requirements  Servercall points  Name  Requirements  Servercall points	Run_Obs1_ReadBl None  Name Type Access to Requirements  Run_Obs1_ReadBl None  Name Type Access to Requirements	sscp_ReadBlock_2 SynchronousServerCallPoir Obs1_ReadBlock_2 None  sscp_ReadBlock_3 SynchronousServerCallPoir Obs1_ReadBlock_3 None  vent_Obs1_4
ENTITIES	Requirements  Servercall points  Name  Requirements  Servercall points	Run_Obs1_ReadBl None  Name Type Access to Requirements  Run_Obs1_ReadBl None  Name Type Access to Requirements	sscp_ReadBlock_2 SynchronousServerCallPoir Obs1_ReadBlock_2 None  sscp_ReadBlock_3 SynchronousServerCallPoir Obs1_ReadBlock_3 None  vent_Obs1_4



SWC Name	Observation_SWC2				
	Name	Obs2_JobFinished_	1		
	Туре	PPortPrototype			
	Interface	JobFinished_1	JobFinished_1		
PORTS					
PORTS	Name	Obs2_JobFinished_	2		
	Туре	PPortPrototype			
	Interface	JobFinished_2			
	Name	OperationInvokedEvent_Obs2			
	Runnable Entity	Run_Obs2_JobFinished_1			
		Access to	Obs2	_JobFinished_1	
		Requirements	None		
Operation					
Invoked Event	Name	OperationInvolkeEvent_Obs2_2		os2_2	
	Runnable Entity	Run_Obs2_JobFinis	shed_2		
		Access to		Obs2_JobFinished_2	
		Requirements	3	None	

Service Dependency

Convict Deponds	Name	SwServiceDependency_Immediate
	RoleBasedPortAssignment	Ctrl_JobFinished_1 (NvMNotifyJobFinished)
	RoleBasedPortAssignment	Ctrl_RestoreBlockDefaults_Client_1 (NvMService)
	RoleBasedPortAssignment	Ctrl_WriteBlock_1 (NvMService)
	RoleBasedPortAssignment	Ctrl_SetBlockProtection_1 (NvMAdmin)
	NvDataPort	PP_SendData3, PP_SendData1
Control_SWC	ServiceNeeds	NvBlockNeeds : storeImmediate – True nRomBlocks : 1
	Name	SwcServiceDependancy_Cyclic_Ctrl
	RoleBasedPortAssignment	Ctrl_GetErrorStatus_2 (NvMService)
	NvDataPort	PP_SendData2
	ServiceNeeds	NvBlockNeeds : storeImmediate : False



	storeCyclic : True
	cyclicWritingPeriod : 10 sec
	calcRamBlockCrc : True
	useCRCCompMechanism : True
Name	SwcServiceDependancy_Cyclic_Shutdown_Ctrl
NvDataPort	PP_SendData4, PP_SendData5
	NvBlockNeeds : storeImmediate : False
	storeCyclic : True
ServiceNeeds	cyclicWritingPeriod : 10 sec
	storeAtShutDown : True
	useAutoValidationAtShutDown : True
Name	SwcServiceDependancy_NoDirtyFlag_Ctrl
RoleBasedPortAssignment	Ctrl_WriteBlock_4 (NvMService)
NvDataPort	PP_SendData6
	NvBlockNeeds : storeImmediate : False
	storeCyclic : False
ServiceNeeds	cyclicWritingPeriod : 10 sec
	storeAtShutDown : False
	useAutoValidationAtShutDown : False

	Name	SwServiceDependency_Immediate
	RoleBasedPortAssignmen t	Obs1_JobFinished_1 (NvMNotifyJobFinished)
	RoleBasedPortAssignmen t	Obs1_ReadBlock_1 (NvMService)
	RoleBasedPortAssignmen t	Obs1_ReadBlock_3 (NvMService)
	NvDataPort	RP_ObserveData1, RP_ObserveData3
Observation_SWC1		
Observation_Swc1	Name	SwServiceDependency_Cyclic_Obs1
	RoleBasedPortAssignmen t	Obs1_JobFinished_2 (NvMNotifyJobFinished)
	RoleBasedPortAssignmen t	Obs1_ReadBlock_2 (NvMService)
	NvDataPort	RP_ObserveData2
	_	
	Name	SwServiceDependency_Cyclic_Shutdown_Obs 1



RoleBasedPortAssignmen t	Obs1_JobFinished_3 (NvMNotifyJobFinished)
RoleBasedPortAssignmen t	Obs1_ReadBlock_3 (NvMService)
NvDataPort	RP_ObserveData4, RP_ObserveData_5
Name	SwServiceDependency_Cyclic_NoDirtyFlag_O bs1
RoleBasedPortAssignmen t	Obs1_JobFinished_4 (NvMNotifyJobFinished)
NvDataPort	RP_ObserveData8

	Name	SwServiceDependency_Immediate_Obs2
	RoleBasedPortAssignment	Obs2_JobFinished_1 (NvMNotifyJobFinished)
	NvDataPort	RP_ObserveData6
Observation SWC2		
Observation_SWC2	Name	SwServiceDependency_Cyclic_Obs2
	RoleBasedPortAssignment	Obs2_JobFinished_2 (NvMNotifyJobFinished)
	NvDataPort	RP_ObserveData7

	Name	NvBlockDescriptor1
	RoleBasedPortAssignment	Nv_JobFinished_1 (NvMNotifyJobFinished)
	RoleBasedPortAssignment	Nv_JobFinished_1_Obs1 (NvMNotifyJobFinished)
	RoleBasedPortAssignment	Nv_JobFinished_1_Obs2 (NvMNotifyJobFinished)
	RoleBasedPortAssignment	Nv_SetBlockProtection_1 (NvMAdmin)
NvBlockSwComponentType	RoleBasedPortAssignment	Nv_WriteBlock_1 (NvMService)
	RoleBasedPortAssignment	Nv_ReadBlock_1 (NvMService)
	NvRamBlockElement	PR_ReceiveData1, PR_ReceiveData3
	RamBlock	Nv_MainRecord {Nv_Data4; Nv_Record {Nv_Data1; Nv_Data2} }
	RomBlock	Nv_MainRecord {Nv_Data5; Nv_Record {Nv_Data1; Nv_Data2} }



	Initvalue : Nv_Data4 : 0x64
	Nv_Record {Nv_Data1 : 0xAAAA Nv_Data2 : 0xBBBB }
NvBlockNeeds	NvBlockDescriptor1Needs : storeImmediate – True nRomBlocks : 1
Name	NvBlockDescriptor2
RoleBasedPortAssignment	Nv_JobFinished_2_Obs1 (NvMNotifyJobFinished)
RoleBasedPortAssignment	Nv_JobFinished_2_Obs2 (NvMNotifyJobFinished)
RoleBasedPortAssignment	Nv_ReadBlock_2 (NvMService)
RoleBasedPortAssignment	Nv_GetErrorStatus_2 (NvMService)
NvRamBlockElement	PR_ReceiveData2
RamBlock	Nv_Array[4] : uint16
NvBlockNeeds	NvBlockDescriptor2Needs: storeImmediate: False storeCyclic: True cyclicWritingPeriod: 10sec calcRamBlockCrc: True useCRCCompMechanism: True
Name	NvBlockDescriptor3
RoleBasedPortAssignment	Nv_JobFinished_3_Obs1 (NvMNotifyJobFinished)
RoleBasedPortAssignment	Nv_ReadBlock_3 (NvMService)
NvRamBlockElement	PR_ReceiveData4, PR_ReceiveData5
RamBlock	Nv_Record1 { Nv_Data5 : uint16 ; Nv_Data3_Bitfield
NvBlockNeeds	NvBlockDescriptor3Needs: storeImmediate: False storeCyclic: True storeAtShutdown: True cyclicWritingPeriod: 10sec
Name	NvBlockDescriptor4
RoleBasedPortAssignment	Nv_JobFinished_4_Obs1 (NvMNotifyJobFinished)
RoleBasedPortAssignment	Nv_WriteBlock_4 (NvMService)
NvRamBlockElement	PR_ReceiveData6



RamBlock	Nv_Data6 : uint16
NvBlockNeeds	NvBlockDescriptor4Needs: storeImmediate: False storeCyclic: False storeAtShutdown: False supportDirtyFlag: False

#### 7.1.2.4 Mandatory vs Customizable Parts

Not Applicable

#### 7.1.3 Test Case Design

Not Applicable

### 7.2 Re-usable Test Steps

None.

#### 7.3 Test Cases

### 7.3.1 [ATS\_RTE\_01237] Implicit Write Access to NvDataElements - PrimitiveData Type of Write Immediate Block

Test Objective	Implicit Write Access to NvDataElements - PrimitiveData Type of Write Immediate Block		
ID	ATS_RTE_01237	AUTOSAR Releases	4.1.1 4.2.1 4.2.2
Affected Modules	RTE, NVM	State	reviewed
	ATR: ATR_ATR_00129 ATR: ATR_ATR_00130		
Trace to SWS Item	NVRAMManager: SWS_NvM_00 RTE: SWS_Rte_03829 RTE: SWS_Rte_08083 RTE: SWS_Rte_08085 RTE: SWS_Rte_08086 RTE: SWS_Rte_08087 RTE: SWS_Rte_08088 RTE: SWS_Rte_08089	455	
Requirements / Reference to Test Environment	UC05.01, UC05.02		
Configuration Parameters	This testcase uses : Control_SW Observation_SWC1 Control_SWC with Sender Interfa ApplicationPrimitiveDataType App_Data5 : uint32		wComponentType and



	NvBlockSwComponentType and Observation Nv_Data4 : App_Data5	_SWC1 has following interface:	
	NvBlockSwComponentType has NvBlockDescriptor1: PR_ReceiveData1Event triggers NvM_WriteBlock. supportDirtyFlag : True storeImmediate : True		
	Composition: Control_SWC.PP_SendData1 a NvBlockDescriptor1.PR_ReceiveData1 are convBlockDescriptor1.PR_ReceiveData1 and Care connected.	onnected.	
	C/S Interface for JobFinished from NvM for N NvBlockSwComponent Clientports : NvBlockDescriptor1	vBlockDescriptor1	
	Server Ports : In Control_SWC, Observation_	SWC1	
	C/S Interface for NvM_ReadBlock for NvBlock	«Descriptor1	
	NvBlockSwComponent : ServerPort Observation_SWC1 : ClientPort		
Summary	To check the NvDataHandling for Implicit Sender Receiver Communication for PrimitiveDataType with dirtyflag mechanism is enabled and storeImmediate is configured as True.		
	Once Implicit Write is completed by Control_SWC, NvM_WriteBlock will be triggered for NvBlockDescriptor1 based on Data Receive Event.		
	Wait until JobEndNotification for NvM_WriteBlock. Observation_SWC1 invokes NvM_ReadBlock for NvBlockDescriptor1.		
	Once NvM_ReadBlock gets JobEndNotification, Observation_SWC1 reads its require port. Data read is the updated value in RAM Block by Control_SWC.		
Needed Adaptation to other Releases	For Autosar 4.0.3, instead of PRPortPrototype, needs to configure PPort and RPort separately for NvBlockDescriptor		
Pre-conditions	None		
Main Test Exec	ution		
Test Steps		Pass Criteria	
Step 1	[CP]		
	Run_Ctrl_1 starts		
Step 2	[RUN <run_ctrl_1>]</run_ctrl_1>		
	Run_Ctrl_1 executes Rte_IWrite on VDP_Nv1 with value as below:		
	App_Data5 = 0x0A		
Step 3	[CP]		
	Run_Ctrl_1 is preempted by Run_Obs1_1		
Step 4	[RUN <run_obs1_1>]</run_obs1_1>	[RUN <run_obs1_1>]</run_obs1_1>	



	Run_Obs1_1 executes Rte_IRead from VDP_Nv1	Read data is initial value of NvBlock element and not the updated value from Control_SWC.
Otau E	ropi	Nv_Data4 = 0x190
Step 5	[CP]  Run_Obs1_1 terminates	
	Run_Ctrl_1 is resumed.	
Step 6	[CP]  Run_Ctrl_1 terminates	
Step 7	[SWC <nvblockswcomponent>]</nvblockswcomponent>	[SWC <nvblockswcomponent>]</nvblockswcomponent>
	PR_ReceiveData1Event invokes Run_NvM_WriteBlock which triggers NvM_WriteBlock for ImmediateBlock.	NvM_WriteBlock should return E_OK.
Step 8	[CP]	[SWC <observation_swc1></observation_swc1>
	Wait until JobEndNotification (NvM_WriteBlock) from NvM  Check call for NvMNotifyJobFinished	NvMNotifyJobFinished server operation of Run_Obs1_JobFinished_1 has been called for NvMBlockDescriptor1 with Serviceld value 0x7 and job_result NVM_REQ_OK.
Step 9	[CP]  Run_Obs1_ReadBlock_1 starts	
Step 10	[RUN <run_obs1_readblock_1></run_obs1_readblock_1>	[RUN <run_obs1_readblock_1]< th=""></run_obs1_readblock_1]<>
Step 11	[CP]	[SWC <observation_swc1></observation_swc1>
	Wait until JobEndNotification (NvM_ReadBlock) from NvM Check call for NvMNotifyJobFinished	NvMNotifyJobFinished server operation of Run_Obs1_JobFinished_1 has been called for NvMBlockDescriptor1 with Serviceld value 0x6 and job_result NVM_REQ_OK.
Step 12	[CP]	
	Run_Obs1_1 starts	
Step 13	[RUN <run_obs1_1>]</run_obs1_1>	[RUN <run_obs1_1>]</run_obs1_1>
	Run_Obs1_1 executes Rte_IRead from VDP_Nv1	Read data is as below:
D (	<b>1</b>	Nv_Data4 = 0x0A
Post- conditions	None	



#### 7.3.2 [ATS\_RTE\_01252] Explicit Write Access to NvDataElements - Composite type (Array) of Write Cyclic Block

Test Objective	Explicit Write Access to NvDataE Block	Elements - Co	omposite type (Array) of Write Cyclic
ID	ATS_RTE_01252	AUTOSAR Releases	4.1.1 4.2.1 4.2.2
Affected Modules	RTE, NVM	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00129 ATR: ATR_ATR_00130		
Trace to SWS Item	NVRAMManager: SWS_NvM_00455 RTE: SWS_Rte_03829 RTE: SWS_Rte_03833 RTE: SWS_Rte_08082 RTE: SWS_Rte_08084 RTE: SWS_Rte_08086 RTE: SWS_Rte_08087 RTE: SWS_Rte_08088 RTE: SWS_Rte_08089		
Requirements / Reference to Test Environment	UC05.01, UC05.02		
Configuration Parameters	This testcase uses: Control_SWC, NvBlockSwComponentType and Observation_SWC1  Control_SWC with Sender Interface: ApplicationArrayDataType App_Array[4]: uint16  NvBlockSwComponentType and Observation_SWC1 has following interface: Nv_Array[4]: App_Array[4]  NvBlockSwComponentType has NvBlockDescriptor2 which is configured as storeCyclic NvM_WriteBlock will be triggered periodically. supportDirtyFlag: True  Composition: Control_SWC.PP_SendData2 and NvBlockDescriptor2.PR_ReceiveData2 are connected. NvBlockDescriptor2.PR_ReceiveData2 and Observation_SWC1.RP_ObserveData2 are connected.  C/S Interface for JobFinished from NvM for NvBlockDescriptor2 NvBlockSwComponent: Clientport for NvBlockDescriptor2 Observation_SWC1 and Observation_SWC2 - Server Ports  C/S Interface for NvM_ReadBlock for NvBlockDescriptor2		



Summary	To check the NvDataHandling for Explicit Sender Receiver Communication for Composite Type like Arrays with dirtyflag mechanism is enabled and storeCyclic is configured as True.  Once Explicit Write is completed by Control_SWC, NvM_WriteBlock will be triggered for NvBlockDescriptor2 in the next periodic activity based on Timing Event.  Wait until JobEndNotification for NvM_WriteBlock. Observation_SWC1 invokes NvM_ReadBlock for NvBlockDescriptor2.	
Needed	Once NvM_ReadBlock gets JobEndNotification require port. Data read is the updated value in For Autosar 4.0.3, instead of PRPortPrototype	n RAM Block by Control_SWC.
Adaptation to other Releases	separately for NvBlockDescriptor	_
Pre-conditions		
Main Test Execu	ution	
Test Steps		Pass Criteria
Step 1	[CP] Run_Ctrl_2 starts	
Step 2	[RUN <run 2="" ctrl="">]</run>	[RUN <run_ctrl_2>]</run_ctrl_2>
	Run_Ctrl_2 executes Rte_Write on VDP_Nv2 with value as below:  App_Array[0] = 0xAABB  App_Array[1] = 0xBBCC  App_Array[2] = 0xCCDD  App_Array[3] = 0xDDEE	Rte_Write should return RTE_E_OK.
Step 3	[CP]  Run_Ctrl_2 is preempted by Run_Obs1_2	
Step 4	[RUN <run_obs1_2>]</run_obs1_2>	[RUN <run_obs1_2>]</run_obs1_2>
	Run_Obs1_2 executes Rte_Read from VDP_Nv2	Read data is updated value from Control_SWC  Nv_Array[0] = 0xAABB  Nv_Array[1] = 0xBBCC  Nv_Array[2] = 0xCCDD
		Nv_Array[3] = 0xDDEE
Step 5	[CP]	



	Run_Obs1_2 terminates.	
	Run_Ctrl_2 is resumed.	
Step 6	[CP]	
Step 7	Run_Ctrl_2 terminates [SWC <nvblockswcomponent>]</nvblockswcomponent>	[SWC <nvblockswcomponent>]</nvblockswcomponent>
Step 1		
	Timing Event PR_TimingData2Event invokes Run_NvM_WriteBlock_2 in the next periodic activity which triggers NvM_WriteBlock	NvM_WriteBlock should return E_OK
Step 8	[CP]	[SWC <observation_swc1>]</observation_swc1>
	Wait until JobEndNotification (NvM_WriteBlock) from NvM	NvMNotifyJobFinished server operation of Run Obs1 JobFinished 2 has been
	Check call for NvMNotifyJobFinished	called for NvMBlockDescriptor2 with ServiceId value 0x7 and job_result NVM_REQ_OK.
Step 9	[CP]	
Step 10	Run_Obs1_ReadBlock_2 starts [RUN <run_obs1_readblock_2>]</run_obs1_readblock_2>	[RUN <run_obs1_readblock_2>]</run_obs1_readblock_2>
·	Run_Obs1_ReadBlock_2 executes Rte_Call of NvM_ReadBlock() for NvMBlockDescriptor2	
Step 11	[CP]	[SWC <observation_swc1>]</observation_swc1>
	Wait until JobEndNotification (NvM_ReadBlock) from NvM	NvMNotifyJobFinished server operation of Run_Obs1_JobFinished_2 has been
	Check call for NvMNotifyJobFinished	called for NvMBlockDescriptor2 with ServiceId value 0x6 and job_result NVM_REQ_OK.
Step 12	[CP]	
	Run_Obs1_2 starts	
Step 13	[RUN <run_obs1_2>]</run_obs1_2>	[RUN <run_obs1_2>]</run_obs1_2>
	Run_Obs1_2 executes Rte_Read from VDP_Nv2	Read data is as below:
		Nv_Array[0] = 0xAABB
		Nv_Array[1] = 0xBBCC
		Nv_Array[2] = 0xCCDD
		Nv_Array[3] = 0xDDEE
Post- conditions	None	



### 7.3.3 [ATS\_RTE\_01283] Implicit Write Access to NvDataElements - Structure Data Type of Write Immediate Block

Test Objective	Implicit Write Access to NvDataE Block	lements - St	ructure Data Type of Write Immediate
ID	ATS_RTE_01283	AUTOSAR Releases	4.1.1 4.2.1 4.2.2
Affected Modules	Rte, NvM	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00129 ATR: ATR_ATR_00130		
Trace to SWS Item	NVRAMManager: SWS_NvM_00 RTE: SWS_Rte_03829 RTE: SWS_Rte_03830 RTE: SWS_Rte_08082 RTE: SWS_Rte_08087	455	
Requirements / Reference to Test Environment	UC05.01, UC05.02		
Parameters  269 of 200	This testcase uses: Control_SW Observation_SWC1 Control_SWC: ApplicationRecordDataType App_Record: Record Record { App_Data1: uint16 App_Data2: uint16 App_Data3: uint16 App_Data4: uint16 } NvBlockSwComponentType and Nv_Record { Nv_Data1: uint16 Nv_Data2: uint16 } NvBlockSwComponentType has PR_ReceiveData3Event triggers supportDirtyFlag: True storeImmediate: True  Composition:Control_SWC.PP_S NvBlockDescriptor1.PR_Receive NvBlockDescriptor1.PR_Receive are connected.  PortInterfaceMapping: App_Data1-> Nv_Data1 App_Data2-> Nv_Data2  NvBlockDescriptor1 C/S Interface for JobFinished NvBlockSwComponent: Clientpot Observation_SWC1 - Server Por	Observation  NvBlockDes  NvM_WriteE  SendData3 a  Data3 are co Data3 and C	n_SWC1 has following interface: scriptor1: Block.



	C/S Interface for NvM_ReadBlock NvBlockSwComponent : ServerPort Observation_SWC1 : ClientPort	
Summary	To check the NvDataHandling for Implicit Sender Receiver Communication for Composite types like C Structures with dirtyflag mechanism is enabled and storeImmediate is configured as True.	
	Once Implicit Write is completed by Control_S triggered for NvBlockDescriptor1 based on Da	
	Wait until JobEndNotification for NvM_WriteB NvM_ReadBlock for NvBlockDescriptor1.	lock. Observation_SWC1 invokes
	Once NvM_ReadBlock gets JobEndNotification require port. Data read is the updated value in	
Needed Adaptation to other Releases	For Autosar 4.0.3, instead of PRPortPrototype separately for NvBlockDescriptor	e, needs to configure PPort and RPort
Pre-conditions	None	
Main Test Exec	ution	
Test Steps		Pass Criteria
Step 1	[CP]	
Step 2	Run_Ctrl_3 starts [RUN <run_ctrl_3>]</run_ctrl_3>	
	Run_Ctrl_3 executes Rte_IWrite on VDP_ImplWrite2 with value as below:  { App_Data1 = 0x55AA App_Data2 = 0xAA55 App_Data3 = 0x5A5A App_Data4 = 0xA5A5 }	
Step 3	[CP] Run_Ctrl_3 terminates	
Step 4		[SWC <nvblockswcomponent>]</nvblockswcomponent>
·		NvM_WriteBlock should return E_OK
Step 5	[CP]	[SWC <observation_swc1>]</observation_swc1>
		NvMNotifyJobFinished server operation of



	Wait until JobEndNotification (NvM_WriteBlock) from NvM Check call for NvMNotifyJobFinished	Run_Obs1_JobFinished_1 has been called for NvMBlockDescriptor1 with ServiceId value 0x7 and job_result NVM_REQ_OK.
Step 6	[CP]  Run_Obs1_ReadBlock_1 starts	
Step 7	[RUN <run_obs1_readblock_1>]  Run_Obs1_ReadBlock_1 executes Rte_Call of NvM_ReadBlock() for NvBlockDescriptor1</run_obs1_readblock_1>	[RUN <run_obs1_readblock_1>]  NvM_ReadBlock() should return E_OK.</run_obs1_readblock_1>
Step 8	[CP]  Wait until JobEndNotification (NvM_ReadBlock) from NvM  Check call for NvMNotifyJobFinished	[SWC <observation_swc1>]  NvMNotifyJobFinished server operation of Run_Obs1_JobFinished_1 has been called for NvMBlockDescriptor1 with ServiceId value 0x6 and job_result NVM_REQ_OK.</observation_swc1>
Step 9	[CP] Run_Obs1_3 starts	
Step 10	[RUN <run_obs1_3>] Run_Obs1_3 executes Rte_IRead from VDP_Nv3</run_obs1_3>	[RUN <run_obs1_3>] Read data is as below: Nv_Data1 = 0x55AA Nv_Data2 = 0xAA55</run_obs1_3>
Post- conditions	None	

## 7.3.4 [ATS\_RTE\_01253] Explicit Write Access to NvDataElements - Boolean to BitField Type of Write Cyclic Block

•	Explicit Write Access to NvDataElements - Boolean to BitField Type of Write Cyclic Block		
ID		AUTOSAR Releases	4.2.1 4.2.2
Affected Modules	RTE, NVM	State	reviewed
	ATR: ATR_ATR_00129 ATR: ATR_ATR_00130		
ltem	NVRAMManager: SWS_NvM_00455 RTE: SWS_Rte_03831 RTE: SWS_Rte_08082 RTE: SWS_Rte_08086 RTE: SWS_Rte_08087		
Requirements / Reference	UC05.01, UC05.02		



to Test			
Environment Configuration Parameters	This testcase uses : Control_SWC, NvBlockSwComponentType and Observation_SWC1		
	Control_SWC with Sender Interface: ApplicationPrimitiveDataType App_boolean_element : boolean		
	NvBlockSwComponentType and Observation	_SWC1 has following interface:	
	Nv_Data3_bitfield : uint8	•	
	NvBlockSwComponentType has NvBlockDescriptor3 which is configured as storeCyclic and storeAtShutdown NvM_WriteBlock will be triggered periodically		
	supportDirtyFlag : True		
	Composition: Control_SWC.PP_SendData4 a NvBlockDescriptor3.PR_ReceiveData4 are convelled NvBlockDescriptor3.PR_ReceiveData4 and Care connected.	onnected.	
	C/S Interface for JobFinished from NvM for NvBlockDescriptor3 NvBlockSwComponent : Clientport for NvBlockDescriptor3 Observation_SWC1 - Server Ports		
	C/S Interface for NvM_ReadBlock for NvBlockDescriptor3 NvBlockSwComponent : ServerPort Observation_SWC1 : ClientPort		
Summary	To check the NvDataHandling for Explicit Sender Receiver Communication for Boolean to Bitfield data type with dirtyflag mechanism is enabled.		
	Once Explicit Write is completed by Control_SWC, NvM_WriteBlock will be triggered for NvBlockDescriptor3 in the next periodic activity based on Timing Event since service dependency for this data type is storeCyclic.		
	Wait until JobEndNotification for NvM_WriteB NvM_ReadBlock for NvBlockDescriptor3.	lock. Observation_SWC1 invokes	
	Once NvM_ReadBlock gets JobEndNotification, Observation_SWC1 reads its require port. Data read is the updated value in RAM Block in respective bitfiled by Control SWC.		
Needed Adaptation to other Releases	NA NA		
Pre-conditions	None		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[CP] Run_Ctrl_4 starts		
Step 2	[RUN <run_ctrl_4>]</run_ctrl_4>	[RUN <run_ctrl_4>]</run_ctrl_4>	
		Rte_Write should return RTE_E_OK.	



	_	
	Run_Ctrl_4 executes Rte_Write on	
	VDP_ExplWrite2 with value as below:	
	App_Boolean_Data = True	
Step 3	[CP]	
Step 3	[OI ]	
	Run_Ctrl_4 terminates	
Step 4	[SWC <nvblockswcomponent>]</nvblockswcomponent>	[SWC <nvblockswcomponent>]</nvblockswcomponent>
•		
	PR_TimingData4Event invokes	NvM_SetRamBlockStatus should
	Run_NvM_WriteBlock_3 in the next periodic	return E_OK
	activity which triggers NvM_SetRamBlockStatus for	
	NvBlockDescriptor3 with blockchanged	
	parameter as True	
Step 5	[SWC <nvblockswcomponent>]</nvblockswcomponent>	[SWC <nvblockswcomponent>]</nvblockswcomponent>
	Run_NvM_WriteBlock_3 triggers	NvM_WriteBlock should return E_OK.
Ston C	NvM_WriteBlock	ICANC (Chapmation CMC4, 1
Step 6	[CP]	[SWC <observation_swc1>]</observation_swc1>
	Wait until JobEndNotification	NvMNotifyJobFinished server
	(NvM_WriteBlock) from NvM	operation of
		Run_Obs1_JobFinished_3 has been
	Check call for NvMNotifyJobFinished	called for NvBlockDescriptor3 with
		ServiceId value 0x7 and job_result NVM_REQ_OK.
Step 7	[CP]	
	Run_Obs1_ReadBlock_3 starts	
Step 8	[RUN <run_obs1_readblock_3>]</run_obs1_readblock_3>	[RUN <run_obs1_readblock_3>]</run_obs1_readblock_3>
	Run_Obs1_ReadBlock_3 executes Rte_Call	
Step 9	of NvM_ReadBlock() for NvBlockDescriptor3  [CP]	E_OK. [SWC <observation_swc1>]</observation_swc1>
Step 9	[CF]	[SWC <observation_swc1>]</observation_swc1>
	Wait until JobEndNotification	NvMNotifyJobFinished server
	(NvM_ReadBlock) from NvM	operation of
		Run_Obs1_JobFinished_2 has been
	Check call for NvMNotifyJobFinished	called for NvBlockDescriptor3 with ServiceId value 0x6 and job_result
		NVM REQ OK.
Step 10	[CP]	
	Run_Obs1_4 starts	
Step 11	[RUN <run_obs1_4>]</run_obs1_4>	[RUN <run_obs1_4>]</run_obs1_4>
	Run_Obs1_4 executes Rte_Read from VDP Nv4	Read data is as below:
	V DIINV4	Nv_Data3_Bitfield = 0x08
		Hint : Computation Method - Sets the
		Hint : Computation Method - Sets the 3rd bit in RAM Block.
Post- conditions	None	



## 7.3.5 [ATS\_RTE\_01254] Explicit Write Access to NvDataElements - Primitive Data Type of Write At Shutdown Block

	Explicit Write Access to NvDataElements - Primitive Data Type of Write At Shutdown Block		
ID	ATS_RTE_01254	AUTOSAR Releases	4.2.1 4.2.2
Affected Modules	RTE, NVM	State	reviewed
	ATR: ATR_ATR_00129 ATR: ATR_ATR_00130		
ltem	NVRAMManager: SWS_NvM_00 RTE: SWS_Rte_03831 RTE: SWS_Rte_08080 RTE: SWS_Rte_08088	453	
Requirements / Reference to Test Environment	UC05.01, UC05.02, UC05.03		
Configuration Parameters	This testcase uses : Control_SW Observation_SWC1	C, NvBlockS	SwComponentType and
	Control_SWC with Sender Interface: ApplicationPrimitiveDataType App_Data6 : uint16		
	NvBlockSwComponentType and Observation_SWC1 has following interface: Nv_Data5 : App_Data6		
	NvBlockSwComponentType has NvBlockDescriptor3 which is configured as below: storeCyclic: True storeAtShutdown: True useAutoValidationAtShutDown: True supportDirtyFlag: True		
	Composition: Control_SWC.PP_SendData5, NvBlockDescriptor3.PR_ReceiveData5 and Observation_SWC1.RP_ObserveData5 are connected.  C/S Interface for JobFinished from NvM for NvBlockDescriptor3 NvBlockSwComponent : Clientport for NvBlockDescriptor3 Observation_SWC1 - Server Ports		
	C/S Interface for NvM_ReadBlock NvBlockSwComponent : ServerP Observation_SWC1 : ClientPort	ort	
Summary	To check the NvDataHandling for Primitive Data Type with dirtyflag		nder Receiver Communication for is enabled.
		since service	SWC, NvM_SetRamBlockStatus will be e dependency for this data type is on the same.



	Observation SWC1 invokes NvM ReadBlock	for NyBlock Descriptor3, Opco	
	NvM_ReadBlock gets JobEndNotification, Observation_SWC1 reads its require		
	port. Data read is the updated value in RAM Block by Control_SWC.		
Needed	NA		
Adaptation to other Releases			
Pre-conditions	None		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[CP]		
	Run_Ctrl_5 starts		
Step 2		[RUN <run_ctrl_5>]</run_ctrl_5>	
		[	
		Rte_Write should return RTE_E_OK.	
	VDP_Nv5 with value as below :		
	App_Data6 = 0x5A5A		
Step 3	[CP]		
01 1	Run_Ctrl_5 terminates	rowo N. Bl I O O	
Step 4	[SWC <nvblockswcomponent>]</nvblockswcomponent>	[SWC <nvblockswcomponent>]</nvblockswcomponent>	
	PR_TimingData5Event invokes	NvM_SetRamBlockStatus should	
	Run_WriteBlock_5 which triggers	return E_OK	
	NvM_SetRamBlockStatus with blockchanged parameter as True		
Step 5		[SWC <nvblockswcomponent>]</nvblockswcomponent>	
_	Run_WriteBlock_5 triggers NvM_WriteBlock		
Step 6	[CP]	[SWC <observation_swc1>]</observation_swc1>	
	Wait until JobEndNotification	NvMNotifyJobFinished server	
	(NvM_WriteBlock) from NvM	operation of	
		Run_Obs1_JobFinished_3 has been called for NvBlockDescriptor3 with	
	Check call for NvMNotifyJobFinished	Serviceld value 0x7 and job_result	
		NVM_REQ_OK.	
Step 7	[CP]	[SWC <nvblockswcomponent>]</nvblockswcomponent>	
	NvM_WriteAll shall be triggered by BswM	MultiBlockJobStatusInformation	
	during ECU shutdown	(NvM_WriteAll) has been called with	
		ServiceId value 0x0d and job_result NVM REQ OK	
Step 8	[LT <powersupply>]</powersupply>	IVW_REQ_OR	
2.06.0	F		
	Power off ECU		
Step 9	[CP]		
	Wait for n seconds [ n depends on time		
	needed for platform to shutdown]		
Step 10	[LT <powersupply>]</powersupply>		
	D 50U		
	Power on ECU		



Step 11	[CP]	
	Run_Obs1_ReadBlock_3 starts	
Step 12	[RUN <run_obs1_readblock_3>]</run_obs1_readblock_3>	[RUN <run_obs1_readblock_3>]</run_obs1_readblock_3>
	Run_Obs1_ReadBlock_3 executes Rte_Call	NvM_ReadBlock() should return
	of NvM_ReadBlock() for NvBlockDescriptor3	E_OK
Step 13	[CP]	[SWC <observation_swc1>]</observation_swc1>
•		
	Wait until JobEndNotification	NvMNotifyJobFinished server
	(NvM_ReadBlock) from NvM	operation of
		Run_Obs1_JobFinished_3 has been
	Check call for NvMNotifyJobFinished	called for NvBlockDescriptor3 with
	·	ServiceId value 0x6 and job_result
		NVM_REQ_OK.
Step 14	[CP]	
	Run_Obs1_5 starts	
Step 15	[RUN <run_obs1_5>]</run_obs1_5>	[RUN <run_obs1_5>]</run_obs1_5>
	Run_Obs1_5 executes Rte_Read from	Read data is as below:
	VDP_Nv5	
		Nv_Data5 = 0x5A5A
Post-	None	•
conditions		

### 7.3.6 [ATS\_RTE\_01255] Write Optimization if useCRCCompMechanism is True

Test Objective	Write Optimization if useCRCCompMechanism is True		
ID	ATS_RTE_01255	AUTOSAR Releases	4.2.1 4.2.2
Affected Modules	RTE, NVM	State	reviewed
	ATR: ATR_ATR_00129 ATR: ATR_ATR_00130		
ltem	RTE: SWS_Rte_03829 RTE: SWS_Rte_08082 RTE: SWS_Rte_08086 RTE: SWS_Rte_08087		
Requirements / Reference to Test Environment	UC05.01, UC05.02, UC05.03		
Configuration Parameters	This testcase uses: Control_SWC, NvBlockSwComponentType and Observation_SWC1 Control_SWC with Sender Interface: ApplicationArrayDataType App_Array[4]: uint16  NvBlockSwComponentType and Observation_SWC1 has following interface:		



	1		
	Nv_Array[4] : App_Array[4]		
	NvBlockSwComponentType has NvBlockDescriptor2 which is configured as storeCyclic		
	NvM_WriteBlock will be triggered periodically. supportDirtyFlag : True		
	Composition: Control_SWC.PP_SendData2, NvBlockDescriptor2.PR_ReceiveData2 and Observation_SWC1.RP_ObserveData2 are connected.		
	C/S Interface for JobFinished from NvM for NvBlockDescriptor2 NvBlockSwComponent : Clientport for NvBlockDescriptor2 Observation_SWC1 - Server Ports		
	C/S Interface for NvM_ReadBlock for NvBlock NvBlockSwComponent : ServerPort Observation_SWC1 : ClientPort	kDescriptor2	
	C/S Interface for NvM_GetErrorStatus for NvE NvBlockSwComponent : ServerPort Control_SWC : ClientPort	BlockDescriptor2	
Summary	To check the CRCCompMechanism feature in like Arrays with dirtyflag mechanism is enable		
	Once Explicit Write is completed by Control_SWC, NvM_WriteBlock will be triggered for NvBlockDescriptor2 in the next periodic activity based on Timing Event.		
	Invoke NvM_WriteAll without changing the data in RAM Block. Wait until 5 seconds. Control_SWC should invoke NvM_GetErrorStatus for NvBlockDescriptor2.		
	JobResult for the block should return NVM_REQ_BLOCK_SKIPPED because CRC matches with last Write Job.		
Needed Adaptation to other Releases	NA		
Pre-conditions	None		
Main Test Execu			
Test Steps		Pass Criteria	
Step 1	[CP]		
Stop 2	Run_Ctrl_2 starts	[RUN <run_ctrl_2>]</run_ctrl_2>	
Step 2	[RUN <run_ctrl_2>]</run_ctrl_2>	[RON-Ruii_Ctii_2>]	
	Run_Ctrl_2 executes Rte_Write on VDP_Nv2 with value as below:	Rte_Write should return RTE_E_OK	
	App_Array[0] = 0x1A1A		
	App_Array[1] = 0x2B2B		
	App_Array[2] = 0x3C3C		
	App_Array[3] = 0x4D4D		



Step 3	[CP]	
	Dura Otal O tampinatas	
Step 4	Run_Ctrl_2 terminates  [SWC <nvblockswcomponent>]</nvblockswcomponent>	[SWC <nvblockswcomponent>]</nvblockswcomponent>
Step 4	[OWO (WDIOCKOWOOMponent/)	[OWO (NVBIOCKOWCOIIIpolient)]
	PR_TimingData2Event invokes	NvM_WriteBlock should return E_OK.
	Run_NvM_WriteBlock_2 in the next periodic activity which triggers NvM_WriteBlock.	
Step 5	[CP]	[SWC <observation_swc1>]</observation_swc1>
	Wait until JobEndNotification	NvMNotifyJobFinished server
	(NvM_WriteBlock) from NvM	operation of
		Run_Obs1_JobFinished_2 has been
	Check call for NvMNotifyJobFinished	called for NvBlockDescriptor2 with ServiceId value 0x7 and job_result
		NVM_REQ_OK.
Step 6	[CP]	
	Run_Obs1_ReadBlock_2 starts	
Step 7	[RUN <run_obs1_readblock_2>]</run_obs1_readblock_2>	[RUN <run_obs1_readblock_2>]</run_obs1_readblock_2>
	Run_Obs1_ReadBlock_2 executes Rte_Call	NvM_PoadBlock() should return
	of NvM_ReadBlock() for NvBlockDescriptor2	
Step 8	[CP]	[SWC <observation_swc1>]</observation_swc1>
	Wait until JobEndNotification	NvMNotifyJobFinished server
	(NvM_ReadBlock) from NvM	operation of
	Check call for NvMNotifyJobFinished	Run_Obs1_JobFinished_2 has been called for NvBlockDescriptor2 with
	Check call for invivinoury 300 Finished	ServiceId value 0x6 and job_result
Cton 0	roni	NVM_REQ_OK.
Step 9	[CP]	
	Run_Obs1_2 starts	
Step 10	[RUN <run_obs1_2>]</run_obs1_2>	[RUN <run_obs1_2>]</run_obs1_2>
	Run Obs1 2 executes Rte Read from	Read data is as below:
	VDP_Nv2	
		Nv_Array[0] = 0x1A1A
		Nv_Array[1] = 0x2B2B
		Nv_Array[2] = 0x3C3C
		Nv_Array[3] = 0x4D4D
Step 11	[CP]	
	Invoke NvM_WriteAll	
Step 12	[CP]	
	Wait for 5seconds.	
Step 13	[CP]	
	D . 011 0.15	
	Run_Ctrl_GetError_2 starts	



Step 14	[RUN <run_ctrl_geterror_2>]</run_ctrl_geterror_2>	[SWC <control_swc>]</control_swc>
	Run_Ctrl_GetError_2 executes Rte_Call of NvM_GetErrorStatus for NvBlockDescriptor2	1. NvM_GetErrorStatus should return E_OK.
		RequestResultPtr parameter should be updated with NVM_REQ_BLOCK_SKIPPED for NvBlockDescriptor2.
Post- conditions	None	

### 7.3.7 [ATS\_RTE\_01284] Implicit Read Access of Ram Block from Multiple SWC's

Test Objective	Implicit Read Access of Ram Block from Multiple SWC's		
ID	ATS_RTE_01284	AUTOSAR Releases	4.1.1 4.2.1 4.2.2
Affected Modules	Rte, NvM	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00129 ATR: ATR_ATR_00130		
Trace to SWS Item	NVRAMManager: SWS_NvM_00455 RTE: SWS_Rte_03829 RTE: SWS_Rte_08085 RTE: SWS_Rte_08086		
Requirements / Reference to Test Environment	UC05.01, UC05.02		
Configuration Parameters	This testcase uses: Control_SWC, NvBlockSwComponentType, Observation_SWC1 and Observation_SWC2  Control_SWC with Sender Interface: Primitive Data Type App_Data5: uint32  NvBlockSwComponentType and Observation_SWC1 has following interface: Nv_Data4: uint32  NvBlockSwComponentType has NvBlockDescriptor1: PR_ReceiveData1Event triggers NvM_WriteBlock.  Composition: Control_SWC.PP_SendData1 and NvBlockDescriptor1.PR_ReceiveData1 are connected. NvBlockDescriptor1.PR_ReceiveData1 and Observation_SWC1.RP_ObserveData1 are connected. NvBlockDescriptor1.PR_ReceiveData1 and Observation_SWC2.RP_ObserveData6 are connected.  C/S Interface for JobFinished from NvM for NvBlockDescriptor1 NvBlockSwComponent: Clientport for NvBlockDescriptor1 Control_SWC, Observation_SWC1 and Observation_SWC2 - Server Ports		



Summary	To check the NvDataHandling for Implicit Read from Multiple SWC's for Primitive Data Type if dirtyflag mechanism is enabled.			
	Control Starts, does an implicit write on its provide port. NvM_WriteBlock will be invoked by the Data Receive Event once implicit write is completed.			
	Wait until JobFinished for NvM_WriteBlock. C port. Data read is the actual value written fron			
	Observation_SWC2 reads its require port. Da Control SWC.	ta read is the actual value written from		
Needed Adaptation to other Releases	For Autosar 4.0.3, instead of PRPortPrototype separately for NvBlockDescriptor	e, needs to configure PPort and RPort		
Pre-conditions	None			
Main Test Execu	ution			
Test Steps		Pass Criteria		
Step 1	[CP]			
	Run_Ctrl_1 starts			
Step 2	[RUN <run_ctrl_1>]</run_ctrl_1>			
	Run_Ctrl_1 executes Rte_IWrite on VDP_Nv1 with value as below:  App_Data5 = 0x05			
Step 3	[CP]			
	Run_Ctrl_1 is preempted by Run_Obs1_1			
Step 4	[RUN <run_obs1_1>]</run_obs1_1>	[RUN <run_obs1_1>]</run_obs1_1>		
	Run_Obs1_1 executes Rte_IRead on VDP_Nv1	Read data is initial value in RAMBlock and not the updated value from Control_SWC.		
		Nv_Data4 = 0x190		
Step 5	[CP]			
	Run_Obs1_1 terminates			
	Dun Chri 4 in required			
Ston 6	Run_Ctrl_1 is resumed.			
Step 6	[CP]			
	Run_Ctrl_1 is preempted by Run_Obs2_1			
Step 7	[RUN <run_obs2_1>] [RUN<run_obs1_1>]</run_obs1_1></run_obs2_1>			
	Run_Obs2_1 executes Rte_IRead on VDP_Nv1	Read data is initial value in RAMBlock and not the updated value from Control_SWC.		
		Nv_Data4 = 0x190		
Step 8	[CP]	111 - 0x 130		
C.Op O	10.1			
	1	I .		



	Run_Obs2_1 terminates.	
	Run_Ctrl_1 is resumed.	
Step 9	[CP]	
	Run_Ctrl_1 terminates	
Step 10	[SWC <nvblockswcomponent>]</nvblockswcomponent>	[SWC <nvblockswcomponent>]</nvblockswcomponent>
	PR_ReceiveData1Event triggers Run_NvM_WriteBlock which triggers NvM_WriteBlock for immediate block.	NvM_WriteBlock should return E_OK.
Step 11	[CP]	[SWC <observation_swc1>]</observation_swc1>
	Wait until JobEndNotification (NvM_WriteBlock) from NvM Check call for NvMNotifyJobFinished	NvMNotifyJobFinished server operation of Run_Obs1_JobFinished_1 has been called for NvBlockDescriptor1 with serviceid value 0x7 and job_result NVM_REQ_OK.
Step 12	[CP]	[SWC <observation_swc2>]</observation_swc2>
	Wait until JobEndNotification (NvM_WriteBlock) from NvM Check call for NvMNotifyJobFinished	NvMNotifyJobFinished server operation of Run_Obs2_JobFinished_1 has been called for NvBlockDescriptor1 with serviceid value 0x7 and job_result NVM_REQ_OK.
Step 13	[CP]	
	Run_Obs1_1 starts	
Step 14	[RUN <run_obs1_1>]</run_obs1_1>	[RUN <run_obs1_1>]</run_obs1_1>
	Run_Obs1_1 executes Rte_IRead on VDP_Nv1	Read data is as below:
	100	Nv_Data4 = 0x05
Step 15	[CP]	
	Run_Obs2_1 starts	
Step 16	[RUN <run_obs2_1>]</run_obs2_1>	[RUN <run_obs2_1>]</run_obs2_1>
	Run_Obs2_1 executes Rte_IRead on VDP_Nv1	Read data is as below:
		Nv_Data4 = 0x05
Post- conditions	None	

# 7.3.8 [ATS\_RTE\_01285] Explicit Read Access of Nv Data Elements from Multiple SWC's

Test Objective	Explicit Read Access of Nv Data Elements from Multiple SWC's			
ID	TS_RTE_01285 AUTOSAR 4.1.1 4.2.1 4.2.2			
		Releases		



Affected Modules	Rte, NvM	State	reviewed	
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00129 ATR: ATR_ATR_00130			
Trace to SWS Item	RTE: SWS_Rte_03830 RTE: SWS_Rte_03833 RTE: SWS_Rte_08082			
Requirements / Reference to Test Environment	UC05.01, UC05.02			
Configuration Parameters	This testcase uses : Control_SW0 Observation_SWC1 and Observa		wComponentType,	
	Control_SWC with Sender Interfa Array VDP_Nv2 : App_Array[4] (Applica	ce:	ıtaType)	
	NvBlockSwComponentType, Obs following interface:	ervation_SV	VC1 and Observation_SWC2 has	
	Nv_Array[4] : App_Array[4]			
	NvBlockSwComponentType has NvBlockDescriptor2 which is configured as storeCyclic NvM_WriteBlock will be triggered periodically. supportDirtyFlag: True  Composition: Control_SWC.PP_SendData2 and NvBlockDescriptor2.PR_ReceiveData2 are connected. NvBlockDescriptor2.PR_ReceiveData2 and Observation_SWC1.RP_ObserveData are connected. NvBlockDescriptor2.PR_ReceiveData2 and Observation_SWC2.RP_ObserveData are connected.			
	C/S Interface for JobFinished fror NvBlockSwComponent : Clientpo Observation_SWC1 and Observa	rt for NvBloc	kDescriptor2	
Summary	To check the NvDataHandling for Type like Arrays if dirtyflag mecha		nd from Multiple SWC's for Composite bled.	
	Control Starts, does an Explicit Write on the Provided Port. NvM_WriteBlock will be invoked by the Timing Event in the next periodic activity.			
	Wait until JobFinished for NvM_WriteBlock. Observation_SWC1 reads its port. Data read is the actual value written from Control SWC. Observation terminates.			
	Observation_SWC2 reads its req Control SWC. Observation termin		ta read is the actual value written from	
Needed Adaptation to other Releases	For Autosar 4.0.3, instead of PRF separately for NvBlockDescriptor	PortPrototype	e, needs to configure PPort and RPort	
Pre-conditions	Pre-conditions None			
Main Test Execu	ution			



Test Steps		Pass Criteria
Step 1	[CP]	
•		
	Run_Ctrl_2 starts	
Step 2	[RUN <run_ctrl_2>]</run_ctrl_2>	
	Run_Ctrl_2 executes Rte_Write on	
	VDP_Nv2 with value as below:	
	App_Array[0] = 0x5A5A	
	App_Array[1] = 0xA5A5	
	71 71 71	
	App_Array[2] = 0x55AA	
	App_Array[3] = 0xAA55	
Step 3	[CP]	
	,	
	Run_Ctrl_2 is preempted by Run_Obs1_2	
Step 4	[RUN <run_obs1_2>]</run_obs1_2>	[RUN <run_obs1_2>]</run_obs1_2>
	Run_Obs1_2 executes Rte_Read from	Read data is updated value from
	VDP_Nv2	Control_SWC
		Nv_Array[0] = 0x5A5A
		Nv_Array[1] = 0xA5A5
		_ ,,,
		Nv_Array[2] = 0x55AA
		Nv_Array[3] = 0xAA55
Step 5	[CP]	ivi_x anay[o] = ox a loc
	Run_Obs1_2 terminates.	
	Run Ctrl 2 is resumed.	
Step 6	[CP]	
	,	
	Run_Ctrl_2 terminates	
Step 7	[SWC <nvblockswcomponent>]</nvblockswcomponent>	[SWC <nvblockswcomponent>]</nvblockswcomponent>
	PR_TimingData2Event invokes	NvM_WriteBlock should return E_OK.
	Run_NvM_WriteBlock_2 in the next periodic	
	activity which triggers NvM_WriteBlock.	
Step 8	[CP]	[SWC <observation_swc1>]</observation_swc1>
	Wait until JobEndNotification	NvMNotifyJobFinished server
	(NvM_WriteBlock) from NvM	operation of
	Chook coll for No MAN Letter Let Timinter	Run_Obs1_JobFinished_2 has been called for NvBlockDescriptor2 with
	Check call for NvMNotifyJobFinished	serviceid value 0x7 and job_result
		NVM_REQ_OK.
Step 9	[CP]	[SWC <observation_swc2>]</observation_swc2>



Step 10	Wait until JobEndNotification (NvM_WriteBlock) from NvM Check call for NvMNotifyJobFinished  [CP]	NvMNotifyJobFinished server operation of Run_Obs2_JobFinished_2 has been called for NvBlockDescriptor2 with serviceid value 0x7 and job_result NVM_REQ_OK.
	Run_Obs1_2 starts	
Step 11	[RUN <run_obs1_2>]</run_obs1_2>	[RUN <run_obs1_2>]</run_obs1_2>
	Run_Obs1_2 executes Rte_Read on VDP_Nv2	Read data is as below:
		$Nv\_Array[0] = 0x5A5A$
		Nv_Array[1] = 0xA5A5
		Nv_Array[2] = 0x55AA
		Nv_Array[3] = 0xAA55
Step 12	[CP]	
	Run_Obs2_2 starts	
Step 13	[RUN <run_obs2_2>]</run_obs2_2>	[RUN <run_obs2_2>]</run_obs2_2>
	Run_Obs2_2 executes Rte_Read on VDP_Nv2	Read data is as below:
	12. 2.1.2	Nv_Array[0] = 0x5A5A
		Nv_Array[1] = 0xA5A5
		Nv_Array[2] = 0x55AA
		Nv_Array[0] = 0xAA55
Post- conditions	None	

## 7.3.9 [ATS\_RTE\_01261] NvMNotification and InitNotifyCallback using ClientServer Interface

Test Objective	NvMNotification and InitNotifyCallback using ClientServer Interface			
ID	ATS_RTE_01261 AUTOSAR 4.1.1 4.2.1 4.2.2 Releases			
Affected Modules	RTE, NVM State reviewed			
Trace to Requirement on Acceptance	ATR: ATR_ATR_00129			



Test Document			
Trace to SWS Item	NVRAMManager: SWS_NvM_00456 RTE: SWS_Rte_07625 RTE: SWS_Rte_07626 RTE: SWS_Rte_07629 RTE: SWS_Rte_07630 RTE: SWS_Rte_07631		
Requirement s / Reference to Test Environment			
n Parameters	This testcase uses: Control_SWC, NvBlockSwComponentType and Observation_SWC1  Control_SWC Client Port: Ctrl_RestoreBlockDefaults_Client_1 Server Port: Ctrl_JobFinished_1  NvBlockSwComponent  Server Port: Nv_RestoreBlockDefaults_1 Client Port: Nv_JobFinished_1  NvBlockDescriptor1 nROMBlocks: 1 should be configured with default values for respective data types  Vdp_Nv1 and VDP_ImplWrite3  Observation_SWC1  Server Port: Obs1_JobFinished_1		
Summary	NvMNotifyJobFinished for NvBlockDescriptor1 is mapped to Control_SWC and Observation_SWC1  This testcase is to test the NvMJobFinished and InitNotifyCallback using NvM_RestoreBlockDefaults api of NvM.  Control_SWC should invokes NvM_RestoreBlockDefaults api.  NvM will provide Job End Notification to Rte and Rte should invoke NvMNotifyJobFinished with RequestResult to Control_SWC and Observation_SWC1.  Observation starts by Observation_SWC1 and reads its require port. Data read is the		
Needed Adaptation to other Releases Pre-	default value of respective RAMBlock.  For Autosar 4.0.3, instead of PRPortPrototype, needs to configure PPort and RPort separately for NvBlockDescriptor  None		
conditions	INOLIG		
Main Test Execution			
Test Steps		Pass Criteria	
Step 1	[CP]  Run_Ctrl_RestoreBlockDefaults_1 starts		
	ran_otti_rastoreblockbetaults_r stafts		



Step 2	[RUN <run_ctrl_restoreblockdefaults_< th=""><th>[RUN<run_ctrl_restoreblockdefaults_< th=""></run_ctrl_restoreblockdefaults_<></th></run_ctrl_restoreblockdefaults_<>	[RUN <run_ctrl_restoreblockdefaults_< th=""></run_ctrl_restoreblockdefaults_<>
	1>]	1>]
	Run_Ctrl_RestoreBlockDefaults_1	NvM PostoroPlockDefaulte() should return
	executes Rte Call of	NvM_RestoreBlockDefaults() should return E OK
	NvM_RestoreBlockDefaults() for	
	NvBlockDescriptor1	
Step 3	[CP]	
	Wait until InitBlockCallback from NvM	
Step 4	[SWC <nvblockswcomponent>]</nvblockswcomponent>	
	Over the defection of a form DOMBLE Live	
	Copy the default value from ROMBlock in	
Cton E	NvMBlockDescriptor1 to RAMBlock	ISMC Control SMC 1
Step 5	[CP]	[SWC <control_swc>]</control_swc>
	Wait until JobEndNotification	NvMNotifyJobFinished server operation of
	(NvM_RestoreBlockDefaults) from NvM	Run_Ctrl_JobFinished_1 has been called
		for NvBlockDescriptor1 with ServiceId
	Check call for NvMNotifyJobFinished	value 0x8 and job_result NVM_REQ_OK.
Step 6	[CP]	[SWC <observation_swc1>]</observation_swc1>
	Wait until JobEndNotification	NvMNotifyJobFinished server operation of
	(NvM_RestoreBlockDefaults) from NvM	Run_Obs1_JobFinished_1 has been called
		for NvBlockDescriptor1 with ServiceId
	Check call for NvMNotifyJobFinished	value 0x8 and job_result NVM_REQ_OK.
Step 7	[CP]	
	Run_Obs1_1 starts	
Step 8	[RUN <run_obs1_1>]</run_obs1_1>	[RUN <run_obs1_1>]</run_obs1_1>
Step 0		
	Run_Obs1_1 executes Rte_IRead from	Read data is a default value as below:
	VDP_Nv1	
		Nv_Data4 = 0x64
Step 9	[CP]	
	Run_Obs1_3 starts	
Step 10	[RUN <run_obs1_3>]</run_obs1_3>	[RUN <run_obs1_3>]</run_obs1_3>
Step 10		
	Run_Obs1_3 executes Rte_IRead from	Read data for Record is default value as
	VDP_Nv3	below:
		[
		Nv_Data1 = 0xAAAA
		Nv_Data2 = 0xBBBB
Post-	None	
conditions		

### 7.3.10 [ATS\_RTE\_01262] Initialization of RAMBlock with Initivalue of VDP

Test Objectiv	e Initialization of RAMBlock with Initivalue of VDP



ID	ATS_RTE_01262	AUTOSAR Releases	4.1.1 4.2.1 4.2.2
Affected Modules	Rte	State	reviewed
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00129		
Trace to SWS Item	RTE: SWS_Rte_03852 RTE: SWS_Rte_07046 RTE: SWS_Rte_07632		
Requirements / Reference to Test Environment	UC05.01		
Configuration Parameters	This testcase uses: Control_SWC, NvBlockSwComponentType and Observation_SWC1 Control_SWC with Sender Interface: ApplicationPrimitiveDataType App_Data5: uint32  NvBlockSwComponentType and Observation_SWC1 has following interface: Nv_Data4: App_Data5  NvBlockSwComponentType has NvBlockDescriptor1:  Composition: Control_SWC.PP_SendData1 and NvBlockDescriptor1.PR_ReceiveData1 are connected. NvBlockDescriptor1.PR_ReceiveData1 and Observation_SWC1.RP_ObserveData1 are connected.		
	This testcase is to test the initialization of RAMBlock with initvalue of corresponding Variable Data Port while RTE starts.  At the time of RTE Initialization, RAMBlock configured in the NvMBlockDescriptor will be initialized with initvalue configured for VDP.  SWC should invoke Implicit Read to check the corresponding values are initialized		
Needed Adaptation to other Releases	properly.  For Autosar 4.0.3, instead of PRPortPrototype, needs to configure PPort and RPort separately for NvBlockDescriptor		
Pre-conditions	Rte_Init should be executed which initializes the VDP_Nv1  VDP_Nv1 = 0x190		
Main Test Execu	ution		
Test Steps			Pass Criteria
Step 1	[CP] Run_Obs1_1 starts		
Step 2	[RUN <run_obs1_1>]  Run_Obs1_1 executes Rte_IRea VDP_Nv1</run_obs1_1>	d from	[RUN <run_obs1_1>] Read data is as below:</run_obs1_1>
Post- conditions	None		Nv_Data4 = 0x190



## 7.3.11 [ATS\_RTE\_01263] Rejection of NvM\_WriteBlock by NvM if BlockProtection is enabled by SWC

Test	Rejection of NvM WriteBlock by	v NvM if Blo	ckProtection is enabled by SWC
Objective	rtojeenen er rttm_rtmezieen s	,	on retection is enabled by evve
ID	ATS_RTE_01263	AUTOSAR Releases	4.0.3 4.1.1 4.2.1 4.2.2
Affected Modules	NVM	State	reviewed
Trace to Requirement on Acceptance	ATR: ATR_ATR_00129		
Test Document			
Trace to SWS Item	NVRAMManager: SWS_NvM_0	00737	
Requirement s / Reference to Test	UC05.01		
Environment			
Configuration Parameters	This testcase uses : Control_SWC and NvBlockSwComponentType Control_SWC Client Port : Ctrl_WriteBlock_1 Client Port : Ctrl_SetBlockProtection_1		
	Server Port : Ctrl_JobFinished_1  NvBlockSwComponent  Server Port : Nv_WriteBlock_1 Server Port : Nv_SetBlockProtection_1 Client Port : Nv_JobFinished_1		
Summary	This testcase is to test the Rejection of NvM_WriteBlock call fromControl_SWC by NvM when respective block is protected.  Control_SWC invokes NvM_SetBlockProtection with ProtectionEnabled as True.  Control_SWC invokes NvM_WriteBlock for protected block. NvM should return E_NOT_OK and report DEM Error NVM_E_WRITE_PROTECTED.		
Needed Adaptation to other Releases	NA		
Pre- conditions	None		
Main Test Execution			
Test Steps			Pass Criteria
Step 1	[CP]	otosts	
Step 2	Run_Ctrl_SetBlockProtection_1 [RUN <run_ctrl_setblockprot ]<="" th=""><th></th><th>[RUN<run_ctrl_setblockprotection_1> ]</run_ctrl_setblockprotection_1></th></run_ctrl_setblockprot>		[RUN <run_ctrl_setblockprotection_1> ]</run_ctrl_setblockprotection_1>



	Run_Ctrl_SetBlockProtection_1 executes Rte_Call of NvM_SetBlockProtection() for NvBlockDescriptor1 with protectionenabled parameter as True	NvM_SetBlockProtection should return E_OK.
Step 3	[CP]  Run_Ctrl_WriteBlock_1 starts	
·	[RUN <run_ctrl_writeblock_1>]  Run_Ctrl_WriteBlock_1 executes Rte_Call of NvM_WriteBlock() for NvBlockDescriptor1 which is write protected</run_ctrl_writeblock_1>	[RUN <run_ctrl_writeblock_1>]  NvM_WriteBlock should return E_NOT_OK.</run_ctrl_writeblock_1>
Step 5	[SWC <control_swc>] Check status of DEM Event NVM_E_WRITE_PROTECTED.</control_swc>	[SWC <control_swc>] Status Bit "TestFailed" of DEM Event NVM_E_WRITE_PROTECTED is set.</control_swc>
Post- conditions	None	

### 7.3.12 [ATS\_RTE\_01288] Write Access to NvDataElements if storeDirtyFlag is False

Test Objective	Write Access to NvDataElements if storeDirtyFlag is False			
ID	ATS_RTE_01288	AUTOSAR Releases	4.1.1 4.2.1 4.2.2	
Affected Modules	RTE, NVM	State	reviewed	
Trace to Requirement on Acceptance Test Document	ATR: ATR_ATR_00129			
Trace to SWS Item	NVRAMManager: SWS_NvM_00455 RTE: SWS_Rte_07668			
Requirements / Reference to Test Environment	UC05.01, UC05.02			
	This testcase uses: Control_SWC, NvBlockSwComponentType and Observation_SWC1  Control_SWC with Sender Interface: ApplicationPrimitive Data Type App_Data7: uint16  NvBlockSwComponentType and Observation_SWC1 has following interface: Nv_Data6: App_Data7  NvBlockSwComponentType has NvBlockDescriptor4 which is configured as below: supportDirtyFlag: False storeCyclic: False storeAtShutdown: False  Composition: Control_SWC.PP_SendData6,			



	NvBlockDescriptor4.PR_ReceiveData6 and Observation_SWC1.RP_ObserveData8 are connected.		
	C/S Interface for NvM_WriteBlock for NvBlockDescriptor4 NvBlockSwComponent : ServerPort Control_SWC : ClientPort		
	C/S Interface for JobFinished from NvM for NvBlockDescriptor4 NvBlockSwComponent: Clientport for NvBlockDescriptor4 Observation_SWC1 - Server Ports		
	C/S Interface for NvM_ReadBlock for NvBlockDescriptor4 NvBlockSwComponent : ServerPort Observation_SWC1 : ClientPort		
Summary	To check the NvDataHandling for Explicit Sen Primitive Data Type if dirtyflag mechanism is o		
	Control_SWC has to invoke client-server open NvBlockDescriptor4 to complete the write open		
	Observation_SWC1 invokes NvM_ReadBlock JobEndNotification from NvM.	for NvBlockDescriptor4. Wait until	
	Observation_SWC1 does the explicit read on its require port.The read data will have latest value which is written by Control_SWC		
Needed Adaptation to other Releases	For Autosar 4.0.3, instead of PRPortPrototype separately for NvBlockDescriptor	e, needs to configure PPort and RPort	
Pre-conditions	None		
Main Test Exec	ution		
Test Steps		Pass Criteria	
Step 1	[CP]		
	Run_Ctrl_6 starts		
Step 2	[RUN <run_ctrl_6>]</run_ctrl_6>	[RUN <run_ctrl_6>]</run_ctrl_6>	
	Run_Ctrl_6 executes Rte_Write on VDP_Nv6 with value as below:	Rte_Write should return RTE_E_OK	
	App_Data7 = 0x1A1A		
Step 3	[CP]		
	Run_Ctrl_6 terminates		
Step 4	[CP]		
	Run_Ctrl_WriteBlock_4 starts		
Step 5	[RUN <run_ctrl_writeblock_4>]</run_ctrl_writeblock_4>	[RUN <run_ctrl_writeblock_4>]</run_ctrl_writeblock_4>	
	Run_Ctrl_WriteBlock_4 executes Rte_Call of NvM_WriteBlock for Block_4	NvM_WriteBlock should return E_OK	
Step 6	[CP]	[SWC <observation_swc1>]</observation_swc1>	
		NvMNotifyJobFinished server	
		operation of	



	Wait until JobEndNotification	Run_Obs1_JobFinished_4 has been
	(NvM_WriteBlock) from NvM	called for NvBlockDescriptor4 with Serviceld value 0x7 and job_result
	Check call for NvMNotifyJobFinished	NVM_REQ_OK.
Step 7	[CP]	
	Run_Obs1_ReadBlock_4 starts	
Step 8	[RUN <run_obs1_readblock_4>]</run_obs1_readblock_4>	[RUN <run_obs1_readblock_4>]</run_obs1_readblock_4>
	Run_Obs1_ReadBlock_4 executes Rte_Call of NvM_ReadBlock() for NvBlockDescriptor4	NvM_ReadBlock should return E_OK
Step 9	[CP]	[SWC <observation_swc1>]</observation_swc1>
	Wait until JobEndNotification (NvM_ReadBlock) from NvM  Check call for NvMNotifyJobFinished	NvMNotifyJobFinished server operation of Run_Obs1_JobFinished_4 has been called for NvBlockDescriptor4 with Serviceld value 0x6 and job_result NVM_REQ_OK.
Step 10	[CP]	
	Run_Obs1_6 starts	
Step 11	[RUN <run_obs1_6>]</run_obs1_6>	[RUN <run_obs1_6>]</run_obs1_6>
	Run_Obs1_6 executes Rte_Read from VDP_Nv6	Read data is as below:
		Nv_Data6 = 0x1A1A
Post- conditions	None	



### 8 Miscellaneous features

## 8.1 General Test Objective and Approach

This test suite provides additional test cases for miscellaneous features of the RTE, when they do not require a complete test suite on their own.

#### 8.1.1 Test System

#### 8.1.1.1 Overview on Architecture

The basic test setup is depicted in Figure 9. Test cases require a SW-C on the SUT, which uses the tested features. This SW-C may need multiple PortPrototypes and RunnableEntities, which re described in each test case's "Configuration Parameters" field. A result may be observed on the bus.




Figure 9: Test Setup for Inter-ECU Test

#### 8.1.1.2 Specific Requirements

None

#### 8.1.1.3 Test Coordination Requirements

Test Coordination Procedures are needed to synchronize the runnables of the SWCs or to wait for different invocation instances of runnables.

TCPs are also needed to collect the test results of the SWCs and the Bus simulation at one central place in order to derive the test verdict.

It is up to the test system designer/implementer to define that "central place" and to design/implement the test coordination functionality.



### 8.1.2 Test Configuration

The configuration required to implement and execute the test cases is described in the "Configuration Parameters" field of each test case.

These requirement on configuration describe

- The needed configuration for the description of the SW-C associated to the test case
- The needed configuration for the EcuExtract associated to the test case

## 8.2 Re-usable Test Steps

None.

### 8.3 Test Cases

### 8.3.1 [ATS\_RTE\_00691] InterRunnableVariables With Explicit Behavior

Toot Objective	InterRunnableVariables With Explicit Behavior		
-			
ID	ATS_RTE_00691	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Item	RTE: SWS_Rte_01305 RTE: SWS_Rte_01306 RTE: SWS_Rte_03560 RTE: SWS_Rte_03565 RTE: SWS_Rte_03567 RTE: SWS_Rte_03580		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * VariableDataPrototype_TC59 in the role explicitInterRunnableVariable - with initValue configured (Ex: 0x05)  * A RunnableEntity to execute the test sequence - with a readLocalVariable which references VariableDataPrototype_TC59 - with a writtenLocalVariable which references VariableDataPrototype_TC59		
Summary	The test checks for explicit access to IRV the value read for an IRV before it is written and checks that an IRV value written explicitly is available immediately for reading by executing Rte_IrvRead in the same execution-instance as the Rte_IrvWrite call.		
Needed Adaptation to other Releases			
	DUT shall be initialized EcuM module shall be in RUN state		
Main Test Execu	ution		
Test Steps			Pass Criteria



Step 1	[SWC] Invoke Rte_IrvRead to read VariableDataPrototype_TC59.	[SWC] Rte_IrvRead returns the initValue
Step 2	[SWC] Invoke Rte_IrvWrite to write VariableDataPrototype_TC59 with a value different from the initValue.	-
Step 3	[SWC] Invoke Rte_IrvRead to read VariableDataPrototype_TC59.	[SWC] Rte_IrvRead returns the data which was written through Rte_IrvWrite.
Post- conditions	NONE	

# 8.3.2 [ATS\_RTE\_00692] InterRunnableVariables With Implicit Behavior

Test Objective	InterRunnableVariables With Implicit Behavior		
ID	ATS_RTE_00692	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01303 RTE: SWS_Rte_01304 RTE: SWS_Rte_03550 RTE: SWS_Rte_03553 RTE: SWS_Rte_03580 RTE: SWS_Rte_03582 RTE: SWS_Rte_03584 RTE: SWS_Rte_07022		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * A PPortPrototype and an RPortPrototype typed by a ClientServerInterface with one operation Operation_TC60  - these ports are connected  * VariableDataPrototype_TC60 in the role implicitInterRunnableVariable  - with initValue configured (Ex: 0x05)  * RunnableEntity_TC60 to execute the test sequence  - with a readLocalVariable which references VariableDataPrototype_TC60  - with a writtenLocalVariable which references VariableDataPrototype_TC60  - with a SynchronousServerCallPoint  * RunnableEntity_TC60Server  - started by an OperationInvokedEvent which references Operation_Tc60  - with a readLocalVariable which references VariableDataPrototype_TC60		
Summary	The test checks for implicit access to IRV the value read for an IRV before it is written and checks that an IRV value written implicitly is available only after the end of the execution-instance.		



Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state		
Main Test Execu	ution		
Test Steps		Pass Criteria	
Step 1	[RUN <runnableentity_tc60>] Invoke Rte_IrvIRead to read VariableDataPrototype_TC60.</runnableentity_tc60>	[RUN <runnableentity_tc60>] Rte_IrvIRead returns initValue.</runnableentity_tc60>	
Step 2	[RUN <runnableentity_tc60>] Invoke Rte_IrvIWrite to write VariableDataPrototype_TC60 initValue+1.</runnableentity_tc60>	-	
Step 3	[RUN <runnableentity_tc60>] Invoke Rte_IrvIRead to read VariableDataPrototype_TC60.</runnableentity_tc60>	[RUN <runnableentity_tc60>] Rte_IrvIRead returns initValue+1.</runnableentity_tc60>	
Step 4	[RUN <runnableentity_tc60>] Invoke Operation_TC60</runnableentity_tc60>	[RUN <runnableentity_tc60server>] RunnableEntity_TC60Server is invoked.</runnableentity_tc60server>	
Step 5	[RUN <runnableentity_tc60server>] Invoke Rte_IrvIRead to read VariableDataPrototype_TC60.</runnableentity_tc60server>	[RUN <runnableentity_tc60server>] Rte_IrvIRead returns initValue.</runnableentity_tc60server>	
Step 6	[RUN <runnableentity_tc60server>] Return to exit from this RunnableEntity_TC60 execution-instance.</runnableentity_tc60server>	[RUN <runnableentity_tc60>] Rte_Call returns and RunnableEntity_TC60 resumes its execution.</runnableentity_tc60>	
Step 7	[RUN <runnableentity_tc60>] Return to exit from this RunnableEntity_TC60 execution-instance.</runnableentity_tc60>	-	
Step 8	[CP] Wait for the next execution-instance of RunnableEntity_TC60.	[RUN <runnableentity_tc60>] RunnableEntity_TC60 is invoked.</runnableentity_tc60>	
Step 9	[RUN <runnableentity_tc60>] [SWC] Invoke Rte_IrvIRead to read VariableDataPrototype_TC60.</runnableentity_tc60>	[RUN <runnableentity_tc60>] Rte_IrvIRead returns initValue+1.</runnableentity_tc60>	
Step 10	[RUN <runnableentity_tc60>] Invoke Operation_TC60</runnableentity_tc60>	[RUN <runnableentity_tc60server>] RunnableEntity_TC60Server is invoked.</runnableentity_tc60server>	
Step 11	[RUN <runnableentity_tc60server>] Invoke Rte_IrvIRead to read VariableDataPrototype_TC60.</runnableentity_tc60server>	[RUN <runnableentity_tc60server>] Rte_IrvIRead returns initValue+1.</runnableentity_tc60server>	
Post- conditions	NONE		

# 8.3.3 [ATS\_RTE\_00693] Enhanced Rte\_Mode API Functionality

Test Objective	Enhanced Rte_Mode API Functionality		
ID		AUTOSA R Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed



Trace to		
Requireme		
nt on		
Acceptance		
Test		
Document		
Trace to	RTE: SWS_Rte_02512	
	RTE: SWS_Rte_02631	
	RTE: SWS_Rte_02632	
	RTE: SWS_Rte_02667	
	RTE: SWS_Rte_02669	
	RTE: SWS_Rte_02609	
	RTE: SWS_Rte_07173	
	RTE: SWS_Rte_08500	
	RTE: SWS_Rte_08501	
	RTE: SWS_Rte_08504	
	RTE: SWS_Rte_08505	
Requireme		
nts /		
Reference		
to Test		
Environme		
nt		
Configurati	A ModeDeclarationGroup MDG_TC67 with	
on	* 2 ModeDeclarations: StopMode=0 EndMode=1	
_	* initialMode=StopMode	
raiailleteis	IIIIIaliviode=Stopiviode	
	A CIAI C with	
	A SW-C with	
	* A PPortPrototype which	
	- is typed with a ModeSwitchInterface with a ModeDeclarationGroupPrototype with	
	type=MDG_TC67	
	- has a ModeSwitchSenderComSpec with enhancedModeApi=TRUE	
	* An RPortPrototype which	
	- is typed by the same ModeSwitchInterface	
	- has a ModeSwitchReceiverComSpec with enhancedModeApi=TRUE	
	- is connected with the previous PPortPrototype	
	* RunnableEntity_TC67 to initiate the test sequence	
	- with a modeSwitchPoint which references the ModeDeclarationGroupPrototype of the	
	PPortPrototype	
	- with a modeAccessPoint which references the ModeDeclarationGroupPrototype of the	
	RPortPrototype	
	* RunnableEntity_OnEntryEndMode which	
	is started by a SwcModeSwitchEvent (activation=onEntry mode=EndMode)	
	<ul> <li>has a modeAccessPoint which references the ModeDeclarationGroupPrototype of the</li> </ul>	
	RPortPrototype	
Summary	This test case verifies the enhanced Rte_Mode API. When an application SW-C calls	
,	Enhanced Rte_Mode' API the RTE provides the currently active mode of the requested	
	mode switch port and if the mode machine instance is in transition then additionally the	
	values of the previous mode and the next mode are provided.	
Needed	1 222	
Adaptation		
to other		
Releases		
	DUT shall be initialized	
conditions	EcuM module shall be in RUN state	
Main Test Ex	recution	
Test Steps	Pass Criteria	
rear archa	r ass Citteria	



Step 1	[RUN <runnableentity_tc67>] Invoke Rte_Mode(&amp;PreviousMode, &amp;NextMode).</runnableentity_tc67>	[RUN <runnableentity_tc67>] Rte_Mode returns RTE_MODE_MDG_TC67_StopMode and the value in the OUT parameters are: PreviousMode=RTE_MODE_MDG_TC67_St opMode NextMode=RTE_MODE_MDG_TC67_StopM ode</runnableentity_tc67>
Step 2	[RUN <runnableentity_tc67>] Invoke Rte_Switch(RTE_MODE_MDG_TC67_End dMode)</runnableentity_tc67>	[RUN <runnableentity_tc67>] Rte_Switch returns RTE_E_OK.</runnableentity_tc67>
Step 3	-	[RUN <runnableentity_onentryendmode>] RunnableEntity_OnEntryEndMode is invoked.</runnableentity_onentryendmode>
Step 4	[RUN <runnableentity_onentryendmode &gt;] Invoke Rte_Mode(&amp;PreviousMode, &amp;NextMode).</runnableentity_onentryendmode 	[RUN <runnableentity_onentryendmode>] Rte_Mode returns RTE_TRANSITION_MDG_TC67 and the value in the OUT parameters are: PreviousMode=RTE_MODE_MDG_TC67_St opMode NextMode=RTE_MODE_MDG_TC67_EndM ode</runnableentity_onentryendmode>
Step 5	[CP] Wait for the next execution-instance of RunnableEntity_TC67	[RUN <runnableentity_tc67>] RunnableEntity_TC67is invoked.</runnableentity_tc67>
Step 6	[RUN <runnableentity_tc67>] Invoke Rte_Mode(&amp;PreviousMode, &amp;NextMode).</runnableentity_tc67>	[RUN <runnableentity_tc67>] Rte_Mode returns RTE_MODE_MDG_TC67_EndMode and the value in the OUT parameters are: PreviousMode=RTE_MODE_MDG_TC67_E ndMode NextMode=RTE_MODE_MDG_TC67_EndM ode</runnableentity_tc67>
Step 7	[RUN <runnableentity_tc67>] Invoke Rte_Switch(RTE_MODE_MDG_TC67_EndMode)</runnableentity_tc67>	[RUN <runnableentity_tc67>] Rte_Switch returns RTE_E_OK.</runnableentity_tc67>
Step 8	-	[RUN <runnableentity_onentryendmode>] RunnableEntity_OnEntryEndMode is invoked.</runnableentity_onentryendmode>
Step 9	>] Invoke Rte_Mode(&PreviousMode, &NextMode).	[RUN <runnableentity_onentryendmode>] Rte_Mode returns RTE_TRANSITION_MDG_TC67 and the value in the OUT parameters are: PreviousMode=RTE_MODE_MDG_TC67_E ndMode NextMode=RTE_MODE_MDG_TC67_EndM ode</runnableentity_onentryendmode>
Post- conditions	NONE	



## 8.3.4 [ATS\_RTE\_00702] Ports APIs Functionality

Test	Ports APIs Functionality		
Objective			
ID	ATS_RTE_00702	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
	RTE: SWS_Rte_01354 RTE: SWS_Rte_01355 RTE: SWS_Rte_02613 RTE: SWS_Rte_02614 RTE: SWS_Rte_02615 RTE: SWS_Rte_02619 RTE: SWS_Rte_03602 RTE: SWS_Rte_03603		
Requirements / Reference to Test Environment			
Parameters	2 SenderReceiverInterfaces: IF_TC92a, IF_TC92b with VariableDataPrototype_TC92a (resp. VariableDataPrototype_TC92), swImplPolicy standard  A SW-C with * PPortPrototype P_TC92a1, typed by IF_TC92a * PPortPrototype P_TC92a2, typed by IF_TC92a * PPortPrototype P_TC92b1, typed by IF_TC92b * PPortPrototype P_TC92b2, typed by IF_TC92b * Referenced by PortAPIOption, indirectAPI=TRUE, except P_TC92b2: indirectAPI=FALSE  * RPortPrototype R_TC92a1, typed by IF_TC92a, connected to P_TC92a1 * RPortPrototype P_TC92a2, typed by IF_TC92a, connected to P_TC92a2 * RPortPrototype P_TC92b1, typed by IF_TC92b, connected to P_TC92b1 * RPortPrototype P_TC92b1, typed by IF_TC92b, connected to P_TC92b2 * With NonqueuedReceiverComSpec, initValue=0  * RunnableEntity to execute the test sequence - with a 4 dataSendPoints for the dataElements in P_TC92a1, P_TC92b2, P_TC92b1, P_TC92b2 - with a 4 dataReceivePointByValue for the dataElements in R_TC92a1, R_TC92a2, R_TC92b1, R_TC92b1		
Summary	Rte_Ports API provide an array of the ports of a given interface type and a given provide / require usage that can be accessed by the indirect API. i.e. Rte_Ports API returns array of port data structures of the corresponding interface type and usage. Rte_NPorts API provides the number of ports of a given interface type and provide/require usage that can be accessed through the indirect API. i.e. Rte_NPorts API returns number of port data structures of the corresponding interface type and usage. Rte_Port API provides access to the port data structure for a single port of a particular software component instance. This allows a software component to extract		



	a sub-group of ports characterized by the same interface sub-group.	e in order to iterate over this
Needed Adaptation to other Releases		
	DUT shall be initialized	
	EcuM module shall be in RUN state	
Main Test Exe		
Test Steps		Pass Criteria
•	[SWC] Invoke Rte_Ports_IF_TC92a_P.	[SWC] Rte_Ports returns an array of PortHandles != NULL_PTR.
	[SWC] Invoke Rte_NPorts_IF_TC92a_P.	[SWC] Rte_NPorts returns 2.
	[SWC] For the 2 port handles returned by Rte_Ports invoke the function pointer named Write_VariableDataPrototype_TC92a in the port handle with value 1.	[SWC] Each function call returns RTE_E_OK.
	[SWC] Invoke Rte_DRead_R_TC92a1_VariableDataPrototype_TC92a	[SWC] Rte_DRead returns 1
	[SWC] Invoke Rte_DRead_R_TC92a2_VariableDataPrototype_TC92a	[SWC] Rte_DRead returns 1
Step 6	[SWC] Invoke Rte_Ports_IF_TC92b_P.	[SWC] Rte_Ports returns an array of ports with address != NULL_PTR.
Step 7	[SWC] Invoke Rte_NPorts_IF_TC92b_P.	[SWC] Rte_NPorts returns 1.
	[SWC] For the port handle returned by Rte_Ports invoke the function pointer named Write_VariableDataPrototype_TC92b in the port handle with value 1.	[SWC] The function call returns RTE_E_OK.
Step 9	[SWC] Invoke Rte_DRead_R_TC92b1_VariableDataPrototype_TC92b	[SWC] Rte_DRead returns 1
	[SWC] Invoke Rte_DRead_R_TC92b2_VariableDataPrototype_TC92b	[SWC] Rte_DRead returns 0
Step 11	[SWC] Invoke Rte_Port_P_TC92b2.	[SWC] Rte_Port returns a PortHandle!=NULL_PTR.
	[SWC] For the port handle returned by Rte_Port invoke the function pointer named Write_VariableDataPrototype_TC92b in the port handle with value 2.	[SWC] The function call returns RTE_E_OK.
	[SWC] Invoke Rte_DRead_R_TC92b1_VariableDataPrototype_TC92b	[SWC] Rte_DRead returns 2



•
NONE
INONE

## 8.3.5 [ATS\_RTE\_00703] Rte\_Prm API Functionality

Test Objective	Rte_Prm API Functionality		
ID	ATS_RTE_00703	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document		-	
Trace to SWS Item	RTE: SWS_Rte_03928 RTE: SWS_Rte_03929		
Requirements / Reference to Test Environment			
Configuration Parameters	A ParameterSwComponentType  * ParameterDataPrototype_TC97 with initValue = Ex:1  A SW-C with  * An RPortPrototype to receive ParameterDataPrototype_TC97  - connected to the ParameterSwComponentType  * A RunnableEntity to execute the test sequence  - with a parameterAccess which references ParameterDataPrototype_TC97		
Summary	A SW-C is connected to a ParameterSwComponentType. The test case checks that the value of the parameter can be accessed with the Rte_Prm API.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state		
Main Test Execu	Main Test Execution		
Test Steps	Pass Criteria		
Step 1	[SWC] Invoke Rte_Prm		[SWC] Rte_Prm returns the parameter's value (Ex: 1).
Post- conditions	NONE		

## 8.3.6 [ATS\_RTE\_00704] Rte\_CData API For sharedParameter

Test Objective	Rte_CData API For sharedParameter		
ID		AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed



Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01252 RTE: SWS_Rte_01300 RTE: SWS_Rte_03927		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with  * ParameterDataPrototype_TC98 in the role sharedParameter with initValue=Ex: 1  * A RunnableEntity to execute the test sequence  - with a parameterAccess which references ParameterDataPrototype_TC98		
Summary	A SW-C is configured with a ParameterDataPrototype in the role sharedParameter. The test case checks that the value for the parameter can be accessed with the Rte_CData API.		
Needed Adaptation to other Releases			
Pre-conditions	DUT shall be initialized EcuM module shall be in RUN state		
Main Test Execu	Main Test Execution		
Test Steps		Pass Criteria	
Step 1	[SWC] Invoke Rte_CData for the sharedParameter ParameterDataPrototype_TC98.	[SWC] Rte_CData returns the initValue of ParameterDataPrototype_TC98.	
Post- conditions	NONE		

# 8.3.7 [ATS\_RTE\_00705] Rte\_CData API For perInstanceParameter

Test Objective	Rte_CData API For perInstanceParameter		
ID	ATS_RTE_00705	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
Trace to SWS Item	RTE: SWS_Rte_01252 RTE: SWS_Rte_01300 RTE: SWS_Rte_03952		
Requirements / Reference to Test Environment			
Configuration Parameters	A SW-C with * ParameterDataPrototype_TC99 in the role perInstanceParameter with initValue=Ex: 1		



	* A RunnableEntity to execute the test sequence - with a parameterAccess which references ParameterDataPrototype_TC99	
	A SW-C is configured with a ParameterDataPrototype in the role perInstanceParameter.  The test case checks that the value for the parameter can be accessed with the Rte CData API.	
Needed Adaptation to other Releases		
	DUT shall be initialized EcuM module shall be in RUN state	
Main Test Execution		
Test Steps	st Steps Pass Criteria	
·	[SWC] Invoke Rte_CData for the perInstanceParameter ParameterDataPrototype_TC99	[SWC] Rte_CData returns the initValue of ParameterDataPrototype_TC99.
Post- conditions	NONE	•

# 8.3.8 [ATS\_RTE\_00706] Rte\_Pim API Functionality

Test Objective	Rte_Pim API Functionality		
ID	ATS_RTE_00706	AUTOSAR Releases	4.0.3 4.2.1 4.2.2
Affected Modules	RTE	State	reviewed
Trace to Requirement on Acceptance Test Document			
	RTE: SWS_Rte_01118 RTE: SWS_Rte_01119 RTE: SWS_Rte_01299		
Requirements / Reference to Test Environment			
Parameters	An ApplicationSwComponentType with  * attribute supportsMultipleInstantiation=TRUE  * VariableDataPrototype_TC100 in the role arTypedPerInstanceMemory with initValue=Ex: 1  * RunnableEntity_TC100 to execute the test sequence  This ApplicationSwComponentType is instantiated twice.		
	The test case checks that the Rte_Pim API provides access to different PerInstanceMemory in case an ApplicationSwComponentType is instantiated multiple times.		
Needed Adaptation to other Releases			
	DUT shall be initialized EcuM module shall be in RUN state		



Main Test Execution		
Test Steps		Pass Criteria
Step 1	[CP] Wait for the execution of RunnableEntity_TC100 for the first instance of the ApplicationSwComponentType.	[RUN <runnableentity_tc100>] RunnableEntity_TC100 is invoked.</runnableentity_tc100>
Step 2	[SWC] Invoke Rte_Pim_VariableDataPrototype_TC100 for the Rte_Instance received in step 1.	[RUN <runnableentity_tc100>] Rte_Pim returns the reference to a PerInstanceMemory!= NULL_PTR.</runnableentity_tc100>
Step 3	Wait for the execution of RunnableEntity_TC100 for the other instance	[RUN <runnableentity_tc100>] RunnableEntity_TC100 is invoked with a Rte_Instance argument that differ from the one in step 1.</runnableentity_tc100>
Step 4	the instance received in step 3.	[RUN <runnableentity_tc100>] Rte_Pim returns the reference to a PerInstanceMemory!= NULL_PTR that differs from the address returned by Rte_Pim in step 2.</runnableentity_tc100>
Post- conditions	NONE	