

<b>Document Title</b>	Requirements on Operating System Interface
<b>Document Owner</b>	AUTOSAR
<b>Document Responsibility</b>	AUTOSAR
<b>Document Identification No</b>	718

<b>Document Status</b>	Final
<b>Part of AUTOSAR Standard</b>	Adaptive Platform
<b>Part of Standard Release</b>	18-03

<b>Document Change History</b>			
<b>Date</b>	<b>Release</b>	<b>Changed by</b>	<b>Description</b>
2018-03-29	18-03	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Removed: RS_OSI_00101, RS_OSI_00200 and RS_OSI_00205.</li> <li>Added: [<a href="#">RS_OSI_00103</a>].</li> </ul>
2017-10-27	17-10	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Minor changes, document clean up</li> </ul>
2017-03-31	17-03	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Initial release</li> </ul>

## Disclaimer

This work (specification and/or software implementation) and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the work.

The material contained in this work is protected by copyright and other types of intellectual property rights. The commercial exploitation of the material contained in this work requires a license to such intellectual property rights.

This work may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the work may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The work has been developed for automotive applications only. It has neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

## Table of Contents

1	Scope of this document	4
1.1	Document Conventions . . . . .	5
2	Acronyms and Abbreviations	6
3	Constraints and assumptions	7
3.1	Limitations . . . . .	7
3.2	Applicability to car domains . . . . .	7
4	Functional overview	8
5	Requirements Tracing	9
6	Requirements specification	10
6.1	Assumption of Use . . . . .	10
6.2	General Requirements . . . . .	10
6.3	Operating System Functionality Requirements . . . . .	12
7	References	14

## 1 Scope of this document

This document specifies the requirements of Adaptive Platform on the Operating System that is part of the Foundation in the Adaptive Platform.

## 1.1 Document Conventions

The representation of requirements in AUTOSAR documents follows the table specified in [TPS\_STDT\_00078], see Standardization Template, chapter Support for Traceability ([1]).

The verbal forms for the expression of obligation specified in [TPS\_STDT\_00053] shall be used to indicate requirements, see Standardization Template, chapter Support for Traceability ([1]).

## 2 Acronyms and Abbreviations

There are no acronyms and abbreviations relevant within this document that are not included in the [2, AUTOSAR glossary].

## 3 Constraints and assumptions

### 3.1 Limitations

This chapter lists known limitations of `Operating System Interface` in terms of unimplemented requirements. The intent is to provide an indication how the requirement specification will evolve future releases.

The following requirements are described within this document but not otherwise considered in this release:

- [\[RS\\_OSI\\_00201\]](#)
- [\[RS\\_OSI\\_00202\]](#)
- [\[RS\\_OSI\\_00203\]](#)
- [\[RS\\_OSI\\_00204\]](#)

The functionality described above is subject to modification and will be considered for inclusion in a future release of this document.

### 3.2 Applicability to car domains

No restrictions to applicability.

## 4 Functional overview

The Operating System is responsible for run-time resource management (including time) for all Applications on and within the Adaptive Platform. This includes not only the Adaptive Applications that run on top of ARA provided by Adaptive Platform, but also the Functional Clusters that constitute the platform, which are also implemented as Applications. The OS functions in cooperation with Execution Management which is responsible for platform initialization and the start-up / shut-down of Applications.

Note that this Operating System Interface (OSI) requirement specification contains two different categories. The first category contains the requirements that are directly needed by the Adaptive Applications. The other category contains the ones that are needed by the Adaptive Platform to realize implementation of Functional Clusters, especially the required mechanisms are difficult or inefficient to be implemented by other software entity than the OS. The most notable such Functional Cluster requiring the various OS mechanisms is Execution Management.



## 5 Requirements Tracing

The following table references the features specified in [3] and links to the fulfillments of these.

Feature	Description	Satisfied by
[RS_Main_00002]	AUTOSAR shall provide a software platform for high performance computing platforms	<a href="#">[RS_OSI_00100]</a> <a href="#">[RS_OSI_00201]</a> <a href="#">[RS_OSI_00202]</a> <a href="#">[RS_OSI_00203]</a>
[RS_Main_00010]	AUTOSAR shall support the development of safety related systems.	<a href="#">[RS_OSI_00204]</a> <a href="#">[RS_OSI_00206]</a>
[RS_Main_00049]	AUTOSAR shall provide an Execution Management for running multiple applications	<a href="#">[RS_OSI_00105]</a> <a href="#">[RS_OSI_00206]</a>
[RS_Main_00050]	AUTOSAR shall provide an Execution Framework towards applications to implement concurrent application internal control flows.	<a href="#">[RS_OSI_00104]</a> <a href="#">[RS_OSI_00203]</a> <a href="#">[RS_OSI_00204]</a>
[RS_Main_00060]	AUTOSAR shall provide a standardized software interface for communication between Applications	<a href="#">[RS_OSI_00104]</a>
[RS_Main_00106]	AUTOSAR shall provide the possibility to extend the software with new SWCs without recompiling the platform foundation	<a href="#">[RS_OSI_00201]</a> <a href="#">[RS_OSI_00202]</a> <a href="#">[RS_OSI_00203]</a> <a href="#">[RS_OSI_00206]</a>
[RS_Main_00150]	AUTOSAR shall support the deployment and reallocation of AUTOSAR Application Software	<a href="#">[RS_OSI_00100]</a>
[RS_Main_00200]	AUTOSAR specifications shall allow resource efficient implementations	<a href="#">[RS_OSI_00201]</a> <a href="#">[RS_OSI_00202]</a> <a href="#">[RS_OSI_00203]</a>
[RS_Main_00340]	AUTOSAR shall support the continuous timing requirement analysis	<a href="#">[RS_OSI_00102]</a>
[RS_Main_00460]	AUTOSAR shall standardize methods to organize mode management on Application, ECU and System level	<a href="#">[RS_OSI_00104]</a> <a href="#">[RS_OSI_00105]</a>
[RS_Main_00513]	AUTOSAR shall support language bindings for different programming languages	<a href="#">[RS_OSI_00103]</a>

## 6 Requirements specification

This chapter describes all requirements driving the work to define the Operating Systems functionality.

### 6.1 Assumption of Use

This section describes Application use cases that will run on the Adaptive Platform. These use cases are not requirements to the Adaptive Platform in the strict sense, but rather assumptions on properties of Application running on the Adaptive Platform. These assumptions are used to motivate the further requirements, and provide hints for Application developers to check if their use cases are covered in this specification document and which specific requirements are derived from those use cases.

The Operating System section defines requirements on the Operating System that Applications can consider fulfilled in order to achieve their function.

### 6.2 General Requirements

**[RS\_OSI\_00100] The Operating System Interface provided to Applications shall provide a PSE51-compliant API.** [

<b>Type:</b>	draft
<b>Description:</b>	The foundation of the Operating System provided to the Application shall be POSIX-compliant as defined by PSE51.
<b>Rationale:</b>	The defined functionality of the POSIX profile PSE51 defined by IEEE1003.13 [4] is provided by various off-the-shelf operating systems. The PSE51 profile is intended for embedded systems, with a single multi-threaded process, no file system, no user and group support and only selected options from more general IEEE1003.1 [5], which is the well-known POSIX standard. PSE51 offers functions for basic synchronized I/O, high-resolution timer, signals, semaphores, shared memory and threads. As the envisioned Application software components will not require to fork new processes themselves, and only need limited direct access to files, the PSE51 profile is thought to be sufficient.
<b>Dependencies:</b>	–
<b>Use Case:</b>	Application portability.
<b>Supporting Material:</b>	IEEE1003.13 [4] and IEEE1003.1 [5]

] ([RS\\_Main\\_00002](#), [RS\\_Main\\_00150](#))

**[RS\_OSI\_00102] The Operating System Interface shall support time-triggered execution.** [

<b>Type:</b>	draft
--------------	-------

<b>Description:</b>	The Operating System shall facilitate time-triggered Application execution.
<b>Rationale:</b>	Application can be time-triggered. The OS needs to provide mechanisms to allow the time-triggered execution of applications. The triggers, need to contain at least external timers, but not limited to.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

](RS\_Main\_00340)

**[RS\_OSI\_00103] The Operating System Interface shall support C++ [**

<b>Type:</b>	draft
<b>Description:</b>	The Operating System interface shall support C++/11.
<b>Rationale:</b>	Application are written in C++ and interfaces are expected to conform to C++/11. Note that the POSIX API consists of C functions which can be invoked from a C++ program.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

](RS\_Main\_00513)

**[RS\_OSI\_00104] The Operating System Interface shall support the reaction on Application-external stimuli from devices. [**

<b>Type:</b>	draft
<b>Description:</b>	The Operating System shall enable Application to react on external stimuli from devices.
<b>Rationale:</b>	Application will react on reception of functional data, signals and timers from the platform. Certain computations shall be executed in reaction on these application-external stimuli.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

](RS\_Main\_00050, RS\_Main\_00060, RS\_Main\_00460)

**[RS\_OSI\_00105] The Operating System Interface shall support the start of Execution Management. [**

<b>Type:</b>	draft
<b>Description:</b>	The Operating System shall provide means to start the Execution Management functional cluster as first process.
<b>Rationale:</b>	Execution Management is responsible for startup and shutdown of all Applications of the Adaptive Platform.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–

<b>Supporting Material:</b>	–
-----------------------------	---

|(RS\_Main\_00049, RS\_Main\_00460)

### 6.3 Operating System Functionality Requirements

**[RS\_OSI\_00201] The Operating System shall provide mechanisms for system memory budgeting.** [

<b>Type:</b>	draft
<b>Description:</b>	The Operating System shall provide mechanisms to configure memory budgeting for each Application or for groups of Applications.
<b>Rationale:</b>	In order to ensure resource availability in the context of multithreaded application, the system integrator/architect may require a set of tools to configure memory budgeting for each Application or for groups of Applications.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

|(RS\_Main\_00002, RS\_Main\_00106, RS\_Main\_00200)

**[RS\_OSI\_00202] The Operating System shall provide mechanisms for CPU time budgeting.** [

<b>Type:</b>	draft
<b>Description:</b>	The Operating System shall provide mechanisms to configure resource budgeting in terms of CPU time for each Application or group of Applications.
<b>Rationale:</b>	In order to ensure schedulability in the context of multithreaded application, the system integrator/architect may require a set of tools to configure CPU time allocated for each Application or for groups of Applications.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

|(RS\_Main\_00002, RS\_Main\_00106, RS\_Main\_00200)

**[RS\_OSI\_00203] The Operating System should provide mechanisms for binding processes to CPU cores.** [

<b>Type:</b>	draft
<b>Description:</b>	The Operating System should provide mechanisms for binding individual processes or groups of processes to CPU cores.
<b>Rationale:</b>	In order to ensure correct task schedulability, the system integrator may require a set of tools to configure the CPU affinity.
<b>Dependencies:</b>	–

<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

]([RS\\_Main\\_00002](#), [RS\\_Main\\_00050](#), [RS\\_Main\\_00106](#), [RS\\_Main\\_00200](#))

**[RS\_OSI\_00204] The Operating System shall support authorized operating system object access for the software entities which are allowed to do so.** [

<b>Type:</b>	draft
<b>Description:</b>	The Operating System shall provide access rights and permissions mechanisms to achieve secure data access and data exchange.
<b>Rationale:</b>	The Operating System consists of a collection of hardware and software objects, e.g. pipes, files. Safety or/and Security related requirements may be imposed to grant special access rights and permissions in order to avoid unauthorized access to communication channels or to ensure exclusive access to the Application specific data stored persistently.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

]([RS\\_Main\\_00010](#), [RS\\_Main\\_00050](#))

**[RS\_OSI\_00206] The Operating System shall provide multi-process support for isolation of applications.** [

<b>Type:</b>	draft
<b>Description:</b>	The Operating System shall provide mechanisms to let multiple Applications run isolated from each other.
<b>Rationale:</b>	Each process that participates in an Application may have a different robustness, safety and security level. As a consequence, an incorrect memory access from one Application execution shall not result in a corruption of memory in another Application, unless the data area is explicitly shared. In addition, a process may not access or read data from another process without explicit data sharing.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

]([RS\\_Main\\_00010](#), [RS\\_Main\\_00049](#), [RS\\_Main\\_00106](#))

## 7 References

- [1] Standardization Template  
AUTOSAR\_TPS\_StandardizationTemplate
- [2] Glossary  
AUTOSAR\_TR\_Glossary
- [3] Main Requirements  
AUTOSAR\_RS\_Main
- [4] IEEE Standard for Information Technology- Standardized Application Environment Profile (AEP)-POSIX Realtime and Embedded Application Support  
<https://standards.ieee.org/findstds/standard/1003.13-2003.html>
- [5] Standard for Information Technology–Portable Operating System Interface (POSIX(R)) Base Specifications, Issue 7  
<http://pubs.opengroup.org/onlinepubs/9699919799/>
- [6] Requirements on Execution Management  
AUTOSAR\_RS\_ExecutionManagement
- [7] Requirements on Communication Management  
AUTOSAR\_RS\_CommunicationManagement