

Document Title	Requirements on Diagnostics
Document Owner	AUTOSAR
Document Responsibility	AUTOSAR
Document Identification No	004

Document Status	Final
Part of AUTOSAR Standard	Foundation
Part of Standard Release	1.5.0

Document Change History			
Date	Release	Changed by	Description
2018-10-31	1.5.0	AUTOSAR Release Management	<ul style="list-style-type: none"> • New requirements for CP and AP • Structural optimization of document
2018-03-29	1.4.0	AUTOSAR Release Management	<ul style="list-style-type: none"> • New requirements for CP and AP • Structural optimization of document
2017-12-08	1.3.0	AUTOSAR Release Management	<ul style="list-style-type: none"> • Minor corrections • Update of requirements tracing
2017-10-27	1.2.0	AUTOSAR Release Management	<ul style="list-style-type: none"> • Restructured document • New requirements for CP and AP • Common requirements for CP and AP
2017-03-31	1.1.0	AUTOSAR Release Management	<ul style="list-style-type: none"> • Merge and alignment with AP requirements • Restructured chapter 4 • Removed reference to HIS
2016-11-30	1.0.0	AUTOSAR Release Management	<ul style="list-style-type: none"> • –Migration of document to standard "Foundation"– • Additional requirements for ISO14229-1 conformance • Parallel access for DEM • Parallel processing of OBD and UDS services • Independent fault memory access for virtual ECUs

2015-07-31	4.2.2	AUTOSAR Release Management	<ul style="list-style-type: none"> • Clarification of bootloader interaction • Interfaces for DCM communication via PDU router • Rework of document structure
2014-10-31	4.2.1	AUTOSAR Release Management	<ul style="list-style-type: none"> • Support of WWH-OBd (Major change) • Support of UDS service \$38 ("RequestFileTransfer"), (Change) • Added new requirements for runtime errors and transient errors (Change) • Aging of events (Change)
2014-03-31	4.1.3	AUTOSAR Release Management	<ul style="list-style-type: none"> • New requirement for processing a new request in DEM • New requirement for event management mechanisms in DEM
2013-03-15	4.1.1	AUTOSAR Release Management	<ul style="list-style-type: none"> • OBd-specific configuration capabilities in DCM and DEM • Event de-bouncing in DEM • Freeze Frame and Extended Data Record handling in DEM • Support of SAE J1939 • Link Requirement with BSW Feature Document • Updating format of requirements according to TPS_StandardizationTemplate
2011-12-22	4.0.3	AUTOSAR Release Management	<ul style="list-style-type: none"> • Clarification of DET functionality • Formal Rework for Requirements Tracing
2011-04-15	4.0.2	AUTOSAR Release Management	<ul style="list-style-type: none"> • Clarification of DET functionality (remove BSW04088)
2010-09-30	3.1.5	AUTOSAR Release Management	<ul style="list-style-type: none"> • Document structure reworked and extended • Improvement of DEM behavior description • Introduce the approach for functional diagnostics of SW-Cs • Added requirements for further diagnostic modules (DLT/DET) • Legal disclaimer revised

2008-08-13	3.1.1	AUTOSAR Release Management	<ul style="list-style-type: none"> • Remove requirement BSW04062 • Added requirement [SRS_Diag_04082] for OBDII support • Legal disclaimer revised
2007-12-21	3.0.1	AUTOSAR Release Management	<ul style="list-style-type: none"> • Document meta information extended • Small layout adaptations made
2007-01-24	2.1.15	AUTOSAR Release Management	<ul style="list-style-type: none"> • "Advice for users" revised • "Revision Information" added
2006-11-28	2.1	AUTOSAR Release Management	<ul style="list-style-type: none"> • Legal Disclaimer revised
2006-05-16	2.0	AUTOSAR Release Management	<ul style="list-style-type: none"> • Minor formal changes
2005-05-31	1.0	AUTOSAR Release Management	<ul style="list-style-type: none"> • Initial Release

Disclaimer

This work (specification and/or software implementation) and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the work.

The material contained in this work is protected by copyright and other types of intellectual property rights. The commercial exploitation of the material contained in this work requires a license to such intellectual property rights.

This work may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the work may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The work has been developed for automotive applications only. It has neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

Table of Contents

1	Scope of the Document	11
2	Acronyms and Abbreviations	11
3	Conventions to be used	12
4	Requirements Specification	13
4.1	Common Diagnostic requirements for Classic and Adaptive Platform	13
	[SRS_Diag_04200] Support event combination	13
	[SRS_Diag_04150] Support the primary fault memory defined by ISO 14229-1	13
	[SRS_Diag_04214] Support the user defined fault memories defined by ISO 14229-1	14
	[SRS_Diag_04068] The diagnostic in AUTOSAR shall support event specific debounce counters to improve signal quality internally (According to ISO 14229-1 Appendix D)	14
	[SRS_Diag_04225] The diagnostic in AUTOSAR shall support event specific time base debounce counters	15
	[SRS_Diag_04115] The optional parameter DTCSettingControlOption-Record as part of UDS service ControlDTCSetting shall be limited to GroupOfDTC	15
	[SRS_Diag_04164] Independent event memories for multiple diagnostic server instances (virtual ECUs)	16
	[SRS_Diag_04064] Provide configurable buffer sizes for storage of the events, status information and environmental data	16
	[SRS_Diag_04172] Inform external service processors about outcome of the final response	17
	[SRS_Diag_04127] Configurable record numbers and trigger options for DTCSnapshotRecords and DTCExtendedDataRecords	17
	[SRS_Diag_04177] Custom diagnostic services	17
	[SRS_Diag_04059] Configuration of timing parameters	18
	[SRS_Diag_04033] Support the upload/download services for reading/writing data in an ECU in an extended and manufacturer specific diagnostic session	18
	[SRS_Diag_04020] Suppress responses to diagnostic tool requests	19
	[SRS_Diag_04119] Handle the execution of diagnostic services according to the assigned diagnostic session	19
	[SRS_Diag_04016] Support "Busy handling" by sending a negative response 0x78	20
	[SRS_Diag_04006] Manage session handling	20
	[SRS_Diag_04005] Manage Security Access level handling	20
	[SRS_Diag_04135] Support UDS service \$38 (RequestFileTransfer)	21
	[SRS_Diag_04100] Interface for logging and tracing	21
	[SRS_Diag_04098] Interact with standard bootloader	22

[SRS_Diag_04159] Control of DTC storage	22
[SRS_Diag_04157] Reporting of DTCs and related data	23
[SRS_Diag_04156] Support DTCFunctionalUnit	23
[SRS_Diag_04077] Uses standard mechanisms provided by persistency modules	23
[SRS_Diag_04131] Consistent event management mechanisms	24
[SRS_Diag_04117] Configurable behavior for DTC deletion	24
[SRS_Diag_04107] Provide defensive behavior	24
[SRS_Diag_04105] Event memory management	25
[SRS_Diag_04091] Notification about valid freeze frame data to applica- tions	25
[SRS_Diag_04151] Event status handling	26
[SRS_Diag_04071] Process events according to their defined impor- tance like priority and/or severity	26
[SRS_Diag_04125] Event debounce counter shall be configurable	26
[SRS_Diag_04136] Configurable "confirmed" threshold	27
[SRS_Diag_04140] Aging for UDS status bits "confirmedDTC" and "test- FailedSinceLastClear"	27
[SRS_Diag_04141] Ability to synchronize the event data capturing with the reported event	28
[SRS_Diag_04230] Support of UDS service 0x29 (Authentication)	28
[SRS_Diag_04231] Supported client certificates	29
[SRS_Diag_04232] Access rights in client certificates	29
[SRS_Diag_04233] Access granularity of diagnostic services	30
[SRS_Diag_04234] Binary compatibility of white list for individual access	30
[SRS_Diag_04235] Client certificate validity	31
[SRS_Diag_04236] Client certificate target identification	31
[SRS_Diag_04237] Client certificate evaluation	31
[SRS_Diag_04238] Logging certificate evaluation	32
[SRS_Diag_04239] Diagnostic services in deauthenticated state	32
[SRS_Diag_04240] Application based authentication	33
[SRS_Diag_04133] Aging for event memory entries	33
[SRS_Diag_04063] Process a dedicated event identifier for each mon- itoring path to support an autonomous handling of different events/faults	33
[SRS_Diag_04148] Provide capabilities to inform applications about di- agnostic data changes	34
[SRS_Diag_04097] Decentralized and modular diagnostic configuration in applications	34
[SRS_Diag_04067] Provide the diagnostic status information according to ISO 14229-1	35
[SRS_Diag_04179] Provide interfaces for monitoring application.	35
[SRS_Diag_04178] Support operation cycles according to ISO 14229-1	36
[SRS_Diag_04201] Support a configuration to assign specific events to a customer specific DTC	36

[SRS_Diag_04180] Process all UDS Services related to diagnostic fault memory of ISO 14229-1 internally	36
[SRS_Diag_04182] Provide an application interface to change operation cycles states	37
[SRS_Diag_04183] Notify interested parties about event status changes	37
[SRS_Diag_04185] Notify applications about the clearing of an event . .	37
[SRS_Diag_04186] Notify applications about the start or restart of an operation cycle	38
[SRS_Diag_04204] Provide the current status of each warning indicator.	38
[SRS_Diag_04202] Report DTCs getting active to the error logging module/system	38
[SRS_Diag_04205] Support of SnapshotRecords	39
[SRS_Diag_04206] Support of ExtendedDataRecords	39
[SRS_Diag_04189] Support a fine grained configuration for SnapshotRecords and ExtendedDataRecords	40
[SRS_Diag_04190] Usage of internal data elements in SnapshotRecords and ExtendedDataRecords	40
[SRS_Diag_04192] Provide the ability to handle event specific enable conditions	41
[SRS_Diag_04219] Provide the ability to handle event specific storage conditions	41
[SRS_Diag_04194] ClearDTC shall be accessible for applications . . .	41
[SRS_Diag_04195] Chronological reporting order of the DTCs located in the configured event memory	42
[SRS_Diag_04211] Persistent storage of DTC status and environmental data	42
[SRS_Diag_04196] UDS Service handling for all diagnostic services defined in ISO 14229-2	42
[SRS_Diag_04203] Common checks on all supported UDS Services Requests	43
[SRS_Diag_04226] Diagnostic session check	43
[SRS_Diag_04227] Common check for Security Access	44
[SRS_Diag_04228] Common check for Message lengths	44
[SRS_Diag_04197] Clearing the user defined fault memory	44
[SRS_Diag_04198] Process all UDS Services related to session and security management of ISO 14229 internally	45
[SRS_Diag_04199] Provide a configurable UDS service execution mechanism at runtime to decide if a UDS request shall be processed or not	45
[SRS_Diag_04208] Inform the application about diagnostic session and diagnostic security level changes on each tester connection.	46
[SRS_Diag_04218] Support of UDS service 0x2F InputOutputControl-ByIdentifier	46
[SRS_Diag_04222] Independence of clearing DTC status and system degradation	46

	[SRS_Diag_04224] Support the UDS service 0x31 (RoutineControl) according to ISO 14229-1	47
4.2	Diagnostic requirements for the Classic Platform	47
4.2.1	Functional Requirements	47
	[SRS_Diag_04213] Support the mirror fault memory defined by ISO 14229-1	47
	[SRS_Diag_04112] The DEM module shall support DTCs according to SAE J1939	48
	[SRS_Diag_04139] Support subfunction 0x42 of UDS service 0x19	48
	[SRS_Diag_04129] Provide OBD-specific configuration capabilities	48
	[SRS_Diag_04163] Parallel OBD and UDS processing	49
	[SRS_Diag_04161] Provide support for the ASMIP algorithm	49
4.2.2	Fault Memory Management	50
	[SRS_Diag_04002] The Diagnostic event (fault) management shall be established as Basic SW Module	50
	[SRS_Diag_04057] Classification of events for series production, OBD and expert usage	50
	[SRS_Diag_04124] Store the current debounce counter value non-volatile to over a powerdown cycle	51
	[SRS_Diag_04118] Optionally support event displacement	51
	[SRS_Diag_04123] Harmonized Driving/WarmUp cycles	52
	[SRS_Diag_04093] Memory overflow indication	52
	[SRS_Diag_04109] Provide an interface to retrieve the number of event memory entries	53
	[SRS_Diag_04126] Configurable suppression of events	53
	[SRS_Diag_04110] SAE J1939 lamp status	54
	[SRS_Diag_04111] SAE J1939 Expanded-FreezeFrame	54
	[SRS_Diag_04113] Support a set of SAE J1939 DM-messages	54
	[SRS_Diag_04137] Definition of replacement failure	55
	[SRS_Diag_04155] Notify applications and BSW modules about updates of event related data	56
	[SRS_Diag_04160] ResponseOnEvent according to ISO 14229-1	56
	[SRS_Diag_04215] Support of UDS service ReadDataByPeriodicIdentifier (0x2A)	56
	[SRS_Diag_04217] Adding the Lamp status pertinent to a specific Fault Event/DTC available as DemInternalDataClass shall be codified in the same format of DM31	57
	[SRS_Diag_04165] Triggering of multiple events upon a master event is reported	57
	[SRS_Diag_04031] Notify the Function Inhibition Manager (FIM) upon changes of the event status in order to process them according to the SW components dependencies	58
	[SRS_Diag_04220] Support DTCs suppression	58

	[SRS_Diag_04221] In-Use-Monitor Performance Ratio indicates how often the OBD system monitors particular components, compared to the amount of the vehicle operation	58
	[SRS_Diag_04223] Support Snapshot Records data pre-storage	59
4.2.2.1	DTC and event-related data	59
	[SRS_Diag_04162] Parallel fault memory access	59
4.2.3	Diagnostic Communication	60
	[SRS_Diag_04007] Provide a diagnostic service handling for the applications involved in diagnostic functionality	60
	[SRS_Diag_04021] Handling of different diagnostic sessions in parallel	60
	[SRS_Diag_04032] Different diagnostic addresses shall be supported by multiple (physical) channels	61
	[SRS_Diag_04058] Ability to access different event memories	61
	[SRS_Diag_04024] Access and handle specific data elements and data element groups if requested by an external scan tool	61
	[SRS_Diag_04015] Timing handling according to ISO15765-3	62
	[SRS_Diag_04019] Provide confirmation after transmit diagnostic responses to the application	62
	[SRS_Diag_04120] Support a predefined AddressAndLengthFormatIdentifier	63
	[SRS_Diag_04121] Provide the handling of service Dynamically-DefineDataIdentifier according to ISO 14229-1	63
	[SRS_Diag_04153] Support generic connections	63
	[SRS_Diag_04011] Provide diagnostic state information to applications	64
	[SRS_Diag_04003] Network independent design	64
	[SRS_Diag_04147] Communication with the transport layers to receive and send diagnostic data	65
4.2.4	Function Inhibition Manager (FIM)	65
4.3	Diagnostic requirements for the Adaptive Platform	65
	[SRS_Diag_04166] Several tester conversations in parallel with assigned priorities	65
	[SRS_Diag_04209] Pseudo parallel client interaction according to ISO	66
	[SRS_Diag_04210] Fully parallel client interaction	66
	[SRS_Diag_04167] Conversation preemption/abortion	66
	[SRS_Diag_04168] Adding of user-defined transport layers	67
	[SRS_Diag_04169] Provide an interface for external UDS service processors.	67
	[SRS_Diag_04170] Provide connection specific meta information to external service processors	68
	[SRS_Diag_04171] Synchronous and asynchronous interaction with external service processors	68

[SRS_Diag_04173] Different signature types, when delegating processing of UDS service to the application	69
[SRS_Diag_04174] Provide SA and TA to external service processors	69
[SRS_Diag_04216] Support for multiple Diagnostic Server Instances	69
4.4 Configuration	70
5 Requirements Tracing	70
6 References	72
6.1 Deliverables of AUTOSAR	72
6.2 Related standards and norms	72
6.2.1 ITEA-EAST	72
6.2.2 ISO	73

1 Scope of the Document

This document specifies system requirements of AUTOSAR Diagnostic. It is meant to be independent of any particular implementation and it contains foundation requirements, common to AUTOSAR Classic and Adaptive Platform, as well as requirements specific to Classic Platform and Adaptive Platform.

In the Classic Platform chapter the handling of the legislated OBD and enhanced Diagnostics shall be achieved. As far as possible the set of diagnostic basic software elements should consist of already existing elements of modules of automotive software. Only in case of good reasons valid elements of basic software should be part of the set. If such the definition of these valid elements is not part of this work package. Nevertheless the information about basic software elements additionally required shall be given to related work groups.

In the Adaptive Platform chapter, some constraints should be notify related to the Adaptive environment: - only support for Ethernet as physical communication infrastructure will be provided, and no other typical bus communication is planned for release 1.0; on these grounds, all classical SRS Diagnostics requirements referring to standards (i.e. J1939) considering other bus protocols (i.e. FlexRay, CAN ..) were not considered in this specification

- due to insufficient information about the car domains where the AUTOSAR Adaptive Platform will apply, OBD protocol (standardized as ISO 15031) is also not subject of this specification

- Release 1.0 of AUTOSAR Adaptive Platform is planned to be a learning environment for future development as a consequence its interfaces are described with ICC1 (Interface Conformance Class) granularity level, meaning that no internal DM interfaces are to be specified

2 Acronyms and Abbreviations

Abbreviation / Acronym:	Description:
CAN	Controller Area Network (communication bus)
Dem	Diagnostic Event Manager
DID	Diagnostic Identifier
DM	Diagnostic Management
DoIP	Diagnostic over IP - transport protocol for diagnostic services standardized as ISO 13400

DTC	Diagnostic Trouble Code
ECU	Electronic Control Unit
IDL	Interface Description Language
OBD	On-board Diagnostic (standardized as ISO 15031)
RTE	Runtime Environment
SA	Source Address (diagnostics address of the tester)
SID	Service Identifier (hexa number to uniquely identify UDS services) 0x22 for Read Data by Identifier service 0x2E for Write to Non-Volatile memory service
SWC	Software Component (could refer either to Classic Platform SW-C or to Adaptive Platform SW-C)
TA	Target Address (diagnostic address of the ECU)
UDS	Unified Diagnostic Specification standardized as ISO 14229

Table 2.1: table:acronyms

3 Conventions to be used

In requirements, the following specific semantics are used :

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY" and "OPTIONAL" in this document are to be interpreted . Note that the requirement level of the document in which they are used modifies the force of these words.

- **SHALL:** This word means that the definition is an absolute requirement of the specification.
- **SHALL NOT:** This phrase means that the definition is an absolute prohibition of the specification.
- **MUST:** This word, or the terms "REQUIRED" or "SHALL", mean that the definition is an absolute requirement of the specification.
- **MUST NOT:** This phrase, or the phrase "SHALL NOT", means that the definition is an absolute prohibition of the specification.
- **SHOULD:** This word, or the adjective "RECOMMENDED", mean that there may exist valid reasons in particular circumstances to ignore a particular item, but the

full implications must be understood and carefully weighed before choosing a different course.

- **SHOULD NOT:** This phrase, or the phrase "NOT RECOMMENDED" mean that there may exist valid reasons in particular circumstances when the particular behavior is acceptable or even useful, but the full implications should be understood and the case carefully weighed before implementing any behavior described with this label.
- **MAY:** This word, or the adjective "OPTIONAL", means that an item is truly optional. One vendor may choose to include the item because a particular market-place requires it or because the vendor feels that it enhances the product while another vendor may omit the same item. An implementation, which does not include a particular option, **MUST** be prepared to inter operate with another implementation, which does include the option, though perhaps with reduced functionality. In the same vein an implementation, which does include a particular option, **MUST** be prepared to inter operate with another implementation, which does not include the option (except, of course, for the feature the option provides).

4 Requirements Specification

4.1 Common Diagnostic requirements for Classic and Adaptive Platform

[SRS_Diag_04200] Support event combination [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall allow combining several individual events to trigger a single DTC.
Rationale:	Advanced fault analysis
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	Improved clustering and judging of events/faults. Several internal hardware faults of an electronic control unit can be mapped onto a single "ECU internal" failure to reduce the number of Diagnostic Trouble Codes shown to the technician in the service workshop.

](RS_Main_00260)

[SRS_Diag_04150] Support the primary fault memory defined by ISO 14229-1 [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support the primary fault memory defined by ISO 14229-1.
Rationale:	Storage of fault information for workshops.
AppliesTo:	CP, AP
Dependencies:	Production line, garage after reparation,...
Use Case:	The primary fault memory is used to store fault information that is related to defects in the vehicle and helps the workshops to identify the fault and repair it.
Supporting Material:	–

](RS_Main_00260)

[SRS_Diag_04214] Support the user defined fault memories defined by ISO 14229-1 [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support the user defined fault memories defined by ISO 14229-1.
Rationale:	Independent storage of fault information.
Use Case:	User defined fault memories are used by OEM and Tier1 during development or for storing warranty relevant information inside. This information is not relevant for workshops or repairing the vehicle.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	ISO 14229-1 v.2013

](RS_Main_00260)

[SRS_Diag_04068] The diagnostic in AUTOSAR shall support event specific debounce counters to improve signal quality internally (According to ISO 14229-1 Appendix D) [

Type:	Valid
Description:	The following types of debounce mechanisms shall be supported: The diagnostic in AUTOSAR module shall provide the ability to configure the jump behavior including jump up and jump down threshold value of the debounce counter in case of pre-passed or pre-failed event reporting. If failure detection jitters (e.g. sporadically reported pre-passed events), failure detection must not be delayed or prevented. The provision of jumping behavior of the debounce counter shall ensure the failure detection time because debouncing always starts from a defined starting point. This type of counters can be managed either internally or externally.





Rationale:	Advanced fault analysis
Use Case:	All applications and system modules can report events. The diagnostic module processes all these events and is able to provide a central de-bounce behavior for event classification and status management.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00260](#), [RS_Main_00420](#))

[SRS_Diag_04225] The diagnostic in AUTOSAR shall support event specific time base debounce counters [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support event specific time base debounce counters. The time based debouncing use a configurable time instead of counter threshold. The time is reloaded and running after the last monitor result/event status is different to the previous. After the time is exceeded the event has qualified. This type of counters can be managed either internally or externally.
Rationale:	Advanced fault analysis
Use Case:	All applications and system modules can report events. The diagnostic module processes all these events and is able to provide a central de-bounce behavior for event classification and status management.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00260](#), [RS_Main_00420](#))

[SRS_Diag_04115] The optional parameter DTCSettingControlOptionRecord as part of UDS service ControlDTCSetting shall be limited to GroupOfDTC [

Type:	Valid
Description:	ISO14229-1 does not specify how the parameter DTCSettingControlOptionRecord needs to be used. Therefore, the usage of the parameter shall be limited to GroupOfDTC.
Rationale:	Currently, no other use case for parameter DTCSettingControlOptionRecord is known than the usage for GroupOfDTC.
Use Case:	Fault storage is activated and deactivated for one specific DTC or for all DTCs.
AppliesTo:	CP, AP





Dependencies:	–
Supporting Material:	ISO14229-1 v.2013

](RS_Main_00260)

[SRS_Diag_04164] Independent event memories for multiple diagnostic server instances (virtual ECUs) [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide multiple sets of independent event memories that can store information independently from each other.
Rationale:	Individual assignment of fault memories to dedicated diagnostic servers.
Use Case:	ECUs with multiple independent diagnostic servers. Common faults of the host ECU shall be stored in each of the virtual ECU which is affected by such a fault. Common faults need to be stored in each virtual ECU to ensure that storing and clearing of fault entries has no or little side-effects with the information stored in other virtual ECUs. This use-case assumes that the cost to store a common fault in multiple event memory entries is accepted because sharing of a single event memory entry may have unintended side-effects.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

](RS_Main_00260)

[SRS_Diag_04064] Provide configurable buffer sizes for storage of the events, status information and environmental data [

Type:	Valid
Description:	Diagnostic in AUTOSAR shall provide configurable buffer sizes to store events, status information and environmental data. Due to resource limitation, only a few of the possible event related data is stored in the ECU. The system designer shall be able to dedicate an amount of non-volatile memory to be used for fault memory storage.
Rationale:	Storage of all event related data is not feasible due to the amount of required memory. This configurable buffer sizes allow to dedicate memory independent from the number of events or event related data size.
Use Case:	In case of large systems with many events a selection of events shall take place to fulfill NVRAM / RAM constraints of smaller processors.
AppliesTo:	CP, AP
Dependencies:	–





Supporting Material:	
-----------------------------	--

]([RS_Main_00011](#))

[SRS_Diag_04172] Inform external service processors about outcome of the final response [

Type:	Valid
Description:	For each UDS service which diagnostic in AUTOSAR delegates to a application for processing, it shall inform the application, whether a response has been successfully sent out or not.
Rationale:	For long running service processing, which delegate the processing to separate threads, the asynchronous callback model is more efficient, while for simple service processors the strict synchronous model is easier to implement.
AppliesTo:	CP, AP
Dependencies:	SRS_Diag_04169
Use Case:	Flexibility for service processor implementations.

]([RS_Main_00260](#), [RS_Main_00420](#))

[SRS_Diag_04127] Configurable record numbers and trigger options for DTC-SnapshotRecords and DTCExtendedDataRecords [

Type:	Valid
Description:	The diagnostic in AUTOSAR module shall provide the capability to configure record numbers and trigger options for the storage of DTCSnapshotRecords and DTCExtendedDataRecords.
Rationale:	Advanced fault analysis
Use Case:	Flexible handling of DTCSnapshotRecords and DTCExtendedDataRecords
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00260](#))

[SRS_Diag_04177] Custom diagnostic services [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support the configuration of custom diagnostic services.
Rationale:	In some cases diagnostic services beyond the set of services standardized in ISO 14229-1 are needed.
AppliesTo:	CP, AP
Dependencies:	RS_DEXT_00047
Use Case:	Most of the services that are in ISO 14229-1 and are also specified by AUTOSAR. Modifying the existing services behavior or adding customized behavior to existing services (e.g. not having session P2 timing values in the positive response to diagnostic session control or adding specific services such as "data log" services).

]([RS_Main_00260](#))

[SRS_Diag_04059] Configuration of timing parameters [

Type:	Valid
Description:	Every physical layer requires specific timing parameter values therefore it is necessary to include the ability to configure the timing constraints depending on the used network. The timing parameters are set to default values when a communication starts and shall be changeable at runtime.
Rationale:	Usability with different networks.
Use Case:	The diagnostic communication can be done at different networks (e.g. CAN/LIN/FlexRay/Ethernet).
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	

]([RS_Main_00011](#), [RS_Main_00260](#))

[SRS_Diag_04033] Support the upload/download services for reading/writing data in an ECU in an extended and manufacturer specific diagnostic session [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support the UDS services RequestDownload, RequestUpload, TransferData, RequestTransferExit (0x34-0x37) according to ISO 14229-1:2013. Note that in the Classic Platform these services are usually also implemented inside the bootloader which is out of scope of this requirement.
Rationale:	Provide means to upload and download data blocks.



△

Use Case:	Downloading configuration or application data during end of line or development. Another use case is uploading data blocks from the ECU for evaluation or verification purposes.
AppliesTo:	CP, AP
Dependencies:	
Supporting Material:	ISO14229-1 v.2013

](RS_Main_00011)

[SRS_Diag_04020] Suppress responses to diagnostic tool requests [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support the suppressPosRspMsgIndicationBit and the defined behavior according to ISO 14229-1:2013.
Rationale:	The tester is not interested in the positive response in certain situations. It prevents bus burst as result of a functional request.
Use Case:	In most cases, the positive responses are not relevant for functional requests to set the vehicle in a certain state. This can be a sequence of service 0x85, 0x28 and functional 0x3E during reprogramming to keep the vehicle in a 'silent' state without normal bus communication and DTC setting switched off.
AppliesTo:	CP, AP
Dependencies:	
Supporting Material:	ISO14229-1 v.2013

](RS_Main_00011)

[SRS_Diag_04119] Handle the execution of diagnostic services according to the assigned diagnostic session [

Type:	Valid
Description:	If a diagnostic session transition occurs (initiated by UDS Service 0x10), the diagnostic in AUTOSAR shall only maintain active diagnostic functionality if supported in the new session and if not prohibited by security access.
Rationale:	No interruption of diagnostic functionality
Use Case:	Deactivation of fault management and normal communication during ECU reprogramming
AppliesTo:	CP, AP
Dependencies:	
Supporting Material:	ISO14229-1 v.2013

](RS_Main_00011)

[SRS_Diag_04016] Support "Busy handling" by sending a negative response 0x78 [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide the sending of the negative response 0x78 in order get more time to build up the final positive or negative response.
Rationale:	Ensure a steady and save communication link and guarantee specified timing conditions.
Use Case:	When an application cannot provide the response in the protocol specific time
AppliesTo:	CP, AP
Dependencies:	
Supporting Material:	ISO14229-1 v.2013

]([RS_Main_00011](#))

[SRS_Diag_04006] Manage session handling [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support the transition from a default session to any other session, also back to the default session. (A diagnostic session enables a specific set of diagnostic services and/or functionality).
Rationale:	Some diagnostic services are not available in the default session. Therefore it is necessary to have information about the current session and no service which is connected to a non default session will be processed in the default session.
Use Case:	Special services need a different session than the default session, e.g. Reduction of communication traffic on the network in order to get more performance for the flash programming.
AppliesTo:	CP, AP
Dependencies:	[SRS_Diag_04005] SecurityAccess level handling
Supporting Material:	–

]([RS_Main_00011](#))

[SRS_Diag_04005] Manage Security Access level handling [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall manage the handling of the UDS-service 0x27 (SecurityAccess) and also the Security level handling. The accessibility of the services (service identifier) in the actual security level shall be checked.
Rationale:	Some diagnostic services are in dependence to a security access level. Therefore it is necessary to have information about the current level and no service which is restricted by security will be processed without authorization.





Use Case:	Not all diagnostic services are allowed in each security level.
AppliesTo:	CP, AP
Dependencies:	
Supporting Material:	–

]([RS_Main_00011](#))

[SRS_Diag_04135] Support UDS service \$38 (RequestFileTransfer) [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support UDS service 0x38 ("RequestFileTransfer").
Rationale:	The requestFileTransfer service is used by the client to initiate a file data transfer from either the client to the server or from the server to the client (download or upload). Additionally, this service has capabilities to retrieve information about the file system
Use Case:	Upload of files (e.g. data files, graphics, navigation data...)
AppliesTo:	CP, AP
Dependencies:	[SRS_Diag_04059] Configuration of timing parameter
Supporting Material:	ISO 14229-1 v.2013

]([RS_Main_00011](#))

[SRS_Diag_04100] Interface for logging and tracing [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide an interface for DLT to transport log and trace data using a diagnostic service. Logging and tracing data are sent via this service and control requests from the logging and tracing modules are received. For this purpose the ResponseOnEvent service is implemented. The diagnostic in AUTOSAR should provide an interface for DLT to send data and receive control requests.
Rationale:	Logging and trace needs an interface to send LogAndTrace data out of the ECU. A bus independent access to the ECU over standardized diagnostic is provided. This is available during production phase and provides a secured session control. Because log and trace messages are event triggered and the storage on the ECU is limited, these messages must be sent when they occur.
Use Case:	<ul style="list-style-type: none"> • Transmitting log and trace data during a diagnostic session • Advanced Diagnostic Tracing, optional via telematics services





AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

](RS_Main_00011)

[SRS_Diag_04098] Interact with standard bootloader [

Type:	Valid
Description:	<p>Integration of a standard bootloader into the AUTOSAR architecture.</p> <ul style="list-style-type: none"> • If the diagnostic in AUTOSAR is requested to change into the programming session (\$1002), it shall either send the final response and then activate the bootloader or it shall not send the final response and activate the bootloader where the activate the bootloader and the final response shall be sent by the bootloader (according HIS [FL-504]). • The diagnostic in AUTOSAR shall be able to check environmental conditions (e.g. engine speed) before activating the bootloader. • The diagnostic in AUTOSAR shall provide a configurable NRC 0x78 (RCRRP, retrigger the timeout supervision of the diagnostic client) response during transition to the bootloader.
Rationale:	Bootloader concept has to be standardized within AUTOSAR.
Use Case:	Usage of "off-the-shelf" bootloader
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

](RS_Main_00260)

[SRS_Diag_04159] Control of DTC storage [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support control of DTC storage via UDS service 0x85.
Rationale:	Avoiding unwanted storage of DTCs.
Use Case:	No DTCs storage when functional communication is deactivated during ECU reprogramming.
AppliesTo:	CP, AP
Dependencies:	–





Supporting Material:	–
-----------------------------	---

](RS_Main_00011)

[SRS_Diag_04157] Reporting of DTCs and related data [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide the reporting of DTCs and related data.
Rationale:	Report failure memory data to the requester.
Use Case:	All services reporting fault memory data.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

](RS_Main_00011)

[SRS_Diag_04156] Support DTCFunctionalUnit [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support DTCFunctionalUnit according to ISO 14229-1.
Rationale:	Compliance to ISO 14229-1.
Use Case:	OEM-specific use of DTCs.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

](RS_Main_00011)

[SRS_Diag_04077] Uses standard mechanisms provided by persistency modules [

Type:	Valid
Description:	–
Rationale:	Non volatile data storage
Use Case:	Triggered data storage during normal ECU operation to avoid loss of volatile data / event information.
AppliesTo:	CP, AP





Dependencies:	–
Supporting Material:	–

]([RS_Main_00130](#), [RS_Main_00440](#))

[SRS_Diag_04131] Consistent event management mechanisms [

Type:	Valid
Description:	All memory locations except mirror memory shall use the same event management mechanisms.
Rationale:	Ensure identical event management behavior.
Use Case:	–
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00260](#))

[SRS_Diag_04117] Configurable behavior for DTC deletion [

Type:	Valid
Description:	Usually, only ClearAllDTCs is used for the deletion of DTCs. Therefore, a configurable behavior which optionally limits the deletion of DTCs to ClearAllDTCs.
Rationale:	OEM specific behavior
Use Case:	Allow only ClearAllDTCs and therefore optimization of ClearDTC behavior.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00260](#))

[SRS_Diag_04107] Provide defensive behavior [

Type:	Valid
Description:	For safety-related applications, the diagnostic in AUTOSAR shall ensure data integrity of fault information stored in non-volatile memory.
Rationale:	Error protection of fault memory is needed for safety-related applications
Use Case:	Fault memory could have been corrupted





AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	Use the optional CRC and redundancy capabilities provided by the AUTOSAR persistency modules for stored fault memory blocks. Only blocks assigned to error events of high severity can be protected. These blocks can be stored in non-volatile memory when the error event is confirmed (before shutdown of the ECU)

](RS_Main_00011)

[SRS_Diag_04105] Event memory management [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall be able to handle valid events, update existing event memory entries or replace events in case of a full event memory. The processing is triggered externally (e.g. by the reported event status) or depends on internal information (e.g. value of debounce counter \timer, occurrence counter, ...)
Rationale:	Support of fault storage and analysis
Use Case:	Support of fault storage and analysis
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	ISO 14229-1 v.2013

](RS_Main_00420)

[SRS_Diag_04091] Notification about valid freeze frame data to applications [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall be enabled to notify other applications (or system modules) about valid freeze frame data (e.g. time stamp). If this functionality is configured for an event, it shall be executed every time a valid freeze frame is stored in the event memory.
Rationale:	Providing freeze frame data (like time stamp) to applications or system modules. Additionally this functionality provides a simple way for providing this data to other components (every time valid data is available) to avoid cyclic polling.
Use Case:	The information provided by this functionality is needed by modules like a special 'Diagnostic active response handler'.
AppliesTo:	CP, AP
Dependencies:	–





Supporting Material:	–
-----------------------------	---

](RS_Main_00260)

[SRS_Diag_04151] Event status handling [

Type:	Valid
Description:	Diagnostics shall support event status handling.
Rationale:	Support OEM specific event status handling
Use Case:	Evaluation of monitor results and deriving corresponding actions from them
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

](RS_Main_00260)

[SRS_Diag_04071] Process events according to their defined importance like priority and/or severity [

Type:	Valid
Description:	The events shall be sorted or assigned to a specific priority (e.g. Severity Mask - ISO14229-1 v.2013, Annex D3) representing their importance like: <ul style="list-style-type: none"> • Healed events can be overwritten; • Privileged storing in case of Event Buffer filled up with less privileged events.
Rationale:	ISO14229-1 v.2013
Use Case:	Improved clustering and judging of events.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	ISO14229-1 v.2013

](RS_Main_00260)

[SRS_Diag_04125] Event debounce counter shall be configurable [

Type:	Valid
Description:	It shall be configurable if the debounce counter shall be frozen or reset, when at least one enable condition for the event is set to "not fulfilled" or when ControlDTCSetting is set to "disabled". In case of switching the enable conditions to "fulfilled" the monitor needs to be informed to restart the event detection. In case of switching ControlDTCSetting to "re-enabled" the monitor needs to be informed to restart the event detection.
Rationale:	Flexible usage of internal debouncing
Use Case:	–
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

](RS_Main_00420)

[SRS_Diag_04136] Configurable "confirmed" threshold [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support a postbuild configurable "confirmed" threshold.
Rationale:	Flexible usage of local legislated requirements.
Use Case:	Support different legislated requirements in different markets (US/EURO). For the US market the MIL and the ConfirmedDTC is activated after 2 DCY (Driving Cycles). For the EUR market the MIL and the ConfirmedDTC is activated after 3 DCY (Driving Cycles).
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

](RS_Main_00260)

[SRS_Diag_04140] Aging for UDS status bits "confirmedDTC" and "test-FailedSinceLastClear" [

Type:	Valid
--------------	-------





Description:	The diagnostic in AUTOSAR shall provide the capability to age both the confirmedDTC bit and the testFailedSinceLastClear bit after a configurable number of aging cycles has been reached. The value at which each bit is aged may be different between the two.
Rationale:	–
Use Case:	–
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

](RS_Main_00260)

[SRS_Diag_04141] Ability to synchronize the event data capturing with the reported event [

Type:	Valid
Description:	The diagnostics in AUTOSAR shall be able to detect which reported event initiated the data capturing. For extended data records it shall be possible to store data related with the reported event and for snapshot record capturing the information which call has caused the triggering shall be provided.
Rationale:	If events are reported with high frequency, at the point in time the data is captured it is unclear, to which reported event the data is stored.
Use Case:	Reported failed events shall store information such as an exact time stamp or PDU ID of a failed communication. Until the point in time the data is asynchronously captured, multiple of such failures might have occurred and it is unclear to which reported event the data needs to be provided.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

](RS_Main_00260)

[SRS_Diag_04230] Support of UDS service 0x29 (Authentication) [

Type:	Valid
Description:	Diagnostics in AUTOSAR shall support the ISO 14229-1:2018 service 0x29 Authentication with sub-functions for "Authentication with PKI Certificate Exchange (APCE)" to grant access to diagnostic services. The service shall be implemented as internal service (in the BSW) without interaction with applications over middleware.
Rationale:	The authentication service provides a standardized way in authenticating a tester and ECU and grant access to diagnostic services depending on the certificate content.





Use Case:	A repair shop diagnostic tester authenticates with an ECU to gain access to diagnostic services that are explicitly allowed to be executed for a repair shop.
AppliesTo:	CP, AP
Dependencies:	SRS_Diag_XXXX3
Supporting Material:	Concept 636 "Security Extensions" - C5, ISO14229-1:2018 Authentication Service 0x29

]([RS_Main_00170](#))

[SRS_Diag_04231] Supported client certificates [

Type:	Valid
Description:	Diagnostics in AUTOSAR shall support the client certificate formats CVC and X.509 in service 0x29 diagnostic requests. The supported certificate type shall be configurable.
Rationale:	Only the subset of common known and used client certificate types shall be accepted by diagnostics in AUTOSAR. This allows a standardized handling and evaluation of certificates and content.
Use Case:	The OEM PKI issues a certificate for a repair shop diagnostic tester. The diagnostic tester and authenticates itself with the ECU.
AppliesTo:	CP, AP
Dependencies:	SRS_Diag_XXXX1
Supporting Material:	Concept 636 "Security Extensions"

]([RS_Main_00260](#))

[SRS_Diag_04232] Access rights in client certificates [

Type:	Valid
Description:	<p>The client certificate extensions shall contain well-defined data with diagnostic access rights. The following access rights types shall be available:</p> <ul style="list-style-type: none"> • Role based access rights • Dynamic access rights <p>For role based access rights, the ECU maintains information about diagnostic services allowed to be executed if the tester has gained authentication in that role. The valid client certificate sets the tester into that role. Certificates can contain multiple roles to be active at the same point in time.</p> <p>For dynamic access rights, the certificate contains a whitelist of allowed diagnostic services to be executed. The white list access shall allow wildcards</p>



△

	<p>on PDU level. Both access right types can be active at any point in time and a logical 'Or' operation shall be applied.</p> <p>The structured data layout of the certificate's access rights content shall be specified by AUTOSAR.</p>
Rationale:	Only well-defined client certificate shall be accepted by diagnostics in AUTOSAR that allows a standardized handling and evaluation of certificates and content.
Use Case:	The OEM PKI issues a certificate for a repair shop with role based or individual access rights for diagnostic services.
AppliesTo:	CP, AP
Dependencies:	SRS_Diag_XXXX1
Supporting Material:	Concept 636 "Security Extensions"

](RS_Main_00170)

[SRS_Diag_04233] Access granularity of diagnostic services [

Type:	Valid
Description:	<p>Certificates provide role based and individual access rights definition. Diagnostics in AUTOSAR shall provide a diagnostic service access right by evaluation properties of services to be executed in the following order:</p> <ul style="list-style-type: none"> • service ID (SID) • service Id and sub-function (SF) • data identifier (DID) • routine identifier (RID). <p>A service can be executed, if any of the above properties is part of the role or current dynamic access rights (white list).</p>
Rationale:	A definition is required how, the diagnostic service is identified to be executed. Especially the level of granularity is important to reduce the resource consumption to a minimum. The SID check is very coarse but efficient, for services with sub-function the sub-function can be taken into account. Further services with DIDs and RIDs are identified by this identifier only.
Use Case:	An authentication state allows to execute any ECU reset service, is restricted to extended session, allows 5 DIDs and one RID to be executed.
AppliesTo:	CP, AP
Dependencies:	SRS_Diag_XXXX5
Supporting Material:	Concept 636 "Security Extensions"

](RS_Main_00170)

[SRS_Diag_04234] Binary compatibility of white list for individual access [

Type:	Valid
Description:	Diagnostics in AUTOSAR shall specify the white list binary layout. This layout shall be compatible for all ECUs independent from the endianness in place.
Rationale:	A definition is required how a white list shall look like so it can be downloaded into any ECU software independent from the used implementation.
Use Case:	A certain binary layout for a white list shall define a well-defined set of diagnostic services that are allowed to be executed.
AppliesTo:	CP, AP
Dependencies:	SRS_Diag_XXXX5
Supporting Material:	Concept 636 "Security Extensions"

](RS_Main_00170)

[SRS_Diag_04235] Client certificate validity [

Type:	Valid
Description:	Diagnostics in AUTOSAR shall evaluate the client certificates validity period and refuse expired our not yet valid certificates.
Rationale:	Control the certificate lifetime and limit the potential of outdated certificates.
Use Case:	The OEM PKI issues a certificate (e.g. for a repair shop) for a defined period.
AppliesTo:	CP, AP
Dependencies:	SRS_Diag_XXXX1
Supporting Material:	Concept 636 "Security Extensions"

](RS_Main_00170)

[SRS_Diag_04236] Client certificate target identification [

Type:	Valid
Description:	Diagnostics in AUTOSAR shall provide standardized means for target identification. A target can be identified by OEM defined criteria such as VIN, vehicle line or ECU type.
Rationale:	Control the certificates validity on defined targets only.
Use Case:	The OEM PKI issues a certificate for a vehicle with a certain VIN or an only for one type of ECU.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	Concept 636 "Security Extensions"

](RS_Main_00170)

[SRS_Diag_04237] Client certificate evaluation [

Type:	Valid
Description:	Diagnostics in AUTOSAR shall use the diagnostic policy manager to evaluate client certificates from service 0x29 requests. The result of a certificate evaluation is the decision if the certificate is valid and which diagnostic services are allowed for execution. Based on the active certificate it grants access for received diagnostic requests.
Rationale:	AUTOSAR shall define the semantics for the certificate payload. This allows to have a standardized check for certificate validities and evaluation of contained access rights.
Use Case:	A repair shop diagnostic tester initiates an authentication by sending its certificate. A set of diagnostic services is available to the diagnostic tester after authentication.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	Concept 636 "Security Extensions"

](RS_Main_00170)

[SRS_Diag_04238] Logging certificate evaluation [

Type:	Valid
Description:	The diagnostic policy manager shall report a security event every time a certificate is passed for evaluation. The event data shall contain at least the result of the certificate evaluation.
Rationale:	Forensic analysis and interested parties require information which kind of access was requested and granted to diagnostic testers.
Use Case:	A certificated with extended access rights is provided by the diagnostic tester. A security event provides information about that specific certificate was provided to the ECU.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	Concept 636 "Security Extensions"

](RS_Main_00170)

[SRS_Diag_04239] Diagnostic services in deauthenticated state [

Type:	Valid
Description:	Diagnostics in AUTOSAR shall have a configuration to allow execution of dedicated diagnostic services in deauthenticated state.
Rationale:	At least the services to authenticate the tester, shall be available in all authentication states.



△

Use Case:	Sending a service 0x29 in deauthenticated state to reach an authentication state.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	Concept 636 "Security Extensions"

](RS_Main_00170)

[SRS_Diag_04240] Application based authentication [

Type:	Valid
Description:	Diagnostics in AUTOSAR shall provide means to applications to change the authentication state of unauthenticated connections.
Rationale:	An individual authentication with each ECU in the vehicle might be take too much time some for some applications.
Use Case:	An application based centralized authentication broadcast is required to gain access to a set of diagnostic services.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	Concept 636 "Security Extensions"

](RS_Main_00170)

[SRS_Diag_04133] Aging for event memory entries [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support aging for event memory entries to remove entries from the event memory which have not failed for a specific number of operating cycles.
Rationale:	Remove information from fault memory that is not relevant for a repair action.
Use Case:	Network timeout fault that has been detected, but is not in active state any more.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

](RS_Main_00260)

[SRS_Diag_04063] Process a dedicated event identifier for each monitoring path to support an autonomous handling of different events/faults [

Type:	Valid
Description:	For the internal administration the diagnostic in AUTOSAR needs a unique identification of each monitoring path. This identification shall be handled via an event ID value (Integer).
Rationale:	A monitoring path shall be uniquely identified by its unique event ID value.
Use Case:	Unique fault identification which can be used for enhanced debugging.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

](RS_Main_00011)

[SRS_Diag_04148] Provide capabilities to inform applications about diagnostic data changes [

Type:	Valid
Description:	The diagnostic in AUTOSAR modules shall provide capabilities to inform applications about diagnostic data changes. The capabilities shall cover the provision of corresponding interfaces and configuration options for data elements and associated triggers.
Rationale:	Applications requires information about data changes).
Use Case:	Applications needs to be informed about a status change of a DTC to be able to react on this DTC status.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

](RS_Main_00260)

[SRS_Diag_04097] Decentralized and modular diagnostic configuration in applications [

Type:	Valid
Description:	Applications can provide diagnostic information. The diagnostic in AUTOSAR module shall be able to generate ports to be connected to these applications in order access this diagnostic data.
Rationale:	Because of decentralized configuration and interface requirements each application shall provide and implement diagnostic interfaces to allow code generation and port connection





Use Case:	<p>Use-case example:</p> <ul style="list-style-type: none"> • As of today functions and associated diagnostics are developed by several parties. Thus for each function and its monitoring application (e.g. torque management in an engine controller) the diagnostic capabilities are defined separately and will not necessarily be coordinated during development. • System integration and combination of diagnostics for accessibility through diagnostic in AUTOSAR requires that the individual functions and diagnostic features are connected to be compiled as a complete diagnostic system (which is in case of OBD2 certification relevant). <p>Use-case summary:</p> <ol style="list-style-type: none"> 0. develop decentralized modular software and its diagnostics without permanent interaction with other application developers. 0. Combine modules and extract module-specific diagnostic data. 0. link diagnostic data from applications to the diagnostic in AUTOSAR.
AppliesTo:	CP, AP
Dependencies:	—
Supporting Material:	ISO 14229-1 v.2013

]([RS_Main_00420](#), [RS_Main_00260](#))

[SRS_Diag_04067] Provide the diagnostic status information according to ISO 14229-1 [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide the diagnostic status information according to the DTCStatusMask, ISO 14229-1 v.2013 (refer to DTC status mask), Annex D5
Rationale:	Advanced fault analysis
Use Case:	Improved fault and event tracking and analysis
AppliesTo:	CP, AP
Dependencies:	—
Supporting Material:	ISO 14229-1 v.2013

]([RS_Main_00420](#), [RS_Main_00260](#))

[SRS_Diag_04179] Provide interfaces for monitoring application. [

Type:	Valid
Description:	AUTOSAR Diagnostics shall provide an interface to monitoring application for reporting and processing monitor results. The reported result shall uniquely be identified by an EventID.
Rationale:	Test results reported by monitoring applications are handled diagnostic in AUTOSAR internally. The interaction between diagnostic in AUTOSAR and the application is realized using a dedicated interface.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	Monitoring applications report test results as soon as valid results are available by using the provided interface.

]([RS_Main_00260](#))

[SRS_Diag_04178] Support operation cycles according to ISO 14229-1 [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide a configurable set of system cycles that may qualify the event in an additional manner.
Rationale:	Operation cycles are essential for event status management.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	Starting of an operation cycle triggers many types of system reactions.
Supporting Material:	ISO 14229-1 v.2013 and ISO 15031-5

]([RS_Main_00260](#))

[SRS_Diag_04201] Support a configuration to assign specific events to a customer specific DTC [

Type:	Valid
Description:	Assignment of events to customer specific or standardized DTCs.
Rationale:	Events are used diagnostic in AUTOSAR internally only. An external scan tool requests a DTC number which was assigned to one or multiple events/monitors.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	Internal monitor results (e.g. driver can be experienced) are observable via a scan tool enabling external fault analysis.

]([RS_Main_00260](#))

[SRS_Diag_04180] Process all UDS Services related to diagnostic fault memory of ISO 14229-1 internally [

Type:	Valid
Description:	Service implementation of all UDS services, which are related to fault memory shall be implemented internally within diagnostic in AUTOSAR without delegating the processing/part of the processing to external modules.
Rationale:	Since diagnostic in AUTOSAR is also responsible for fault memory management, all fault memory related UDS services have to be processed internally.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	Fault memory handling like 0x85, 0x14, 0x19 have to be processed internally.
Supporting Material:	ISO 14229-1

](RS_Main_00260)

[SRS_Diag_04182] Provide an application interface to change operation cycles states [

Type:	Valid
Description:	Operation cycles handled by the diagnostic in AUTOSAR can be started, stopped or restarted by application.
Rationale:	Operation cycle state transitions are trigger conditions for event status management according to ISO 14229-1.
AppliesTo:	CP, AP
Dependencies:	SRS_Diag_04178
Use Case:	Monitoring application starts an operation cycle. This triggers some status changes for the relevant events.

](RS_Main_00060)

[SRS_Diag_04183] Notify interested parties about event status changes [

Type:	Valid
Description:	Event status change report shall be available for application subscribing for the notification.
Rationale:	Event specific status information is handled diagnostic in AUTOSAR internally, the change of the status might be relevant for monitoring or other applications.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	The application gets informed about relevant event status change.

](RS_Main_00060)

[SRS_Diag_04185] Notify applications about the clearing of an event [

Type:	Valid
Description:	Interested monitoring application shall be notified about the clearing of event status information and event related data.
Rationale:	Monitor reinitialization can be triggered by the clear notification.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	After the event status is cleared diagnostic in AUTOSAR informs the relevant monitoring application which can be reinitialized.

]([RS_Main_00060](#))

[SRS_Diag_04186] Notify applications about the start or restart of an operation cycle [

Type:	Valid
Description:	Interested monitoring application shall be informed about the start or restart of operation cycles.
Rationale:	Monitor reinitialization can be triggered by the start of an operation cycle.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	A monitor application gets initialized after diagnostic in AUTOSAR informs it about the start of a relevant operation cycle.

]([RS_Main_00060](#))

[SRS_Diag_04204] Provide the current status of each warning indicator. [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall derive the current warning indicator status from the assigned events according to ISO 14229-1. The warningIndicatorRequested bit shall be set according to ISO 14229-1.
Rationale:	The warning indicator status is used to activate or deactivate indicators like lamps, text message or a beep. The state is calculated in diagnostic in AUTOSAR wherefore the information needs to be distribution to the application.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	Indications of certain malfunctions to the driver (e.g. Malfunction Indicator Lamp (MIL)).

]([RS_Main_00060](#), [RS_Main_00420](#))

[SRS_Diag_04202] Report DTCs getting active to the error logging module/system [

Type:	Valid
Description:	Diagnostics in AUTOSAR shall report DTCs to the error logging module/system
Rationale:	To have an overview of all log, trace error messages and to set all of them in the correct context with the error events reported to the diagnostic in AUTOSAR, it is important to have all this messages and events in one list (context). This makes an analysis of the reported errors more efficient and gives a correct picture of the ongoing sequences, which report an error.
AppliesTo:	CP, AP
Dependencies:	—
Use Case:	The application sets an event status diagnostic in AUTOSAR forwards it to the logging system The logging system inserts the action to the log list

]([RS_Main_00260](#))

[SRS_Diag_04205] Support of SnapshotRecords [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support SnapshotRecords according to ISO 14229-1. Each DTC can optionally have one or more SnapshotDataRecords. The supported record numbers shall be configurable. Only a atomic update of the whole record shall be supported. The storage trigger shall be configurable per snapshot record number. The configurable trigger is based on the following DTC status bit transitions: TestFailed_Set; Confirmed_Set; Pending_Set FaultDetectionCounterThreshold_Reached. The environmental data shall be captured from external applications.
Rationale:	Advanced fault analysis.
AppliesTo:	CP, AP
Dependencies:	[SRS_Diag_04189]
Use Case:	Improved clustering and judging of events/faults.
Supporting Material:	ISO 14229-1

]([RS_Main_00260](#), [RS_Main_00011](#))

[SRS_Diag_04206] Support of ExtendedDataRecords [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support ExtendedDataRecords according to ISO 14229-1. Each DTC can optionally have one or more ExtendedDataRecords. The record numbers shall be configurable. Only a atomic update of the whole record shall



△

	<p style="text-align: center;">△</p> <p>be supported. The storage trigger shall be configurable per Extended data number. The configurable trigger is based on the following DTC status bit transitions: TestFailed_Set; Confirmed_Set; Pending_Set FaultDetectionCounterThreshold_Reached.</p>
Rationale:	Advanced fault analysis.
AppliesTo:	CP, AP
Dependencies:	[SRS_Diag_04189]
Use Case:	Improved clustering and judging of events/faults.
Supporting Material:	ISO 14229-1

]([RS_Main_00260](#), [RS_Main_00011](#))

[SRS_Diag_04189] Support a fine grained configuration for SnapshotRecords and ExtendedDataRecords [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall be able to handle fine grained layout configurations for event related data. Data elements might be collected from different applications and merged to different DIDs or ExtendedDataRecords.
Rationale:	Advanced fault analysis.
AppliesTo:	CP, AP
Dependencies:	—
Use Case:	diagnostic in AUTOSAR collects SnapshotRecord data from different application and merges diagnostic information into one DID.

]([RS_Main_00260](#), [RS_Main_00011](#))

[SRS_Diag_04190] Usage of internal data elements in SnapshotRecords and ExtendedDataRecords [

Type:	Valid
Description:	It shall be possible to assign the diagnostic in AUTOSAR internal data elements like Operation Cycle Counter, Fault Detection Counter (FDC) and Occurrence Counter to Snapshot- and ExtendedDataRecords. While reading the Snapshot- or ExtendedDataRecord the current value of the diagnostic in AUTOSAR internal data element shall be reported.
Rationale:	Some data objects that are internally generated by the diagnostic in AUTOSAR can be retrieved by UDS service 0x19 ReadDTCInformation.
AppliesTo:	CP, AP
Dependencies:	[SRS_Diag_04205]

▽



Use Case:	Reading Operation Cycle Counter, Fault Detection Counter and Occurrence Counter.
------------------	--

]([RS_Main_00260](#), [RS_Main_00011](#))

[SRS_Diag_04192] Provide the ability to handle event specific enable conditions

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support enable conditions per event. If an event specific enable condition is not fulfilled, the reported event status is not processed.
Rationale:	Support mechanisms to avoid large amounts of event memory entries in case of specific ECU conditions.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	In certain vehicle conditions, such as engine cranking, it shall be avoided to evaluate the result of a monitoring application for a certain time.

]([RS_Main_00260](#), [RS_Main_00420](#))

[SRS_Diag_04219] Provide the ability to handle event specific storage conditions

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support storage conditions per event. If an event specific storage condition is not fulfilled, no event related data is captured and UDS status bits 2 (PendingDTC) and 3 (ConfirmedDTC) is not processed.
Rationale:	Support mechanisms to avoid event memory entries in situations where the event related data is of no interest.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	For certain events only safety related information (e.g. via Fim) are derived but the further processing can be skipped as another root cause is active and only event related data for that root cause is stored.

]([RS_Main_00260](#), [RS_Main_00420](#))

[SRS_Diag_04194] ClearDTC shall be accessible for applications

Type:	Valid
Description:	The service ClearDTC provided by the diagnostic in AUTOSAR supports the functionality of clearing the DTCs of a specified memory origin. This service shall be available not only inside the diagnostic in AUTOSAR, but also for the application.
Rationale:	The UDS job 0x14 ClearDiagnosticInformation supports only the clearing of primary memory. Clearing of user defined memory origins is usually handled by the application, that is why the ClearDTC service shall be provided.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	A routine control UDS job activates application, which clears the DTCs of a user defined memory using the ClearDTC service in diagnostic in AUTOSAR.

]([RS_Main_00260](#), [RS_Main_00060](#))

[SRS_Diag_04195] Chronological reporting order of the DTCs located in the configured event memory [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall be able to handle the order of event occurrences (e.g. represented by a time stamp or odometer value).
Rationale:	Advanced fault analysis.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	When processing 0x19 UDS job, DTCs are returned in the chronological order.

]([RS_Main_00260](#), [RS_Main_00011](#))

[SRS_Diag_04211] Persistent storage of DTC status and environmental data [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support the non-volatile storage for event status and environmental data parameters required by ISO 14229-1.
Rationale:	According to the ISO 14229-1 UDS specification a set of status information and environmental data shall be stored non-volatile.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	Status information is stored non-volatile over power cycles.
Supporting Material:	ISO 14229-1 Appendix D

]([RS_Main_00011](#))

[SRS_Diag_04196] UDS Service handling for all diagnostic services defined in ISO 14229-2 [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall implement the protocol handling for all UDS services defined in ISO 14229-2.
Rationale:	The diagnostic in AUTOSAR shall be the central service handler for UDS diagnostics.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	Interaction with UDS compliant tester on Ethernet.
Supporting Material:	ISO 14229

]([RS_Main_00260](#))

[SRS_Diag_04203] Common checks on all supported UDS Services Requests [

Type:	Valid
Description:	For UDS services the support for the requested SID shall be checked by the diagnostic module. If the service ID is valid and depending on the service ID, the potential sub-function identifier shall be checked for support by the diagnostic module.
Rationale:	The diagnostic in AUTOSAR shall be UDS compliant and shall do general checks, which can be done on UDS protocol level centrally, independently whether the service is processed internally or externally by a applications as service processor.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	It must verified if the services requested is supported or not (i.g. ClearDTC,...)
Supporting Material:	ISO 14229

]([RS_Main_00260](#))

[SRS_Diag_04226] Diagnostic session check [

Type:	Valid
Description:	For UDS services the support for Diagnostic session shall be checked by the diagnostic module.
Rationale:	The diagnostic in AUTOSAR shall be UDS compliant and shall do general checks, which can be done on UDS protocol level centrally, independently whether the service is processed internally or externally by applications as service processor.
AppliesTo:	CP, AP
Dependencies:	–



△

Use Case:	Session change should allow only specified changes.
Supporting Material:	ISO 14229

](RS_Main_00260)

[SRS_Diag_04227] Common check for Security Access [

Type:	Valid
Description:	For UDS services the support for Diagnostic security level shall be checked by the diagnostic module.
Rationale:	The diagnostic in AUTOSAR shall be UDS compliant and shall do general checks, which can be done on UDS protocol level centrally, independently whether the service is processed internally or externally by applications as service processor.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	To protect services from being accessed by non-authorized users.
Supporting Material:	ISO 14229

](RS_Main_00260)

[SRS_Diag_04228] Common check for Message lengths [

Type:	Valid
Description:	For UDS services the support for Message length shall be checked by the diagnostic module.
Rationale:	The diagnostic in AUTOSAR shall be UDS compliant and shall do general checks, which can be done on UDS protocol level centrally, independently whether the service is processed internally or externally by applications as service processor.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	The message length must be checked and if it does not respect a predefined range , the requested service will be rejected.
Supporting Material:	ISO 14229

](RS_Main_00260)

[SRS_Diag_04197] Clearing the user defined fault memory [

Type:	Valid
Description:	The clearance of user defined fault memory shall be possible according to the ISO 14229 draft document: "02_ISO_14229-1_Comments-Summary_2016-09-13.docx" via diagnostic requests.
Rationale:	Provide a standardized way to clear user defined fault memory.
AppliesTo:	CP, AP
Dependencies:	—
Use Case:	OEM and TIER1 using the user defined fault memory need to clear the user defined memory. A standardized way make OEM or TIER1 specific solutions obsolete, which were incompatible to each.
Supporting Material:	ISO 14229-1

]([RS_Main_00260](#))

[SRS_Diag_04198] Process all UDS Services related to session and security management of ISO 14229 internally [

Type:	Valid
Description:	Service implementation of all UDS services, which are related to session and security management (DiagnosticSessionControl, SecurityAccess and TesterPresent from 'Diagnostic and Communication Management functional unit'), shall be implemented internally within diagnostic in AUTOSAR without delegating the processing/part of the processing to external modules. This does NOT exclude, that diagnostic in AUTOSAR does callout to external application for instance to get/check certain security keys. But the state machine/protocol is handled internally by diagnostic in AUTOSAR.
Rationale:	Session and security management is an integral part of general UDS service handling and has therefore to be implemented internally.
AppliesTo:	CP, AP
Dependencies:	—
Use Case:	General diagnostic protocol processing.
Supporting Material:	ISO 14229

]([RS_Main_00260](#), [RS_Main_00011](#))

[SRS_Diag_04199] Provide a configurable UDS service execution mechanism at runtime to decide if a UDS request shall be processed or not [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support to query configured application, whether a received UDS service request shall be processed or rejected.
Rationale:	Infrastructural/OEM specific supervisor components decide about service execution on a basis of ECU/vehicle state.
AppliesTo:	CP, AP
Dependencies:	–
Use Case:	Control of service access centrally done in one application.

|(RS_Main_00260, RS_Main_00011)

[SRS_Diag_04208] Inform the application about diagnostic session and diagnostic security level changes on each tester connection. [

Type:	Valid
Description:	In case the currently active UDS session or security level change on a tester conversation, the diagnostic in AUTOSAR shall provide a notification mechanism for the application, to inform the applications about the new session or security level and the affected tester connection.
Rationale:	Session changes happen asynchronously to service processor implementations. But there exists functionality that needs to react on session changes.
AppliesTo:	CP, AP
Dependencies:	[SRS_Diag_04169]
Use Case:	Flexibility for service processor implementations.

|(RS_Main_00260, RS_Main_00011)

[SRS_Diag_04218] Support of UDS service 0x2F InputOutputControlByIdentifier [

Type:	Valid
Description:	The Diagnostic Management shall support the ISO 14229-1 service 0x2F InputOutputControlByIdentifier
Rationale:	Allow to simulate input values and to control output values
AppliesTo:	CP, AP
Use Case:	In workshop or production checks with the input and output channels of the ECU is needed.
Supporting Material:	ISO 14229-1

|(RS_Main_00260, RS_Main_00011)

[SRS_Diag_04222] Independence of clearing DTC status and system degradation [

Type:	Valid
Description:	Independence of clearing DTC status and system degradation
Rationale:	Clearing of DTCs must not influence the system degradation. Otherwise on a clear, the system would go to normal operation and cause serious issues with functionalities (e.g. wrong actuation)
AppliesTo:	CP, AP
Use Case:	To achieve clearing of DTC status information and simultaneously keep the system degradation, it shall be possible for events to not to change their failed status upon a call of clear. Nevertheless status bytes of DTCs which are not related to system degradation shall be cleared
Supporting Material:	ISO 14229-1

]([RS_Main_00260](#), [RS_Main_00011](#))

[SRS_Diag_04224] Support the UDS service 0x31 (RoutineControl) according to ISO 14229-1 [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support the ISO 14229-1 service 0x31 RoutineControl with all sub-functions
Rationale:	RoutineControl is an integral part of ISO 14229-1 and used in most ECUs for customer specific actions triggered by diagnostic services.
AppliesTo:	CP, AP
Use Case:	Diagnostic tester starts a routine in the server.
Supporting Material:	ISO 14229-1

]([RS_Main_00260](#), [RS_Main_00011](#))

4.2 Diagnostic requirements for the Classic Platform

4.2.1 Functional Requirements

[SRS_Diag_04213] Support the mirror fault memory defined by ISO 14229-1 [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support the mirror fault memory defined by ISO 14229-1.
Rationale:	Extended storage of fault information independent from the primary fault memory.



△

Use Case:	Mirror fault memory is used by OEM and Tier1 during development or for storing warranty relevant information inside. DTCs in the mirror memory are triggered along with a DTC in the primary fault memory, but it has different event related data stored and it is not cleared by clearing the primary fault memory. The information stored in the mirror memory is not relevant for workshops or to repair the vehicle.
AppliesTo:	CP
Dependencies:	–
Supporting Material:	ISO 14229-1 v.2013

](RS_Main_00260)

[SRS_Diag_04112] The DEM module shall support DTCs according to SAE J1939

Type:	Valid
Description:	The DEM module shall support DTCs according to SAE J1939-73.
Rationale:	Support of SAE J1939-73
Use Case:	Diagnostics in HDV, HD-OBDD
AppliesTo:	CP
Dependencies:	DEM, J1939DCM
Supporting Material:	–

](RS_Main_00260)

[SRS_Diag_04139] Support subfunction 0x42 of UDS service 0x19

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support subfunction 0x42 of UDS service 0x19 to retrieve WWH-OBDD-specific DTCs matching the requested DTC status mask and severity mask record.
Rationale:	Support of WWH-OBDD
Use Case:	Improved fault and event tracking and analysis
AppliesTo:	CP
Dependencies:	–
Supporting Material:	Support of WWH-OBDD

](RS_Main_00260)

[SRS_Diag_04129] Provide OBD-specific configuration capabilities

Type:	Valid
Description:	<p>The diagnostic in AUTOSAR shall provide the following configuration capabilities:</p> <ul style="list-style-type: none"> • OBD- ECU kind 1: ECU acts as OBD Master ECU (Master or Primary ECU) • OBD- ECU kind 2: ECU acts as OBD Slave ECU (Dependent / Secondary ECU) • OBD- ECU kind 3: ECU acts as non-OBD ECU <p>The diagnostic in AUTOSAR shall both provide corresponding configuration parameters to switch on/switch off module-specific OBD functionality.</p> <p>Depending on the configured use case, the associated application interfaces shall be provided to connect different OBD-ECU kinds on application level (via bus communication).</p>
Rationale:	UseCase-specific module configuration.
Use Case:	Optimization of RAM/ROM consumption.
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

](RS_Main_00260)

[SRS_Diag_04163] Parallel OBD and UDS processing [

Type:	Valid
Description:	Diagnostics shall support the parallel processing of OBD and UDS protocols.
Rationale:	Vehicles can be equipped with On-board testers which send diagnostic requests at any arbitrary point in time. Legislative OBD requests need to be processed independently from a UDS requests from On-board testers.
Use Case:	Parallel reception of diagnostic requests from multiple testers.
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

](RS_Main_00260)

[SRS_Diag_04161] Provide support for the ASMIP algorithm [

Type:	Valid
Description:	The diagnostic in AUTOSARs shall consider the ASMIP algorithm (Alternative Statistical MIL Illumination Protocol) according to the Californian Code of Regulation 13 CCR section 1968.2.
Rationale:	Supporting OBD use cases.
Use Case:	Dynamical threshold modification.
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00260](#))

4.2.2 Fault Memory Management

[SRS_Diag_04002] The Diagnostic event (fault) management shall be established as Basic SW Module [

Type:	Valid
Description:	The Diagnostic event (error) management shall be a Basic SW Module described in the Diagnostic WP. Diagnostic event (error) management is out of scope for Mode Management.
Rationale:	SW Architecture
Use Case:	Improved fault and event tracking and analysis for Service, assembly line, OBD-SCAN-Tool
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00260](#))

[SRS_Diag_04057] Classification of events for series production, OBD and expert usage [

Type:	Valid
Description:	<p>The diagnostic in AUTOSAR shall support a classification of events for the following types of events:</p> <ul style="list-style-type: none"> • Events that are defined for error analysis in the service station shall be stored in the primary event memory.



△

	<p style="text-align: center;">△</p> <ul style="list-style-type: none"> Events that are defined for detailed error analysis by experts in the after sale department are stored in the secondary error memory. <p>Errors that occur during the development process shall be reported to the debugging modules. Therefore, debugging module APIs shall be used which (are not provided by the diagnostic in AUTOSAR).</p>
Rationale:	After sales analysis
Use Case:	Distinction between service station relevant and after sales relevant events.
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00011](#))

[SRS_Diag_04124] Store the current debounce counter value nonvolatile to over a powerdown cycle [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall be able to store the current debounce counter value non-volatile to over a power-down cycle.
Rationale:	Support of DTC de-bouncing within several power cycles.
Use Case:	While the typical DTC operation cycle for a DTC is to start at power up and end at power down, there are different situations, when a particular DTC must define its operation cycle to span multiple ECU power up/down cycles. In this case, the FDC would need to be stored in NVM as it may never make it to 127 during a single power up.
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00260](#), [RS_Main_00420](#))

[SRS_Diag_04118] Optionally support event displacement [

Type:	Valid
--------------	-------

▽



Description:	The diagnostic in AUTOSAR shall optionally support event displacement. The following sequence of different displacement criteria shall be possible: 0. Priority; 0. Active/passive status (optional); 0. Occurrence.
Rationale:	Limited hardware (memory resources) in ECU.
Use Case:	Error memory is full and Valid event is reported to diagnostic in AUTOSAR.
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

](RS_Main_00260)

[SRS_Diag_04123] Harmonized Driving-/WarmUp cycles [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support harmonized Driving-/WarmUp cycles. The calculation of Driving-/WarmUp cycles is based on legal requirements.
Rationale:	OBD certification requires vehicle consistent calculations based on a harmonized Driving-/WarmUp cycle in the centralized OBD Master ECU.
Use Case:	Qualification of OBD-relevant DTCs
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

](RS_Main_00260)

[SRS_Diag_04093] Memory overflow indication [

Type:	Valid
Description:	For each Event Memory it shall be indicated if the related event memory (e.g. primary, secondary, mirror) is full and the next event occurs to be stored in this event memory.
Rationale:	The information that an event memory overflow occurred is very important for fault analysis.





Use Case:	<ul style="list-style-type: none"> • Triggering further internal behavior (e.g displacement strategies) • Linking this information to a dedicated Extended Data Record • Vendor specific UDS-Service
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00260](#))

[SRS_Diag_04109] Provide an interface to retrieve the number of event memory entries [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide an interface to retrieve the number of event memory entries currently stored in Primary, Secondary and Mirror Memory to the application. Additionally, the corresponding Client Server Interface shall be provided.
Rationale:	The interface is required from application, to check if event memory entries exist that influence the ECU behavior.
Use Case:	There is an application message where a status bit must be set as soon as events are stored in the event memory. Therefore, the application needs to know how many event memory entries exist.
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00420](#))

[SRS_Diag_04126] Configurable suppression of events [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide a postbuild/loadable boolean configuration option per event. If this configuration is set to true the event behaves the same as if it is suppressed by API call. An event suppressed by configuration can not be activated via API call.
Rationale:	Use case-specific configuration of fault memory, only required events are visible and usable in ECU.
Use Case:	Variant coding
AppliesTo:	CP





Dependencies:	–
Supporting Material:	–

]([RS_Main_00260](#))

[SRS_Diag_04110] SAE J1939 lamp status [

Type:	Valid
Description:	The composite and DTC-specific lamp status of the following lamps shall be supported: Malfunction Indicator Lamp, Red Stop Lamp, Amber Warning Lamp and Protect Lamp.
Rationale:	Support of SAE J1939-73
Use Case:	Diagnostics in HDV, HDOBD
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00260](#), [RS_Main_00420](#))

[SRS_Diag_04111] SAE J1939 Expanded-FreezeFrame [

Type:	Valid
Description:	The composite and DTC-specific lamp status of the following lamps shall be supported: Malfunction Indicator Lamp, Red Stop Lamp, Amber Warning Lamp and Protect Lamp.
Rationale:	Support of SAE J1939-73
Use Case:	Diagnostics in HDV, HDOBD
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00260](#), [RS_Main_00420](#))

[SRS_Diag_04113] Support a set of SAE J1939 DM-messages [

Type:	Valid
--------------	-------





Description:	The following DM-messages shall be supported:																																										
	<table border="1"> <thead> <tr> <th>Name</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>DM01</td> <td>Active Diagnostic Trouble Codes</td> </tr> <tr> <td>DM02</td> <td>Previously Active Diagnostic Trouble Codes</td> </tr> <tr> <td>DM03</td> <td>Diagnostic Data Clear/Reset for Previously Active DTCs</td> </tr> <tr> <td>DM04</td> <td>Freeze Frame Parameters</td> </tr> <tr> <td>DM05</td> <td>Diagnostic Readiness 1</td> </tr> <tr> <td>DM06</td> <td>Emission Related Pending DTCs</td> </tr> <tr> <td>DM11</td> <td>Diagnostic Data Clear/Reset for Active DTCs</td> </tr> <tr> <td>DM12</td> <td>Emissions Related Active DTCs</td> </tr> <tr> <td>DM13</td> <td>Stop Start Broadcast</td> </tr> <tr> <td>DM19</td> <td>Calibration Information</td> </tr> <tr> <td>DM20</td> <td>Monitor Performance Ratio SAE J1939-73 Revised SEP2006</td> </tr> <tr> <td>DM21</td> <td>Diagnostic Readiness 2</td> </tr> <tr> <td>DM23</td> <td>Previously Active Emission Related Faults</td> </tr> <tr> <td>DM24</td> <td>SPN Support</td> </tr> <tr> <td>DM25</td> <td>Expanded Freeze Frame</td> </tr> <tr> <td>DM26</td> <td>Diagnostic Readiness 3</td> </tr> <tr> <td>DM28</td> <td>Permanent DTCs</td> </tr> <tr> <td>DM29</td> <td>Regulated DTC Counts (Pending, Permanent, MIL-On, PMIL-On)</td> </tr> <tr> <td>DM31</td> <td>DTC to Lamp Association</td> </tr> <tr> <td>DM35</td> <td>Immediate Fault Status</td> </tr> </tbody> </table>	Name	Description	DM01	Active Diagnostic Trouble Codes	DM02	Previously Active Diagnostic Trouble Codes	DM03	Diagnostic Data Clear/Reset for Previously Active DTCs	DM04	Freeze Frame Parameters	DM05	Diagnostic Readiness 1	DM06	Emission Related Pending DTCs	DM11	Diagnostic Data Clear/Reset for Active DTCs	DM12	Emissions Related Active DTCs	DM13	Stop Start Broadcast	DM19	Calibration Information	DM20	Monitor Performance Ratio SAE J1939-73 Revised SEP2006	DM21	Diagnostic Readiness 2	DM23	Previously Active Emission Related Faults	DM24	SPN Support	DM25	Expanded Freeze Frame	DM26	Diagnostic Readiness 3	DM28	Permanent DTCs	DM29	Regulated DTC Counts (Pending, Permanent, MIL-On, PMIL-On)	DM31	DTC to Lamp Association	DM35	Immediate Fault Status
	Name	Description																																									
	DM01	Active Diagnostic Trouble Codes																																									
	DM02	Previously Active Diagnostic Trouble Codes																																									
	DM03	Diagnostic Data Clear/Reset for Previously Active DTCs																																									
	DM04	Freeze Frame Parameters																																									
	DM05	Diagnostic Readiness 1																																									
	DM06	Emission Related Pending DTCs																																									
	DM11	Diagnostic Data Clear/Reset for Active DTCs																																									
	DM12	Emissions Related Active DTCs																																									
	DM13	Stop Start Broadcast																																									
	DM19	Calibration Information																																									
	DM20	Monitor Performance Ratio SAE J1939-73 Revised SEP2006																																									
	DM21	Diagnostic Readiness 2																																									
	DM23	Previously Active Emission Related Faults																																									
	DM24	SPN Support																																									
	DM25	Expanded Freeze Frame																																									
	DM26	Diagnostic Readiness 3																																									
DM28	Permanent DTCs																																										
DM29	Regulated DTC Counts (Pending, Permanent, MIL-On, PMIL-On)																																										
DM31	DTC to Lamp Association																																										
DM35	Immediate Fault Status																																										
Rationale:	Support of SAE J1939-73																																										
Use Case:	Diagnostics in HDV, HD-OBD																																										
AppliesTo:	CP																																										
Dependencies:	–																																										
Supporting Material:	–																																										

]([RS_Main_00260](#), [RS_Main_00420](#))

[SRS_Diag_04137] Definition of replacement failure [

Type:	Valid
Description:	Upon filtering the storage of failure reports by central conditions (Storage Condition), it shall be possible to define and store a replacement failure info which then can be stored to the event memory. This replacement failure will represent the actual failure reason.
Rationale:	Improvement of failure analysis.
Use Case:	–
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00260](#))

[SRS_Diag_04155] Notify applications and BSW modules about updates of event related data [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall notify other applications / BSW modules about updates of the event-related data in the event memory.
Rationale:	Changes to the event related data are done internally while evaluating event information passed from the monitoring application. Third parties interested in the change of event related data need to get notified.
Use Case:	Allow OEM specific reaction on updates of the event related data.
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

] ([RS_Main_00260](#))

[SRS_Diag_04160] ResponseOnEvent according to ISO 14229-1 [

Type:	Valid
Description:	Diagnostics shall support ResponseOnEvent according to ISO 14229-1.
Rationale:	Needed for failure analysis and fault memory tracking.
Use Case:	Inform diagnostic tooling about certain runtime conditions.
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

] ([RS_Main_00260](#))

[SRS_Diag_04215] Support of UDS service ReadDataByPeriodicIdentifier (0x2A)

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support UDS service ReadDataByPeriodicIdentifier (0x2A) with all supported sub-functions according to ISO 14229-1.
Rationale:	Periodic transmission of measurements/data by the diagnostic server (ECU), instead of frequent polling by re-requesting the same data via ReadDataByIdentifier. Further it is possible to reach higher update rates of measurements (e.g. 2ms).
Use Case:	Monitor measurement values over time by diagnostics.
AppliesTo:	CP
Dependencies:	–



△

Supporting Material:	—
-----------------------------	---

](RS_Main_00260)

[SRS_Diag_04217] Adding the Lamp status pertinent to a specific Fault Event/DTC available as DemInternalDataClass shall be codified in the same format of DM31 [

Type:	Valid
Description:	when a Fault Event memory entry is coming, the related FreezeFrame includes the pertinent DTC lamp status with the SPN number for each kind of lamp. In fact, the format of this data shall also be compliant to the content of the DM31 with the same codification/format and SPNs identification. In other word this solution would ensure that the user is able to retrieve the pertinent lamp status as it becomes a memory entry even if the DM31 request is not done in the same moment.
Rationale:	After sales analysis.
Use Case:	Provide lamp status per DTC to diagnostic testers.
AppliesTo:	CP
Dependencies:	—
Supporting Material:	—

](RS_Main_00260)

[SRS_Diag_04165] Triggering of multiple events upon a master event is reported [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide the capability to trigger multiple events upon an event is reported.
Rationale:	From one unique fault source, multiple events shall be derived and each derived event can trigger an own DTC and event memory entry.
Use Case:	Storing DTCs from one unique source into different event memories without changing and recompiling the reporting software. A given software can report event status information and depending on configuration multiple DTCs and event related data in different fault memories can be stored.
AppliesTo:	CP
Dependencies:	—
Supporting Material:	—

](RS_Main_00260)

[SRS_Diag_04031] Notify the Function Inhibition Manager (FIM) upon changes of the event status in order to process them according to the SW components dependencies [

Type:	Valid
Description:	Control (enable/disable) of functionalities of SW components based on the following inhibit condition: - faults
Rationale:	Event status information for function inhibition
Use Case:	Usage of event status information for function inhibition
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00011](#))

[SRS_Diag_04220] Support DTCs suppression [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide the possibility to suppress DTCs to be visible in diagnostic services. Suppressed DTCs shall be available internally and processed as any other DTCs
Rationale:	DTCs need to be hidden in certain conditions (e.g. dedicated markets)
Use Case:	Hide DTCs in certain markets
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00011](#))

[SRS_Diag_04221] In-Use-Monitor Performance Ratio indicates how often the OBD system monitors particular components, compared to the amount of the vehicle operation [

Type:	Valid
Description:	The diagnostic in AUTOSARs shall provide a means to indicates how often the OBD system monitors particular components, compared to the amount of the vehicle operation. This is done through In-Use-Monitor Performance Ratio (IUMPR). It is defined as the number of times a fault could have been found (=numerator), divided by the number of times the vehicle operation conditions have been fulfilled (=denominator) as defined in the respective OBD regulations.
Rationale:	Supporting OBD use cases





Use Case:	Calculation of IUMPR for legal regulation
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

](RS_Main_00011)

[SRS_Diag_04223] Support Snapshot Records data pre-storage [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide means to applications to immediately trigger capturing snapshot record data. This captured data shall be stored in the snapshot record if the trigger condition is fulfilled in a later point in time
Rationale:	Snapshot record data would always have the data value at a point in time when a trigger occurs which might be too late as the environmental data already has changed since the first fault occurrence
Use Case:	Capture snapshot record data at the first time the fault occurs
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

](RS_Main_00011)

4.2.2.1 DTC and event-related data

[SRS_Diag_04162] Parallel fault memory access [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide parallel access to the fault memory to various clients. Each client shall be able to access the fault memory independent from other clients. Conflicts occurring during parallel access to shared resources shall be resolved.
Rationale:	OEMs require parallel access to diagnostics.
Use Case:	<ul style="list-style-type: none"> • Support of OBD and UDS in parallel • Software interacting with secondary ECUs in OBD • Software components accessing event memory data
AppliesTo:	CP
Dependencies:	–





Supporting Material:	–
-----------------------------	---

](RS_Main_00011)

4.2.3 Diagnostic Communication

[SRS_Diag_04007] Provide a diagnostic service handling for the applications involved in diagnostic functionality [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide the diagnostic service handling, according to ISO14229-1 v.2013, ISO 15031-5 and ISO 15765-3 for the communication between an AUTOSAR conform ECU and an internal tester or an external diagnostic tool).
Rationale:	Only one diagnostic service instance in an ECU.
Use Case:	<p>Communication with an external diagnostic tools in :</p> <ul style="list-style-type: none"> • development • manufacturing • service (garage) • OBD scan tools <p>Communication with an internal tester.</p>
AppliesTo:	CP
Dependencies:	–
Supporting Material:	ISO14229-1 v.2013, ISO 15031-5, ISO 15765-3

](RS_Main_00011)

[SRS_Diag_04021] Handling of different diagnostic sessions in parallel [

Type:	Valid
Description:	Handle an established diagnostic communication and a parallel diagnostic access request in parallel. This is necessary to open a diagnostic access with high priority and the controlled shutdown of the established diagnostic access with low priority.
Rationale:	To prioritize handling of different diagnostic protocols e.g. OBD and normal diagnostic communication as UDS.
Use Case:	An internal vehicle diagnostic tester communication is interrupted by OBD diagnostic access request.



△

AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

](RS_Main_00011)

[SRS_Diag_04032] Different diagnostic addresses shall be supported by multiple (physical) channels [

Type:	Valid
Description:	Modern ECUs contain more than one functionality (e.g. board computer, instrument cluster). Each functionality shall be addressable by a diagnostic tool with a different diagnostic address. This does not imply that those multiple requests are allowed in parallel.
Rationale:	High flexibility and granularity for addressing of applications
Use Case:	At the service (garage) a fault symptom is based on functionality. The service only wants to address this functionality.
AppliesTo:	CP
Dependencies:	[SRS_Diag_04021] Switch diagnostic communication access
Supporting Material:	–

](RS_Main_00011)

[SRS_Diag_04058] Ability to access different event memories [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support diagnostic services to read or remove event entries from the configured event memory seperatly.
Rationale:	Advanced fault analysis
Use Case:	The development departments of the OEMs and Suppliers need as much as possible deeper fault/event analysis although the mechanics may have deleted the faults or may not need to know if there are more detailed root causes for an event or fault.
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

](RS_Main_00011)

[SRS_Diag_04024] Access and handle specific data elements and data element groups if requested by an external scan tool [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide interfaces for applications to access diagnostic data and to process diagnostic services. The size of a diagnostic data element is derived by the interface or provided as an attribute of the API call itself.
Rationale:	Optimized usage of resources
Use Case:	Transfer environmental / FreezeFrame data of the diagnostic in AUTOSAR.
AppliesTo:	CP, AP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00011](#))

[SRS_Diag_04015] Timing handling according to ISO15765-3 [

Type:	Valid
Description:	In ISO15765-3 timing handling for physical and functional communication and error reaction is described. The diagnostic in AUTOSAR shall work according this specification. Timing parameters shall be configurable (see dependencies).
Rationale:	Ensure a steady and save communication link and guarantee specified timing conditions.
Use Case:	Optimizing of timing for high performance during reprogramming.
AppliesTo:	CP
Dependencies:	[SRS_Diag_04059] Configuration of timing parameter
Supporting Material:	ISO15765-3

]([RS_Main_00011](#))

[SRS_Diag_04019] Provide confirmation after transmit diagnostic responses to the application [

Type:	Valid
Description:	Diagnostic in AUTOSAR shall notify applications about successful or failed transmission of diagnostic responses.
Rationale:	Provide application a mean to get notified on transmission results. Some operations shall only be started after the transmission. Without this notification an application will have no knowledge when to start an operation depending on a previous transmission. Service response confirmation is defined by ISO 14229-1 v.2013.
Use Case:	E.g.reset function. The ECU shall only be reset if the positive response was sent on the bus.



△

AppliesTo:	CP, AP
Dependencies:	
Supporting Material:	ISO14229-1 v.2013

]([RS_Main_00011](#))

[SRS_Diag_04120] Support a predefined AddressAndLengthFormatIdentifier [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support a predefined AddressAndLengthFormatIdentifier for UDS service \$23 (ReadMemoryByAddress), UDS service 0x2C (DynamicallyDefineDataIdentifier with subservice DefineByMemoryAddress), UDS service 0x3D (WriteMemoryByAddress), UDS service 0x34 (RequestDownload) and UDS service 0x35 (RequestUpload).
Rationale:	AddressAndLengthFormatIdentifier is defined once and afterwards used in corresponding UDS services.
Use Case:	Static configuration of AddressAndLengthFormatIdentifier
AppliesTo:	CP, AP
Dependencies:	—
Supporting Material:	ISO14229-1 v.2013

]([RS_Main_00011](#), [RS_Main_00260](#))

[SRS_Diag_04121] Provide the handling of service DynamicallyDefineDataIdentifier according to ISO 14229-1 [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide the handling of service DynamicallyDefineDataIdentifier according to ISO 14229-1 v.2013.
Rationale:	Standardized ISO 14229-1 v.2013 behavior
Use Case:	—
AppliesTo:	CP
Dependencies:	—
Supporting Material:	ISO14229-1 v.2013

]([RS_Main_00011](#), [RS_Main_00260](#))

[SRS_Diag_04153] Support generic connections [

Type:	Valid
Description:	Diagnostics shall support generic connections. Addressed information is then using MetaData.
Rationale:	Channel and connection configuration optimization through the layers.
Use Case:	Limit the request execution due to vehicle- or ECU states/-conditions.
AppliesTo:	CP
Dependencies:	Generic connections are supported for CAN diagnostics using normal fixed or mixed 29 bit addressing formats according to ISO15765-2. Depending on the actual layout of the CAN IDs, generic connections could also be used for extended or normal and mixed 11 bit addressing formats.
Supporting Material:	–

]([RS_Main_00260](#))

[SRS_Diag_04011] Provide diagnostic state information to applications [

Type:	Valid
Description:	Applications need to know about the actual session and security state, because it is not predictable if the information's lead to a different functional diagnostic behavior.
Rationale:	Functional requirement
Use Case:	With the diagnostic session which the garage is using, it is allowed to switch between different sets of parameters. With an enhanced diagnostic session which could be used in development and a corresponding security level, it is allowed to change the data within the set of parameters.
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00011](#))

[SRS_Diag_04003] Network independent design [

Type:	Valid
Description:	All network (CAN, LIN, FlexRay, MOST, Ethernet) dependent parts shall be done outside the diagnostic in AUTOSAR. That means that all interfaces to the transport protocol modules shall be network independent.
Rationale:	The diagnostic in AUTOSAR describes only the services for communication and the behavior of network is out of scope. Highest granularity and best option to adapt upcoming networks.
Use Case:	The diagnostic in AUTOSAR has to be network independent. The interface to the transport protocol shall be network independent.





AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00011](#), [RS_Main_00260](#))

[SRS_Diag_04147] Communication with the transport layers to receive and send diagnostic data [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall communicate with the transport layer modules to receive and send diagnostic data.
Rationale:	Ensure diagnostic communication.
Use Case:	Support of various transport protocols (ISO-15765-2, ...).
AppliesTo:	CP
Dependencies:	–
Supporting Material:	–

]([RS_Main_00011](#), [RS_Main_00260](#))

4.2.4 Function Inhibition Manager (FIM)

The specification of Software requirements of the function inhibition manager is not a part of this specification. For details, please refer to the AUTOSAR_FIM_SRS.

4.3 Diagnostic requirements for the Adaptive Platform

[SRS_Diag_04166] Several tester conversations in parallel with assigned priorities [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall generally support a configurable amount of tester conversations/connections in parallel. Per tester connection, a priority shall be configurable. The priority is assigned to the tester address (SA of the UDS request), which identifies the connection.
Rationale:	ECUs in the Adaptive Platform generally have enough resources to handle multiple tester conversations in parallel.



△

AppliesTo:	AP
Dependencies:	–
Use Case:	Support for vehicle internal and external testers in parallel, which can not be easily synchronized.
Supporting Material:	ISO 14229-1

]([RS_Main_00260](#), [RS_Main_00011](#))

[SRS_Diag_04209] Pseudo parallel client interaction according to ISO [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support the parallelism defined by the ISO as pseudo parallel concept, which is defined in ISO 14229-1 under Figure J.2.
AppliesTo:	AP
Dependencies:	–
Use Case:	Support of scenarios, where testers in parallel is only allowed, when in default session.
Supporting Material:	ISO 14229-1

]([RS_Main_00260](#), [RS_Main_00011](#))

[SRS_Diag_04210] Fully parallel client interaction [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support fully parallel client interaction, where clients are fully shielded from each other and can have different non-default sessions.
Rationale:	ECUs in the Adaptive Platform generally have enough resources to handle multiple tester conversations in parallel.
AppliesTo:	AP
Dependencies:	–
Use Case:	Support of scenarios, where maximum of testers in parallel shall be allowed
Supporting Material:	ISO 14229-1

]([RS_Main_00260](#), [RS_Main_00011](#))

[SRS_Diag_04167] Conversation preemption/abortion [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall generally support the preemption of a tester conversation in case all configured tester connections are currently active and a new connection of a tester with higher priority than an existing one takes place, it shall abort the lowest priority conversation and accept the new connection/conversation.
Rationale:	A ECU will have limited resources for parallel processing of diagnostic requests and different requests will have different priorities therefore the need for abortion.
AppliesTo:	AP
Dependencies:	–
Use Case:	Support for vehicle internal and external testers in parallel, which can not be easily synchronized.
Supporting Material:	ISO 14229-1

](RS_Main_00260)

[SRS_Diag_04168] Adding of user-defined transport layers [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support adding of user-defined transport layers.
Rationale:	Although the Adaptive Platform starts out with Ethernet support, later extension to other networks (CAN, FlexRay) should already be prepared. Additionally there is at least one OEM, which has its own DoIP implementation, which differs from ISO 13400. It should be possible to integrate this DoIP implementation with manageable effort/costs.
AppliesTo:	AP
Dependencies:	–
Use Case:	Plugability of UDS transport layers, to support different networks.

](RS_Main_00260)

[SRS_Diag_04169] Provide an interface for external UDS service processors. [

Type:	Valid
Description:	For all UDS services, which are NOT processed/implemented internally by diagnostic in AUTOSAR (either by configuration or generally not supported internally), but by external service processors, the diagnostic in AUTOSAR has to delegate the processing to the external application.
Rationale:	The majority of diagnostic services is implemented by the application, where the diagnostic in AUTOSAR has to delegate the service processing to.
AppliesTo:	AP





Dependencies:	[SRS_Diag_04097], [SRS_Diag_04007]
Use Case:	Service processing by software components.
Supporting Material:	ISO 14229-1

](RS_Main_00260, RS_Main_00420)

[SRS_Diag_04170] Provide connection specific meta information to external service processors [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide connection specific meta-information to the external service processor, which is processing the UDS service request. At least DoIP shall be supported and the meta-information shall contain Src-IP-Adr/Port and Target-IP-Adr/Port of the request. The meta-information should be designed, that it can later easily extended to also cover connection information of other network technologies (like CAN, Flexray).
Rationale:	Sometimes the reaction of service processor implementations on a UDS request depend on the connection properties of the tester.
Dependencies:	[SRS_Diag_04169]
Use Case:	Flexibility for service processor implementations.
AppliesTo:	AP
Dependencies:	–

](RS_Main_00260, RS_Main_00420)

[SRS_Diag_04171] Synchronous and asynchronous interaction with external service processors [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support both types of interaction: <ul style="list-style-type: none"> • Calling a service processor synchronously, which means a blocking call until the service processor returns the final result (pos./neg. response, optional out parameters). • Calling a service processor asynchronously, which means a call to the service processor, where the service processor returns, that the job is not yet finished and later reports back to diagnostic in AUTOSAR via a separate callback, that the service processing has finished.
Rationale:	For long running service processing, which delegate the processing to own worker threads, the asynchronous callback model is more efficient, while for simple service processors the strict synchronous model is easier to implement.
AppliesTo:	AP



△

Dependencies:	[SRS_Diag_04169]
Use Case:	Flexibility for service processor implementations.

]([RS_Main_00260](#), [RS_Main_00420](#))

[SRS_Diag_04173] Different signature types, when delegating processing of UDS service to the application [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall support the following signatures, when delegating processing of UDS service to the application: <ul style="list-style-type: none"> • Untyped interface, where the entire payload including SID and sub-service is given as a byte array to service processors • Typed interface per SID, sub-service and data element, where a mapping from the UDS parameters/data stream to datatypes is described in the configuration.
Rationale:	Depending on the use case/complexity of the UDS service and its parameters, it is much more efficient to do the parsing/interpretation in the implementation of the service processor. On the other hand, there are use cases, where the description of mapping from UDS data stream to interface type has the benefit, that the service processor implementation may stay unchanged, where the mapping description may be adapted to an altered on the wire representation.
AppliesTo:	AP
Dependencies:	[SRS_Diag_04169]
Use Case:	Flexibility for service processor implementations.

]([RS_Main_00260](#), [RS_Main_00420](#))

[SRS_Diag_04174] Provide SA and TA to external service processors [

Type:	Valid
Description:	The diagnostic in AUTOSAR shall provide source and target address to the external service processor, which is processing the UDS service request.
Rationale:	Sometimes the reaction of service processor implementations on a UDS request depend on the tester (SA) or on the target.
AppliesTo:	AP
Dependencies:	[SRS_Diag_04169]
Use Case:	Flexibility for service processor implementations.

]([RS_Main_00260](#), [RS_Main_00420](#))

[SRS_Diag_04216] Support for multiple Diagnostic Server Instances [

Type:	Valid
Description:	The Diagnostics in AUTOSAR shall be able to handle multiple Diagnostic Server Instances. Each Diagnostic Server Instance shall be addressable by its own set of target address and they shall be almost independent of each other. Exceptions like EcuReset needs to be coordinated between the server instances.
Rationale:	Software on AP is grouped in so called SoftwareClusters, and each cluster shall be diagnosed on its own.
AppliesTo:	AP
Dependencies:	–
Use Case:	Multiple SoftwareClusters deployed on single AP and each SoftwareCluster is diagnosed separately.

]([RS_Main_00260](#), [RS_Main_00420](#))

4.4 Configuration

5 Requirements Tracing

The following tables reference the requirements specified in [?,] and links to the fulfillment of these. Please note that if column "Satisfied by" is empty for a specific requirement this means that this requirement is not fulfilled by this document.

Requirement	Description	Satisfied by
[RS_Main_00011]	AUTOSAR shall support the development of reliable systems	[SRS_Diag_04003] [SRS_Diag_04005] [SRS_Diag_04006] [SRS_Diag_04007] [SRS_Diag_04011] [SRS_Diag_04015] [SRS_Diag_04016] [SRS_Diag_04019] [SRS_Diag_04020] [SRS_Diag_04021] [SRS_Diag_04024] [SRS_Diag_04031] [SRS_Diag_04032] [SRS_Diag_04033] [SRS_Diag_04057] [SRS_Diag_04058] [SRS_Diag_04059] [SRS_Diag_04063] [SRS_Diag_04064] [SRS_Diag_04100] [SRS_Diag_04107] [SRS_Diag_04119] [SRS_Diag_04120] [SRS_Diag_04121] [SRS_Diag_04135] [SRS_Diag_04147] [SRS_Diag_04156] [SRS_Diag_04157] [SRS_Diag_04159] [SRS_Diag_04162] [SRS_Diag_04166] [SRS_Diag_04189] [SRS_Diag_04190] [SRS_Diag_04195] [SRS_Diag_04198] [SRS_Diag_04199] [SRS_Diag_04205] [SRS_Diag_04206] [SRS_Diag_04208] [SRS_Diag_04209] [SRS_Diag_04210] [SRS_Diag_04211] [SRS_Diag_04218] [SRS_Diag_04220] [SRS_Diag_04221] [SRS_Diag_04222] [SRS_Diag_04223] [SRS_Diag_04224]

[RS_Main_00060]	AUTOSAR shall provide a standardized software interface for communication between Applications	[SRS_Diag_04182] [SRS_Diag_04183] [SRS_Diag_04185] [SRS_Diag_04186] [SRS_Diag_04194] [SRS_Diag_04204]
[RS_Main_00130]	AUTOSAR shall provide an abstraction from hardware	[SRS_Diag_04077]
[RS_Main_00170]	AUTOSAR shall provide secure access to ECU data and services	[SRS_Diag_04230] [SRS_Diag_04232] [SRS_Diag_04233] [SRS_Diag_04234] [SRS_Diag_04235] [SRS_Diag_04236] [SRS_Diag_04237] [SRS_Diag_04238] [SRS_Diag_04239] [SRS_Diag_04240]
[RS_Main_00260]	AUTOSAR shall provide diagnostics means during runtime, for production and services purposes	[SRS_Diag_04002] [SRS_Diag_04003] [SRS_Diag_04059] [SRS_Diag_04067] [SRS_Diag_04068] [SRS_Diag_04071] [SRS_Diag_04091] [SRS_Diag_04093] [SRS_Diag_04097] [SRS_Diag_04098] [SRS_Diag_04110] [SRS_Diag_04111] [SRS_Diag_04112] [SRS_Diag_04113] [SRS_Diag_04115] [SRS_Diag_04117] [SRS_Diag_04118] [SRS_Diag_04120] [SRS_Diag_04121] [SRS_Diag_04123] [SRS_Diag_04124] [SRS_Diag_04126] [SRS_Diag_04127] [SRS_Diag_04129] [SRS_Diag_04131] [SRS_Diag_04133] [SRS_Diag_04136] [SRS_Diag_04137] [SRS_Diag_04139] [SRS_Diag_04140] [SRS_Diag_04141] [SRS_Diag_04147] [SRS_Diag_04148] [SRS_Diag_04150] [SRS_Diag_04151] [SRS_Diag_04153] [SRS_Diag_04155] [SRS_Diag_04160] [SRS_Diag_04161] [SRS_Diag_04163] [SRS_Diag_04164] [SRS_Diag_04165] [SRS_Diag_04166] [SRS_Diag_04167] [SRS_Diag_04168] [SRS_Diag_04169] [SRS_Diag_04170] [SRS_Diag_04171] [SRS_Diag_04172] [SRS_Diag_04173] [SRS_Diag_04174] [SRS_Diag_04177] [SRS_Diag_04178] [SRS_Diag_04179] [SRS_Diag_04180] [SRS_Diag_04189] [SRS_Diag_04190] [SRS_Diag_04192] [SRS_Diag_04194] [SRS_Diag_04195] [SRS_Diag_04196] [SRS_Diag_04197] [SRS_Diag_04198] [SRS_Diag_04199] [SRS_Diag_04200] [SRS_Diag_04201] [SRS_Diag_04202] [SRS_Diag_04203] [SRS_Diag_04205] [SRS_Diag_04206] [SRS_Diag_04208] [SRS_Diag_04209]

		[SRS_Diag_04210] [SRS_Diag_04213] [SRS_Diag_04214] [SRS_Diag_04215] [SRS_Diag_04216] [SRS_Diag_04217] [SRS_Diag_04218] [SRS_Diag_04219] [SRS_Diag_04222] [SRS_Diag_04224] [SRS_Diag_04225] [SRS_Diag_04226] [SRS_Diag_04227] [SRS_Diag_04228] [SRS_Diag_04231]
[RS_Main_00420]	AUTOSAR shall use established software standards and consolidate de-facto standards for basic software functionality	[SRS_Diag_04067] [SRS_Diag_04068] [SRS_Diag_04097] [SRS_Diag_04105] [SRS_Diag_04109] [SRS_Diag_04110] [SRS_Diag_04111] [SRS_Diag_04113] [SRS_Diag_04124] [SRS_Diag_04125] [SRS_Diag_04169] [SRS_Diag_04170] [SRS_Diag_04171] [SRS_Diag_04172] [SRS_Diag_04173] [SRS_Diag_04174] [SRS_Diag_04192] [SRS_Diag_04204] [SRS_Diag_04216] [SRS_Diag_04219] [SRS_Diag_04225]
[RS_Main_00440]	AUTOSAR shall standardize access to non-volatile memory	[SRS_Diag_04077]

6 References

6.1 Deliverables of AUTOSAR

1. General Requirements of Basic Software Modules:
AUTOSAR_SRS_BSWGeneral.pdf
2. Specification of the Virtual Functional Bus : *AUTOSAR_EXP_VFB.pdf*
3. Software Standardization Template : *AUTOSAR_TPS_StandardizationTemplate.pdf*

6.2 Related standards and norms

6.2.1 ITEA-EAST

4. D1.5-General Architecture; ITEAEAST-EEA, Version 1.0; chapter 3, page 72 et seq.
5. D2.1-Embedded Basic Software Structure Requirements; ITEAEAST-EEA, Version 1.0 or higher
6. D2.2-Description of existing solutions; ITEA/EAST-EEA, Version 1.0 or higher.

6.2.2 ISO

7. ISO 14229-1 Unified diagnostic services (UDS) Part 1: Specification and Requirements (v.2013)
8. ISO 15031-5 Communication between vehicle and external equipment for emissions related diagnostics Part 5: Emissions related diagnostic services (2005-01-13)
9. ISO 15765-3 Diagnostics on controller area network (CAN) Part 3: Implementation of unified diagnostic services (UDS on CAN) (2004-10-06)
10. ISO 15765-4 Diagnostics on controller area network (CAN) Part 4: Requirements for emissions-related systems (2005-01-04)