

<b>Document Title</b>	Requirements on Operating System Interface
<b>Document Owner</b>	AUTOSAR
<b>Document Responsibility</b>	AUTOSAR
<b>Document Identification No</b>	718

<b>Document Status</b>	published
<b>Part of AUTOSAR Standard</b>	Adaptive Platform
<b>Part of Standard Release</b>	R22-11

<b>Document Change History</b>			
<b>Date</b>	<b>Release</b>	<b>Changed by</b>	<b>Description</b>
2022-11-24	R22-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Changed [<a href="#">RS_OSI_00103</a>] to point to [<a href="#">RS_Main_00060</a>]</li> </ul>
2021-11-25	R21-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Added [<a href="#">RS_OSI_00209</a>]</li> </ul>
2020-11-30	R20-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Uptrace to RS_Safety[1] document</li> <li>Clarified Execution Management description</li> <li>Moved time-triggered execution to RS_ExecutionManagement[2]</li> </ul>
2019-11-28	R19-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Updated document structure</li> <li>Changed Document Status from Final to published</li> </ul>
2019-03-29	19-03	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Added: use case for [<a href="#">RS_OSI_00201</a>] and [<a href="#">RS_OSI_00202</a>]</li> </ul>
2018-10-31	18-10	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Removed: RS_OSI_00102 and RS_OSI_00105</li> <li>Added: [<a href="#">RS_OSI_00207</a>], [<a href="#">RS_OSI_00208</a>].</li> </ul>
2018-03-29	18-03	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Removed: RS_OSI_00101, RS_OSI_00200 and RS_OSI_00205.</li> <li>Added: [<a href="#">RS_OSI_00103</a>].</li> </ul>

2017-10-27	17-10	AUTOSAR Release Management	<ul style="list-style-type: none"><li>• Minor changes, document clean up</li></ul>
2017-03-31	17-03	AUTOSAR Release Management	<ul style="list-style-type: none"><li>• Initial release</li></ul>

## **Disclaimer**

This work (specification and/or software implementation) and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the work.

The material contained in this work is protected by copyright and other types of intellectual property rights. The commercial exploitation of the material contained in this work requires a license to such intellectual property rights.

This work may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the work may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The work has been developed for automotive applications only. It has neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

## Contents

1	Scope of This Document	5
2	Conventions to be Used	6
2.1	Requirements Guidelines	6
2.1.1	Requirements Quality	6
2.1.2	Requirements Identification	6
2.1.3	Requirements Status	6
3	Acronyms and Abbreviations	7
4	Requirements Specification	8
4.1	Functional Overview	8
4.2	Functional Requirements	8
4.2.1	Assumption of Use	8
4.2.2	General Requirements	9
4.2.3	Operating System Requirements	10
4.3	Non-Functional Requirements	13
5	Requirements Tracing	14
6	References	18

# 1 Scope of This Document

This document specifies the requirements of [AUTOSAR Adaptive Platform](#) on the [Operating System](#) that is part of the Foundation in the [AUTOSAR Adaptive Platform](#).

## 2 Conventions to be Used

The representation of requirements in AUTOSAR documents follows the table specified in [TPS\_STDT\_00078], see Standardization Template [3], chapter Support for Traceability.

The verbal forms for the expression of obligation specified in [TPS\_STDT\_00053] shall be used to indicate requirements, see Standardization Template [3], chapter Support for Traceability.

### 2.1 Requirements Guidelines

#### 2.1.1 Requirements Quality

**[RS\_OSI\_NA]{DRAFT}** [These requirements are not applicable as they are not within the scope of this release.] ([RS\\_Main\\_00026](#), [RS\\_Main\\_00030](#), [RS\\_Main\\_00080](#), [RS\\_Main\\_00180](#), [RS\\_Main\\_00190](#), [RS\\_Main\\_00230](#), [RS\\_Main\\_00250](#), [RS\\_Main\\_00260](#), [RS\\_Main\\_00261](#), [RS\\_Main\\_00270](#), [RS\\_Main\\_00280](#), [RS\\_Main\\_00300](#), [RS\\_Main\\_00301](#), [RS\\_Main\\_00310](#), [RS\\_Main\\_00320](#), [RS\\_Main\\_00340](#), [RS\\_Main\\_00350](#), [RS\\_Main\\_00360](#), [RS\\_Main\\_00440](#), [RS\\_Main\\_00445](#), [RS\\_Main\\_00490](#), [RS\\_Main\\_00491](#), [RS\\_Main\\_00500](#), [RS\\_Main\\_00501](#), [RS\\_Main\\_00507](#), [RS\\_Main\\_00510](#), [RS\\_Main\\_00511](#), [RS\\_Main\\_00650](#), [RS\\_Main\\_00653](#), [RS\\_Main\\_01001](#), [RS\\_Main\\_01002](#), [RS\\_Main\\_01003](#), [RS\\_Main\\_01004](#), [RS\\_Main\\_01005](#), [RS\\_Main\\_01007](#), [RS\\_Main\\_01008](#), [RS\\_Main\\_01025](#), [RS\\_Main\\_01026](#))

#### 2.1.2 Requirements Identification

#### 2.1.3 Requirements Status

The following requirements are described within this document but not otherwise considered in this release:

- [\[RS\\_OSI\\_00204\]](#)
- [\[RS\\_OSI\\_00208\]](#)

The functionality described above is subject to modification and will be considered for inclusion in a future release of this document.

### 3 Acronyms and Abbreviations

Abbreviation / Acronym:	Description:
Operating System Interface	A <a href="#">Functional Cluster</a> within the <a href="#">Adaptive Platform Foundation</a> .
AUTOSAR Adaptive Platform	see <a href="#">[4]</a> AUTOSAR Glossary
Adaptive Platform Foundation	see <a href="#">[4]</a> AUTOSAR Glossary
Adaptive Application	see <a href="#">[4]</a> AUTOSAR Glossary
Execution Management	The element of the <a href="#">AUTOSAR Adaptive Platform</a> responsible for the ordered startup and shutdown of the <a href="#">AUTOSAR Adaptive Platform</a> and <a href="#">Adaptive Applications</a> .
Application	see <a href="#">[4]</a> AUTOSAR Glossary
Operating System	Software responsible for managing <a href="#">Processes</a> on a <a href="#">Machine</a> and for providing an interface to hardware resources.
Machine	see <a href="#">[4]</a> AUTOSAR Glossary
Process	see <a href="#">[4]</a> AUTOSAR Glossary
Functional Cluster	see <a href="#">[4]</a> AUTOSAR Glossary

## 4 Requirements Specification

### 4.1 Functional Overview

The [Operating System](#) is responsible for run-time resource management (including time) for all [Applications](#) on and within the [AUTOSAR Adaptive Platform](#). This includes not only the [Adaptive Applications](#) that run on top of ARA provided by [AUTOSAR Adaptive Platform](#), but also the [Functional Clusters](#) that constitute the platform, which are also implemented as [Applications](#). The OS functions in cooperation with [Execution Management](#) which is responsible for platform initialization and the start-up / shut-down of [Applications](#).

Note that this [Operating System Interface](#) (OSI) requirement specification contains two different categories. The first category contains the requirements that are directly needed by the [Adaptive Applications](#). The other category contains the ones that are needed by the [AUTOSAR Adaptive Platform](#) to realize implementation of [Functional Clusters](#), especially the required mechanisms are difficult or inefficient to be implemented by other software entity than the OS. The most notable such [Functional Cluster](#) requiring the various OS mechanisms is [Execution Management](#).

### 4.2 Functional Requirements

This chapter describes all requirements driving the work to define the [Operating Systems](#) functionality.

#### 4.2.1 Assumption of Use

This section describes execution environment of the [AUTOSAR Adaptive Platform](#) that is directly or indirectly used to run the [Applications](#). This execution environment is not requirements to the [AUTOSAR Adaptive Platform](#) in the strict sense, but rather assumptions on properties of [Application](#) running on the [AUTOSAR Adaptive Platform](#). These assumptions are used to motivate the further requirements, and provide hints for [Application](#) developers to check if their use cases are covered in this specification document and which specific requirements are derived from those use cases.

The [Operating System](#) section defines requirements on the [Operating System](#) that processes can consider fulfilled in order to achieve their function.



## 4.2.2 General Requirements

This section describes APIs that should be exposed to processes on the [AUTOSAR Adaptive Platform](#) that closely relates to the [Operating System](#) functionality. Some libraries in the system may be considered by a Developer to be part of the [Operating System](#) without strictly-speaking belonging to it, for example the C++ runtime libraries. For the purpose of this section, the [Operating System](#) kernel and its libraries are considered to be a single entity.

**[RS\_OSI\_00100] The Operating System Interface provided to processes shall provide a PSE51-compliant API. [**

<b>Description:</b>	The foundation of the <a href="#">Operating System</a> provided to the process shall be POSIX-compliant as defined by PSE51.
<b>Rationale:</b>	The defined functionality of the POSIX profile PSE51 defined by IEEE1003.13 [5] is provided by various off-the-shelf operating systems. The PSE51 profile is intended for embedded systems, with a single multi-threaded process, no file system, no user and group support and only selected options from more general IEEE1003.1 [6], which is the well-known POSIX standard. PSE51 offers functions for basic synchronized I/O, high-resolution timer, signals, semaphores, shared memory and threads. As the envisioned <a href="#">Application</a> software components will not require to fork new processes themselves, and only need limited direct access to files, the PSE51 profile is thought to be sufficient.
<b>Dependencies:</b>	–
<b>Use Case:</b>	Application portability.
<b>Supporting Material:</b>	IEEE1003.13 [5] and IEEE1003.1 [6]

]([RS\\_Main\\_00002](#), [RS\\_Main\\_00050](#), [RS\\_Main\\_00150](#), [RS\\_Main\\_00420](#))

**[RS\_OSI\_00103] The Operating System Interface shall support C++. [**

<b>Description:</b>	The <a href="#">Operating System</a> interface shall support C++11.
<b>Rationale:</b>	Processes are written in C++ and interfaces are expected to conform to C++11. Note that the POSIX API consists of C functions which can be invoked from a C++ program.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

]([RS\\_Main\\_00060](#))

**[RS\_OSI\_00104] The Operating System Interface shall support the reaction on process-external stimuli from devices.** [

<b>Description:</b>	The <a href="#">Operating System</a> shall enable processes to react on external stimuli from devices.
<b>Rationale:</b>	<a href="#">Application</a> will react on reception of functional data, signals and timers from the platform. Certain computations shall be executed in reaction on these application-external stimuli.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

] ([RS\\_Main\\_00050](#), [RS\\_Main\\_00060](#), [RS\\_Main\\_00460](#))

**[RS\_OSI\_00105] The Operating System Interface shall support the start of [Execution Management](#).** [

<b>Description:</b>	The <a href="#">Operating System</a> shall provide means to start the <a href="#">Execution Management</a> functional cluster as first process.
<b>Rationale:</b>	<a href="#">Execution Management</a> is responsible for startup and shutdown of all processes of the <a href="#">AUTOSAR Adaptive Platform</a> .
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

] ([RS\\_Main\\_00049](#), [RS\\_Main\\_00460](#))

### 4.2.3 Operating System Requirements

**[RS\_OSI\_00201] The Operating System shall provide mechanisms for system memory budgeting.** [

<b>Description:</b>	The <a href="#">Operating System</a> shall provide mechanisms to configure memory budgeting for each process or for groups of processes.
<b>Rationale:</b>	In order to ensure resource availability in the context of a multi-process system, the system integrator/architect may require a set of tools to configure memory budgeting for each process or for groups of process.
<b>Dependencies:</b>	–
<b>Use Case:</b>	security - protection against DoS attacks - resource starvation types.
<b>Supporting Material:</b>	–

] ([RS\\_Main\\_00002](#), [RS\\_Main\\_00010](#), [RS\\_Main\\_00011](#), [RS\\_Main\\_00012](#), [RS\\_Main\\_00106](#), [RS\\_Main\\_00150](#), [RS\\_Main\\_00514](#), [RS\\_SAF\\_21402](#))

**[RS\_OSI\_00202] The Operating System shall provide mechanisms for CPU time budgeting.** [

<b>Description:</b>	The <a href="#">Operating System</a> shall provide mechanisms to configure resource budgeting in terms of CPU time for each process or group of processes.
<b>Rationale:</b>	In order to ensure schedulability in the context of a multi-process system, the system integrator/architect may require a set of tools to configure CPU time allocated for each process or for groups of processes.
<b>Dependencies:</b>	–
<b>Use Case:</b>	security - protection against DoS attacks - resource starvation types.
<b>Supporting Material:</b>	–

] ([RS\\_Main\\_00002](#), [RS\\_Main\\_00010](#), [RS\\_Main\\_00011](#), [RS\\_Main\\_00012](#), [RS\\_Main\\_00106](#), [RS\\_Main\\_00150](#), [RS\\_Main\\_00514](#), [RS\\_SAF\\_21401](#))

**[RS\_OSI\_00203] The Operating System should provide mechanisms for binding processes to CPU cores.** [

<b>Description:</b>	The <a href="#">Operating System</a> should provide mechanisms for binding individual processes or groups of processes to CPU cores.
<b>Rationale:</b>	In order to ensure correct task schedulability, the system integrator may require a set of tools to configure the CPU affinity of processes. In a multi-core system, it may be relevant to ensure some process can only run on some CPU cores, to allow other less- or differently-restricted processes to concurrently progress.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

] ([RS\\_Main\\_00002](#), [RS\\_Main\\_00010](#), [RS\\_Main\\_00011](#), [RS\\_Main\\_00012](#), [RS\\_Main\\_00050](#), [RS\\_Main\\_00106](#), [RS\\_Main\\_00514](#))

**[RS\_OSI\_00204]{DRAFT} The Operating System shall support authorized operating system object access for the software entities which are allowed to do so.** [

<b>Description:</b>	The <a href="#">Operating System</a> shall provide access rights and permissions mechanisms to achieve secure data access and data exchange.
<b>Rationale:</b>	The <a href="#">Operating System</a> consists of a collection of hardware and software objects, e.g. pipes, files. Safety or/and Security related requirements may be imposed to grant special access rights and permissions in order to avoid unauthorized access to communication channels or to ensure exclusive access to the process-specific data stored persistently.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

] ([RS\\_Main\\_00010](#), [RS\\_Main\\_00170](#), [RS\\_Main\\_00514](#))

**[RS\_OSI\_00206] The Operating System shall provide multi-process support for isolation of applications.** [

<b>Description:</b>	The <a href="#">Operating System</a> shall provide mechanisms to let multiple processes run isolated from each other.
<b>Rationale:</b>	Each process may have a different robustness, safety and security level. As a consequence, an incorrect memory access from one process execution shall not result in a corruption of memory in another process, unless the data area is explicitly shared. In addition, a process may not access or read data from another process without explicit data sharing.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

]([RS\\_Main\\_00010](#), [RS\\_Main\\_00049](#), [RS\\_Main\\_00106](#), [RS\\_SAF\\_21403](#))

**[RS\_OSI\_00207] The Operating System shall provide the capability to share code and data in an implicit manner.** [

<b>Description:</b>	The <a href="#">Operating System</a> shall provide mechanisms to run the same code and associated data copy in multiple processes by using a shared object mechanism, where data is either read-only or a process-private copy.
<b>Rationale:</b>	To allow more efficient memory usage both in runtime memory and non-volatile storage, as well as making platform updates faster, applications may be linked against shared code and data objects. Using shared objects is not intended however to be mandatory for use by the <a href="#">AUTOSAR Adaptive Platform</a> , as security, safety or other constraints may require not to use this feature.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

]([RS\\_Main\\_00410](#), [RS\\_Main\\_00150](#), [RS\\_Main\\_00503](#))

**[RS\_OSI\_00208]{DRAFT} The Operating System shall only allow processes to access required functionality.** [

<b>Description:</b>	The <a href="#">Operating System</a> shall ensure that either a process does not access operating system functionality via a system call at all, or the system call has to be authorized.
<b>Rationale:</b>	A process with full access to the Platform could cause significant damage.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	This requirement was visible before 18-10 Specification Release as <a href="#">[RS_SEC_05009]</a> .

]([RS\\_Main\\_00010](#), [RS\\_Main\\_00514](#))

**[RS\_OSI\_00209]{DRAFT} The [Operating System](#) shall support error handling including unrecoverable errors. [**

<b>Description:</b>	The <a href="#">Operating System</a> shall support error handling including unrecoverable errors.
<b>Rationale:</b>	The operating system may face conditions where has no mechanism to recover the system. These situations are typically expected to result from a misconfigured system and therefore a suitable response might be to halt startup so that the misconfiguration can be resolved outside of the OS context.
<b>Dependencies:</b>	–
<b>Use Case:</b>	The Operating System can not start EM and hence the platform as a whole cannot be started - it is not possible to recover from this situation hence The OS shall halt startup.
<b>Supporting Material:</b>	This requirement was visible before 18-10 Specification Release as [RS_SEC_05009].

]([RS\\_Main\\_00010](#), [RS\\_Main\\_00514](#))

### 4.3 Non-Functional Requirements

No content.

## 5 Requirements Tracing

The following tables reference the requirements specified in [7] and links to the fulfillment of these. Please note that if column “Satisfied by” is empty for a specific requirement this means that this requirement is not fulfilled by this document.

Requirement	Description	Satisfied by
[RS_Main_00002]	AUTOSAR shall provide a software platform for high performance computing platforms	<a href="#">[RS_OSI_00100]</a> <a href="#">[RS_OSI_00201]</a> <a href="#">[RS_OSI_00202]</a> <a href="#">[RS_OSI_00203]</a>
[RS_Main_00010]	Safety Mechanisms	<a href="#">[RS_OSI_00201]</a> <a href="#">[RS_OSI_00202]</a> <a href="#">[RS_OSI_00203]</a> <a href="#">[RS_OSI_00204]</a> <a href="#">[RS_OSI_00206]</a> <a href="#">[RS_OSI_00208]</a> <a href="#">[RS_OSI_00209]</a>
[RS_Main_00011]	Mechanisms for Reliable Systems	<a href="#">[RS_OSI_00201]</a> <a href="#">[RS_OSI_00202]</a> <a href="#">[RS_OSI_00203]</a>
[RS_Main_00012]	Highly Available Systems Support	<a href="#">[RS_OSI_00201]</a> <a href="#">[RS_OSI_00202]</a> <a href="#">[RS_OSI_00203]</a>
[RS_Main_00026]	AUTOSAR shall support high speed and high bandwidth communication between executed SW	<a href="#">[RS_OSI_NA]</a>
[RS_Main_00030]	Safety Related Process Support	<a href="#">[RS_OSI_NA]</a>
[RS_Main_00049]	AUTOSAR shall provide an Execution Management for running multiple applications	<a href="#">[RS_OSI_00105]</a> <a href="#">[RS_OSI_00206]</a>
[RS_Main_00050]	AUTOSAR shall provide an Execution Framework towards applications to implement concurrent application internal control flows	<a href="#">[RS_OSI_00100]</a> <a href="#">[RS_OSI_00104]</a> <a href="#">[RS_OSI_00203]</a>
[RS_Main_00060]	Standardized Application Communication Interface	<a href="#">[RS_OSI_00103]</a> <a href="#">[RS_OSI_00104]</a>
[RS_Main_00080]	Formal Description Language	<a href="#">[RS_OSI_NA]</a>
[RS_Main_00106]	AUTOSAR shall provide the possibility to extend the software with new SWCs without recompiling the platform foundation	<a href="#">[RS_OSI_00201]</a> <a href="#">[RS_OSI_00202]</a> <a href="#">[RS_OSI_00203]</a> <a href="#">[RS_OSI_00206]</a>
[RS_Main_00150]	AUTOSAR shall support the deployment and reallocation of AUTOSAR Application Software	<a href="#">[RS_OSI_00100]</a> <a href="#">[RS_OSI_00201]</a> <a href="#">[RS_OSI_00202]</a> <a href="#">[RS_OSI_00207]</a>
[RS_Main_00170]	AUTOSAR shall provide secure access to ECU data and services	<a href="#">[RS_OSI_00204]</a>
[RS_Main_00180]	Intellectual Property Protection	<a href="#">[RS_OSI_NA]</a>
[RS_Main_00190]	Non-AUTOSAR Software Integration	<a href="#">[RS_OSI_NA]</a>
[RS_Main_00230]	Network Technology Support	<a href="#">[RS_OSI_NA]</a>

Requirement	Description	Satisfied by
[RS_Main_00250]	AUTOSAR methodology shall provide a predefinition of typical roles and activities	[RS_OSI_NA]
[RS_Main_00260]	Runtime Diagnostics Means	[RS_OSI_NA]
[RS_Main_00261]	AUTOSAR shall provide means for calibration	[RS_OSI_NA]
[RS_Main_00270]	Backward Compatibility	[RS_OSI_NA]
[RS_Main_00280]	Standardized Automotive Communication Protocols	[RS_OSI_NA]
[RS_Main_00300]	AUTOSAR shall provide data exchange formats to support work-share in large inter and intra company development groups	[RS_OSI_NA]
[RS_Main_00301]	AUTOSAR shall specify profiles for data exchange to support work-share in large inter- and intra-company development groups	[RS_OSI_NA]
[RS_Main_00310]	AUTOSAR shall support hierarchical Application Software design methods	[RS_OSI_NA]
[RS_Main_00320]	AUTOSAR shall provide formats to specify system development	[RS_OSI_NA]
[RS_Main_00340]	AUTOSAR shall support the continuous timing requirement analysis	[RS_OSI_NA]
[RS_Main_00350]	Documented Software Architecture	[RS_OSI_NA]
[RS_Main_00360]	Variant Management Support	[RS_OSI_NA]
[RS_Main_00410]	AUTOSAR shall provide specifications for routines commonly used by Application Software to support sharing and optimization	[RS_OSI_00207]
[RS_Main_00420]	AUTOSAR shall use established software standards and consolidate de-facto standards for basic software functionality	[RS_OSI_00100]
[RS_Main_00440]	AUTOSAR shall standardize access to non-volatile memory	[RS_OSI_NA]
[RS_Main_00445]	AUTOSAR shall standardize access to crypto-specific HW and SW	[RS_OSI_NA]
[RS_Main_00460]	AUTOSAR shall standardize methods to organize mode management on Application, ECU and System level	[RS_OSI_00104] [RS_OSI_00105]
[RS_Main_00490]	AUTOSAR processes shall be compliant to ISO26262	[RS_OSI_NA]
[RS_Main_00491]	Function Monitoring	[RS_OSI_NA]

Requirement	Description	Satisfied by
[RS_Main_00500]	AUTOSAR shall provide naming conventions	[RS_OSI_NA]
[RS_Main_00501]	AUTOSAR shall support redundancy concepts	[RS_OSI_NA]
[RS_Main_00503]	AUTOSAR shall support change of communication and application software at runtime.	[RS_OSI_00207]
[RS_Main_00507]	Development Collaboration Support	[RS_OSI_NA]
[RS_Main_00510]	Secure Onboard Communication	[RS_OSI_NA]
[RS_Main_00511]	AUTOSAR shall support virtualization	[RS_OSI_NA]
[RS_Main_00514]	System Security Support	[RS_OSI_00201] [RS_OSI_00202] [RS_OSI_00203] [RS_OSI_00204] [RS_OSI_00208] [RS_OSI_00209]
[RS_Main_00650]	AUTOSAR shall support up - and download of data and software	[RS_OSI_NA]
[RS_Main_00653]	Means for Functional Modeling	[RS_OSI_NA]
[RS_Main_01001]	Intra ECU Communication Support	[RS_OSI_NA]
[RS_Main_01002]	AUTOSAR shall support service-oriented communication	[RS_OSI_NA]
[RS_Main_01003]	AUTOSAR shall support data-oriented communication	[RS_OSI_NA]
[RS_Main_01004]	AUTOSAR shall support standards for wireless off-board communication	[RS_OSI_NA]
[RS_Main_01005]	AUTOSAR shall establish communication paths dynamically	[RS_OSI_NA]
[RS_Main_01007]	AUTOSAR communication shall assure quality of service on communication	[RS_OSI_NA]
[RS_Main_01008]	AUTOSAR shall provide secure communication with off-board entities	[RS_OSI_NA]
[RS_Main_01025]	AUTOSAR shall support debugging of software on the target and onboard	[RS_OSI_NA]
[RS_Main_01026]	AUTOSAR shall support tracing and profiling on the target and onboard	[RS_OSI_NA]
[RS_SAF_21401]	The OS shall support a mechanism that prevents starvation of applications or processes on the basis of CPU usage (under the respect of available resources).	[RS_OSI_00202]



Requirement	Description	Satisfied by
[RS_SAF_21402]	The OS shall support resource reservation for memory in the interval [min,max]. If max is not specified it shall be considered as unlimited.	[RS_OSI_00201]
[RS_SAF_21403]	Operating System shall ensure that only allowed memory accesses are made.	[RS_OSI_00206]

## 6 References

- [1] Safety Requirements for AUTOSAR Adaptive Platform and AUTOSAR Classic Platform  
AUTOSAR\_RS\_Safety
- [2] Requirements on Execution Management  
AUTOSAR\_RS\_ExecutionManagement
- [3] Standardization Template  
AUTOSAR\_TPS\_StandardizationTemplate
- [4] Glossary  
AUTOSAR\_TR\_Glossary
- [5] IEEE Standard for Information Technology- Standardized Application Environment Profile (AEP)-POSIX Realtime and Embedded Application Support  
<https://standards.ieee.org/findstds/standard/1003.13-2003.html>
- [6] Standard for Information Technology–Portable Operating System Interface (POSIX(R)) Base Specifications, Issue 7  
<http://pubs.opengroup.org/onlinepubs/9699919799/>
- [7] Main Requirements  
AUTOSAR\_RS\_Main