

Document Title	General Requirements on SPAL
Document Owner	AUTOSAR
Document Responsibility	AUTOSAR
Document Identification No	9

Document Status	published
Part of AUTOSAR Standard	Classic Platform
Part of Standard Release	R23-11

Document Change History			
Date	Release	Changed by	Description
2023-11-23	R23-11	AUTOSAR Release Management	<ul style="list-style-type: none"> • Editorial changes
2022-11-24	R22-11	AUTOSAR Release Management	<ul style="list-style-type: none"> • No content changes
2021-11-25	R21-11	AUTOSAR Release Management	<ul style="list-style-type: none"> • No content changes
2020-11-30	R20-11	AUTOSAR Release Management	<ul style="list-style-type: none"> • No content changes
2019-11-28	R19-11	AUTOSAR Release Management	<ul style="list-style-type: none"> • No content changes • Changed Document Status from Final to published
2018-10-31	4.4.0	AUTOSAR Release Management	<ul style="list-style-type: none"> • Editorial changes
2017-12-08	4.3.1	AUTOSAR Release Management	<ul style="list-style-type: none"> • SRS requirements refer to BMW specifications removed • Removed references to HIS • minor corrections / clarifications / editorial changes; for details please refer to the ChangeDocumentation
2016-11-30	4.3.0	AUTOSAR Release Management	<ul style="list-style-type: none"> • Editorial changes



△

2014-10-31	4.2.1	AUTOSAR Release Management	<ul style="list-style-type: none"> • Editorial changes
2013-03-15	4.1.1	AUTOSAR Administration	<ul style="list-style-type: none"> • Link Requirement with BSW Feature Document • Updating format of requirements according to TPS StandardizationTemplate
2010-09-30	3.1.5	AUTOSAR Administration	<ul style="list-style-type: none"> • Changes in SRS SPAL 12461: removed “All other registers shall be initialized by the start-up code” from description
2010-02-02	3.1.4	AUTOSAR Administration	<ul style="list-style-type: none"> • Legal disclaimer revised
2008-08-13	3.1.1	AUTOSAR Administration	<ul style="list-style-type: none"> • Legal disclaimer revised
2007-12-21	3.0.1	AUTOSAR Administration	<ul style="list-style-type: none"> • Document meta information extended • Small layout adaptations made
2007-01-24	2.1.15	AUTOSAR Administration	<ul style="list-style-type: none"> • Updated the use case in SRS SPAL 12092 • Deleted the supporting material in SRS SPAL 12077 since it was referencing a rejected requirement BSW12161 • Legal disclaimer revised • “Advice for users” revised • “Revision Information” added
2006-05-16	2.0	AUTOSAR Administration	<ul style="list-style-type: none"> • Split the document. Each SPAL driver now has its own requirements document • Changed the wake-up requirements • Added 3 requirements • Changed 9 requirements • Rejected 5 requirements
2005-05-31	1.0	AUTOSAR Administration	<ul style="list-style-type: none"> • Initial release

Disclaimer

This work (specification and/or software implementation) and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the work.

The material contained in this work is protected by copyright and other types of intellectual property rights. The commercial exploitation of the material contained in this work requires a license to such intellectual property rights.

This work may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the work may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The work has been developed for automotive applications only. It has neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

Contents

1	Scope of Document	5
2	Requirements Guidelines	6
2.1	Conventions used	6
2.2	Requirements quality	7
2.3	Requirements identification	7
2.4	Requirements status	7
3	Acronyms and abbreviations	9
4	Conceptual Issues	10
4.1	General Rules	10
4.2	List of drivers not affected by the clock frequency	10
4.3	MCAL relevant ECU Power Modes	10
4.4	Wake-up Scenarios	10
4.5	Scheduling and integration of drivers	11
5	Requirements Specification	12
5.1	Functional Requirements	12
5.1.1	General Requirements	12
5.1.1.1	Configuration	12
5.1.1.2	Initialization	13
5.1.1.3	Normal Operation	16
5.1.1.4	Fault Operation	18
5.1.1.5	Shutdown Operation	19
5.2	Non-Functional Requirements (Qualities)	20
5.2.1	Timing requirements	20
5.2.2	Software design requirements	20
5.2.3	Process requirements	21
6	Requirements Tracing	22
7	References	23

1 Scope of Document

This document specifies general requirements on Basic Software Modules of the following software layers:

- Microcontroller Abstraction Layer
- ECU Abstraction Layer

Those modules are of the following type:

- Drivers for μ C-internal and external peripherals
- Handlers
- Interfaces

The selection of modules is derived from the WP Architecture BSW Module List and Layered Architecture. The following modules are in scope:

- Memory drivers and interfaces (internal/external EEPROM, Flash, Flash EEPROM Emulation)
- I/O drivers (PORT, ADC, DIO, PWM, ICU, OCU)
- I/O Hardware Abstraction
- ECU onboard communication drivers and handlers (SPI)
- System drivers (internal/external Watchdog, MCU, GPT, RAM test)

Constraints

First scope for specification of requirements on basic software modules are systems which are not safety relevant. For this reason safety requirements are assigned to medium priority.

2 Requirements Guidelines

Existing specifications shall be referenced (in form of a single requirement). Differences to these specifications are specified as additional requirements.

2.1 Conventions used

- The representation of requirements in AUTOSAR documents follows the table specified in [1].
- In requirements, the following specific semantics are used (taken from Request for Comment RFC 2119 from the Internet Engineering Task Force IETF)

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as follows.

Note that the requirement level of the document in which they are used modifies the force of these words.

- **MUST:** This word, or the adjective "LEGALLY REQUIRED", means that the definition is an absolute requirement of the specification due to legal issues.
- **MUST NOT:** This phrase, or the phrase "MUST NOT", means that the definition is an absolute prohibition of the specification due to legal issues.
- **SHALL:** This phrase, or the adjective "REQUIRED", means that the definition is an absolute requirement of the specification.
- **SHALL NOT:** This phrase means that the definition is an absolute prohibition of the specification.
- **SHOULD:** This word, or the adjective "RECOMMENDED", means that there may exist valid reasons in particular circumstances to ignore a particular item, but the full implications must be understood and carefully weighed before choosing a different course.
- **SHOULD NOT:** This phrase, or the phrase "NOT RECOMMENDED", means that there may exist valid reasons in particular circumstances when the particular behavior is acceptable or even useful, but the full implications should be understood and the case carefully weighed before implementing any behavior described with this label.
- **MAY:** This word, or the adjective "OPTIONAL", means that an item is truly optional. One vendor may choose to include the item because a particular marketplace requires it or because the vendor feels that it enhances the product while another vendor may omit the same item.

An implementation, which does not include a particular option, SHALL be prepared to interoperate with another implementation, which does include the option, though perhaps with reduced functionality. In the same vein an implementation, which does include a particular option, SHALL be prepared to interoperate with another implementation, which does not include the option (except, of course, for the feature the option provides.)

2.2 Requirements quality

All Requirements shall have the following properties:

- Redundancy

Requirements shall not be repeated within one requirement or in other requirements

- Clearness

All requirements shall allow one possibility of interpretation only. Only technical terms of the glossary may be used.

- Atomicity

Each Requirement shall only contain one requirement. A Requirement is atomic if it cannot be split up in further requirements.

- Testability

Requirements shall be testable by analysis, review or test.

- Traceability

The source and status of a requirement shall be visible at all times.

2.3 Requirements identification

Each requirement has its unique identifier starting with the prefix "BSW" (for "Basic Software"). For any review annotations, remarks or questions please refer to this unique ID rather than chapter or page numbers!

2.4 Requirements status

Each chapter shall be structured in the following way:

Functional Requirements:

- Configuration (which elements of the module need to be configurable)

- Initialization
- Normal Operation
- Shutdown Operation
- Fault Operation
- ...

Non-Functional Requirements:

- Timing Requirements
- Resource Usage
- Usability
- Output for other WPs (e.g. Description Templates, Tooling,...)
- ...

3 Acronyms and abbreviations

The glossary below includes acronyms and abbreviations relevant to General Requirements on SPAL that are not included in the AUTOSAR Glossary [2].

Abbreviation / Acronym:	Description:
CS	Chip Select
DIO	Digital Input Output
ECU	Electric Control Unit
ICU	Interrupt Capture Unit
MAL	Old name of Microcontroller Abstraction Layer (replaced by MCAL because 'MAL' is a French term meaning 'bad')
MCAL	Microcontroller Abstraction Layer
MCU	Microcontroller Unit
MMU	Memory Management Unit
Master	A device controlling other devices (slaves, see below)
Slave	A device being completely controlled by a master device
NMI	Non Maskable Interrupt
OS	Operating System
OCU	Output Compare Unit
PLL	Phase Locked Loop
PWM	Pulse Width Modulation
RX	Reception (in the context of bus communication)
SPAL	Standard Peripheral Abstraction Layer (The name of this working group)
SFR	Special Function Register
RTE	Runtime Environment
WP	Work Package
STD	Standard
REQ	Requirement
UNINIT	Uninitialized (= not initialized)

Table 3.1: Acronyms and abbreviations used in the scope of this Document

As this is a document from professionals for professionals, all other terms are expected to be known.

4 Conceptual Issues

4.1 General Rules

1. Don't do anything within our callbacks that exceeds 50 μ s runtime this will affect the system performance too much.
2. Each driver specification is designed so that the driver itself will take care of atomicity and data integrity for data inside of the driver.
3. Application buffers shall be passed as pointers from the user to the driver.

4.2 List of drivers not affected by the clock frequency

The clock frequency is a parameter that has a very large influence to most of the drivers included in WP "Specification / Standardization of BSW". Below is a list of the software modules that do not have a direct dependency on the clock frequency:

- PORT
- DIO
- RAM test

Conclusion: Most of the drivers have a strong dependency of the clock frequency therefore it is very important to carefully consider the influence across the whole system when configuring each software component.

4.3 MCAL relevant ECU Power Modes

The drivers included in WP "Specification / Standardization of BSW" shall support the ECU power modes defined in the Specification of ECU State Manager.

Different clock modes have to be supported. All drivers shall support re-initialization with different configuration settings. Please refer to the document "ECU State Manager".

4.4 Wake-up Scenarios

Due to different timing requirements (e.g. ECUs that wake up cyclically and only check some inputs and go to sleep again as fast as possible) different initialization procedures are necessary. Examples:

- Initialization after Wake-up

- Initialization after Power On Reset

Conclusion: It is not possible to have a standard wake-up sequence. This sequence depends on the microcontroller hardware and the system requirements. Current specified concept allows for a standardized way to handle wake-up signaling and offers the possibility to customize the actual wake-up sequence.

4.5 Scheduling and integration of drivers

Today, 90% of the functions of known ECUs are scheduled cooperatively. Reasons are:

- Technical: Lower overhead (task switch time and task stack consumption) in comparison to pre-emptive systems
- Technical: Better possibility to create a deterministic behavior
- Technical: It is easier to reach stable 95% system load with a cooperative system than with a full pre-emptive
- Historical: Many ECUs are using a cooperative scheduling concept

For this reason, all drivers shall allow to be used within a cooperatively scheduled system. They shall not implement blocking code and expect that they are pre-empted by the operating system. Implementation hint: use state machines instead of linear code.

5 Requirements Specification

5.1 Functional Requirements

5.1.1 General Requirements

This chapter contains general requirements which apply to all modules of the Microcontroller and ECU Abstraction Layers, but not necessarily to Basic Software Modules of other layers.

5.1.1.1 Configuration

[SRS_SPAL_12263] The implementation of all driver modules shall allow the configuration of specific module parameter types at link time [

Description:	The implementation of all driver modules shall allow the configuration of the following module parameter types at link time: <ul style="list-style-type: none"> • values written to hardware registers • values used within the driver module (e.g. timings) • callback functions Those parameters shall be placed in a module external initialization data structure.
Rationale:	Delivery of driver modules as object code
Use Case:	Internal development models of e.g. SVDO and Hella
Dependencies:	[SRS_SPAL_12264] Specification of configuration items
Supporting Material:	Sophisticated software design techniques are necessary to achieve similar scalability and resource efficiency like source code.

]()

[SRS_SPAL_12056] All driver modules shall allow the static configuration of notification mechanism [

Description:	All driver modules shall allow the static configuration of notification mechanisms. Pointers to callback functions shall not be passed via the API.
Rationale:	Flexibility and scalability
Use Case:	Give the possibility to run a driver within a protected operating system. Callbacks passed by the API and "pointing anywhere" cannot be used within a protected OS. MISRA recommends avoiding dynamic pointers to functions.
Dependencies:	–





Supporting Material:	–
-----------------------------	---

](RS_BRF_01064)

[SRS_SPAL_12267] Wakeup sources shall be initialized by MCAL drivers and/or the MCU driver [

Description:	Wakeup sources shall be initialized by MCAL drivers and/or the MCU driver. Possible wake-up sources are e.g. reset, watchdog, NMI, interrupt etc.
Rationale:	Allow the configuration of MCU to wake-up.
Use Case:	The GPT interrupt is enabled by the GPT driver and should wake-up the MCU from Idle/Sleep/Stop mode.
Dependencies:	–
Supporting Material:	–

](RS_BRF_01104, RS_BRF_01496)

5.1.1.2 Initialization

[SRS_SPAL_12057] All driver modules shall implement an interface for initialization [

Description:	All driver modules shall implement an interface for initialization. This service shall initialize all module global variables and those SFRs that are used by this module.
Rationale:	Basic functionality.
Use Case:	–
Dependencies:	[SRS_SPAL_12125] Initialization of hardware resources
Supporting Material:	–

](RS_BRF_01096)

[SRS_SPAL_12125] All driver modules shall only initialize the configured resources [

Description:	All driver modules shall only initialize the configured resources. Resources that are not configured in the configuration file shall not be touched.
Rationale:	Allow integration with complex drivers without resource conflicts.
Use Case:	Timer channels 0..3 are used by the GPT driver, timer channels 4..6 are used by complex drivers
Dependencies:	[SRS_SPAL_12057] Driver module initialization





Supporting Material:	–
-----------------------------	---

](RS_BRF_01096)

[SRS_SPAL_12163] All driver modules shall implement an interface for de-initialization [

Description:	All driver modules shall implement an interface for de-initialization. This service shall reset all module global variables and all SFRs that are used by this module to their default reset value. Values of registers which are not writeable are excluded.
Rationale:	Shut down the module. Create the same conditions like before initialization. Empty queues.
Use Case:	–
Dependencies:	–

](RS_BRF_01096)

[SRS_SPAL_12461] Specific rules regarding initialization of controller registers shall apply to all driver implementations [

Description:	The following rules regarding initialization of controller registers shall apply to all driver implementations: 1. If the hardware allows for only one usage of the register, the driver module implementing that functionality is responsible for initializing the register 2. If the register can affect several hardware modules and if it is an I/O register it shall be initialized by the PORT driver 3. If the register can affect several hardware modules and if it is not an I/O register it shall be initialized by the MCU driver 4. One-time writable registers that require initialization directly after reset shall be initialized by the startup code
Rationale:	Unambiguous initialization of controller registers, no changes in driver implementation needed for different configurations.
Use Case:	1. All registers concerning the flash module shall be initialized by the flash driver 2. I/O Registers that can be used either for CAN, ADC or DIO shall be initialized by the PORT driver 3. Registers that affect the clock settings of different hardware modules shall be initialized by the MCU driver 4. Registers affecting the mapping of the register set, RAM or EEPROM shall be initialized in the startup code
Dependencies:	–





Supporting Material:	I/O register: Everything that can affect the functionality of a port pin.
-----------------------------	---

](RS_BRF_01096)

[SRS_SPAL_12462] The register initialization settings shall be published [

Description:	The implementers of the respective driver modules have to publish all register initialization settings in the driver modules documentation.
Rationale:	The configurator (human or tool responsible for configuring the software) needs to get the register settings of the register that are not initialized directly by the driver
Use Case:	–
Dependencies:	SRS_SPAL_12461
Supporting Material:	–

]()

[SRS_SPAL_12463] The register initialization settings shall be combined and forwarded [

Description:	The configurator shall combine all initialization settings from different drivers and check them for consistency (dependency and conflict). If this check is successful it shall forward those combined settings to the module that is responsible for initializing the hardware. If there are any inconsistencies, the configurator has to raise an error and the system build process has to be restarted.
Rationale:	Make sure all controller registers are used in a consistent way and all driver requirements on register initialization settings are fulfilled.
Use Case:	–
Dependencies:	[SRS_SPAL_12461], [SRS_SPAL_12462]
Supporting Material:	–

](RS_BRF_01096)

[SRS_SPAL_12068] The modules of the MCAL shall be initialized in a defined sequence [

Description:	The modules of the MCAL shall be initialized in the following sequence: 1. disable global interrupts 2. initialize overall registers (MCAL system module) 3. initialize all drivers 4. global interrupts may be enabled
---------------------	---





Rationale:	Defined initialization sequence without side effects.
Use Case:	Power On Reset
Dependencies:	–
Supporting Material:	–

](RS_BRF_01096)

[SRS_SPAL_12069] All drivers of the SPAL that wake up from a wake-up interrupt shall report the wake-up reason [

Description:	<p>All drivers of the SPAL that wake up from a wake-up interrupt shall report the wake-up reason to the ECU State Manager via the IO hardware abstraction.</p> <p>Notifications come from SPAL-drivers and shall be handled within the IO hardware abstraction module before the wake up reason is sent to the ECU state manager.</p> <p>Implementation hint: Usually this notification is done from the ISR of the wake-up.</p>
Rationale:	The ECU State Manager needs the wake-up reason. It allows guaranteeing low consumption. For the ICU for instance, it avoids the report of non valid wake-up reasons (spikes).
Use Case:	The ISR of the associated wake-up interrupt calls the wake-up report function of the ECU State Manager if wake-up occurs.
Dependencies:	–
Supporting Material:	–

](RS_BRF_01104)

5.1.1.3 Normal Operation

[SRS_SPAL_00157] All drivers and handlers of the AUTOSAR Basic Software shall implement notification mechanisms of drivers and handlers [

Description:	<p>All drivers and handlers of the AUTOSAR Basic Software shall implement the following notification mechanisms (configurable per module) for use within the Basic Software:</p> <ul style="list-style-type: none"> • Polling (by reading a status information) • Callback functions • Error reporting function of the Default Error Tracer • Event reporting function of the Diagnostic Event Manager
---------------------	--



△

Rationale:	Flexible integration Avoidance of strong coupling and dependencies
Use Case:	The completion of an EEPROM write command can be signaled via a callback function or by setting status information (which is accessible via the module interface). A fault occurred during EEPROM writing (cell defective) can be signaled to the Diagnostic Event Manager.
Dependencies:	Review annotation #35 of Mr. Schumpelt/Bosch
Supporting Material:	–

]([RS_BRF_01064](#), [RS_BRF_02232](#), [RS_BRF_02168](#))

[SRS_SPAL_12169] All driver modules that provide different operation modes shall provide a service for mode selection [

Description:	All driver modules that provide different operation modes shall provide a service for mode selection. This service allows switching from one operation mode to another operation mode without the need of de-initialization and new initialization.
Rationale:	Allow operation mode changes where a full de-initialization and a new initialization would cause not desired artifacts.
Use Case:	Switch EEPROM driver from normal mode to burst mode
Dependencies:	[SRS_SPAL_12064] Change of operation mode during running operation
Supporting Material:	–

]()

[SRS_SPAL_12063] All driver modules shall only support raw value mode [

Description:	All driver modules shall only support raw value mode. In this mode values passed via the API services are used directly without further scaling.
Rationale:	Scaling and adaptation to physical values is task of the ECU Abstraction Layer. Raw value mode provides the highest performance.
Use Case:	The I/O Hardware Abstraction converts a raw ADC value to a scaled value (e.g. voltage) and the other way round.
Dependencies:	–
Supporting Material:	–

]()

[SRS_SPAL_12075] All drivers with random streaming capabilities shall use application buffers [

Description:	All drivers with random streaming capabilities (memory drivers) shall use application buffers. The caller shall not change the data during job processing of the driver.
Rationale:	Minimal RAM consumption, runtime efficiency
Use Case:	The EEPROM write service gets a pointer to the source data to be written. During EEPROM write operation the driver reads data from the application buffer. The EEPROM driver does not provide an own data buffer.
Dependencies:	–
Supporting Material:	–

]()

[SRS_SPAL_12129] The ISRs shall be responsible for resetting the interrupt flags and calling the according notification function [

Description:	The ISRs shall be responsible for resetting the interrupt flags and calling the according notification function.
Rationale:	The notification functions can be user defined and therefore not allowed to have direct access to hardware.
Use Case:	–
Dependencies:	–
Supporting Material:	–

]()

5.1.1.4 Fault Operation

[SRS_SPAL_12064] All driver modules shall raise an error if the change of the operation mode leads to degradation of running operations [

Description:	All driver modules shall raise an error if the change of the operation mode leads to degradation of running operations. The running operation shall be maintained. Further comment: This error condition shall never happen in correct system designs.
Rationale:	–
Use Case:	The SPI EEPROM operation mode is valid during a running SPI communication sequence.
Dependencies:	[SRS_SPAL_12169] Control of operation mode





Supporting Material:	–
-----------------------------	---

]([RS_BRF_02168](#), [RS_BRF_01440](#))

[SRS_SPAL_12448] All driver modules shall have a specific behavior after a development error detection [

Description:	In case of a development error detection, all driver modules shall <ul style="list-style-type: none"> • report the error to the Default Error Tracer (DET) • skip the desired functionality (leave service without any action) • in case of standard return value return E_NOT_OK • in case of arbitrary return values (e.g. Dio_ReadPort) return 0
Rationale:	Uniform behavior of all SPAL modules. Avoid processing of wrong API parameters and thus avoid damage to hardware or dangerous system behavior.
Use Case:	The development error detection is enabled for a Driver. The driver service is called with a faulty input parameter value. The service shall NOT process the command (which might result in a serious malfunction).
Dependencies:	[SRS_SPAL_00157] Notification mechanisms of drivers and handlers
Supporting Material:	–

]([RS_BRF_02232](#))

5.1.1.5 Shutdown Operation

[SRS_SPAL_12067] All driver modules shall set their wake-up conditions depending on the selected operation mode [

Description:	All driver modules shall set their wake-up conditions depending on the selected operation mode.
Rationale:	Allow enabling of module specific wake-up interrupts.
Use Case:	Example: The ECU state manager switches the ECU power mode to 'ECU_POWERMODE_SLEEP'. The modules 'GPT' and 'ICU' enable specific wake-up interrupts according to their configuration related to 'ECU_POWERMODE_SLEEP'.
Dependencies:	[SRS_SPAL_12169] Control of operation mode
Supporting Material:	–

]([RS_BRF_01104](#))

5.2 Non-Functional Requirements (Qualities)

5.2.1 Timing requirements

[SRS_SPAL_12077] All drivers shall provide a non blocking implementation [

Description:	All drivers shall provide a non blocking implementation. Note: 'blocking implementation' in this requirement means 'insensible, uncooperative usage of processor time' like long term loops.
Rationale:	Avoid undetermined waiting times. Allow all drivers to be used within a cooperatively scheduled system.
Use Case:	The waiting loop for the 'ADC Conversion Ready Flag' shall have an additional timeout condition.
Dependencies:	–
Supporting Material:	–

]()

[SRS_SPAL_12078] The drivers shall be coded in a way that is most efficient in terms of memory and runtime resources [

Description:	The drivers shall be coded in a way that is most efficient in terms of memory and runtime resources.
Rationale:	Avoid waste of resources.
Use Case:	Usage of the driver in embedded automotive systems.
Dependencies:	–
Supporting Material:	–

]()

5.2.2 Software design requirements

[SRS_SPAL_12092] The driver's API shall be accessed by its handler or manager [

Description:	If a driver is controlled by a handler or a manager, it is not allowed to bypass the handler/manager and access the driver's API directly. If a driver does not have a handler/manager above, it may be accessed directly.
Rationale:	Consistent access. Handlers and Managers shall not be bypassed.



△

Use Case:	The EEPROM driver is controlled exclusively by the NVRAM Manager via the EEPROM Abstraction module and the Memory Abstraction Interface. No other form of access to the EEPROM driver's API shall be allowed.
Dependencies:	–
Supporting Material:	–

]()

[SRS_SPAL_12265] Configuration data shall be kept constant [

Description:	The contents of the init structure passed to the module via the init function shall be kept constant and available during runtime. Comment: Usually, this init data structure is located in ROM.
Rationale:	The module could access this structure at any time.
Use Case:	–
Dependencies:	–
Supporting Material:	–

] ([RS_BRF_01152](#))

5.2.3 Process requirements

[SRS_SPAL_12264] Specification of configuration items shall be provided [

Description:	The SWS (software specification) shall specify for each configuration element <ul style="list-style-type: none"> • whether it is configurable before or after compile time • where this configuration item is located (init data structure, configuration header file *_Cfg.h)
Rationale:	Enable correct implementation of configuration parameters that allow for object code delivery
Use Case:	–
Dependencies:	[SRS_SPAL_12263] Configuration after compile time
Supporting Material:	–

]()

6 Requirements Tracing

The following table references the features specified in [3] and links to the fulfillments of these.

Requirement	Description	Satisfied by
[RS_BRF_01064]	AUTOSAR BSW shall provide callback functions in order to access upper layer modules	[SRS_SPAL_00157] [SRS_SPAL_12056]
[RS_BRF_01096]	AUTOSAR shall support start-up and shutdown of ECUs	[SRS_SPAL_12057] [SRS_SPAL_12068] [SRS_SPAL_12125] [SRS_SPAL_12163] [SRS_SPAL_12461] [SRS_SPAL_12463]
[RS_BRF_01104]	AUTOSAR shall support sleep and wake-up of ECUs and buses	[SRS_SPAL_12067] [SRS_SPAL_12069] [SRS_SPAL_12267]
[RS_BRF_01152]	AUTOSAR shall support limited dynamic reconfiguration	[SRS_SPAL_12265]
[RS_BRF_01440]	AUTOSAR services shall support system diagnostic functionality	[SRS_SPAL_12064]
[RS_BRF_01496]	AUTOSAR shall standardize how events which move an ECU out of the SLEEP mode are handled	[SRS_SPAL_12267]
[RS_BRF_02168]	AUTOSAR diagnostics shall provide a central classification and handling of abnormal operative conditions	[SRS_SPAL_00157] [SRS_SPAL_12064]
[RS_BRF_02232]	AUTOSAR shall support development with run-time assertion checks	[SRS_SPAL_00157] [SRS_SPAL_12448]

Table 6.1: RequirementsTracing

7 References

- [1] Standardization Template
AUTOSAR_FO_TPS_StandardizationTemplate
- [2] Glossary
AUTOSAR_FO_TR_Glossary
- [3] Requirements on AUTOSAR Features
AUTOSAR_CP_RS_Features