

Document Title	Specification of Basic Software Multicore Library
Document Owner	AUTOSAR
Document Responsibility	AUTOSAR
Document Identification No	946

Document Status	published
Part of AUTOSAR Standard	Classic Platform
Part of Standard Release	R23-11

Document Change History			
Date	Release	Changed by	Description
2023-11-23	R23-11	AUTOSAR Release Management	<ul style="list-style-type: none"> • Added note for MemoryAllocation • Bugfixes
2022-11-24	R22-11	AUTOSAR Release Management	<ul style="list-style-type: none"> • Introduced BMC Atomic Datatypes • Reworked APIs to make use of Atomic Datatypes • Cleaned up library
2021-11-25	R21-11	AUTOSAR Release Management	<ul style="list-style-type: none"> • No content changes
2020-11-30	R20-11	AUTOSAR Release Management	<ul style="list-style-type: none"> • Improved the structure of the 'error sections' of the SWS documents • CONC_643 "BSW Multicore Distribution" finalized
2019-11-28	R19-11	AUTOSAR Release Management	<ul style="list-style-type: none"> • Initial release

Disclaimer

This work (specification and/or software implementation) and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the work.

The material contained in this work is protected by copyright and other types of intellectual property rights. The commercial exploitation of the material contained in this work requires a license to such intellectual property rights.

This work may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the work may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The work has been developed for automotive applications only. It has neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

Contents

1	Introduction and functional overview	5
2	Acronyms and Abbreviations	6
3	Related documentation	7
3.1	Input documents & related standards and norms	7
3.2	Related specification	7
4	Constraints and assumptions	8
4.1	Limitations	8
4.2	Applicability to car domains	8
5	Dependencies to other modules	9
6	Requirements Tracing	10
7	Functional specification	12
7.1	Error Classification	12
7.1.1	Development Errors	12
7.1.2	Runtime Errors	12
7.1.3	Transient Faults	12
7.1.4	Production Errors	12
7.1.5	Extended Production Errors	12
7.2	Initialization and Shutdown	12
7.3	Using Library API	13
7.4	Library Implementation	13
8	API specification	15
8.1	Imported types	15
8.2	Type definitions	15
8.2.1	Bmc_AtomicUType	15
8.2.2	Bmc_AtomicSType	15
8.2.3	Bmc_AtomicFlagType	16
8.3	Macro definitions	16
8.4	Function definitions	16
8.4.1	Flag Routines	17
8.4.1.1	Bmc_FlagTestAndSet	17
8.4.1.2	Bmc_FlagClear	17
8.4.2	Load and Store Routines	18
8.4.2.1	Bmc_Load	18
8.4.2.2	Bmc_Store	19
8.4.2.3	Bmc_Exchange	19
8.4.2.4	Bmc_CompareExchange	20
8.4.3	Fetch Routines	21
8.4.3.1	Bmc_FetchAdd	22

8.4.3.2	Bmc_FetchSub	23
8.4.3.3	Bmc_FetchOr	24
8.4.3.4	Bmc_FetchXor	25
8.4.3.5	Bmc_FetchAnd	26
8.4.4	Fence Routines	27
8.4.4.1	Bmc_ThreadFence	27
8.4.5	Version API	27
8.4.5.1	Bmc_GetVersionInfo	27
8.5	Callback notifications	28
8.6	Scheduled functions	28
8.7	Expected Interfaces	28
8.7.1	Mandatory Interfaces	28
8.7.2	Optional Interfaces	28
8.7.3	Configurable interfaces	29
9	Sequence diagrams	30
10	Configuration specification	31
10.1	Published Information	31
10.2	Configuration Option	31
A	History of Constraints and Specification Items	32
A.1	Constraint and Specification Item History of this Document According to AUTOSAR Release R22-11	32
A.1.1	Added Specification Items in R22-11	32
A.1.2	Changed Specification Items in R22-11	32
A.1.3	Deleted Specification Items in R22-11	32
A.2	Constraint and Specification Item History of this Document According to AUTOSAR Release R23-11	32
A.2.1	Added Specification Items in R23-11	32
A.2.2	Changed Specification Items in R23-11	33
A.2.3	Deleted Specification Items in R23-11	33
B	Not applicable requirements	34

1 Introduction and functional overview

This specification describes the functionality, API and the configuration of the AUTOSAR library for atomic routines.

This library (Bmc) contains the following routines:

- flag test and set
- flag clear
- store
- load
- exchange
- compare and exchange
- fetch and add
- fetch and subtract
- fetch and or
- fetch and xor
- fetch and and
- thread fence

All routines are re-entrant and can be used by multiple runnables at the same time.

2 Acronyms and Abbreviations

The glossary below includes acronyms and abbreviations relevant to the Bmc module that are not included in the [1, AUTOSAR glossary].

Abbreviation/Acronym:	Description:
Bmc	Basic Software Multicore Library
DET	Default Error Tracer
s16	Mnemonic for <code>sint16</code> , specified in <code>AUTOSAR_SWS_PlatformTypes</code>
s32	Mnemonic for <code>sint32</code> , specified in <code>AUTOSAR_SWS_PlatformTypes</code>
s64	Mnemonic for <code>sint64</code> , specified in <code>AUTOSAR_SWS_PlatformTypes</code>
s8	Mnemonic for <code>sint8</code> , specified in <code>AUTOSAR_SWS_PlatformTypes</code>
u16	Mnemonic for <code>uint16</code> , specified in <code>AUTOSAR_SWS_PlatformTypes</code>
u32	Mnemonic for <code>uint32</code> , specified in <code>AUTOSAR_SWS_PlatformTypes</code>
u64	Mnemonic for <code>uint64</code> , specified in <code>AUTOSAR_SWS_PlatformTypes</code>
u8	Mnemonic for <code>uint8</code> , specified in <code>AUTOSAR_SWS_PlatformTypes</code>

3 Related documentation

3.1 Input documents & related standards and norms

- [1] Glossary
AUTOSAR_FO_TR_Glossary
- [2] General Specification of Basic Software Modules
AUTOSAR_CP_SWS_BSWGeneral
- [3] General Requirements on Basic Software Modules
AUTOSAR_CP_SRS_BSWGeneral
- [4] Requirements on Libraries
AUTOSAR_CP_SRS_Libraries

3.2 Related specification

AUTOSAR provides a General Specification on Basic Software modules [2], which is also valid for BSWMulticoreLibrary.

Thus, the specification SWS BSW General shall be considered as additional and required specification for BSWMulticoreLibrary.

4 Constraints and assumptions

4.1 Limitations

No limitations.

4.2 Applicability to car domains

No restrictions.

5 Dependencies to other modules

[SWS_BMC_00001] [The Bmc module shall provide the following files: C files `Bmc_<name>.c` used to implement the library. All C files shall be pre-fixed with 'Bmc_'. The header file `Bmc.h` provides all public function prototypes and types defined by the Bmc library specification.]([SRS_LIBS_00005](#))

Implementation and grouping of routines with respect to C files is recommended as per options below and there is no restriction to follow these proposals.

Option 1: `<Name>` can be a function name providing one C file per function, e.g.: `Bmc_FlagClear.c` etc.

Option 2: `<Name>` can be a common name of a group of functions:

2.1 Group by routine family:

e.g.: `Bmc_Flag.c`, `Bmc_Fetch.c`

2.2 Group by other methods (individual grouping allowed)

Option 3: `<Name>` can be removed so that a single C file shall contain all Bmc functions, e.g.: `Bmc.c`. Using one of the above options gives certain flexibility of choosing suitable granularity with reduced number of C files. Linking only on-demand is also possible in case of some options.

6 Requirements Tracing

The following tables reference the requirements specified in [3], [4] and links to the fulfillment of these. Please note that if column “Satisfied by” is empty for a specific requirement this means that this requirement is not fulfilled by this document.

Requirement	Description	Satisfied by
[SRS_BSW_00304]	All AUTOSAR Basic Software Modules shall use only AUTOSAR data types instead of native C data types	[SWS_BMC_00015]
[SRS_BSW_00306]	AUTOSAR Basic Software Modules shall be compiler and platform independent	[SWS_BMC_00016]
[SRS_BSW_00348]	All AUTOSAR standard types and constants shall be placed and organized in a standard type header file	[SWS_BMC_00014]
[SRS_BSW_00374]	All Basic Software Modules shall provide a readable module vendor identification	[SWS_BMC_00044]
[SRS_BSW_00378]	AUTOSAR shall provide a boolean type	[SWS_BMC_00015]
[SRS_BSW_00379]	All software modules shall provide a module identifier in the header file and in the module XML description file.	[SWS_BMC_00044]
[SRS_BSW_00402]	Each module shall provide version information	[SWS_BMC_00044]
[SRS_BSW_00407]	Each BSW module shall provide a function to read out the version information of a dedicated module implementation	[SWS_BMC_00043]
[SRS_BSW_00411]	All AUTOSAR Basic Software Modules shall apply a naming rule for enabling/disabling the existence of the API	[SWS_BMC_00043]
[SRS_BSW_00437]	Memory mapping shall provide the possibility to define RAM segments which are not to be initialized during startup	[SWS_BMC_00013]
[SRS_BSW_00448]	Module SWS shall not contain requirements from other modules	[SWS_BMC_00999]
[SRS_LIBS_00001]	The functional behavior of each library functions shall not be configurable	[SWS_BMC_00045]
[SRS_LIBS_00002]	A library shall be operational before all BSW modules and application SW-Cs	[SWS_BMC_00005]
[SRS_LIBS_00003]	A library shall be operational until the shutdown	[SWS_BMC_00006]
[SRS_LIBS_00004]	Using libraries shall not pass through a port interface	[SWS_BMC_00007]
[SRS_LIBS_00005]	Each library shall provide one header file with its public interface	[SWS_BMC_00001]
[SRS_LIBS_00007]	Using a library should be documented	[SWS_BMC_00008] [SWS_BMC_00012]





Requirement	Description	Satisfied by
[SRS_LIBS_00015]	It shall be possible to configure the microcontroller so that the library code is shared between all callers	[SWS_BMC_00009]
[SRS_LIBS_00017]	Usage of macros should be avoided	[SWS_BMC_00010]
[SRS_LIBS_00018]	A library function may only call library functions	[SWS_BMC_00011]

Table 6.1: RequirementsTracing

7 Functional specification

7.1 Error Classification

Section "Error Handling" of the document "General Specification of Basic Software Modules" describes the error handling of the Basic Software in detail. Above all, it constitutes a classification scheme consisting of five error types which may occur in BSW modules.

Based on this foundation, the following section specifies particular errors arranged in the respective subsections below.

7.1.1 Development Errors

There are no development errors.

7.1.2 Runtime Errors

There are no runtime errors.

7.1.3 Transient Faults

There are no transient faults.

7.1.4 Production Errors

There are no production errors.

7.1.5 Extended Production Errors

There are no extended production errors.

7.2 Initialization and Shutdown

[SWS_BMC_00005] [The Bmc library shall not require an initialization phase. A Library function may be called at the very first step of ECU initialization, e.g. even by the OS or EcuM, thus the library shall be ready.] ([SRS_LIBS_00002](#))

[SWS_BMC_00006] [The Bmc library shall not require a shutdown operation phase.]
([SRS_LIBS_00003](#))

7.3 Using Library API

[SWS_BMC_00007] [The Bmc API can be directly called from BSW modules or SWCs. No port definition is required. It is a pure function call.]([SRS_LIBS_00004](#))

[SWS_BMC_00008] [Using a library should be documented. If a BSW module or a SWC uses a library, the developer should add an ImplementationDependencyOnArtifact in the BSW/SWC template. minVersion and maxVersion parameters correspond to the supplier version. In case of an AUTOSAR library, these parameters may be left empty because a SWC or BSW module may rely on a library behavior, not on a supplier implementation. However, the SWC or BSW modules shall be compatible with the AUTOSAR platform where they are integrated.]([SRS_LIBS_00007](#))

The user has to ensure that atomic data are allocated in a memory which allows atomic access. Hence it might be useful to use a vendor specific but unique {refinement} keyword in the memory allocation keyword (MAKW) or respective software addressing methods (SwAddrMethod) which can be used to derive according MemoryAllocation options for the purpose of mapping.

7.4 Library Implementation

[SWS_BMC_00009] [The Bmc library shall be implemented in a way that the code can be shared among callers in different memory partitions.]([SRS_LIBS_00015](#))

[SWS_BMC_00010] [Usage of macros should be avoided. The functions should be declared as functions or inline functions.]([SRS_LIBS_00017](#))

[SWS_BMC_00011] [A library function shall not call any BSW modules functions, e.g. the DET. A library function can call other library functions because a library function shall be re-entrant. But other BSW modules functions may not be re-entrant.]([SRS_LIBS_00018](#))

[SWS_BMC_00012] [The library, written in the C programming language, should conform to the MISRA C Standard. Please refer to SWS_BSW_00115 for more details.]([SRS_LIBS_00007](#))

[SWS_BMC_00013] [Each AUTOSAR library Module implementation <library>*.c and <library>*.h shall map their code to memory sections using the AUTOSAR memory mapping mechanism.]([SRS_BSW_00437](#))

[SWS_BMC_00014] [Each AUTOSAR library Module implementation <library>*.c that uses AUTOSAR integer data types and/or the standard return type, shall include the header file Std_Types.h.]([SRS_BSW_00348](#))

[SWS_BMC_00015] [All AUTOSAR library Modules should use the AUTOSAR data types (integers, boolean) instead of native C data types unless this library is clearly identified to be compliant only with one platform.] ([SRS_BSW_00378](#), [SRS_BSW_00304](#))

[SWS_BMC_00016] [All AUTOSAR library Modules should avoid direct use of compiler and platform specific keywords unless this library is clearly identified to be compliant only with one platform.] ([SRS_BSW_00306](#))

8 API specification

8.1 Imported types

In this chapter, all types included from the following files are listed.

[SWS_Bmc_91000] Definition of imported datatypes of module Bmc [

<i>Module</i>	<i>Header File</i>	<i>Imported Type</i>
Std	Std_Types.h	Std_VersionInfoType

]()

8.2 Type definitions

Note: Most likely the Bmc AtomicTypes will be the native datatype of the microcontroller (e.g. uint32/sint32 for a 32 bit microcontroller).

8.2.1 Bmc_AtomicUType

[SWS_Bmc_91016] Definition of datatype Bmc_AtomicUType [

<i>Name</i>	Bmc_AtomicUType		
<i>Kind</i>	Type		
<i>Derived from</i>	uint		
<i>Range</i>	-	–	The Bmc_AtomicUType shall always be mapped to a platform specific type where atomic operations can be realized by the respective HW platform, to ensure that all the operations performed on this type are lock-free
<i>Description</i>	The type shall be used for all unsigned data items, which are used for Bmc library functions.		
<i>Available via</i>	Bmc.h		

]()

8.2.2 Bmc_AtomicSType

[SWS_Bmc_91017] Definition of datatype Bmc_AtomicSType [

<i>Name</i>	Bmc_AtomicSType		
<i>Kind</i>	Type		
<i>Derived from</i>	sint		



△

Range	-	-	The Bmc_AtomicSType shall always be mapped to a platform specific type where atomic operations can be realized by the respective HW platform, to ensure that all the operations performed on this type are lock-free
Description	The type shall be used for all signed data items, which are used for Bmc library functions.		
Available via	Bmc.h		

]()

8.2.3 Bmc_AtomicFlagType

[SWS_Bmc_91018] Definition of datatype Bmc_AtomicFlagType [

Name	Bmc_AtomicFlagType		
Kind	Type		
Derived from	boolean		
Range	-	-	The Bmc_AtomicFlagType shall always be mapped to a platform specific type where atomic operations can be realized by the respective HW platform, to insure that all the operations performed on this type are lock-free
Description	The type shall be used for all Flag data items, which are used for Bmc library functions.		
Available via	Bmc.h		

]()

8.3 Macro definitions

No Macro definitions.

8.4 Function definitions

Note: All atomic operations will provide sequentially consistent ordering (see https://en.cppreference.com/w/c/atomic/memory_order#Sequentially-consistent_ordering).

8.4.1 Flag Routines

8.4.1.1 Bmc_FlagTestAndSet

[SWS_Bmc_91003] Definition of API function Bmc_FlagTestAndSet [

Service Name	Bmc_FlagTestAndSet	
Syntax	<pre>boolean Bmc_FlagTestAndSet (volatile Bmc_AtomicFlagType* Object)</pre>	
Service ID [hex]	0x01	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	None	
Parameters (inout)	Object	Object
Parameters (out)	None	
Return value	boolean	The value pointed to by Object immediately before the effects
Description	Atomically sets the value pointed to by Object to true.	
Available via	Bmc.h	

]()

[SWS_BMC_00019] [The function `Bmc_FlagTestAndSet` atomically sets the value pointed to by Object to `TRUE`. It returns this value before the operation, i.e., `TRUE`, if it was already set and `FALSE` otherwise.]()

8.4.1.2 Bmc_FlagClear

[SWS_Bmc_91004] Definition of API function Bmc_FlagClear [

Service Name	Bmc_FlagClear	
Syntax	<pre>void Bmc_FlagClear (volatile Bmc_AtomicFlagType* Object)</pre>	
Service ID [hex]	0x02	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	None	
Parameters (inout)	Object	Object
Parameters (out)	None	
Return value	None	
Description	Atomically sets the value pointed to by Object to false.	
Available via	Bmc.h	

]()

[SWS_BMC_00021] [The function `Bmc_FlagClear` atomically sets the value pointed to by Object to `FALSE`.]()

8.4.2 Load and Store Routines

[SWS_BMC_00046] [All load and store routines shall implicitly make use of the feature explicitly introduced by [Bmc_ThreadFence](#).]()

8.4.2.1 Bmc_Load

[SWS_Bmc_91019] Definition of API function [Bmc_Load_u](#) [

Service Name	Bmc_Load_u	
Syntax	<pre>Bmc_AtomicUType Bmc_Load_u (const volatile Bmc_AtomicUType* Object)</pre>	
Service ID [hex]	0x10 to 0x13	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	None	
Parameters (inout)	Object	–
Parameters (out)	None	
Return value	Bmc_AtomicUType	The value pointed to by Object
Description	Atomically loads the value pointed to by Object and returns it.	
Available via	Bmc.h	

]()

[SWS_Bmc_91020] Definition of API function [Bmc_Load_s](#) [

Service Name	Bmc_Load_s	
Syntax	<pre>Bmc_AtomicSType Bmc_Load_s (const volatile Bmc_AtomicSType* Object)</pre>	
Service ID [hex]	0x14 to 0x17	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	None	
Parameters (inout)	Object	–
Parameters (out)	None	
Return value	Bmc_AtomicSType	The value pointed to by Object
Description	Atomically loads the value pointed to by Object and returns it.	
Available via	Bmc.h	

]()

8.4.2.2 Bmc_Store

[SWS_Bmc_91021] Definition of API function Bmc_Store_u [

Service Name	Bmc_Store_u	
Syntax	<pre>void Bmc_Store_u (volatile Bmc_AtomicUType* Object, Bmc_AtomicUType Desired)</pre>	
Service ID [hex]	0x20 to 0x23	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	Desired	Value to be stored
Parameters (inout)	Object	Object
Parameters (out)	None	
Return value	None	
Description	Atomically replaces the value pointed to by Object with the value of Desired.	
Available via	Bmc.h	

]()

[SWS_Bmc_91022] Definition of API function Bmc_Store_s [

Service Name	Bmc_Store_s	
Syntax	<pre>void Bmc_Store_s (volatile Bmc_AtomicSType* Object, Bmc_AtomicSType Desired)</pre>	
Service ID [hex]	0x24 to 0x27	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	Desired	Value to be stored
Parameters (inout)	Object	Object
Parameters (out)	None	
Return value	None	
Description	Atomically replaces the value pointed to by Object with the value of Desired.	
Available via	Bmc.h	

]()

8.4.2.3 Bmc_Exchange

[SWS_Bmc_91025] Definition of API function Bmc_Exchange_u [

Service Name	Bmc_Exchange_u	
Syntax	<pre>Bmc_AtomicUType Bmc_Exchange_u (volatile Bmc_AtomicUType* Object, Bmc_AtomicUType Desired)</pre>	





Service ID [hex]	0x30 to 0x33	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	Desired	Value to be stored
Parameters (inout)	Object	Object
Parameters (out)	None	
Return value	Bmc_AtomicUType	The value pointed to by Object immediately before the effects
Description	Atomically replaces the value pointed to by Object with the value of Desired and returns the value pointed to by Object immediately before the effects.	
Available via	Bmc.h	

]()

[SWS_Bmc_91026] Definition of API function `Bmc_Exchange_s` [

Service Name	<code>Bmc_Exchange_s</code>	
Syntax	<pre> Bmc_AtomicSType Bmc_Exchange_s (volatile Bmc_AtomicSType* Object, Bmc_AtomicSType Desired) </pre>	
Service ID [hex]	0x34 to 0x37	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	Desired	Value to be stored
Parameters (inout)	Object	Object
Parameters (out)	None	
Return value	Bmc_AtomicSType	The value pointed to by Object immediately before the effects
Description	Atomically replaces the value pointed to by Object with the value of Desired and returns the value pointed to by Object immediately before the effects.	
Available via	Bmc.h	

]()

8.4.2.4 `Bmc_CompareExchange`

[SWS_Bmc_91023] Definition of API function `Bmc_CompareExchange_u` [

Service Name	<code>Bmc_CompareExchange_u</code>	
Syntax	<pre> boolean Bmc_CompareExchange_u (volatile Bmc_AtomicUType* Object, Bmc_AtomicUType* Expected, Bmc_AtomicUType Desired) </pre>	
Service ID [hex]	0x40 to 0x43	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	Desired	Value to be stored



△

Parameters (inout)	Object	Object
	Expected	Value to be stored
Parameters (out)	None	
Return value	boolean	The result of the comparison
Description	Atomically compares the value pointed to by Object for equality with that in Expected, and if true, replaces the value pointed to by Object with Desired, and if false, updates the value in Expected with the value pointed to by Object.	
Available via	Bmc.h	

]()

[SWS_Bmc_91024] Definition of API function Bmc_CompareExchange_s [

Service Name	Bmc_CompareExchange_s	
Syntax	<pre>boolean Bmc_CompareExchange_s (volatile Bmc_AtomicSType* Object, Bmc_AtomicSType* Expected, Bmc_AtomicSType Desired)</pre>	
Service ID [hex]	0x44 to 0x47	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	Desired	Value to be stored
Parameters (inout)	Object	Object
	Expected	Value to be stored
Parameters (out)	None	
Return value	boolean	The result of the comparison
Description	Atomically compares the value pointed to by Object for equality with that in Expected, and if true, replaces the value pointed to by Object with Desired, and if false, updates the value in Expected with the value pointed to by Object.	
Available via	Bmc.h	

]()

8.4.3 Fetch Routines

[SWS_BMC_00047] [All fetch routines shall implicitly make use of the feature explicitly introduced by [Bmc_ThreadFence](#).]()

8.4.3.1 Bmc_FetchAdd

[SWS_Bmc_91027] Definition of API function Bmc_FetchAdd_u [

Service Name	Bmc_FetchAdd_u	
Syntax	<pre>Bmc_AtomicUType Bmc_FetchAdd_u (volatile Bmc_AtomicUType* Object, Bmc_AtomicUType Operand)</pre>	
Service ID [hex]	0x50 to 0x53	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	Operand	Value for the operation
Parameters (inout)	Object	Object
Parameters (out)	None	
Return value	Bmc_AtomicUType	The value pointed to by Object immediately before the effects
Description	Atomically replaces the value pointed to by Object with the result of the addition applied to the value pointed to by Object and the given Operand.	
Available via	Bmc.h	

]()

[SWS_Bmc_91028] Definition of API function Bmc_FetchAdd_s [

Service Name	Bmc_FetchAdd_s	
Syntax	<pre>Bmc_AtomicSType Bmc_FetchAdd_s (volatile Bmc_AtomicSType* Object, Bmc_AtomicSType Operand)</pre>	
Service ID [hex]	0x54 to 0x57	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	Operand	Value for the operation
Parameters (inout)	Object	Object
Parameters (out)	None	
Return value	Bmc_AtomicSType	The value pointed to by Object immediately before the effects
Description	Atomically replaces the value pointed to by Object with the result of the addition applied to the value pointed to by Object and the given Operand.	
Available via	Bmc.h	

]()

8.4.3.2 Bmc_FetchSub

[SWS_Bmc_91033] Definition of API function Bmc_FetchSub_u [

Service Name	Bmc_FetchSub_u	
Syntax	<pre>Bmc_AtomicUType Bmc_FetchSub_u (volatile Bmc_AtomicUType* Object, Bmc_AtomicUType Operand)</pre>	
Service ID [hex]	0x60 to 0x63	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	Operand	Value for the operation
Parameters (inout)	Object	Object
Parameters (out)	None	
Return value	Bmc_AtomicUType	The value pointed to by Object immediately before the effects
Description	Atomically replaces the value pointed to by Object with the result of the subtraction applied to the value pointed to by Object and the given Operand.	
Available via	Bmc.h	

]()

[SWS_Bmc_91034] Definition of API function Bmc_FetchSub_s [

Service Name	Bmc_FetchSub_s	
Syntax	<pre>Bmc_AtomicSType Bmc_FetchSub_s (volatile Bmc_AtomicSType* Object, Bmc_AtomicSType Operand)</pre>	
Service ID [hex]	0x64 to 0x67	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	Operand	Value for the operation
Parameters (inout)	Object	Object
Parameters (out)	None	
Return value	Bmc_AtomicSType	The value pointed to by Object immediately before the effects
Description	Atomically replaces the value pointed to by Object with the result of the subtraction applied to the value pointed to by Object and the given Operand.	
Available via	Bmc.h	

]()

8.4.3.3 Bmc_FetchOr

[SWS_Bmc_91031] Definition of API function Bmc_FetchOr_u [

Service Name	Bmc_FetchOr_u	
Syntax	<pre>Bmc_AtomicUType Bmc_FetchOr_u (volatile Bmc_AtomicUType* Object, Bmc_AtomicUType Operand)</pre>	
Service ID [hex]	0x70 to 0x73	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	Operand	Value for the operation
Parameters (inout)	Object	Object
Parameters (out)	None	
Return value	Bmc_AtomicUType	The value pointed to by Object immediately before the effects
Description	Atomically replaces the value pointed to by Object with the result of the or-operation applied to the value pointed to by Object and the given Operand.	
Available via	Bmc.h	

]()

[SWS_Bmc_91032] Definition of API function Bmc_FetchOr_s [

Service Name	Bmc_FetchOr_s	
Syntax	<pre>Bmc_AtomicSType Bmc_FetchOr_s (volatile Bmc_AtomicSType* Object, Bmc_AtomicSType Operand)</pre>	
Service ID [hex]	0x74 to 0x77	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	Operand	Value for the operation
Parameters (inout)	Object	Object
Parameters (out)	None	
Return value	Bmc_AtomicSType	The value pointed to by Object immediately before the effects
Description	Atomically replaces the value pointed to by Object with the result of the or-operation applied to the value pointed to by Object and the given Operand.	
Available via	Bmc.h	

]()

8.4.3.4 Bmc_FetchXor

[SWS_Bmc_91035] Definition of API function Bmc_FetchXor_u [

Service Name	Bmc_FetchXor_u	
Syntax	<pre>Bmc_AtomicUType Bmc_FetchXor_u (volatile Bmc_AtomicUType* Object, Bmc_AtomicUType Operand)</pre>	
Service ID [hex]	0x80 to 0x83	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	Operand	Value for the operation
Parameters (inout)	Object	Object
Parameters (out)	None	
Return value	Bmc_AtomicUType	The value pointed to by Object immediately before the effects
Description	Atomically replaces the value pointed to by Object with the result of the xor-operation applied to the value pointed to by Object and the given Operand.	
Available via	Bmc.h	

]()

[SWS_Bmc_91036] Definition of API function Bmc_FetchXor_s [

Service Name	Bmc_FetchXor_s	
Syntax	<pre>Bmc_AtomicSType Bmc_FetchXor_s (volatile Bmc_AtomicSType* Object, Bmc_AtomicSType Operand)</pre>	
Service ID [hex]	0x84 to 0x87	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	Operand	Value for the operation
Parameters (inout)	Object	Object
Parameters (out)	None	
Return value	Bmc_AtomicSType	The value pointed to by Object immediately before the effects
Description	Atomically replaces the value pointed to by Object with the result of the xor-operation applied to the value pointed to by Object and the given Operand.	
Available via	Bmc.h	

]()

8.4.3.5 Bmc_FetchAnd

[SWS_Bmc_91029] Definition of API function Bmc_FetchAnd_u [

Service Name	Bmc_FetchAnd_u	
Syntax	<pre>Bmc_AtomicUType Bmc_FetchAnd_u (volatile Bmc_AtomicUType* Object, Bmc_AtomicUType Operand)</pre>	
Service ID [hex]	0x90 to 0x93	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	None	
Parameters (inout)	Object	Object
	Operand	Value for the operation
Parameters (out)	None	
Return value	Bmc_AtomicUType	The value pointed to by Object immediately before the effects
Description	Atomically replaces the value pointed to by Object with the result of the and-operation applied to the value pointed to by Object and the given Operand.	
Available via	Bmc.h	

]()

[SWS_Bmc_91030] Definition of API function Bmc_FetchAnd_s [

Service Name	Bmc_FetchAnd_s	
Syntax	<pre>Bmc_AtomicSType Bmc_FetchAnd_s (volatile Bmc_AtomicSType* Object, Bmc_AtomicSType Operand)</pre>	
Service ID [hex]	0x94 to 0x97	
Sync/Async	Synchronous	
Reentrancy	Reentrant	
Parameters (in)	None	
Parameters (inout)	Object	Object
	Operand	Value for the operation
Parameters (out)	None	
Return value	Bmc_AtomicSType	The value pointed to by Object immediately before the effects
Description	Atomically replaces the value pointed to by Object with the result of the and-operation applied to the value pointed to by Object and the given Operand.	
Available via	Bmc.h	

]()

8.4.4 Fence Routines

8.4.4.1 Bmc_ThreadFence

[SWS_Bmc_91014] Definition of API function Bmc_ThreadFence [

Service Name	Bmc_ThreadFence
Syntax	void Bmc_ThreadFence (void)
Service ID [hex]	0x03
Sync/Async	Synchronous
Reentrancy	Reentrant
Parameters (in)	None
Parameters (inout)	None
Parameters (out)	None
Return value	None
Description	Creates a sequentially consistent acquire and release fence. An acquire and release fence instruction prevents the memory reordering of any read or write which precedes it in program order with any read or write which follows it in program order.
Available via	Bmc.h

]()

[SWS_BMC_00041] [The function [Bmc_ThreadFence](#) creates a sequentially consistent acquire and release fence.]()

Note: It may also serve as a compiler barrier which stops the compiler from moving instructions across it either way for optimization purposes. Any instruction that occurs in program order before this instruction will not be reordered after this instruction. Every instruction that occurs after this instruction will not be reordered before this instruction.

8.4.5 Version API

8.4.5.1 Bmc_GetVersionInfo

[SWS_Bmc_91015] Definition of API function Bmc_GetVersionInfo [

Service Name	Bmc_GetVersionInfo
Syntax	void Bmc_GetVersionInfo (Std_VersionInfoType* Versioninfo)
Service ID [hex]	0xFF
Sync/Async	Synchronous
Reentrancy	Reentrant
Parameters (in)	None
Parameters (inout)	None





Parameters (out)	Versioninfo	Pointer to where to store the version information of this module. Format according [BSW00321]
Return value	None	
Description	Returns the version information of this library.	
Available via	Bmc.h	

}]()

[SWS_BMC_00043] [If source code for caller and callee of `Bmc_GetVersionInfo` is available, the Bmc library should realize `Bmc_GetVersionInfo` as a macro defined in the module's header file.] ([SRS_BSW_00407](#), [SRS_BSW_00411](#))

8.5 Callback notifications

None.

8.6 Scheduled functions

The Bmc library does not have scheduled functions.

8.7 Expected Interfaces

In this section, all interfaces required from other modules are listed.

8.7.1 Mandatory Interfaces

This section defines all interfaces that are required to fulfill the core functionality of the module.

[SWS_Bmc_91001] Definition of mandatory interfaces in module Bmc [

API Function	Header File	Description
There are no mandatory interfaces.		

}]()

8.7.2 Optional Interfaces

This section defines all interfaces that are required to fulfill an optional functionality of the module.

[SWS_Bmc_91002] Definition of optional interfaces in module Bmc [

<i>API Function</i>	<i>Header File</i>	<i>Description</i>
There are no optional interfaces.		

]()

8.7.3 Configurable interfaces

None.

9 Sequence diagrams

Not applicable.

10 Configuration specification

10.1 Published Information

[SWS_BMC_00044] [The standardized common published parameters as required by SRS_BSW_00402 in the General Requirements on Basic Software Modules [3] shall be published within the header file of this module and need to be provided in the BSW Module Description. The according module abbreviation can be found in the List of Basic Software Modules] ([SRS_BSW_00402](#), [SRS_BSW_00374](#), [SRS_BSW_00379](#))

Additional module-specific published parameters are listed below if applicable.

10.2 Configuration Option

[SWS_BMC_00045] [The Bmc library shall not have any configuration options that may affect the functional behavior of the routines. I.e. for a given set of input parameters, the outputs shall be always the same. For example, the returned value in case of error shall not be configurable.] ([SRS_LIBS_00001](#))

However, a library vendor is allowed to add specific configuration options concerning library implementation, e.g. for resource consumption optimization.

A History of Constraints and Specification Items

Please note that the lists in this chapter also include constraints and specification items that have been removed from the specification in a later version. These constraints and specification items do not appear as hyperlinks in the document.

A.1 Constraint and Specification Item History of this Document According to AUTOSAR Release R22-11

A.1.1 Added Specification Items in R22-11

[\[SWS_BMC_00046\]](#) [\[SWS_BMC_00047\]](#) [\[SWS_Bmc_91016\]](#) [\[SWS_Bmc_91017\]](#)
[\[SWS_Bmc_91018\]](#) [\[SWS_Bmc_91019\]](#) [\[SWS_Bmc_91020\]](#) [\[SWS_Bmc_91021\]](#)
[\[SWS_Bmc_91022\]](#) [\[SWS_Bmc_91023\]](#) [\[SWS_Bmc_91024\]](#) [\[SWS_Bmc_91025\]](#)
[\[SWS_Bmc_91026\]](#) [\[SWS_Bmc_91027\]](#) [\[SWS_Bmc_91028\]](#) [\[SWS_Bmc_91029\]](#)
[\[SWS_Bmc_91030\]](#) [\[SWS_Bmc_91031\]](#) [\[SWS_Bmc_91032\]](#) [\[SWS_Bmc_91033\]](#)
[\[SWS_Bmc_91034\]](#) [\[SWS_Bmc_91035\]](#) [\[SWS_Bmc_91036\]](#)

A.1.2 Changed Specification Items in R22-11

[\[SWS_BMC_00013\]](#) [\[SWS_BMC_00014\]](#) [\[SWS_BMC_00016\]](#) [\[SWS_Bmc_91003\]](#)
[\[SWS_Bmc_91004\]](#) [\[SWS_Bmc_91014\]](#) [\[SWS_Bmc_91015\]](#)

A.1.3 Deleted Specification Items in R22-11

[\[SWS_BMC_00017\]](#) [\[SWS_BMC_00023\]](#) [\[SWS_BMC_00025\]](#) [\[SWS_BMC_00027\]](#)
[\[SWS_BMC_00029\]](#) [\[SWS_BMC_00031\]](#) [\[SWS_BMC_00033\]](#) [\[SWS_BMC_00035\]](#)
[\[SWS_BMC_00037\]](#) [\[SWS_BMC_00039\]](#) [\[SWS_Bmc_91005\]](#) [\[SWS_Bmc_91006\]](#)
[\[SWS_Bmc_91007\]](#) [\[SWS_Bmc_91008\]](#) [\[SWS_Bmc_91009\]](#) [\[SWS_Bmc_91010\]](#)
[\[SWS_Bmc_91011\]](#) [\[SWS_Bmc_91012\]](#) [\[SWS_Bmc_91013\]](#)

A.2 Constraint and Specification Item History of this Document According to AUTOSAR Release R23-11

A.2.1 Added Specification Items in R23-11

[\[SWS_Bmc_91000\]](#) [\[SWS_Bmc_91001\]](#) [\[SWS_Bmc_91002\]](#)

A.2.2 Changed Specification Items in R23-11

[\[SWS_Bmc_91025\]](#) [\[SWS_Bmc_91026\]](#)

A.2.3 Deleted Specification Items in R23-11

none

B Not applicable requirements

[SWS_BMC_00999] [These requirements are not applicable to this specification.]
([SRS_BSW_00448](#))