

| | |
|-----------------------------------|--|
| Document Title | Specification of Communication Stack Types |
| Document Owner | AUTOSAR |
| Document Responsibility | AUTOSAR |
| Document Identification No | 50 |

| | |
|---------------------------------|------------------|
| Document Status | published |
| Part of AUTOSAR Standard | Classic Platform |
| Part of Standard Release | R23-11 |

| Document Change History | | | |
|--------------------------------|----------------|----------------------------|--|
| Date | Release | Changed by | Description |
| 2023-11-23 | R23-11 | AUTOSAR Release Management | <ul style="list-style-type: none"> • Added ListElemStructType • Added TimeTupleType, TimeStampType, TimeStampQualType • Changed the size of PNCHandleType |
| 2022-11-24 | R22-11 | AUTOSAR Release Management | <ul style="list-style-type: none"> • Removed reference to CompilerAbstraction |
| 2021-11-25 | R21-11 | AUTOSAR Release Management | <ul style="list-style-type: none"> • Added CbkHandleIdType in Type definitions |
| 2020-11-30 | R20-11 | AUTOSAR Release Management | <ul style="list-style-type: none"> • Removed IcomConfigIdType and IcomSwitch_ErrorType from Type definitions |
| 2019-11-28 | R19-11 | AUTOSAR Release Management | <ul style="list-style-type: none"> • Renamed of general types headers • Changed Document Status from Final to published |
| 2018-10-31 | 4.4.0 | AUTOSAR Release Management | <ul style="list-style-type: none"> • Editorial changes |
| 2017-12-08 | 4.3.1 | AUTOSAR Release Management | <ul style="list-style-type: none"> • Editorial changes |





| | | | |
|------------|-------|----------------------------|---|
| 2016-11-30 | 4.3.0 | AUTOSAR Release Management | <ul style="list-style-type: none"> Removed Type BusTrcvErrorType because it is not used at all Updated PduInfoType for addressing in Upper Layers using MetaData Update of SWS document as per BSW General document |
| 2015-07-31 | 4.2.2 | AUTOSAR Release Management | <ul style="list-style-type: none"> Editorial changes |
| 2014-10-31 | 4.2.1 | AUTOSAR Release Management | <ul style="list-style-type: none"> MetaData information is added in PduInfoType |
| 2014-03-31 | 4.1.3 | AUTOSAR Release Management | <ul style="list-style-type: none"> Added support for Pretended network data type |
| 2013-10-31 | 4.1.2 | AUTOSAR Release Management | <ul style="list-style-type: none"> Removed the published information Editorial changes Removed chapter(s) on change documentation |
| 2013-03-15 | 4.1.1 | AUTOSAR Administration | <ul style="list-style-type: none"> Added support for Partial network data type Revised Notification type and RetryInfo type Additional input (SWS_BSW_General) added for SWS_CommunicationStackTypes |
| 2011-12-22 | 4.0.3 | AUTOSAR Administration | <ul style="list-style-type: none"> ComStack Artifacts have been generated from BSW Model Update of SWS document for new traceability mechanism |
| 2010-09-30 | 3.1.5 | AUTOSAR Administration | <ul style="list-style-type: none"> Add TPParameterType and Enumeration value TP_NO_RETRY in RetryInfoType ComStack_Types.h divided into ComStack_Types.h and ComStack_Cfg.h PduIdType and PduLengthType defined in ComStack_Cfg.h file |



△

| | | | |
|------------|--------|------------------------|--|
| 2010-02-02 | 3.1.4 | AUTOSAR Administration | <ul style="list-style-type: none"> • Typo errors are corrected throughout the document • General return codes for NotifResultType has been added to support Tp_ChangeParameterRequest • TpDataStateType and RetryInfoType has been added to store the Tp buffer status information • Common Published information has been updated • Legal disclaimer revised |
| 2008-08-13 | 3.1.1 | AUTOSAR Administration | <ul style="list-style-type: none"> • Legal disclaimer revised |
| 2007-07-24 | 2.1.16 | AUTOSAR Administration | <ul style="list-style-type: none"> • Chapter numbers in chapter 8.1 corrected • New data type NetworkHandleType created according item Comtype026 established • Syntax correction in PduInfoType • Document meta information extended • Small layout adaptations made |
| 2007-01-24 | 2.1.15 | AUTOSAR Administration | <ul style="list-style-type: none"> • "Advice for users" revised • "Revision Information" added • Changed "sender" to "receiver" at NTFRSLT_E_WRT_OVRN |
| 2006-11-28 | 2.1.2 | AUTOSAR Administration | <ul style="list-style-type: none"> • NTFRSLT_E_TIMEOUT_Bs changed to NTFRSLT_E_TIMEOUT_BS • NTFRSLT_E_TIMEOUT_Cr changed to NTFRSLT_E_TIMEOUT_CR • Definitions according to compiler abstraction added • Legal disclaimer revised |
| 2006-11-28 | 2.1.1 | AUTOSAR Administration | <ul style="list-style-type: none"> • Initial release (The V1.0.0 was only as Pre-Release available within Release 1.0) |

Disclaimer

This work (specification and/or software implementation) and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the work.

The material contained in this work is protected by copyright and other types of intellectual property rights. The commercial exploitation of the material contained in this work requires a license to such intellectual property rights.

This work may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the work may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The work has been developed for automotive applications only. It has neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

Contents

| | | |
|--------|---|----|
| 1 | Introduction and functional overview | 7 |
| 2 | Acronyms and Abbreviations | 8 |
| 3 | Related documentation | 9 |
| 3.1 | Input documents & related standards and norms | 9 |
| 3.2 | Related specification | 9 |
| 4 | Constraints and assumptions | 10 |
| 4.1 | Limitations | 10 |
| 4.2 | Applicability to car domains | 10 |
| 4.3 | Applicability to safety related environments | 10 |
| 5 | Dependencies to other modules | 11 |
| 6 | Requirements Tracing | 12 |
| 7 | Functional specification | 13 |
| 7.1 | General issues | 13 |
| 7.2 | Error Classification | 13 |
| 7.2.1 | Development Errors | 13 |
| 7.2.2 | Runtime Errors | 13 |
| 7.2.3 | Transient Faults | 13 |
| 7.2.4 | Production Errors | 14 |
| 7.2.5 | Extended Production Errors | 14 |
| 7.3 | Security Events | 14 |
| 8 | API specification | 15 |
| 8.1 | Type definitions | 15 |
| 8.1.1 | PduIdType | 15 |
| 8.1.2 | PduLengthType | 16 |
| 8.1.3 | PduInfoType | 16 |
| 8.1.4 | PNCHandleType | 17 |
| 8.1.5 | TPParameterType | 17 |
| 8.1.6 | BufReq_ReturnType | 18 |
| 8.1.7 | TpDataStateType | 18 |
| 8.1.8 | RetryInfoType | 19 |
| 8.1.9 | NetworkHandleType | 19 |
| 8.1.10 | CbkHandleIdType | 19 |
| 8.1.11 | TimeTupleType | 20 |
| 8.1.12 | TimeStampType | 20 |
| 8.1.13 | TimeStampQualType | 21 |
| 8.1.14 | ListElemStructType | 21 |
| 8.2 | Function definitions | 22 |

| | | |
|------|-----------------------------|----|
| 9 | Sequence diagrams | 23 |
| 10 | Configuration specification | 24 |
| 10.1 | Published Information | 24 |
| A | Not applicable requirements | 25 |

1 Introduction and functional overview

This document specifies the AUTOSAR communication stack type header file. It contains all types that are used across several modules of the communication stack of the basic software and all types of all basic software modules that are platform and compiler independent.

It is strongly recommended that those communication stack type files are unique within the AUTOSAR community to guarantee unique types and to avoid type changes when changing from supplier A to B.

2 Acronyms and Abbreviations

The glossary below includes acronyms and abbreviations relevant to the Communication Stack Types that are not included in the [1, AUTOSAR glossary].

| Acronym: | Description: |
|----------|--|
| API | Application Programming Interface |
| DCM | Diagnostic Communication Manager |
| I-PDU | Interaction Layer PDU. In AUTOSAR the Interaction Layer is equivalent to the Communication Services Layer. |
| L-PDU | Data Link Layer PDU. In AUTOSAR the Data Link Layer is equivalent to the Communication Hardware Abstraction and Microcontroller Abstraction Layer. |
| N-PDU | Network Layer PDU. In AUTOSAR the Network Layer is equivalent to the Transport Protocol. |
| OSEK/VDX | In May 1993 OSEK has been founded as a joint project in the German automotive industry aiming at an industry standard for an open-ended architecture for distributed control units in vehicles. OSEK is an abbreviation for the German term "Offene Systeme und deren Schnittstellen für die Elektronik im Kraftfahrzeug" (English: Open Systems and the Corresponding Interfaces for Automotive Electronics). Initial project partners were BMW, Bosch, Daimler Chrysler, Opel, Siemens, VW and the IIT of the University of Karlsruhe as co-ordinator. The French car manufacturers PSA and Renault joined OSEK in 1994 introducing their VDX-approach (Vehicle Distributed eXecutive) which is a similar project within the French automotive industry. At the first workshop on October 1995 the OSEK/VDX group presented the results of the harmonised specification between OSEK and VDX. After the 2nd international OSEK/VDX Workshop in October 1997 the 2nd versions of the specifications were published. |
| PDU | Protocol Data Unit |
| SDU | Service Data Unit - Payload of PDU |
| TP | Transport Protocol |

Table 2.1: Acronyms used in the scope of this Document

| Abbreviation: | Description: |
|---------------|--|
| Com | Communication |
| EcuC | ECU Configuration |
| e.g. | [lat.] exempli gratia = [eng.] for example |
| i.e. | [lat.] it est = [eng.] that is |

Table 2.2: Abbreviations used in the scope of this Document

3 Related documentation

3.1 Input documents & related standards and norms

- [1] Glossary
AUTOSAR_FO_TR_Glossary
- [2] General Specification of Basic Software Modules
AUTOSAR_CP_SWS_BSWGeneral
- [3] Requirements on Communication
AUTOSAR_CP_SRS_COM

3.2 Related specification

AUTOSAR provides a General Specification on Basic Software modules [2, SWS BSW General], which is also valid for Communication Stack Types.

Thus, the specification SWS BSW General shall be considered as additional and required specification for Communication Stack Types.

4 Constraints and assumptions

4.1 Limitations

No limitations.

4.2 Applicability to car domains

No restrictions.

4.3 Applicability to safety related environments

No restrictions, because the subject of this specification is a header file specifying types. It does not include or implement any functionality.

5 Dependencies to other modules

The communication stack type header file defines communication types based on the platform types [PltfTypes] (Platform_Types.h) header file. To prevent multiple includes of header files, the communication stack header file includes the standard types header file [StdTypes] which already includes both other files.

6 Requirements Tracing

The following tables reference the requirements specified in [3] and links to the fulfillment of these. Please note that if column “Satisfied by” is empty for a specific requirement this means that this requirement is not fulfilled by this document.

| Requirement | Description | Satisfied by |
|-----------------|--|--|
| [SRS_BSW_00441] | Naming convention for type, macro and function | [SWS_COMTYPE_91005] |
| [SRS_Com_02043] | AUTOSAR COM and LargeDataCOM shall provide a receive indication function | [SWS_Comtype_00004] [SWS_Comtype_00006] [SWS_Comtype_00007] [SWS_Comtype_00010] [SWS_Comtype_00014] [SWS_Comtype_00015] [SWS_Comtype_00017] [SWS_Comtype_00030] |
| [SRS_Com_02045] | AUTOSAR COM and LargeDataCOM shall provide a function to request the transmit buffer data for lower layer triggered transmission | [SWS_Comtype_00004] [SWS_Comtype_00006] [SWS_Comtype_00007] [SWS_Comtype_00010] [SWS_Comtype_00014] [SWS_Comtype_00015] [SWS_Comtype_00017] [SWS_Comtype_00030] |
| [SRS_Com_02095] | AUTOSAR COM and LargeDataCOM shall use the TP to fragment and reassemble large signals | [SWS_Comtype_00004] [SWS_Comtype_00006] [SWS_Comtype_00007] [SWS_Comtype_00010] [SWS_Comtype_00014] [SWS_Comtype_00015] [SWS_Comtype_00017] [SWS_Comtype_00030] |
| [SRS_Com_02114] | AUTOSAR COM and LargeDataCOM shall support independent development of CP Software Clusters | [SWS_COMTYPE_91001] |
| [SRS_Eth_00105] | Support of time stamping in hardware | [SWS_COMTYPE_91002] [SWS_COMTYPE_91003] [SWS_COMTYPE_91004] |
| [SRS_Eth_00167] | PTP Physical Clock Adjustment | [SWS_COMTYPE_91002] |
| [SRS_Eth_00172] | Ethernet Driver hardware supported data transfer | [SWS_COMTYPE_91005] |

Table 6.1: RequirementsTracing

7 Functional specification

7.1 General issues

[SWS_Comtype_00004] [It is not allowed to add any project or supplier specific extension to this file. Any extension invalidates the AUTOSAR conformity.] ([SRS_Com_02043](#), [SRS_Com_02045](#), [SRS_Com_02095](#))

[SWS_Comtype_00015] [Because many of the communication stack type are depending on the appropriate ECU, this file shall be generated dependent on the specific ECU configuration for each ECU independently.] ([SRS_Com_02043](#), [SRS_Com_02045](#), [SRS_Com_02095](#))

[SWS_Comtype_00030] [The value of [PduIdType](#) and [PduLengthType](#) shall be derived from the 'PduIdTypeEnum' and 'PduLengthTypeEnum' of the EcuCPduCollection container respectively.] ([SRS_Com_02043](#), [SRS_Com_02045](#), [SRS_Com_02095](#))

7.2 Error Classification

Section "Error Handling" of the document [2] "General Specification of Basic Software Modules" describes the error handling of the Basic Software in detail. Above all, it constitutes a classification scheme consisting of five error types which may occur in BSW modules.

Based on this foundation, the following section specifies particular errors arranged in the respective subsections below.

7.2.1 Development Errors

There are no development errors.

7.2.2 Runtime Errors

There are no runtime errors.

7.2.3 Transient Faults

There are no transient faults.

7.2.4 Production Errors

There are no production errors.

7.2.5 Extended Production Errors

There are no extended production errors.

7.3 Security Events

The module does not report security events.

8 API specification

8.1 Type definitions

8.1.1 PduldType

[SWS_COMTYPE_00005] Definition of datatype PduldType [

| | | | |
|----------------------|---|---|--|
| Name | PduldType | | |
| Kind | Type | | |
| Derived from | Basetype | Variation | |
| | uint16 | The size of this global type depends on the maximum number of PDUs used within one software module. | |
| | uint8 | The size of this global type depends on the maximum number of PDUs used within one software module. | |
| Range | 0...<Pduldmax> | – | Zero-based integer number The size of this global type depends on the maximum number of PDUs used within one software module. This parameter shall be generated by the generator tool depending on the value configured in EcuC virtual layer. This parameter shall be generated in ComStack_Cfg.h file Example : If no software module deals with more PDUs that 256, this type can be set to uint8. If at least one software module handles more than 256 PDUs, this type must globally be set to uint16. |
| Description | This type is used within the entire AUTOSAR Com Stack except for bus drivers. | | |
| Available via | ComStack_Types.h | | |

]()

[SWS_Comtype_00006] [Variables of this type serve as a unique identifier of a PDU within a software module or a set thereof, and also for interaction of two software modules where the Pduld of the corresponding target module is being used for referencing.] ([SRS_Com_02043](#), [SRS_Com_02045](#), [SRS_Com_02095](#))

[SWS_Comtype_00007] [In order to be able to perform table-indexing within a software module, variables of this type shall be zero-based and consecutive.

There might be several ranges of Pdulds in a module, one for each type of operation performed within that module (e.g. sending and receiving).] ([SRS_Com_02043](#), [SRS_Com_02045](#), [SRS_Com_02095](#))

[SWS_Comtype_00014] [Pduldmax, the maximum number of a Pduld range, is the number -1 of PDUs dealt with in the corresponding type of operation within that module.] ([SRS_Com_02043](#), [SRS_Com_02045](#), [SRS_Com_02095](#))

8.1.2 PduLengthType

[SWS_COMTYPE_00008] Definition of datatype PduLengthType [

| | | | |
|----------------------|---|--|--|
| Name | PduLengthType | | |
| Kind | Type | | |
| Derived from | Basetype | Variation | |
| | uint16 | The size of this global type depends on the maximum length of PDUs to be sent by an ECU. | |
| | uint32 | The size of this global type depends on the maximum length of PDUs to be sent by an ECU. | |
| | uint8 | The size of this global type depends on the maximum length of PDUs to be sent by an ECU. | |
| Range | 0...<PduLengthmax> | – | Zero-based integer number The size of this global type depends on the maximum length of PDUs to be sent by an ECU. This parameter shall be generated by the generator tool depending on the value configured in EcuC virtual layer. This parameter shall be generated in ComStack_Cfg.h file Example : If no segmentation is used the length depends on the maximum payload size of a frame of the underlying communication system (for FlexRay maximum size is 255, therefore uint8). If segmentation is used it depends on the maximum length of a segmented N-PDU (in general uint16 is used) |
| Description | This type shall be used within the entire AUTOSAR Com Stack of an ECU except for bus drivers. | | |
| Available via | ComStack_Types.h | | |

]()

[SWS_Comtype_00010] [Variables of this type serve as length information of a PDU. The length information is provided in number of bytes.] ([SRS_Com_02043](#), [SRS_-Com_02045](#), [SRS_Com_02095](#))

[SWS_Comtype_00017] [PduLengthmax, the maximum length of a Pdu, is the length of the largest (possibly segmented) PDU to be sent by the ECU.] ([SRS_Com_02043](#), [SRS_Com_02045](#), [SRS_Com_02095](#))

8.1.3 PduInfoType

[SWS_COMTYPE_00011] Definition of datatype PduInfoType [

| | |
|-----------------|-------------|
| Name | PduInfoType |
| Kind | Structure |
| Elements | SduDataPtr |





| | | |
|----------------------|--|---|
| | Type | uint8* |
| | Comment | Pointer to the SDU (i.e. payload data) of the PDU. The type of this pointer depends on the memory model being used at compile time. |
| | MetaDataPtr | |
| | Type | uint8* |
| | Comment | Pointer to the meta data (e.g. CAN ID, socket ID, diagnostic addresses) of the PDU, consisting of a sequence of meta data items. The length and type of the meta data items is statically configured for each PDU. Meta data items with more than 8 bits use platform byte order. |
| | SduLength | |
| | Type | PduLengthType |
| | Comment | Length of the SDU in bytes. |
| Description | Variables of this type shall be used to store the basic information about a PDU of any type, namely a pointer variable pointing to its SDU (payload), a pointer to Meta Data of the PDU, and the corresponding length of the SDU in bytes. | |
| Available via | ComStack_Types.h | |

]()

8.1.4 PNCHandleType

[SWS_COMTYPE_00036] Definition of datatype PNCHandleType [

| | |
|----------------------|--|
| Name | PNCHandleType |
| Kind | Type |
| Derived from | uint16 |
| Description | Used to store the identifier of a partial network cluster. |
| Available via | ComStack_Types.h |

]()

8.1.5 TPParameterType

[SWS_COMTYPE_00031] Definition of datatype TPParameterType [

| | | | |
|----------------------|---|------|---|
| Name | TPParameterType | | |
| Kind | Enumeration | | |
| Range | TP_STMIN | 0x00 | Separation Time |
| | TP_BS | 0x01 | Block Size |
| | TP_BC | 0x02 | The Band width control parameter used in FlexRay transport protocol module. |
| Description | Specify the parameter to which the value has to be changed (BS or STmin). | | |
| Available via | ComStack_Types.h | | |

]()

8.1.6 BufReq_ReturnType

[SWS_COMTYPE_00012] Definition of datatype BufReq_ReturnType [

| | | | |
|----------------------|---|------|---|
| Name | BufReq_ReturnType | | |
| Kind | Enumeration | | |
| Range | BUFREQ_OK | 0x00 | Buffer request accomplished successful. This status shall have the value 0. |
| | BUFREQ_E_NOT_OK | 0x01 | Buffer request not successful. Buffer cannot be accessed. This status shall have the value 1. |
| | BUFREQ_E_BUSY | 0x02 | Temporarily no buffer available. It's up the requester to retry request for a certain time. This status shall have the value 2. |
| | BUFREQ_E_OVFL | 0x03 | No Buffer of the required length can be provided. This status shall have the value 3. |
| Description | Variables of this type shall be used to store the result of a buffer request. | | |
| Available via | ComStack_Types.h | | |

]()

8.1.7 TpDataStateType

[SWS_COMTYPE_00027] Definition of datatype TpDataStateType [

| | | | |
|----------------------|---|------|--|
| Name | TpDataStateType | | |
| Kind | Enumeration | | |
| Range | TP_DATACONF | 0x00 | TP_DATACONF indicates that all data, that have been copied so far, are confirmed and can be removed from the TP buffer. Data copied by this API call are excluded and will be confirmed later. |
| | TP_DATARETRY | 0x01 | TP_DATARETRY indicates that this API call shall copy already copied data in order to recover from an error. In this case TxTpData Cnt specifies the offset of the first byte to be copied by the API call. |
| | TP_CONFPENDING | 0x02 | TP_CONFPENDING indicates that the previously copied data must remain in the TP. |
| Description | Variables of this type shall be used to store the state of TP buffer. | | |
| Available via | ComStack_Types.h | | |

]()

8.1.8 RetryInfoType

[SWS_COMTYPE_00037] Definition of datatype RetryInfoType [

| | | | |
|----------------------|---|--|--|
| Name | RetryInfoType | | |
| Kind | Structure | | |
| Elements | TpDataState | | |
| | Type | TpDataStateType | |
| | Comment | The enum type to be used to store the state of Tp buffer. | |
| | TxTpDataCnt | | |
| | Type | PduLengthType | |
| | Comment | Offset from the current position which identifies the number of bytes to be retransmitted. | |
| Description | Variables of this type shall be used to store the information about Tp buffer handling. | | |
| Available via | ComStack_Types.h | | |

]()

8.1.9 NetworkHandleType

[SWS_COMTYPE_00038] Definition of ImplementationDataType NetworkHandleType [

| | | | |
|----------------------|---|---|---------------------------|
| Name | NetworkHandleType | | |
| Kind | Type | | |
| Derived from | uint8 | | |
| Range | 0..255 | – | Zero-based integer number |
| Description | Variables of the type NetworkHandleType shall be used to store the identifier of a communication channel. | | |
| Variation | – | | |
| Available via | ComStack_Types.h | | |

]()

8.1.10 CbkHandleIdType

[SWS_COMTYPE_91001]{DRAFT} Definition of datatype CbkHandleIdType [

| | | | |
|----------------------|---|--|--|
| Name | CbkHandleIdType (draft) | | |
| Kind | Type | | |
| Derived from | uint16 | | |
| Description | Used for the handle Ids of Com and LdCom user callbacks. Tags: atp.Status=draft | | |
| Available via | ComStack_Types.h | | |

]([SRS_Com_02114](#))

8.1.11 TimeTupleType

[SWS_COMTYPE_91002]{DRAFT} Definition of datatype TimeTupleType [

| | | |
|----------------------|---|--|
| Name | TimeTupleType (draft) | |
| Kind | Structure | |
| Elements | timestampClockValue | |
| | Type | TimeStampType |
| | Comment | Value of the clock, which is used of ingress/egress timestamping |
| | disciplinedClockValue | |
| | Type | TimeStampType |
| | Comment | Value of the adjustable HW clock |
| | timeQuality | |
| | Type | TimeStampQualType |
| Description | <p>The Time Tuple represents the clock values of two related HW clocks</p> <ul style="list-style-type: none"> • the value of the clock used for timestamping of frames • and the corresponding value of the adjustable HW clock, derived by cross-timestamping <p>Tags: atp.Status=draft</p> | |
| Available via | ComStackTypes.h | |

]([SRS_Eth_00167](#), [SRS_Eth_00105](#))

8.1.12 TimeStampType

[SWS_COMTYPE_91003]{DRAFT} Definition of datatype TimeStampType [

| | | |
|-----------------|--|--|
| Name | TimeStampType (draft) | |
| Kind | Structure | |
| Elements | nanoseconds | |
| | Type | uint32 |
| | Comment | Nanoseconds part of the time |
| | seconds | |
| | Type | uint32 |
| | Comment | 32 bit LSB of the 48 bits Seconds part of the time |
| | secondsHi | |
| | Type | uint16 |
| Comment | 16 bit MSB of the 48 bits Seconds part of the time | |





| | |
|----------------------|--|
| Description | <p>Variables of this type are used for expressing time stamps including relative time and absolute calendar time. The absolute time starts at 1970-01-01.</p> <p>Value range of Seconds part:</p> <ul style="list-style-type: none"> • 0 .. (2⁴⁸ - 1), i.e. 0 to 3257812230d [0xFFFF FFFF FFFF] <p>Value range of Nanoseconds part:</p> <ul style="list-style-type: none"> • 0 to 999999999ns [0x3B9AC9FF] • invalid value in nanoseconds: [0x3B9ACA00] to [0x3FFFFFFF] • Bit 30 and 31 reserved, default: 0 <p>Tags: atp.Status=draft</p> |
| Available via | ComStackTypes.h |

](SRS_Eth_00105)

8.1.13 TimeStampQualType

[SWS_COMTYPE_91004]{DRAFT} Definition of datatype TimeStampQualType [

| | | | |
|----------------------|---|---|----------------------------------|
| Name | TimeStampQualType (draft) | | |
| Kind | Enumeration | | |
| Range | VALID | 0 | Timestamp is valid |
| | INVALID | 1 | Timestamp is invalid |
| | UNCERTAIN | 2 | Status of timestamp is uncertain |
| Description | <p>Depending on the HW, quality information regarding the evaluated timestamp might be supported. If not supported, the value shall be always Valid. For Uncertain and Invalid values, the upper layer shall discard the time stamp.</p> <p>Tags: atp.Status=draft</p> | | |
| Available via | ComStackTypes.h | | |

](SRS_Eth_00105)

8.1.14 ListElemStructType

[SWS_COMTYPE_91005]{DRAFT} Definition of datatype ListElemStructType [

| | | |
|-----------------|----------------------------|----------------------------|
| Name | ListElemStructType (draft) | |
| Kind | Structure | |
| Elements | DataLength | |
| | Type | uint16 |
| | Comment | Represents length of data |
| | DataPtr | |
| | Type | uint8* |
| | Comment | Represents pointer to data |
| NextListElemPtr | | |





| | | |
|----------------------|---|-------------------------------------|
| | Type | ListElemStructType* |
| | Comment | Pointer to next list element |
| Description | <p>This type defines one element of a single linked list. Each element represents on part of an associated data block. The data block could form for example an Ethernet frame. Each element addresses a data location, the data length and a pointer to the next element. The last node (tail) has NextListElemPtr set to NUL_PTR. The re-construction process of a data block (e.g. Ethernet frame) is performed by traversing from the first data element (head) to the last data element (tail). The single linked list is linked in network order (big-endian). Thus, the head element represents the most significant part of the data block (e.g. Ethernet frame)</p> <p>Tags: atp.Status=draft</p> | |
| Available via | ComStack_Types.h | |

|(SRS_BSW_00441, SRS_Eth_00172)

8.2 Function definitions

Not applicable.

9 Sequence diagrams

Not applicable.

10 Configuration specification

10.1 Published Information

For details refer to the chapter 10.3 “Published Information” in [\[2\]](#).

A Not applicable requirements

[SWS_Comtype_NA] [These requirements are not applicable to this specification.] (*SRS_BSW_00003, SRS_BSW_00004, SRS_BSW_00005, SRS_BSW_00006, SRS_BSW_00007, SRS_BSW_00009, SRS_BSW_00010, SRS_BSW_00101, SRS_BSW_00159, SRS_BSW_00160, SRS_BSW_00161, SRS_BSW_00162, SRS_BSW_00164, SRS_BSW_00167, SRS_BSW_00168, SRS_BSW_00171, SRS_BSW_00172, SRS_BSW_00300, SRS_BSW_00301, SRS_BSW_00302, SRS_BSW_00304, SRS_BSW_00305, SRS_BSW_00306, SRS_BSW_00307, SRS_BSW_00308, SRS_BSW_00309, SRS_BSW_00310, SRS_BSW_00312, SRS_BSW_00314, SRS_BSW_00318, SRS_BSW_00321, SRS_BSW_00323, SRS_BSW_00325, SRS_BSW_00327, SRS_BSW_00328, SRS_BSW_00330, SRS_BSW_00331, SRS_BSW_00333, SRS_BSW_00334, SRS_BSW_00335, SRS_BSW_00336, SRS_BSW_00337, SRS_BSW_00339, SRS_BSW_00341, SRS_BSW_00342, SRS_BSW_00343, SRS_BSW_00344, SRS_BSW_00345, SRS_BSW_00346, SRS_BSW_00347, SRS_BSW_00348, SRS_BSW_00350, SRS_BSW_00351, SRS_BSW_00353, SRS_BSW_00357, SRS_BSW_00358, SRS_BSW_00359, SRS_BSW_00360, SRS_BSW_00369, SRS_BSW_00373, SRS_BSW_00374, SRS_BSW_00377, SRS_BSW_00378, SRS_BSW_00379, SRS_BSW_00380, SRS_BSW_00383, SRS_BSW_00384, SRS_BSW_00385, SRS_BSW_00386, SRS_BSW_00388, SRS_BSW_00389, SRS_BSW_00390, SRS_BSW_00392, SRS_BSW_00393, SRS_BSW_00394, SRS_BSW_00395, SRS_BSW_00396, SRS_BSW_00397, SRS_BSW_00398, SRS_BSW_00399, SRS_BSW_00400, SRS_BSW_00401, SRS_BSW_00402, SRS_BSW_00403, SRS_BSW_00404, SRS_BSW_00405, SRS_BSW_00406, SRS_BSW_00407, SRS_BSW_00408, SRS_BSW_00409, SRS_BSW_00410, SRS_BSW_00411, SRS_BSW_00413, SRS_BSW_00414, SRS_BSW_00415, SRS_BSW_00416, SRS_BSW_00417, SRS_BSW_00419, SRS_BSW_00422, SRS_BSW_00423, SRS_BSW_00424, SRS_BSW_00425, SRS_BSW_00426, SRS_BSW_00427, SRS_BSW_00428, SRS_BSW_00429, SRS_BSW_00432, SRS_BSW_00433, SRS_BSW_00437, SRS_BSW_00438, SRS_BSW_00439, SRS_BSW_00440, SRS_BSW_00447, SRS_BSW_00448, SRS_BSW_00449, SRS_BSW_00450, SRS_BSW_00451, SRS_BSW_00452, SRS_BSW_00453, SRS_BSW_00454, SRS_BSW_00456, SRS_BSW_00457, SRS_BSW_00458, SRS_BSW_00459, SRS_BSW_00460, SRS_BSW_00461, SRS_BSW_00462, SRS_BSW_00463, SRS_BSW_00464, SRS_BSW_00465, SRS_BSW_00466, SRS_BSW_00467, SRS_BSW_00469, SRS_BSW_00470, SRS_BSW_00471, SRS_BSW_00472, SRS_BSW_00473, SRS_BSW_00477, SRS_BSW_00478, SRS_BSW_00479, SRS_BSW_00480, SRS_BSW_00481, SRS_BSW_00482, SRS_BSW_00483, SRS_BSW_00484, SRS_BSW_00485, SRS_BSW_00486, SRS_BSW_00487, SRS_BSW_00488, SRS_BSW_00489, SRS_BSW_00490, SRS_BSW_00491, SRS_BSW_00492, SRS_BSW_00493, SRS_BSW_00494, SRS_Com_00177, SRS_Com_00192, SRS_Com_00218, SRS_Com_02030, SRS_Com_02037, SRS_Com_02040, SRS_Com_02041, SRS_Com_02042, SRS_Com_02044, SRS_Com_02046, SRS_Com_02058, SRS_Com_02067, SRS_Com_02077, SRS_Com_02078, SRS_Com_02079, SRS_Com_02080, SRS_Com_02082, SRS_Com_02083, SRS_Com_02084,*

*SRS_Com_02086, SRS_Com_02087, SRS_Com_02088, SRS_Com_02089, SRS -
Com_02090, SRS_Com_02091, SRS_Com_02092, SRS_Com_02093, SRS_Com -
02094, SRS_Com_02096, SRS_Com_02097, SRS_Com_02098, SRS_Com_02107,
SRS_Com_02108, SRS_Com_02109, SRS_Com_02110, SRS_Com_02111, SRS -
Com_02112, SRS_Com_02113)*