

Document Title	Requirements on Timing Extensions
Document Owner	AUTOSAR
Document Responsibility	AUTOSAR
Document Identification No	410

Document Status	published
Part of AUTOSAR Standard	Foundation
Part of Standard Release	R23-11

Document Change History			
Date	Release	Changed by	Description
2023-11-23	R23-11	AUTOSAR Release Management	<ul style="list-style-type: none"> • Editorial changes
2022-11-24	R22-11	AUTOSAR Release Management	<ul style="list-style-type: none"> • Added RS_TIMEX_00026 • Remove uptrace to defunct requirements RS_Main_00160, RS_Main_00161, RS_Main_00480
2021-11-25	R21-11	AUTOSAR Release Management	<ul style="list-style-type: none"> • No content changes
2020-11-30	R20-11	AUTOSAR Release Management	<ul style="list-style-type: none"> • Migration of document to standard AUTOSAR Foundation (FO) • Added requirement for supporting Adaptive Platform • Added requirement for supporting Classic Platform Software Custer • Revised the structure of the document to comply with the specifications for AUTOSAR requirements specifications



△

2019-11-28	R19-11	AUTOSAR Release Management	<ul style="list-style-type: none"> • The status of requirement RS_TIMEX_00021 is set to "removed" and all remaining references within the document have been cleaned up. • Rationale has been given and reference to use case has been added for RS_TIMEX_00014. • Changed Document Status from Final to published
2018-10-31	4.4.0	AUTOSAR Release Management	<ul style="list-style-type: none"> • Added requirements RS_TIMEX_00022 and RS_TIMEX_00023.
2017-12-08	4.3.1	AUTOSAR Release Management	<ul style="list-style-type: none"> • Editorial changes.
2016-11-30	4.3.0	AUTOSAR Release Management	<ul style="list-style-type: none"> • Editorial changes.
2015-07-31	4.2.2	AUTOSAR Release Management	<ul style="list-style-type: none"> • Editorial changes.
2014-10-31	4.2.1	AUTOSAR Release Management	<ul style="list-style-type: none"> • Editorial changes.
2013-10-31	4.1.2	AUTOSAR Release Management	<ul style="list-style-type: none"> • Removed requirement RS_TIMEX_00021 because it is an duplicate of RS_TIMEX_00009.
2011-12-22	4.0.3	AUTOSAR Administration	<ul style="list-style-type: none"> • Added requirements RS_TIMEX_00013 to RS_TIMEX_00021 in order to reflect new features to be supported.
2009-12-18	4.0.1	AUTOSAR Administration	<ul style="list-style-type: none"> • Initial Release

Disclaimer

This work (specification and/or software implementation) and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the work.

The material contained in this work is protected by copyright and other types of intellectual property rights. The commercial exploitation of the material contained in this work requires a license to such intellectual property rights.

This work may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the work may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The work has been developed for automotive applications only. It has neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

Contents

1	Introduction	8
1.1	Scope of this document	8
1.2	Document Conventions	9
1.3	Guidelines	10
2	Use Case and Requirements Tracing	11
3	Requirements	14
3.1	Platform Independent Requirements	14
3.1.1	Timing properties	14
3.1.2	Timing constraints	14
3.1.3	Optionality of timing constraints	15
3.1.4	Event chains	15
3.1.5	Structure of event chains	16
3.1.6	Triggering behavior of event chains	16
3.1.7	Synchronization of event chains	17
3.1.8	Multiple asynchronous time bases	17
3.1.9	Validity of timing properties and constraints	18
3.1.10	Mode dependency	18
3.1.11	Sensor/actuator delay	19
3.1.12	Some elements of the Timing Extensions shall be blueprintable	19
3.1.13	Synchronization constraint on events	20
3.1.14	AUTOSAR Methodology support	20
3.1.15	Support for System Level Logical Execution Time	21
3.2	Classic Platform Requirements	21
3.2.1	Loop-back signal flow in sender-receiver communication	21
3.2.2	Specification of timing resources	22
3.2.3	Runnable Entities	23
3.2.4	Timing Requirements of SW-Components	23
3.2.5	Predefined events for port interfaces at VFB level	24
3.2.6	Support for events indicating variable accesses	24
3.2.7	Support for Logical Execution Time	25
3.2.8	Support for Specifying Synchronization	26
3.2.9	Support for Software Cluster	26
3.3	Adaptive Platform Requirements	27
3.3.1	Support for Service Oriented Communication	27
4	Supported use cases	28
4.1	End-to-end timing	28
4.1.1	Use case 1: Local Timing Analysis (Scheduling Analysis)	28
4.1.2	Use case 2: Analysis of end-to-end timing in open loop control systems	28
4.1.3	Use case 3: Analysis of end-to-end timing in closed loop control systems	29

4.1.4	Use case 4: Validation of end-to-end timing	29
4.2	Synchronization	29
4.2.1	Use case 5: Sensor data fusion in multi-sensor systems	29
4.2.2	Use case 6: Actuator synchronization	30
4.2.3	Use case 7: Bus synchronization and Gateway	30
4.3	Early prediction	30
4.3.1	Use case 8: Modification impacts due to adding a component	31
4.3.2	Use case 9: Support for hardware dimensioning	31
4.3.3	Use case 10: Topology decisions	32
5	Change History	33
5.1	Change History of this document according to AUTOSAR Release 4.1.1	33
5.1.1	Added Requirements in R4.1.1	33
5.1.2	Changed Requirements in R4.1.1	33
5.1.3	Deleted Requirements in R4.1.1	33
5.2	Change History of this document according to AUTOSAR Release 4.1.2	33
5.2.1	Added Requirements in R4.1.2	33
5.2.2	Changed Requirements in R4.1.2	34
5.2.3	Deleted Requirements in R4.1.2	34
5.3	Change History of this document according to AUTOSAR Release 4.1.3	34
5.3.1	Added Requirements in R4.1.3	34
5.3.2	Changed Requirements in R4.1.3	34
5.3.3	Deleted Requirements in R4.1.3	34
5.4	Change History of this document according to AUTOSAR Release 4.2.1	34
5.4.1	Added Requirements in R4.2.1	34
5.4.2	Changed Requirements in R4.2.1	34
5.4.3	Deleted Requirements in R4.2.1	35
5.5	Change History of this document according to AUTOSAR Release 4.2.2	35
5.5.1	Added Requirements in R4.2.2	35
5.5.2	Changed Requirements in R4.2.2	35
5.5.3	Deleted Requirements in R4.2.2	35
5.6	Change History of this document according to AUTOSAR Release 4.3.0	35
5.6.1	Added Requirements in R4.3.0	35
5.6.2	Changed Requirements in R4.3.0	35
5.6.3	Deleted Requirements in R4.3.0	35
5.7	Change History of this document according to AUTOSAR Release 4.3.1	36
5.7.1	Added Requirements in R4.3.1	36
5.7.2	Changed Requirements in R4.3.1	36
5.7.3	Deleted Requirements in R4.3.1	36
5.8	Change History of this document according to AUTOSAR Release 4.4.0	36
5.8.1	Added Requirements in R4.4.0	36
5.8.2	Changed Requirements in R4.4.0	36
5.8.3	Deleted Requirements in R4.4.0	36
5.9	Change History of this document according to AUTOSAR Release R19-11	37
5.9.1	Added Requirements in R19-11	37

5.9.2	Changed Requirements in R19-11	37
5.9.3	Deleted Requirements in R19-11	37
5.10	Change History of this document according to AUTOSAR Release R20-11	37
5.10.1	Added Requirements in R20-11	37
5.10.2	Changed Requirements in R20-11	37
5.10.3	Deleted Requirements in R20-11	37
5.11	Change History of this document according to AUTOSAR Release R21-11	38
5.11.1	Added Requirements in R21-11	38
5.11.2	Changed Requirements in R21-11	38
5.11.3	Deleted Requirements in R21-11	38
5.12	Change History of this document according to AUTOSAR Release R22-11	38
5.12.1	Added Requirements in R22-11	38
5.12.2	Changed Requirements in R22-11	38
5.12.3	Deleted Requirements in R22-11	38
5.13	Change History of this document according to AUTOSAR Release R23-11	39
5.13.1	Added Requirements in R23-11	39
5.13.2	Changed Requirements in R23-11	39
5.13.3	Deleted Requirements in R23-11	39

References

- [1] Specification of Timing Extensions for Classic Platform
AUTOSAR_CP_TPS_TimingExtensions
- [2] Specification of Timing Extensions for Adaptive Platform
AUTOSAR_AP_TPS_TimingExtensions
- [3] Standardization Template
AUTOSAR_FO_TPS_StandardizationTemplate
- [4] Main Requirements
AUTOSAR_FO_RS_Main
- [5] Timing Analysis and Design
AUTOSAR_FO_TR_TimingAnalysis

1 Introduction

This document defines the requirements imposed on the AUTOSAR Specification of Timing Extensions [1] and [2]. In general, the AUTOSAR Specification of Timing Extensions shall support both AUTOSAR platforms, namely the Classic and Adaptive Platform. Therefore, the chapter 3 is subdivided into three sections: section 3.1 contains the requirements imposed on both platforms, section 3.2 contains requirements that are imposed solely on the classic platform, and section 3.3 contains requirements that are imposed solely on the adaptive platform.

1.1 Scope of this document

This document collects the requirements on the Timing Model and its incorporation into the AUTOSAR templates.

The main goal of the Timing Model is the extension of the AUTOSAR templates with timing information to enable the analysis and validation of a system's timing behavior.

The requirements collected in this document will be satisfied by the AUTOSAR Specification of Timing Extension [1] and [2].

1.2 Document Conventions

The representation of requirements in AUTOSAR documents follows the table specified in [TPS_STDT_00078], see Standardization Template, chapter Support for Traceability ([3]).

The verbal forms for the expression of obligation specified in [TPS_STDT_00053] shall be used to indicate requirements, see Standardization Template, chapter Support for Traceability ([3]).

1.3 Guidelines

Existing specifications shall be referenced (in form of a single requirement). Differences to these specifications are specified as additional requirements. All Requirements shall have the following properties:

- **Redundancy**
Requirements shall not be repeated within one requirement or in other requirements.
- **Clearness**
All requirements shall allow one possibility of interpretation only. Used technical terms that are not in the glossary must be defined.
- **Atomicity**
Each Requirement shall only contain one requirement. A Requirement is atomic if it cannot be split up in further requirements.
- **Testability**
Requirements shall be testable by analysis, review or test.
- **Traceability**
The source and status of a requirement shall be visible at all times.

2 Use Case and Requirements Tracing

The following table list all use cases, main requirements, and links them to the related requirements.

Requirement	Description	Satisfied by
[RS_Main_00010]	Safety Mechanisms	[RS_TIMEX_00022] [RS_TIMEX_00023] [RS_TIMEX_00025] [RS_TIMEX_00026]
[RS_Main_00011]	Mechanisms for Reliable Systems	[RS_TIMEX_00022] [RS_TIMEX_00023] [RS_TIMEX_00025] [RS_TIMEX_00026]
[RS_Main_00030]	Safety Related Process Support	[RS_TIMEX_00001] [RS_TIMEX_00002] [RS_TIMEX_00003] [RS_TIMEX_00004] [RS_TIMEX_00005] [RS_TIMEX_00009] [RS_TIMEX_00010] [RS_TIMEX_00011] [RS_TIMEX_00012] [RS_TIMEX_00013] [RS_TIMEX_00014] [RS_TIMEX_00015] [RS_TIMEX_00016] [RS_TIMEX_00017] [RS_TIMEX_00018] [RS_TIMEX_00019] [RS_TIMEX_00020] [RS_TIMEX_00025]
[RS_Main_00050]	AUTOSAR shall provide an Execution Framework towards applications to implement concurrent application internal control flows	[RS_TIMEX_00022] [RS_TIMEX_00023] [RS_TIMEX_00025] [RS_TIMEX_00026]
[RS_Main_00080]	Formal Description Language	[RS_TIMEX_00001] [RS_TIMEX_00002] [RS_TIMEX_00004] [RS_TIMEX_00005] [RS_TIMEX_00009] [RS_TIMEX_00010] [RS_TIMEX_00011] [RS_TIMEX_00012] [RS_TIMEX_00013] [RS_TIMEX_00014] [RS_TIMEX_00015] [RS_TIMEX_00016] [RS_TIMEX_00017] [RS_TIMEX_00018] [RS_TIMEX_00019] [RS_TIMEX_00020]
[RS_Main_00130]	Hardware Abstraction Layer	[RS_TIMEX_00022] [RS_TIMEX_00023] [RS_TIMEX_00026]
[RS_Main_00150]	AUTOSAR shall support the deployment and reallocation of AUTOSAR Application Software	[RS_TIMEX_00022] [RS_TIMEX_00023] [RS_TIMEX_00024] [RS_TIMEX_00025] [RS_TIMEX_00026]
[RS_Main_00180]	Intellectual Property Protection	[RS_TIMEX_00001] [RS_TIMEX_00002] [RS_TIMEX_00004] [RS_TIMEX_00005] [RS_TIMEX_00009] [RS_TIMEX_00010] [RS_TIMEX_00012] [RS_TIMEX_00013] [RS_TIMEX_00014] [RS_TIMEX_00015] [RS_TIMEX_00016] [RS_TIMEX_00017] [RS_TIMEX_00018] [RS_TIMEX_00019] [RS_TIMEX_00020]
[RS_Main_00200]	Resource Efficiency	[RS_TIMEX_00001] [RS_TIMEX_00002] [RS_TIMEX_00004] [RS_TIMEX_00005] [RS_TIMEX_00009] [RS_TIMEX_00010] [RS_TIMEX_00012] [RS_TIMEX_00013] [RS_TIMEX_00014] [RS_TIMEX_00015] [RS_TIMEX_00016] [RS_TIMEX_00017] [RS_TIMEX_00018] [RS_TIMEX_00019] [RS_TIMEX_00020] [RS_TIMEX_00022] [RS_TIMEX_00023] [RS_TIMEX_00025] [RS_TIMEX_00026]





Requirement	Description	Satisfied by
[RS_Main_00230]	Network Technology Support	[RS_TIMEX_00001] [RS_TIMEX_00002] [RS_TIMEX_00004] [RS_TIMEX_00005] [RS_TIMEX_00009] [RS_TIMEX_00010] [RS_TIMEX_00012] [RS_TIMEX_00013] [RS_TIMEX_00014] [RS_TIMEX_00015] [RS_TIMEX_00016] [RS_TIMEX_00017] [RS_TIMEX_00018] [RS_TIMEX_00019] [RS_TIMEX_00020]
[RS_Main_00300]	AUTOSAR shall provide data exchange formats to support work-share in large inter and intra company development groups	[RS_TIMEX_00001] [RS_TIMEX_00002] [RS_TIMEX_00004] [RS_TIMEX_00005] [RS_TIMEX_00009] [RS_TIMEX_00010] [RS_TIMEX_00011] [RS_TIMEX_00012] [RS_TIMEX_00013] [RS_TIMEX_00014] [RS_TIMEX_00015] [RS_TIMEX_00016] [RS_TIMEX_00017] [RS_TIMEX_00018] [RS_TIMEX_00019] [RS_TIMEX_00020] [RS_TIMEX_00025]
[RS_Main_00310]	AUTOSAR shall support hierarchical Application Software design methods	[RS_TIMEX_00001] [RS_TIMEX_00002] [RS_TIMEX_00004] [RS_TIMEX_00005] [RS_TIMEX_00009] [RS_TIMEX_00010] [RS_TIMEX_00012] [RS_TIMEX_00013] [RS_TIMEX_00014] [RS_TIMEX_00015] [RS_TIMEX_00016] [RS_TIMEX_00017] [RS_TIMEX_00018] [RS_TIMEX_00019] [RS_TIMEX_00020]
[RS_Main_00320]	AUTOSAR shall provide formats to specify system development	[RS_TIMEX_00001] [RS_TIMEX_00002] [RS_TIMEX_00004] [RS_TIMEX_00005] [RS_TIMEX_00009] [RS_TIMEX_00010] [RS_TIMEX_00011] [RS_TIMEX_00012] [RS_TIMEX_00013] [RS_TIMEX_00014] [RS_TIMEX_00015] [RS_TIMEX_00016] [RS_TIMEX_00017] [RS_TIMEX_00018] [RS_TIMEX_00019] [RS_TIMEX_00020]
[RS_Main_00340]	AUTOSAR shall support the continuous timing requirement analysis	[RS_TIMEX_00001] [RS_TIMEX_00002] [RS_TIMEX_00004] [RS_TIMEX_00005] [RS_TIMEX_00006] [RS_TIMEX_00007] [RS_TIMEX_00008] [RS_TIMEX_00009] [RS_TIMEX_00010] [RS_TIMEX_00011] [RS_TIMEX_00012] [RS_TIMEX_00013] [RS_TIMEX_00014] [RS_TIMEX_00015] [RS_TIMEX_00016] [RS_TIMEX_00017] [RS_TIMEX_00018] [RS_TIMEX_00019] [RS_TIMEX_00020]
[RS_Main_00350]	Documented Software Architecture	[RS_TIMEX_00001] [RS_TIMEX_00002] [RS_TIMEX_00004] [RS_TIMEX_00005] [RS_TIMEX_00009] [RS_TIMEX_00010] [RS_TIMEX_00012] [RS_TIMEX_00013] [RS_TIMEX_00014] [RS_TIMEX_00015] [RS_TIMEX_00016] [RS_TIMEX_00017] [RS_TIMEX_00018] [RS_TIMEX_00019] [RS_TIMEX_00020]
[RS_Main_00360]	Variant Management Support	[RS_TIMEX_00001] [RS_TIMEX_00002] [RS_TIMEX_00004] [RS_TIMEX_00005] [RS_TIMEX_00009] [RS_TIMEX_00010] [RS_TIMEX_00011] [RS_TIMEX_00012] [RS_TIMEX_00013] [RS_TIMEX_00014] [RS_TIMEX_00015] [RS_TIMEX_00016] [RS_TIMEX_00017] [RS_TIMEX_00018] [RS_TIMEX_00019] [RS_TIMEX_00020]





Requirement	Description	Satisfied by
[RS_Main_00410]	AUTOSAR shall provide specifications for routines commonly used by Application Software to support sharing and optimization	[RS_TIMEX_00022] [RS_TIMEX_00023] [RS_TIMEX_00026]
[RS_Main_00460]	AUTOSAR shall standardize methods to organize mode management on Application, ECU and System level	[RS_TIMEX_00001] [RS_TIMEX_00002] [RS_TIMEX_00004] [RS_TIMEX_00005] [RS_TIMEX_00009] [RS_TIMEX_00010] [RS_TIMEX_00011] [RS_TIMEX_00012] [RS_TIMEX_00013] [RS_TIMEX_00014] [RS_TIMEX_00015] [RS_TIMEX_00016] [RS_TIMEX_00017] [RS_TIMEX_00018] [RS_TIMEX_00019] [RS_TIMEX_00020]
[RS_Main_00490]	AUTOSAR processes shall be compliant to ISO26262	[RS_TIMEX_00001] [RS_TIMEX_00002] [RS_TIMEX_00004] [RS_TIMEX_00005] [RS_TIMEX_00009] [RS_TIMEX_00010] [RS_TIMEX_00011] [RS_TIMEX_00012] [RS_TIMEX_00013] [RS_TIMEX_00014] [RS_TIMEX_00015] [RS_TIMEX_00016] [RS_TIMEX_00017] [RS_TIMEX_00018] [RS_TIMEX_00019] [RS_TIMEX_00020]
[RS_Main_00500]	AUTOSAR shall provide naming conventions	[RS_TIMEX_00001] [RS_TIMEX_00002] [RS_TIMEX_00004] [RS_TIMEX_00005] [RS_TIMEX_00009] [RS_TIMEX_00010] [RS_TIMEX_00011] [RS_TIMEX_00012] [RS_TIMEX_00013] [RS_TIMEX_00014] [RS_TIMEX_00015] [RS_TIMEX_00016] [RS_TIMEX_00017] [RS_TIMEX_00018] [RS_TIMEX_00019] [RS_TIMEX_00020]
[RS_Main_01001]	Intra ECU Communication Support	[RS_TIMEX_00022] [RS_TIMEX_00023] [RS_TIMEX_00026]

Table 2.1: RequirementsTracing

3 Requirements

This chapter describes all requirements that are the basis for the AUTOSAR Specification of Timing Extensions [1] and [2]. The requirements trace back to main requirements [4].

3.1 Platform Independent Requirements

This section defines requirements imposed on all AUTOSAR platforms, namely the AUTOSAR Classic, AUTOSAR Adaptive and AUTOSAR Abstract Platform.

3.1.1 Timing properties

[RS_TIMEX_00001] Timing properties [

Description:	The AUTOSAR templates shall provide the means to describe the timing properties of a system's dynamics, which are determined by the consumption of computation, communication, and other hardware resources.
Rationale:	The description of timing properties in the AUTOSAR templates is an essential prerequisite for the analysis and validation of a system's timing behavior or its prediction early in the process.
Use Case:	Analysis and validation of timing behavior, early prediction of modification impacts, support for hardware dimensioning, system configuration optimization. See also sections 4.1.1 , 4.1.2 , 4.1.3 , 4.1.4 , 4.2.1 , 4.2.2 , 4.2.3 , 4.3.1 , 4.3.2 and 4.3.3
Dependencies:	-
AppliesTo:	AP, CP
Supporting Material:	-

]([RS_Main_00030](#), [RS_Main_00080](#), [RS_Main_00180](#), [RS_Main_00200](#), [RS_Main_00230](#), [RS_Main_00300](#), [RS_Main_00310](#), [RS_Main_00320](#), [RS_Main_00340](#), [RS_Main_00350](#), [RS_Main_00360](#), [RS_Main_00460](#), [RS_Main_00490](#), [RS_Main_00500](#))

3.1.2 Timing constraints

[RS_TIMEX_00002] Timing constraints [

Description:	The AUTOSAR templates shall provide the means to describe timing constraints, such as software and hardware latency, input/output delay, synchronization, and execution order with clearly defined semantics. Also, the scope and the boundaries of timing constraints shall be explicitly described.
---------------------	---





Rationale:	The description of timing constraints in the AUTOSAR templates is an essential prerequisite to formally capture expectations and limitations on a system's timing behavior which guide the system generation process and can be used to validate a given system configuration.
Use Case:	Analysis and validation of timing behavior, support for hardware dimensioning, system configuration optimization. See also sections 4.1.1 , 4.1.2 , 4.1.3 , 4.1.4 , 4.2.1 , 4.2.2 , 4.2.3 , 4.3.1 , 4.3.2 and 4.3.3
Dependencies:	[RS_TIMEX_00004]
AppliesTo:	AP, CP
Supporting Material:	-

|([RS_Main_00030](#), [RS_Main_00080](#), [RS_Main_00180](#), [RS_Main_00200](#), [RS_Main_00230](#), [RS_Main_00300](#), [RS_Main_00310](#), [RS_Main_00320](#), [RS_Main_00340](#), [RS_Main_00350](#), [RS_Main_00360](#), [RS_Main_00460](#), [RS_Main_00490](#), [RS_Main_00500](#))

3.1.3 Optionality of timing constraints

[RS_TIMEX_00003] Optionality of timing constraints [

Description:	The usage of timing constraints in the AUTOSAR templates shall be optional.
Rationale:	Usually timing constraints are only specified for a limited number of e.g. safety-related sub-systems, but not for the complete system.
Use Case:	Analysis and validation of timing behavior
Dependencies:	-
AppliesTo:	AP, CP
Supporting Material:	-

|([RS_Main_00030](#))

3.1.4 Event chains

[RS_TIMEX_00004] Event chains [

Description:	The AUTOSAR templates shall provide the means to describe timing specific event chains. An event chain is used as the subject to attach a timing constraint. It describes the temporal correlation between two observable events, referred to as stimulus and response, that have a functional dependency.
Rationale:	Event chains are an essential prerequisite to define the scope and semantics of timing constraints.





Use Case:	Analysis and validation of timing behavior. See also sections 4.1.1 , 4.1.2 , 4.1.3 , 4.1.4 , 4.2.1 , 4.2.2 , 4.2.3 , 4.3.1 , 4.3.2 and 4.3.3
Dependencies:	-
AppliesTo:	AP, CP
Supporting Material:	-

]([RS_Main_00030](#), [RS_Main_00080](#), [RS_Main_00180](#), [RS_Main_00200](#), [RS_Main_00230](#), [RS_Main_00300](#), [RS_Main_00310](#), [RS_Main_00320](#), [RS_Main_00340](#), [RS_Main_00350](#), [RS_Main_00360](#), [RS_Main_00460](#), [RS_Main_00490](#), [RS_Main_00500](#))

3.1.5 Structure of event chains

[RS_TIMEX_00005] Structure of event chains [

Description:	It shall be possible to organize event chains in hierarchies. That is, event chains can be built up from arbitrary event sub-chains. Leaves of the hierarchy are atomic event chains. Atomic event chains are defined in the sense that stimulus and response are clearly defined by the interaction semantics.
Rationale:	A hierarchical event chain structure supports the scalability and evolution of timing constraints.
Use Case:	Analysis and validation of timing behavior. See also sections 4.1.1 , 4.1.2 , 4.1.3 , 4.1.4 , 4.2.1 , 4.2.2 , 4.2.3 , 4.3.1 , 4.3.2 and 4.3.3
Dependencies:	[RS_TIMEX_00004]
AppliesTo:	AP, CP
Supporting Material:	-

]([RS_Main_00030](#), [RS_Main_00080](#), [RS_Main_00180](#), [RS_Main_00200](#), [RS_Main_00230](#), [RS_Main_00300](#), [RS_Main_00310](#), [RS_Main_00320](#), [RS_Main_00340](#), [RS_Main_00350](#), [RS_Main_00360](#), [RS_Main_00460](#), [RS_Main_00490](#), [RS_Main_00500](#))

3.1.6 Triggering behavior of event chains

[RS_TIMEX_00006] Triggering behavior of event chains [

Description:	The AUTOSAR templates shall provide the means to describe the triggering behavior (e.g. periodic, sporadic, and arbitrary) of event chains.
Rationale:	The analysis and validation of an event chain's timing constraints requires to make assumptions about the occurrence characteristics of the according stimulus and response events.
Use Case:	Analysis and validation of timing behavior. See also sections 4.1.1 , 4.1.2 , 4.1.3 , 4.1.4 , 4.2.1 , 4.2.2 , 4.2.3 , 4.3.1 , 4.3.2 and 4.3.3



△

Dependencies:	[RS_TIMEX_00004]
AppliesTo:	AP, CP
Supporting Material:	-

](RS_Main_00340)

3.1.7 Synchronization of event chains

[RS_TIMEX_00007] Synchronization of event chains [

Description:	The AUTOSAR templates shall provide the means to describe timing constraints for the synchronization of multiple event chains with possibly independent stimulus and response events.
Rationale:	Synchronization is a key issue when redundant communication is considered.
Use Case:	Analysis and validation of timing behavior. See also sections 4.1.1 , 4.1.2 , 4.1.3 , 4.1.4 , 4.2.1 , 4.2.2 , 4.2.3 , 4.3.2 and 4.3.3
Dependencies:	[RS_TIMEX_00002],[RS_TIMEX_00004]
AppliesTo:	AP, CP
Supporting Material:	-

](RS_Main_00340)

3.1.8 Multiple asynchronous time bases

[RS_TIMEX_00008] Multiple asynchronous time bases [

Description:	The AUTOSAR templates shall provide the means to describe multiple asynchronous clocks/time bases and their interrelation.
Rationale:	In networked systems it is reasonable to describe synchronous events even for multiple asynchronous time bases.
Use Case:	Analysis and validation of timing behavior. See also sections 4.1.1 , 4.1.2 , 4.1.3 , 4.1.4 , 4.2.1 , 4.2.2 , 4.2.3 , 4.3.2 and 4.3.3
Dependencies:	-
AppliesTo:	AP, CP
Supporting Material:	-

](RS_Main_00340)

3.1.9 Validity of timing properties and constraints

[RS_TIMEX_00010] Validity of timing properties and constraints [

Description:	The AUTOSAR templates shall provide the means to describe the validity of timing properties and constraints, e.g. for a certain hardware or software configuration.
Rationale:	To utilize timing properties and constraints correctly, it is necessary to know the context in which they were obtained: for example a WCET is only valid for a specific implementation and target platform.
Use Case:	Analysis and validation of timing behavior. See also sections 4.1.1 , 4.1.2 , 4.1.3 , 4.1.4 , 4.2.1 , 4.2.2 , 4.2.3 , 4.3.1 , 4.3.2 and 4.3.3
Dependencies:	[RS_TIMEX_00001],[RS_TIMEX_00002]
AppliesTo:	AP, CP
Supporting Material:	-

]([RS_Main_00030](#), [RS_Main_00080](#), [RS_Main_00180](#), [RS_Main_00200](#), [RS_Main_00230](#), [RS_Main_00300](#), [RS_Main_00310](#), [RS_Main_00320](#), [RS_Main_00340](#), [RS_Main_00350](#), [RS_Main_00360](#), [RS_Main_00460](#), [RS_Main_00490](#), [RS_Main_00500](#))

3.1.10 Mode dependency

[RS_TIMEX_00011] Mode dependency [

Description:	The AUTOSAR templates shall provide the means to describe the dependency of timing properties and constraints on operation modes defined on system and ECU level.
Rationale:	Depending on the mode a system's behavior may change, which has an impact on the system's timing characteristics.
Use Case:	Analysis and validation of timing behavior. See also sections 4.1.1 , 4.1.2 , 4.1.3 , 4.1.4 , 4.2.1 , 4.2.2 , 4.2.3 , 4.3.1 , 4.3.2 and 4.3.3
Dependencies:	[RS_TIMEX_00001],[RS_TIMEX_00002],[RS_TIMEX_00010]
AppliesTo:	AP, CP
Supporting Material:	-

]([RS_Main_00030](#), [RS_Main_00080](#), [RS_Main_00300](#), [RS_Main_00320](#), [RS_Main_00340](#), [RS_Main_00360](#), [RS_Main_00460](#), [RS_Main_00490](#), [RS_Main_00500](#))

3.1.11 Sensor/actuator delay

[RS_TIMEX_00012] Sensor/actuator delay [

Description:	The AUTOSAR templates shall provide the means to describe the time relation between a physical sensor acquisition (or a physical actuator change) and the availability (or provision) of the corresponding data to (from) a software component dealing with this sensor (or actuator).
Rationale:	This information can be used to specify the time delay for the data flow between a physical sensor (or actuator) to the corresponding sensor (or actuator) software component without referring to a concrete hardware realization.
Use Case:	Analysis and validation of timing behavior. See also sections 4.1.1 , 4.1.2 , 4.1.3 , 4.1.4 , 4.2.1 , 4.2.2 , 4.2.3 , 4.3.1 , 4.3.2 and 4.3.3
Dependencies:	[RS_TIMEX_00002]
AppliesTo:	AP, CP
Supporting Material:	-

] ([RS_Main_00030](#), [RS_Main_00080](#), [RS_Main_00180](#), [RS_Main_00200](#), [RS_Main_00230](#), [RS_Main_00300](#), [RS_Main_00310](#), [RS_Main_00320](#), [RS_Main_00340](#), [RS_Main_00350](#), [RS_Main_00360](#), [RS_Main_00460](#), [RS_Main_00490](#), [RS_Main_00500](#))

3.1.12 Some elements of the Timing Extensions shall be blueprintable

[RS_TIMEX_00016] Some elements of the Timing Extensions shall be blueprintable [

Description:	The Timing Extensions shall enable one to specifying timing constraints for elements, namely elements of port interfaces, part of the Application Interface specification.
Rationale:	The information contained in the Application Interface Specification shall be annotated with the tolerated age, periods, etc.
Use Case:	-
Dependencies:	[RS_TIMEX_00001]
AppliesTo:	AP, CP
Supporting Material:	-

] ([RS_Main_00030](#), [RS_Main_00080](#), [RS_Main_00180](#), [RS_Main_00200](#), [RS_Main_00230](#), [RS_Main_00300](#), [RS_Main_00310](#), [RS_Main_00320](#), [RS_Main_00340](#), [RS_Main_00350](#), [RS_Main_00360](#), [RS_Main_00460](#), [RS_Main_00490](#), [RS_Main_00500](#))

3.1.13 Synchronization constraint on events

[RS_TIMEX_00017] Synchronization constraint on events [

Description:	The Timing Extension shall enable on to impose synchronization constraints on two or more timing description events.
Rationale:	While building up systems it is necessary to specify that the occurrence of events shall be synchronous, like in case of a turn signal indicator, anti blocking systems where information from several wheels are important.
Use Case:	-
Dependencies:	[RS_TIMEX_00001]
AppliesTo:	AP, CP
Supporting Material:	-

] ([RS_Main_00030](#), [RS_Main_00080](#), [RS_Main_00180](#), [RS_Main_00200](#), [RS_Main_00230](#), [RS_Main_00300](#), [RS_Main_00310](#), [RS_Main_00320](#), [RS_Main_00340](#), [RS_Main_00350](#), [RS_Main_00360](#), [RS_Main_00460](#), [RS_Main_00490](#), [RS_Main_00500](#))

3.1.14 AUTOSAR Methodology support

[RS_TIMEX_00019] AUTOSAR Methodology support [

Description:	The Timing Extensions shall provide means to support reuse and the usage of timing models already specified on the SW-C type level.
Rationale:	The Timing Extensions lack the support of supporting reuse in an efficient way. In order to accomplish this the Timing Extension shall provide means to make use of timing models from different timing views.
Use Case:	-
Dependencies:	[RS_TIMEX_00001]
AppliesTo:	AP, CP
Supporting Material:	-

] ([RS_Main_00030](#), [RS_Main_00080](#), [RS_Main_00180](#), [RS_Main_00200](#), [RS_Main_00230](#), [RS_Main_00300](#), [RS_Main_00310](#), [RS_Main_00320](#), [RS_Main_00340](#), [RS_Main_00350](#), [RS_Main_00360](#), [RS_Main_00460](#), [RS_Main_00490](#), [RS_Main_00500](#))

3.1.15 Support for System Level Logical Execution Time

[RS_TIMEX_00026]{DRAFT} Support for System Level Logical Execution Time [

Description:	<p>The AUTOSAR templates shall provide the means to support the description of <i>System Level Logical Execution Time</i> (SL-LET). In particular the following shall be described:</p> <ul style="list-style-type: none"> Parameters of a SL-LET <i>interval</i>: Length, type of recurrence and recurrence. The relation between SL-LET intervals, like offset, gap and overlap. Data that is exchanged at the beginning and the end of a SL-LET interval. The (hierarchical) composition of SL-LET intervals. LET intervals that are associated with a SL-LET interval (CP only).
Rationale:	<p>SL-LET can be used to describe a time-deterministic data flow in different design stages respectively on different abstraction levels. SL-LET intervals can be refined/decomposed and may be associated with LET intervals in CP. While SL-LET intervals refer to exchanged data types (e.g. ports of a SW component), LET intervals refer to a group of executable entities.</p>
Use Case:	<p>Design and define timing behavior of applications as well as analysis and validation of timing behavior.</p>
Dependencies:	<p>[RS_TIMEX_00001], [RS_TIMEX_00002], [RS_TIMEX_00003], [RS_TIMEX_00004], [RS_TIMEX_00006]</p>
AppliesTo:	<p>AP, CP</p>
Supporting Material:	<p>[5]</p>

](RS_Main_00010, RS_Main_00011, RS_Main_00050, RS_Main_00130, RS_Main_00150, RS_Main_00200, RS_Main_00410, RS_Main_01001)

3.2 Classic Platform Requirements

3.2.1 Loop-back signal flow in sender-receiver communication

[RS_TIMEX_00009] Loop-back signal flow in sender-receiver communication [

Description:	<p>It shall be possible to annotate connections among SW-Cs on VFB level, to indicate that a sender-receiver communication needs to be buffered.</p>
Rationale:	<p>When software components are connected to work together using sender-receiver communication there is a natural signal flow implied in this composition where one SW-Component produces some data which is then consumed and further processed by another software component. When such a setup also contains loop-back of signals it is no longer possible to determine which signal-flow is to be processed during one pass and which signal flow shall be buffered as the loop-back for the next execution.</p>





Use Case:	<p>A filter algorithm which is implemented using several software components and feeds the result of the algorithm back as an input. When this loop-back signal flow is annotated, the relationships between the other software components can be arranged in a sequence and the execution order of the involved runnable entities can be determined.</p> <p>Analysis and validation of timing behavior in closed loop control systems. See also sections 4.1.2, 4.1.3 and 4.1.4</p>
Dependencies:	[RS_TIMEX_00001], [RS_TIMEX_00003]
AppliesTo:	CP
Supporting Material:	Requirements on BSW & RTE Features

[RS_Main_00030](#), [RS_Main_00080](#), [RS_Main_00180](#), [RS_Main_00200](#), [RS_Main_00230](#), [RS_Main_00300](#), [RS_Main_00310](#), [RS_Main_00320](#), [RS_Main_00340](#), [RS_Main_00350](#), [RS_Main_00360](#), [RS_Main_00460](#), [RS_Main_00490](#), [RS_Main_00500](#)

3.2.2 Specification of timing resources

[RS_TIMEX_00013] Specification of timing resources for software-component description

Description:	The AUTOSAR templates shall provide means to impose execution time constraints on executable entities in order to ensure temporal resource consumption.
Rationale:	<p>One of the main criteria for mapping of SW-C onto ECUs is the resource requirement of the complete SW system assigned to a single ECU. In order to estimate the total amount of resources required for a software system, it is necessary to have the information for each of the assigned SW-Cs. Concerning this use case, the relevant CPU specific resource information is the worst case execution time. Again, please note that the overall use case can not fully be covered within the scope of this document because the final assessment of resource consumption is only feasible in the context of an ECU configuration. On the other hand, the assessment in the scope of the ECU configuration needs preparation by specifying resource claims in the scope of a software-component. This constraint is mainly caused by the fact that the relevant basic software configuration can only be available in the scope of an ECU configuration for the first time in the workflow. It is obvious that the basic software contributes to a more or less large extend to the overall resource consumption.</p>
Use Case:	For integration purposes it is necessary to specify the worst case execution time of an executable entity in order to ensure proper integration with regard to temporal requirements.
Dependencies:	-
AppliesTo:	CP
Supporting Material:	-

]([RS_Main_00030](#), [RS_Main_00080](#), [RS_Main_00180](#), [RS_Main_00200](#), [RS_Main_00230](#), [RS_Main_00300](#), [RS_Main_00310](#), [RS_Main_00320](#), [RS_Main_00340](#), [RS_Main_00350](#), [RS_Main_00360](#), [RS_Main_00460](#), [RS_Main_00490](#), [RS_Main_00500](#))

3.2.3 Runnable Entities

[RS_TIMEX_00014] Sequence of execution of runnable entities [

Description:	The AUTOSAR templates shall provide means to specify constraints on the order of execution of different runnable entities.
Rationale:	In some cases, data dependencies between runnable entities cannot be used to deduce an order of execution among a set of runnable entities. Either such data dependencies are ambiguous and therefore lead not to a specific order of execution, or no data dependencies do not exist among runnable entities and an order of execution need to be enforced.
Use Case:	Analysis and validation of timing behavior. See also sections 4.1.1
Dependencies:	[RS_SWCT_00090]
AppliesTo:	CP
Supporting Material:	-

]([RS_Main_00030](#), [RS_Main_00080](#), [RS_Main_00180](#), [RS_Main_00200](#), [RS_Main_00230](#), [RS_Main_00300](#), [RS_Main_00310](#), [RS_Main_00320](#), [RS_Main_00340](#), [RS_Main_00350](#), [RS_Main_00360](#), [RS_Main_00460](#), [RS_Main_00490](#), [RS_Main_00500](#))

3.2.4 Timing Requirements of SW-Components

[RS_TIMEX_00015] Timing-requirements of SW-Components [

Description:	The SW-Component template must allow specifying the timing-requirements of each runnable entity of a SW-Component (e.g.): <ul style="list-style-type: none"> • Period • Reaction time
Rationale:	The SW-Component template must allow describing: <ul style="list-style-type: none"> • how often it has to be run • the time between a stimulus like e.g. the state change of a hardware or software entity and the expected reaction of the system (e.g. response, actuator activation)
Use Case:	-
Dependencies:	[RS_TIMEX_00013]
AppliesTo:	CP
Supporting Material:	-

](RS_Main_00030, RS_Main_00080, RS_Main_00180, RS_Main_00200, RS_Main_00230, RS_Main_00300, RS_Main_00310, RS_Main_00320, RS_Main_00340, RS_Main_00350, RS_Main_00360, RS_Main_00460, RS_Main_00490, RS_Main_00500)

3.2.5 Predefined events for port interfaces at VFB level

[RS_TIMEX_00018] Predefined events for port interfaces at VFB level [

Description:	The Timing Extensions shall provide timing description event types dedicated to ports, like trigger port.
Rationale:	Due to the introduction of new types of ports, like the trigger port, the Timing Extensions shall provide specific types of timing description events to support such ports.
Use Case:	-
Dependencies:	[RS_TIMEX_00001]
AppliesTo:	CP
Supporting Material:	-

](RS_Main_00030, RS_Main_00080, RS_Main_00180, RS_Main_00200, RS_Main_00230, RS_Main_00300, RS_Main_00310, RS_Main_00320, RS_Main_00340, RS_Main_00350, RS_Main_00360, RS_Main_00460, RS_Main_00490, RS_Main_00500)

3.2.6 Support for events indicating variable accesses

[RS_TIMEX_00020] Support for events indicating variable accesses [

Description:	The Timing Extension shall provide means to reference the point-in-time when executable entities, namely runnable entities, access variables.
Rationale:	In some cases it is necessary to reference the point-in-time when executable entities access variable data and being capable to impose timing constraints on these timing description events. For example, in the VFB timing view an age constraint is imposed on the point-in-time a variable data prototype is received. But there may be several executable entities accessing such variable data, but some of those executable entities may have different age timing constraints. In order to avoid that such runnable entities are mapped to a task with a higher activation frequency than required, it would be good to annotate the specific variable access.
Use Case:	-
Dependencies:	[RS_TIMEX_00001]
AppliesTo:	CP
Supporting Material:	-

](RS_Main_00030, RS_Main_00080, RS_Main_00180, RS_Main_00200, RS_Main_00230, RS_Main_00300, RS_Main_00310, RS_Main_00320, RS_Main_00340, RS_Main_00350, RS_Main_00360, RS_Main_00460, RS_Main_00490, RS_Main_00500)

3.2.7 Support for Logical Execution Time

[RS_TIMEX_00022] Support for Logical Execution Time [

Description:	<p>The AUTOSAR templates shall provide the means to support the description of <i>Logical Execution Time</i> (LET) respectively Time Determinism. In particular the following shall be described:</p> <ul style="list-style-type: none"> • Parameters of a LET <i>interval</i>: Length, type of recurrence and recurrence • The relation between LET intervals, like offset, gap and overlap. • Executable entities and/or groups of executable entities that shall be executed in the context of LET. • Data exchange that shall be conducted in the context of a LET interval, namely the time deterministic exchange of data between executable entities and/or groups of executable entities. • Means to specify an order of execution among a number of executable entities.
Rationale:	<p>Time determinism is a crucial characteristic in embedded distributed real-time systems that ensures:</p> <ul style="list-style-type: none"> • reliable operation of such systems due to deterministic data exchange and execution of executable entities, and • analysis and validation of such systems in order to perform timing analysis early in the development process.
Use Case:	<p>Design and define timing behavior of applications as well as analysis and validation of timing behavior.</p>
Dependencies:	<p>[RS_TIMEX_00001], [RS_TIMEX_00002], [RS_TIMEX_00003], [RS_TIMEX_00004], [RS_TIMEX_00006]</p>
AppliesTo:	<p>CP</p>
Supporting Material:	<p>-</p>

]([RS_Main_00010](#), [RS_Main_00011](#), [RS_Main_00050](#), [RS_Main_00130](#), [RS_Main_00150](#), [RS_Main_00200](#), [RS_Main_00410](#), [RS_Main_01001](#))

3.2.8 Support for Specifying Synchronization

[RS_TIMEX_00023] Support for Specifying Synchronization [

Description:	The AUTOSAR templates shall provide the means to support specification of synchronization among executable entities and/or groups of executable entities.
Rationale:	In some cases it is not sufficient to specify the execution order of executable entities and use synchronization timing constraints to express that executable entities must not be executed before others have completed their execution. The Execution Order Constraint provided by the AUTOSAR Timing Extensions allows to specify an order among executable entities but does <i>not</i> provide means to specify where in this order synchronization means shall be used to guarantee that a number of executable entities complete execution before other executable entities are permitted to start execution. The Synchronization Timing Constraint provided by the AUTOSAR Timing Extensions allows specifying synchronization with regard to temporal characteristics, namely a time interval.
Use Case:	Ensure proper synchronization during execution of executable entities which are executed in different tasks and on different cores.
Dependencies:	[RS_TIMEX_00022]
AppliesTo:	CP
Supporting Material:	-

](RS_Main_00010, RS_Main_00011, RS_Main_00050, RS_Main_00130, RS_Main_00150, RS_Main_00200, RS_Main_00410, RS_Main_01001)

3.2.9 Support for Software Cluster

[RS_TIMEX_00025] Support for Software Cluster [

Description:	The AUTOSAR templates shall provide the means to support specification of timing for software clusters.
Rationale:	The AUTOSAR Flexibility allows for specifying various software clusters. Some software clusters provide temporal and dynamic resources and other software clusters require temporal and dynamic resources. These provisions and needs are described using the capabilities of the timing extensions considering the scope of one or more software clusters.
Use Case:	-
Dependencies:	-
AppliesTo:	CP
Supporting Material:	-

](RS_Main_00010, RS_Main_00011, RS_Main_00030, RS_Main_00050, RS_Main_00150, RS_Main_00200, RS_Main_00300)

3.3 Adaptive Platform Requirements

This section defines requirements specifically imposed on the AUTOSAR Adaptive Platform.

3.3.1 Support for Service Oriented Communication

[RS_TIMEX_00024]{DRAFT} Support for Service Oriented Communication [

Description:	The AUTOSAR templates shall provide the means to support specification of timing for service oriented communication.
Rationale:	The AUTOSAR Adaptive Platform provides the service oriented communication for communications among adaptive applications.
Use Case:	-
Dependencies:	-
AppliesTo:	AP
Supporting Material:	-

](RS_Main_00150)

4 Supported use cases

The timing information in AUTOSAR shall support the following use cases.

The functional use cases depicted within the following sections are derived by practical applications implemented and experienced within several pre-series projects. The use cases are gathered from chassis applications. They are derived from functional implementations of vehicle functions. Therefore, the following descriptions do not depict specific applications but explain common characteristics of chassis functions utilizing timing-relevant problems. These include

- timing constraints mainly driven by closed loop control characteristics
- transmission of data in equidistant time slices, forced by FlexRay bus
- calculation of application data synchronous to bus schedule

4.1 End-to-end timing

One typical use case for the information given by the timing model of AUTOSAR is timing analysis. Timing analysis is a rather general term that can be split up into various sub-activities needed to be done to obtain an overall end-to-end timing analysis. It can be distinguished between the local timing analysis of a single resource (an ECU or bus) and the global timing analysis of several interconnected resources (ECUs and busses). Timing analysis results can be used for validation by comparing analysis results with given timing constraints.

4.1.1 Use case 1: Local Timing Analysis (Scheduling Analysis)

An engineer might want to analyze the local timing behavior of a single resource with no respect to global dependencies. Thus, the local timing analysis addresses isolated scheduling questions regarding either a single bus or an ECU (a processor on that ECU). For example, in an early design phase this can help to get an impression of the resource utilization. Furthermore, local timing analysis can be also used for optimization purposes.

Local timing analysis is a basis for end-to-end analysis. This is addressed in the following sections.

4.1.2 Use case 2: Analysis of end-to-end timing in open loop control systems

Typical open loop control systems contain at least a sensor, a controller, and an actuator component. For analysis of such a control system the end-to-end timing is needed. Analysis of end-to-end timing includes:

- Identification of different event chains and alternative event chain segments.
- Analysis of end-to-end delay
- Scrutinize the impact of different execution orders on timing properties, namely the end-to-end delay.
- Determine the degrees of freedom in the event chain and/or the execution order.
- Select the most reasonable, i.e. most reliable or most effective, event chain.

4.1.3 Use case 3: Analysis of end-to-end timing in closed loop control systems

In comparison to the analysis of end-to-end timing in open loop control systems the closed loop control systems contain one or more feedback loops. The analysis requires the identification and description of these feedback loops and how to deal with them in terms of timing. Furthermore, the impact of the timing properties shall be analyzable.

4.1.4 Use case 4: Validation of end-to-end timing

Based on the results obtained during the analysis of end-to-end timing it shall be possible to validate whether the actual/given timing behaviour of the system satisfies its constraints. Concrete examples include validation of response times, buffer sizes or throughput. In all cases results of the analysis methods or simulation/measurement can be used to determine the system timing behaviour to be validated against the given set of timing constraints.

4.2 Synchronization

Synchronization in timing analysis is concerned with the time correlation of concurrent event chains within a common functional context. Two or more event chains are said to be synchronous, if the occurrences of the corresponding stimulus and/or response events coincide in time with a certain predefined tolerance.

Herefore the following use cases shall be regarded.

4.2.1 Use case 5: Sensor data fusion in multi-sensor systems

A modern automobile typically features several sensors across its on-board network. These sensors can be used by many software functions. Some of them require data from different sensors simultaneously to calculate a more sophisticated correlation of sensor information.

Examples for functions that include sensor data fusion are ACC (adaptive cruise control, requiring radar and wheel data) or PDC (park distance control, requiring several sensors of one type to gain an overall environment model).

Timing analysis of this kind of functions can not only focus on isolated signal paths of each sensor for its own. The more interesting part is the synchronization of these paths involved in the function. Hence, the timing model must be capable of expressing *synchronicity constraints* for several event chains and offer the information needed for their validation.

4.2.2 Use case 6: Actuator synchronization

Additional to the before mentioned use case regarding sensor data fusion, it must be possible to synchronize actuators as well. Modern control systems contain distributed intelligent actuators, whose synchronization is crucial in order to ensure simultaneous operation. One example for an application of this use case is the synchronous door opening function. General speaking, such use cases have the common behavior that the access to the actuators is triggered by the same stimulus event. If the access shall be synchronized, then a specification of such timing constraints must be possible.

A typical example is the synchronization of the hazard warning light. First of all, event chains are specified for each indicator light, modeling the timing flow between the change of the hazard warning light switch and the state change of the indicators (e.g. blinking). The stimulus events of the several event chains are correlated, namely the change of the switch. For the response events (namely the activation of the indicator lights) it must be possible to specify a synchronization constraint in order to restrict the occurrence of the response events, i.e. to force their synchronized activation.

4.2.3 Use case 7: Bus synchronization and Gateway

There are several scenarios for Gateway synchronization. The gateway could be synchronized with one or more FlexRay bus to reduce sending or reading delays of gateway tasks. It should also be possible to synchronize several gateway activities to optimize the transmission time on the subsequent CAN.

4.3 Early prediction

The previous section has depicted general use cases, where an appropriate, timing augmented AUTOSAR meta model is an enabler for End-To-End timing analysis in different domains. In the following section regarding early prediction, we address now use cases where such an analysis framework can be used in order to enable *timing analysis during design phase*. Thus, an early prediction of the timing behavior can be done, resolving potential weak points in the design as soon as possible. The timing

validation is made based on estimates or partly known timing information in system design or specification phases.

4.3.1 Use case 8: Modification impacts due to adding a component

Component integration is a manifolded problem. First of all, the component to be integrated must provide timing data to enable analysis (and simulation, respectively) whether the component would fit into the target system, as well as to determine the impact on the target system. So the target system imposes some timing constraints on the component to be integrated. On the other hand the component to be integrated imposes some timing constraints on the target system in order to operate properly.

The timing uncertainty in this use-case is rather limited compared to use-case hardware dimensioning. Timing properties and most of the constraints are well known in the system already. Also the timing properties (and possible constraints) of the components that should be integrated are known at least in certain parts or can be provided on a rough estimate. Nevertheless, the impact on timing for integration of the additional component could be analyzed and validated. Even if the new component is not yet implemented (so properties are based on completely guessed values) this use-case can avoid expensive software re-design or even hardware modifications (e.g. increased ECU-clock) in early design phases.

The main reason for this use case is the fact that due to a wrong timing behaviour the integration of new software to existing systems can lead to unexpected phenomenons like priority inversion, deadlocks and so on. Therefore, a simple calculation of the established (let's say, *70 percent CPU usage*) and the new (*20 percent*, for example) software and their addition is not an acceptable consideration of timing behavior.

4.3.2 Use case 9: Support for hardware dimensioning

Hardware resources¹ significantly influence the timing behavior of software. On the other hand hardware cost should be limited to the absolute minimum, since they dominate piece costs. Thus, for minimizing costs, it is straightforward to search in the hardware design space² to allow software components to provide timing properties that barely fulfill the timing constraints. The basic questions which are of importance could be the clock-rate of an ECU, the bandwidth of a bus or the access speed for memory modules and so on. A basic requirement is that the influence of hardware configurations for timing properties are known (At least as guessed values). If this holds, timing behavior could be validated for certain hardware settings and the minimal cost solution could be chosen in early design phases.

¹e.g. computational power and bandwidth, but also access times for memory.

²for this use case a fixed system topology is assumed

4.3.3 Use case 10: Topology decisions

The main goal of fixing a specific topology is the optimization of the whole system with respect to predefined quality criteria. These may include maximum latencies, minimum bus load and so on. The mentioned decisions are made on the base of a state the system is in. To determine this state, analyzable information is needed which provides access to the system's characteristics.

With respect to timing, one meaningful optimization criterion is a minimum age of sensor data at its processing. Consider a FlexRay based communication system with a length of the communication cycle of 10ms. If a sensor ECU providing data each 40ms, there may be good reasons to use cycle multiplexing, assigning a certain slot at each 4th communication cycle to the sensor ECU. However, reaching the goal of minimum data age, additional information is needed. Thus, defining the actual FlexRay slot to be assigned to the sensor ECU (and multiplexed with other data or - even - ECUs) needs exact knowledge about the points in time when the sensor data can be written to the buffers of the FR communication controller. This slot should be as close as possible at the time the sensor is available in the HW buffers. This may include estimated jitter values and release offsets referred to a certain reference event (like the *FR cycle start*), for example.

5 Change History

Please note that the lists in this chapter also include requirement items that have been removed from the specification in a later version. These requirement items do not appear as hyperlinks in the document.

5.1 Change History of this document according to AUTOSAR Release 4.1.1

5.1.1 Added Requirements in R4.1.1

Number	Heading
[RS_TIMEX_00013]	Specification of timing resources (formerly RS_SWCT_02050)
[RS_TIMEX_00014]	Sequence of execution of runnable entities (formerly RS_SWCT_03060)
[RS_TIMEX_00015]	Timing requirements for SW-C (formerly RS_SWCT_03080)
[RS_TIMEX_00013]	Specification of timing resources for software-component description
[RS_TIMEX_00014]	Sequence of execution of runnable entities
[RS_TIMEX_00015]	Timing-requirements of SW-Components
[RS_TIMEX_00016]	Some elements of the Timing Extensions shall be blueprintable
[RS_TIMEX_00017]	Synchronization constraint on events
[RS_TIMEX_00018]	Predefined events for port interfaces at VFB level
[RS_TIMEX_00019]	AUTOSAR Methodology support
[RS_TIMEX_00020]	Support for events indicating variable accesses
[RS_TIMEX_00021]	Age constraint on assembly connector

Table 5.1: Added Specification Items in 4.1.1

5.1.2 Changed Requirements in R4.1.1

none

5.1.3 Deleted Requirements in R4.1.1

none

5.2 Change History of this document according to AUTOSAR Release 4.1.2

5.2.1 Added Requirements in R4.1.2

none

5.2.2 Changed Requirements in R4.1.2

none

5.2.3 Deleted Requirements in R4.1.2

Number	Heading
[RS_TIMEX_00021]	Age constraint on assembly connector. NOTE. Duplicate of [RS_TIMEX_00009]

Table 5.2: Removed Specification Items in 4.1.2

5.3 Change History of this document according to AUTOSAR Release 4.1.3

5.3.1 Added Requirements in R4.1.3

none

5.3.2 Changed Requirements in R4.1.3

none

5.3.3 Deleted Requirements in R4.1.3

none

5.4 Change History of this document according to AUTOSAR Release 4.2.1

5.4.1 Added Requirements in R4.2.1

none

5.4.2 Changed Requirements in R4.2.1

none

5.4.3 Deleted Requirements in R4.2.1

none

5.5 Change History of this document according to AUTOSAR Release 4.2.2

5.5.1 Added Requirements in R4.2.2

none

5.5.2 Changed Requirements in R4.2.2

none

5.5.3 Deleted Requirements in R4.2.2

none

5.6 Change History of this document according to AUTOSAR Release 4.3.0

5.6.1 Added Requirements in R4.3.0

none

5.6.2 Changed Requirements in R4.3.0

none

5.6.3 Deleted Requirements in R4.3.0

none

5.7 Change History of this document according to AUTOSAR Release 4.3.1

5.7.1 Added Requirements in R4.3.1

none

5.7.2 Changed Requirements in R4.3.1

none

5.7.3 Deleted Requirements in R4.3.1

none

5.8 Change History of this document according to AUTOSAR Release 4.4.0

5.8.1 Added Requirements in R4.4.0

Number	Heading
[RS_TIMEX_00022]	Support for Logical Execution Time
[RS_TIMEX_00023]	Support for Specifying Synchronization

Table 5.3: Added Specification Items in 4.4.0

5.8.2 Changed Requirements in R4.4.0

none

5.8.3 Deleted Requirements in R4.4.0

none

5.9 Change History of this document according to AUTOSAR Release R19-11

5.9.1 Added Requirements in R19-11

none

5.9.2 Changed Requirements in R19-11

none

5.9.3 Deleted Requirements in R19-11

none

5.10 Change History of this document according to AUTOSAR Release R20-11

5.10.1 Added Requirements in R20-11

Number	Heading
[RS_TIMEX_00024]	Support for Service Oriented Communication
[RS_TIMEX_00025]	Support for Software Cluster

Table 5.4: Added Specification Items in 20-11

5.10.2 Changed Requirements in R20-11

none

5.10.3 Deleted Requirements in R20-11

none

5.11 Change History of this document according to AUTOSAR Release R21-11

5.11.1 Added Requirements in R21-11

none

5.11.2 Changed Requirements in R21-11

none

5.11.3 Deleted Requirements in R21-11

none

5.12 Change History of this document according to AUTOSAR Release R22-11

5.12.1 Added Requirements in R22-11

Number	Heading
[RS_TIMEX_00026]	Support for System Level Logical Execution Time

Table 5.5: Added Requirements in R22-11

5.12.2 Changed Requirements in R22-11

none

5.12.3 Deleted Requirements in R22-11

none

5.13 Change History of this document according to AUTOSAR Release R23-11

5.13.1 Added Requirements in R23-11

none

5.13.2 Changed Requirements in R23-11

none

5.13.3 Deleted Requirements in R23-11

none