

Document Title	Requirements on System Template
Document Owner	AUTOSAR
Document Responsibility	AUTOSAR
Document Identification No	213

Document Status	published
Part of AUTOSAR Standard	Classic Platform
Part of Standard Release	R24-11

Document Change History			
Date	Release	Changed by	Description
2024-11-27	R24-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Added Firewall requirement</li> <li>Replaced several requirements by a general variant handling requirement. For details please refer to the ChangeDocumentation.</li> </ul>
2023-11-23	R23-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Added IEEE1722Tp Stream support requirement</li> <li>Added Ethernet Switch Filtering and Policing requirement</li> </ul> <p>For details please refer to the ChangeDocumentation</p>
2022-11-24	R22-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Updated [RS_SYST_00042]</li> </ul>
2021-11-25	R21-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>No content changes</li> </ul>
2020-11-30	R20-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Added Software Cluster requirements;For details please refer to the ChangeDocumentation</li> </ul>
2019-11-28	R19-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Added requirement for Signal-To-Service Translation</li> <li>Changed Document Status from Final to published</li> </ul>





2018-10-31	4.4.0	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>minor corrections / clarifications / editorial changes; For details please refer to the ChangeDocumentation</li> </ul>
2017-12-08	4.3.1	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>editorial changes;</li> </ul>
2016-11-30	4.3.0	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>minor corrections / clarifications / editorial changes; For details please refer to the ChangeDocumentation</li> </ul>
2015-07-31	4.2.2	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>minor corrections / clarifications / editorial changes; For details please refer to the ChangeDocumentation</li> </ul>
2014-10-31	4.2.1	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Added requirements <a href="#">[RS_SYST_00049]</a>, <a href="#">[RS_SYST_00050]</a>, <a href="#">[RS_SYST_00051]</a>, <a href="#">[RS_SYST_00052]</a>, <a href="#">[RS_SYST_00053]</a>, <a href="#">[RS_SYST_00054]</a>, <a href="#">[RS_SYST_00055]</a>, <a href="#">[RS_SYST_00056]</a></li> </ul>
2013-10-31	4.1.2	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Layout update.</li> </ul>
2013-03-15	4.1.1	AUTOSAR Administration	<ul style="list-style-type: none"> <li>Added requirements <a href="#">[RS_SYST_00043]</a>, <a href="#">[RS_SYST_00044]</a>, <a href="#">[RS_SYST_00045]</a>, <a href="#">[RS_SYST_00046]</a>, <a href="#">[RS_SYST_00047]</a>, <a href="#">[RS_SYST_00048]</a></li> </ul>
2011-12-22	4.0.3	AUTOSAR Administration	<ul style="list-style-type: none"> <li>Added requirement <a href="#">[RS_SYST_00042]</a></li> </ul>
2009-12-18	4.0.1	AUTOSAR Administration	<ul style="list-style-type: none"> <li>Added requirements <a href="#">[RS_SYST_00027]</a>, <a href="#">[RS_SYST_00028]</a>, <a href="#">[RS_SYST_00029]</a>, <a href="#">[RS_SYST_00030]</a>, <a href="#">[RS_SYST_00031]</a>, <a href="#">[RS_SYST_00037]</a>, <a href="#">[RS_SYST_00038]</a>, <a href="#">[RS_SYST_00039]</a>, <a href="#">[RS_SYST_00041]</a></li> <li>Refined requirement SYSCT0004 with SYSCT32, SYSCT33, SYSCT34, SYSCT35, SYSCT36</li> <li>Refined requirement SYSCT0005 with <a href="#">[RS_SYST_00037]</a> and <a href="#">[RS_SYST_00040]</a></li> <li>Refined requirement <a href="#">[RS_SYST_00007]</a>, <a href="#">[RS_SYST_00001]</a>, <a href="#">[RS_SYST_00035]</a></li> <li>Legal disclaimer revised</li> </ul>



△

2008-08-13	3.1.1	AUTOSAR Administration	<ul style="list-style-type: none"><li>• Legal disclaimer revised</li></ul>
2007-12-21	3.0.1	AUTOSAR Administration	<ul style="list-style-type: none"><li>• Added requirements [RS_SYST_00025] and [RS_SYST_00026]</li><li>• Set requirement [RS_SYST_00023] to "postponed"</li><li>• Document meta information extended</li><li>• Small layout adaptations made</li></ul>
2006-11-28	2.1	AUTOSAR Administration	<p>Release as a separate Document. The Specification of System Template V1.0.0 has been split into independent documents for Release 2.1</p> <ul style="list-style-type: none"><li>• Legal disclaimer revised</li><li>• Release Notes added</li><li>• "Advice for users" revised</li><li>• "Revision Information" added</li></ul>
2005-05-31	1.0	AUTOSAR Administration	<ul style="list-style-type: none"><li>• Initial release as part of the Specification of System Template V1.0.0</li></ul>

## **Disclaimer**

This work (specification and/or software implementation) and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the work.

The material contained in this work is protected by copyright and other types of intellectual property rights. The commercial exploitation of the material contained in this work requires a license to such intellectual property rights.

This work may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the work may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The work has been developed for automotive applications only. It has neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

## Contents

1	Scope of this document	9
1.1	Document Conventions	9
1.2	Requirements Tracing	10
2	Requirements	12
2.1	Category: Main Requirements	12
2.1.1	Compatibility between the AUTOSAR Templates	12
2.2	Category: System Template Requirements	12
2.2.1	Legacy systems	12
2.2.2	Basic Software and RTE Resources	13
2.2.3	Iterative Development	13
2.2.4	Mapping of Software Components to ECUs	14
2.2.5	Mapping of Software Components to ECUs: Clustering	14
2.2.6	Mapping of Software Components to ECUs: Separation	15
2.2.7	Topology Description	16
2.2.8	Data Segmentation	16
2.2.9	Dedicated physical connections	17
2.2.10	Mapping of signals to the same physical line	17
2.2.11	Mapping of signals to different physical lines	18
2.2.12	Mapping of signals to a specific physical line	18
2.2.13	Exclusion of signals from a specific physical line	19
2.2.14	ECU Communication via CAN	19
2.2.15	ECU Communication via LIN	20
2.2.16	ECU Communication via FlexRay	20
2.2.17	Derivation of COM Stack Configuration Parameters from the System Template	21
2.2.18	ECU Extract generation rules	21
2.2.19	IPdu End-to-End Communication Protection support	22
2.2.20	Dynamic length signals	22
2.2.21	Dynamic length IPdus	23
2.2.22	Distribution of Application and Vehicle Mode Requests	23
2.2.23	Timing properties	24
2.2.24	Support of SAE J1939 Protocol Features	24
2.2.25	ECU Communication via Ethernet	25
2.2.26	Support for Partial Networking	26
2.2.27	Communication via Complex Drivers	26
2.2.28	Description of custom bus systems	27
2.2.29	Co-existing System artifacts in the same model	27
2.2.30	Network and physical representation on signal level	28
2.2.31	CAN with Flexible Data-Rate	28
2.2.32	Support of Efficient COM for large data configuration	29
2.2.33	Data transformation of inter-ECU communication	29
2.2.34	Support of COM Based Data Transformation	30

2.2.35	Translation between signal-based and service-oriented communication	30
2.2.36	Naming conventions	31
2.2.37	Support of Secured Pdus	31
2.2.38	Support of Container Pdus	32
2.2.39	E2E-protected communication	32
2.2.40	Assigning communication graphs to particular RTE Implementation Plug-Ins	33
2.2.41	Optional Elements	33
2.2.42	Software Cluster	34
2.2.43	Interaction of a Software Cluster with the environment	34
2.2.44	Software Cluster Resource	35
2.2.45	Ethernet IEEE1722Tp Stream support	35
2.2.46	Ethernet Switch Filtering and Policing	36
2.2.47	Firewall configuration	36
2.2.48	Support of Variant Handling	37
3	Change History	38
3.1	Change History for AUTOSAR 4.0.1 against 3.1.5	38
3.1.1	Removed SRS Items	38
3.1.2	Changed SRS Items	38
3.1.3	Added SRS Items	38
3.2	Change History for AUTOSAR 4.0.2 against 4.0.1	39
3.2.1	Removed SRS Items	39
3.2.2	Changed SRS Items	39
3.2.3	Added SRS Items	39
3.3	Change History for AUTOSAR 4.0.3 against 4.0.2	39
3.3.1	Removed SRS Items	39
3.3.2	Changed SRS Items	39
3.3.3	Added SRS Items	39
3.4	Change History for AUTOSAR 4.1.1 against 4.0.3	39
3.4.1	Removed SRS Items	39
3.4.2	Changed SRS Items	40
3.4.3	Added SRS Items	40
3.5	Change History for AUTOSAR 4.1.1 against 4.1.2	40
3.5.1	Removed SRS Items	40
3.5.2	Changed SRS Items	40
3.5.3	Added SRS Items	40
3.6	Change History for AUTOSAR 4.1.2 against 4.2.1	40
3.6.1	Removed SRS Items	40
3.6.2	Changed SRS Items	40
3.6.3	Added SRS Items	41
3.7	Change History for AUTOSAR 4.2.1 against 4.2.2	41
3.7.1	Removed SRS Items	41
3.7.2	Changed SRS Items	41
3.7.3	Added SRS Items	41

3.8	Change History for AUTOSAR 4.2.2 against 4.3.0 . . . . .	41
3.8.1	Added Requirements in 4.3.0 . . . . .	41
3.8.2	Changed Requirements in 4.3.0 . . . . .	41
3.8.3	Deleted Requirements in 4.3.0 . . . . .	42
3.9	Change History for AUTOSAR 4.3.0 against 4.3.1 . . . . .	42
3.9.1	Added Requirements in 4.3.1 . . . . .	42
3.9.2	Changed Requirements in 4.3.1 . . . . .	42
3.9.3	Deleted Requirements in 4.3.1 . . . . .	42
3.10	Change History for AUTOSAR 4.3.1 against 4.4.0 . . . . .	42
3.10.1	Added Requirements in 4.4.0 . . . . .	42
3.10.2	Changed Requirements in 4.4.0 . . . . .	42
3.10.3	Deleted Requirements in 4.4.0 . . . . .	43
3.11	Change History for AUTOSAR 4.4.0 against 19-11 . . . . .	43
3.11.1	Added Requirements in 19-11 . . . . .	43
3.11.2	Changed Requirements in 19-11 . . . . .	43
3.11.3	Deleted Requirements in 19-11 . . . . .	43
3.12	Change History for AUTOSAR R19-11 against R20-11 . . . . .	43
3.12.1	Added Requirements in R20-11 . . . . .	43
3.12.2	Changed Requirements in R20-11 . . . . .	43
3.12.3	Deleted Requirements in R20-11 . . . . .	44
3.13	Change History for AUTOSAR R20-11 against R21-11 . . . . .	44
3.13.1	Added Requirements in R21-11 . . . . .	44
3.13.2	Changed Requirements in R21-11 . . . . .	44
3.13.3	Deleted Requirements in R21-11 . . . . .	44
3.14	Change History for AUTOSAR R21-11 against R22-11 . . . . .	44
3.14.1	Added Requirements in R22-11 . . . . .	44
3.14.2	Changed Requirements in R22-11 . . . . .	44
3.14.3	Deleted Requirements in R22-11 . . . . .	44
3.15	Change History for AUTOSAR R22-11 against R23-11 . . . . .	45
3.15.1	Added Requirements in R23-11 . . . . .	45
3.15.2	Changed Requirements in R23-11 . . . . .	45
3.15.3	Deleted Requirements in R23-11 . . . . .	45
3.16	Change History for AUTOSAR R23-11 against R24-11 . . . . .	45
3.16.1	Added Requirements in R24-11 . . . . .	45
3.16.2	Changed Requirements in R24-11 . . . . .	45
3.16.3	Deleted Requirements in R24-11 . . . . .	46

## References

- [1] System Template  
AUTOSAR\_CP\_TPS\_SystemTemplate
- [2] Standardization Template  
AUTOSAR\_FO\_TPS\_StandardizationTemplate
- [3] Main Requirements  
AUTOSAR\_FO\_RS\_Main
- [4] IEEE Standard 1722-2016 - IEEE Standard for a Transport Protocol for Time-Sensitive Applications in Bridged Local Area Networks

# 1 Scope of this document

This document collects the requirements on the System Template (SYS-T). The main goal of the System Template is the definition of a relationship between the pure Software View on the System and a Physical System Architecture with networked ECUs.

The System Template covers the following areas:

- System topology: In the system topology the logical layout of the system is described. This means it is documented which ECU is connected to which cluster or channel.
- Communication properties: The central purpose of a communication system is the exchange of frames with certain properties.
- Mapping: The mapping covers the distribution of software components to ECUs as well as the mapping of data elements that are to be exchanged between software components onto signals and frames.

The requirements collected in this document will be satisfied by the System Template specification [1]. This document implements most of the requirements stated here.

## 1.1 Document Conventions

The representation of requirements in AUTOSAR documents follows the table specified in [TPS\_STDT\_00078], see Standardization Template, chapter Support for Traceability ([2]).

The verbal forms for the expression of obligation specified in [TPS\_STDT\_00053] shall be used to indicate requirements, see Standardization Template, chapter Support for Traceability ([2]).

## 1.2 Requirements Tracing

The following table references the requirements specified in [3] and links to the fulfillment of these.

Requirement	Description	Satisfied by
[RS_Main_00010]	Safety Mechanisms	[RS_SYST_00028] [RS_SYST_00056]
[RS_Main_00026]	AUTOSAR shall support high speed and high bandwidth communication between executed SW	[RS_SYST_00048] [RS_SYST_00049] [RS_SYST_00050] [RS_SYST_00055]
[RS_Main_00030]	Safety Related Process Support	[RS_SYST_00003] [RS_SYST_00008] [RS_SYST_00009] [RS_SYST_00016] [RS_SYST_00017] [RS_SYST_00018] [RS_SYST_00019] [RS_SYST_00020]
[RS_Main_00060]	Standardized Application Communication Interface	[RS_SYST_00031] [RS_SYST_00057]
[RS_Main_00100]	AUTOSAR shall provide standardized Basic Software	[RS_SYST_00002] [RS_SYST_00025]
[RS_Main_00150]	AUTOSAR shall support the deployment and reallocation of AUTOSAR Application Software	[RS_SYST_00002] [RS_SYST_00007] [RS_SYST_00008] [RS_SYST_00009] [RS_SYST_00016] [RS_SYST_00017] [RS_SYST_00018] [RS_SYST_00019] [RS_SYST_00020]
[RS_Main_00170]	AUTOSAR shall provide secure access to ECU data and services	[RS_SYST_00065]
[RS_Main_00180]	Intellectual Property Protection	[RS_SYST_00027]
[RS_Main_00190]	Non-AUTOSAR Software Integration	[RS_SYST_00001]
[RS_Main_00230]	Network Technology Support	[RS_SYST_00013] [RS_SYST_00014] [RS_SYST_00044] [RS_SYST_00052]
[RS_Main_00280]	Standardized Automotive Communication Protocols	[RS_SYST_00058]
[RS_Main_00300]	AUTOSAR shall provide data exchange formats to support work-share in large inter and intra company development groups	[RS_SYST_00006] [RS_SYST_00027]
[RS_Main_00320]	AUTOSAR shall provide formats to specify system development	[RS_SYST_00007] [RS_SYST_00013] [RS_SYST_00045] [RS_SYST_00047]
[RS_Main_00340]	AUTOSAR shall support the continuous timing requirement analysis	[RS_SYST_00037]
[RS_Main_00360]	Variant Management Support	[RS_SYST_00066]
[RS_Main_00400]	AUTOSAR shall provide a layered software architecture	[RS_SYST_00043]
[RS_Main_00430]	AUTOSAR shall support established automotive communication standards	[RS_SYST_00021] [RS_SYST_00022] [RS_SYST_00024] [RS_SYST_00025] [RS_SYST_00029] [RS_SYST_00030] [RS_SYST_00038] [RS_SYST_00039] [RS_SYST_00052]
[RS_Main_00460]	AUTOSAR shall standardize methods to organize mode management on Application, ECU and System level	[RS_SYST_00042]
[RS_Main_00500]	AUTOSAR shall provide naming conventions	[RS_SYST_00053]
[RS_Main_00510]	Secure Onboard Communication	[RS_SYST_00054]
[RS_Main_01002]	AUTOSAR shall support service-oriented communication	[RS_SYST_00059]





Requirement	Description	Satisfied by
[RS_Main_01003]	AUTOSAR shall support data-oriented communication	[RS_SYST_00051] [RS_SYST_00059]
[RS_Main_01008]	AUTOSAR shall provide secure communication with off-board entities	[RS_SYST_00065]

**Table 1.1: Requirements Tracing**

## 2 Requirements

### 2.1 Category: Main Requirements

#### 2.1.1 Compatibility between the AUTOSAR Templates

##### [RS\_SYST\_00006] Compatibility between the AUTOSAR Templates

*Upstream requirements:* [RS\\_Main\\_00300](#)

〔

<b>Description:</b>	The compatibility between the AUTOSAR Templates must be guaranteed. In this context, compatibility means that each AUTOSAR template can have references to elements of another AUTOSAR template.
<b>Rationale:</b>	Ensuring coherence and interoperability between AUTOSAR templates.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Development of an in-vehicle electronic architecture (software modelling, hardware modelling and mapping constraint modelling) using the same tool chain.
<b>Supporting Material:</b>	—

〕

### 2.2 Category: System Template Requirements

#### 2.2.1 Legacy systems

##### [RS\_SYST\_00001] Mixed Systems (AUTOSAR/NON-AUTOSAR)

*Upstream requirements:* [RS\\_Main\\_00190](#)

〔

<b>Description:</b>	System constraints, which arise through usage of mixed systems, must be treated by System Template.
<b>Rationale:</b>	The transition between non-AUTOSAR systems to full-AUTOSAR systems can only be achieved gradually. Furthermore, interoperability with legacy solutions must be ensured. Thus, it must be possible to have AUTOSAR and non-AUTOSAR ECUs together on the same system ("mixed" systems).
<b>Dependencies:</b>	None identified.

▽



<b>Use Case:</b>	Gradual AUTOSAR introduction into an existing architecture e.g. it shall be possible to handle signals not originating from AUTOSAR software components.
<b>Supporting Material:</b>	–



## 2.2.2 Basic Software and RTE Resources

### [RS\_SYST\_00002] Basic Software Resources and RTE Resources

*Upstream requirements:* [RS\\_Main\\_00150](#), [RS\\_Main\\_00100](#)



<b>Description:</b>	The System Template has to cover resource requests of the basic SW and the RTE.
<b>Rationale:</b>	Resources of an ECU are, by their own definition, limited (RAM, ROM, CPU time, etc.). Such limitations act as constraints during the mapping process.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Taking into account memory limitations when allocating AUTOSAR services and features on a small ECU.
<b>Supporting Material:</b>	–



## 2.2.3 Iterative Development

### [RS\_SYST\_00003] Iterative Development

*Upstream requirements:* [RS\\_Main\\_00030](#)



<b>Description:</b>	The System Template has to support an iterative system development.
<b>Rationale:</b>	During the development of an AUTOSAR system, solutions found in former steps of the system design process are themselves system constraints for the next system generation steps.
<b>Dependencies:</b>	None identified.





<b>Use Case:</b>	If new functionalities are added to a vehicle project in a late development phase, the current mapping become itself a constraint for the mapping of the new SW components associated with such new functionalities.
<b>Supporting Material:</b>	–



## 2.2.4 Mapping of Software Components to ECUs

### [RS\_SYST\_00007] Mapping of Software Components to ECUs

*Upstream requirements:* [RS\\_Main\\_00320](#), [RS\\_Main\\_00150](#)



<b>Description:</b>	The System Template has to describe the mapping of software components to ECUs. An optional mapping of software components to individual processing units residing in one ECU shall also be possible.
<b>Rationale:</b>	–
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	For safety reasons (or simply due to the experience) some specific Software Components can run only on some specific ECUs. Such "pre-mapping" is a constraint for the real mapping process.
<b>Supporting Material:</b>	–



## 2.2.5 Mapping of Software Components to ECUs: Clustering

### [RS\_SYST\_00008] SWC Cluster

*Upstream requirements:* [RS\\_Main\\_00030](#), [RS\\_Main\\_00150](#)



<b>Description:</b>	The System Constraint Description has to cover the clustering of SW Components. SW Component Clustering means that two SW Components cannot be divided and must be mapped to the same ECU.
---------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



△

<b>Rationale:</b>	Due to performance requirements, to safe communication requirements or simply to experience, some communication paths must be prevented to be mapped onto an external bus. Involved SW Components shall then be mapped together onto the same ECU.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Safe communication, which may not be carried out over a communication bus, or very strict timing requirements.
<b>Supporting Material:</b>	–

]

## 2.2.6 Mapping of Software Components to ECUs: Separation

### [RS\_SYST\_00009] SWC Separation

*Upstream requirements: [RS\\_Main\\_00030](#), [RS\\_Main\\_00150](#)*

[

<b>Description:</b>	The System Constraint Description has to cover the separation of SW Components. SW Component Separation means that two SW Components cannot be on the same ECU.
<b>Rationale:</b>	To enhance the independence of redundant SWC.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Two redundant Software Components, implementing safety critical functions, will not be mapped together on the same ECU because of safety requirements (of course, redundancy does not always imply SWC separation).
<b>Supporting Material:</b>	–

]

## 2.2.7 Topology Description

### [RS\_SYST\_00013] Topology

*Upstream requirements:* [RS\\_Main\\_00320](#), [RS\\_Main\\_00230](#)

[

<b>Description:</b>	The System Template has to describe the topology of an EE System.
<b>Rationale:</b>	The available communication paths limit the possible distributions of SW Components to some ECUs.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Mapping of SW Components being tightly linked from a functional point of view: the topology must then be known in order to avoid too long data paths.
<b>Supporting Material:</b>	–

]

## 2.2.8 Data Segmentation

### [RS\_SYST\_00014] Data Segmentation

*Upstream requirements:* [RS\\_Main\\_00230](#)

[

<b>Description:</b>	The System Template must provide information, which can be used for the segmenting of (application) data to more than 1 frame.
<b>Rationale:</b>	Data length limitations of the underlying bus technology.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Transmission of diagnostic data, often longer than bus specific maximum frame size.
<b>Supporting Material:</b>	–

]

## 2.2.9 Dedicated physical connections

### [RS\_SYST\_00016] Dedicated physical connections

*Upstream requirements:* [RS\\_Main\\_00150](#), [RS\\_Main\\_00030](#)

〔

<b>Description:</b>	The System Constraint Description shall be able to describe that a signal has to be sent over a dedicated wire, which is only used by two SW-Components (sender and receiver).
<b>Rationale:</b>	This technique is commonly used in current safety concepts.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Communication with the airbag module.
<b>Supporting Material:</b>	—

〕

## 2.2.10 Mapping of signals to the same physical line

### [RS\_SYST\_00017] Mapping of signals to the same physical line

*Upstream requirements:* [RS\\_Main\\_00150](#), [RS\\_Main\\_00030](#)

〔

<b>Description:</b>	The System Constraint Description shall be able to describe that a group of signals has to be sent via the same physical line.
<b>Rationale:</b>	—
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	—
<b>Supporting Material:</b>	—

〕

## 2.2.11 Mapping of signals to different physical lines

### [RS\_SYST\_00018] Mapping of signals to different physical lines

*Upstream requirements:* [RS\\_Main\\_00150](#), [RS\\_Main\\_00030](#)

〔

<b>Description:</b>	The System Constraint Description shall be able to describe, if needed, that signals between ECUs are sent via different physical lines.
<b>Rationale:</b>	To support hardware and information redundancy (as a mean to support fault detection and fault handling).
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	A mean to guarantee the transmission of very safety critical data, is to force the sending of redundant copies onto different physical lines.
<b>Supporting Material:</b>	–

〕

## 2.2.12 Mapping of signals to a specific physical line

### [RS\_SYST\_00019] Mapping of signals to a specific physical line

*Upstream requirements:* [RS\\_Main\\_00150](#), [RS\\_Main\\_00030](#)

〔

<b>Description:</b>	The System Constraint Description shall be able to describe that signals have to be mapped to a specific physical line.
<b>Rationale:</b>	Some signals have to be mapped to specific physical lines due to e.g. special performance and/or safety needs.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Powertrain signals have to be mapped to a high-speed bus, due to their timing requirements.
<b>Supporting Material:</b>	–

〕

### 2.2.13 Exclusion of signals from a specific physical line

#### [RS\_SYST\_00020] Exclusion of signals from a specific physical line

*Upstream requirements:* [RS\\_Main\\_00150](#), [RS\\_Main\\_00030](#)

〔

<b>Description:</b>	The System Constraint Description shall be able to describe that signals have not to be mapped to a specific physical line.
<b>Rationale:</b>	Some physical lines can result unsuitable (too slow, unsafe communication protocol, etc.) for the transmission of some specific signals.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Most of power train signals cannot be mapped to a low speed CAN bus, due to their timing requirements.
<b>Supporting Material:</b>	–

〕

### 2.2.14 ECU Communication via CAN

#### [RS\_SYST\_00021] ECU Communication via CAN

*Upstream requirements:* [RS\\_Main\\_00430](#)

〔

<b>Description:</b>	The System Template has to cover the system communication via CAN Bus.
<b>Rationale:</b>	CAN is widely used in the automotive systems.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Development of a complete, multi-networked, in-vehicle electronic architecture.
<b>Supporting Material:</b>	–

〕

## 2.2.15 ECU Communication via LIN

### [RS\_SYST\_00022] ECU Communication via LIN

*Upstream requirements:* [RS\\_Main\\_00430](#)

〔

<b>Description:</b>	The System Template has to cover the system communication via LIN.
<b>Rationale:</b>	LIN is widely used in the automotive systems.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Development of a complete, multi-networked, in-vehicle electronic architecture.
<b>Supporting Material:</b>	–

〕

## 2.2.16 ECU Communication via FlexRay

### [RS\_SYST\_00024] ECU Communication via FlexRay

*Upstream requirements:* [RS\\_Main\\_00430](#)

〔

<b>Description:</b>	The System Template has to cover the system communication via FlexRay.
<b>Rationale:</b>	FlexRay is going to become a standard communication protocol in the automotive industry.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Development of a complete, multi-networked, in-vehicle electronic architecture.
<b>Supporting Material:</b>	–

〕

## 2.2.17 Derivation of COM Stack Configuration Parameters from the System Template

### [RS\_SYST\_00025] Derivation of COM Stack Configuration Parameters from the System Template

*Upstream requirements:* [RS\\_Main\\_00430](#), [RS\\_Main\\_00100](#)

「

<b>Description:</b>	The System Template shall enable the configuration of the Com Stack of the ECU. It handles those parameters that are necessary to describe the inter-ECU communication. Configuration parameters local to an ECU are not in the scope of the System Template.
<b>Rationale:</b>	All ECUs connected in one communication cluster needs to be configured consistently.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Generate Base ECU Configuration from ECU Extract
<b>Supporting Material:</b>	–

」

## 2.2.18 ECU Extract generation rules

### [RS\_SYST\_00027] ECU Extract generation rules

*Upstream requirements:* [RS\\_Main\\_00180](#), [RS\\_Main\\_00300](#)

「

<b>Description:</b>	The ECU Extract is derived from a System Description. The specification for generating the ECU Extract shall be detailed enough to enable semantically unambiguous generation of this artifact.
<b>Rationale:</b>	Tool interoperability requires unambiguous description of the ECU Extract.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Generate Base ECU Configuration from ECU Extract
<b>Supporting Material:</b>	–

」

## 2.2.19 IPdu End-to-End Communication Protection support

### [RS\_SYST\_00028] IPdu End-to-End Communication Protection support

*Upstream requirements:* [RS\\_Main\\_00010](#)

〔

<b>Description:</b>	The System Template shall enable to select E2E protection settings for IPdus.
<b>Rationale:</b>	Protect communication between COM modules.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Transmission of safety-related data on a single channel without redundancy.
<b>Supporting Material:</b>	–

〕

## 2.2.20 Dynamic length signals

### [RS\_SYST\_00029] Dynamic length signals

*Upstream requirements:* [RS\\_Main\\_00430](#)

〔

<b>Description:</b>	The System Template shall support a definition of dynamic length signals.
<b>Rationale:</b>	A Signal shall have either a static length or its length should vary up to some statically defined maximum. Signals with a maximum length are called dynamic length signals.
<b>Dependencies:</b>	Dynamic length signals can change size during run time.
<b>Use Case:</b>	None identified.
<b>Supporting Material:</b>	OSEK COM

〕

## 2.2.21 Dynamic length IPdus

### [RS\_SYST\_00030] Dynamic length IPdus

*Upstream requirements:* [RS\\_Main\\_00430](#)

〔

<b>Description:</b>	The System Template shall support a definition of IPdus that contain dynamic length signals.
<b>Rationale:</b>	Dynamic length IPdus can change size during run time.
<b>Dependencies:</b>	<a href="#">[RS_SYST_00029]</a>
<b>Use Case:</b>	The Network Layer and the Data Link Layer are capable of transmitting and receiving both fixed and dynamic-length I-Pdus as determined by the Interaction Layer.
<b>Supporting Material:</b>	OSEK COM

〕

## 2.2.22 Distribution of Application and Vehicle Mode Requests

### [RS\_SYST\_00031] Distribution of Application and Vehicle Mode Requests

*Upstream requirements:* [RS\\_Main\\_00060](#)

〔

<b>Description:</b>	The System Template shall support the distribution of application and vehicle mode requests to all affected ECUs.
<b>Rationale:</b>	A Mode Requester is an entity that requests modes from a Mode Manager by sending some data via a port with a Mode Request interface. The Mode Manager receives the incoming information, arbitrates the requests and decides upon a resulting mode.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Depending on Vehicle and Application Modes, the BSW modes may change, e.g. the communication needs of an Application may cause a change in the BSW Mode of a communication network.
<b>Supporting Material:</b>	–

〕

## 2.2.23 Timing properties

### [RS\_SYST\_00037] Timing properties

*Upstream requirements:* [RS\\_Main\\_00340](#)

〔

<b>Description:</b>	The System Template shall provide the means to describe the timing properties of a system's dynamics, which are determined by the consumption of computation, communication, and other hardware resources.
<b>Rationale:</b>	The description of timing properties in the System Template is an essential prerequisite for the analysis and validation of a system's timing behavior or its prediction early in the process.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Analysis and validation of timing behavior, early prediction of modification impacts, support for hardware dimensioning, system configuration optimization
<b>Supporting Material:</b>	–

〕

## 2.2.24 Support of SAE J1939 Protocol Features

### [RS\_SYST\_00038] Support of SAE J1939 Protocol Features

*Upstream requirements:* [RS\\_Main\\_00430](#)

〔

<b>Description:</b>	The System Template has to cover the system communication via SAE J1939.
<b>Rationale:</b>	SAE J1939 protocol is an industry standard that is used in automotive systems.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Development of a complete, multi-networked, in-vehicle electronic architecture.
<b>Supporting Material:</b>	–

〕

## 2.2.25 ECU Communication via Ethernet

### [RS\_SYST\_00039] ECU Communication via Ethernet

*Upstream requirements:* [RS\\_Main\\_00430](#)

]

<b>Description:</b>	The System Template has to cover the system communication via Ethernet.
<b>Rationale:</b>	Ethernet is going to become a standard communication protocol in the automotive industry.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Development of a complete, multi-networked, in-vehicle electronic architecture.
<b>Supporting Material:</b>	–

]

### [RS\_SYST\_00052] Ethernet Switch Configuration

*Upstream requirements:* [RS\\_Main\\_00430](#), [RS\\_Main\\_00230](#)

]

<b>Description:</b>	Ethernet Switch Configuration shall provide standardized artifacts to describe the structure of egress ports, port scheduling mechanisms as well as the forwarding process within the switch. Common parameters which can be written to a switch, e.g. during the initialization phase, need to be integrated in the system description.
<b>Rationale:</b>	The timing behavior of messages within the switch depends on the configuration of switches. Therefore, the switch behavior needs to be described.
<b>Dependencies:</b>	–
<b>Use Case:</b>	Provide the description of an Ethernet topology including the model for switches and their behavior.
<b>Supporting Material:</b>	–

]

## 2.2.26 Support for Partial Networking

### [RS\_SYST\_00042] Support for Partial Networking

*Upstream requirements:* [RS\\_Main\\_00460](#)

〔

<b>Description:</b>	System Template shall support the definition of partial network clusters, the mapping of virtual function clusters to partial network clusters and the wakeup information of individual ECUs.  The System Template shall define constraints regarding the design of Partial Network topologies. Supported and unsupported Partial Network topologies shall be clearly defined to ensure a proper PNC handling.
<b>Rationale:</b>	System Template shall contain all system relevant parameters required for the configuration of a partial network.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Describe the size and location of the system wide partial network cluster vector.  Model the existence of multiple top-level PNC coordinators. Model the coordination of PNCs on selected channels.
<b>Supporting Material:</b>	–

〕

## 2.2.27 Communication via Complex Drivers

### [RS\_SYST\_00043] Communication via Complex Drivers

*Upstream requirements:* [RS\\_Main\\_00400](#)

〔

<b>Description:</b>	System Template shall support the Pdu-based communication via Complex Drivers.
<b>Rationale:</b>	It shall be possible to describe the Complex Driver Pdus that are transmitted over the network.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	A new BSW module is used above the PduR, e.g a Diagnostic Service.
<b>Supporting Material:</b>	–

〕

## 2.2.28 Description of custom bus systems

### [RS\_SYST\_00044] Description of custom bus systems

*Upstream requirements:* [RS\\_Main\\_00230](#)

〔

<b>Description:</b>	System Template shall support the integration of custom bus systems on the topology level.
<b>Rationale:</b>	It shall be possible to describe the complete network topology of a vehicle with a System Description.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Alternative communication technologies (e.g. I2C, USB, serial line) are integrated as Complex Drivers
<b>Supporting Material:</b>	—

〕

## 2.2.29 Co-existing System artifacts in the same model

### [RS\_SYST\_00045] Co-existing System artifacts in the same model

*Upstream requirements:* [RS\\_Main\\_00320](#)

〔

<b>Description:</b>	The System Template shall provide means to describe different System Extracts, which can co exist with the complete system description and each other in the same model.
<b>Rationale:</b>	—
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	The OEM hands a system extract over to the supplier, as a formal "requirement" specification. The supplier extends and refactors this system extract. In the next development cycle the OEM hands over an updated system extract to the supplier. The supplier updates his system extract according to the update of the OEM.
<b>Supporting Material:</b>	[RS_METH_00077]

〕

### 2.2.30 Network and physical representation on signal level

#### [RS\_SYST\_00047] Network and physical representation on signal level

*Upstream requirements:* [RS\\_Main\\_00320](#)

〔

<b>Description:</b>	The System Template shall provide means to describe the physical representation and the network representation of signals.
<b>Rationale:</b>	–
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

〕

### 2.2.31 CAN with Flexible Data-Rate

#### [RS\_SYST\_00048] CAN with Flexible Data-Rate

*Upstream requirements:* [RS\\_Main\\_00026](#)

〔

<b>Description:</b>	The System Template shall support the CAN FD protocol.
<b>Rationale:</b>	CAN FD increases the bandwidth of a CAN network and allows payload larger than 8 byte.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Development of a complete, multi-networked, in-vehicle electronic architecture
<b>Supporting Material:</b>	–

〕

### 2.2.32 Support of Efficient COM for large data configuration

#### [RS\_SYST\_00049] Support of Efficient COM for large data configuration

*Upstream requirements:* [RS\\_Main\\_00026](#)

〔

<b>Description:</b>	The System Template shall support the configuration of communication over Efficient COM for large data.
<b>Rationale:</b>	Efficient COM for large data provides a lean mechanism how the interaction of RTE with the Communication Stack is handled. There are however some prerequisites which need to be fulfilled if this interaction shall be done via Efficient COM for large data. The System Template shall define these prerequisites.
<b>Dependencies:</b>	–
<b>Use Case:</b>	IPdus which only contain one signal and have no special transmission mode defined can be processed by Efficient COM for large data.
<b>Supporting Material:</b>	–

〕

### 2.2.33 Data transformation of inter-ECU communication

#### [RS\_SYST\_00050] Data transformation of inter-ECU communication

*Upstream requirements:* [RS\\_Main\\_00026](#)

〔

<b>Description:</b>	The System Template shall provide the means to describe data transformation for inter-ECU communication.
<b>Rationale:</b>	If data of an inter-ECU communication shall be transformed, this has to be configured within the System to enable sending and receiving ECUs to execute the data transformation.
<b>Dependencies:</b>	None identified.
<b>Use Case:</b>	Large composite data shall be mapped in one go to bus communication to avoid the mapping of each atomic element of the composite data.
<b>Supporting Material:</b>	–

〕

### 2.2.34 Support of COM Based Data Transformation

#### [RS\_SYST\_00051] Support of COM Based Data Transformation

*Upstream requirements:* [RS\\_Main\\_01003](#)

〔

<b>Description:</b>	The System Template shall provide the means to define the usage of the uint8-array API to pass the serialized representation of a composite data to COM module.
<b>Rationale:</b>	The AUTOSAR transformer chain provides means to serialize composite data into a uint8-array representation. This serialized uint8-array shall be passed as one entity to COM.
<b>Dependencies:</b>	–
<b>Use Case:</b>	Usage of transformer with COM based serialization and Com Interaction to enable the communication with ECUs running AUTOSAR R4.1 versions and earlier.
<b>Supporting Material:</b>	–

〕

### 2.2.35 Translation between signal-based and service-oriented communication

#### [RS\_SYST\_00059] The System Template shall support the translation between signal-based and service-oriented communication.

*Upstream requirements:* [RS\\_Main\\_01002](#), [RS\\_Main\\_01003](#)

〔

<b>Description:</b>	The System Template shall support the translation between signal-based and service-oriented communication.
<b>Rationale:</b>	Adaptive Platform restricts communication to Service-oriented communication, the rest of the vehicle however still uses Signal-based communication means - therefore a translation of these two approaches has to be performed.
<b>Use Case:</b>	Data which is produced on a Can ECU is needed at an Adaptive machine in a safe and secure manner. The translation may be implemented on a Classic platform gateway Ecu.
<b>Dependencies:</b>	As an alternative the translation may be implemented on the Adaptive platform.
<b>Supporting Material:</b>	–

〕

### 2.2.36 Naming conventions

**[RS\_SYST\_00053] The System Template shall provide the ability to define naming conventions for public symbols**

*Upstream requirements: [RS\\_Main\\_00500](#)*

〔

<b>Description:</b>	The System Template shall provide the ability to define naming conventions for public symbols. This especially includes requirement ids, module abbreviations, meta data and configuration symbols used in the document of a release
<b>Rationale:</b>	Avoid ambiguities and name clashes inside the specification. Provide a consistent uniform presentation of meta data to the reader of the specification. Allow automatic processing of specification elements
<b>Use Case:</b>	
<b>Dependencies:</b>	–
<b>Supporting Material:</b>	–

〕

Please note that the System Template does not define specific naming conventions.

### 2.2.37 Support of Secured Pdus

**[RS\_SYST\_00054] Support of Secured Pdus**

*Upstream requirements: [RS\\_Main\\_00510](#)*

〔

<b>Description:</b>	The System Template shall support the definition of Secured Pdus.
<b>Rationale:</b>	It shall be possible to define a Pdu that is supplemented with additional Authentication Information.
<b>Dependencies:</b>	–
<b>Use Case:</b>	Protection of Pdus against unauthorized manipulation and replay attacks.
<b>Supporting Material:</b>	–

〕

## 2.2.38 Support of Container Pdus

### [RS\_SYST\_00055] Support of Container Pdus

*Upstream requirements:* [RS\\_Main\\_00026](#)

〔

<b>Description:</b>	The System Template shall support the definition of Container Pdus.
<b>Rationale:</b>	It shall be possible to define that one Container Pdu shall transport several contained Pdus.
<b>Dependencies:</b>	–
<b>Use Case:</b>	Routing of Pdus from a network onto a network with higher payload possibility (e.g. CAN onto CanFD or Ethernet).
<b>Supporting Material:</b>	–

〕

## 2.2.39 E2E-protected communication

### [RS\_SYST\_00056] E2E-protected communication

*Upstream requirements:* [RS\\_Main\\_00010](#)

〔

<b>Description:</b>	The System Template has to cover the protection of communication via E2E.
<b>Rationale:</b>	Enables safety-related communication over non-safety-related communication buses.
<b>Dependencies:</b>	–
<b>Use Case:</b>	Development of a complete, multi-networked, in-vehicle electronic architecture.
<b>Supporting Material:</b>	–

〕

## 2.2.40 Assigning communication graphs to particular RTE Implementation Plug-Ins

### [RS\_SYST\_00057] Assigning communication graphs to particular RTE Implementation Plug-Ins

*Upstream requirements:* [RS\\_Main\\_00060](#)

Γ

<b>Description:</b>	The System Template shall support to assign communication graphs of software components to particular RTE Implementation Plug-Ins.
<b>Rationale:</b>	The RTE of an ECU is build modularized with RTE Implementation Plug-Ins. Each communication graph is handled by a specific RTE Implementation Plug-In.
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

]

## 2.2.41 Optional Elements

### [RS\_SYST\_00058] The System Template shall support the usage of the TLV encoding in SOME/IP messages

*Upstream requirements:* [RS\\_Main\\_00280](#)

Γ

<b>Description:</b>	The System Template shall provide means to configure a SOME/IP transformer to consider TLV encoding according to the system model
<b>Rationale:</b>	The existence of optional elements in composite data structures is semantically different from the receiver simply taking an initial value if the received information does not contain a respective sub-element of a composite data structure. The receiver is supposed to actively acknowledge the fact that certain information is missing and still be able to deal with this fact in a meaningful way.
<b>Use Case:</b>	A composite data structure that qualifies for TLV encoding is defined and used for communication on the VFB. The SOME/IP transformer configured for this composite data structure needs to take the specification of the tLV encoding into account
<b>Dependencies:</b>	–
<b>Supporting Material:</b>	–

]

## 2.2.42 Software Cluster

**[RS\_SYST\_00060] The System Template shall support the modeling of Software Clusters** [

<b>Description:</b>	The System Template shall provide means to define software clusters composing of AUTOSAR software components and Basic Software Modules
<b>Rationale:</b>	Complex ECUs can be structurally decomposed into Software Clusters. Each Software Cluster is developed, integrated and build independent of the surrounding host system of the enclosing ECU.
<b>Use Case:</b>	Different development partners are responsible for specific software clusters. Each development partner is able to deploy its Software Cluster onto the ECU independently and to keep the rest of the software on the respective ECU unchanged.
<b>Dependencies:</b>	–
<b>Supporting Material:</b>	–

]

## 2.2.43 Interaction of a Software Cluster with the environment

**[RS\_SYST\_00061] The System Template shall provide means to describe the interface of the Software Clusters binary object** [

<b>Description:</b>	The System Template shall provide means to describe the interface of the Software Clusters binary object
<b>Rationale:</b>	The necessary information to access a resource defined inside of a Software Cluster shall be defined in the interface description
<b>Use Case:</b>	Establishment of connections between Software Clusters
<b>Dependencies:</b>	–
<b>Supporting Material:</b>	–

]

## 2.2.44 Software Cluster Resource

**[RS\_SYST\_00062] The System Template shall support the modeling of Software Cluster Resources** [

<b>Description:</b>	The System Template shall support the modeling of Software Cluster Resources
<b>Rationale:</b>	A Software Cluster is able to provide resources that can be accessed by other software clusters and to use resources of other Software Clusters
<b>Use Case:</b>	
<b>Dependencies:</b>	–
<b>Supporting Material:</b>	–

1

## 2.2.45 Ethernet IEEE1722Tp Stream support

## [RS\_SYST\_00063] Ethernet IEEE1722Tp Stream support

<b>Description:</b>	The System Template shall support the modeling of streams according to IEEE Std 1722-2016 [4]
<b>Rationale:</b>	Configuration of streams, the stream providers, and stream consumers.
<b>Use Case:</b>	Define the existence of IEEE1722Tp streams and who is producing and consuming the streams. Provide information about each stream content such that bandwidth calculations are supported.
<b>Dependencies:</b>	–
<b>Supporting Material:</b>	–

1

## 2.2.46 Ethernet Switch Filtering and Policing

### [RS\_SYST\_00064] Ethernet Switch Filtering and Policing [

<b>Description:</b>	The System Template shall support Ethernet Switch Filtering and Policing.
<b>Rationale:</b>	These mechanisms can be used to avoid bursts, restrict babbling idiots and to prevent denial of service attacks.
<b>Use Case:</b>	Ensure bandwidth for critical applications.
<b>Dependencies:</b>	–
<b>Supporting Material:</b>	IEEE Std 802.1Q-2018, section Qci 8.6

]

## 2.2.47 Firewall configuration

### [RS\_SYST\_00065] Firewall configuration

*Upstream requirements:* [RS\\_Main\\_01008](#), [RS\\_Main\\_00170](#)

[

<b>Description:</b>	The System Template shall provide the means to describe network packet patterns that are checked by a Firewall and the respective actions that are carried out by the Firewall in case that the pattern matches with the actual network traffic.
<b>Rationale:</b>	–
<b>Dependencies:</b>	–
<b>Use Case:</b>	–
<b>Supporting Material:</b>	–

]

## 2.2.48 Support of Variant Handling

### [RS\_SYST\_00066] The System Template shall support variant handling

*Upstream requirements:* [RS\\_Main\\_00360](#)

〔

<b>Description:</b>	The System Template shall provide the means to specify variants in a System Description, e.g. Topology, Software Mapping or Communication variants.
<b>Rationale:</b>	–
<b>Dependencies:</b>	–
<b>Use Case:</b>	Express basic product lines (e.g Compact Class, Middle Class, Luxury Class) in an AUTOSAR model.
<b>Supporting Material:</b>	–

〕

## 3 Change History

### 3.1 Change History for AUTOSAR 4.0.1 against 3.1.5

#### 3.1.1 Removed SRS Items

Number	Heading
[RS_SYST_00004]	Variant Handling
[RS_SYST_00005]	Timing Requirements

**Table 3.1: Removed Specification Items in 4.0.1**

#### 3.1.2 Changed SRS Items

Number	Heading
[RS_SYST_00001]	Mixed Systems (AUTOSAR/NON-AUTOSAR)
[RS_SYST_00007]	Mapping of Software Components to ECUs

**Table 3.2: Changed Specification Items in 4.0.1**

#### 3.1.3 Added SRS Items

Number	Heading
[RS_SYST_00027]	ECU Extract generation rules
[RS_SYST_00028]	IPdu End-to-End Communication Protection support
[RS_SYST_00029]	Dynamic length signals
[RS_SYST_00030]	Dynamic length IPdus
[RS_SYST_00031]	Distribution of Application and Vehicle Mode Requests
[RS_SYST_00032]	Topology variants
[RS_SYST_00033]	Software-to-ECU mapping variants
[RS_SYST_00034]	Timing variants
[RS_SYST_00035]	Data mapping variants
[RS_SYST_00036]	Communication variants
[RS_SYST_00037]	Timing properties
[RS_SYST_00038]	Support of SAE J1939 Protocol Features
[RS_SYST_00039]	ECU Communication via Ethernet
[RS_SYST_00040]	Timing constraints
[RS_SYST_00041]	Variants in ECU Extract

**Table 3.3: Added Specification Items in 4.0.1**

## 3.2 Change History for AUTOSAR 4.0.2 against 4.0.1

### 3.2.1 Removed SRS Items

N/A

### 3.2.2 Changed SRS Items

N/A

### 3.2.3 Added SRS Items

N/A

## 3.3 Change History for AUTOSAR 4.0.3 against 4.0.2

### 3.3.1 Removed SRS Items

N/A

### 3.3.2 Changed SRS Items

N/A

### 3.3.3 Added SRS Items

Number	Heading
[RS_SYST_00042]	Support for Partial Networking

Table 3.4: Added Specification Items in 4.0.3

## 3.4 Change History for AUTOSAR 4.1.1 against 4.0.3

### 3.4.1 Removed SRS Items

N/A

### 3.4.2 Changed SRS Items

N/A

### 3.4.3 Added SRS Items

Number	Heading
[RS_SYST_00043]	Communication via Complex Device Drivers
[RS_SYST_00044]	Description of custom bus systems
[RS_SYST_00045]	Co-existing System artifacts in the same model
[RS_SYST_00046]	Different views on the system's SWC-structure
[RS_SYST_00047]	Network and physical representation on signal level
[RS_SYST_00048]	CAN with Flexible Data-Rate

**Table 3.5: Added Specification Items in 4.1.1**

## 3.5 Change History for AUTOSAR 4.1.1 against 4.1.2

### 3.5.1 Removed SRS Items

N/A

### 3.5.2 Changed SRS Items

N/A

### 3.5.3 Added SRS Items

N/A

## 3.6 Change History for AUTOSAR 4.1.2 against 4.2.1

### 3.6.1 Removed SRS Items

N/A

### 3.6.2 Changed SRS Items

Number	Heading
[RS_SYST_00014]	Data Segmentation

--	--

**Table 3.6: Changed Specification Items in 4.2.1**

### 3.6.3 Added SRS Items

Number	Heading
[RS_SYST_00049]	Support of Efficient COM for large data configuration
[RS_SYST_00050]	Data transformation of inter-ECU communication
[RS_SYST_00051]	Support of COM Based Data Transformation
[RS_SYST_00052]	Ethernet Switch Configuration
[RS_SYST_00053]	Naming conventions
[RS_SYST_00054]	Support of Secured Pdus
[RS_SYST_00055]	Support of Container Pdus
[RS_SYST_00056]	E2E-protected communication

**Table 3.7: Added Specification Items in 4.2.1**

## 3.7 Change History for AUTOSAR 4.2.1 against 4.2.2

### 3.7.1 Removed SRS Items

N/A

### 3.7.2 Changed SRS Items

N/A

### 3.7.3 Added SRS Items

N/A

## 3.8 Change History for AUTOSAR 4.2.2 against 4.3.0

### 3.8.1 Added Requirements in 4.3.0

none

### 3.8.2 Changed Requirements in 4.3.0

none

### 3.8.3 Deleted Requirements in 4.3.0

Id	Heading
[RS_SYST_00010]	Exclusive Mapping of SWCs
[RS_SYST_00011]	Dedicated Mapping of SWCs

**Table 3.8: Deleted Traceables in 4.3.0**

## 3.9 Change History for AUTOSAR 4.3.0 against 4.3.1

### 3.9.1 Added Requirements in 4.3.1

none

### 3.9.2 Changed Requirements in 4.3.1

none

### 3.9.3 Deleted Requirements in 4.3.1

none

## 3.10 Change History for AUTOSAR 4.3.1 against 4.4.0

### 3.10.1 Added Requirements in 4.4.0

Number	Heading
[RS_SYST_00057]	Assigning communication graphs to particular RTE Implementation Plug-Ins
[RS_SYST_00058]	The System Template shall support the usage of the TLV encoding in SOME/IP messages

**Table 3.9: Added Requirements in 4.4.0**

### 3.10.2 Changed Requirements in 4.4.0

none

### 3.10.3 Deleted Requirements in 4.4.0

none

## 3.11 Change History for AUTOSAR 4.4.0 against 19-11

### 3.11.1 Added Requirements in 19-11

Number	Heading
[RS_SYST_00059]	The System Template shall support the translation between signal-based and service-oriented communication.

**Table 3.10: Added Requirements in 19-11**

### 3.11.2 Changed Requirements in 19-11

none

### 3.11.3 Deleted Requirements in 19-11

none

## 3.12 Change History for AUTOSAR R19-11 against R20-11

### 3.12.1 Added Requirements in R20-11

Number	Heading
[RS_SYST_00060]	The System Template shall support the modeling of Software Clusters
[RS_SYST_00061]	The System Template shall provide means to describe the interface of the Software Clusters binary object
[RS_SYST_00062]	The System Template shall support the modeling of Software Cluster Resources

**Table 3.11: Added Requirements in R20-11**

### 3.12.2 Changed Requirements in R20-11

none

### **3.12.3 Deleted Requirements in R20-11**

none

## **3.13 Change History for AUTOSAR R20-11 against R21-11**

### **3.13.1 Added Requirements in R21-11**

none

### **3.13.2 Changed Requirements in R21-11**

none

### **3.13.3 Deleted Requirements in R21-11**

none

## **3.14 Change History for AUTOSAR R21-11 against R22-11**

### **3.14.1 Added Requirements in R22-11**

none

### **3.14.2 Changed Requirements in R22-11**

Number	Heading
[RS_SYST_00042]	Support for Partial Networking

**Table 3.12: Changed Requirements in R22-11**

### **3.14.3 Deleted Requirements in R22-11**

none

## 3.15 Change History for AUTOSAR R22-11 against R23-11

### 3.15.1 Added Requirements in R23-11

Number	Heading
[RS_SYST_00063]	Ethernet IEEE1722Tp Stream support
[RS_SYST_00064]	Ethernet Switch Filtering and Policing

**Table 3.13: Added Requirements in R23-11**

### 3.15.2 Changed Requirements in R23-11

none

### 3.15.3 Deleted Requirements in R23-11

none

## 3.16 Change History for AUTOSAR R23-11 against R24-11

### 3.16.1 Added Requirements in R24-11

Number	Heading
[RS_SYST_00065]	Firewall configuration
[RS_SYST_00066]	The System Template shall support variant handling

**Table 3.14: Added Requirements in R24-11**

### 3.16.2 Changed Requirements in R24-11

none

### 3.16.3 Deleted Requirements in R24-11

Number	Heading
[RS_SYST_00015]	Bus bandwidth
[RS_SYST_00023]	ECU Communication via MOST
[RS_SYST_00026]	Fibex compatibility
[RS_SYST_00032]	Topology variants
[RS_SYST_00033]	Software-to-ECU mapping variants
[RS_SYST_00034]	Timing Variants
[RS_SYST_00035]	Data mapping variants
[RS_SYST_00036]	Communication variants
[RS_SYST_00040]	Timing constraints
[RS_SYST_00041]	Variants in ECU Extract
[RS_SYST_00046]	Different views on the system's SWC-structure

**Table 3.15: Deleted Requirements in R24-11**