

<b>Document Title</b>	Requirements on Debugging, Tracing and Profiling support of AUTOSAR Components
<b>Document Owner</b>	AUTOSAR
<b>Document Responsibility</b>	AUTOSAR
<b>Document Identification No</b>	915

<b>Document Status</b>	published
<b>Part of AUTOSAR Standard</b>	Foundation
<b>Part of Standard Release</b>	R24-11

<b>Document Change History</b>			
<b>Date</b>	<b>Release</b>	<b>Changed by</b>	<b>Description</b>
2024-11-27	R24-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>No content changes</li> </ul>
2023-11-23	R23-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Editorial changes</li> </ul>
2022-11-24	R22-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Corrected “Dependencies” of some items</li> <li>Changed ARTI information and ARTI hook items to be more generic</li> </ul>
2021-11-25	R21-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Shifted internal glossary to AUTOSAR glossary</li> </ul>
2020-11-30	R20-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Changed document status from draft to valid</li> </ul>
2019-11-28	R19-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Editorial changes</li> <li>Changed Document Status from Final to published</li> </ul>
2019-03-29	1.5.1	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>No content changes</li> </ul>



△

2018-10-31	1.5.0	AUTOSAR Release Management	<ul style="list-style-type: none"><li>• Initial release</li></ul>
------------	-------	----------------------------------	---

## **Disclaimer**

This work (specification and/or software implementation) and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the work.

The material contained in this work is protected by copyright and other types of intellectual property rights. The commercial exploitation of the material contained in this work requires a license to such intellectual property rights.

This work may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the work may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The work has been developed for automotive applications only. It has neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

## Contents

1	Scope of Document	5
2	Conventions to be used	6
2.1	Document Conventions	6
2.2	Requirements Guidelines	6
2.2.1	Requirements quality	6
2.2.2	Requirements identification	6
2.2.3	Requirements status	6
3	Acronyms and abbreviations	7
4	Requirements Specification	8
4.1	Functional Overview	8
4.2	Functional Requirements on ARTI Template	8
4.3	Functional Requirements on ARTI Description	11
4.4	Functional Requirements on ARTI Hooks	14
4.5	Non-Functional Requirements (Qualities)	16
5	Requirements Tracing	17
6	References	18
A	Change history of AUTOSAR traceable items	19
A.1	Traceable item history of this document according to AUTOSAR Re-lease R22-11	19
A.1.1	Added Requirements in R22-11	19
A.1.2	Changed Requirements in R22-11	19
A.1.3	Deleted Requirements in R22-11	19
A.2	Traceable item history of this document according to AUTOSAR Re-lease R23-11	19
A.2.1	Added Requirements in R23-11	19
A.2.2	Changed Requirements in R23-11	20
A.2.3	Deleted Requirements in R23-11	20
A.3	Traceable item history of this document according to AUTOSAR Re-lease R24-11	20
A.3.1	Added Requirements in R24-11	20
A.3.2	Changed Requirements in R24-11	20
A.3.3	Deleted Requirements in R24-11	20

# 1 Scope of Document

Debugging and tracing enables efficient development, integration, optimization and verification of ECU software. For analyzing several aspects - especially timing aspects - it becomes essential to link the debugging and tracing data to the scheduling of an ECU. Knowledge about tasks, interrupts and runnables, in other words: awareness of the operating system ("OS awareness"), is required.

A good interaction of the tool chain provides complete round-trip engineering from model down to hardware and back - covering several software levels and several phases of the V-model.

The objective of ARTI ("AUTOSAR Run-Time Interface") is an interface description, that allows debugging and tracing of AUTOSAR systems with a flexible awareness supporting different views, such as OS, BSW, RTE, model, user-data and user-defined.

In particular, the interface shall enable tools to perform:

- Debugging
- Tracing
- Timing Measurement
- Profiling

The main focus of this requirements document is the format of the ARTI hooks and the exported ARTI description.

## **2 Conventions to be used**

### **2.1 Document Conventions**

The representation of requirements in AUTOSAR documents follows the table specified in [TPS\_STDT\_00078], see Standardization Template, chapter Support for Traceability ([1]).

The verbal forms for the expression of obligation specified in [TPS\_STDT\_00053] shall be used to indicate requirements, see Standardization Template, chapter Support for Traceability ([1]).

### **2.2 Requirements Guidelines**

Not applicable yet, including subchapters

#### **2.2.1 Requirements quality**

#### **2.2.2 Requirements identification**

#### **2.2.3 Requirements status**

### 3 Acronyms and abbreviations

The glossary below includes acronyms and abbreviations relevant to RS\_ARTI that are not included in the AUTOSAR Glossary [2].

Abbreviation / Acronym:	Description:
ARTI	AUTOSAR Run Time Interface
OS	Operating System

**Table 3.1: Acronyms and Abbreviations**

## 4 Requirements Specification

This chapter describes all requirements driving the work to define ARTI.

### 4.1 Functional Overview

The tools that generate AUTOSAR modules (e.g. OS, RTE, etc.) have to emit internal information about this module. The information shall allow to debug and trace the behavior of this module. Additional tools will collect all ARTI information of an ECU and allow selecting specific items to trace and create tracing hook files for a specific trace channel (e.g. internal buffer, hardware trace buffers, etc.). The build environment creates the final application, which then can be used in the ECU. Debugging and tracing tools can read in the ARTI information and are “AUTOSAR” aware, giving additional debugging and tracing features to the developer.

ARTI is supposed to work with debug information created by the compilers. This means each module that supports ARTI needs to be compiled with debug information, and the ARTI information has to use the symbol names created by the compiler.

ARTI introduces hooks. In order to use them, they shall be incorporated into the module’s code. Either they are put therein statically, or they have to be configured.

ARTI consists of these functional elements:

- ARTI module description  
The “ARTI Module Description” is emitted as an ARXML file, standardized by the ARTI Template.
- ARTI hook implementations  
The ARTI hooks are implemented within the AUTOSAR module’s source code.

### 4.2 Functional Requirements on ARTI Template

The requirements in this section all concern how the ARTI template shall be defined.



**[RS\_ARTIFO\_00001] The ARTI Description shall be the root for the whole ARTI information of an ECU**

Upstream requirements: [RS\\_Main\\_01025](#), [RS\\_Main\\_01026](#)

[

<b>Description:</b>	The ARTI Template shall be the backbone for all information regarding ARTI of a particular ECU.
<b>Rationale:</b>	To access Run-Time information of an ECU, a tool needs to have one reference to look for the information. All further detailed information can be found by following the contents of this reference. Note that this requirement does not imply that all relevant information is copied into the template. References to elements in other templates may be included to avoid redundant elements in the model.
<b>Dependencies:</b>	ARTI tools need to be able to read other templates (esp. ECU), too, if these are referenced by the ARTI description.
<b>Use Case:</b>	The ARTI Template includes specifications on how to model generic classes and instances, without changing the template, allowing to specify the access to any arbitrary object of the ECU. The template includes references to other templates and components to be able to use this information, too.
<b>Supporting Material:</b>	-

]

**[RS\_ARTIFO\_00002] The ARTI Description shall support generic objects**

Upstream requirements: [RS\\_Main\\_01025](#), [RS\\_Main\\_01026](#)

[

<b>Description:</b>	Generic objects define arbitrary objects.
<b>Rationale:</b>	A generic object is any arbitrary object that is not part of another module. The definition shall be able to define the layout of an object ("class") as well as the values of a specific instance.
<b>Dependencies:</b>	-
<b>Use Case:</b>	The generic object definition defines how an arbitrary object should show up in a debugger or when tracing.
<b>Supporting Material:</b>	-

]

**[RS\_ARTIFO\_00003] The ARTI Description shall support a class definition of a generic object**

Upstream requirements: [RS\\_Main\\_01025](#), [RS\\_Main\\_01026](#)

<b>Description:</b>	The class definition of a generic object defines the layout of an arbitrary object.
<b>Rationale:</b>	An object that is not part of another AUTOSAR module has to be defined to an ARTI consuming tool. The ARTI Template shall provide a mechanism to define the object layout (“class”) with its name, description, and parameters.
<b>Dependencies:</b>	-
<b>Use Case:</b>	The generic object definition defines how an arbitrary object should show up in a debugger or when tracing.
<b>Supporting Material:</b>	-

**[RS\_ARTIFO\_00004] The ARTI Description shall support an instance definition of a generic object**

Upstream requirements: [RS\\_Main\\_01025](#), [RS\\_Main\\_01026](#)

<b>Description:</b>	The instance definition of a generic object defines the values of an arbitrary object instance.
<b>Rationale:</b>	The ARTI Template shall define, how an ARTI consuming tool can evaluate the parameters of an object instance.
<b>Dependencies:</b>	-
<b>Use Case:</b>	-
<b>Supporting Material:</b>	-

**[RS\_ARTIFO\_00005] The ARTI Description shall support expressions to evaluate a parameter value**

Upstream requirements: [RS\\_Main\\_01025](#)

<b>Description:</b>	Expressions define how a specific value of a parameter can be accessed on the target.
<b>Rationale:</b>	Expressions are typically represented as C expression.
<b>Dependencies:</b>	-



△

<b>Use Case:</b>	Expressions and values are used by a debugger to display a current state of the application.
<b>Supporting Material:</b>	-

]

**[RS\_ARTIFO\_00006] The ARTI Description shall support constants used by object parameters**

*Upstream requirements:* [RS\\_Main\\_01025](#), [RS\\_Main\\_01026](#)

[

<b>Description:</b>	Constants define the value of an object parameter.
<b>Rationale:</b>	Object parameters may be constant. This definition shall supply the container for the constant.
<b>Dependencies:</b>	-
<b>Use Case:</b>	Object parameters may refer to expressions or constants. This is the definition for constant parameters.
<b>Supporting Material:</b>	-

]

**[RS\_ARTIFO\_00007] The ARTI Description shall support parameter maps**

*Upstream requirements:* [RS\\_Main\\_01025](#), [RS\\_Main\\_01026](#)

[

<b>Description:</b>	Parameter maps translate the value of a parameter to a string to display.
<b>Rationale:</b>	A parameter value may refer to a specific meaning (e.g. "state"). The parameter map allows to translate the value to a (human readable) string.
<b>Dependencies:</b>	-
<b>Use Case:</b>	Parameter maps are used by an ARTI consuming tool to display a parameter value in a meaningful way.
<b>Supporting Material:</b>	-

]

### 4.3 Functional Requirements on ARTI Description

The requirements in this section all concern how the ARTI description shall be defined.

**[RS\_ARTIFO\_00008] The ARTI description shall follow the ARTI Template.**

*Upstream requirements:* [RS\\_Main\\_01025](#), [RS\\_Main\\_01026](#)

[

<b>Description:</b>	All information concerning ARTI shall be collected in the ARTI description, following the ARTI Template.
<b>Rationale:</b>	To access Run-Time information of an ECU, a tool needs to know how to read the information. By strictly following the template, the tool is able to extract all necessary information without further user interaction.
<b>Dependencies:</b>	ARTI tools need to be able to read and understand the ARTI Template and possibly other templates (e.g. ECU).
<b>Use Case:</b>	Using the ARTI description, an ARTI tool is able to detect, visualize and measure arbitrary objects of an ECU.
<b>Supporting Material:</b>	-

]

**[RS\_ARTIFO\_00009] The ARTI description shall include all class definitions of generic objects.**

*Upstream requirements:* [RS\\_Main\\_01025](#), [RS\\_Main\\_01026](#)

[

<b>Description:</b>	All generic (arbitrary) objects that should be processed by an ARTI consuming tool shall be defined in a class definition, following the ARTI Template.
<b>Rationale:</b>	An ARTI consuming tool needs to know the layout of all generic objects used by the module.
<b>Dependencies:</b>	-
<b>Use Case:</b>	Evaluating the form of display for generic objects.
<b>Supporting Material:</b>	-

]

**[RS\_ARTIFO\_00010] The ARTI description shall include all instance definitions of generic objects.**

*Upstream requirements:* [RS\\_Main\\_01025](#), [RS\\_Main\\_01026](#)

[

<b>Description:</b>	All generic (arbitrary) instances of objects that should be processed by an ARTI consuming tool shall be defined in an instance definition, following the ARTI Template.
<b>Rationale:</b>	An ARTI consuming tool needs to know how to get the values of parameters of generic objects.



△

<b>Dependencies:</b>	-
<b>Use Case:</b>	Evaluating the values to display for generic objects.
<b>Supporting Material:</b>	-

]

**[RS\_ARTIFO\_00011] The ARTI description shall include all expression definitions to evaluate parameter values.**

*Upstream requirements:* [RS\\_Main\\_01025](#)

[

<b>Description:</b>	All expressions used to evaluate parameter values shall be defined, following the ARTI Template.
<b>Rationale:</b>	An ARTI consuming tool needs to know how to read the values of parameters from the target. Expressions are typically represented as C expression.
<b>Dependencies:</b>	-
<b>Use Case:</b>	Evaluating the values to display for object parameters.
<b>Supporting Material:</b>	-

]

**[RS\_ARTIFO\_00012] The ARTI description shall include all constant definitions used by parameters.**

*Upstream requirements:* [RS\\_Main\\_01025](#), [RS\\_Main\\_01026](#)

[

<b>Description:</b>	All constants used by parameters shall be defined, following the ARTI Template.
<b>Rationale:</b>	Object parameters may be constant. An ARTI consuming tool needs to know which parameter is constant and which value to show.
<b>Dependencies:</b>	-
<b>Use Case:</b>	Evaluating the values to display for object parameters.
<b>Supporting Material:</b>	-

]

**[RS\_ARTIFO\_00013] The ARTI description shall include all parameter maps used by parameters.**

*Upstream requirements:* [RS\\_Main\\_01025](#), [RS\\_Main\\_01026](#)

[

<b>Description:</b>	All parameter maps used by parameters shall be defined, following the ARTI Template.
<b>Rationale:</b>	A parameter value may refer to a specific meaning (e.g. “state”). The parameter map translates the value of a specific parameter to a (human readable) string.
<b>Dependencies:</b>	-
<b>Use Case:</b>	Parameter maps are used by an ARTI consuming tool to display a parameter value in a meaningful way.
<b>Supporting Material:</b>	-

]

## 4.4 Functional Requirements on ARTI Hooks

The requirements in this section all concern how ARTI hooks shall be used and defined.

**[RS\_ARTIFO\_00014] ARTI Hooks shall be implemented with minimal intrusion**

*Upstream requirements:* [RS\\_Main\\_01026](#)

[

<b>Description:</b>	ARTI Hooks shall be implemented in source code with as minimal intrusion as possible.
<b>Rationale:</b>	ARTI Hooks will be extended by an ARTI consuming tool, possibly adding extra code that affects the run-time of the application. This intrusion should be kept as minimal as possible, e.g. by using “C” macros for implementation of the ARTI Hooks.
<b>AppliesTo:</b>	CP
<b>Dependencies:</b>	–
<b>Use Case:</b>	Hooks may be implemented as “C” macros. This allows easily to expand the macros to “nothing”, causing no intrusion or side effects at all. An ARTI consuming tool may choose to extend the macro to supply information to this tool.
<b>Supporting Material:</b>	-

]

**[RS\_ARTIFO\_00015] ARTI Hooks shall follow a fixed format**

Upstream requirements: [RS\\_Main\\_01026](#)

[

<b>Description:</b>	ARTI Hooks shall follow a fixed format.
<b>Rationale:</b>	To allow an ARTI consuming tool to expand the ARTI Hooks it is beneficially if these follow a common format.
<b>AppliesTo:</b>	CP
<b>Dependencies:</b>	RS_ARTIFO_00014
<b>Use Case:</b>	Hooks may be implemented as “C” macros. This allows easily to expand the macros to “nothing”, causing no intrusion or side effects at all. An ARTI consuming tool may choose to extend the macro to supply information to this tool.
<b>Supporting Material:</b>	-

]

**[RS\_ARTIFO\_00016] ARTI Hooks shall provide information about the calling context**

Upstream requirements: [RS\\_Main\\_01026](#)

[

<b>Description:</b>	ARTI Hooks shall provide information about the calling context.
<b>Rationale:</b>	To ensure that the ARTI Hook implementation creates as little over head as possible ARTI consuming tool needs to know the calling context.
<b>Dependencies:</b>	RS_ARTIFO_00014
<b>Use Case:</b>	An ARTI consuming tool may choose to extend the macro to supply information to this tool in the current context. This mainly concerns the privilege level and whether interrupts are looked or not.
<b>Supporting Material:</b>	-

]

**[RS\_ARTIFO\_00017] ARTI Hooks shall provide the name of the class they belong to**

Upstream requirements: [RS\\_Main\\_01026](#)

[

<b>Description:</b>	ARTI Hooks shall provide the name of the class they belong to.
<b>Rationale:</b>	Hooks shall be grouped into classes belonging to a similar functionality (events)
<b>Dependencies:</b>	RS_ARTIFO_00014



△

<b>Use Case:</b>	To provide better modularity of the hooks and an ARTI consuming tool, the events shall be grouped into classes (e.g. scheduler or communication events). The particular class names are specified in the according platform document.
<b>Supporting Material:</b>	-

]

#### [RS\_ARTIFO\_00018] ARTI Hooks shall provide the name of the event

Upstream requirements: [RS\\_Main\\_01026](#)

[

<b>Description:</b>	ARTI Hooks shall provide the name of the event. These events should be grouped into classes.
<b>Rationale:</b>	
<b>Dependencies:</b>	RS_ARTIFO_00014
<b>Use Case:</b>	The event names are used by an ARTI consuming tool to identify specific events. The event names are specified in the according platform document.
<b>Supporting Material:</b>	-

]

#### [RS\_ARTIFO\_00019] ARTI Hooks shall provide parameters for the event

Upstream requirements: [RS\\_Main\\_01026](#)

[

<b>Description:</b>	ARTI Hooks shall provide parameters for the event. The number of parameters is specified by the appropriate event specification.
<b>Rationale:</b>	
<b>Dependencies:</b>	RS_ARTIFO_00014
<b>Use Case:</b>	ARTI consuming tools may need extra parameters to identify a specific object that belongs to an event (e.g. scheduler entity, sender/receiver id).
<b>Supporting Material:</b>	-

]

## 4.5 Non-Functional Requirements (Qualities)

No content.



## 5 Requirements Tracing

The following table references the requirements specified in [3] and links to the fulfillments of these.

Requirement	Description	Satisfied by
[RS_Main_01025]	AUTOSAR shall support debugging of software on the target and onboard	[RS_ARTIFO_00001] [RS_ARTIFO_00002] [RS_ARTIFO_00003] [RS_ARTIFO_00004] [RS_ARTIFO_00005] [RS_ARTIFO_00006] [RS_ARTIFO_00007] [RS_ARTIFO_00008] [RS_ARTIFO_00009] [RS_ARTIFO_00010] [RS_ARTIFO_00011] [RS_ARTIFO_00012] [RS_ARTIFO_00013]
[RS_Main_01026]	AUTOSAR shall support tracing and profiling on the target and onboard	[RS_ARTIFO_00001] [RS_ARTIFO_00002] [RS_ARTIFO_00003] [RS_ARTIFO_00004] [RS_ARTIFO_00006] [RS_ARTIFO_00007] [RS_ARTIFO_00008] [RS_ARTIFO_00009] [RS_ARTIFO_00010] [RS_ARTIFO_00012] [RS_ARTIFO_00013] [RS_ARTIFO_00014] [RS_ARTIFO_00015] [RS_ARTIFO_00016] [RS_ARTIFO_00017] [RS_ARTIFO_00018] [RS_ARTIFO_00019]

**Table 5.1: Requirements Tracing**

## 6 References

- [1] Standardization Template  
AUTOSAR\_FO\_TPS\_StandardizationTemplate
- [2] Glossary  
AUTOSAR\_FO\_TR\_Glossary
- [3] Main Requirements  
AUTOSAR\_FO\_RS\_Main

## A Change history of AUTOSAR traceable items

### A.1 Traceable item history of this document according to AUTOSAR Release R22-11

#### A.1.1 Added Requirements in R22-11

none

#### A.1.2 Changed Requirements in R22-11

Number	Heading
[RS_ARTIFO_00014]	ARTI Hooks shall be implemented with minimal intrusion
[RS_ARTIFO_00015]	ARTI Hooks shall follow a fixed format
[RS_ARTIFO_00016]	ARTI Hooks shall provide information about the calling context
[RS_ARTIFO_00017]	ARTI Hooks shall provide the name of the class they belong to
[RS_ARTIFO_00018]	ARTI Hooks shall provide the name of the event
[RS_ARTIFO_00019]	ARTI Hooks shall provide parameters for the event

**Table A.1: Changed Requirements in R22-11**

#### A.1.3 Deleted Requirements in R22-11

none

### A.2 Traceable item history of this document according to AUTOSAR Release R23-11

#### A.2.1 Added Requirements in R23-11

none

### A.2.2 Changed Requirements in R23-11

Number	Heading
[RS_ARTIFO_00014]	ARTI Hooks shall be implemented with minimal intrusion
[RS_ARTIFO_00015]	ARTI Hooks shall follow a fixed format
[RS_ARTIFO_00016]	ARTI Hooks shall provide information about the calling context
[RS_ARTIFO_00017]	ARTI Hooks shall provide the name of the class they belong to
[RS_ARTIFO_00018]	ARTI Hooks shall provide the name of the event
[RS_ARTIFO_00019]	ARTI Hooks shall provide parameters for the event

**Table A.2: Changed Requirements in R23-11**

### A.2.3 Deleted Requirements in R23-11

none

## A.3 Traceable item history of this document according to AUTOSAR Release R24-11

### A.3.1 Added Requirements in R24-11

none

### A.3.2 Changed Requirements in R24-11

none

### A.3.3 Deleted Requirements in R24-11

none