

Document Title	Collection of constraints on AUTOSAR M1 models
Document Owner	AUTOSAR
Document Responsibility	AUTOSAR
Document Identification No	635

Document Status	published
Part of AUTOSAR Standard	Adaptive Platform
Part of Standard Release	R25-11

Document Change History			
Date	Release	Changed by	Description
2025-11-27	R25-11	AUTOSAR Release Management	<ul style="list-style-type: none"> Updated constraints according to changes in TPS documents
2024-11-27	R24-11	AUTOSAR Release Management	<ul style="list-style-type: none"> Updated constraints according to changes in TPS documents
2023-11-23	R23-11	AUTOSAR Release Management	<ul style="list-style-type: none"> Updated constraints according to changes in TPS documents
2022-11-24	R22-11	AUTOSAR Release Management	<ul style="list-style-type: none"> Updated constraints according to changes in TPS documents
2021-11-25	R21-11	AUTOSAR Release Management	<ul style="list-style-type: none"> Updated constraints according to changes in TPS documents
2020-11-30	R20-11	AUTOSAR Release Management	<ul style="list-style-type: none"> Updated constraints according to changes in TPS documents Removed all SWS constraints Split document into 3 documents, reflecting the standards CP, AP, FO
2019-11-28	R19-11	AUTOSAR Release Management	<ul style="list-style-type: none"> Updated constraints according to changes in SWS and TPS documents Changed Document Status from Final to published
2018-10-31	4.4.0	AUTOSAR Release Management	<ul style="list-style-type: none"> Completion of constraint context by adding tables and classtables referenced by model constraints to this document



△

2017-12-08	4.3.1	AUTOSAR Release Management	<ul style="list-style-type: none"> • minor corrections / clarifications / editorial changes; For details please refer to the ChangeDocumentation
2016-11-30	4.3.0	AUTOSAR Release Management	<ul style="list-style-type: none"> • minor corrections / clarifications / editorial changes; For details please refer to the ChangeDocumentation
2015-07-31	4.2.2	AUTOSAR Release Management	<ul style="list-style-type: none"> • minor corrections / clarifications / editorial changes; For details please refer to the ChangeDocumentation
2014-10-31	4.2.1	AUTOSAR Release Management	<ul style="list-style-type: none"> • Editorial changes
2013-10-31	4.1.2	AUTOSAR Release Management	<ul style="list-style-type: none"> • Updated constraints according to changes in SWS and TPS documents
2013-03-15	4.1.1	AUTOSAR Administration	<ul style="list-style-type: none"> • Initial Release

Disclaimer

This work (specification and/or software implementation) and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the work.

The material contained in this work is protected by copyright and other types of intellectual property rights. The commercial exploitation of the material contained in this work requires a license to such intellectual property rights.

This work may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the work may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The work has been developed for automotive applications only. It has neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

Table of Contents

1	Document Information and Content	6
2	Autosar Model Constraints	7
2.1	AP_TPS_MachineConfiguration	7
2.2	AP_TPS_ManifestSpecification	9
2.3	AP_TPS_TimingExtensions	153
A	Mentioned Class Tables	158
B	Change history of AUTOSAR traceable items	385
B.1	Traceable item history of this document according to AUTOSAR Release R25-11	385
B.1.1	Added Constraints in R25-11	385
B.1.2	Changed Constraints in R25-11	389
B.1.3	Deleted Constraints in R25-11	392
B.2	Traceable item history of this document according to AUTOSAR Release R24-11	392
B.2.1	Added Constraints in R24-11	392
B.2.2	Changed Constraints in R24-11	396
B.2.3	Deleted Constraints in R24-11	415

References

- [1] SOME/IP Protocol Specification
AUTOSAR_FO_PRS_SOMEIPProtocol
- [2] ISO 10646:2012 – Information technology – Universal Coded Character Set (UCS)
<https://www.iso.org>
- [3] Specification of Execution Management
AUTOSAR_AP_SWS_ExecutionManagement

1 Document Information and Content

This auxiliary document provides a collection of constraints for AUTOSAR models. All constraints are copied from template specification from the AUTOSAR Adaptive Platform, so this document does not introduce any new constraints.

A list of the documents that the constraints originate from can be found in the table of contents. Chapter [2](#) contains the collected constraints, grouped by source documents. All constraints from the same source document are contained within a single section.

2 Autosar Model Constraints

2.1 AP_TPS_MachineConfiguration

[constr_9322] **ApmcFunctionalClusterDef** category restriction

Status: DRAFT

Imposition time: IT_CfgFc

[The following values for the attribute `category` of `ApmcFunctionalClusterDef` are reserved by the AUTOSAR Standard:

- STANDARDIZED_CLUSTER_DEFINITION
- VENDOR_SPECIFIC_CLUSTER_DEFINITION

]

[constr_10579] Existence of **definition**

Status: DRAFT

Imposition time: IT_CfgFc

[In the context of an `ApmcAbstractValue`, the reference in the role `definition` shall exist.]

[constr_10580] Restriction regarding the value of **ApmcDefinitionElement.lowerMultiplicity** vs. **ApmcDefinitionElement.lowerMultiplicity**

Status: DRAFT

Imposition time: IT_CfgFc

[In the context of any given `ApmcDefinitionElement`, if attribute `upperMultiplicity` exists, then its value shall be greater or equal to the value of the attribute `lowerMultiplicity` in the same context.]

[constr_10581] Existence of reference in the role **ApmcFunctionalClusterValue.definition**

Status: DRAFT

Imposition time: IT_CfgFc

[For each `ApmcFunctionalClusterValue`, the reference in the role `definition` shall exist.]

[constr_10582] Existence of reference in the role **ApmcContainerValue.definition**

Status: DRAFT

Imposition time: IT_CfgFc

[For each `ApmcContainerValue`, the reference in the role `definition` shall exist.]

[constr_10583] Existence of reference in the role [ApmcContainerElementValue.definition](#)

Status: DRAFT

Imposition time: IT_CfgFc

[For each [ApmcContainerElementValue](#), the reference in the role [definition](#) shall exist.]

[constr_10584] Allowed [value](#) for a [ApmcNumericalParamValue](#) that implements an boolean-style parameter

Status: DRAFT

Imposition time: IT_CfgFc

[For any [ApmcNumericalParamValue](#) that refers to an [ApmcBooleanParamDef](#) in the role [definition](#), the content of the [ApmcNumericalParamValue.value](#) shall only be either 0 or 1.]

[constr_10585] Allowed [value](#) for a [ApmcTextualParamValue](#) that implements an enumeration-style parameter

Status: DRAFT

Imposition time: IT_CfgFc

[For any [ApmcTextualParamValue](#) that refers to an [ApmcEnumerationParamDef](#) in the role [definition](#), the content of the [ApmcTextualParamValue.value](#) shall only be identical to the [shortName](#) of one of the [ApmcEnumerationLiteralDefs](#) that are aggregated by the applicable [ApmcEnumerationParamDef](#) in the role [literal](#).]

[constr_10635] Allowed target type of the reference in the role [ApmcRevisionLabelParamValue.definition](#)

Status: DRAFT

Imposition time: IT_CfgFc

[The reference in the role [ApmcRevisionLabelParamValue.definition](#) shall **only** refer to an [ApmcRevisionLabelParamDef](#).]

[constr_10636] Allowed target type of the reference in the role [ApmcStrongRevisionLabelParamValue.definition](#)

Status: DRAFT

Imposition time: IT_CfgFc

[The reference in the role [ApmcStrongRevisionLabelParamValue.definition](#) shall **only** refer to an [ApmcStrongRevisionLabelParamDef](#).]

[constr_10637] Allowed target type of the reference in the role [ApmcIPv4AddressParamValue.definition](#)

Status: DRAFT

Imposition time: IT_CfgFc

[The reference in the role [ApmcIPv4AddressParamValue.definition](#) shall **only** refer to an [ApmcIPv4AddressParamDef](#).]

[constr_10638] Allowed target type of the reference in the role `ApmcIPv6AddressParamValue.definition`*Status:* DRAFT*Imposition time:* IT_CfgFc

[The reference in the role `ApmcIPv6AddressParamValue.definition` shall **only** refer to an `ApmcIPv6AddressParamDef`.]

[constr_10639] Allowed target type of the reference in the role `ApmcMacAddressParamValue.definition`*Status:* DRAFT*Imposition time:* IT_CfgFc

[The reference in the role `ApmcMacAddressParamValue.definition` shall **only** refer to an `ApmcMacAddressParamDef`.]

[constr_10640] Allowed target type of the reference in the role `ApmcUriParamValue.definition`*Status:* DRAFT*Imposition time:* IT_CfgFc

[The reference in the role `ApmcUriParamValue.definition` shall **only** refer to an `ApmcUriParamDef`.]

[constr_10643] Existence of attributes `ApmcDefinitionElement.upperMultiplicity` and `ApmcDefinitionElement.upperMultiplicityIsInfinite`*Status:* DRAFT*Imposition time:* IT_CfgFc

[For each `ApmcDefinitionElement`, **either** the attribute `upperMultiplicity` or `upperMultiplicityIsInfinite` shall exist.]

[constr_10644] Target of a `ApmcReferenceValue` where `definition.isFuncClusterEndpointRef` is set to `true`*Status:* DRAFT*Imposition time:* IT_CfgFc

[If an `ApmcContainerValue` is referenced from an `ApmcReferenceValue` where `definition.isFuncClusterEndpointRef` is set to `true`, then the referenced `ApmcContainerValue` shall refer in the role `definition` to an `ApmcParamConfContainerDef` where attribute `isFuncClusterEndpoint` is also set to `true`.]

2.2 AP_TPS_ManifestSpecification

[constr_1473] No support for `PRPortPrototype`*Imposition time:* IT_BefAraApiGen

[A `ServiceInterface` shall not be referenced by a `PRPortPrototype` in the role `providedRequiredInterface`.]

[constr_1478] SwDataDefProps applicable to ApplicationDataTypes exclusive to the AUTOSAR adaptive platform

Imposition time: IT_BefAraApiGen

[

Attributes of SwDataDefProps	Root Elem.		Attribute Existence per Category
	ApplicationAssocMapDataType	ApplicationAssocMapElement	ASSOCIATIVE_MAP
additionalNativeTypeQualifier			
annotation	x	x	*
baseType			
compuMethod			
dataConstr			
displayFormat	x	x	0..1
implementationDataType			
invalidValue			
stepSize			
swAddrMethod			
swAlignment			
swBitRepresentation			
swCalibrationAccess			
swCalprmAxisSet			
swComparisonVariable			
swDataDependency			
swHostVariable			
swImplPolicy			
swIntendedResolution			
swInterpolationMethod			
swIsVirtual			
swPointerTargetProps			
swRecordLayout			
swRefreshTiming			
swTextProps			
swValueBlockSize			
unit			
valueAxisDataType			

]

[constr_1482] Mapping of service interfaces vs. mapping of service interface elements*Imposition time:* IT_BefAraApiGen

[In order to establish a mapping between a given pair of `ServiceInterfaces`, at most **one of** the following alternatives can exist:

- the given pair of `ServiceInterfaces` is referenced by a `ServiceInterfaceMapping`, where one `ServiceInterface` is referenced in the role `sourceServiceInterface` and the other `ServiceInterface` is referenced in the role `compositeServiceInterface`.
- an arbitrary mixture of the following options exists:
 - an `event` aggregated by one of the given `ServiceInterfaces` is referenced by a `ServiceInterfaceEventMapping` in the role `sourceEvent` and one `events` aggregated by the other given `ServiceInterface` is referenced by the same `ServiceInterfaceEventMapping` in the role `targetEvent`.
 - a `trigger` aggregated by one of the given `ServiceInterfaces` is referenced by a `ServiceInterfaceTriggerMapping` in the role `sourceTrigger` and one `trigger` aggregated by the other given `ServiceInterface` is referenced by the same `ServiceInterfaceTriggerMapping` in the role `targetTrigger`.
 - a `field` aggregated by one of the given `ServiceInterfaces` is referenced by a `ServiceInterfaceFieldMapping` in the role `sourceField` and one `fields` aggregated by the other given `ServiceInterface` is referenced by the same `ServiceInterfaceFieldMapping` in the role `targetField`.
 - a `method` aggregated by one of the given `ServiceInterfaces` is referenced by a `ServiceInterfaceMethodMapping` in the role `sourceMethod` and one `methods` aggregated by the other given `ServiceInterface` is referenced by the same `ServiceInterfaceMethodMapping` in the role `targetMethod`.

]

[constr_1483] Applicability of a `ServiceInterface`*Imposition time:* IT_BefAraApiGen

[The applicability of a `ServiceInterface` shall be limited to the *AUTOSAR adaptive platform*, i.e. a `ServiceInterface` shall only be taken to type a `PortPrototype` if the latter is aggregated by an `AdaptiveApplicationSwComponentType` or by a `CompositionSwComponentType` defined in the context of an `Executable`.]

[constr_1488] Initialization of a `DataPrototype` typed by an `ApplicationAssocMapDataType`

Imposition time: IT_BefAraApiGen

[A `DataPrototype` typed by an `ApplicationAssocMapDataType` shall only be initialized by an `ApplicationAssocMapValueSpecification`.]

[constr_1489] Uniqueness of `ApplicationAssocMapValueSpecification.mapElementTuple.key`

Imposition time: IT_BefAraApiGen

[The value of all `mapElementTuple.key` elements in the context of a given `ApplicationAssocMapValueSpecification` shall be unique.]

[constr_1490] Allowed value for `Executable.category` if `ProcessToMachineMapping` references a `NonOsModuleInstantiation`

Imposition time: IT_Mani

[If a `ProcessToMachineMapping` references a `NonOsModuleInstantiation`, then the `Process` referenced in the role `ProcessToMachineMapping.process` shall only refer (in the role `Process.executable`) to an `Executable` where attribute `Executable.category` is set to `PLATFORM_LEVEL` (see [constr_1605]).]

[constr_1492] `SwComponentType` referenced in the role `Executable.rootSwComponentPrototype.applicationType`

Imposition time: IT_BefAraApiGen

[Any `SwComponentType` referenced in the role `Executable.rootSwComponentPrototype.applicationType`, or used to type a `SwComponentPrototype` nested inside the `SwComponentType` referenced in the role `Executable.rootSwComponentPrototype.applicationType` shall **only** be either a `CompositionSwComponentType` or an `AdaptiveApplicationSwComponentType`.]

[constr_1494] Initial value for `event`

Imposition time: IT_BefAraApiGen

[A `ServiceInterface.event` shall **not** have an `initValue`.]

[constr_1507] `PortInterfaceToDataTypeMapping` is only applicable to `PortInterfaces` that contain modeled data types

Imposition time: IT_BefAraApiGen

[`PortInterfaceToDataTypeMapping.portInterface` shall only refer to **any** of the following sub-classes of `PortInterface`:

- `ServiceInterface`
- `PersistencyKeyValueStorageInterface`
- `DiagnosticRoutineInterface`
- `DiagnosticDataIdentifierInterface`

- `DiagnosticDataElementInterface`
- `DiagnosticSovdContentInterface`
- `DiagnosticSovdContentElementInterface`
- `DiagnosticSovdOperationInterface`

]

[constr_1536] Definition of `SoftwareCluster` applies for a single `Machine`

Imposition time: `IT_Mani`

[Within the scope of a `SoftwareCluster`, each `Process` referenced in the role `containedProcess` shall be mapped (e.g. by means of the existence of a `ProcessToMachineMapping`) to the same `Machine`.]

[constr_1549] Value of `ProcessorCore.coreId`

Imposition time: `IT_SysDes`

[The value of `ProcessorCore.coreId` shall be unique in the context of the enclosing `Processor`.]

[constr_1550] Reference from `Process` to `ProcessDesign`

Imposition time: `IT_Mani`

[Each `ProcessDesign` shall only be referenced from a single `Process`.]

[constr_1551] Existence of `DataPrototypeInServiceInterfaceRef.dataPrototype` vs. `DataPrototypeInServiceInterfaceRef.elementInImplDatatype`

Imposition time: `IT_BefAraApiGen`

[For every given `DataPrototypeInServiceInterfaceRef`, either the aggregation `DataPrototypeInServiceInterfaceRef.dataPrototype` or `DataPrototypeInServiceInterfaceRef.elementInImplDatatype` shall exist.]

[constr_1553] Restriction for `ProcessToMachineMapping`

Imposition time: `IT_Mani`

[The following restrictions apply for the usage of `ProcessToMachineMapping`:

1. Each combination of `Process` and `Machine` shall only be referenced by one `ProcessToMachineMapping` in the role `process` or `machine`.
2. Each `Process` shall only be referenced by a single `ProcessToMachineMapping` in the role `process`.

]

[constr_1554] Restriction regarding attribute `PersistencyKeyValuePair.initValue`

Imposition time: IT_Mani

[The concrete sub-class of `ValueSpecification` aggregated in the role `PersistencyKeyValuePair.initValue` shall not (after resolving a possible redirection by means of `ConstantReference`) be a `ReferenceValueSpecification`.]

[constr_1555] Restriction applicable for `PersistencyPortPrototypeToKeyValueStorageMapping.portPrototype`

Imposition time: IT_Mani

[The reference `PersistencyPortPrototypeToKeyValueStorageMapping.portPrototype` shall only be used for a `PortPrototype` typed by a `PersistencyKeyValueStorageInterface`.]

[constr_1556] Restriction applicable for `PersistencyPortPrototypeToFileStorageMapping.portPrototype`

Imposition time: IT_Mani

[The reference `PersistencyPortPrototypeToFileStorageMapping.portPrototype` shall only be used for a `PortPrototype` typed by a `PersistencyFileStorageInterface`.]

[constr_1560] Usage of `SoftwareClusterDesign.requiredARElement`

Imposition time: IT_SubSysDes

[The reference `SoftwareClusterDesign.requiredARElement` shall not be used to refer to another `SoftwareClusterDesign` or even `SoftwareCluster`.]

[constr_1566] Usage of `SoftwareCluster.containedARElement`

Imposition time: IT_Mani

[The reference `SoftwareCluster.containedARElement` shall not be used to refer to a `SoftwareCluster` or a `SoftwareClusterDesign`.]

[constr_1570] Restriction for `UserDefinedServiceInterfaceDeployment` of category `SERVICE_INTERFACE_DEPLOYMENT_IPC`

Imposition time: IT_Mani

[An `AdaptivePlatformServiceInstance` that references a `UserDefinedServiceInterfaceDeployment` of category `SERVICE_INTERFACE_DEPLOYMENT_IPC` shall **only** be referenced by a `UserDefinedServiceInstanceToMachineMapping` in the role `serviceInstance` that in turn references a `UserDefinedCommunicationConnector`.]

[constr_1571] CppImplementationDataType is limited

Imposition time: IT_BefAraApiGen

[The usage of a `CppImplementationDataType` is limited to the context of `AdaptiveApplicationSwComponentTypes` and `CompositionSwComponentTypes` defined in the context of an `Executable`.]

[constr_1576] Existence of CppTemplateArgument.templateType vs. CppTemplateArgument allocator

Imposition time: IT_BefAraApiGen

[For any given `CppTemplateArgument`, at most one of the references

- `CppTemplateArgument.templateType` or
- `CppTemplateArgument.allocator`

]

[constr_1578] Applicable data categories

Imposition time: IT_BefAraApiGen

[

Category	Applicable to ...								Description
	<code>ApplicationArrayDataType</code>	<code>ApplicationRecordDataType</code>	<code>ApplicationPrimitiveDataType</code>	<code>ApplicationRecordElement</code>	<code>ApplicationArrayElement</code>	<code>ApplicationValueSpecification</code>	<code>StdCppImplementationDataType</code>	<code>CustomCppImplementationDataType</code>	
VALUE			x	x	x	x	x		Contains a single value. See also [TPS_MANI_03192].
TYPE_REFERENCE							x		The element is defined via reference to another data type (via <code>CppImplementationDataType.typeReference</code>).
STRUCTURE		x		x	x		x		Holds one or several further elements which can have different <code>AutosarDataTypes</code> . See also [TPS_MANI_03180].
VARIANT							x	x	Can hold values of different data types. It is similar to <code>STRUCTURE</code> except that all of its members start at the same location in memory. A <code>VARIANT</code> data prototype can contain only one of its elements at a time and represents a type-safe union. The size of the <code>VARIANT</code> is at least the size of the largest member. See also [TPS_MANI_03189].
ARRAY	x			x	x		x	x	A fixed-sized array of sub-elements of the same data type. See also [TPS_MANI_03169].
VECTOR							x	x	An array of elements of the same data type that is able to grow at run-time. See also [TPS_MANI_03174].





Category	Applicable to ...								Description
	ApplicationArrayDataType	ApplicationRecordDataType	ApplicationPrimitiveDataType	ApplicationRecordElement	ApplicationArrayElement	ApplicationValueSpecification	StdCppImplementationDataType	CustomCppImplementationDataType	
ASSOCIATIVE_MAP							x	x	An associative array of key-value pairs. See also [TPS_MANI_03183].
STRING			x	x	x	x	x		Contains a text string. See also [TPS_MANI_03178].
BOOLEAN			x	x	x	x			Contains one boolean state. Depending on the CPU direct addressing of single bits may not be available. So a byte or a word can be used to store only one logical state.

[constr_1579] **SwDataDefProps** applicable to **CppImplementationDataTypes** exclusive to the **AUTOSAR adaptive platform**

Imposition time: IT_BefAraApiGen

Attributes of SwDataDefProps	Root Element		Attribute Existence per Category							
	CppImplementationDataType	CppImplementationDataTypeElement	VALUE	TYPE_REFERENCE	STRUCTURE	VARIANT	ARRAY	VECTOR	ASSOCIATIVE_MAP	STRING
additionalNativeTypeQualifier										
annotation	x	x	*	*	*	*	*	*	*	*
baseType										
compuMethod	x	x		0..1						
dataConstr.dataConstrRule.physConstrs	x	x		d/c			d/c	d/c		
dataConstr.dataConstrRule.internalConstrs	x	x		0..1			0..1	0..1		
displayFormat	x	x	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1





Attributes of SwDataDefProps	Root Element		Attribute Existence per Category							
	CppImplementationDataType	CppImplementationDataTypeElement	VALUE	TYPE_REFERENCE	STRUCTURE	VARIANT	ARRAY	VECTOR	ASSOCIATIVE_MAP	STRING
implementationDataType										
invalidValue	x	x		0..1						0..1
stepSize										
swAddrMethod										
swAlignment										
swBitRepresentation										
swCalibrationAccess										
swCalprmAxisSet										
swComparisonVariable										
swDataDependency										
swHostVariable										
swImplPolicy										
swIntendedResolution										
swInterpolationMethod										
swIsVirtual										
swPointerTargetProps										
swPointerTargetProps.swDataDefProps										
swRecordLayout										
swRefreshTiming	x		0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1
swTextProps										
swValueBlockSize										
unit										
valueAxisDataType										

[constr_1581] Value of fileElement.fileName

Imposition time: IT_BefAraApiGen

[Within the scope of any given `PersistencyFileStorageInterface`, the value of all `fileElement.fileName` shall be unique.]

[constr_1582] `PersistencyKeyValuePair.valueDataType` shall match to `AbstractImplementationDataType` for the corresponding `PersistencyDataElement`

Imposition time: IT_Mani

[Each `PersistencyKeyValuePair.valueDataType` shall match the `AbstractImplementationDataType` that either directly or indirectly (via the applicable `DataTypeMap`) types the corresponding (based on identical values of the respective `shortName`) `PersistencyDataElement`.]

[constr_1589] Value of `file.fileName`

Imposition time: IT_Mani

[Within the scope of any given `PersistencyFileStorage`, the value of all `file.fileName` shall be unique.

A `fileName` is considered unique if there are no other `fileNames` with **exactly** the same sequence of characters¹.]

[constr_1593] Completeness of the existence of a set of `TlvDataIdDefinition.tlvArguments`

Imposition time: IT_BefAraApiGen

[If the reference `TlvDataIdDefinition.tlvArgument` exists for one argument of a given `ClientServerOperation` then further `TlvDataIdDefinition.tlvArgument` shall exist **for all** arguments of the given `ClientServerOperation` and all affected `TlvDataIdDefinition` shall be aggregated by the same `TransformationPropsToServiceInterfaceElementMapping`.]

[constr_1594] Consistent assignment of TLV data IDs to `ApplicationRecordDataType`

Imposition time: IT_BefAraApiGen

[For every `ApplicationRecordDataType` where direct members set the attribute `ApplicationRecordElement.isOptional` to the value `true` references to **all direct members** of this `ApplicationRecordDataType` shall be created on the basis of the definition of `TlvDataIdDefinition`.]

[constr_1595] Consistent assignment of TLV data IDs to `CppImplementationDataType` or `CppImplementationDataTypeElement`

Imposition time: IT_BefAraApiGen

[For every `CppImplementationDataType` of category `STRUCTURE` where direct members set the attribute `CppImplementationDataTypeElement.isOptional` to the value `true` references to **all direct members** of this `CppImplementationDataType` shall be created on the basis of the definition of `TlvDataIdDefinition`.]

¹The characters "x" and "X" are not considered as identical characters for this purpose.

[constr_1596] Scope of the uniqueness of the value of `TlvDataIdDefinition.id` for references to `ArgumentDataPrototype`*Imposition time:* IT_BefAraApiGen

[For all `TlvDataIdDefinition` that are referencing `ArgumentDataPrototypes` of a given `ClientServerOperation` in the role `tlvArgument`, the attribute `TlvDataIdDefinition.id` **shall exist and have a unique value per communication direction**, i.e. in the context of the collection of all

- `arguments` where attribute `direction` is set to either `in` or `inout`
- `arguments` where attribute `direction` is set to either `out` or `inout`
- `arguments` where attribute `direction` is set to `inout` (if the `method` **only** has `arguments` where attribute `direction` is set to `inout`)

of the respective enclosing `ClientServerOperation`.]

[constr_1597] Scope of the uniqueness of the value of `TlvDataIdDefinition.id` for references to `ApplicationRecordElement`*Imposition time:* IT_BefAraApiGen

[For all `TlvDataIdDefinition` that are referencing `ApplicationRecordElements` of a given `ApplicationDataType` in the role `tlvRecordElement` the attribute `TlvDataIdDefinition.id` **shall exist and have a unique value** in the context of respective enclosing `ApplicationRecordDataType`.]

[constr_1598] Scope of the uniqueness of the value of `TlvDataIdDefinition.id` for references to `CppImplementationDataTypeElement`*Imposition time:* IT_BefAraApiGen

[For all `TlvDataIdDefinition` that are referencing `CppImplementationDataTypeElements` of a given `CppImplementationDataType/CppImplementationDataTypeElement` in the role `tlvImplementationDataTypeElement` the attribute `TlvDataIdDefinition.id` **shall exist and have a unique value** in the context of respective enclosing `CppImplementationDataType` or `CppImplementationDataTypeElement`.]

[constr_1599] `TlvDataIdDefinition` referencing `ArgumentDataPrototype`*Imposition time:* IT_BefAraApiGen

[Each `ArgumentDataPrototype` shall be referenced **at most once** in the role `tlvArgument` in the context of the same `TransformationPropsToServiceInterfaceElementMapping`.]

[constr_1600] TlvDataIdDefinition referencing ApplicationRecordElement

Imposition time: IT_BefAraApiGen

[Each `ApplicationRecordElement` shall be referenced **at most once** in the role `tlvRecordElement` in the context of the same `TransformationPropsToServiceInterfaceElementMapping`.]

[constr_1601] TlvDataIdDefinition referencing CppImplementationDataTypeElement

Imposition time: IT_BefAraApiGen

[Each `CppImplementationDataTypeElement` shall be referenced **at most once** in the role `tlvImplementationDataTypeElement` in the context of the same `TransformationPropsToServiceInterfaceElementMapping`.]

[constr_1603] Completeness of the existence of a set of TlvDataIdDefinition.tlvRecordElements

Imposition time: IT_BefAraApiGen

[If the reference `TlvDataIdDefinition.tlvRecordElement` exists for one element of a given `ApplicationRecordDataType` then further `TlvDataIdDefinition.tlvRecordElement` shall exist **for all** elements of the given `ApplicationRecordDataType` and all affected `TlvDataIdDefinition` shall be aggregated by the same `TransformationPropsToServiceInterfaceElementMapping`.]

[constr_1604] Completeness of the existence of a set of TlvDataIdDefinition.tlvImplementationDataTypeElements

Imposition time: IT_BefAraApiGen

[If the reference `TlvDataIdDefinition.tlvImplementationDataTypeElement` exists for one subElement of a given `CppImplementationDataType` or `CppImplementationDataTypeElement` then further `TlvDataIdDefinition.tlvImplementationDataTypeElement` shall exist **for all** subElements of the given `CppImplementationDataType` or `CppImplementationDataTypeElement` and all affected `TlvDataIdDefinition` shall be aggregated by the same `TlvDataIdDefinitionSet`.]

[constr_1605] Standardized values of attribute Executable.category

Imposition time: IT_BefAraApiGen

[The following values for attribute `Executable.category` are standardized by AUTOSAR:

- `PLATFORM_LEVEL`: the `Executable` represents software on the platform level (i.e. conceptually located *on the level of* the middleware).
- `APPLICATION_LEVEL`: the `Executable` represents software on the application level (i.e. conceptually located *above* the middleware).

]

[constr_1606] Processes with mutual ExecutionDependency*Imposition time:* IT_Mani

[A `Process.stateDependentStartupConfig.executionDependency` shall not refer to any `ModeDeclaration` owned by a second `Process` that in turn refers via `stateDependentStartupConfig.executionDependency` to any `ModeDeclaration` owned by the first `Process`.]

[constr_1613] File name of matching pairs of PersistencyFileElement and PersistencyFile*Imposition time:* IT_Mani

[The value of attributes `PersistencyFileElement.fileName` and `PersistencyFile.fileName` shall be identical for matching pairs (as identified by the application of [TPS_MANI_01187]) of `PersistencyFileStorage` and `PersistencyFile`.]

[constr_1618] Ability to shut down*Imposition time:* IT_Mani

[In the context of one `Machine`, at least one `Process` shall have a `stateDependentStartupConfig.functionGroupState` that has the `shortName` Shut-down.]

[constr_1619] Ability to restart*Imposition time:* IT_Mani

[In the context of one `Machine`, at least one `Process` shall have a `stateDependentStartupConfig.functionGroupState` that has the `shortName` Restart.]

[constr_1625] Existence of reference ApApplicationError.errorDomain*Imposition time:* IT_BefAraApiGen

[For each `ApApplicationError`, the reference `errorDomain` shall exist.

In other words, the association of an `ApApplicationError` with a corresponding `ApApplicationErrorDomain` is mandatory.]

[constr_1628] Definition of static length field sizes in case of TLV usage*Imposition time:* IT_BefAraApiGen

[If the aggregation `tlvDataIdDefinition` exists for a given `TransformationPropsToServiceInterfaceElementMapping` then attributes

- `sizeofArrayLengthField`,
- `sizeofStringLengthField`,
- `sizeofStructLengthField`, and
- `sizeofUnionLengthField`

]

[constr_1629] Identical sizes of length fields in case of TLV usage*Imposition time:* IT_BefAraApiGen

[If the aggregation `tlvDataIdDefinition` exists for a given `TransformationPropsToServiceInterfaceElementMapping` then attributes

- `sizeofArrayLengthField`,
- `sizeofStringLengthField`,
- `sizeofStructLengthField`, and
- `sizeofUnionLengthField`

]

[constr_1630] No definition of length field sizes on `DataPrototype` level in case of TLV usage*Imposition time:* IT_BefAraApiGen

[If the reference in the role `tlvDataIdDefinition` exists for a given `TransformationPropsToServiceInterfaceElementMapping` then attributes

- `sizeofArrayLengthField`,
- `sizeofStringLengthField`,
- `sizeofStructLengthField`, and
- `sizeofUnionLengthField`

shall not be individually defined on the level of a `DataPrototype` (i.e. by means of the reference `SomeipDataPrototypeTransformationProps.someipTransformationProps`) but only on the level of a `ServiceInterface` (i.e. by means of the reference `TransformationPropsToServiceInterfaceElementMapping.transformationProps`).]

[constr_1658] Number of `DiagnosticTroubleCodeUdsToClearConditionGroupMapping` elements per `DiagnosticTroubleCodeUds`*Imposition time:* IT_DiagDes

[The mapping element `DiagnosticTroubleCodeUdsToClearConditionGroupMapping` shall be created no more than once per `DiagnosticTroubleCodeUds`.

If several `DiagnosticTroubleCodeUdsToClearConditionGroupMapping` elements referring to the same `DiagnosticTroubleCodeUds` are defined, then the Clear Condition Group mapping shall be regarded as defective.]

[constr_1659] Restriction for the usage of `CppImplementationDataTypeElementQualifier.inplace`*Imposition time:* IT_BefAraApiGen

[The attribute `CppImplementationDataTypeElementQualifier.inplace` shall only exist if the target referenced in the role `CppImplementationDataTypeElementQualifier.typeReference` is an `StdCppImplementationDataType` that has the attribute `category` set to either of the values

- `ARRAY`
- `VECTOR`
- `ASSOCIATIVE_MAP`
- `VARIANT`
- `STRUCTURE`
- `STRING`
- `TYPE_REFERENCE`, if the `CppImplementationDataType` refers to a `CompuMethod` of `category` `TEXTTABLE`

]

[constr_1660] Restriction for the usage of `CppTemplateArgument.inplace`*Imposition time:* IT_BefAraApiGen

[The attribute `CppTemplateArgument.inplace` shall only exist if the target referenced in the role `CppTemplateArgument.templateType` is an `StdCppImplementationDataType` that has the attribute `category` set to either of the values

- `ARRAY`
- `VECTOR`
- `ASSOCIATIVE_MAP`
- `VARIANT`
- `STRUCTURE`
- `STRING`

]

[constr_1661] Multiplicity of `OsModuleInstantiation.resourceGroup`*Imposition time:* IT_Mani

[Any given `OsModuleInstantiation` shall always define at least one `resourceGroup`.]

[constr_1664] Unique **ApApplicationError.shortName**

Imposition time: IT_BefAraApiGen

[Within the set of all **ApApplicationErrors** that reference a given **ApApplicationErrorDomain** in the role **errorDomain** the attribute **ApApplicationError.shortName** shall have a unique value.]

[constr_1665] Unique **ApApplicationError.errorCode**

Imposition time: IT_BefAraApiGen

[Within the set of all **ApApplicationErrors** that reference a given **ApApplicationErrorDomain** in the role **errorDomain** the attribute **ApApplicationError.errorCode** shall have a unique value.]

[constr_1666] References from **PersistencyPortPrototypeToKeyValueStorageMapping** to **PersistencyKeyValueStorage**

Imposition time: IT_Mani

[Each **PersistencyKeyValueStorage** shall only be referenced by at most one **PersistencyPortPrototypeToKeyValueStorageMapping**.]

[constr_1667] References from **PersistencyPortPrototypeToFileStorageMapping** to **PersistencyFileStorage**

Imposition time: IT_Mani

[Each **PersistencyFileStorage** shall only be referenced by at most one **PersistencyPortPrototypeToFileStorageMapping**.]

[constr_1668] Allowed combinations of **PersistencyRedundancyChecksum.length** and **algorithmFamily**

Imposition time: IT_BefAraApiGen

[

	8	16	32	64
CRC_J1850	X			
CRC_CCITT_FALSE		X		
CRC_ETHERNET			X	
CRC_0x42F0E1EBA9EA3693				X
CRC_8H2F	X			
CRC_16ARC		X		
CRC_32P4			X	

]

[constr_1673] Existence of attributes **hasGetter**, **hasSetter**, and **hasNotifier**

Imposition time: IT_BefAraApiGen

[For any given **Field**, all of the attributes

- **hasGetter**

- `hasSetter`
- `hasNotifier`

shall exist and at least one of the attributes shall be set to `true`.]

[constr_1675] Existence of attribute `ApSomeipTransformationProps.stringEncoding`

Imposition time: `IT_BefAraApiGen`

[The attribute `TransformationPropsToServiceInterfaceElementMapping.transformationProps.stringEncoding` shall only exist for a `event`, `methodCall`, `methodReturn`, or `field` (referenced by the same `TransformationPropsToServiceInterfaceElementMapping`) that consists of or contains a `DataPrototype` typed by a `CppImplementationDataType` of category `STRING`.]

[constr_1676] Consistency of references `shallRunOn` and `shallNotRunOn`

Imposition time: `IT_Mani`

[Within the context of one `ProcessToMachineMapping`, all `ProcessorCores` referenced in the role `shallRunOn` or `shallNotRunOn` shall be aggregated by the same `Processor`.]

[constr_1677] Mutual exclusive existence of references `shallRunOn` and `shallNotRunOn`

Imposition time: `IT_Mani`

[For any given `ProcessToMachineMapping`, either the reference in the role `shallRunOn` or the reference in the role `shallNotRunOn` may exist.]

[constr_1678] Allowed values for attribute `ApSomeipTransformationProps.stringEncoding`

Imposition time: `IT_BefAraApiGen`

[Imposed by technical restrictions in the definition of the SOME/IP message format [1, PRS SOME/IP Protocol], only two possible values of attribute `ApSomeipTransformationProps.stringEncoding` are allowed:

- UTF-8: UCS Transformation Format 8
- UTF-16: Character encoding for Unicode *code points* based on 16 bit *code units* [2, ISO 10646]

]

[constr_1688] `StateDependentStartupConfig` shall only refer to `Function Group States` of the same `Function Group`

Imposition time: `IT_Mani`

[For all `StateDependentStartupConfigs` aggregated in the role `Process.stateDependentStartupConfig`, references in the role `functionGroupState` to `ModeDeclaration` shall only refer to `ModeDeclarations` aggregated by the same

`ModeDeclarationGroup` in the context of the same `ModeDeclarationGroupPrototype` (that represents the actual `Function Group`).]

[constr_1689] Modeling of a startup dependency between different **Processes**

Imposition time: IT_Mani

[The existence of attribute `Process.stateDependentStartupConfig.executionDependency` is only valid if

- the owner of the `stateDependentStartupConfig.executionDependency` (in other words: the **referencing Process**) and
- the owner of the `ModeDeclarationGroupPrototype` referenced in the role `contextModeDeclarationGroupPrototype` within the reference `stateDependentStartupConfig.executionDependency.processState` (i.e. the **referenced Process**)

refer to the **identical Function Group State** formalized as `ModeDeclaration`.]

[constr_1691] `UcmModuleInstantiation.identifier` shall be unique

Imposition time: IT_Mani

[The value of attribute `UcmModuleInstantiation.identifier` shall be unique for each `Machine` in a given vehicle.]

[constr_1692] Value of `schedulingPriority`

Imposition time: IT_Mani

[The value of attribute `StartupConfig.schedulingPriority` shall be set to a positive integer value.]

[constr_1693] Relation of **Executable**, **ProcessDesign**, and **Process**

Imposition time: IT_SysDes

[Any `Executable` that is referenced by a `ProcessDesign` shall also be referenced by every `Process` that references the `ProcessDesign`.]

[constr_1695] Semantics of a **Grant** depends on the existence of `CmModuleInstantiation`

Status: DRAFT

Imposition time: IT_Mani

[The existence of `Grants` shall only be enforced if in the context of the enclosing `Machine` an `CmModuleInstantiation` has been defined and is referencing the `Grant`.]

[constr_1696] ClientServerOperation aggregated by DiagnosticRoutineInterface

Imposition time: IT_BefAraApiGen

[Any ClientServerOperation aggregated by a DiagnosticRoutineInterface shall not define the following attributes:

- fireAndForget
- possibleApError
- possibleApErrorSet

]

[constr_1697] Restriction for ClientServerOperation aggregated by a DiagnosticDataIdentifierInterface

Imposition time: IT_BefAraApiGen

[If meta-class DiagnosticDataIdentifierInterface aggregates two ClientServerOperations, then

- The two ClientServerOperations shall have the same number of arguments.
- The arguments on the n^{th} position in the collection of arguments shall have identical properties, except the direction. In particular, the following conditions shall be fulfilled with respect to attribute direction:
 - Any ArgumentDataPrototype aggregated by a ClientServerOperation that is itself aggregated in the role DiagnosticDataIdentifierInterface.read shall set attribute direction to out.
 - Any ArgumentDataPrototype aggregated by a ClientServerOperation that is itself aggregated in the role DiagnosticDataIdentifierInterface.write shall set attribute direction to in.

]

[constr_1708] Combination of CppImplementationDataTypeElement.isOptional and CppImplementationDataTypeElementQualifier.inplace

Imposition time: IT_BefAraApiGen

[If a CppImplementationDataTypeElement is typed by a CppImplementationDataType of category STRUCTURE then the combination of attribute CppImplementationDataTypeElement.isOptional set to true and CppImplementationDataTypeElement.typeReference.inplace set to true is not allowed.]

[constr_1710] Consistency of values of attributes `PersistencyInterface.redundancy` and `PersistencyRedundancyHandling.scope`*Imposition time:* IT_Mani

[If attribute `PersistencyInterface.redundancy` is set to value `PersistencyRedundancyEnum.redundantPerElement` then attribute `PersistencyRedundancyHandling.scope` shall be set to `PersistencyRedundancyHandlingScopeEnum.persistencyRedundancyHandlingScopeElement` for at least one `PersistencyRedundancyHandling` aggregated by the corresponding `PersistencyDeployment`.]

[constr_1723] `ProvidedSomeipServiceInstance` shall be unique in respect of `serviceInstanceId`, `serviceInterfaceId` and `majorVersion` on a VLAN*Imposition time:* IT_Mani

[On a VLAN, each `ProvidedSomeipServiceInstance` shall have a different `serviceInstanceId`, `serviceInterfaceId` and `majorVersion` value combination.

In other words, no two `ProvidedSomeipServiceInstances` shall have the same `serviceInstanceId`, `serviceInterfaceId` and `majorVersion` value combination during runtime on the same VLAN.]

[constr_1727] Qualified combinations of `PortPrototypes` and `PhmSupervisedEntityInterface` on application software level*Imposition time:* IT_BefAraApiGen

[Within the context of an `Executable` of category `APPLICATION_LEVEL` the usage of `PhmSupervisedEntityInterface` is **only** supported for an `RPortPrototype`.]

[constr_1729] Qualified combinations of `PortPrototypes` and `PhmSupervisionRecoveryNotificationInterface` on State Management software level*Imposition time:* IT_BefAraApiGen

[Within the context of an `Executable` of category `APPLICATION_LEVEL` the usage of `PhmSupervisionRecoveryNotificationInterface` is **only** supported for a `PPortPrototype`.]

[constr_1731] Value of `UcmDescription.identifier` in the scope of a `VehiclePackage`*Imposition time:* IT_Mani

[Within the scope of any given `VehiclePackage`, no two `UcmDescriptions` shall define the same value of attribute `identifier`.]

[constr_1736] Multiplicity of reference `LogicalSupervision.initialCheckpoint`*Imposition time:* IT_Mani

[At the time of target-configuration of a `LogicalSupervision`, at least one reference to meta-class `SupervisionCheckpoint` in the role `initialCheckpoint` shall exist.]

[constr_1737] Multiplicity of reference `LogicalSupervision.finalCheckpoint`*Imposition time:* IT_Mani

[At the time of target-configuration of a `LogicalSupervision`, at least one reference to meta-class `SupervisionCheckpoint` in the role `finalCheckpoint` shall exist.]

[constr_1740] Multiplicity of reference `LogicalSupervision.transition`*Imposition time:* IT_Mani

[At the time of target-configuration of a `LogicalSupervision`, at least one reference to meta-class `CheckpointTransition` in the role `LogicalSupervision.transition` shall exist.]

[constr_1742] Multiplicity of reference `SupervisionCheckpoint.phmCheckpoint`*Imposition time:* IT_Mani

[At the time of target-configuration of a `SupervisionCheckpoint`, one reference to meta-class `PhmCheckpoint` in the role `phmCheckpoint` shall exist.]

[constr_1743] `CppImplementationDataType.headerFile` vs. `CppImplementationDataType.typeEmitter`*Imposition time:* IT_BefAraApiGen

[The two attributes `CppImplementationDataType.headerFile` and `CppImplementationDataType.typeEmitter` shall always be used mutually exclusive.

In other words, a subclass of `CppImplementationDataType` shall either use `headerFile` or `typeEmitter`. The simultaneous usage of both attributes is not supported.]

[constr_1746] Mutual exclusive existence of `PersistencyInterface.redundancy` and `PersistencyInterface.redundancyHandling`*Imposition time:* IT_BefAraApiGen

[For each `PersistencyInterface`, either the attribute `redundancy` or the aggregation of `PersistencyRedundancyHandling` in the role `redundancyHandling` may exist.]

[constr_1747] Completeness of the **SoftwareCluster.version**

Imposition time: IT_Mani

[The **SoftwareCluster.version** shall contain all the following parts:

- Major version
- Minor version
- Patch version
- Additional labels for pre-release version and build metadata

]

[constr_1748] Existence of references **TlvDataIdDefinition.tlvArgument**, **TlvDataIdDefinition.tlvRecordElement**, and **TlvDataIdDefinition.tlvImplementationDataTypeElement**

Imposition time: IT_BefAraApiGen

[For each **TlvDataIdDefinition**, only one out of the following references shall exist:

- reference to an **ArgumentDataPrototype** in the role **tlvArgument**
- reference to an **ApplicationRecordElement** in the role **tlvRecordElement**
- reference to an **AbstractImplementationDataTypeElement** in the role **tlvImplementationDataTypeElement**.

]

[constr_1751] Value of **PersistencyRedundancyMOutOfN.m**

Imposition time: IT_BefAraApiGen

[The value of attribute **PersistencyRedundancyMOutOfN.m** shall be set at least to 1 and at most to the value of attribute **PersistencyRedundancyMOutOfN.n**, i.e. the allowed interval is [1..**PersistencyRedundancyMOutOfN.n**].]

[constr_1764] Counterpart of **PhmCheckpoint**

Imposition time: IT_Mani

[Each **PhmCheckpoint** shall be referenced once and only once in the role **targetPhmCheckpoint** by a **PhmCheckpointInExecutableInstanceRef** with the same **Executable** and chain of **contextComponentPrototype** and **contextRPortPrototype** that is aggregated by a **SupervisionCheckpoint** in combination with a specific **Process**. This reference shall exist.]

[constr_1769] Existence of **ProcessArgument.argument**

Imposition time: IT_Mani

[For each **ProcessArgument**, attribute **argument** shall exist.]

[constr_1770] Value of `ProvidedSomeipServiceInstance.serviceInstanceId`*Imposition time:* IT_Mani

[For each `ProvidedSomeipServiceInstance.serviceInstanceId`, the value shall be in the range 0..65534.]

[constr_1784] Restriction for the reference to `UploadableExclusivePackageElement`*Imposition time:* IT_Mani

[A reference to an `UploadableExclusivePackageElement` shall not cross the boundary of the enclosing `SoftwareCluster`, i.e. the target `UploadableExclusivePackageElement` of such a reference shall not be located in a different `SoftwareCluster` than the owner of the reference.]

[constr_1785] Restriction regarding the reference into another `SoftwareCluster`*Imposition time:* IT_Mani

[A reference from an element in one `SoftwareCluster` to an element located in another `SoftwareCluster` shall only exist if the `design` of the `SoftwareCluster` that owns the referenced element is referenced by a `SoftwareClusterDependencyCompareCondition` in the context of the mentioned `SoftwareClusterDependencyFormula` in the role `part.softwareClusterDesign`.

[**constr_1784**] applies.]

[constr_1786] Restriction to use `functionGroup` in terms of `SoftwareCluster`*Imposition time:* IT_Mani

[Each `functionGroup` shall only be referenced in the role `claimedFunctionGroup` by **at most one** `SoftwareCluster`.]

[constr_1787] Restricted use of Function Groups in the context of a `SoftwareCluster`*Imposition time:* IT_Mani

[All `Processes` referenced by a `SoftwareCluster` in the role `containedProcess` shall only aggregate `StateDependentStartupConfigs` where the reference `functionGroupState` refers to a `ModeDeclarationGroupPrototype` (as context) that is also referenced by the same `SoftwareCluster` in the role `claimedFunctionGroup`.]

[constr_1788] Restriction to `SoftwareCluster` of `category` `PLATFORM_CORE`*Imposition time:* IT_Mani

[On each `Machine`, exactly one `SoftwareCluster` of `category` `PLATFORM_CORE` shall be deployed.]

[constr_3287] Mandatory information of a `ProvidedSomeipServiceInstance`

Imposition time: IT_Mani

[The `ProvidedSomeipServiceInstance` shall always define the `serviceInstanceId`.]

[constr_3288] IP configuration restriction for `unicastNetworkEndpoints`

Imposition time: IT_Mani

[A `NetworkEndpoint` that is referenced by a `EthernetCommunicationConnector` in the role `unicastNetworkEndpoint` shall have either

- one `Ipv4Configuration` or
- one `Ipv6Configuration`

as `networkEndpointAddress` that is defined in the unicast IP range according to the rules defined in [TPS_MANI_03005] and [TPS_MANI_03006].]

[constr_3290] Transport Protocol attributes defined for a `ProvidedSomeipServiceInstance`

Imposition time: IT_Mani

[Each `SomeipServiceInstanceToMachineMapping` that is defined for a `ProvidedSomeipServiceInstance` shall define either

- a `udpPort` or
- a `tcpPort` or
- a `udpPort` and a `tcpPort`.

]

[constr_3300] Allowed `ServiceMethodDeployment.method` references

Imposition time: IT_Mani

[The `ClientServerOperation` that is referenced by `ServiceMethodDeployment` in the role `method` shall be defined in the context of a `ServiceInterface` that is referenced by the `ServiceInterfaceDeployment` in the role `serviceInterface` that contains the `ServiceMethodDeployment`.]

[constr_3301] Allowed `ServiceEventDeployment.event` references

Imposition time: IT_Mani

[The `VariableDataPrototype` that is referenced by `ServiceEventDeployment` in the role `event` shall be defined in the context of a `ServiceInterface` that is referenced by the `ServiceInterfaceDeployment` in the role `serviceInterface` that contains the `ServiceEventDeployment`.]

[constr_3302] Allowed `ServiceFieldDeployment.field` references*Imposition time:* IT_Mani

[The `Field` that is referenced by `ServiceFieldDeployment` in the role `field` shall be defined in the context of a `ServiceInterface` that is referenced by the `ServiceInterfaceDeployment` in the role `serviceInterface` that contains the `ServiceFieldDeployment`.]

[constr_3304] Value of attribute `SomeipEventGroup.eventGroupId` shall be unique*Imposition time:* IT_Mani

[The value of attribute `eventGroupId` shall be unique in the context of the enclosing `SomeipServiceInterfaceDeployment`.]

[constr_3305] Value of attribute `SomeipEventDeployment.eventId` shall be unique*Imposition time:* IT_Mani

[The value of `eventId` shall be unique in the context of the enclosing `SomeipServiceInterfaceDeployment`, unless `SomeipEventDeployment.serializer` is set to `SerializationTechnologyEnum.signalBased`.]

[constr_3306] Value of attribute `methodId` shall be unique per `SomeipServiceInterfaceDeployment`*Imposition time:* IT_Mani

[The value of `methodId` shall be unique in the context of the enclosing `SomeipServiceInterfaceDeployment`.]

[constr_3308] `SomeipEventDeployment.transportProtocol` setting to `tcp` and the impact on `ProvidedSomeipServiceInstances`*Imposition time:* IT_Mani

[If `SomeipEventDeployment.transportProtocol` is set to `tcp` then each `ProvidedSomeipServiceInstance` that refers the `SomeipServiceInterfaceDeployment` in the role `serviceInterfaceDeployment` shall only be mapped to a `MachineDesign` with a `SomeipServiceInstanceToMachineMapping` with a configured `tcpPort`.]

[constr_3309] `SomeipMethodDeployment.transportProtocol` setting to `udp` and the impact on `ProvidedSomeipServiceInstances`*Imposition time:* IT_Mani

[If `SomeipMethodDeployment.transportProtocol` is set to `udp` then each `ProvidedSomeipServiceInstance` that refers the `SomeipServiceInterfaceDeployment` in the role `serviceInterfaceDeployment` shall only be mapped to a `MachineDesign` with a `SomeipServiceInstanceToMachineMapping` with a configured `udpPort`.]

[constr_3310] SomeipMethodDeployment.transportProtocol setting to tcp and the impact on ProvidedSomeipServiceInstances*Imposition time:* IT_Mani

[If `SomeipMethodDeployment.transportProtocol` is set to `tcp` then each `ProvidedSomeipServiceInstance` that refers the `SomeipServiceInterfaceDeployment` in the role `serviceInterfaceDeployment` shall only be mapped to a `MachineDesign` with a `SomeipServiceInstanceToMachineMapping` with a configured `tcpPort`.]

[constr_3320] Aggregation of CommunicationConnector by MachineDesign*Imposition time:* IT_MachDes

[Meta-Class `MachineDesign` shall only aggregate `EthernetCommunicationConnectors` in the role `communicationConnector`. No other subclass of `CommunicationConnector` shall appear in this aggregation.]

[constr_3349] Usage of ApplicationAssocMapDataType is limited*Imposition time:* IT_BefAraApiGen

[The usage of an `ApplicationAssocMapDataType` is limited to the context of `AdaptiveApplicationSwComponentTypes` and `CompositionSwComponentTypes` defined in the context of an `Executable`, i.e. such a data type shall not be used on the *AUTOSAR classic platform*.]

[constr_3351] SOME/IP segmentation allowed for udp SomeipEventDeployments*Imposition time:* IT_Mani

[Attribute `SomeipEventDeployment.maximumSegmentLength` shall only be used if the value of attribute `SomeipEventDeployment.transportProtocol` is set to `udp`.]

[constr_3352] SOME/IP segmentation allowed for udp SomeipMethodDeployments*Imposition time:* IT_Mani

[`SomeipMethodDeployment.maximumSegmentLengthRequest` and `SomeipMethodDeployment.maximumSegmentLengthResponse` shall only be used if `SomeipMethodDeployment.transportProtocol` is set to `udp`.]

[constr_3353] Restriction in usage of ApSomeipTransformationProps.sizeOfArrayLengthField*Imposition time:* IT_BefAraApiGen

[The value of the attribute `sizeOfArrayLengthField` shall be either 0, 1, 2 or 4.]

[constr_3354] Restriction in usage of `ApSomeipTransformationProps.sizeOfStructLengthField`*Imposition time:* IT_BefAraApiGen[The value of the attribute `sizeOfStructLengthField` shall be either 0, 1, 2 or 4.]**[constr_3355] Restriction in usage of `ApSomeipTransformationProps.sizeOfUnionLengthField`***Imposition time:* IT_BefAraApiGen[The value of the attribute `sizeOfUnionLengthField` shall be either 0, 1, 2 or 4.]**[constr_3356] Restriction in usage of `ApSomeipTransformationProps.alignment`***Imposition time:* IT_BefAraApiGen[The value of the attribute `alignment` shall be either 8, 16, 32, 64, 128, or 256.]**[constr_3357] Restriction in usage of `ApSomeipTransformationProps.sizeOfUnionTypeSelectorField`***Imposition time:* IT_BefAraApiGen[The value of the attribute `sizeOfUnionTypeSelectorField` shall be either 1, 2 or 4.]**[constr_3359] `RPortPrototypeProps` are related only to `RPortPrototypes`***Imposition time:* IT_BefAraApiGen[The `RPortPrototypeProps` shall be aggregated only by a `RPortPrototype` in the role `portPrototypeProps`.]**[constr_3361] Selective definition of serialization settings***Imposition time:* IT_BefAraApiGen[If a `SomeipDataPrototypeTransformationProps` is defined for a composite `DataPrototype` of an element of a `ServiceInterface` (`method`, `field`, `event`) and if the reference `someipTransformationProps` exists then `SomeipDataPrototypeTransformationProps` that define the reference `someipTransformationProps` shall be defined for all other composite `DataPrototypes` of the `ServiceInterface` element as well.]**[constr_3362] `SomeipEventDeployments` aggregated by a `SomeipFieldDeployment`***Imposition time:* IT_Mani[A `SomeipEventDeployment` that is aggregated by a `SomeipFieldDeployment` in the role `notifier` shall not reference a `VariableDataPrototype` in the role `event`.]

[constr_3363] SomeipMethodDeployments aggregated by a SomeipFieldDeployment*Imposition time:* IT_Mani

[A `SomeipMethodDeployment` that is aggregated by a `SomeipFieldDeployment` in the role `get` or `set` shall not reference a `ClientServerOperation` in the role `method`.]

[constr_3367] FieldMapping.notifierDataElement reference*Imposition time:* IT_SysDes

[The `FieldMapping` shall only contain the `notifierDataElement` reference if the `hasNotifier` attribute in the referenced `field` is set to true.]

[constr_3368] FieldMapping.getterOperation reference*Imposition time:* IT_SysDes

[The `FieldMapping` shall only contain the `getterOperation` reference if the `has-Getter` attribute in the referenced `field` is set to true.]

[constr_3369] FieldMapping.setterOperation reference*Imposition time:* IT_SysDes

[The `FieldMapping` shall only contain the `setterOperation` reference if the `has-Setter` attribute in the referenced `field` is set to true.]

[constr_3370] InterfaceMapping shall map all elements of a single ServiceInterface*Imposition time:* IT_SysDes

[The mappings that are included in an `InterfaceMapping` shall map all elements of a single `ServiceInterface` (i.e. `fields`, `events`, `methods`) to `PortInterface` elements of the classic platform.]

[constr_3371] Mutually exclusive existence of FireAndForgetMethodMapping.dataElement reference and FireAndForgetMethodMapping.trigger reference*Imposition time:* IT_SysDes

[A `FireAndForgetMethodMapping` shall never reference a `dataElement` and a `trigger` at the same time.]

[constr_3372] Restriction in usage of ApSomeipTransformationProps.sizeOfStringLengthField*Imposition time:* IT_BefAraApiGen

[The value of the attribute `sizeOfStringLengthField` shall be either 0, 1, 2 or 4.]

[constr_3374] method with attribute fireAndForget set to true shall not have any inout or out arguments

Imposition time: IT_BefAraApiGen

[A `method` that has the value of attribute `fireAndForget` set to `true` is not allowed to have any `arguments` with `direction` `inout` or `out`.]

[constr_3375] method with attribute fireAndForget set to true shall not reference an `ApApplicationError`

Imposition time: IT_BefAraApiGen

[A `method` that has the value of attribute `fireAndForget` set to `true` is not allowed to reference

- an `ApApplicationError` in role `possibleApError` and/or
- an `ApApplicationErrorSet` in the role `possibleApErrorSet`.

]

[constr_3376] `FireAndForgetMethodMapping` shall reference only fire and forget methods

Imposition time: IT_SysDes

[A `FireAndForgetMethodMapping` is only allowed to reference a `ClientServerOperation` in role `method` for which the value of attribute `method.fireAndForget` is set to `true`.]

[constr_3391] `ServiceInterfaceElementSecureComConfig` references to `ServiceInterfaceDeployment` elements

Imposition time: IT_Mani

[`ServiceInterfaceElementSecureComConfig` element shall be defined for exactly one `ServiceInterface` element and shall therefore contain only one single reference to an element defined in the scope of a `ServiceInterfaceDeployment`.]

[constr_3392] `ServiceInterfaceElementSecureComConfig.dataId` and `ServiceInterfaceElementSecureComConfig.freshnessValueId` are mandatory in case of SecOC communication

Imposition time: IT_Mani

[The attributes `ServiceInterfaceElementSecureComConfig.dataId` and `ServiceInterfaceElementSecureComConfig.freshnessValueId` are mandatory in case of SecOC communication.]

[constr_3393] Usage of `shallRunOn` and `shallNotRunOn` references

Imposition time: IT_Mani

[The `ProcessorCore` that is referenced by a `ProcessToMachineMapping` in the role `shallRunOn` or `shallNotRunOn` shall be aggregated by the `Machine` that is referenced in the role `machine` by the same `ProcessToMachineMapping`.]

[constr_3395] TransformationPropsToServiceInterfaceElementMapping is restricted to one single ServiceInterface*Imposition time:* IT_BefAraApiGen

[All `ServiceInterface` elements that are referenced by the `TransformationPropsToServiceInterfaceElementMapping` in the role `event`, `trigger`, `methodCall`, `methodReturn`, or `field` shall be aggregated by the same `ServiceInterface` in the role `event`, `trigger`, `method` or `field`.]

[constr_3396] Number of Process.stateDependentStartupConfig that refer to the same functionGroupState*Imposition time:* IT_Mani

[Within the context of a given `Process`, no two `StateDependentStartupConfigs` shall refer to the same `ModeDeclaration` in the role `functionGroupState`.]

[constr_3408] Value range of SomeipEventDeployment.eventId*Imposition time:* IT_Mani

[The value of `eventId` shall be in the range of 0..32767.]

[constr_3409] Value range of SomeipMethodDeployment.methodId*Imposition time:* IT_Mani

[The value of `methodId` shall be in the range of 0..32767.]

[constr_3410] Value range of SomeipServiceInterfaceDeployment.serviceInterfaceId*Imposition time:* IT_Mani

[The value of `serviceInterfaceId` shall be in the range of 0..65535.]

[constr_3413] StateDependentStartupConfig of a Process is mapped to exactly one ResourceGroup*Imposition time:* IT_Mani

[Each `StateDependentStartupConfig` of a `Process` shall be assigned to exactly one `ResourceGroup` that is defined in the Machine Manifest.]

[constr_3414] Allowed usage of `PlatformModuleEthernetEndpointConfiguration` attributes that are allowed to be used to configure the network communication in the different platform modules

Status: DRAFT

Imposition time: IT_Mani

PlatformModuleEthernetEndpointConfiguration attributes	Element		
	Usage in DoIpInstantiation	Usage in DltLogSink	Usage in IdsmModuleInstantiation
tcpPort	Optional	Optional	Optional
udpPort	Optional	Optional	Optional
communicationConnector	Mandatory	Mandatory	Mandatory
remoteConfig	N/A	Optional	Mandatory
secureComPropsForUdp	N/A	Optional	Optional
secureComPropsForTcp	Optional	Optional	Optional

[constr_3415] Value range of `ProvidedSomeipServiceInstance.loadBalancingPriority`

Imposition time: IT_Mani

[The value of attribute `ProvidedSomeipServiceInstance.loadBalancingPriority` shall be in the range of 0..65535.]

[constr_3416] Value range of `ProvidedSomeipServiceInstance.loadBalancingWeight`

Imposition time: IT_Mani

[The value of attribute `ProvidedSomeipServiceInstance.loadBalancingWeight` shall be in the range of 0..65535.]

[constr_3417] `UserDefinedEventDeployments` aggregated by a `UserDefinedFieldDeployment`

Imposition time: IT_Mani

[A `UserDefinedEventDeployment` that is aggregated by a `UserDefinedFieldDeployment` in the role `notifier` shall not reference a `VariableDataPrototype` in the role `event`.]

[constr_3418] `UserDefinedMethodDeployments` aggregated by a `UserDefinedFieldDeployment`

Imposition time: IT_Mani

[A `UserDefinedMethodDeployment` that is aggregated by a `UserDefinedFieldDeployment` in the role `get` or `set` shall not reference a `ClientServerOperation` in the role `method`.]

[constr_3419] Allowed usage of `UdpNmNetworkConfiguration` attributes

Imposition time: IT_Mani

[The `UdpNmNetworkConfiguration` that is aggregated by `UdpNmCluster` in the role `networkConfiguration` shall have either

- `ipv4MulticastIpAddress` or
- `ipv6MulticastIpAddress`.

]

[constr_3421] Fibex elements applicable for a `System` of `category` `MACHINE_DESIGN_EXTRACT`

Imposition time: IT_SysDes

[A `System` with the `category` `MACHINE_DESIGN_EXTRACT` is allowed to reference the following `fibexElements`:

- `CommunicationCluster`
- `MachineDesign`
- `GlobalTimeDomain`
- `NmConfig`

]

[constr_3423] `StateDependentStartupConfig` of a `Process` shall reference a `functionGroupState`

Imposition time: IT_Mani

[Each `StateDependentStartupConfig` of a `Process` shall reference at least one `ModeDeclaration` in the role `functionGroupState`.]

[constr_3424] `StateDependentStartupConfig` shall never reference the `functionGroupState` `Off`

Imposition time: IT_Mani

[A `StateDependentStartupConfig` shall never reference the `ModeDeclaration` that has the `shortName` `Off` in the role `functionGroupState`. Please note that the `Off` `ModeDeclaration` is a special state in a `Function Group` as defined by [TPS_MANI_03195].]

[constr_3425] Restriction of `DoIpInstantiations` on a `Machine`

Imposition time: IT_Mani

[Each `Machine` shall aggregate at most one `DoIpInstantiation` in the role `moduleInstantiation`.]

[constr_3429] No allocator usage for `CppImplementationDataTypes` of category `VARIANT`

Imposition time: IT_BefAraApiGen

[`CppImplementationDataType` of category `VARIANT` is not allowed to aggregate a `templateArgument` that points to an `Allocator` in the role `allocator`.]

[constr_3433] Aggregation of `templateArguments` for an `ARRAY`

Imposition time: IT_BefAraApiGen

[`CppImplementationDataType` of category `ARRAY` that boils down to `ara::core::Array` shall aggregate exactly one `templateArgument` that defines the type of elements contained in the `CppImplementationDataType` of category `ARRAY`.]

[constr_3434] Aggregation of `templateArguments` for a `VECTOR`

Imposition time: IT_BefAraApiGen

[A `CppImplementationDataType` of category `VECTOR` that boils down to `ara::core::Vector` shall aggregate at least one and at most two `templateArgument` where the first one shall define the type of elements contained in the `CppImplementationDataType` of category `VECTOR` with the `templateType` reference.]

[constr_3443] Specification of a namespace for a `StdCppImplementationDataType`

Imposition time: IT_BefAraApiGen

[The definition of a `namespace` for a `StdCppImplementationDataType` of category `VALUE` is not allowed.

For this value of `category` the `std` namespace is already assumed by the usage of the `StdCppImplementationDataType`.]

[constr_3446] `CppTemplateArgument` with `allocator` reference and the `inplace` flag

Imposition time: IT_BefAraApiGen

[A `CppTemplateArgument` that points with an `allocator` reference to an `Allocator` shall not have the `inplace` flag set to a value.]

[constr_3447] `ApSomeipTransformationProps.sizeOfArrayLengthField` that equals 0

Imposition time: IT_BefAraApiGen

[The `sizeOfArrayLengthField` value of 0 is only allowed to be used if a fixed size array for which the `SomeipDataPrototypeTransformationProps` is defined is referenced within the aggregated `DataPrototypeInServiceInterfaceRef`.]

[constr_3462] CppTemplateArgument.templateType reference to StdCppImplementationDataType of category STRUCTURE and the inplace flag*Imposition time:* IT_BefAraApiGen

[CppTemplateArgument.templateType that points to a StdCppImplementationDataType of category STRUCTURE shall have the inplace attribute set to false.]

[constr_3485] UDP endpoint using DTLS SERVER role can only serve provided service instances*Imposition time:* IT_Mani

[A ServiceInstanceToMachineMapping that refers to TlsSecureComProps in the role secureComPropsForUdp is only allowed to reference ProvidedApServiceInstances in the role serviceInstance if the TlsSecureComProps has the category TLS_SERVER.]

[constr_3486] TCP endpoint using TLS SERVER role can only serve provided service instances*Imposition time:* IT_Mani

[A ServiceInstanceToMachineMapping that refers to TlsSecureComProps in the role secureComPropsForTcp is only allowed to reference ProvidedApServiceInstances in the role serviceInstance if the TlsSecureComProps has the category TLS_SERVER.]

[constr_3487] TCP endpoint can only serve provided or required service instances exclusively*Imposition time:* IT_Mani

[ServiceInstanceToMachineMapping is not allowed to refer to a ProvidedApServiceInstance and at the same time a RequiredApServiceInstance in the role serviceInstance if

- the ServiceInterfaceDeployment that is referenced by the ProvidedApServiceInstance in the role serviceInterfaceDeployment and
- the ServiceInterfaceDeployment that is referenced by the RequiredApServiceInstance in the role serviceInterfaceDeployment

both contain defined tcp content that is described by the transportProtocol attribute in the deployment elements of SOME/IP or DDS.

In other words a TCP endpoint can only serve provided or required service instances exclusively.]

[constr_3492] DoIpInstantiation.logicalAddress shall be defined as member in the **DoIpRequestConfiguration**

Imposition time: IT_Mani

[The **DoIpInstantiation.logicalAddress** shall be a member of the intervals of available physical addresses configured for the **DoIpInstantiation** in the **requestConfiguration**.]

[constr_3493] Applicable attributes for standardized E2E Profiles

Imposition time: IT_Mani

E2E Attributes	Root Element			Attribute Existence per Profile											
	End2EndEventProtectionProps	End2EndMethodProtectionProps	E2EProfileConfiguration	PROFILE_04	PROFILE_05	PROFILE_06	PROFILE_07	PROFILE_08	PROFILE_11	PROFILE_22	PROFILE_04m	PROFILE_07m	PROFILE_44	PROFILE_08m	PROFILE_44m
dataId	x	x		1	1	1	1	1	1	n	1	1	1	1	1
dataLength	x	x			x				x	x					
minDataLength	x	x		x		x	x	x			x	x	x	x	x
maxDataLength	x	x		x		x	x	x			x	x	x	x	x
dataUpdatePeriod	x	x		x	x	x	x	x	x	x	x	x	x	x	x
sourceId		x									x	x		x	x
dataIdMode			x						x						
maxDeltaCounter			x	x	x	x	x	x	x	x	x	x	x	x	x
maxErrorStateInit			x	x	x	x	x	x	x	x	x	x	x	x	x
maxErrorStateInvalid			x	x	x	x	x	x	x	x	x	x	x	x	x
maxErrorStateValid			x	x	x	x	x	x	x	x	x	x	x	x	x
minOkStateInit			x	x	x	x	x	x	x	x	x	x	x	x	x
minOkStateInvalid			x	x	x	x	x	x	x	x	x	x	x	x	x
minOkStateValid			x	x	x	x	x	x	x	x	x	x	x	x	x
windowSizeValid			x	x	x	x	x	x	x	x	x	x	x	x	x
windowSizeInvalid			x	x	x	x	x	x	x	x	x	x	x	x	x
windowSizeInit			x	x	x	x	x	x	x	x	x	x	x	x	x
clearFromValidToInvalid			x	x	x	x	x	x	x	x	x	x	x	x	x

[constr_3495] Supported value range for attribute DoIpFunctionalClusterDesign.eid

Imposition time: IT_SysDes

[The supported value range of attribute **DoIpFunctionalClusterDesign.eid** is limited to the interval [0..281474976710655].]

[constr_3496] Supported value range for attribute `DoIpInstantiation.gid`*Imposition time:* IT_Mani

[The supported value range of attribute `DoIpInstantiation.gid` is limited to the interval [0..281474976710655].]

[constr_3497] Supported value range for attribute `DoIpFunctionalClusterDesign.maxRequestBytes`*Imposition time:* IT_SysDes

[The supported value range of attribute `DoIpFunctionalClusterDesign.maxRequestBytes` is limited to the interval [0..4294967295].]

[constr_3498] Supported value range for attribute `DoIpInstantiation.logicalAddress`*Imposition time:* IT_Mani

[The supported value range of attribute `DoIpInstantiation.logicalAddress` is limited to the interval [0..65535].]

[constr_3499] Supported value range for attribute `DoIpRequestConfiguration.startAddress`*Imposition time:* IT_Mani

[The supported value range of attribute `DoIpRequestConfiguration.startAddress` is limited to the interval [0..65535].]

[constr_3528] Value range of `DdsServiceInstanceProps.domainId`*Imposition time:* IT_Mani

[The value of attribute `DdsServiceInstanceProps.domainId` at `DdsProvidedServiceInstance` and `domainId` at `DdsRequiredServiceInstance` shall be in the range of a signed 32-bit integer.]

[constr_3529] Value range of `DdsProvidedServiceInstance.serviceInstanceId`*Imposition time:* IT_Mani

[The value of attribute `DdsProvidedServiceInstance.serviceInstanceId` shall be in the range of 0..65535.]

[constr_3530] Mandatory definition of `checkpointId`*Imposition time:* IT_BefAraApiGen

[The `checkpointId` shall be defined for every `PhmCheckpoint` element.]

[constr_3538] Only one `ServiceInstanceToMachineMapping` per technology and `CommunicationConnector`*Imposition time:* IT_Mani

[Each `AdaptivePlatformServiceInstance` shall only be referenced up to once by a specific `ServiceInstanceToMachineMapping` subclass in the role `serviceInstance` where the `ServiceInstanceToMachineMapping` refer to the same `CommunicationConnector`.]

[constr_3539] Only one `AliveSupervision` per `SupervisionCheckpoint`*Imposition time:* IT_Mani

[A `SupervisionCheckpoint` shall only be referenced up to once by an `AliveSupervision` in the role `checkpoint` in the context of an identical `SupervisionMode`.]

[constr_3540] `SupervisionCheckpoint` in supervision graph*Imposition time:* IT_Mani

[Each `SupervisionCheckpoint` shall only be part of one supervision graph in the context of an identical `SupervisionMode`.]

[constr_3541] `qosProfile` mandatory for `DdsProvidedServiceInstance`*Imposition time:* IT_Mani

[The attribute `qosProfile` shall be defined for every `DdsProvidedServiceInstance`.]

[constr_3542] `qosProfile` mandatory for `DdsRequiredServiceInstance`*Imposition time:* IT_Mani

[The attribute `qosProfile` shall be defined for every `DdsRequiredServiceInstance`.]

[constr_3550] Existence of `ServiceInstanceToSignalMapping` for an event with `signalBased` serialization*Imposition time:* IT_Mani

[If

- an `event` is referenced by a `SomeipEventDeployment` in the role `event` and
- the attribute `SomeipEventDeployment.serializer` is set to `signalBased`,

then a `ServiceInstanceToSignalMapping` shall exist with `eventElementMapping` referring to the `event` in the role `dataPrototypeInServiceInterfaceRef`.]

[constr_3551] Full mapping of target `ISignalGroup`*Imposition time:* IT_Mani

[If

- an `ISignalTriggering` is part of a `ServiceInstanceToSignalMapping` and
- the `ISignalTriggering` refers to an `ISignalPort` with `communicationDirection` equals `out` and
- the `ISignalTriggering` refers to an `ISignalGroup` in the role `iSignalGroup`,

then a `SignalBasedEventElementToISignalTriggeringMapping` shall exist for every `ISignal` referenced by the `ISignalGroup` in the role `iSignal`.]

[constr_3552] Full mapping of target **event**

Imposition time: IT_Mani

[If

- the `ServiceInstanceToSignalMapping` refers to a `ProvidedSomeipServiceInstance` and
- the `dataPrototypeInServiceInterfaceRef` refers to a `DataPrototype` which is part of a composite data type,

then a `SignalBasedEventElementToISignalTriggeringMapping` shall exist for every `DataPrototype` that is part of the composite data type.]

[constr_3553] Existence of **ServiceInstanceToSignalMapping** for an **field** with **signalBased** serialization

Imposition time: IT_Mani

[If a `field` is referenced by a `SomeipFieldDeployment` in the role `field` and that `SomeipFieldDeployment` aggregates a `SomeipEventDeployment` in the role `notifier` and the `SomeipEventDeployment` has an attribute `SomeipEventDeployment.serializer` set to `signalBased` then there shall exist a `ServiceInstanceToSignalMapping` with a `fieldMapping` referring to the `field` in the role `dataPrototypeInServiceInterfaceRef` and the `SignalBasedFieldToISignalTriggeringMapping` shall refer to a `ISignalTriggering` in the role `notifierSignalTriggering`.]

[constr_3554] E2E protection configuration check

Imposition time: IT_Mani

[If the `SignalServiceTranslationEventProps.safeTranslation` equals `true` then the signal-based payload shall have an `EndToEnd` profile defined.]

[constr_3555] No support for **SecuredIPdu.useAsCryptographicIPdu** set to **true**

Imposition time: IT_Mani

[If a `PduTriggering` is referencing a `SecuredIPdu` where the attribute `useAsCryptographicIPdu` is set to the value `true`, then no subclass of `Ab-`

`stractSignalBasedToISignalTriggeringMapping` shall refer to an `ISignalTriggering` that in turn refers to an `ISignal` that is referenced in the role `iSignal` by any `ISignalToIPduMapping` that is owned by the `ISignalIPdu` referenced by the `SecuredIPdu` in the role `payload`.]

[constr_3557] Mandatory `majorVersion` at `SomeipServiceInterfaceDeployment.serviceInterfaceVersion`

Imposition time: IT_Mani

[If the `SomeipServiceVersion` is aggregated at the `SomeipServiceInterfaceDeployment` in the role `serviceInterfaceVersion` then the attribute `SomeipServiceVersion.majorVersion` shall be defined.]

[constr_3558] `RequiredSomeipServiceInstance.blocklistedVersion` is restricted to the usage of `minorVersion`

Imposition time: IT_Mani

[The `majorVersion` attribute shall not be used in the `SomeipServiceVersion` that is aggregated by the `RequiredSomeipServiceInstance` in the role `blocklistedVersion`.]

[constr_3561] `minimumMinorVersion` and `RequiredSomeipServiceInstance.requiredMinorVersion` value

Imposition time: IT_Mani

[The `RequiredSomeipServiceInstance.requiredMinorVersion` shall not have the value `ANY` if `versionDrivenFindBehavior = minimumMinorVersion`.]

[constr_3563] Mandatory topic name values

Imposition time: IT_Mani

[The attributes `methodRequestTopicName`, `methodReplyTopicName`, `fieldRequestTopicName`, `fieldReplyTopicName`, `topicName` shall specify string values, each of them unique within the service interface.]

[constr_3564] Consistency between DDS Service Interface Deployment and Provided DDS Service Instance

Imposition time: IT_Mani

[Transport attributes `DdsServiceInterfaceDeployment.transportProtocol` and `DdsEventDeployment.transportProtocol` shall be consistent with DDS profiles generated and selected by the `DdsQosProps` component of `DdsProvidedServiceInstance`, `DdsFieldQosProps`, and `DdsEventQosProps`.]

[constr_3565] Consistency between DDS Service Interface Deployment and Required DDS Service Instance

Imposition time: IT_Mani

[Transport attributes `DdsServiceInterfaceDeployment.transportProtocol` and `DdsEventDeployment.transportProtocol` shall be consistent with DDS profiles generated and selected by the `DdsQosProps` component of `DdsRequiredServiceInstance`, `DdsFieldQosProps`, and `DdsEventQosProps`.]

[constr_3568] No support for cross `PlatformHealthManagementContribution` references

Imposition time: IT_Mani

[All references originating on elements aggregated by one `PlatformHealthManagementContribution` shall only refer to elements that are part of the same `PlatformHealthManagementContribution` aggregation chain.]

[constr_3569] Applicability of attribute `invalidValue` on `CppImplementationDataType` of category `TYPE_REFERENCE`

Imposition time: IT_BefAraApiGen

[If a `CppImplementationDataType` of category `TYPE_REFERENCE` has an `invalidValue` defined, then the referenced `CppImplementationDataType` (via `typeReference`) shall eventually be of `category`.]

[constr_3612] Multiplicity of references `recoveryNotification`, `recoveryAction`, and `process` at `RecoveryNotificationToPPortPrototypeMapping`

Imposition time: IT_Mani

[The references `recoveryNotification`, `recoveryAction`, and `process` shall be defined for each `RecoveryNotificationToPPortPrototypeMapping`.]

[constr_3613] Reference to a `PhmSupervisionRecoveryNotificationInterface` in the context of a `HealthChannelSupervision`

Imposition time: IT_Mani

[If the `RecoveryNotification` is aggregated by a `HealthChannelSupervision` then the `RecoveryNotificationToPPortPrototypeMapping` shall refer to a `PPortPrototype` in the role `recoveryAction` typed by `PhmSupervisionRecoveryNotificationInterface`.]

[constr_3619] Mandatory references of `TimeBaseProviderToPersistencyMapping`

Imposition time: IT_Mani

[The references `TimeBaseProviderToPersistencyMapping.persistencyDeploymentElement` and `TimeBaseProviderToPersistencyMapping.timeBaseProvider` shall exist.]

[constr_3623] SupervisionCheckpoints in the context of a GlobalSupervision*Imposition time:* IT_Mani

[All `SupervisionCheckpoints` belonging to the same `PhmSupervisedEntityInterface` instance (`SupervisionCheckpoints` with identical `PhmCheckpointInExecutableInstanceRef.contextRootSwComponentPrototype`, `contextComponentPrototype`, `contextRPortPrototype`, and `process` references) shall only be referenced by `PhmSupervisions` which are aggregated by the same `GlobalSupervision`.]

[constr_3624] At least one Supervision defined in the context of a GlobalSupervision*Imposition time:* IT_Mani

[At least one `AliveSupervision`, `LogicalSupervision`, or `DeadlineSupervision` shall be defined in the scope of a `GlobalSupervision`.]

[constr_3625] DeadlineSupervision referencing CheckpointTransition in the context of a GlobalSupervision*Imposition time:* IT_Mani

[`DeadlineSupervision` aggregated in a `GlobalSupervision` shall only refer to a `CheckpointTransition` which is aggregated by the same `GlobalSupervision`.]

[constr_3626] LogicalSupervision referencing CheckpointTransition in the context of a GlobalSupervision*Imposition time:* IT_Mani

[`LogicalSupervision` aggregated in a `GlobalSupervision` shall only refer to `CheckpointTransitions` that are aggregated by the same `GlobalSupervision`.]

[constr_3627] Existence of SupervisionModeCondition.stateReference*Imposition time:* IT_Mani

[At the time of target-configuration of `SupervisionModeCondition`, at least one aggregation of `PhmStateReference` in the role `SupervisionModeCondition.stateReference` shall exist.]

[constr_3628] Reference to Function Group State from a SupervisionModeCondition*Imposition time:* IT_Mani

[If a `Function Group State` is referenced by a `SupervisionModeCondition` in the scope of one `GlobalSupervision`, then that same `Function Group State` shall NOT be referenced by any other `SupervisionModeCondition` in the scope of the same `GlobalSupervision`.]

[constr_3629] Identical Function Group in the scope of a **GlobalSupervision**

Imposition time: IT_Mani

[Within the context of one **GlobalSupervision**, all **SupervisionMode.mode-Condition** shall only aggregate **FunctionGroupPhmStateReferences** in the role **stateReference** where the reference **FunctionGroupPhmStateReference.functionGroupState.contextModeDeclarationGroupPrototype** refers to the identical **ModeDeclarationGroupPrototype** (that implements the **Function Group**, as far as state management is concerned).]

[constr_3630] **GlobalSupervision** and **Process** relation

Imposition time: IT_Mani

[Within the context of one **GlobalSupervision**, all aggregated **PhmSupervisions** shall refer to **SupervisionCheckpoints** where the referenced **Process** aggregates a **stateDependentStartupConfig** that in turn refers to a **functionGroup-State** where the **contextModeDeclarationGroupPrototype** refers to the identical **ModeDeclarationGroupPrototype** (that implements the **Function Group**, as far as state management is concerned).]

[constr_3631] Global supervision restricted to one **Function Group**

Imposition time: IT_Mani

[The **Function Group** (**ModeDeclarationGroupPrototype**) referenced in [constr_3629] and [constr_3630] shall be identical for one particular **GlobalSupervision**.]

[constr_3632] Supervision of a Supervised Entity Instance in the scope of a **Function Group State**

Imposition time: IT_Mani

[A **Supervised Entity Instance** shall be configured with checkpoint supervision (all **SupervisionCheckpoints** of the **Supervised Entity Instance** are covered by **AliveSupervision**, **DeadlineSupervision**, **LogicalSupervision**, **NoCheckpointSupervision**) or **NoSupervision** in all **Function Group States** in which the corresponding **Process** is configured to be executed.]

[constr_3633] Mandatory attributes of **AliveSupervision**

Imposition time: IT_Mani

[The following attributes of **AliveSupervision** shall be defined:

- **aliveReferenceCycle**
- **checkpoint**
- **expectedAliveIndications**
- **failedReferenceCyclesTolerance**
- **minMargin**

- `maxMargin`

]

[constr_3634] Multiplicity of `CheckpointTransition.source` and `CheckpointTransition.target`

Imposition time: IT_Mani

[Each `CheckpointTransition` shall define exactly one `source` reference and one `target` reference.]

[constr_3635] Mandatory attributes of `DeadlineSupervision`

Imposition time: IT_Mani

[The following attributes of `DeadlineSupervision` shall be defined:

- `transition`
- `minDeadline`
- `maxDeadline`

]

[constr_3636] Consistent `ISignal` communication direction `in` and `RequiredApServiceInstance`

Imposition time: IT_Mani

[If the `ServiceInstanceToSignalMapping.serviceInstance` refers to a `RequiredApServiceInstance` then any `ServiceInstanceToSignalMapping.eventElementMapping` (respectively `ServiceInstanceToSignalMapping.fieldMapping`) shall refer to an `ISignalTriggering` which in turn refers to an `ISignalPort` with `communicationDirection` equal to `in`.]

[constr_3637] Consistent `ISignal` communication direction `out` and `ProvidedApServiceInstance`

Imposition time: IT_Mani

[If the `ServiceInstanceToSignalMapping.serviceInstance` refers to a `ProvidedApServiceInstance` then any `ServiceInstanceToSignalMapping.eventElementMapping` (respectively `ServiceInstanceToSignalMapping.fieldMapping`) shall refer to an `ISignalTriggering` which in turn refers to an `ISignalPort` with `communicationDirection` equal to `out`.]

[constr_3640] Existence of `SupervisionMode.modeCondition`

Imposition time: IT_Mani

[For each `SupervisionMode` the attribute `modeCondition` shall exist.]

[constr_3641] Allowed combinations of `ServiceInterfaceDeployment`, `AdaptivePlatformServiceInstance`, `ServiceInstanceToMachineMapping`

Imposition time: IT_Mani

	<code>DdsProvidedServiceInstance</code>	<code>ProvidedSomeipServiceInstance</code>	<code>ProvidedUserDefinedServiceInstance</code>	<code>DdsRequiredServiceInstance</code>	<code>RequiredSomeipServiceInstance</code>	<code>RequiredUserDefinedServiceInstance</code>
<code>DdsServiceInterfaceDeployment</code>	Yes	No	Yes	Yes	No	Yes
<code>SomeipServiceInterfaceDeployment</code>	No	Yes	Yes	No	Yes	Yes
<code>UserDefinedServiceInterfaceDeployment</code>	No	No	Yes	No	No	Yes
<code>DdsServiceInstanceToMachineMapping</code>	Yes	No	No	Yes	No	No
<code>SomeipServiceInstanceToMachineMapping</code>	No	Yes	No	No	Yes	No
<code>UserDefinedServiceInstanceToMachineMapping</code>	No	Yes	Yes	No	Yes	Yes

[constr_3642] Restriction of aggregation of `PortPrototypeProps` to the Adaptive Platform

Imposition time: IT_BefAraApiGen

[The aggregation of `PortPrototypeProps` is only supported in the context of a `SwComponentType` that is (transitively) referenced by `rootSwComponentPrototype`.]

[constr_3643] No filter support for service-signal-translation direction

Imposition time: IT_Mani

[If a `ServiceInstanceToSignalMapping.serviceInstance` refers to a `ProvidedApServiceInstance` then

- every `SignalBasedEventElementToISignalTriggeringMapping` aggregated in the role `eventElementMapping` and
- every `SignalBasedFieldToISignalTriggeringMapping` aggregated in the role `fieldMapping`

shall not have a `SignalBasedEventElementToISignalTriggeringMapping.filter` (resp. `SignalBasedFieldToISignalTriggeringMapping.filter`) defined.]

[constr_3644] No `transmissionTrigger` support for `service-signal-translation` direction*Imposition time:* IT_Mani

[If a `ServiceInstanceToSignalMapping.serviceInstance` refers to a `ProvidedApServiceInstance` then

- every `SignalBasedEventElementToISignalTriggeringMapping` aggregated in the role `eventElementMapping` and
- every `SignalBasedFieldToISignalTriggeringMapping` aggregated in the role `fieldMapping`

shall not have a `SignalBasedEventElementToISignalTriggeringMapping.transmissionTrigger` (respectively `SignalBasedFieldToISignalTriggeringMapping.transmissionTrigger`) defined.]

[constr_3645] `discoveryType` mandatory for `DdsProvidedServiceInstance`*Imposition time:* IT_Mani

[The attribute `discoveryType` shall be defined for every `DdsProvidedServiceInstance`.]

[constr_3646] `resourceIdentifierType` mandatory for `DdsProvidedServiceInstance`*Imposition time:* IT_Mani

[The attribute `resourceIdentifierType` shall be defined for every `DdsProvidedServiceInstance`.]

[constr_3647] `resourceIdentifierType` value for `USER_DATA` QoS-based discovery*Imposition time:* IT_Mani

[If the value of `discoveryType` is `domainParticipantUserDataQos`, for a given `DdsProvidedServiceInstance`, the only valid value for attribute `resourceIdentifierType` is `partition`.]

[constr_3648] `discoveryType` mandatory for `DdsRequiredServiceInstance`*Imposition time:* IT_Mani

[The attribute `discoveryType` shall be defined for every `DdsRequiredServiceInstance`.]

[constr_3649] Consistent `SupervisionCheckpoint.process` reference*Imposition time:* IT_Mani

[If a `SupervisionCheckpoint` refers to a `Process` in the role `process`, then

- the `SupervisionCheckpoint` shall refer to a `PhmCheckpoint` which is defined in a `PhmSupervisedEntityInterface` and

- that `PhmSupervisedEntityInterface` types an `RPortPrototype` of an `AdaptiveApplicationSwComponentType` and
- that `AdaptiveApplicationSwComponentType` is used in the scope of an `Executable` and
- that `Executable` is referenced by the same `Process` as `SupervisionCheckpoint.process`.

]

[constr_3650] `headerId` required in case of Arbitrary Message Header

Status: DRAFT

Imposition time: IT_Mani

[If [TPS_MANI_03577] applies, then the respective `SoConIPduIdentifier.headerId` shall be defined.]

[constr_3674] Existence of `NoSupervision.targetPhmSupervisedEntity`

Imposition time: IT_Mani

[For each `NoSupervision` the attribute `targetPhmSupervisedEntity` shall exist.]

[constr_3675] Existence of `NoSupervision.process`

Imposition time: IT_Mani

[For each `NoSupervision` the attribute `process` shall exist.]

[constr_3676] Exclusive usage of `NoSupervision`

Imposition time: IT_Mani

[For a Supervised Entity Instance, in a given `SupervisionMode`, either a checkpoint supervision (`AliveSupervision`, `DeadlineSupervision`, `LogicalSupervision`, and/or `NoCheckpointSupervision` referencing all `SupervisionCheckpoints` corresponding to the Supervised Entity Instance) or `NoSupervision` shall be configured, but not both.]

[constr_3677] `ComGrants` referencing DDS Service Instances

Status: DRAFT

Imposition time: IT_Mani

[`ComGrants` associated with `DdsProvidedServiceInstances` or `DdsRequiredServiceInstances` via the `serviceInstance` attribute shall not be referenced by `CmModuleInstantiation.grant`.]

[constr_3678] Existence of attributes for `DdsSecureComProps`

Status: DRAFT

Imposition time: IT_Mani

[The following attributes of `DdsSecureComProps` shall exist:

- `identity`
- `governance`

]

[constr_3679] Existence of attributes for `DdsSecureGovernance`*Status:* DRAFT*Imposition time:* IT_Mani[The following attributes of `DdsSecureGovernance` shall exist:

- at least one `domainId`
- `identityCertificateAuthority`
- `permissionCertificateAuthority`
- `allowUnauthenticatedParticipants`
- `enableJoinAccessControl`
- `discoveryProtectionKind`
- `livelinessProtectionKind`
- `rtpsProtectionKind`

]

[constr_3680] Existence of attributes for `DdsTopicAccessRule`*Imposition time:* IT_Mani[The following attributes of `DdsTopicAccessRule` shall exist:

- `enableDiscoveryProtection`
- `enableLivelinessProtection`
- `enableReadAccessControl`
- `enableWriteAccessControl`
- `metadataProtectionKind`
- `dataProtectionKind`

]

[constr_3681] Supported values of `DdsTopicAccessRule.dataProtectionKind`*Imposition time:* IT_Mani[Only values `none`, `sign`, or `encryptAndSign` from `DdsProtectionKindEnum` shall be used when setting `DdsTopicAccessRule.dataProtectionKind`.]

[constr_3682] Values of `DdsDomainRange.min` and `DdsDomainRange.max`

Imposition time: IT_Mani

[The value of `DdsDomainRange.min` shall be less than or equal to the value of `DdsDomainRange.max`.]

[constr_3683] Attributes referencing `DdsTopicAccessRule`

Imposition time: IT_Mani

[`DdsServiceInterfaceDeployment.fieldTopicsAccessRule`, `DdsServiceInterfaceDeployment.methodTopicsAccessRule`, and `DdsEventDeployment.eventTopicAccessRule` shall be set if the Service Interface Deployment is to be used by Service Instances relying in DDS Security (meaning `DdsServiceInstanceToMachineMapping.secureComPropsForDds` is defined).]

[constr_3684] Mutual exclusivity of Secure Communication Properties

Imposition time: IT_Mani

[The attributes `ServiceInstanceToMachineMapping.secOcComPropsForMulticast` and `DdsServiceInstanceToMachineMapping.secureComPropsForDds` are mutually exclusive, meaning zero or just one of them shall be set depending on whether no security, SecOC, or DDS Security is chosen as data-level security (optionally) above transport-level security.]

[constr_3690] `DdsServiceInterfaceDeployment.serviceInterfaceId` value shall not conflict with topic-based service discovery

Imposition time: IT_SysDes

[The value "discovery" for `DdsServiceInterfaceDeployment.serviceInterfaceId` is reserved and shall not be used for modeled `DdsServiceInterfaceDeployments` Note that in the context of the *AUTOSAR adaptive platform*.]

[constr_3691] Existence of `ServiceInterfaceElementSecureComConfig.securedRxVerification`

Imposition time: IT_Mani

[The attribute `ServiceInterfaceElementSecureComConfig.securedRxVerification` shall only be defined for a `ServiceInterfaceElementSecureComConfig` with the following definitions:

- The `ServiceInterfaceElementSecureComConfig` is aggregated by a `RequiredApServiceInstance` and defines at least one of the following roles:
 - `ServiceInterfaceElementSecureComConfig.event`
 - `ServiceInterfaceElementSecureComConfig.fieldNotifier`
 - `ServiceInterfaceElementSecureComConfig.getterReturn`
 - `ServiceInterfaceElementSecureComConfig.setterReturn`
 - `ServiceInterfaceElementSecureComConfig.methodReturn`

- The `ServiceInterfaceElementSecureComConfig` is aggregated by a `ProvidedApServiceInstance` and defines at least one of the following roles:
 - `ServiceInterfaceElementSecureComConfig.getterCall`
 - `ServiceInterfaceElementSecureComConfig.setterCall`
 - `ServiceInterfaceElementSecureComConfig.methodCall`

]

[constr_3692] `DataPrototypeInServiceInterfaceInstanceRef.targetDataPrototype` in the context of a `SignalBasedFireAndForgetMethodToISignalTriggeringMapping`

Imposition time: IT_Mani

[If a `DataPrototypeInServiceInterfaceInstanceRef` is aggregated by a `SignalBasedFireAndForgetMethodToISignalTriggeringMapping` in the role `dataPrototypeInMethodArgumentInstanceRef`, then the reference `DataPrototypeInServiceInterfaceInstanceRef.targetDataPrototype` shall refer to an `ArgumentDataPrototype`.]

[constr_3693] `EthernetCommunicationConnector.category` is set to `CAN_XL`

Imposition time: IT_SysDes

[If a `EthernetCommunicationConnector` is aggregated by the `MachineDesign` where attribute `category` is set to `CAN_XL`, then a reference from the `EthernetCommunicationConnector` to a `CanXlProps` in the role `canXlProps` shall exist.]

[constr_3694] Existence of `canXlConfig` vs. `canXlConfigReqs`

Imposition time: IT_SysDes

[For each `CanXlProps`, one of

- `canXlConfig` or
- `canXlConfigReqs`

shall exist.]

[constr_3709] `AliveSupervision.terminatingCheckpoint` required for self terminating `Processes`

Imposition time: IT_Mani

[Only if a `Process`

- refers to a `StartupConfig` (via `stateDependentStartupConfig`), and that `StartupConfig` has the attribute `StartupConfig.terminationBehavior` set to the value `TerminationBehaviorEnum.processIsSelfTerminating`, and

- the `StateDependentStartupConfig.functionGroupState` is identical to the respective `GlobalSupervision.supervisionMode.modeCondition.stateReference.functionGroupState` and
- there exists an `AliveSupervision` which refers to a `SupervisionCheckpoint` in the role `checkpoint`, and that `SupervisionCheckpoint` refers to that `Process`, then

there shall exist an `AliveSupervision.terminatingCheckpoint` reference from the `AliveSupervision`.]

[constr_3710] `Process` referenced by `AliveSupervision.terminatingCheckpoint`

Imposition time: IT_Mani

[The `SupervisionCheckpoint` that is referenced in the role `AliveSupervision.terminatingCheckpoint` shall refer to the same `Process` as the `SupervisionCheckpoint` that is referenced by the `AliveSupervision.checkpoint`.]

[constr_3711] `AliveSupervision.terminatingCheckpointTimeoutUntilTermination`

Imposition time: IT_Mani

[If an `AliveSupervision` has the reference `AliveSupervision.terminatingCheckpoint` defined, then the attribute `AliveSupervision.terminatingCheckpointTimeoutUntilTermination` shall be defined.]

[constr_3712] Exclusive usage of `NoCheckpointSupervision`

Imposition time: IT_Mani

[If a `SupervisionCheckpoint` is referenced by a `NoCheckpointSupervision` in the role `checkpoint`, then that `SupervisionCheckpoint` shall not be referenced by any other checkpoint supervision (`AliveSupervision`, `DeadlineSupervision` (via `CheckpointTransition`), `LogicalSupervision` (also via or `CheckpointTransition`)) in the scope of one `SupervisionMode`.]

[constr_3715] Reference in the role `SomeipEventGroup.event`

Imposition time: IT_Mani

[In the context of a given `SomeipServiceInterfaceDeployment`, all aggregated `SomeipEventDeployments` shall be referenced at least once in the role `event` by `SomeipEventGroups` that in turn are aggregated at the same `SomeipServiceInterfaceDeployment`.]

[constr_3720] Upper multiplicity of reference in the role `ComGrantDesign.remoteSubject`*Status:* DRAFT*Imposition time:* IT_GraDes

[In the context of `ComGrantDesign`, the reference in the role `remoteSubject` shall exist at most once.]

[constr_3721] Upper multiplicity of reference in the role `EthernetCommunicationConnector.unicastNetworkEndpoint`*Imposition time:* IT_Mani

[In the context of `EthernetCommunicationConnector`, the reference in the role `unicastNetworkEndpoint` shall exist at most once.]

[constr_3722] Upper multiplicity of reference in the role `EthernetCommunicationConnector.canXlProps`*Imposition time:* IT_Mani

[In the context of `EthernetCommunicationConnector`, the reference in the role `canXlProps` shall exist at most once.]

[constr_3723] Upper multiplicity of reference in the role `MachineDesign.tcpIpProps`*Imposition time:* IT_SysDes

[In the context of `MachineDesign`, the reference in the role `tcpIpProps` shall exist at most once.]

[constr_3724] Upper multiplicity of reference in the role `MachineDesign.tcpIpIcmpProps`*Imposition time:* IT_SysDes

[In the context of `MachineDesign`, the reference in the role `tcpIpIcmpProps` shall exist at most once.]

[constr_3725] Upper multiplicity of reference in the role `MachineDesign.ethIpProps`*Imposition time:* IT_SysDes

[In the context of `MachineDesign`, the reference in the role `ethIpProps` shall exist at most once.]

[constr_3727] Upper multiplicity of reference in the role `SoftwareClusterDesign.intendedTargetMachine`*Imposition time:* IT_SubSysDes

[In the context of `SoftwareClusterDesign`, the reference in the role `intendedTargetMachine` shall exist at most once.]

[constr_3728] Upper multiplicity of reference in the role `IdsPlatformInstantiation.networkInterface`*Status:* DRAFT*Imposition time:* IT_Mani

[In the context of `IdsPlatformInstantiation`, the reference in the role `networkInterface` shall exist at most once.]

[constr_3729] Upper multiplicity of reference in the role `LogAndTraceInstantiation.timeBaseResource`*Imposition time:* IT_Mani

[In the context of `LogAndTraceInstantiation`, the reference in the role `timeBaseResource` shall exist at most once.]

[constr_3730] Upper multiplicity of reference in the role `HealthChannel.recoveryNotification`*Imposition time:* IT_Mani

[In the context of `HealthChannel`, the reference in the role `recoveryNotification` shall exist at most once.]

[constr_3731] Upper multiplicity of reference in the role `ProcessDesign.executable`*Imposition time:* IT_SubSysDes

[In the context of `ProcessDesign`, the reference in the role `executable` shall exist at most once.]

[constr_3732] Upper multiplicity of reference in the role `Process.executable`*Imposition time:* IT_Mani

[In the context of `Process`, the reference in the role `executable` shall exist at most once.]

[constr_3734] Upper multiplicity of reference in the role `DoIpNetworkConfiguration.networkConfiguration`*Imposition time:* IT_Mani

[In the context of `DoIpNetworkConfiguration`, the reference in the role `networkConfiguration` shall exist at most once.]

[constr_3772] Range of `ApApplicationError.errorCode` for interoperability with the AUTOSAR classic platform*Imposition time:* IT_SysDes

[If a SOME/IP service instance interacts with a classic platform according to [TPS_MANI_03674], then the value of attribute `ApApplicationError.errorCode` used according to [TPS_MANI_01191] shall not exceed the closed interval [1..63].]

[constr_3773] Uniqueness of `ApApplicationError.errorCode` for interoperability with the AUTOSAR classic platform*Imposition time:* IT_BefAraApiGen

[If a SOME/IP service instance interacts with a classic platform according to [TPS_MANI_03674], then the set of `ApApplicationErrors` configured for a `ClientServerOperation` according to [TPS_MANI_01191] shall all have unique `ApApplicationError.errorCode` values defined.]

[constr_3774] Existence of `EthernetMacRawDataStreamMapping.localCommConnector`*Status:* DRAFT*Imposition time:* IT_Mani

[The reference `EthernetMacRawDataStreamMapping.localCommConnector` shall exist.]

[constr_3775] Existence of `IEEE1722RawDataStreamConsumerMapping.ieee1722Stream`*Status:* DRAFT*Imposition time:* IT_Mani

[The reference `IEEE1722RawDataStreamConsumerMapping.ieee1722Stream` shall exist.]

[constr_3776] Existence of `IEEE1722RawDataStreamProducerMapping.ieee1722Stream`*Status:* DRAFT*Imposition time:* IT_Mani

[The reference `IEEE1722RawDataStreamProducerMapping.ieee1722Stream` shall exist.]

[constr_3777] Existence of `IEEE1722AcfBusRawDataStreamConsumerMapping.acfBus`*Status:* DRAFT*Imposition time:* IT_Mani

[At least one reference `IEEE1722AcfBusRawDataStreamConsumerMapping.acfBus` shall exist.]

[constr_3778] Existence of `IEEE1722AcfBusPartRawDataStreamConsumerMapping.acfBusPart`*Status:* DRAFT*Imposition time:* IT_Mani

[At least one reference `IEEE1722AcfBusPartRawDataStreamConsumerMapping.acfBusPart` shall exist.]

[constr_3795] No Platform Health Management supervision for non-reporting Executables*Imposition time:* IT_BefAraApiGen

[If an Executable has Executable.reportingBehavior set to ExecutionStateReportingBehaviorEnum.doesNotReportExecutionState, then none of the SwComponentTypes that are used to type SwComponentPrototype used in the composition definition of the rootSwComponentPrototype shall define an RPortPrototype typed by a PhmSupervisedEntityInterface.]

[constr_3798] Applicable attributes for an Ethernet node on the adaptive platform*Imposition time:* IT_SysDes

[If a CouplingPort is aggregated by an EthernetCommunicationController and that EthernetCommunicationController is in turn aggregated by a MachineDesign, then the attributes defined in the column "Endpoint" of [TPS_SYST_02422] are applicable.]

[constr_3823] Existence of GlobalSupervision.expiredSupervisionTolerance*Imposition time:* IT_Mani

[For each GlobalSupervision the attribute expiredSupervisionTolerance shall exist.]

[constr_5000] Supported value range for attribute DoIpRequestConfiguration.endAddress*Imposition time:* IT_Mani

[The supported value range of attribute DoIpRequestConfiguration.endAddress is limited to the interval [0..65535].]

[constr_5004] Mapping of a Process to a Machine is mandatory in the Execution Manifest*Imposition time:* IT_Mani

[Each Process shall be mapped by a ProcessToMachineMapping to one Machine.]

[constr_5033] Compatibility of data types with category VALUE*Imposition time:* IT_BefAraApiGen

[An ApplicationDataType of category VALUE can only be mapped to a CppImplementationDataType which also has category VALUE.]

[constr_5034] Compatibility of data types with category BOOLEAN*Imposition time:* IT_BefAraApiGen

[An ApplicationDataType of category BOOLEAN can only be mapped to a CppImplementationDataType of category VALUE.]

[constr_5035] Compatibility of data types with **category STRING**

Imposition time: IT_BefAraApiGen

[A `CppImplementationDataType` where attribute `category` is set to the value `STRING` can only be mapped to an `ApplicationDataType`

- where attribute `category` is set to the value `STRING` **and**
- where attribute `swDataDefProps.swTextProps.baseType.baseTypeDefinition.baseTypeEncoding` is set to the value `UTF-8`.

]

[constr_5036] Compatibility of data types with **category ARRAY**

Imposition time: IT_BefAraApiGen

[An `ApplicationDataType` of `category ARRAY` can only be mapped to

- a `CppImplementationDataType` of `category ARRAY` **or**
- a `CppImplementationDataType` of `category VECTOR`.

]

[constr_5037] Compatibility of data types with **category ARRAY with variable-Size**

Imposition time: IT_BefAraApiGen

[An `ApplicationDataType` of `category ARRAY` that includes one `Application-ArrayElement` with `arraySizeSemantics` set to `variableSize` in one of the defined dimensions shall be mapped to

- a `CppImplementationDataType` of `category VECTOR`

]

[constr_5038] Compatibility of data types with **category ARRAY with fixedSize**

Imposition time: IT_BefAraApiGen

[An `ApplicationDataType` of `category ARRAY` that includes only `Application-ArrayElements` with `arraySizeSemantics` set to `fixedSize` in all defined dimensions shall be mapped to

- a `CppImplementationDataType` of `category ARRAY`

]

[constr_5039] Compatibility of data types with **category STRUCTURE**

Imposition time: IT_BefAraApiGen

[An `ApplicationDataType` of `category STRUCTURE` can only be mapped to a `CppImplementationDataType` of `category STRUCTURE`.]

[constr_5040] Compatibility of `ApplicationRecordDataType` and `CppImplementationDataType` that both represent an Optional Element Structure*Imposition time:* IT_BefAraApiGen

[An `ApplicationRecordDataType` that represents an Optional Element Structure can only be mapped to a `CppImplementationDataType` of category `STRUCTURE` that represents an Optional Element Structure if corresponding pairs of elements have the same value of the attribute `isOptional`.]

[constr_5041] Compatibility of data types with category `ASSOCIATIVE_MAP`*Imposition time:* IT_BefAraApiGen

[An `ApplicationDataType` of category `ASSOCIATIVE_MAP` can only be mapped to a `CppImplementationDataType` of category `ASSOCIATIVE_MAP`.]

[constr_5042] No data type mapping for `CppImplementationDataType` of category `VARIANT`*Imposition time:* IT_BefAraApiGen

[An `ApplicationDataType` shall never be mapped to a `CppImplementationDataType` of category `VARIANT`.]

[constr_5043] Forbidden mappings to `CppImplementationDataType`*Imposition time:* IT_BefAraApiGen

[An `ApplicationDataType` of category `COM_AXIS`, `RES_AXIS`, `CURVE`, `MAP`, `CUBOID`, `CUBE_4`, `CUBE_5` is not supported by the Adaptive Platform and can therefore not be mapped to a `CppImplementationDataType`.]

[constr_5044] `DataTypeMap` for composite data types*Imposition time:* IT_BefAraApiGen

[In the context of a given `ServiceInterface`, all pairs of `ApplicationDataType` and `CppImplementationDataType` used in the context of the definition of an `ApplicationCompositeDataType` used in the context of an `event`, `field`, `method` shall be described in a `DataTypeMap` that is contained in one of the `DataTypeMappingSets` that are referenced in a `PortInterfaceToDataTypeMapping` that also references the mentioned `ServiceInterface`.]

[constr_5045] Only one `SomeipServiceDiscovery` configuration per VLAN is allowed*Imposition time:* IT_SysDes

[Only a single `NetworkEndpoint` on an `EthernetPhysicalChannel` (VLAN) is allowed to be referenced by a `SomeipServiceDiscovery` element in the role `multicastSdIpAddress`.]

[constr_5047] Supported values of `TlsSecureComProps.category`*Imposition time:* IT_Mani

[The only supported values of attribute `TlsSecureComProps.category` are:

- **TLS_SERVER**: the `TlsSecureComProps` assumes the role of the *server* in the TLS connection.
- **TLS_CLIENT**: the `TlsSecureComProps` assumes the role of the *client* in the TLS connection.

]

[constr_5048] Existence of `TlsCryptoCipherSuite.certificate` and `TlsCryptoCipherSuite.pskIdentity` in the *server* role*Imposition time:* IT_Mani

[Either

- the reference to `CryptoServiceCertificate` in the role `TlsCryptoCipherSuite.certificate`
- the aggregation of `TlsPskIdentity` in the role `TlsCryptoCipherSuite.pskIdentity`

shall exist if the `TlsCryptoCipherSuite` is aggregated by `TlsSecureComProps` that has the attribute `category` set to the value `TLS_SERVER`.]

[constr_5052] `ProvidedSomeipServiceInstances` of the same *serviceInterface* on one Machine*Imposition time:* IT_Mani

[`ProvidedSomeipServiceInstances` that are referring to the same `SomeipServiceInterfaceDeployment` element or to several `SomeipServiceInterfaceDeployments` that all have the same SOME/IP credentials (`SomeipServiceInterfaceDeployment.serviceInterfaceId` and `SomeipServiceInterfaceDeployment.serviceInterfaceVersion.majorVersion`) shall not be mapped to the same combination of:

- IP address that is assigned by the `SomeipServiceInstanceToMachineMapping` with the reference to the `EthernetCommunicationConnector` that in turn references the `NetworkEndpoint` and
- UDP Port or TCP Port number that are defined by the `SomeipServiceInstanceToMachineMapping.udpPort` and `SomeipServiceInstanceToMachineMapping.tcpPort` references to the `ApApplicationEndpoint`.

]

[constr_5056] Restriction of sub-class of `CompositionSwComponentType.connector`

Imposition time: IT_BefAraApiGen

[In the context of a `CompositionSwComponentType.connector` (transitively) referenced by a `Executable.rootSwComponentPrototype`, the only supported sub-class of `SwConnector` is `PassThroughSwConnector`.]

[constr_5057] `PassThroughSwConnector` and `ServiceInterfaceMapping`

Imposition time: IT_BefAraApiGen

[If a `PassThroughSwConnector` is defined between two Ports in a `CompositionSwComponentType` either:

- a `ServiceInterfaceMapping` between the `ServiceInterfaces` of these two Ports shall be defined and the `PassThroughSwConnector` shall reference the relevant `ServiceInterfaceMapping` in the role `mapping` or
- `ServiceInterfaceElementMappings` for elements of `ServiceInterfaces` of the two Ports shall be defined and the `PassThroughSwConnector` shall reference the relevant `ServiceInterfaceElementMappings` in the role `serviceInterfaceElementMapping`.

]

[constr_5102] Usage of remote port ranges in `IPSecRule` is not allowed

Imposition time: IT_SysDes

[`IPSecRule.remotePortRangeStart` and `IPSecRule.remotePortRangeEnd` shall always be set to the same value.]

[constr_5103] Usage of local port ranges in `IPSecRule` is not allowed

Imposition time: IT_SysDes

[`IPSecRule.localPortRangeStart` and `IPSecRule.localPortRangeEnd` shall always be set to the same value.]

[constr_5115] Search for a specific SOME/IP ServiceInstance and for all SOME/IP ServiceInstances over the same `RPortPrototype`

Imposition time: IT_Mani

[A `RequiredSomeipServiceInstance` that configures the search for a specific ServiceInstance on SOME/IP (with concrete `requiredServiceInstanceId`) and a `RequiredSomeipServiceInstance` that configures the search for ALL ServiceInstances on SOME/IP (with `requiredServiceInstanceId` = ALL) that are mapped using `ServiceInstanceToMachineMapping` to the same `EthernetCommunicationConnector` (and therefore are searching for SOME/IP ServiceInstances on the same VLAN) are not allowed to be mapped by `ServiceInstanceToPortPrototypeMappings` to the same `RPortPrototype`.]

[constr_5155] `SomeipServiceInstanceToMachineMapping` only supports a single Address Family*Imposition time:* IT_Mani

[A `SomeipServiceInstanceToMachineMapping` shall only support a single Address Family, i.e. either IPv4 or IPv6. If IPv4 is defined for IP unicast communication according to [constr_3288] then the `SomeipProvidedEventGroups` in `ProvidedSomeipServiceInstances` that are referenced by the `SomeipServiceInstanceToMachineMapping` shall only define an `ipv4MulticastIpAddress`.

If IPv6 is defined for IP unicast communication according to [constr_3288] then the `SomeipProvidedEventGroups` in `ProvidedSomeipServiceInstances` that are referenced by the `SomeipServiceInstanceToMachineMapping` shall only define an `ipv6MulticastIpAddress`.]

[constr_5156] `SomeipEventDeployment.transportProtocol` setting to `udp` and the impact on `ProvidedSomeipServiceInstances`*Imposition time:* IT_Mani

[If `SomeipEventDeployment.transportProtocol` is set to `udp` then each `ProvidedSomeipServiceInstance` that refers the `SomeipServiceInterfaceDeployment` in the role `serviceInterfaceDeployment` shall only be mapped to a `MachineDesign` with a `SomeipServiceInstanceToMachineMapping` with a configured `udpPort`.]

[constr_5161] `RequiredSomeipServiceInstance` that is mapped by a `SomeipServiceInstanceToMachineMapping` without a configured `tcpPort` and `udpPort`*Imposition time:* IT_Mani

[A `RequiredSomeipServiceInstance` that is mapped to a `EthernetCommunicationConnector` by a `SomeipServiceInstanceToMachineMapping` that does not have neither a `udpPort` nor a `tcpPort` is not allowed to reference a `SomeipServiceInterfaceDeployment` that includes `SomeipMethodDeployments` (directly or indirectly via `ServiceFieldDeployment`).]

[constr_5227] Mandatory elements of `UdpNmCluster`*Imposition time:* IT_Mani

[The following attributes shall always be defined for the `UdpNmCluster`:

- `nmMsgCycleTime`
- `nmNetworkTimeout`
- `nmRepeatMessageTime`
- `nmWaitBusSleepTime`
- `communicationCluster`

]

[constr_5228] Partial Networking timing constraint

Imposition time: IT_Mani

[For Partial Networking the following timing constraints shall be ensured: (`MachineDesign.pnResetTimer` + `MachineDesign.pncPrepareSleepTimer`) < `UdpNmCluster.nmNetworkTimeout`.]

[constr_5230] Attribute `E2EProfileCompatibilityProps.transitToInvalidExtended` shall exist for each `E2EProfileConfiguration`

Imposition time: IT_Mani

[For each `E2EProfileConfiguration`, a reference role to `E2EProfileCompatibilityProps` in the role `e2eProfileCompatibilityProps` shall exist and the referenced `E2EProfileCompatibilityProps` shall define a value for the attribute `transitToInvalidExtended`.]

[constr_5238] `CryptoKeySlotAllowedModification.restrictUpdate` and the relationship to `maxNumberOfAllowedUpdates`

Status: DRAFT

Imposition time: IT_BefAraApiGen

[If the `CryptoKeySlotAllowedModification.restrictUpdate` is set to true then `CryptoKeySlotAllowedModification.maxNumberOfAllowedUpdates` shall be set to a value.]

[constr_5239] Predefined values for `CryptoKeySlotContentAllowedUsage.allowedKeyslotUsage`

Status: DRAFT

Imposition time: IT_BefAraApiGen

[The following values for `CryptoKeySlotContentAllowedUsage.allowedKeyslotUsage` are predefined by AUTOSAR:

- ALLOW-DATA-ENCRYPTION,
- ALLOW-DATA-DECRYPTION,
- ALLOW-MAC
- ALLOW-SIGNATURE-GENERATION
- ALLOW-SIGNATURE-VERIFICATION
- ALLOW-KEY-AGREEMENT
- ALLOW-KEY-DERIVATION
- ALLOW-KEY-WRAPPING
- ALLOW-KEY-UNWRAPPING
- ALLOW-PERSIST

- ALLOW-SECURED-EXPORT
- ALLOW-PLAINTEXT-EXPORT
- ALLOW-DERIVED-PLAINTEXT-EXPORT
- ALLOW-RNG-INIT
- ALLOW-HASH-CALCULATION

]

[constr_5240] Restriction applicable for [CryptoProviderToPortPrototypeMapping.portPrototype](#)

Status: DRAFT

Imposition time: IT_Mani

[The reference [CryptoProviderToPortPrototypeMapping.portPrototype](#) shall only be used for an [RPortPrototype](#) typed by a [CryptoProviderInterface](#).]

[constr_5241] Restriction applicable for [AbstractCryptoKeySlotToPortPrototypeMapping.portPrototype](#)

Status: DRAFT

Imposition time: IT_Mani

[The reference [AbstractCryptoKeySlotToPortPrototypeMapping.portPrototype](#) shall only be used for an [RPortPrototype](#) typed by a [CryptoKeySlotInterface](#).]

[constr_5242] Restriction applicable for [CryptoCertificateToPortPrototypeMapping.portPrototype](#)

Status: DRAFT

Imposition time: IT_Mani

[The reference [CryptoCertificateToPortPrototypeMapping.portPrototype](#) shall only be used for an [RPortPrototype](#) typed by a [CryptoCertificateInterface](#).]

[constr_5250] Protection of [AdaptivePlatformServiceInstances](#) of the same [ServiceInterfaceDeployment](#)

Imposition time: IT_Mani

[If several [AdaptivePlatformServiceInstances](#) exist that are referencing the same [ServiceInterfaceDeployment](#) and these [AdaptivePlatformServiceInstances](#) contain aggregated [End2EndMethodProtectionProps](#) and/or [End2EndEventProtectionProps](#) then the [E2EProfileConfigurations](#) that are referenced by the [End2EndMethodProtectionProps](#) and [End2EndEventProtectionProps](#) shall have the same [profileName](#) defined.]

[constr_5260] UDP endpoint using DTLS CLIENT role can only serve required service instances*Imposition time:* IT_Mani

[A [ServiceInstanceToMachineMapping](#) that refers to [TlsSecureComProps](#) in the role [secureComPropsForUdp](#) is only allowed to reference [RequiredApServiceInstances](#) in the role [serviceInstance](#) if the [TlsSecureComProps](#) has the category [TLS_CLIENT](#).]

[constr_5261] TCP endpoint using TLS CLIENT role can only serve required service instances*Imposition time:* IT_Mani

[A [ServiceInstanceToMachineMapping](#) that refers to [TlsSecureComProps](#) in the role [secureComPropsForTcp](#) is only allowed to reference [RequiredApServiceInstances](#) in the role [serviceInstance](#) if the [TlsSecureComProps](#) has the category [TLS_CLIENT](#).]

[constr_5275] Existence of [LogAndTraceInstantiation.dltEcu](#)*Imposition time:* IT_Mani

[For each [LogAndTraceInstantiation](#) the reference to [DltEcu](#) in the role [dltEcu](#) shall exist.]

[constr_5276] Existence of [LogAndTraceInstantiation.logSink](#)*Imposition time:* IT_Mani

[Each [LogAndTraceInstantiation](#) shall reference at least one [DltLogSink](#) in the role [logSink](#).]

[constr_5277] Applicable values of `DltLogSink.category` vs. `DltLogSink` attributes

Imposition time: IT_Mani

[

Category	Applicable to ...					
	<code>DltLogSink.logChannelId</code>	<code>DltLogSink.endpointConfiguration</code>	<code>DltLogSink.path</code>	<code>DltLogSink.bufferOutput</code>	<code>DltLogSink.nonVerboseMode</code>	<code>DltLogSink.segmentationSupported</code>
<code>DLT_LOGSINK_REMOTE</code>	x					
<code>DLT_LOGSINK_DLT</code>	x	x			x	x
<code>DLT_LOGSINK_FILE</code>			x			
<code>DLT_LOGSINK_CONSOLE</code>				x		
<code>DLT_LOGSINK_ARTI</code>						

]

[constr_5278] `DltLogSink` with category `DLT_LOGSINK_REMOTE` is only allowed to be referenced by `DltLogSinkToPortPrototypeMapping`

Imposition time: IT_Mani

[`DltLogSink` with category `DLT_LOGSINK_REMOTE` shall not be referenced by `LogAndTraceInstantiation` in the role `logSink`.]

[constr_5279] `DltLogSink` with category `DLT_LOGSINK_DLT` is only allowed to be referenced by `LogAndTraceInstantiation`

Imposition time: IT_Mani

[`DltLogSink` with category `DLT_LOGSINK_DLT` shall not be referenced by `DltLogSinkToPortPrototypeMapping` in the role `dltLogSink`.]

[constr_5281] Existence of `DltLogSink.defaultTraceState`

Imposition time: IT_Mani

[For each `DltLogSink`, attribute `defaultTraceState` shall exist.]

[constr_5282] Existence of `DltLogSinkToPortPrototypeMapping.process`

Imposition time: IT_Mani

[Each `DltLogSinkToPortPrototypeMapping` shall reference a `Process` in the role `process`.]

[constr_5283] Existence of `DltLogSinkToPortPrototypeMapping.dltLogSink`*Imposition time:* IT_Mani

[Each `DltLogSinkToPortPrototypeMapping` shall reference at least one `DltLogSink` in the role `dltLogSink`.]

[constr_5284] Existence of `DltLogSinkToPortPrototypeMapping.dltContext`*Imposition time:* IT_Mani

[Each `DltLogSinkToPortPrototypeMapping` shall reference a `DltContext` in the role `dltContext`.]

[constr_5285] Existence of `PortPrototype` references in `DltLogSinkToPortPrototypeMapping`*Imposition time:* IT_Mani

[Each `DltLogSinkToPortPrototypeMapping` shall reference exactly one `PortPrototype` in the role `rPortPrototype` or `pPortPrototype`.]

[constr_5286] Restriction applicable for `DltLogSinkToPortPrototypeMapping.rPortPrototype`*Imposition time:* IT_Mani

[The reference `DltLogSinkToPortPrototypeMapping.rPortPrototype` shall only be used for a `RPortPrototype` typed by a `LogAndTraceInterface` or by a `ServiceInterface`.]

[constr_5287] Restriction applicable for `DltLogSinkToPortPrototypeMapping.pPortPrototype`*Imposition time:* IT_Mani

[The reference `DltLogSinkToPortPrototypeMapping.pPortPrototype` shall only be used for a `PPortPrototype` typed by a `ServiceInterface`.]

[constr_5288] Existence of `process` reference in `DltApplicationToProcessMapping`*Imposition time:* IT_Mani

[Each `DltApplicationToProcessMapping` shall reference a `Process` in the role `process`.]

[constr_5289] Existence of `dltApplication` reference in `DltApplicationToProcessMapping`*Imposition time:* IT_Mani

[Each `DltApplicationToProcessMapping` shall reference a `DltApplication` in the role `dltApplication`.]

[constr_5290] PPortPrototype is not allowed to be typed by LogAndTraceInterface*Imposition time:* IT_BefAraApiGen

[A PPortPrototype is not allowed to reference a LogAndTraceInterface in the role providedInterface.]

[constr_5291] Allowed usage of LTMessageCollectionToPortPrototypeMapping.rPort*Imposition time:* IT_BefAraApiGen

[An LTMessageCollectionToPortPrototypeMapping shall (in the role rPort) only refer to a RPortPrototype that is typed by a LogAndTraceInterface.]

[constr_5292] Assigned dltSessionId shall be consistent for the same Port-Prototype*Imposition time:* IT_Mani

[If several DltLogSinkToPortPrototypeMappings are referencing the same PortPrototype in the role rPortPrototype or pPortPrototype then the value for the dltSessionId in all these DltLogSinkToPortPrototypeMappings shall be the same.]

[constr_5316] Allowed ServiceEventDeployment.trigger references*Imposition time:* IT_Mani

[The Trigger that is referenced by ServiceEventDeployment in the role trigger shall be defined in the context of a ServiceInterface that is referenced by the ServiceInterfaceDeployment in the role serviceInterface that contains the ServiceEventDeployment.]

[constr_5317] ServiceEventDeployment not allowed to reference an event and a trigger at the same time*Imposition time:* IT_Mani

[The ServiceEventDeployment element shall reference either:

- a VariableDataPrototype in the role event or
- a Trigger in the role trigger,

but not both at the same time.]

[constr_5318] Existence of ServiceInstanceToSignalMapping for an trigger with signalBased serialization*Imposition time:* IT_Mani

[If a trigger is referenced by a SomeipEventDeployment in the role trigger and the attribute SomeipEventDeployment.serializer is set to signalBased then a ServiceInstanceToSignalMapping shall exist with triggerMapping referring to the trigger in the role trigger.]

[constr_5324] MachineDesign.communicationController aggregation restriction

Imposition time: IT_MachDes

[MachineDesign is only allowed to aggregate an EthernetCommunicationController in the role communicationController.]

[constr_5332] Mandatory multicast endpoint in case of multicastThreshold different from 0

Imposition time: IT_Mani

[If SomeipProvidedEventGroup.multicastThreshold is configured to a value different from 0, then

- SomeipProvidedEventGroup.eventMulticastUdpPort

and either

- SomeipProvidedEventGroup.ipv4MulticastIpAddress or
- SomeipProvidedEventGroup.ipv6MulticastIpAddress

]

[constr_5333] No multicast in case of TCP

Imposition time: IT_Mani

[If a SomeipProvidedEventGroup references only SomeipEventDeployments that have the attribute transportProtocol set to tcp (via SomeipProvidedEventGroup.eventGroup.event) then this SomeipProvidedEventGroup shall not have a SomeipProvidedEventGroup.multicastThreshold attribute or shall have the SomeipProvidedEventGroup.multicastThreshold set to 0.]

[constr_5338] ProvidedSomeipServiceInstance shall offer all SomeipEventGroups for subscription

Imposition time: IT_Mani

[In the scope of a ProvidedSomeipServiceInstance, SomeipProvidedEventGroups shall be defined such that

- every aggregated ProvidedSomeipServiceInstance.providedEventGroup references a SomeipEventGroup in the context of the SomeipServiceInterfaceDeployment referenced from the enclosing ProvidedSomeipServiceInstance in the role serviceInterfaceDeployment
- each SomeipEventGroup defined in the scope of the SomeipServiceInterfaceDeployment referenced from the enclosing ProvidedSomeipServiceInstance in the role serviceInterfaceDeployment shall be referenced from exactly one SomeipProvidedEventGroup aggregated in the role providedEventGroup in the scope of the enclosing ProvidedSomeipServiceInstance.

]

[constr_5339] SomeipEventGroups of a SomeipServiceInterfaceDeployment shall be referenced at most once from a RequiredSomeipServiceInstance that instantiates the SomeipServiceInterfaceDeployment

Imposition time: IT_Mani

[Each `SomeipEventGroup` that is defined in a `SomeipServiceInterfaceDeployment` shall be referenced at most once from a `SomeipRequiredEventGroup` that is aggregated by the `RequiredSomeipServiceInstance` that is referencing the `SomeipServiceInterfaceDeployment` in the role `serviceInterfaceDeployment`.]

[constr_5343] Usage of `DoIpNetworkConfiguration.eidRetrieval`

Imposition time: IT_Mani

[If `DoIpNetworkConfiguration.eidRetrieval` is set to `eidUseConfigValue` then `DoIpInstantiation.doIpDesign.eid` shall exist and a value shall be assigned to it.]

[constr_5347] Supported value range for attribute `SecOcSecureComProps.authenticationVerifyAttempts`

Imposition time: IT_Mani

[The supported value range of attribute `SecOcSecureComProps.authenticationVerifyAttempts` is limited to the interval [0..65535].]

[constr_5348] Mandatory `initialMode` in `ModeDeclarationGroup` that is referenced by `StateDependentFirewall`

Status: DRAFT

Imposition time: IT_Mani

[The `ModeDeclarationGroup` that is referenced via a `ModeDeclaration` from `StateDependentFirewall` in the role `firewallState` shall define an `initialMode`.]

[constr_5349] Mandatory `defaultAction` in `StateDependentFirewall`

Status: DRAFT

Imposition time: IT_Mani

[The `StateDependentFirewall` shall always define the attribute `defaultAction`.]

[constr_5350] Mandatory `action` in `FirewallRuleProps`

Status: DRAFT

Imposition time: IT_Mani

[The `FirewallRuleProps` shall always define the attribute `action`.]

[constr_5351] FirewallRule is allowed to aggregate at most one protocol subelement*Status:* DRAFT*Imposition time:* IT_Mani

[A FirewallRule is allowed to aggregate either:

- someipSdRule
- someipRule
- doIpRule

]

[constr_5352] DdsRule.submessageType value restriction*Status:* DRAFT*Imposition time:* IT_Mani

[The value of DdsRule.submessageType is restricted to the following values:

- 0x01 (PAD)
- 0x06 (ACKNACK)
- 0x07 (HEARTBEAT)
- 0x08 (GAP)
- 0x09 (INFO_TS)
- 0x0c (INFO_SRC)
- 0x0d (INFO_REPLY_IP4)
- 0x0e (INFO_DST)
- 0x0f (INFO_REPLY)
- 0x12 (NACK_FRAG)
- 0x13 (HEARTBEAT_FRAG)
- 0x15 (DATA)
- 0x16 (DATA_FRAG)

]

[constr_5353] DdsRule.readerEntityId and DdsRule.writerEntityId value restriction*Status:* DRAFT*Imposition time:* IT_Mani

[The value of DdsRule.readerEntityId and DdsRule.writerEntityId is only allowed to be set if the value of DdsRule.submessageType is set to one of the following values:

- 0x06 (ACKNACK)
- 0x07 (HEARTBEAT)
- 0x08 (GAP)
- 0x15 (DATA)

]

[constr_5355] *SomeipServiceInstanceToMachineMapping* with configured remote peer addresses shall not mix *ProvidedSomeipServiceInstances* and *RequiredSomeipServiceInstances*

Imposition time: IT_Mani

[A *SomeipServiceInstanceToMachineMapping* that contains a reference to a *SomeipRemoteUnicastConfig* with the *remoteUnicastConfig* shall not reference:

- *ProvidedSomeipServiceInstances* in the role *serviceInstance* and
- *RequiredSomeipServiceInstances* in the role *serviceInstance* at the same time.

]

[constr_5356] *RequiredSomeipServiceInstance* is allowed to have only a single statically configured remote peer as service provider

Imposition time: IT_Mani

[A *SomeipServiceInstanceToMachineMapping* that contains references to a *RequiredSomeipServiceInstance* with the *serviceInstance* is allowed to reference only a single *SomeipRemoteUnicastConfig* in the role *remoteUnicastConfig*.]

[constr_5357] *SomeipRemoteMulticastConfig* shall only be used on required side

Imposition time: IT_Mani

[Only a *SomeipServiceInstanceToMachineMapping* that contains references to one or several *RequiredSomeipServiceInstances* with the *serviceInstance* role is allowed to reference one or several *SomeipRemoteMulticastConfigs* in the role *remoteUnicastConfig*.]

[constr_5358] *AdaptiveFirewallToPortPrototypeMapping.rPortPrototype* restriction

Status: DRAFT

Imposition time: IT_Mani

[The *AdaptiveFirewallToPortPrototypeMapping* is only allowed to reference a *RPortPrototype* that is typed by the *FirewallStateSwitchInterface*. This rule shall be imposed.]

[constr_5366] Allowed target of `ComEventGrant.serviceDeployment` reference*Status:* DRAFT*Imposition time:* IT_Mani

[`ComEventGrant` is allowed to reference only a `ServiceEventDeployment` in the role `serviceDeployment` that in turn references a `VariableDataPrototype` in the role `event`.]

[constr_5367] Allowed target of `ComTriggerGrant.serviceDeployment` reference*Status:* DRAFT*Imposition time:* IT_Mani

[`ComTriggerGrant` is allowed to reference only a `ServiceEventDeployment` in the role `serviceDeployment` that in turn references a `Trigger` in the role `trigger`.]

[constr_5368] Multiplicity of the reference in the role `ComTriggerGrant.serviceDeployment`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `ComTriggerGrant`, the reference in the role `serviceDeployment` shall exist.]

[constr_5372] SecureComProps for a PlatformModuleEthernetEndpointConfiguration that contains a UDP configuration*Imposition time:* IT_Mani

[Only a `PlatformModuleEthernetEndpointConfiguration` that is referencing an `ApApplicationEndpoint` in the role `udpPort` is allowed to reference `SecureComProps` in the role `secureComPropsForUdp`.]

[constr_5373] SecureComProps for a PlatformModuleEthernetEndpointConfiguration that contains a TCP configuration*Imposition time:* IT_Mani

[Only a `PlatformModuleEthernetEndpointConfiguration` that is referencing an `ApApplicationEndpoint` in the role `tcpPort` is allowed to reference `SecureComProps` in the role `secureComPropsForTcp`.]

[constr_5381] Modeling of Security Event reports by FunctionalCluster shall not be done via `ProcessToMachineMapping`*Imposition time:* IT_Mani

[If a `Process` is mapped by the `ProcessToMachineMapping` and this `ProcessToMachineMapping` references a `NonOsModuleInstantiation` in the role `nonOsModuleInstantiation`, then this `Process` shall not be referenced by a `SecurityEventMapping` in the role `process`.]

[constr_5392] Assignment of the same `event` to several `SomeipEventGroups` is forbidden in case one of the `SomeipEventGroups` has the `multicastThreshold` set to a value greater than 0

Imposition time: IT_Mani

[The same `SomeipEventDeployment` (Event) shall not be referenced by several `SomeipEventGroups` if these `SomeipEventGroups`

- are referenced by different `SomeipProvidedEventGroups` in the context of one `Machine` and
- one or more of these `SomeipProvidedEventGroups` has the `multicastThreshold` set to a value >0

except for the case that all these `SomeipProvidedEventGroups` have the `multicastThreshold` set to the value 1.]

[constr_6815] Existence of `CppTemplateArgument.templateType` for `CppImplementationDataType` of category `STRING`

Imposition time: IT_BefAraApiGen

[In a `CppImplementationDataType` of category `STRING`, the reference `templateType` shall not exist.]

[constr_6905] `CppTemplateArgument allocator`

Imposition time: IT_BefAraApiGen

[The reference `CppTemplateArgument.allocator` shall only exist if the `StdCppImplementationDataType.category` is set to either of the values:

- `STRING`
- `VECTOR`
- `ASSOCIATIVE_MAP`

]

[constr_9323] Restriction of `DoIpFunctionalClusterDesign` on a `MachineDesign`

Imposition time: IT_SysDes

[Each `MachineDesign` shall aggregate at most one `DoIpFunctionalClusterDesign` in the role `functionalClusterDesign`.]

[constr_9324] Allowed `PlatformModuleEthernetEndpointConfiguration.communicationConnector` references

Imposition time: IT_SysDes

[The `PlatformModuleEthernetEndpointConfiguration` that is referenced by a `DoIpNetworkConfigurationDesign` shall only reference `EthernetCommunicationConnectors` that are aggregated by the `MachineDesign` that is also aggre-

gating the `DoIpNetworkConfigurationDesign` via the `DoIpFunctionalClusterDesign`.]

[constr_9325] `DoIpFunctionalClusterDesign.doIpLogicalAddress.logicalAddress` shall be within the physical address boundaries defined by `DoIpRequestConfiguration`

Imposition time: IT_SysDes

[The value of `DoIpFunctionalClusterDesign.doIpLogicalAddress.logicalAddress` shall be within the physical address boundaries defined by `DoIpRequestConfiguration` that is aggregated by the `DoIpFunctionalClusterDesign` in the role `requestConfigurationDesign`.]

[constr_9327] SOME/IP segment reception monitoring allowed for udp Someip EventDeployments

Imposition time: IT_Mani

[Attribute `SomeipEventDeployment.segmentReceptionTimeoutTime` shall only be used if the value of attribute `SomeipEventDeployment.transportProtocol` is set to `udp`.]

[constr_9328] Reception Monitoring of SOME/IP segments is allowed for udp SomeipMethodDeployments

Imposition time: IT_Mani

[`SomeipMethodDeployment.segmentReceptionTimeoutTimeRequest` and `SomeipMethodDeployment.segmentReceptionTimeoutTimeResponse` shall only be used if the value of attribute `SomeipMethodDeployment.transportProtocol` is set to `udp`.]

[constr_9329] Allowed `PlatformModuleEthernetEndpointConfiguration.tcpPort` and `PlatformModuleEthernetEndpointConfiguration.udpPort` references

Imposition time: IT_Mani

[The `PlatformModuleEthernetEndpointConfiguration` shall only reference `ApApplicationEndpoints` in the role `tcpPort` and `udpPort` that are aggregated by the `EthernetCommunicationConnector` that is also referenced by the same `PlatformModuleEthernetEndpointConfiguration` in the role `communicationConnector`.]

[constr_9334] Supported value range for attribute `GenericTpConnection.sourceAddressRangeStart`

Imposition time: IT_Mani

[The supported value range of attribute `GenericTpConnection.sourceAddressRangeStart` is limited to the interval 0..65535.]

[constr_9335] Supported value range for attribute `GenericTpConnection.sourceAddressRangeEnd`*Imposition time:* IT_Mani

[The supported value range of attribute `GenericTpConnection.sourceAddressRangeEnd` is limited to the interval 0..65535.]

[constr_9336] `DoIpNetworkConfigurationDesign` shall reference a `GenericTpConnection`*Imposition time:* IT_SysDes

[Each `DoIpNetworkConfigurationDesign` element shall reference at least one `GenericTpConnection` in the role `tpConnection`.]

[constr_9337] Same `priority` for overlapping address ranges in the context of the same `MachineDesign`*Imposition time:* IT_SysDes

[All `GenericTpConnections` referenced in the scope of the same `MachineDesign` that have an overlapping range defined by `sourceAddressRangeStart` and `sourceAddressRangeEnd` shall also define the identical values of attribute `priority`.]

[constr_9338] `GenericTpConnection.sourceAddressRangeStart` shall be less or equal of `GenericTpConnection.sourceAddressRangeEnd`*Imposition time:* IT_Mani

[The value of `GenericTpConnection.sourceAddressRangeStart` shall be less or equal the value of `GenericTpConnection.sourceAddressRangeEnd`.]

[constr_9344] Supported value range for attribute `DoIpFunctionalClusterDesign.doIpProtocolVersion`*Imposition time:* IT_SysDes

[The supported value range of attribute `DoIpFunctionalClusterDesign.doIpProtocolVersion` is limited to the interval [2..4].]

[constr_9350] All Provided Service Instances using the same UDP endpoint shall use the same DTLS SERVER configuration settings*Imposition time:* IT_Mani

[If more than one `SomeipServiceInstanceToMachineMapping` is referencing a `ProvidedSomeipServiceInstance` and all these `SomeipServiceInstanceToMachineMappings` are referencing the same `ApApplicationEndpoint` in the role `udpPort` and the same `EthernetCommunicationConnector` in the role `communicationConnector` then all these `SomeipServiceInstanceToMachineMappings` shall reference the same `TlsSecureComProps` with category `TLS_SERVER` in the role `secureComPropsForUdp`.]

[constr_9351] All Provided Service Instances using the same TCP endpoint shall use the same TLS SERVER configuration settings

Imposition time: IT_Mani

[If more than one `SomeipServiceInstanceToMachineMapping` is referencing a `ProvidedSomeipServiceInstance` and all these `SomeipServiceInstanceToMachineMappings` are referencing the same `ApApplicationEndpoint` in the role `tcpPort` and the same `EthernetCommunicationConnector` in the role `communicationConnector` then all these `SomeipServiceInstanceToMachineMappings` shall reference the same `TlsSecureComProps` with category `TLS_SERVER` in the role `secureComPropsForTcp`.]

[constr_9352] Mutual exclusive existence of `RemoteEndpointConfiguration.tcpPort` and `RemoteEndpointConfiguration.udpPort`

Imposition time: IT_Mani

[For each `RemoteEndpointConfiguration`, either the attribute `udpPort` or the attribute `tcpPort` shall exist.]

[constr_9353] Mutual exclusive existence of `RemoteEndpointConfiguration.ipv4Address` and `RemoteEndpointConfiguration.ipv6Address`

Imposition time: IT_Mani

[For each `RemoteEndpointConfiguration`, either the attribute `ipv4Address` or the attribute `ipv6Address` shall exist.]

[constr_9356] Upper multiplicity of reference in the role `DoIpNetworkConfigurationDesign.networkConfiguration`

Imposition time: IT_SysDes

[In the context of `DoIpNetworkConfigurationDesign`, the reference in the role `networkConfiguration` shall exist at most once.]

[constr_9370] `ApSomeipTransformationProps` shall be defined at most once for a `ServiceInterface` element

Imposition time: IT_BefAraApiGen

[For each `ServiceInterface` element (i.e. an `event`, `field`, `methodCall` or `methodReturn`) at most one `TransformationPropsToServiceInterfaceElementMapping` shall be defined that references `ApSomeipTransformationProps` in the role `transformationProps`.]

[constr_9392] Existence of reference `TraceSwitchConfig.traceMessage`

Imposition time: IT_BefAraApiGen

[The reference in the role `TraceSwitchConfig.traceMessage` shall exist.]

[constr_9393] Existence of attribute `TraceSwitchConfig.traceSwitch`*Imposition time:* IT_BefAraApiGen

[The attribute `TraceSwitchConfig.traceSwitch` shall exist.]

[constr_9394] Existence of reference `TraceSwitchConfig.executable`*Imposition time:* IT_BefAraApiGen

[The reference in the role `TraceSwitchConfig.executable` shall exist.]

[constr_10002] Only one mapping per `PortPrototype`*Imposition time:* IT_DiagDes

[If one instance of the following sub-classes of `DiagnosticSwMapping` – that refers to a given `ProcessDesign` – refers to a `PortPrototype`, then no other instance of `DiagnosticSwMapping` that refers to the same `ProcessDesign` shall refer to the same `PortPrototype`:

- `DiagnosticEventPortMapping` that is associated with a `RPortPrototype` typed by a `DiagnosticMonitorInterface` or a `DiagnosticEventInterface`.
- `DiagnosticOperationCyclePortMapping` that is associated with a `RPortPrototype` typed by a `DiagnosticOperationCycleInterface`.
- `DiagnosticEnableConditionPortMapping` that is associated with a `RPortPrototype` typed by a `DiagnosticConditionInterface`.
- `DiagnosticClearConditionPortMapping` that is associated with a `RPortPrototype` typed by a `DiagnosticConditionInterface`.
- `DiagnosticIndicatorPortMapping` that is associated with a `RPortPrototype` typed by a `DiagnosticIndicatorInterface`.
- `DiagnosticMemoryDestinationPortMapping` that is associated with an `RPortPrototype` typed by a `DiagnosticDTCInformationInterface`.
- `DiagnosticSecurityLevelPortMapping` that is associated with a `PPortPrototype` typed by a `DiagnosticSecurityLevelInterface`.
- `DiagnosticDataPortMapping` that is associated with a `PPortPrototype` typed by a `DiagnosticDataIdentifierInterface`.
- `DiagnosticSecurityLevelPortMapping` that is associated with a `PPortPrototype` typed by a `DiagnosticSecurityLevelInterface`.
- `DiagnosticServiceValidationMapping` that is associated with a `PPortPrototype` typed by a `DiagnosticServiceValidationInterface`.

]

[constr_10003] Restriction for the existence of `DiagnosticDataPortMapping.diagnosticDataIdentifier` vs. `DiagnosticDataPortMapping.diagnosticDataElement`

Imposition time: IT_DiagDes

[For each `DiagnosticDataPortMapping`, **either** the reference in the role `diagnosticDataIdentifier` **or** `diagnosticDataElement` shall exist.]

[constr_10021] Existence of `IdsmModuleInstantiation`

Status: DRAFT

Imposition time: IT_Mani

[On each `Machine`, only one instance of the Intrusion Detection System Manager (modeled by `IdsmModuleInstantiation`) shall exist.]

[constr_10023] Mandatory content of any `functionGroup`

Imposition time: IT_Mani

[All `ModeDeclarationGroupPrototypes` aggregated by a `FunctionGroupSet` in the role `functionGroup` shall refer to a `ModeDeclarationGroup` that contains one `ModeDeclaration` with the `shortName` `Verify`.]

[constr_10029] `ServiceInterfaceDeployment` (except `DdsServiceInterfaceDeployment`) shall cover all elements of the corresponding `ServiceInterface`

Imposition time: IT_Mani

[With the exception of `DdsServiceInterfaceDeployment`, if a `ServiceInterfaceDeployment` references a `ServiceInterface` in the role `serviceInterface`, then all `methods`, `fields`, `triggers`, and `events` defined in the context of the referenced `ServiceInterface` shall be referenced by respective `methodDeployments`, `fieldDeployments`, and `eventDeployments` owned by the referencing `ServiceInterfaceDeployment`.]

[constr_10030] Existence of `DiagnosticDataIdentifierInterface.read`

Imposition time: IT_BefAraApiGen

[Attribute `DiagnosticDataIdentifierInterface.read` shall exist.]

[constr_10031] Existence of `DiagnosticRoutineInterface.start`

Imposition time: IT_BefAraApiGen

[Attribute `DiagnosticRoutineInterface.start` shall exist.]

[constr_10035] Completeness of the `PersistencyDeployment.version`

Imposition time: IT_Mani

[The `PersistencyDeployment.version` shall contain all the following parts:

- Major version

- Minor version
- Patch version
- Additional labels for pre-release version and build metadata

]

[constr_10037] Existence of attribute `TagWithOptionalValue.sequenceOffset` in the context of attribute `capabilityRecord` owned by `ProvidedSomeipServiceInstance`, `RequiredSomeipServiceInstance`, or `AbstractServiceInstance`

Imposition time: IT_Mani

[For all `capabilityRecord` modeled in the context of `ProvidedSomeipServiceInstance`, `RequiredSomeipServiceInstance`, or `AbstractServiceInstance`, attribute `TagWithOptionalValue.sequenceOffset` shall not exist.]

[constr_10046] Value of `PersistencyRedundancyMOutOfN.n`

Imposition time: IT_BefAraApiGen

[The value of attribute `PersistencyRedundancyMOutOfN.n` shall be set at least to 2 and at most to 255, i.e. the allowed interval is [2..255].]

[constr_10047] Restriction for the applicability of `DiagnosticMonitorPortMapping`

Imposition time: IT_DiagDes

[If an `RPortPrototype` is referenced by a `DiagnosticMonitorPortMapping`, then the `RPortPrototype` shall be typed by a `DiagnosticMonitorInterface`.]

[constr_10048] Existence of reference from `DiagnosticMonitorPortMapping` to `DiagnosticEvent`

Imposition time: IT_DiagDes

[Each `DiagnosticEvent` shall only be referenced by exactly one `DiagnosticMonitorPortMapping` or `DiagnosticMultipleMonitorPortMapping`.]

[constr_10049] Restriction for the applicability of `DiagnosticEventPortMapping`

Imposition time: IT_DiagDes

[If an `RPortPrototype` is referenced by a `DiagnosticEventPortMapping`, then the `RPortPrototype` shall be typed by a `DiagnosticEventInterface`.]

[constr_10050] Restriction for the applicability of [DiagnosticOperationCyclePortMapping](#)*Imposition time:* IT_DiagDes

[If an [RPortPrototype](#) is referenced by a [DiagnosticOperationCyclePortMapping](#), then the [RPortPrototype](#) shall be typed by a [DiagnosticOperationCycleInterface](#).]

[constr_10051] Existence of reference from [DiagnosticOperationCyclePortMapping](#) to [DiagnosticOperationCycle](#)*Imposition time:* IT_DiagDes

[Each [DiagnosticOperationCycle](#) shall only be referenced by exactly one [DiagnosticOperationCyclePortMapping](#).]

[constr_10052] Restriction for the applicability of [DiagnosticEnableConditionPortMapping](#)*Imposition time:* IT_DiagDes

[If an [RPortPrototype](#) is referenced by a [DiagnosticEnableConditionPortMapping](#), then the [RPortPrototype](#) shall be typed by a [DiagnosticConditionInterface](#).]

[constr_10053] Existence of reference from [DiagnosticEnableConditionPortMapping](#) to [DiagnosticEnableCondition](#)*Imposition time:* IT_DiagDes

[Each [DiagnosticEnableCondition](#) shall only be referenced by at most one [DiagnosticEnableConditionPortMapping](#).]

[constr_10054] Restriction for the applicability of [DiagnosticClearConditionPortMapping](#)*Imposition time:* IT_DiagDes

[If an [RPortPrototype](#) is referenced by a [DiagnosticClearConditionPortMapping](#), then the [RPortPrototype](#) shall be typed by a [DiagnosticConditionInterface](#).]

[constr_10055] Existence of reference from [DiagnosticClearConditionPortMapping](#) to [DiagnosticClearCondition](#)*Imposition time:* IT_DiagDes

[Each [DiagnosticClearCondition](#) shall only be referenced by at most one [DiagnosticClearConditionPortMapping](#).]

[constr_10056] Restriction for the applicability of `DiagnosticIndicatorPortMapping`*Imposition time:* IT_DiagDes

[If an `RPortPrototype` is referenced by a `DiagnosticIndicatorPortMapping`, then the `RPortPrototype` shall be typed by a `DiagnosticIndicatorInterface`.]

[constr_10057] Restriction for the applicability of `DiagnosticMemoryDestinationPortMapping`*Imposition time:* IT_DiagDes

[If an `RPortPrototype` is referenced by a `DiagnosticMemoryDestinationPortMapping`, then the `RPortPrototype` shall be typed by a `DiagnosticDTCInformationInterface`.]

[constr_10058] Restriction for the applicability of `DiagnosticSecurityLevelPortMapping`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is referenced by a `DiagnosticSecurityLevelPortMapping`, then the `PPortPrototype` shall be typed by a `DiagnosticSecurityLevelInterface`.]

[constr_10059] Existence of reference from `DiagnosticSecurityLevelPortMapping` to `DiagnosticSecurityLevel`*Imposition time:* IT_DiagDes

[Each `DiagnosticSecurityLevel` shall only be referenced by exactly one `DiagnosticSecurityLevelPortMapping`.]

[constr_10060] `PortInterface` of `PPortPrototype` referenced by `DiagnosticDataPortMapping`*Imposition time:* IT_DiagDes

[Any particular `PPortPrototype` that is referenced in the role `DiagnosticDataPortMapping.pPortPrototypeInExecutable` shall be typed by either of

- `DiagnosticDataIdentifierInterface`
- `DiagnosticDataElementInterface`
- `DiagnosticDataIdentifierGenericInterface`

]

[constr_10061] Mapping to `DiagnosticDataIdentifierInterface`, `DiagnosticDataElementInterface`, or `DiagnosticDataIdentifierGenericInterface`*Imposition time:* IT_DiagDes

[All `PPortPrototypes` typed by either

- [DiagnosticDataIdentifierInterface](#)
- [DiagnosticDataElementInterface](#)
- [DiagnosticDataIdentifierGenericInterface](#)

shall **only** be referenced by a [DiagnosticDataPortMapping](#). No other subclass of [DiagnosticSwMapping](#) is eligible for this purpose.]

[constr_10063] Possible values for [DiagnosticServiceValidationMapping.category](#)

Imposition time: IT_DiagDes

[The value of attribute [DiagnosticServiceValidationMapping.category](#) is restricted to the following values:

MANUFACTURER_VALIDATION The enclosing [DiagnosticServiceValidationMapping](#) represents a validation defined by the manufacturer.

SUPPLIER_VALIDATION The enclosing [DiagnosticServiceValidationMapping](#) represents a validation defined by the supplier.

]

[constr_10064] Existence of [DiagnosticServiceValidationMapping.pPortPrototypeInExecutable](#)

Imposition time: IT_DiagDes

[A [PPortPrototype](#) referenced in the role [DiagnosticServiceValidationMapping.pPortPrototypeInExecutable](#) shall be typed by a [DiagnosticServiceValidationInterface](#).]

[constr_10065] Validity of [DiagnosticServiceValidationConfiguration.manufacturerValidationOrder](#)

Imposition time: IT_Mani

[Any [DiagnosticServiceValidationConfiguration.manufacturerValidationOrder](#) shall only refer to a [DiagnosticServiceValidationMapping](#) where attribute [category](#) has been set to **MANUFACTURER_VALIDATION**.]

[constr_10066] Validity of [DiagnosticServiceValidationConfiguration.supplierValidationOrder](#)

Imposition time: IT_Mani

[Any [DiagnosticServiceValidationConfiguration.supplierValidationOrder](#) shall only refer to a [DiagnosticServiceValidationMapping](#) where attribute [category](#) has been set to **SUPPLIER_VALIDATION**.]

[constr_10069] Existence of `SoftwareClusterDiagnosticDeploymentProps.powerDownTime`

Imposition time: IT_Mani

[The attribute `SoftwareClusterDiagnosticDeploymentProps.powerDownTime` shall exist and have a value between 0 and 254 if the referenced `diagnosticExtract` that in turn references in the role `element` a `DiagnosticEcuReset` where attribute `category` is set to the value `ENABLE_RAPID_POWER_SHUT_DOWN`.]

[constr_10070] Value of `RequiredSomeipServiceInstance.requiredServiceInstanceId`

Imposition time: IT_Mani

[For each `RequiredSomeipServiceInstance.requiredServiceInstanceId`, the value shall be in the range 0..65534 or `ALL`.]

[constr_10076] Existence of `RawDataStreamEthernetUdpCredentials.udpPort`

Imposition time: IT_Mani

[In the context of `RawDataStreamEthernetUdpCredentials`, the attribute `udpPort` shall exist.]

[constr_10077] Existence of `ipV4Address` and `ipV6Address` within `AbstractRawDataStreamEthernetCredentials`

Imposition time: IT_Mani

[Within the context of a `AbstractRawDataStreamEthernetCredentials`, either the attribute `ipV4Address` or the attribute `ipV6Address` shall exist.]

[constr_10078] Existence of `RawDataStreamEthernetTcpUdpCredentials.tcpPort` and `udpPort`

Imposition time: IT_Mani

[In the context of a `RawDataStreamEthernetTcpUdpCredentials`, either the attribute `tcpPort` or `udpPort` shall exist.]

[constr_10079] Existence of `EthernetRawDataStreamMapping.localTcpPort` and `localUdpPort`

Imposition time: IT_Mani

[In the context of a `EthernetRawDataStreamMapping.localCommConnector`, only **one** attribute out of

- `localTcpPort`
- `localUdpPort`

shall exist.]

[constr_10080] Existence of initial values for `PersistencyFileElement`*Imposition time:* IT_BefAraApiGen

[For each `PersistencyFileElement`, if the value of attribute `updateStrategy` is set to the value `delete`, then attribute `PersistencyFileElement.contentUri` shall not exist.]

[constr_10081] Existence of initial values in the definition of `PersistencyDataRequiredComSpec`*Imposition time:* IT_BefAraApiGen

[For each `PersistencyDataRequiredComSpec`, if the value of attribute `dataElement.updateStrategy` is set to the value `delete`, then attribute `PersistencyDataRequiredComSpec.initValue` shall not exist.]

[constr_10082] Existence of initial values for `PersistencyFile`*Imposition time:* IT_Mani

[For each `PersistencyFile`, if the value of attribute `updateStrategy` is set to the value `delete`, then attribute `PersistencyFile.contentUri` shall not exist.]

[constr_10083] Existence of initial values for `PersistencyKeyValuePair`*Imposition time:* IT_Mani

[For each `PersistencyKeyValuePair`, if the value of attribute `updateStrategy` is set to the value `delete`, then attribute `PersistencyKeyValuePair.initValue` shall not exist.]

[constr_10086] Existence of `unicastUdpCredentials` and `multicastCredentials` in the context of a `EthernetRawDataStreamServerMapping`*Imposition time:* IT_Mani

[In the context of a `EthernetRawDataStreamServerMapping`, only one aggregation out of

- `remoteClientConfig.multicastCredentials`
- `remoteClientConfig.unicastUdpCredentials`

shall exist.]

[constr_10090] Existence of `ProcessToMachineMapping.persistencyCentralStorageURI`*Imposition time:* IT_Mani

[Attribute `ProcessToMachineMapping.persistencyCentralStorageURI` shall exist if the `Process` referenced in the role `ProcessToMachineMapping.process` is also referenced by at least one of

- `PersistencyPortPrototypeToDeploymentMapping` in the role `process`

- `FunctionalClusterInteractsWithPersistencyDeploymentMapping` in the role `process`

]

[constr_10092] Restriction for the applicability of `DiagnosticAuthenticationPortMapping`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is referenced by a `DiagnosticAuthenticationPortMapping`, then the `PPortPrototype` shall be typed by a `DiagnosticAuthenticationInterface`.]

[constr_10093] Existence of reference from `DiagnosticAuthenticationPortMapping` to `DiagnosticAuthentication`*Imposition time:* IT_DiagDes

[Each `DiagnosticAuthentication` shall only be referenced by exactly one `DiagnosticAuthenticationPortMapping`.]

[constr_10094] Restriction for the applicability of `DiagnosticExternalAuthenticationPortMapping`*Imposition time:* IT_DiagDes

[If an `RPortPrototype` is referenced by a `DiagnosticExternalAuthenticationPortMapping`, then the `RPortPrototype` shall be typed by a `DiagnosticExternalAuthenticationInterface`.]

[constr_10098] Relation of `MachineDesign.pnResetTimer` and `UdpNmCluster.nmMsgCycleTime`*Imposition time:* IT_Mani

[For the configuration of the partial networking timing, the following condition shall be ensured: `MachineDesign.pnResetTimer` > `UdpNmCluster.nmMsgCycleTime`.]

[constr_10101] Attribute `NmHandleToFunctionGroupStateMapping.mappingDirection` is set to `nmHandleActiveToFunctionGroupState` or `nmHandleInactiveToFunctionGroupState`*Imposition time:* IT_Mani

[If the value of attribute `NmHandleToFunctionGroupStateMapping.mappingDirection` is set to the value `NmHandleMappingDirectionEnum.nmHandleActiveToFunctionGroupState` or `NmHandleMappingDirectionEnum.nmHandleInactiveToFunctionGroupState`, then the reference `NmHandleToFunctionGroupStateMapping.functionGroupState` shall not refer to two (or more) **ModeDeclarations of the same `ModeDeclarationGroup`**.]

[constr_10102] Existence of initial values for `PersistencyKeyValuePair`*Imposition time:* IT_Mani

[For each `PersistencyKeyValuePair`, if the value of attribute `updateStrategy` is set to either of the values

- `keepExisting` or
- `overwrite`,

then attribute `PersistencyKeyValuePair.initValue` shall exist.]

[constr_10103] Existence of initial values for `PersistencyFile`*Imposition time:* IT_Mani

[For each `PersistencyFile`, if the value of attribute `updateStrategy` is set to either of the values

- `keepExisting` or
- `overwrite`,

then attribute `PersistencyFile.contentUri` shall exist.]

[constr_10105] Existence of `UcmRetryStrategy.maximumNumberOfRetries`*Imposition time:* IT_Mani

[For each `UcmRetryStrategy`, attribute `maximumNumberOfRetries` shall exist.]

[constr_10106] Existence of `UcmRetryStrategy.retryIntervalTime`*Imposition time:* IT_Mani

[For each `UcmRetryStrategy`, attribute `retryIntervalTime` shall exist.]

[constr_10107] Existence of the attribute `UcmMasterModuleInstantiation.blockInconsistent`*Imposition time:* IT_Mani

[The attribute `UcmMasterModuleInstantiation.blockInconsistent` shall.]

[constr_10108] Existence of the attribute `UcmMasterModuleInstantiation.serviceBusy`*Imposition time:* IT_Mani

[The attribute `UcmMasterModuleInstantiation.serviceBusy` shall exist.]

[constr_10109] Existence of the attribute `UcmMasterModuleInstantiation.updateSessionRejected`*Imposition time:* IT_Mani

[The attribute `UcmMasterModuleInstantiation.updateSessionRejected` shall exist.]

[constr_10110] Existence of `UcmSubordinateModuleInstantiation` on a `Machine`*Imposition time:* IT_Mani

[For each `Machine`, a `ProcessToMachineMapping` shall exist that refers in the role `machine` to the `Machine` and in the role `nonOsModuleInstantiation` to a `UcmSubordinateModuleInstantiation`.]

[constr_10113] Restriction for the existence of `ExecutableLoggingImplementationProps`*Imposition time:* IT_BefAraApiGen

[The aggregation of `ExecutableLoggingImplementationProps` in the role `Executable.implementationProps` is only allowed for an `Executable` where attribute `category` is set to the value `PLATFORM_LEVEL`.]

[constr_10114] Existence of attributes of `DiagnosticEnvDataElementCondition` if the reference in the role `pPortPrototype` exists*Imposition time:* IT_DiagDes

[If the reference in the role `DiagnosticEnvDataElementCondition.pPortPrototype` exists, then the aggregations in the roles `compareValue`, `process`, and `swDataDefProps` shall exist.]

[constr_10124] Multiplicity of attribute `ApplicationAssocMapDataType.key`*Imposition time:* IT_BefAraApiGen

[For each `ApplicationAssocMapDataType`, the attribute `key` shall exist.]

[constr_10125] Multiplicity of attribute `ApplicationAssocMapDataType.value`*Imposition time:* IT_BefAraApiGen

[For each `ApplicationAssocMapDataType`, the attribute `value` shall exist.]

[constr_10126] Multiplicity of attribute `ApplicationAssocMapElementValueSpecification.key`*Imposition time:* IT_BefAraApiGen

[For each `ApplicationAssocMapElementValueSpecification`, the attribute `key` shall exist.]

[constr_10127] Multiplicity of attribute `ApplicationAssocMapElementValueSpecification.value`*Imposition time:* IT_BefAraApiGen

[For each `ApplicationAssocMapElementValueSpecification`, the attribute `value` shall exist.]

[constr_10128] Multiplicity of attribute `CppImplementationDataTypeElementQualifier.typeReference`*Imposition time:* IT_BefAraApiGen

[For each `CppImplementationDataTypeElementQualifier`, the attribute `typeReference` shall exist.]

[constr_10129] Multiplicity of attribute `Field.hasGetter`*Imposition time:* IT_BefAraApiGen

[For each `Field`, the attribute `hasGetter` shall exist.]

[constr_10130] Multiplicity of attribute `Field.hasSetter`*Imposition time:* IT_BefAraApiGen

[For each `Field`, the attribute `hasSetter` shall exist.]

[constr_10131] Multiplicity of attribute `Field.hasNotifier`*Imposition time:* IT_BefAraApiGen

[For each `Field`, the attribute `hasNotifier` shall exist.]

[constr_10132] Multiplicity of attribute `ApApplicationError.errorCode`*Imposition time:* IT_BefAraApiGen

[For each `ApApplicationError`, the attribute `errorCode` shall exist.]

[constr_10133] Multiplicity of attribute `ApApplicationErrorDomain.value`*Imposition time:* IT_BefAraApiGen

[For each `ApApplicationErrorDomain`, the attribute `value` shall exist.]

[constr_10134] Multiplicity of reference in the role `PortInterfaceToDataTypeMapping.dataTypeMappingSet`*Imposition time:* IT_BefAraApiGen

[For each `PortInterfaceToDataTypeMapping`, the reference in the role `dataTypeMappingSet` shall exist at least once.]

[constr_10135] Multiplicity of reference in the role `PortInterfaceToDataTypeMapping.portInterface`*Imposition time:* IT_BefAraApiGen

[For each `PortInterfaceToDataTypeMapping`, the reference in the role `portInterface` shall exist.]

[constr_10136] Multiplicity of reference in the role `ServiceInterfaceMapping.compositeServiceInterface`*Imposition time:* IT_BefAraApiGen

[For each `ServiceInterfaceMapping`, the reference in the role `compositeServiceInterface` shall exist.]

[constr_10137] Multiplicity of reference in the role `ServiceInterfaceMapping.sourceServiceInterface`*Imposition time:* IT_BefAraApiGen

[For each `ServiceInterfaceMapping`, the reference in the role `sourceServiceInterface` shall exist at least once.]

[constr_10138] Multiplicity of reference in the role `ServiceInterfaceEventMapping.sourceEvent`*Imposition time:* IT_BefAraApiGen

[For each `ServiceInterfaceEventMapping`, the reference in the role `sourceEvent` shall exist.]

[constr_10139] Multiplicity of reference in the role `ServiceInterfaceEventMapping.targetEvent`*Imposition time:* IT_BefAraApiGen

[For each `ServiceInterfaceEventMapping`, the reference in the role `targetEvent` shall exist.]

[constr_10140] Multiplicity of reference in the role `ServiceInterfaceFieldMapping.sourceField`*Imposition time:* IT_BefAraApiGen

[For each `ServiceInterfaceFieldMapping`, the reference in the role `sourceField` shall exist.]

[constr_10141] Multiplicity of reference in the role `ServiceInterfaceFieldMapping.targetField`*Imposition time:* IT_BefAraApiGen

[For each `ServiceInterfaceFieldMapping`, the reference in the role `targetField` shall exist.]

[constr_10142] Multiplicity of reference in the role `ServiceInterfaceMethodMapping.sourceMethod`*Imposition time:* IT_BefAraApiGen

[For each `ServiceInterfaceMethodMapping`, the reference in the role `sourceMethod` shall exist.]

[constr_10143] Multiplicity of reference in the role `ServiceInterfaceMethodMapping.targetMethod`*Imposition time:* IT_BefAraApiGen

[For each `ServiceInterfaceMethodMapping`, the reference in the role `targetMethod` shall exist.]

[constr_10144] Multiplicity of reference in the role `PersistencyRedundancyChecksum.algorithmFamily`*Imposition time:* IT_BefAraApiGen

[For each `PersistencyRedundancyChecksum`, the reference in the role `algorithmFamily` shall exist.]

[constr_10145] Multiplicity of reference in the role `PersistencyRedundancyChecksum.length`*Imposition time:* IT_BefAraApiGen

[For each `PersistencyRedundancyChecksum`, the reference in the role `length` shall exist.]

[constr_10146] Multiplicity of reference in the role `PersistencyRedundancyMOutOfN.m`*Imposition time:* IT_BefAraApiGen

[For each `PersistencyRedundancyMOutOfN`, the reference in the role `m` shall exist.]

[constr_10147] Multiplicity of reference in the role `PersistencyRedundancyMOutOfN.n`*Imposition time:* IT_BefAraApiGen

[For each `PersistencyRedundancyMOutOfN`, the reference in the role `n` shall exist.]

[constr_10148] Multiplicity of reference in the role `PersistencyFileElement.contentUri`*Imposition time:* IT_BefAraApiGen

[For each `PersistencyFileElement`, the reference in the role `contentUri` shall exist if the value of attribute `updateStrategy` is set to either

- `PersistencyElementLevelUpdateStrategyEnum.keepExisting` or
- `PersistencyElementLevelUpdateStrategyEnum.overwrite`.

]

[constr_10149] Multiplicity of reference in the role `PersistencyFileElement.fileName`*Imposition time:* IT_BefAraApiGen

[For each `PersistencyFileElement`, the reference in the role `fileName` shall exist.]

[constr_10151] Multiplicity of reference in the role `PhmCheckpoint.checkpointId`*Imposition time:* IT_BefAraApiGen[For each `PhmCheckpoint`, the reference in the role `checkpointId` shall exist.]**[constr_10152] Multiplicity of reference in the role `FieldSenderComSpec.initValue`***Imposition time:* IT_BefAraApiGen[For each `FieldSenderComSpec`, the reference in the role `initValue` shall exist.]**[constr_10154] Multiplicity of reference in the role `ProcessDesignToMachineDesignMapping.processDesign`***Imposition time:* IT_SysDes[For each `ProcessDesignToMachineDesignMapping`, the reference in the role `processDesign` shall exist.]**[constr_10155] Multiplicity of reference in the role `ComOfferServiceGrantDesign.providedServicePort`***Status:* DRAFT*Imposition time:* IT_GraDes[For each `ComOfferServiceGrantDesign`, the reference in the role `providedServicePort` shall exist.]**[constr_10157] Multiplicity of reference in the role `ComFieldGrantDesign.field`***Status:* DRAFT*Imposition time:* IT_GraDes[For each `ComFieldGrantDesign`, the reference in the role `field` shall exist.]**[constr_10158] Multiplicity of reference in the role `ComFieldGrantDesign.role`***Status:* DRAFT*Imposition time:* IT_GraDes[For each `ComFieldGrantDesign`, the reference in the role `role` shall exist.]**[constr_10159] Multiplicity of reference in the role `ComEventGrantDesign.event`***Status:* DRAFT*Imposition time:* IT_GraDes[For each `ComEventGrantDesign`, the reference in the role `event` shall exist.]

[constr_10160] Multiplicity of reference in the role `ComTriggerGrantDesign.trigger`*Status:* DRAFT*Imposition time:* IT_GraDes[For each `ComTriggerGrantDesign`, the reference in the role `trigger` shall exist.]**[constr_10161] Multiplicity of reference in the role `ComMethodGrantDesign.method`***Status:* DRAFT*Imposition time:* IT_GraDes[For each `ComMethodGrantDesign`, the reference in the role `method` shall exist.]**[constr_10162] Multiplicity of reference in the role `DiagnosticClearConditionPortMapping.clearCondition`***Imposition time:* IT_DiagDes[For each `DiagnosticClearConditionPortMapping`, the reference in the role `clearCondition` shall exist.]**[constr_10163] Multiplicity of reference in the role `DiagnosticIndicatorPortMapping.indicator`***Imposition time:* IT_DiagDes[For each `DiagnosticIndicatorPortMapping`, the reference in the role `indicator` shall exist.]**[constr_10164] Multiplicity of reference in the role `DiagnosticMemoryDestinationPortMapping.memoryDestination`***Imposition time:* IT_DiagDes[For each `DiagnosticMemoryDestinationPortMapping`, the reference in the role `memoryDestination` shall exist.]**[constr_10165] Multiplicity of reference in the role `DiagnosticDataPortMapping.process`***Imposition time:* IT_DiagDes[For each `DiagnosticDataPortMapping`, the reference in the role `process` shall exist.]**[constr_10166] Multiplicity of attribute `DiagnosticProvidedDataMapping.dataProvider`***Imposition time:* IT_DiagDes[For each `DiagnosticProvidedDataMapping`, the attribute `dataProvider` shall exist.]

[constr_10167] Multiplicity of attribute `SomeipServiceDiscovery.someipServiceDiscoveryPort`*Imposition time:* IT_SysDes

[For each `SomeipServiceDiscovery`, the attribute `someipServiceDiscoveryPort` shall exist.]

[constr_10169] Multiplicity of reference in the role `Machine.machineDesign`*Imposition time:* IT_Mani

[For each `Machine`, the reference in the role `machineDesign` shall exist.]

[constr_10170] Multiplicity of attribute `Machine.trustedPlatformExecutableLaunchBehavior`*Imposition time:* IT_Mani

[For each `Machine`, the attribute `trustedPlatformExecutableLaunchBehavior` shall exist.]

[constr_10171] Multiplicity of attribute `Machine.processor`*Imposition time:* IT_Mani

[For each `Machine`, at least one aggregation on the role `processor` shall exist.]

[constr_10172] Multiplicity of attribute `Processor.core`*Imposition time:* IT_SysDes

[For each `Processor`, the attribute `core` shall exist.]

[constr_10173] Multiplicity of attribute `ProcessorCore.coreId`*Imposition time:* IT_SysDes

[For each `ProcessorCore`, the attribute `coreId` shall exist.]

[constr_10174] Multiplicity of the reference in the role `ProcessToMachineMapping.process`*Imposition time:* IT_Mani

[For each `ProcessToMachineMapping`, the reference in the role `process` shall exist.]

[constr_10175] Multiplicity of attribute `StateDependentStartupConfig.resourceGroup`*Imposition time:* IT_Mani

[For each `StateDependentStartupConfig`, the attribute `resourceGroup` shall exist.]

[constr_10176] Multiplicity of attribute `StateDependentStartupConfig.startupConfig`*Imposition time:* IT_Mani

[For each `StateDependentStartupConfig`, the attribute `startupConfig` shall exist.]

[constr_10177] Multiplicity of attribute `PersistencyDeployment.updateStrategy`*Imposition time:* IT_Mani

[For each `PersistencyDeployment`, the attribute `updateStrategy` shall exist.]

[constr_10178] Multiplicity of the reference in the role `PersistencyPortPrototypeToDeploymentMapping.process`*Imposition time:* IT_Mani

[For each `PersistencyPortPrototypeToDeploymentMapping`, the reference in the role `process` shall exist.]

[constr_10179] Multiplicity of attribute `PersistencyKeyValuePair.valueDataType`*Imposition time:* IT_Mani

[For each `PersistencyKeyValuePair`, the attribute `valueDataType` shall exist.]

[constr_10180] Multiplicity of the reference in the role `PersistencyPortPrototypeToKeyValueStorageMapping.keyValueStorage`*Imposition time:* IT_Mani

[For each `PersistencyPortPrototypeToKeyValueStorageMapping`, the reference in the role `keyValueStorage` shall exist.]

[constr_10182] Multiplicity of the reference in the role `PersistencyPortPrototypeToFileStorageMapping.fileStorage`*Imposition time:* IT_Mani

[For each `PersistencyPortPrototypeToFileStorageMapping`, the reference in the role `fileStorage` shall exist.]

[constr_10183] Multiplicity of attribute `PersistencyFile.fileName`*Imposition time:* IT_Mani

[For each `PersistencyFile`, the attribute `fileName` shall exist.]

[constr_10184] Multiplicity of the reference in the role `SynchronizedTimeBaseConsumer.networkTimeConsumer`*Imposition time:* IT_Mani

[For each `SynchronizedTimeBaseConsumer`, the reference in the role `networkTimeConsumer` shall exist.]

[constr_10185] Multiplicity of the reference in the role `SynchronizedTimeBaseProvider.networkTimeProvider`*Imposition time:* IT_Mani

[For each `SynchronizedTimeBaseProvider`, the reference in the role `networkTimeProvider` shall exist.]

[constr_10186] Multiplicity of attribute `DoIpFunctionalClusterDesign.entityStatusMaxByteFieldUse`*Imposition time:* IT_SysDes

[For each `DoIpFunctionalClusterDesign`, the attribute `entityStatusMaxByteFieldUse` shall exist.]

[constr_10188] Multiplicity of attribute `DoIpInstantiation.logicalAddress`*Imposition time:* IT_Mani

[For each `DoIpInstantiation`, the attribute `logicalAddress` shall exist.]

[constr_10189] Multiplicity of attribute `DoIpFunctionalClusterDesign.maxRequestBytes`*Imposition time:* IT_SysDes

[For each `DoIpFunctionalClusterDesign`, the attribute `maxRequestBytes` shall exist.]

[constr_10191] Multiplicity of attribute `DoIpNetworkConfiguration.isActivationLineDependent`*Imposition time:* IT_Mani

[For each `DoIpNetworkConfiguration`, the attribute `isActivationLineDependent` shall exist.]

[constr_10192] Multiplicity of attribute `DoIpNetworkConfiguration.maxInitialVehicleAnnouncementTime`*Imposition time:* IT_Mani

[For each `DoIpNetworkConfiguration`, the attribute `maxInitialVehicleAnnouncementTime` shall exist.]

[constr_10193] Multiplicity of attribute `DoIpNetworkConfiguration.maxTesterConnections`*Imposition time:* IT_Mani

[For each `DoIpNetworkConfiguration`, the attribute `maxTesterConnections` shall exist.]

[constr_10194] Multiplicity of attribute `DoIpNetworkConfiguration.networkInterfaceId`*Imposition time:* IT_Mani

[For each `DoIpNetworkConfiguration`, the attribute `networkInterfaceId` shall exist.]

[constr_10197] Multiplicity of attribute `DoIpRequestConfiguration.endAddress`*Imposition time:* IT_Mani

[For each `DoIpRequestConfiguration`, the attribute `endAddress` shall exist.]

[constr_10198] Multiplicity of attribute `DoIpRequestConfiguration.requestType`*Imposition time:* IT_Mani

[For each `DoIpRequestConfiguration`, the attribute `requestType` shall exist.]

[constr_10199] Multiplicity of attribute `DoIpRequestConfiguration.startAddress`*Imposition time:* IT_Mani

[For each `DoIpRequestConfiguration`, the attribute `startAddress` shall exist.]

[constr_10200] Multiplicity of attribute `UcmModuleInstantiation.identifier`*Imposition time:* IT_Mani

[For each `UcmModuleInstantiation`, the attribute `identifier` shall exist.]

[constr_10201] Multiplicity of of the reference in the role `ComGrant.serviceInstance`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `ComGrant`, the reference in the role `serviceInstance` shall exist.]

[constr_10202] Multiplicity of attribute `ComFieldGrant.role`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `ComFieldGrant`, the attribute `role` shall exist.]

[constr_10203] Multiplicity of the reference in the role `ComFieldGrant.serviceDeployment`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `ComFieldGrant`, the reference in the role `serviceDeployment` shall exist.]

[constr_10204] Multiplicity of the reference in the role `ComMethodGrant.serviceDeployment`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `ComMethodGrant`, the reference in the role `serviceDeployment` shall exist.]

[constr_10205] Multiplicity of the reference in the role `ComEventGrant.serviceDeployment`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `ComEventGrant`, the reference in the role `serviceDeployment` shall exist.]

[constr_10206] Multiplicity of the reference in the role `ComOfferServiceGrant.serviceInstance`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `ComOfferServiceGrant`, the reference in the role `serviceInstance` shall exist.]

[constr_10207] Multiplicity of the reference in the role `CryptoProviderToPortPrototypeMapping.cryptoProvider`*Imposition time:* IT_Mani

[For each `CryptoProviderToPortPrototypeMapping`, the reference in the role `cryptoProvider` shall exist.]

[constr_10208] Multiplicity of the reference in the role `CryptoProviderToPortPrototypeMapping.process`*Imposition time:* IT_Mani

[For each `CryptoProviderToPortPrototypeMapping`, the reference in the role `process` shall exist.]

[constr_10209] Existence of the reference in the role `AbstractCryptoKeySlotToPortPrototypeMapping.keySlot`*Imposition time:* IT_Mani

[For each `AbstractCryptoKeySlotToPortPrototypeMapping`, the reference in the role `keySlot` shall exist.]

[constr_10210] Existence of the reference in the role `AbstractCryptoKeySlotToPortPrototypeMapping.process`*Imposition time:* IT_Mani

[For each `AbstractCryptoKeySlotToPortPrototypeMapping`, the reference in the role `process` shall exist.]

[constr_10212] Multiplicity of attribute `SomeipServiceInterfaceDeployment.serviceInterfaceId`*Imposition time:* IT_Mani

[For each `SomeipServiceInterfaceDeployment`, the attribute `serviceInterfaceId` shall exist.]

[constr_10213] Multiplicity of attribute `SomeipServiceInterfaceDeployment.serviceInterfaceVersion`*Imposition time:* IT_Mani

[For each `SomeipServiceInterfaceDeployment`, the attribute `serviceInterfaceVersion` shall exist.]

[constr_10214] Multiplicity of attribute `SomeipEventGroup.eventGroupId`*Imposition time:* IT_Mani

[For each `SomeipEventGroup`, the attribute `eventGroupId` shall exist.]

[constr_10215] Multiplicity of attribute `SomeipEventDeployment.eventId`*Imposition time:* IT_Mani

[For each `SomeipEventDeployment`, the attribute `eventId` shall exist.]

[constr_10216] Multiplicity of attribute `SomeipEventDeployment.transportProtocol`*Imposition time:* IT_Mani

[For each `SomeipEventDeployment`, the attribute `transportProtocol` shall exist.]

[constr_10217] Multiplicity of the attribute `DdsServiceInterfaceDeployment.serviceInterfaceId`*Imposition time:* IT_Mani

[For each `DdsServiceInterfaceDeployment`, the attribute `serviceInterfaceId` shall exist.]

[constr_10218] Multiplicity of reference in the role `ProvidedSomeipServiceInstance.sdServerConfig`*Imposition time:* IT_Mani

[For each `ProvidedSomeipServiceInstance`, the reference in the role `sdServerConfig` shall exist.]

[constr_10219] Multiplicity of attribute `ProvidedSomeipServiceInstance.serviceInstanceId`*Imposition time:* IT_Mani

[For each `ProvidedSomeipServiceInstance`, the attribute `serviceInstanceId` shall exist.]

[constr_10220] Multiplicity of attribute `SomeipProvidedEventGroup.multicastThreshold`*Imposition time:* IT_Mani

[For each `SomeipProvidedEventGroup`, the attribute `multicastThreshold` shall exist.]

[constr_10221] Multiplicity of reference in the role `RequiredSomeipServiceInstance.sdClientConfig`*Imposition time:* IT_Mani

[For each `RequiredSomeipServiceInstance`, the reference in the role `sdClientConfig` shall exist.]

[constr_10222] Multiplicity of the reference in the role `SomeipRequiredEventGroup.sdClientEventGroupTimingConfig`*Imposition time:* IT_Mani

[For each `SomeipRequiredEventGroup`, the reference in the role `sdClientEventGroupTimingConfig` shall exist.]

[constr_10223] Multiplicity of attribute `DdsServiceInstanceProps.domainId`*Imposition time:* IT_Mani

[For each `DdsServiceInstanceProps`, the attribute `domainId` shall exist.]

[constr_10224] Multiplicity of reference in the role `DdsEventQosProps.event`*Imposition time:* IT_Mani

[For each `DdsEventQosProps`, the reference in the role `event` shall exist.]

[constr_10225] Multiplicity of reference in the role `DdsFieldQosProps.field`*Imposition time:* IT_Mani

[For each `DdsFieldQosProps`, the reference in the role `field` shall exist.]

[constr_10226] Multiplicity of attribute `E2EProfileConfiguration.profileName`*Imposition time:* IT_Mani

[For each `E2EProfileConfiguration`, the attribute `profileName` shall exist.]

[constr_10227] Multiplicity of attribute `SecOcJobRequirement.secOcJobSemantic`*Imposition time:* IT_Mani

[For each `SecOcJobRequirement`, the attribute `secOcJobSemantic` shall exist.]

[constr_10228] Multiplicity of attribute `SignalBasedFieldToISignalTriggeringMapping.dataPrototypeInServiceInterfaceRef`*Imposition time:* IT_Mani

[For each `SignalBasedFieldToISignalTriggeringMapping`, the attribute `dataPrototypeInServiceInterfaceRef` shall exist.]

[constr_10230] Multiplicity of attribute `SignalServiceTranslationEventProps.safeTranslation`*Imposition time:* IT_Mani

[For each `SignalServiceTranslationEventProps`, the attribute `safeTranslation` shall exist.]

[constr_10231] Multiplicity of attribute `SignalServiceTranslationEventProps.secureTranslation`*Imposition time:* IT_Mani

[For each `SignalServiceTranslationEventProps`, the attribute `secureTranslation` shall exist.]

[constr_10232] Multiplicity of reference in the role `PersistencyDeploymentToCryptoKeySlotMapping.persistencyDeployment`*Imposition time:* IT_Mani

[For each `PersistencyDeploymentToCryptoKeySlotMapping`, the reference in the role `persistencyDeployment` shall exist.]

[constr_10233] Multiplicity of the reference in the role `SoftwareCluster.vendorSignature`*Imposition time:* IT_Mani

[For each `SoftwareCluster`, the reference in the role `vendorSignature` shall exist.]

[constr_10234] Multiplicity of attribute `SoftwareCluster.version`*Imposition time:* IT_Mani

[For each `SoftwareCluster`, the attribute `version` shall exist.]

[constr_10235] Multiplicity of attribute `SoftwareCluster.vendorId`*Imposition time:* IT_Mani

[For each `SoftwareCluster`, the attribute `vendorId` shall exist.]

[constr_10236] Multiplicity of attribute `SoftwareClusterDiagnosticAddress.addressSemantics`*Imposition time:* IT_Mani

[For each `SoftwareClusterDiagnosticAddress`, the attribute `addressSemantics` shall exist.]

[constr_10237] Multiplicity of attribute `SoftwareClusterDependencyCompareCondition.compareType`*Imposition time:* IT_Mani

[For each `SoftwareClusterDependencyCompareCondition`, the attribute `compareType` shall exist.]

[constr_10240] Multiplicity of attribute `SoftwarePackage.actionType`*Imposition time:* IT_Mani

[For each `SoftwarePackage`, the attribute `actionType` shall exist.]

[constr_10242] Multiplicity of attribute `SoftwarePackage.minimumSupportedUcmVersion`*Imposition time:* IT_Mani

[For each `SoftwarePackage`, the attribute `minimumSupportedUcmVersion` shall exist.]

[constr_10243] Multiplicity of attribute `SoftwarePackage.packagerId`*Imposition time:* IT_Mani

[For each `SoftwarePackage`, the attribute `packagerId` shall exist.]

[constr_10244] Multiplicity of reference in the role `SoftwarePackage.packagerSignature`*Imposition time:* IT_Mani

[For each `SoftwarePackage`, the reference in the role `packagerSignature` shall exist.]

[constr_10245] Multiplicity of reference in the role `SoftwarePackage.softwareCluster`*Imposition time:* IT_Mani

[For each `SoftwarePackage`, the reference in the role `softwareCluster` shall exist.]

[constr_10246] Multiplicity of attribute `SoftwarePackage.uncompressedSoftwareClusterSize`*Imposition time:* IT_Mani

[For each `SoftwarePackage`, the attribute `uncompressedSoftwareClusterSize` shall exist.]

[constr_10247] Multiplicity of reference in the role `VehiclePackage.packagerSignature`*Imposition time:* IT_Mani

[For each `VehiclePackage`, the reference in the role `packagerSignature` shall exist.]

[constr_10248] Multiplicity of reference in the role `UcmDescription.identifier`*Imposition time:* IT_Mani[For each `UcmDescription`, the reference in the role `identifier` shall exist.]**[constr_10249] Multiplicity of reference in the role `VehicleDriverNotification.approvalRequired`***Imposition time:* IT_Mani[For each `VehicleDriverNotification`, the reference in the role `approvalRequired` shall exist.]**[constr_10250] Multiplicity of reference in the role `VehicleDriverNotification.notificationState`***Imposition time:* IT_Mani[For each `VehicleDriverNotification`, the reference in the role `notificationState` shall exist.]**[constr_10251] Multiplicity of the reference in the role `ServiceFieldDeployment.field`***Imposition time:* IT_Mani[For each `ServiceFieldDeployment`, the reference in the role `field` shall exist.]**[constr_10252] Multiplicity of attribute `SignalBasedEventElementToISignalTriggeringMapping.dataPrototypeInServiceInterfaceRef`***Imposition time:* IT_Mani[For each `SignalBasedEventElementToISignalTriggeringMapping`, the attribute `dataPrototypeInServiceInterfaceRef` shall exist.]**[constr_10253] Multiplicity of attribute `SoftwareClusterDependencyCompareCondition.considerBuildNumber`***Imposition time:* IT_Mani[For each `SoftwareClusterDependencyCompareCondition`, the attribute `considerBuildNumber` shall exist.]**[constr_10254] Multiplicity of attribute `SoftwareClusterDependencyCompareCondition.version`***Imposition time:* IT_Mani[For each `SoftwareClusterDependencyCompareCondition`, the attribute `version` shall exist.]

[constr_10255] Multiplicity of attribute `SignalServiceTranslationProps.serviceControl`*Imposition time:* IT_Mani

[For each `SignalServiceTranslationProps`, the attribute `serviceControl` shall exist.]

[constr_10256] Multiplicity of reference in the role `SoftwarePackageStoring.storing`*Imposition time:* IT_Mani

[For each `SoftwarePackageStoring`, the reference in the role `storing` shall exist.]

[constr_10365] Existence of `PersistencyDeployment.deploymentUri`*Imposition time:* IT_Mani

[For each concrete sub-class of `PersistencyDeployment`, attribute `deploymentUri` shall exist.]

[constr_10366] Possible multiplicities of `PersistencyDeployment.deploymentUri`*Imposition time:* IT_Mani

[Possible multiplicities of `PersistencyDeployment.deploymentUri` shall be one of

- 1
- 2
- value of attribute `PersistencyRedundancyMOutOfN.n`

]

[constr_10367] Condition for the multiplicity of attribute `PersistencyDeployment.deploymentUri`*Imposition time:* IT_Mani

[The multiplicity of attribute `PersistencyDeployment.deploymentUri` shall only be greater than 1 if meta-class `PersistencyRedundancyMOutOfN` is aggregated in the role `PersistencyDeployment.redundancyHandling` and attribute `PersistencyDeployment.redundancyHandling.scope` is set to the value `PersistencyRedundancyHandlingScopeEnum.persistencyRedundancyHandlingScopeStorage`.]

[constr_10374] Existence of the attribute `UcmSubordinateModuleInstantiation.verifyUpdate`*Imposition time:* IT_Mani

[The attribute `UcmSubordinateModuleInstantiation.verifyUpdate` shall exist.]

[constr_10375] Existence of the attribute `UcmSubordinateModuleInstantiation.prepareUpdate`

Imposition time: IT_Mani

[The attribute `UcmSubordinateModuleInstantiation.prepareUpdate` shall exist.]

[constr_10376] Existence of the attribute `UcmSubordinateModuleInstantiation.prepareRollback`

Imposition time: IT_Mani

[The attribute `UcmSubordinateModuleInstantiation.prepareRollback` shall exist.]

[constr_10377] Completeness of the modeling of `PersistencyKeyValueDataTypeMapping`

Imposition time: IT_BefAraApiGen

[For each `PersistencyKeyValueDataTypeMapping`, the references in the roles

- `previousDataType`
- `currentDataType`

]

[constr_10378] `PersistencyKeyValueDataTypeMapping` references `AbstractImplementationDataType` in the role `currentDataType`

Imposition time: IT_BefAraApiGen

[Each `PersistencyKeyValueDataTypeMapping` that references to an `AbstractImplementationDataType` as part of the collection in the role `currentDataType` shall also refer to an `AbstractImplementationDataType` in the role `previousDataType`.]

[constr_10379] `PersistencyKeyValueDataTypeMapping` references `ApplicationDataType` in the role `currentDataType`

Imposition time: IT_BefAraApiGen

[Each `PersistencyKeyValueDataTypeMapping` that references to an `ApplicationDataType` as part of the collection in the role `currentDataType` shall also refer to an `ApplicationDataType` in the role `previousDataType`.]

[constr_10380] Target of `ArtifactLocator.representedModelElement`

Imposition time: IT_Mani

[The target of a reference in the role `ArtifactLocator.representedModelElement` shall not be the target of another reference in the role `ArtifactLocator.representedModelElement`.]

[constr_10381] Existence of attribute `ArtifactLocator.uri`*Imposition time:* IT_Mani[For each `ArtifactLocator`, the attribute `uri` shall exist.]**[constr_10382] Existence of attribute `ArtifactLocator.representedModelElement`***Imposition time:* IT_Mani[For each `ArtifactLocator`, the attribute `representedModelElement` shall exist.]**[constr_10384] `PortInterface` used for trigger state requests***Status:* DRAFT*Imposition time:* IT_Mani[Each `RPortPrototype` that is referenced by a `StateManagementRequestTrigger` shall be typed by either

- a subclass of `StateManagementTriggerInterface` or
- a `ServiceInterface`.

]

[constr_10385] `PortInterface` used for error state requests*Status:* DRAFT*Imposition time:* IT_Mani[Each `RPortPrototype` that is referenced by a `StateManagementRequestError` shall be typed by subclass of `StateManagementErrorInterface`.]**[constr_10386] Existence of references `StateManagementStateMachineActionItem.startAgent` and `stopAgent`***Status:* DRAFT*Imposition time:* IT_Mani[For each `StateManagementStateMachineActionItem`, **at most one** of the two references

- `startAgent`
- `stopAgent`

shall exist.]

[constr_10387] Consistency of `StateManagementSetFunctionGroupStateActionItem.rPortPrototype` and `StateManagementSetFunctionGroupStateActionItem.setFunctionGroupState`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `StateManagementSetFunctionGroupStateActionItem`, the `ModeDeclarationGroup` used to type the `ModeDeclaration` that is referenced in the role `setFunctionGroupState` shall be identical to the `ModeDeclarationGroup` referenced in the role `modeGroup` from the `StateManagementFunctionGroupSwitchNotificationInterface` that is used to type the `PPortPrototype` that is referenced in the role `rPortPrototype` from the affected `StateManagementSetFunctionGroupStateActionItem`.]

[constr_10388] Restriction for a `PortInterface` used for state switch notifications*Status:* DRAFT*Imposition time:* IT_Mani

[Each `PPortPrototype` that is referenced by a `StateManagementStateNotification` shall be typed by a `ServiceInterface`.]

[constr_10389] Existence of attribute `StateManagementFunctionGroupSwitchNotificationInterface.modeGroup`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `StateManagementFunctionGroupSwitchNotificationInterface`, the aggregation in the role `modeGroup` shall exist.]

[constr_10390] Existence of reference `StateManagementStateRequest.stateRequestPort`*Status:* DRAFT*Imposition time:* IT_Mani

[Unless the `StateManagementStateRequest` is referenced from a `NmInteractsWithSmMapping`, the reference in the role `stateRequestPort` shall exist.]

[constr_10391] Existence of attribute `StateManagementStateNotification.notificationPort`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `StateManagementStateNotification`, the aggregation in the role `notificationPort` shall exist.]

[constr_10392] Existence of attribute `StateManagementRequestRule.formula`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `StateManagementRequestRule`, the aggregation in the role `formula` shall exist.]

[constr_10393] Existence of reference in the role `StateManagementRequestRule.nextState`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `StateManagementRequestRule`, the reference in the role `nextState` shall exist.]

[constr_10394] Existence of attribute `StateManagementCompareCondition.compareType`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `StateManagementCompareCondition`, the aggregation in the role `compareType` shall exist.]

[constr_10395] Existence of attribute `StateManagementCompareCondition.compareValue`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `StateManagementCompareCondition`, the aggregation in the role `compareValue` shall exist.]

[constr_10396] Existence of reference in the role `StateManagementTriggerCompareRule.assumedCurrentState`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `StateManagementTriggerCompareRule`, the reference in the role `assumedCurrentState` shall exist.]

[constr_10397] Existence of reference in the role `StateManagementSetFunctionGroupStateActionItem.rPortPrototype`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `StateManagementSetFunctionGroupStateActionItem`, the reference in the role `rPortPrototype` shall exist.]

[constr_10398] Existence of reference in the role `StateManagementSetFunctionGroupStateActionItem.setFunctionGroupState`

Status: DRAFT

Imposition time: IT_Mani

[For each `StateManagementSetFunctionGroupStateActionItem`, the reference in the role `setFunctionGroupState` shall exist.]

[constr_10399] Allowed interval of the "index" field according to the initialization rule for data object typed by a `CppImplementationDataType` of category **VARIANT**

Imposition time: IT_BefAraApiGen

[The allowed value range of the "index" field of a `RecordValueSpecification` according to [TPS_MANI_01393] goes from 1 to the number of `templateArguments` owned by the `CppImplementationDataType` of category **VARIANT**.]

[constr_10400] Existence of `SovdServerInstantiation.componentQualifier`

Imposition time: IT_Mani

[For each `SovdServerInstantiation`, attribute `componentQualifier` shall exist.]

[constr_10401] Existence of `SovdGatewayLocalEndpointTcpConfig.tcpPort`

Imposition time: IT_Mani

[For each `SovdGatewayLocalEndpointTcpConfig`, attribute `tcpPort` shall exist.]

[constr_10402] Existence of `SovdGatewayEthernetCredentials.ipv4Address` vs. `SovdGatewayEthernetCredentials.ipv6Address`

Imposition time: IT_Mani

[For each `SovdGatewayEthernetCredentials`, at least one of attributes

- `SovdGatewayEthernetCredentials.ipv4Address`
- `SovdGatewayEthernetCredentials.ipv6Address`

]

[constr_10403] Existence of `SovdGatewayEthernetCredentials.udpPort`

Imposition time: IT_Mani

[For each `SovdGatewayEthernetCredentials`, attribute `udpPort` shall exist.]

[constr_10404] Existence of `SoftwareClusterSovdAddress.componentQualifier`*Imposition time:* IT_Mani

[For each `SoftwareClusterSovdAddress`, attribute `componentQualifier` shall exist.]

[constr_10405] Existence of reference in the role `StateManagementActionList.affectedState`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `StateManagementActionList`, the reference in the role `affectedState` shall exist.]

[constr_10410] Value of `SoftwareClusterDesign.installationBehavior` for a `SoftwareClusterDesign` of category `PLATFORM_CORE`*Imposition time:* IT_Mani

[In a `SoftwareClusterDesign` of category `PLATFORM_CORE`, the attribute `installationBehavior` shall exist and its value shall be set to `cannotBeRemoved`.]

[constr_10411] Existence of `ExecutionDependency` and references to `Function Group States`*Imposition time:* IT_Mani

[Each `StateDependentStartupConfig` that aggregates at least one `ExecutionDependency` in the role `executionDependency` shall reference at most one `ModuleDeclaration` in the role `functionGroupState`.]

[constr_10416] Aggregation of optional `templateArgument` that defines an `Allocator` for a `VECTOR`*Imposition time:* IT_BefAraApiGen

[If a `CppImplementationDataType` of category `VECTOR` that boils down to `ara::core::Vector` aggregates (in addition to the `templateArgument` mentioned in [constr_3434]) one additional `templateArgument`, then this additional `templateArgument` shall reference the `Allocator` by means of the `allocator` reference.]

[constr_10417] Existence of attributes of `CppImplementationDataTypes` depending on the `category`*Imposition time:* IT_BefAraApiGen

[

Attributes of CppImplementationDataType	Attribute Existence per Category							
	VALUE	TYPE_REFERENCE	STRUCTURE	VARIANT	ARRAY	VECTOR	ASSOCIATIVE_MAP	STRING
<code>subElement</code>			1..*					
<code>templateArgument</code>				1..*	1	1..*	2..*	0..1
<code>typeReference</code>		1						
<code>arraySize</code>					1	0..1 ²		

]

[constr_10420] Restriction for the existence of initial values for `PersistencyDataElement`*Imposition time:* IT_BefAraApiGen

[For each `PersistencyKeyValuePair`, if the value of attribute `updateStrategy` is set to the value `PersistencyElementLevelUpdateStrategyEnum.delete`, then the specific `PersistencyDataElement` shall not be referenced by a `PersistencyDataRequiredComSpec` that is aggregated by a `RPortPrototype` that in turn is typed by the `PersistencyInterface` that owns the specific `PersistencyDataElement`.]

[constr_10425] Existence of initial values for `PersistencyDataElement`*Imposition time:* IT_BefAraApiGen

[For each `PersistencyDataElement`, if the value of attribute `PersistencyInterface.updateStrategy` is set to either

- `PersistencyElementLevelUpdateStrategyEnum.keepExisting` or
- `PersistencyElementLevelUpdateStrategyEnum.overwrite`,

then a `PersistencyDataRequiredComSpec` shall be aggregated by a `RPortPrototype` that is typed by the `PersistencyInterface` that owns the specific `PersistencyDataElement`.

The `PersistencyDataRequiredComSpec` shall

- refer to the respective `PersistencyDataElement` and
- aggregate `ValueSpecification` in the role `initValue`.

]

²This depends on the existence of an allocator, see [TPS_MANI_03186].

[constr_10426] Multiplicity of attribute `PersistencyDeploymentElement.updateStrategy`*Imposition time:* IT_Mani

[For each `PersistencyDeploymentElement`, the attribute `updateStrategy` shall exist.]

[constr_10427] Multiplicity of attribute `PersistencyInterfaceElement.updateStrategy`*Imposition time:* IT_Mani

[For each `PersistencyInterfaceElement`, the attribute `updateStrategy` shall exist.]

[constr_10428] Existence of attribute `UcmModuleInstantiation.identifier` in subclasses*Imposition time:* IT_Mani

[The Attribute `identifier` shall **not** exist in a `UcmMasterModuleInstantiation`.]

[constr_10429] Existence of attribute `VehicleRolloutStep.violatedSafetyConditionBehavior`*Imposition time:* IT_Mani

[For each `VehicleRolloutStep`, the attribute `violatedSafetyConditionBehavior` shall exist.]

[constr_10430] Existence of attribute `Machine.defaultApplicationTimeout`*Imposition time:* IT_Mani

[For each `Machine`, the attribute `defaultApplicationTimeout` shall exist.]

[constr_10431] Existence of attribute `Machine.defaultApplicationTimeout.enterTimeoutValue`*Imposition time:* IT_Mani

[For each `Machine`, the attribute `defaultApplicationTimeout.enterTimeoutValue` shall exist.]

[constr_10432] Existence of attribute `Machine.defaultApplicationTimeout.exitTimeoutValue`*Imposition time:* IT_Mani

[For each `Machine`, the attribute `defaultApplicationTimeout.exitTimeoutValue` shall exist.]

[constr_10436] Restriction for the applicability of `DiagnosticMultipleMonitorPortMapping`*Imposition time:* IT_DiagDes

[If an `RPortPrototype` is referenced by a `DiagnosticMultipleMonitorPortMapping`, then the `RPortPrototype` shall be typed by a `DiagnosticMultipleMonitorInterface`.]

[constr_10437] Restriction for the applicability of `DiagnosticMultipleEventPortMapping`*Imposition time:* IT_DiagDes

[If an `RPortPrototype` is referenced by a `DiagnosticMultipleEventPortMapping`, then the `RPortPrototype` shall be typed by a `DiagnosticMultipleEventInterface`.]

[constr_10438] Restriction for the applicability of `DiagnosticMultipleConditionPortMapping`*Imposition time:* IT_DiagDes

[If an `RPortPrototype` is referenced by a `DiagnosticMultipleConditionPortMapping`, then the `RPortPrototype` shall be typed by a `DiagnosticMultipleConditionInterface`.]

[constr_10441] Restriction for `NetworkHandlePortMapping.pPortPrototypeInExecutable`*Imposition time:* IT_Mani

[A `PPortPrototype` referenced in the role `NetworkHandlePortMapping.pPortPrototypeInExecutable` shall only be typed by a `NetworkManagementPortInterface`.]

[constr_10442] Restriction for the applicability of `DiagnosticSovdProximityChallengePortMapping`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is referenced by a `DiagnosticSovdProximityChallengePortMapping` in the role `pPortPrototypeInExecutable`, then the `PPortPrototype` shall be typed by a `DiagnosticSovdProximityChallengeInterface`.]

[constr_10443] Restriction for the applicability of `DiagnosticSovdProximityChallengeInterface`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is typed by a `DiagnosticSovdProximityChallengeInterface`, then the `PortPrototype` shall only be referenced in the role `pPortPrototypeInExecutable` by a `DiagnosticSovdProximityChallengePortMapping`.]

[constr_10444] Existence of [DiagnosticSovdProximityChallengePortMapping](#)*Imposition time:* IT_DiagDes

[Each [DiagnosticContributionSet](#) shall only reference at most one [DiagnosticSovdProximityChallengePortMapping](#) in the role `element`.]

[constr_10445] Existence of the reference in the role [DiagnosticSovdProximityChallengePortMapping.pPortPrototypeInExecutable](#)*Imposition time:* IT_DiagDes

[For each [DiagnosticSovdProximityChallengePortMapping](#), the reference in the role [DiagnosticSovdProximityChallengePortMapping.pPortPrototypeInExecutable](#) shall exist.]

[constr_10446] Existence of the reference in the role [DiagnosticSovdProximityChallengePortMapping.process](#)*Imposition time:* IT_DiagDes

[For each [DiagnosticSovdProximityChallengePortMapping](#), the reference in the role [DiagnosticSovdProximityChallengePortMapping.process](#) shall exist.]

[constr_10447] Restriction for the applicability of [DiagnosticSovdAuthorizationPortMapping](#)*Imposition time:* IT_DiagDes

[If a [PPortPrototype](#) is referenced in the role [pPortPrototypeInExecutable](#) by a [DiagnosticSovdAuthorizationPortMapping](#), then the [PPortPrototype](#) shall be typed by a [DiagnosticSovdAuthorizationInterface](#).]

[constr_10448] Restriction for the applicability of [DiagnosticSovdAuthorizationInterface](#)*Imposition time:* IT_DiagDes

[If a [PPortPrototype](#) is typed by a [DiagnosticSovdAuthorizationInterface](#), then the [PortPrototype](#) shall only be referenced in the role [pPortPrototypeInExecutable](#) by a [DiagnosticSovdAuthorizationPortMapping](#).]

[constr_10449] Existence of [DiagnosticSovdAuthorizationPortMapping](#)*Imposition time:* IT_DiagDes

[Each [DiagnosticContributionSet](#) shall only reference in the role `element` at most one [DiagnosticSovdAuthorizationPortMapping](#).]

[constr_10450] Existence of the reference in the role `DiagnosticSovdAuthorizationPortMapping.pPortPrototypeInExecutable`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdAuthorizationPortMapping`, the reference in the role `DiagnosticSovdAuthorizationPortMapping.pPortPrototypeInExecutable` shall exist.]

[constr_10451] Existence of the reference in the role `DiagnosticSovdAuthorizationPortMapping.process`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdAuthorizationPortMapping`, the reference in the role `DiagnosticSovdAuthorizationPortMapping.process` shall exist.]

[constr_10452] Restriction for the applicability of `DiagnosticSovdBulkDataPortMapping`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is referenced in the role `pPortPrototypeInExecutable` by a `DiagnosticSovdBulkDataPortMapping`, then the `PPortPrototype` shall be typed by a `DiagnosticSovdBulkDataInterface`.]

[constr_10453] Restriction for the applicability of `DiagnosticSovdBulkDataInterface`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is typed by a `DiagnosticSovdBulkDataInterface`, then the `PortPrototype` shall only be referenced in the role `pPortPrototypeInExecutable` by a `DiagnosticSovdBulkDataPortMapping`.]

[constr_10454] Uniqueness of reference from `DiagnosticSovdBulkDataPortMapping` to `DiagnosticSovdBulkData`*Imposition time:* IT_DiagDes

[Each instance `DiagnosticSovdBulkData` shall only be referenced in the role `serviceInstance` by exactly one `DiagnosticSovdBulkDataPortMapping`.]

[constr_10455] Existence of the reference in the role `DiagnosticSovdBulkDataPortMapping.serviceInstance`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdBulkDataPortMapping`, the reference in the role `DiagnosticSovdBulkDataPortMapping.serviceInstance` shall exist.]

[constr_10456] Existence of the reference in the role `DiagnosticSovdBulkDataPortMapping.pPortPrototypeInExecutable`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdBulkDataPortMapping`, the reference in the role `DiagnosticSovdBulkDataPortMapping.pPortPrototypeInExecutable` shall exist.]

[constr_10457] Existence of the reference in the role `DiagnosticSovdBulkDataPortMapping.process`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdBulkDataPortMapping`, the reference in the role `DiagnosticSovdBulkDataPortMapping.process` shall exist.]

[constr_10458] Restriction for the applicability of `DiagnosticSovdUpdatePortMapping`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is referenced in the role `pPortPrototypeInExecutable` by a `DiagnosticSovdUpdatePortMapping`, then the `PPortPrototype` shall be typed by a `DiagnosticSovdUpdateInterface`.]

[constr_10459] Restriction for the applicability of `DiagnosticSovdUpdateInterface`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is typed by a `DiagnosticSovdUpdateInterface`, then the `PortPrototype` shall only be referenced in the role `pPortPrototypeInExecutable` by a `DiagnosticSovdUpdatePortMapping`.]

[constr_10460] Uniqueness of reference from `DiagnosticSovdUpdatePortMapping` to `DiagnosticSovdUpdate`*Imposition time:* IT_DiagDes

[Each instance of `DiagnosticSovdUpdate` shall only be referenced in the role `serviceInstance` by exactly one `DiagnosticSovdUpdatePortMapping`.]

[constr_10461] Existence of the reference in the role `DiagnosticSovdUpdatePortMapping.serviceInstance`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdUpdatePortMapping`, the reference in the role `DiagnosticSovdUpdatePortMapping.serviceInstance` shall exist.]

[constr_10462] Existence of the reference in the role `DiagnosticSovdUpdatePortMapping.pPortPrototypeInExecutable`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdUpdatePortMapping`, the reference in the role `DiagnosticSovdUpdatePortMapping.pPortPrototypeInExecutable` shall exist.]

[constr_10463] Existence of the reference in the role `DiagnosticSovdUpdatePortMapping.process`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdUpdatePortMapping`, the reference in the role `DiagnosticSovdUpdatePortMapping.process` shall exist.]

[constr_10464] Restriction for the applicability of `DiagnosticSovdServiceValidationPortMapping`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is referenced in the role `pPortPrototypeInExecutable` by a `DiagnosticSovdServiceValidationPortMapping`, then the `PPortPrototype` shall be typed by a `DiagnosticSovdServiceValidationInterface`.]

[constr_10465] Restriction for the applicability of `DiagnosticSovdServiceValidationInterface`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is typed by a `DiagnosticSovdServiceValidationInterface`, then the `PortPrototype` shall only be referenced in the role `pPortPrototypeInExecutable` by a `DiagnosticSovdServiceValidationPortMapping`.]

[constr_10466] Existence of the reference in the role `DiagnosticSovdServiceValidationPortMapping.pPortPrototypeInExecutable`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdServiceValidationPortMapping`, the reference in the role `DiagnosticSovdServiceValidationPortMapping.pPortPrototypeInExecutable` shall exist.]

[constr_10467] Existence of the reference in the role `DiagnosticSovdServiceValidationPortMapping.process`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdServiceValidationPortMapping`, the reference in the role `DiagnosticSovdServiceValidationPortMapping.process` shall exist.]

[constr_10468] Restriction for the applicability of `DiagnosticSovdConfigurationPortMapping`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is referenced in the role `pPortPrototypeInExecutable` by a `DiagnosticSovdConfigurationPortMapping`, then the `PPortPrototype` shall be typed by a `DiagnosticSovdConfigurationInterface`.]

[constr_10469] Restriction for the applicability of `DiagnosticSovdConfigurationInterface`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is typed by a `DiagnosticSovdConfigurationInterface`, then the `PortPrototype` shall only be referenced in the role `pPortPrototypeInExecutable` by a `DiagnosticSovdConfigurationPortMapping`.]

[constr_10470] Uniqueness of reference from `DiagnosticSovdConfigurationPortMapping` to `DiagnosticSovdConfiguration`*Imposition time:* IT_DiagDes

[Each instance of a sub-class of `DiagnosticSovdConfiguration` shall only be referenced in the role `serviceInstance` by exactly one `DiagnosticSovdConfigurationPortMapping`.]

[constr_10471] Existence of the reference in the role `DiagnosticSovdConfigurationPortMapping.serviceInstance`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdConfigurationPortMapping`, the reference in the role `DiagnosticSovdConfigurationPortMapping.serviceInstance` shall exist.]

[constr_10472] Existence of the reference in the role `DiagnosticSovdConfigurationPortMapping.pPortPrototypeInExecutable`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdConfigurationPortMapping`, the reference in the role `DiagnosticSovdConfigurationPortMapping.pPortPrototypeInExecutable` shall exist.]

[constr_10473] Existence of the reference in the role `DiagnosticSovdConfigurationPortMapping.process`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdConfigurationPortMapping`, the reference in the role `DiagnosticSovdConfigurationPortMapping.process` shall exist.]

[constr_10477] Existence of **DiagnosticSovdLog**

Imposition time: IT_DiagDes

[Each **DiagnosticContributionSet** shall at most reference a single **DiagnosticSovdLog** in the role **element**.]

[constr_10478] Existence of **DiagnosticSovdUpdate**

Imposition time: IT_DiagDes

[Each **DiagnosticContributionSet** shall at most reference a single **DiagnosticSovdUpdate** in the role **element**.]

[constr_10479] Restriction on values of attribute **DiagnosticSovdMethodPrimitive.category** aggregated in the role **put** in the context of SOVD Update

Imposition time: IT_DiagDes

[If a **DiagnosticSovdMethod** is referenced from a **DiagnosticSovdUpdate** and the attribute **put.category** exists, then the value of the attribute **category** within any **DiagnosticSovdMethodPrimitive** aggregated in the role **put** is restricted to the following values:

- PREPARE
- EXECUTE
- AUTOMATED

]

[constr_10480] Restriction on value of attribute **DiagnosticSovdMethodPrimitive.category** aggregated in the role **get** in the context of SOVD Update

Imposition time: IT_DiagDes

[If a **DiagnosticSovdMethod** is referenced from a **DiagnosticSovdUpdate** and the attribute **get.category** exists, then the value of the attribute **category** within any **DiagnosticSovdMethodPrimitive** aggregated in the role **get** is restricted to the value **STATUS**.]

[constr_10481] Restriction on values of attribute **DiagnosticSovdMethodPrimitive.category** aggregated in the role **get** in the context of SOVD Log

Imposition time: IT_DiagDes

[If a **DiagnosticSovdMethod** is referenced from a **DiagnosticSovdLog** and the attribute **get** exists, then the value of the attribute **category** within any **DiagnosticSovdMethodPrimitive** aggregated in the role **get** is restricted to the values

- CONFIG
- ENTRIES

]

[constr_10482] Restriction on values of attribute `DiagnosticSovdMethodPrimitive.category` aggregated in the roles `put` and `delete` in the context of `SOVD Log`

Imposition time: IT_DiagDes

[If a `DiagnosticSovdMethod` is referenced from a `DiagnosticSovdLog` and the attributes

- `put`
- `delete`

exist, then the value of the attribute `category` within any `DiagnosticSovdMethodPrimitive` aggregated in the role

- `put`
- `delete`

is restricted to the value `CONFIG`.]

[constr_10483] Applicable values of `baseTypeEncoding` in the context of the definition of a `DiagnosticDataElement`

Imposition time: IT_DiagDes

[Any `SwBaseType` referenced in the role `DiagnosticDataElement.swDataDefProps.baseType` shall only set one of the following values for attribute `SwBaseType.baseTypeDefinition.baseTypeEncoding`:

- **BOOLEAN** (for `baseTypeSize` = 8)
- **NONE** (for `baseTypeSize` = 8, 16, 32, or 64)
- **2C** (for `baseTypeSize` = 8, 16, 32, or 64)
- **BCD-P** (for `baseTypeSize` = 8)
- **BCD-UP** (for `baseTypeSize` = 8)
- **IEEE754** (for `baseTypeSize` = 32 or 64)
- **UTF-8** (for `baseTypeSize` = 8)

]

[constr_10484] Existence of `FunctionalClusterInteractsWithPersistencyDeploymentMapping.contractVersion`

Imposition time: IT_Mani

[In the context of `FunctionalClusterInteractsWithPersistencyDeploymentMapping`, the attribute in the role `contractVersion` shall exist.]

[constr_10485] Existence of `PersistencyInterface.contractVersion`

Imposition time: IT_BefAraApiGen

[In the context of `PersistencyInterface`, the attribute in the role `contractVersion` shall exist.]

[constr_10486] Existence of `PersistencyKeyValueDataTypeMapping.previousContractVersion`

Imposition time: IT_BefAraApiGen

[In the context of `PersistencyKeyValueDataTypeMapping`, the attribute in the role `previousContractVersion` shall exist.]

[constr_10487] Only one physical address per `DiagnosticCommonProps`

Imposition time: IT_DiagDes

[Each `DiagnosticCommonProps` shall only aggregate one `SoftwareClusterDiagnosticAddress` where the value of attribute `addressSemantics` is set to `SoftwareClusterDiagnosticAddressSemanticsEnum.physicalAddress`.]

[constr_10489] Existence of `StateManagementModuleInstantiation` in the context of a Machine

Status: DRAFT

Imposition time: IT_Mani

[Each `Machine` shall only aggregate at most one `StateManagementModuleInstantiation` in the role `moduleInstantiation`.]

[constr_10490] `DiagnosticDataElement` shall be directly or indirectly the target of a reference owned by a subclass of `DiagnosticMapping`

Imposition time: IT_DiagDes

[Each `DiagnosticDataElement` shall be directly or indirectly considered by a `DiagnosticMapping`. Therefore, exactly one of the following conditions shall be fulfilled:

- A `DiagnosticDataPortMapping` exists that refers to the respective `DiagnosticDataElement` in the role `diagnosticDataElement`.
- A `DiagnosticDataPortMapping` exists that refers in the role `diagnosticDataIdentifier` to the `DiagnosticDataIdentifier` that aggregates the respective `DiagnosticDataElement` in the role `dataElement.dataElement`.

]

[constr_10491] Type of `PPortPrototype` referenced in the role `IdsmTimestampProviderMapping.pPortPrototypeInExecutable`*Imposition time:* IT_Mani

[A `PPortPrototype` referenced in the role `IdsmTimestampProviderMapping.pPortPrototypeInExecutable` shall only be typed by a `IdsmTimestampProviderInterface`.]

[constr_10492] `PPortPrototype` typed by a `IdsmTimestampProviderInterface`*Imposition time:* IT_Mani

[A `PPortPrototype` that is typed by a `IdsmTimestampProviderInterface` shall only be referenced in the role `pPortPrototypeInExecutable` by a `IdsmTimestampProviderMapping`.]

[constr_10493] Existence of `IdsmTimestampProviderMapping.idsPlatformInstantiation`*Imposition time:* IT_Mani

[For each `IdsmTimestampProviderMapping`, the reference to an `IdsPlatformInstantiation` in the role `idsPlatformInstantiation` shall exist.]

[constr_10494] Existence of `IdsmTimestampProviderMapping.pPortPrototypeInExecutable`*Imposition time:* IT_Mani

[For each `IdsmTimestampProviderMapping`, the instance reference to a `PPortPrototype` in the role `pPortPrototypeInExecutable` shall exist.]

[constr_10495] Existence of `IdsmTimestampProviderMapping.process`*Imposition time:* IT_Mani

[For each `IdsmTimestampProviderMapping`, the reference to a `Process` in the role `process` shall exist.]

[constr_10496] Type of `PPortPrototype` referenced in the role `IdsmContextProviderMapping.pPortPrototypeInExecutable`*Imposition time:* IT_Mani

[A `PPortPrototype` referenced in the role `IdsmContextProviderMapping.pPortPrototypeInExecutable` shall only be typed by a `IdsmContextProviderInterface`.]

[constr_10497] `PPortPrototype` typed by a `IdsmContextProviderInterface`*Imposition time:* IT_Mani

[A `PPortPrototype` that is typed by a `IdsmContextProviderInterface` shall only be referenced in the role `pPortPrototypeInExecutable` by a `IdsmContextProviderMapping`.]

[constr_10498] Existence of `IdsmContextProviderMapping.idsPlatformInstantiation`

Status: DRAFT

Imposition time: IT_Mani

[For each `IdsmContextProviderMapping`, the reference to an `IdsPlatformInstantiation` in the role `idsPlatformInstantiation` shall exist.]

[constr_10499] Existence of `IdsmContextProviderMapping.pPortPrototypeInExecutable`

Imposition time: IT_Mani

[For each `IdsmContextProviderMapping`, the instance reference to a `PPortPrototype` in the role `pPortPrototypeInExecutable` shall exist.]

[constr_10500] Existence of `IdsmContextProviderMapping.process`

Imposition time: IT_Mani

[For each `IdsmContextProviderMapping`, the reference to a `Process` in the role `process` shall exist.]

[constr_10501] Access to time stamps for *Intrusion Detection System Management*

Status: DRAFT

Imposition time: IT_Mani

[Access to time stamps shall be configured in at most **one of two** possible ways:

- by reference in the role `idsTimeBase` from `IdsPlatformInstantiation` to `TimeBaseResource` or
- by creating a `IdsmTimestampProviderMapping` that refers in the role `pPortPrototypeInExecutable` to a `PPortPrototype` defined by a piece of application software that represents a time-stamp provider.

]

[constr_10508] Existence of the attribute `UcmSubordinateModuleInstantiation.maxAvailablePersistencyStorageSpace`

Imposition time: IT_Mani

[The attribute `UcmSubordinateModuleInstantiation.maxAvailablePersistencyStorageSpace` shall exist.]

[constr_10509] Existence of attribute `PersistencyDeployment.maximumAllowedSize`

Imposition time: IT_Mani

[For each concrete sub-class of `PersistencyDeployment`, attribute `maximumAllowedSize` shall exist.]

[constr_10510] Existence of attribute `PersistencyDeployment.minimumSustainedSize`*Imposition time:* IT_Mani

[For each concrete sub-class of `PersistencyDeployment`, attribute `minimumSustainedSize` shall exist.]

[constr_10511] Reference `StateManagementStateRequest.stateRequestPort` shall not exist if `StateManagementStateRequest` is referenced from `NmInteractsWithSmMapping`*Status:* DRAFT*Imposition time:* IT_Mani

[The reference `StateManagementStateRequest.stateRequestPort` shall not exist if `StateManagementStateRequest` is referenced from `NmInteractsWithSmMapping`.]

[constr_10512] Restriction for the value of `StateManagementSleepActionItem.sleepTime`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `StateManagementSleepActionItem`, the value of attribute `sleepTime` shall only have a value greater than 0.]

[constr_10513] Existence of the reference in the role `SmInteractsWithNmMapping.actionItem`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `SmInteractsWithNmMapping`, the reference in the role `actionItem` shall exist.]

[constr_10514] Existence of the reference in the role `SmInteractsWithNmMapping.nmNetworkHandle`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `SmInteractsWithNmMapping`, the reference in the role `nmNetworkHandle` shall exist.]

[constr_10515] Existence of the reference in the role `NmInteractsWithSmMapping.stateRequest`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `NmInteractsWithSmMapping`, the reference in the role `stateRequest` shall exist.]

[constr_10516] Existence of the reference in the role `NmInteractsWithSmMapping.nmNetworkHandle`

Status: DRAFT

Imposition time: IT_Mani

[For each `NmInteractsWithSmMapping`, the reference in the role `nmNetworkHandle` shall exist.]

[constr_10517] Upper multiplicity of reference in the role `IdsPlatformInstantiation.idsTimeBase`

Status: DRAFT

Imposition time: IT_Mani

[In the context of `IdsPlatformInstantiation`, the reference in the role `idsTimeBase` shall exist at most once.]

[constr_10518] Mutually exclusive existence of `FunctionalClusterInteractsWithDiagnosticEventMapping.persistenceDeployment` vs. `functionalCluster`

Imposition time: IT_Mani

[For each `FunctionalClusterInteractsWithDiagnosticEventMapping`, **either** the reference in the role

- `persistenceDeployment` or
- `functionalCluster`

shall exist.]

[constr_10519] Existence of reference `FunctionalClusterInteractsWithDiagnosticEventMapping.diagnosticEvent`

Imposition time: IT_Mani

[For each `FunctionalClusterInteractsWithDiagnosticEventMapping`, the reference in the role `diagnosticEvent` shall exist.]

[constr_10526] `DiagnosticAuthenticationPortMapping` refers to a `PPortPrototype` that is typed by a `DiagnosticTransmitCertificateInterface`

Imposition time: IT_DiagDes

[If a `DiagnosticAuthenticationPortMapping` refers in the role `pPortPrototypeInExecutable` to a `PPortPrototype` that is typed by a `DiagnosticTransmitCertificateInterface`, then the `DiagnosticAuthenticationPortMapping` shall only refer in the role `diagnosticAuthentication` to a `DiagnosticAuthTransmitCertificate` (and vice versa).]

[constr_10528] Existence of `FirewallStateSwitchInterface.firewall-StateMachine`

Status: DRAFT

Imposition time: IT_BefAraApiGen

[For any given `FirewallStateSwitchInterface`, attribute `firewallStateMachine` shall exist at most once.]

[constr_10530] Each Ucm shall process at least one software package

Imposition time: IT_Mani

[Within the context of all `UcmSteps` referencing a specific `UcmDescription` in the role `ucm`, **at least one** `SoftwarePackageStep` shall exist that defines a reference to a `SoftwarePackage` in the role `process`.]

[constr_10535] Restriction for attribute `SenderComSpec.transmissionProps.onChangeDataPrototype`

Status: DRAFT

Imposition time: IT_BefAraApiGen

[If the `SenderComSpec.dataElement` refers to an `AutosarDataPrototype` aggregated by a `ServiceInterface` in the role `event` or `field`, then a `DataPrototypeReference` aggregated in the role `SenderComSpec.transmissionProps.onChangeDataPrototype` shall only exist as

- a `DataPrototypeInPortInterfaceRef` that aggregates a `DataPrototypeInServiceInterfaceInstanceRef` in the role `dataPrototypeInServiceInterface` or
- an `ImplementationDataTypeElementInPortInterfaceRef`.

]

[constr_10536] Existence of `TransmissionComSpecProps.onChangeDataPrototype.dataPrototypeInServiceInterface.rootDataPrototype`

Status: DRAFT

Imposition time: IT_BefAraApiGen

[If all of the following conditions apply:

- the `SenderComSpec.dataElement` refers to an `AutosarDataPrototype` aggregated by a `ServiceInterface` in either the role `event` or `field` and
- the aggregation in the role `TransmissionComSpecProps.onChangeDataPrototype.dataPrototypeInServiceInterface` exists,

then the aggregation in the role `TransmissionComSpecProps.onChangeDataPrototype.dataPrototypeInServiceInterface.rootDataPrototype` shall **not** exist.]

[constr_10537] Existence of `TransmissionComSpecProps.onChangeDataPrototype.rootDataPrototype`

Imposition time: IT_BefAraApiGen

[If all of the following conditions apply:

- the `SenderComSpec.dataElement` refers to an `AutosarDataPrototype` aggregated by a `ServiceInterface` in either the role `event` or `field` and
- the aggregation in the role `TransmissionComSpecProps.onChangeDataPrototype` exists,

then the aggregation in the role `TransmissionComSpecProps.onChangeDataPrototype.rootDataPrototype` shall **not** exist.]

[constr_10540] Arguments of a `ClientServerOperation` shall be fully covered by `SignalBasedFireAndForgetMethodToISignalTriggeringMappings`

Imposition time: IT_Mani

[If

- an `ArgumentDataPrototype` (if it has a primitive data type) or
- a leaf element of an `ArgumentDataPrototype` (if it has a composite data type)

owned by a `ClientServerOperation` is referenced in the role `dataPrototypeInMethodArgumentInstanceRef` by a `SignalBasedFireAndForgetMethodToISignalTriggeringMapping`, then **every other**

- `ArgumentDataPrototype` (if it has a primitive data type) or
- leaf element of an `ArgumentDataPrototype` (if it has a composite data type)

of the enclosing `ClientServerOperation` shall also be referenced in the role `dataPrototypeInMethodArgumentInstanceRef`.]

[constr_10541] Consistent assignment of `ISignalTriggerings` to an `ISignalGroup` for `SignalBasedFireAndForgetMethodToISignalTriggeringMapping`

Imposition time: IT_Mani

[Each `SignalBasedFireAndForgetMethodToISignalTriggeringMapping` affected by [constr_10540] shall also refer to an `ISignalTriggering` that references an `ISignal` that in turn is also referenced in the role `iSignal` by the **same** `ISignalGroup`.]

[constr_10546] `PortPrototype` typed by `DiagnosticGenericUdsInterface` shall only be referenced by `DiagnosticServiceGenericMapping`

Imposition time: IT_DiagDes

[A `PPortPrototype` that is typed by `DiagnosticGenericUdsInterface` shall **only** be referenced in the role `pPortPrototypeInExecutable` by a `DiagnosticServiceGenericMapping`.]

[constr_10547] Reference in the role `UcmStep.ucm` in the context of the enclosing `VehicleRolloutStep`

Imposition time: IT_Mani

[Each `VehiclePackage.ucm` shall be referenced in the role `UcmStep.ucm` **at most once** in the context of an enclosing `VehicleRolloutStep`.]

[constr_10566] Allowed values of attribute `CppImplementationDataType.sw-DataDefProps.compuMethod.category`

Imposition time: IT_BefAraApiGen

[The only allowed values for attribute `CppImplementationDataType3.sw-DataDefProps.compuMethod.category` are

- TEXTTABLE
- BITFIELD_TEXTTABLE

]

[constr_10567] Existence of `DiagnosticSovdMethod.get` resp. `delete` in the context of `DiagnosticSovdFaultMemoryAccess`

Imposition time: IT_DiagDes

[If a `DiagnosticSovdMethod` is referenced from a `DiagnosticSovdFaultMemoryAccess`, then the following restriction for the existence and multiplicity of the attributes of the `DiagnosticSovdMethod` exist:

- `put` [0]
- `post` [0]
- `get` [0..1]
- `delete` [0..1]

]

[constr_10568] Type of `RPortPrototype` referenced in the role `IdsmReportingModeProviderMapping.rPortPrototypeInExecutable`

Imposition time: IT_Mani

[An `RPortPrototype` referenced in the role `IdsmReportingModeProviderMapping.rPortPrototypeInExecutable` shall only be typed by a `IdsmReportingModeProviderInterface`.]

³[constr_1579] applies

[constr_10569] RPortPrototype typed by an IdsmReportingModeProviderInterface*Imposition time:* IT_Mani

[An `RPortPrototype` that is typed by a `IdsmReportingModeProviderInterface` shall only be referenced in the role `rPortPrototypeInExecutable` by a `IdsmReportingModeProviderMapping`.]

[constr_10570] Existence of IdsmReportingModeProviderMapping.idsPlatformInstantiation*Status:* DRAFT*Imposition time:* IT_Mani

[For each `IdsmReportingModeProviderMapping`, the reference to a `IdsPlatformInstantiation` in the role `idsPlatformInstantiation` shall exist.]

[constr_10571] Existence of IdsmReportingModeProviderMapping.rPortPrototypeInExecutable*Imposition time:* IT_Mani

[For each `IdsmReportingModeProviderMapping`, the reference to an `RPortPrototype` in the role `rPortPrototypeInExecutable` shall exist.]

[constr_10572] Existence of IdsmReportingModeProviderMapping.process*Imposition time:* IT_Mani

[For each `IdsmReportingModeProviderMapping`, the reference to a `Process` in the role `process` shall exist.]

[constr_10574] Value of ApApplicationErrorDomain.value shall be unique in the context of a ClientServerOperation*Imposition time:* IT_BefAraApiGen

[Within the context of one `ClientServerOperation`, no two `ApApplicationErrorDomains` referenced in the role `ClientServerOperation.possibleApError.errorDomain` or transitively referenced in the role `ClientServerOperation.possibleApErrorSet.apApplicationError.errorDomain` shall have the identical value of attribute `ApApplicationErrorDomain.value`.]

[constr_10576] Existence of attribute PersistencyDataRequiredComSpec.accessMode*Imposition time:* IT_BefAraApiGen

[Each `PersistencyDataRequiredComSpec` that defines the reference in the role `dataElement` shall **not** define the attribute `accessMode` and vice versa.]

[constr_10578] Existence of the attribute `UcmMasterModuleInstantiation.ucmNotAvailableOnTheNetwork`*Imposition time:* IT_Mani

[The attribute `UcmMasterModuleInstantiation.ucmNotAvailableOnTheNetwork` shall exist.]

[constr_10586] Restriction for the applicability of `DiagnosticDoIpGroupIdentificationPortMapping`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is referenced by a `DiagnosticDoIpGroupIdentificationPortMapping`, then the `PPortPrototype` shall be typed by a `DiagnosticDoIPGroupIdentificationInterface`.]

[constr_10587] Restriction for the applicability of `DiagnosticDoIPGroupIdentificationInterface`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is typed by a `DiagnosticDoIPGroupIdentificationInterface`, then the reference in the role `pPortPrototypeInExecutable` to the `PPortPrototype` shall only originate from a `DiagnosticDoIpGroupIdentificationPortMapping`.]

[constr_10588] Existence of `DiagnosticDoIpGroupIdentificationPortMapping.pPortPrototypeInExecutable`*Imposition time:* IT_DiagDes

[For each `DiagnosticDoIpGroupIdentificationPortMapping`, attribute `pPortPrototypeInExecutable` shall exist.]

[constr_10589] Existence of `DiagnosticDoIpGroupIdentificationPortMapping.process`*Imposition time:* IT_DiagDes

[For each `DiagnosticDoIpGroupIdentificationPortMapping`, attribute `process` shall exist.]

[constr_10590] Restriction for the applicability of `DiagnosticDoIpActivationLinePortMapping`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is referenced in the role `pPortPrototypeInExecutable` by a `DiagnosticDoIpActivationLinePortMapping`, then the `PPortPrototype` shall be typed by a `DiagnosticDoIPActivationLineInterface`.]

[constr_10591] Restriction for the applicability of `DiagnosticDoIPActivationLineInterface`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is typed by a `DiagnosticDoIPActivationLineInterface`, then the reference in the role `pPortPrototypeInExecutable` to the `PPortPrototype` shall only originate from a `DiagnosticDoIpActivationLinePortMapping`.]

[constr_10592] Existence of `DiagnosticDoIpActivationLinePortMapping.pPortPrototypeInExecutable`*Imposition time:* IT_DiagDes

[For each `DiagnosticDoIpActivationLinePortMapping`, attribute `pPortPrototypeInExecutable` shall exist.]

[constr_10593] Existence of `DiagnosticDoIpActivationLinePortMapping.process`*Imposition time:* IT_DiagDes

[For each `DiagnosticDoIpActivationLinePortMapping`, attribute `process` shall exist.]

[constr_10594] Restriction for the applicability of `DiagnosticDoIpTriggerVehicleAnnouncementPortMapping`*Imposition time:* IT_DiagDes

[If an `RPortPrototype` is referenced in the role `rPortPrototypeInExecutable` by a `DiagnosticDoIpTriggerVehicleAnnouncementPortMapping`, then the `RPortPrototype` shall be typed by a `DiagnosticDoIPTriggerVehicleAnnouncementInterface`.]

[constr_10595] Restriction for the applicability of `DiagnosticDoIPTriggerVehicleAnnouncementInterface`*Imposition time:* IT_DiagDes

[If an `RPortPrototype` is typed by a `DiagnosticDoIPTriggerVehicleAnnouncementInterface`, then the reference in the role `rPortPrototypeInExecutable` to the `PPortPrototype` shall only originate from a `DiagnosticDoIpTriggerVehicleAnnouncementPortMapping`.]

[constr_10596] Existence of `DiagnosticDoIpTriggerVehicleAnnouncementPortMapping.rPortPrototypeInExecutable`*Imposition time:* IT_DiagDes

[For each `DiagnosticDoIpTriggerVehicleAnnouncementPortMapping`, attribute `rPortPrototypeInExecutable` shall exist.]

[constr_10597] Existence of `DiagnosticDoIpTriggerVehicleAnnouncementPortMapping.process`*Imposition time:* IT_DiagDes

[For each `DiagnosticDoIpTriggerVehicleAnnouncementPortMapping`, attribute `process` shall exist.]

[constr_10598] Restriction for the applicability of `DiagnosticDoIpEntityIdentificationPortMapping`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is referenced in the role `pPortPrototypeInExecutable` by a `DiagnosticDoIpEntityIdentificationPortMapping`, then the `PPortPrototype` shall be typed by a `DiagnosticDoIpEntityIdentificationInterface`.]

[constr_10599] Restriction for the applicability of `DiagnosticDoIpEntityIdentificationInterface`*Imposition time:* IT_DiagDes

[If a `RPortPrototype` is typed by a `DiagnosticDoIpEntityIdentificationInterface`, then the reference in the role `pPortPrototypeInExecutable` to the `PPortPrototype` shall only originate from a `DiagnosticDoIpEntityIdentificationPortMapping`.]

[constr_10600] Existence of `DiagnosticDoIpEntityIdentificationPortMapping.pPortPrototypeInExecutable`*Imposition time:* IT_DiagDes

[For each `DiagnosticDoIpEntityIdentificationPortMapping`, attribute `pPortPrototypeInExecutable` shall exist.]

[constr_10601] Existence of `DiagnosticDoIpEntityIdentificationPortMapping.process`*Imposition time:* IT_DiagDes

[For each `DiagnosticDoIpEntityIdentificationPortMapping`, attribute `process` shall exist.]

[constr_10602] Restriction for the applicability of `DiagnosticDoIpPowerModePortMapping`*Imposition time:* IT_DiagDes

[If a `PPortPrototype` is referenced in the role `pPortPrototypeInExecutable` by a `DiagnosticDoIpPowerModePortMapping`, then the `PPortPrototype` shall be typed by a `DiagnosticDoIpPowerModeInterface`.]

[constr_10603] Restriction for the applicability of `DiagnosticDoIPPowerModeInterface`*Imposition time:* IT_DiagDes

[If a `RPortPrototype` is typed by a `DiagnosticDoIPPowerModeInterface`, then the reference in the role `pPortPrototypeInExecutable` to the `PPortPrototype` shall only originate from a `DiagnosticDoIPPowerModePortMapping`.]

[constr_10604] Existence of `DiagnosticDoIpPowerModePortMapping.pPortPrototypeInExecutable`*Imposition time:* IT_DiagDes

[For each `DiagnosticDoIpPowerModePortMapping`, attribute `pPortPrototypeInExecutable` shall exist.]

[constr_10605] Existence of `DiagnosticDoIpPowerModePortMapping.process`*Imposition time:* IT_DiagDes

[For each `DiagnosticDoIpPowerModePortMapping`, attribute `process` shall exist.]

[constr_10609] Existence of references in the role `AbstractDoIpPortMapping.rPortPrototypeInExecutable` and `AbstractDoIpPortMapping.pPortPrototypeInExecutable`*Imposition time:* IT_DiagDes

[For each `AbstractDoIpPortMapping`, only one of the references in the role

- `AbstractDoIpPortMapping.rPortPrototypeInExecutable`
- `AbstractDoIpPortMapping.pPortPrototypeInExecutable`

shall exist.]

[constr_10611] Existence of attribute `DoIpLogicalAddress.logicalAddress`*Imposition time:* IT_SysDes

[For each `DoIpLogicalAddress`, attribute `logicalAddress` shall exist.]

[constr_10612] Standardized values for attribute `CryptoKeySlotDesignDescription.cryptoObjectType`*Imposition time:* IT_SysDes

[In the context of `CryptoKeySlotDesignDescription.cryptoObjectType`, **only** the following values shall be used:

- `PUBLIC_KEY`
- `PRIVATE_KEY`
- `SYMMETRIC_KEY`

]

[constr_10613] CryptoKeySlotDesign where attribute **shared** is set to **false**

Imposition time: IT_SysDes

[A **CryptoKeySlotDesign** where attribute **shared** is set to **false** shall not refer to a **CryptoKeySlotUsageDesign** in the role **user**.]

[constr_10614] Existence of attribute CryptoKeySlotDesign.shared

Imposition time: IT_SysDes

[For each **CryptoKeySlotDesign**, the attribute **shared** shall exist.]

[constr_10616] Existence of the reference in the role StateClientInterface.functionGroupType

Status: DRAFT

Imposition time: IT_Mani

[For each **StateClientInterface**, the reference in the role **functionGroupType** shall exist.]

[constr_10617] Existence of the reference in the role FunctionGroupPortMapping.functionGroup

Status: DRAFT

Imposition time: IT_Mani

[For each **FunctionGroupPortMapping**, the reference in the role **functionGroup** shall exist.]

[constr_10618] Existence of the reference in the role FunctionGroupPortMapping.process

Status: DRAFT

Imposition time: IT_Mani

[For each **FunctionGroupPortMapping**, the reference in the role **process** shall exist.]

[constr_10619] Existence of the reference in the role FunctionGroupPortMapping.rPortPrototypeInExecutable

Status: DRAFT

Imposition time: IT_Mani

[For each **FunctionGroupPortMapping**, the reference in the role **rPortPrototypeInExecutable** shall exist.]

[constr_10620] Reference to function group from FunctionGroupPortMapping

Status: DRAFT

Imposition time: IT_Mani

[Each function group modeled as a **ModeDeclarationGroupPrototype** aggregated by a **FunctionGroupSet** shall only be referenced by a single **FunctionGroupPortMapping**.]

[constr_10621] Same `ModeDeclarationGroup` for `StateClientInterface` and `FunctionGroupPortMapping.functionGroup`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `FunctionGroupPortMapping`, the `ModeDeclarationGroup` referenced in the role `FunctionGroupPortMapping.rPortPrototypeInExecutable.requiredInterface.functionGroupType` shall be identical to the `FunctionGroupPortMapping.functionGroup.type`.]

[constr_10622] Existence of `FunctionGroupPortMapping` depending on the role `rPortPrototypeInExecutable` and `process`*Status:* DRAFT*Imposition time:* IT_Mani

[Each combination of `RPortPrototype` and `Process` may be referenced by **at most one** `FunctionGroupPortMapping` in the roles `rPortPrototypeInExecutable` and `process`.]

[constr_10623] Type of `RPortPrototype` referenced in the role `IdsmQualifiedEventReceiverMapping.rPortPrototypeInExecutable`*Imposition time:* IT_Mani

[An `RPortPrototype` referenced in the role `IdsmQualifiedEventReceiverMapping.rPortPrototypeInExecutable` shall only be typed by a `IdsmQualifiedEventReceiverInterface`.]

[constr_10624] `RPortPrototype` typed by an `IdsmQualifiedEventReceiverInterface`*Imposition time:* IT_Mani

[An `RPortPrototype` that is typed by a `IdsmReportingModeProviderInterface` shall only be referenced in the role `rPortPrototypeInExecutable` by a `IdsmQualifiedEventReceiverMapping`.]

[constr_10625] Existence of `IdsmQualifiedEventReceiverMapping.idsPlatformInstantiation`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `IdsmQualifiedEventReceiverMapping`, the reference to a `IdsPlatformInstantiation` in the role `idsPlatformInstantiation` shall exist.]

[constr_10626] Existence of `IdsmQualifiedEventReceiverMapping.rPortPrototypeInExecutable`*Imposition time:* IT_Mani

[For each `IdsmQualifiedEventReceiverMapping`, the reference to an `RPortPrototype` in the role `rPortPrototypeInExecutable` shall exist.]

[constr_10627] Existence of `IdsmQualifiedEventReceiverMapping.process`*Imposition time:* IT_Mani

[For each `IdsmQualifiedEventReceiverMapping`, the reference to a `Process` in the role `process` shall exist.]

[constr_10628] Allowed range of attribute `TimeSyncCorrection.providerRateDeviationMax`*Imposition time:* IT_Mani

[The value of attribute `TimeSyncCorrection.providerRateDeviationMax` shall only be within the interval [0..32000].]

[constr_10629] `DdsServiceInterfaceDeployment` shall cover all applicable elements of the corresponding `ServiceInterface`*Imposition time:* IT_Mani

[If a `DdsServiceInterfaceDeployment` references a `ServiceInterface` in the role `serviceInterface`, then all `fields`, `triggers`, and `events` defined in the context of the referenced `ServiceInterface` shall be referenced by respective `fieldDeployments` and `eventDeployments` owned by the referencing `DdsServiceInterfaceDeployment`.]

[constr_10630] `PPortPrototype` that is typed by a `DiagnosticDataIdentifierInterface` shall be mapped to a `DiagnosticDataIdentifier`*Imposition time:* IT_DiagDes

[Any `DiagnosticDataPortMapping` that refers to a `PPortPrototype` that is typed by a `DiagnosticDataIdentifierInterface` shall only refer to a `DiagnosticDataIdentifier` in the role `diagnosticDataIdentifier`.

In this case, the existence of the reference in the role `DiagnosticDataPortMapping.diagnosticDataElement` is not permitted.]

[constr_10631] `PPortPrototype` that is typed by a `DiagnosticDataElementInterface` shall be mapped to a `DiagnosticDataElement`*Imposition time:* IT_DiagDes

[Any `DiagnosticDataPortMapping` that refers to a `PPortPrototype` that is typed by a `DiagnosticDataElementInterface` shall only refer to a `DiagnosticDataElement` in the role `diagnosticDataElement`.

In this case, the existence of the reference in the role `DiagnosticDataPortMapping.diagnosticDataIdentifier` is not permitted.]

[constr_10633] Existence of references `StateManagementStateMachineActionItem.overrideInitialState` and `stopAgent`*Status:* DRAFT*Imposition time:* IT_Mani

[If the reference in the role `StateManagementStateMachineActionItem.stopAgent` exists, then the instance reference in the role `overrideInitialState` shall **not** exist.]

[constr_10634] `ClientServerOperation` aggregated by meta-class `DiagnosticDataIdentifierInterface` or meta-class `DiagnosticDataElementInterface`*Imposition time:* IT_BefAraApiGen

[Any `ClientServerOperation` aggregated by a `DiagnosticDataIdentifierInterface` or a `DiagnosticDataElementInterface` shall **not** define the following attributes:

- `fireAndForget`
- `possibleApError`
- `possibleApErrorSet`

]

[constr_10641] Existence of reference in the role `StateManagementModuleInstantiation.maxActionListDuration`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `StateManagementModuleInstantiation`, the attribute `maxActionListDuration` shall exist.]

[constr_10648] Target of the reference in the role `DiagnosticDoIpActivationLinePortMapping.networkConfigurationDesign`*Imposition time:* IT_DiagDes

[A `DoIpNetworkConfiguration` shall only be referenced at most once in the role `DiagnosticDoIpActivationLinePortMapping.networkConfigurationDesign`.]

[constr_10649] Existence of reference in the role `DiagnosticDoIpActivationLinePortMapping.networkConfigurationDesign`*Imposition time:* IT_DiagDes

[If a `DoIpNetworkConfiguration` exists where attribute `isActivationLineDependent` exists and is set to `true`, then a `DiagnosticDoIpActivationLinePortMapping` shall exist that references the `DoIpNetworkConfiguration` in the role `networkConfigurationDesign`.]

[constr_10650] Target of the reference in the role `DiagnosticDoIpTriggerVehicleAnnouncementPortMapping.networkConfigurationDesign`*Imposition time:* IT_DiagDes

[A `DoIpNetworkConfiguration` shall only be referenced at most once in the role `DiagnosticDoIpTriggerVehicleAnnouncementPortMapping.networkConfigurationDesign`.]

[constr_10651] Existence of reference in the role `DiagnosticDoIpTriggerVehicleAnnouncementPortMapping.networkConfigurationDesign`*Imposition time:* IT_DiagDes

[If a `DoIpNetworkConfiguration` exists where attribute `isActivationLineDependent` exists and is set to `false`, then a `DiagnosticDoIpTriggerVehicleAnnouncementPortMapping` shall exist that references the `DoIpNetworkConfiguration` in the role `networkConfigurationDesign`.]

[constr_10652] `SystemMappings` applicable for a `System` of category `MACHINE_DESIGN_EXTRACT`*Imposition time:* IT_SysDes

[A `System` with the category `MACHINE_DESIGN_EXTRACT` is only allowed to aggregate a `SystemMapping` in the role `mapping` that in turn only aggregates one or more `PncMappings` in the role `pncMapping`.

The aggregation of **anything beside** `PncMapping` shall be ignored.]

[constr_10653] Existence of attribute `UriDescription.uri`*Imposition time:* IT_Mani

[For each `UriDescription`, the attribute `uri` shall exist.]

[constr_10654] Existence of `PersistencyFileRequiredComSpec`*Imposition time:* IT_BefAraApiGen

[In the context of any given `RPortPrototype` typed by a `PersistencyFileStorageInterface`, **at most** one `PersistencyFileRequiredComSpec` may exist.]

[constr_10655] Allowed range of values for attribute `ServiceInterfaceDeploymentElement.minimumSendInterval`*Imposition time:* IT_Mani

[The allowed value of attribute `ServiceInterfaceDeploymentElement.minimumSendInterval` shall be within the interval [0.0 .. 10.0].]

[constr_10657] Multiplicity of reference in the role `ProcessDesignToMachineDesignMapping.machineDesign`*Imposition time:* IT_SysDes

[For each `ProcessDesignToMachineDesignMapping`, the reference in the role `machineDesign` shall exist.]

[constr_10658] Multiplicity of the reference in the role `ProcessToMachineMapping.machine`*Imposition time:* IT_Mani

[For each `ProcessToMachineMapping`, the reference in the role `machine` shall exist.]

[constr_10659] Consistency of references in the roles `ProcessDesignToMachineDesignMapping.machineDesign` and `shallRunOn` resp. `shallNotRunOn`*Imposition time:* IT_SysDes

[Any `ProcessorCore` that is referenced in the roles `shallRunOn` and `shallNotRunOn` shall be aggregated (via `MachineDesign.processor`) by the `MachineDesign` referenced in the role `ProcessDesignToMachineDesignMapping.machineDesign`.]

[constr_10660] Usage of `shallRunOn` and `shallNotRunOn` references*Imposition time:* IT_SysDes

[The `ProcessorCore` that is referenced by a `ProcessDesignToMachineDesignMapping` in the role `shallRunOn` or `shallNotRunOn` shall be aggregated by the `MachineDesign` that is referenced in the role `machineDesign` by the same `ProcessDesignToMachineDesignMapping`.]

[constr_10661] Consistency of references `shallRunOn` and `shallNotRunOn`*Imposition time:* IT_SysDes

[Within the context of one `ProcessDesignToMachineDesignMapping`, all `ProcessorCores` referenced in the role `shallRunOn` or `shallNotRunOn` shall be aggregated by the same `Processor`.]

[constr_10662] Mutual exclusive existence of references `shallRunOn` and `shallNotRunOn`*Imposition time:* IT_SysDes

[For any given `ProcessDesignToMachineDesignMapping`, either the reference in the role `shallRunOn` or the reference in the role `shallNotRunOn` may exist.]

[constr_10663] Existence of attribute `DiagnosticCommonProps.authenticationTimeout`*Imposition time:* IT_DiagDes

[If a `DiagnosticContributionSet` that aggregates the `DiagnosticCommonProps` also references a `DiagnosticAuthenticationPortMapping` or `DiagnosticExternalAuthenticationPortMapping`, then attribute `DiagnosticCommonProps.authenticationTimeout` shall exist.]

[constr_10666] Restriction for `StateManagementStateMachineActionItem`

Status: DRAFT

Imposition time: IT_Mani

[No `StateManagementStateMachineActionItem` shall refer (in the roles `startAgent` and `stopAgent`) to any `StateManagementStateNotification.stateMachine` where attribute `category` is set to the value `STATE_MANAGEMENT_CONTROLLER`.]

[constr_10682] Restriction of the multiplicity of `DiagnosticExtendedDataRecordInterface.provide.argument`

Imposition time: IT_BefAraApiGen

[A `ClientServerOperation` aggregated in the role `DiagnosticExtendedDataRecordInterface.provide` shall only aggregate exactly one `argument`.]

[constr_10683] Restriction for the data type of `DiagnosticExtendedDataRecordInterface.provide.argument`

Imposition time: IT_BefAraApiGen

[`DiagnosticExtendedDataRecordInterface.provide.argument` shall only be typed by **either**

- an `ApplicationPrimitiveDataType` **or**
- an `ApplicationArrayDataType` where attribute `element` is typed by an `ApplicationPrimitiveDataType` **or**
- a `CppImplementationDataType` where attribute `category` is set to the value `VALUE` **or**
- a `CppImplementationDataType` where attribute `category` is set to the value `ARRAY` that defines exactly one `subElement` where attribute `category` is set to the value `VALUE`.

]

[constr_10684] Restriction for the applicability of `DiagnosticExtendedDataRecordClientPortMapping`

Imposition time: IT_DiagDes

[If an `RPortPrototype` is referenced by a `DiagnosticExtendedDataRecordClientPortMapping`, then the `RPortPrototype` shall be typed by a `DiagnosticExtendedDataRecordInterface`.]

[constr_10685] Restriction for the reference to an `RPortPrototype` typed by a `DiagnosticExtendedDataRecordInterface`

Imposition time: IT_DiagDes

[If an `RPortPrototype` is typed by a `DiagnosticExtendedDataRecordInterface`, it shall only be referenced in the role `rPortPrototypeInExecutable` by a `DiagnosticExtendedDataRecordClientPortMapping`.]

[constr_10686] Multiplicity of reference in the role `DiagnosticExtendedDataRecordClientPortMapping.recordElement`

Imposition time: IT_DiagDes

[For each `DiagnosticExtendedDataRecordClientPortMapping`, the reference in the role `recordElement` shall exist.]

[constr_10690] Existence of `CryptoAlgorithmDescription.cryptoAlgorithmId`

Imposition time: IT_Mani

[For each `CryptoAlgorithmDescription`, attribute `cryptoAlgorithmId` shall exist.]

[constr_10691] Existence of `CryptoAlgorithmDescription.cryptoKeyType`

Imposition time: IT_Mani

[For each `CryptoAlgorithmDescription`, attribute `cryptoKeyType` shall exist.]

[constr_10692] Existence of aggregation in the role `DiagnosticSovdOperationInterface.start`

Imposition time: IT_BefAraApiGen

[For each `DiagnosticSovdOperationInterface`, the aggregation in the role `start` shall exist.]

[constr_10693] Existence of reference in the role `DiagnosticSovdAccessArgument.contentObject`

Imposition time: IT_BefAraApiGen

[For each `DiagnosticSovdAccessArgument`, the reference in the role `contentObject` shall exist.]

[constr_10694] Restriction for `DiagnosticSovdAccessOperation` aggregated by a `DiagnosticSovdContentInterface`

Imposition time: IT_BefAraApiGen

[If the meta-class `DiagnosticSovdContentInterface` aggregates the two supported roles of `DiagnosticSovdAccessOperations` then

- The two `DiagnosticSovdAccessOperations` shall have the same number of `arguments`.
- The `arguments` on the n^{th} position in the collection of `arguments` shall have identical properties, except the `direction`. In particular, the following conditions shall be fulfilled with respect to attribute `direction`:
 - Any `DiagnosticSovdAccessArgument` aggregated by a `DiagnosticSovdAccessOperation` that is itself aggregated in the role `DiagnosticSovdContentInterface.read` shall set attribute `direction` to `out`.

- Any `DiagnosticSovdAccessArgument` aggregated by a `DiagnosticSovdAccessOperation` that is itself aggregated in the role `DiagnosticSovdContentInterface.write` shall set attribute `direction` to `in`.

]

[constr_10695] Existence of `DiagnosticSovdAccessOperation.argument` if `DiagnosticSovdAccessOperation` that is aggregated in the role `DiagnosticSovdContentElementInterface.read`

Imposition time: IT_BefAraApiGen

[For each `DiagnosticSovdAccessOperation` is aggregated in the role `DiagnosticSovdContentElementInterface.read`, the role `DiagnosticSovdAccessOperation.argument` shall exist exactly once and the attribute `argument.direction` shall be set to `ArgumentDirectionEnum.out`.]

[constr_10696] Target of the reference `DiagnosticSovdContentPortMapping.pPortPrototypeInExecutable`

Imposition time: IT_DiagDes

[Any `DiagnosticSovdContentPortMapping` shall **only** reference in the role `pPortPrototypeInExecutable` a `PPortPrototype` that is typed by either

- a `DiagnosticSovdContentInterface` or
- a `DiagnosticSovdContentElementInterface`.

]

[constr_10697] `DiagnosticSovdContentPortMapping` maps on the level of SOVD Data

Imposition time: IT_DiagDes

[If a `DiagnosticSovdContentPortMapping` references in the role `pPortPrototypeInExecutable` a `PPortPrototype` that is typed by a `DiagnosticSovdContentInterface`, then the `DiagnosticSovdContentPortMapping` shall also refer in the role `content` to a `DiagnosticSovdContent`, and vice versa.]

[constr_10698] `DiagnosticSovdContentPortMapping` maps on the level of SOVD Data Element

Imposition time: IT_DiagDes

[If a `DiagnosticSovdContentPortMapping` references in the role `pPortPrototypeInExecutable` a `PPortPrototype` that is typed by a `DiagnosticSovdContentElementInterface`, then the `DiagnosticSovdContentPortMapping` shall also refer in the role `content` to a `DiagnosticSovdContentElement`, and vice versa.]

[constr_10699] Existence of the Reference in the role `DiagnosticSovdContentPortMapping.pPortPrototypeInExecutable`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdContentPortMapping`, the reference in the role `DiagnosticSovdContentPortMapping.pPortPrototypeInExecutable` shall exist.]

[constr_10700] Existence of the Reference in the role `DiagnosticSovdContentPortMapping.content`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdContentPortMapping`, the reference in the role `DiagnosticSovdContentPortMapping.content` shall exist.]

[constr_10701] Existence of the Reference in the role `DiagnosticSovdContentPortMapping.process`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdContentPortMapping`, the reference in the role `DiagnosticSovdContentPortMapping.process` shall exist.]

[constr_10702] Existence of the Reference in the role `DiagnosticSovdOperationPortMapping.pPortPrototypeInExecutable`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdOperationPortMapping`, the reference in the role `DiagnosticSovdOperationPortMapping.pPortPrototypeInExecutable` shall exist.]

[constr_10703] Existence of the Reference in the role `DiagnosticSovdOperationPortMapping.sovdOperation`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdOperationPortMapping`, the reference in the role `DiagnosticSovdOperationPortMapping.sovdOperation` shall exist.]

[constr_10704] Existence of the Reference in the role `DiagnosticSovdOperationPortMapping.process`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdOperationPortMapping`, the reference in the role `DiagnosticSovdOperationPortMapping.process` shall exist.]

[constr_10705] Restriction regarding references in the roles `DiagnosticSovdDataCategory.group` and `DiagnosticSovdData.sovdGroup`*Imposition time:* IT_DiagDes

[In the scope of any given `DiagnosticSovdData`, every `DiagnosticSovdGroup` that is referenced in the role `DiagnosticSovdData.sovdGroup` shall also be ref-

erenced in the role `DiagnosticSovdDataCategory.group` from the `DiagnosticSovdDataCategory` that is referenced in the role `sovdDataCategory` from the enclosing `DiagnosticSovdData`.]

[constr_10706] Existence of reference in the role `DiagnosticSovdData.sovdDataCategory`

Imposition time: IT_DiagDes

[For each `DiagnosticSovdData`, the reference in the role `sovdDataCategory` shall exist.]

[constr_10707] Relation of the values of attributes `minNumberOfElements` and `maxNumberOfElements`

Imposition time: IT_DiagDes

[The value of attribute `DiagnosticSovdArrayContentElement.minNumberOfElements` shall be **smaller or equal** to the value of `DiagnosticSovdArrayContentElement.maxNumberOfElements`.]

[constr_10708] `DiagnosticSovdContentElement` aggregated in the role `DiagnosticSovdArrayContentElement.element` shall not be declared *optional*

Imposition time: IT_DiagDes

[Any `DiagnosticSovdContentElement` aggregated in the role `DiagnosticSovdArrayContentElement.element` shall not set the value of attribute `isOptional` to `true`.]

[constr_10711] Existence of attribute `DiagnosticSovdArrayContentElement.maxNumberOfElements`

Imposition time: IT_DiagDes

[For each `DiagnosticSovdArrayContentElement`, attribute `maxNumberOfElements` shall exist.]

[constr_10712] Allowed roles within `SwDataDefProps` in the context of `DiagnosticSovdPrimitiveContentElement`

Imposition time: IT_DiagDes

[Only the following roles within `SwDataDefProps` in the context of `DiagnosticSovdPrimitiveContentElement` are allowed:

- `dataConstr`
- `unit`

Any role that is not mentioned in the table above shall **not** be used.]

[constr_10713] Target of the reference `DiagnosticSovdOperationPortMapping.pPortPrototypeInExecutable`*Imposition time:* IT_DiagDes

[Any `DiagnosticSovdOperationPortMapping` shall **only** reference in the role `DiagnosticSovdOperationPortMapping.pPortPrototypeInExecutable` a `PPortPrototype` that is typed by a `DiagnosticSovdOperationInterface`.]

[constr_10714] `PPortPrototype` that is typed by a `DiagnosticSovdOperationInterface` as a mapping target*Imposition time:* IT_DiagDes

[Any `PPortPrototype` that is typed by a `DiagnosticSovdOperationInterface` shall only be referenced in the role `PPortPrototype` that is typed by a `DiagnosticSovdOperationInterface` by `DiagnosticSovdOperationPortMapping`.]

[constr_10715] `DiagnosticSovdOperation` shall not refer to `DiagnosticSovdMethod`*Imposition time:* IT_DiagDes

[Any `DiagnosticSovdOperation` shall not refer to `DiagnosticSovdMethod`.]

[constr_10716] Existence of `DiagnosticSovdOperation.start`*Imposition time:* IT_DiagDes

[The aggregation in the role `DiagnosticSovdOperation.start` shall always exist.]

[constr_10717] Existence of `DiagnosticSovdOperation.proximityProofRequired`*Imposition time:* IT_DiagDes

[The aggregation in the role `DiagnosticSovdOperation.proximityProofRequired` shall always exist.]

[constr_10718] Existence of `DiagnosticEnvSovdDataCondition.compareValue`*Imposition time:* IT_DiagDes

[For each `DiagnosticEnvSovdDataCondition`, that attribute `compareValue` shall exist.]

[constr_10719] Existence of `DiagnosticEnvSovdDataCondition.contentElement`*Imposition time:* IT_DiagDes

[For each `DiagnosticEnvSovdDataCondition`, that attribute `contentElement` shall exist.]

[constr_10720] Restriction for the value of `StateManagementSuspendToRamActionItem.maxActionItemDuration`*Status:* DRAFT*Imposition time:* IT_Mani

[For each `StateManagementSuspendToRamActionItem`, the value of attribute `maxActionItemDuration` shall exist and only have a value greater than 0.]

[constr_10721] Target of `AbstractSuspendToRamMapping.pPortPrototypeInExecutable`*Status:* DRAFT*Imposition time:* IT_Mani

[The target of the instanceRef in the role `AbstractSuspendToRamMapping.pPortPrototypeInExecutable` shall only be a `PPortPrototype` that is typed by a `SuspendToRamSatelliteInterface`.]

[constr_10722] Restriction for `PPortPrototype` that is typed by a `SuspendToRamSatelliteInterface`*Status:* DRAFT*Imposition time:* IT_Mani

[A `PPortPrototype` that is typed by a `SuspendToRamSatelliteInterface` shall only be referenced by a `SuspendToRamSatelliteMapping` in the role `pPortPrototypeInExecutable`.]

[constr_10723] Existence of `SuspendToRamSatelliteMapping.moduleInstantiation`*Status:* DRAFT*Imposition time:* IT_Mani

[For each concrete sub-class of `SuspendToRamSatelliteMapping`, attribute `moduleInstantiation` shall exist.]

[constr_10724] Existence of `SuspendToRamSatelliteMapping.pPortPrototypeInExecutable`*Status:* DRAFT*Imposition time:* IT_Mani

[For each concrete sub-class of `SuspendToRamSatelliteMapping`, attribute `pPortPrototypeInExecutable` shall exist.]

[constr_10725] Existence of `SuspendToRamSatelliteMapping.process`*Status:* DRAFT*Imposition time:* IT_Mani

[For each concrete sub-class of `SuspendToRamSatelliteMapping`, attribute `process` shall exist.]

[constr_10726] Target of `AbstractSuspendToRamMapping.pPortPrototypeInExecutable`*Status:* DRAFT*Imposition time:* IT_Mani

[The target of the instanceRef in the role `AbstractSuspendToRamMapping.pPortPrototypeInExecutable` shall only be a `PPortPrototype` that is typed by a `SuspendToRamHubInterface`.]

[constr_10727] Restriction for `PPortPrototype` that is typed by a `SuspendToRamHubInterface`*Status:* DRAFT*Imposition time:* IT_Mani

[A `PPortPrototype` that is typed by a `SuspendToRamHubInterface` shall only be referenced by a `SuspendToRamHubMapping` in the role `pPortPrototypeInExecutable`.]

[constr_10728] Restriction for `SuspendToRamHubMapping.moduleInstantiation`*Status:* DRAFT*Imposition time:* IT_Mani

[Each `SuspendToRamModuleInstantiation` shall only be referenced from at most one `SuspendToRamHubMapping` in the role `moduleInstantiation`.]

[constr_10729] Existence of `SuspendToRamHubMapping.moduleInstantiation`*Status:* DRAFT*Imposition time:* IT_Mani

[For each concrete sub-class of `SuspendToRamHubMapping`, attribute `moduleInstantiation` shall exist.]

[constr_10730] Existence of `SuspendToRamHubMapping.pPortPrototypeInExecutable`*Status:* DRAFT*Imposition time:* IT_Mani

[For each concrete sub-class of `SuspendToRamHubMapping`, attribute `pPortPrototypeInExecutable` shall exist.]

[constr_10731] Existence of `SuspendToRamHubMapping.process`*Status:* DRAFT*Imposition time:* IT_Mani

[For each concrete sub-class of `SuspendToRamHubMapping`, attribute `process` shall exist.]

[constr_10732] Existence of attributes `DiagnosticExtendedDataRecord.trigger` and `update` on the *AUTOSAR adaptive platform**Imposition time:* AP: IT_DiagDes

[For each `DiagnosticExtendedDataRecord`, attributes `trigger` and `update` shall only exist if at least one `DiagnosticExtendedDataRecordElement` is aggregated by a `DiagnosticExtendedDataRecord` in the role `element` that is referenced in the role `DiagnosticExtendedDataRecordClientPortMapping.recordElement`.]

[constr_10733] Uniqueness of reference from `DiagnosticSovdConfigContentMapping` to `DiagnosticSovdConfigurationParameter`*Imposition time:* IT_DiagDes

[Each instance of a sub-class of `DiagnosticSovdConfigurationParameter` shall only be referenced by exactly one `DiagnosticSovdConfigContentMapping`.]

[constr_10734] Existence of the reference in the role `DiagnosticSovdConfigContentMapping.serviceInstance`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdConfigContentMapping`, the reference in the role `DiagnosticSovdConfigContentMapping.serviceInstance` shall exist.]

[constr_10735] Existence of the reference in the role `DiagnosticSovdConfigContentMapping.content`*Imposition time:* IT_DiagDes

[For each `DiagnosticSovdConfigContentMapping`, the reference in the role `DiagnosticSovdConfigContentMapping.content` shall exist.]

2.3 AP_TPS_TimingExtensions

[constr_4569] Restricted usage of Occurrence Expression functions*Status:* DRAFT

[The functions:

- `TIMEX_occurs`,
- `TIMEX_hasOccurred`,
- `TIMEX_timeSinceLastOccurrence`,
- `TIMEX_angleSinceLastOccurrence`,
- `TIMEX_modeActive`

shall only be used for an occurrence expression applied to a `TDEventComplex`.]

[constr_4570] Application rule for the occurrence expression in [TDEventComplex](#)*Status:* DRAFT

[The occurrence expression shall be specified such that it describes an *event* rather than a state. As a consequence the occurrence expression shall ensure that a complex timing event *could* only occur at the occurrence time of one of the referenced [TimingDescriptionEvents](#).]

[constr_4571] Use references only as function operands*Status:* DRAFT

[The references to model elements (e.g. the *timing event* reference targeting [TimingDescriptionEvent](#)) do have specific semantics. The usage of these references within the expression is *only* allowed as operand of the functions mentioned above.]

[constr_4572] Restricted usage of [AutosarOperationArgumentInstance](#) for Content Filter*Status:* DRAFT

[If a content filter is defined for an atomic event then references to [AutosarOperationArgumentInstances](#) are only allowed if the atomic event is of type [TDEventOperation](#). Only if such an atomic event occurs, the value of the operation arguments can be evaluated. Thus, also the scope of the atomic event shall be the same as the [AutosarOperationArgumentInstance](#), meaning that they shall point to the same [ClientServerOperation](#). Finally, references to an [AutosarOperationArgumentInstance](#) with argument direction "out" are only allowed, if the atomic event of type [TDEventOperation](#) refers either to the point in time when the operation call response has been sent (TD-EVENT-OPERATION-TYPE=OPERATION-CALL-RESPONSE-SENT) or to the point in time when the operation call response has been received (TD-EVENT-OPERATION-TYPE=OPERATION-CALL-RESPONSE-RECEIVED).]

[constr_4573] Restricted usage of [AgeConstraint](#)*Status:* DRAFT

[An [AgeConstraint](#) shall only be defined for events of type [TimingDescriptionEvent](#) associated with the receipt and reading of data.]

[constr_4574] Specifying minimum and maximum number of occurrences*Status:* DRAFT

[The minimum and maximum number of occurrences shall be specified such that the following holds: $0 \leq \text{minNumberOfOccurrences} \leq \text{maxNumberOfOccurrences}$.]

[constr_4575] Specifying minimum inter-arrival time and pattern length*Status:* DRAFT

[The minimum inter-arrival time and pattern length shall be specified such that the following holds: $0 < \text{minimumInterArrivalTime} \leq \text{patternLength}$.]

[constr_4576] Specifying pattern length, pattern jitter and pattern period*Status:* DRAFT

[The pattern length, pattern jitter and pattern period shall be specified such that the following holds: $\text{patternLength} + \text{patternJitter} < \text{patternPeriod}$.]

[constr_4579] `SynchronizationTimingConstraint` shall reference at least two events*Status:* DRAFT

[In the case, that the `SynchronizationTimingConstraint` is imposed on events then at least two (2) timing description events shall be referenced.]

[constr_4580] `SynchronizationTimingConstraint` shall reference at least two event chains*Status:* DRAFT

[In the case, that the `SynchronizationTimingConstraint` is imposed on event chains then at least two (2) timing description event chains shall be referenced.]

[constr_4581] Specifying stimulus and response in `TimingDescriptionEventChain`*Status:* DRAFT*Imposition time:* IT_SubClassTeAss

[The references between `TimingDescriptionEventChain` and `TimingDescriptionEvent` playing the role `stimulus` and `response` shall not reference the same `TimingDescriptionEvent`.]

[constr_4582] Specifying event chain `segments`*Status:* DRAFT

[If a `TimingDescriptionEventChain` consists of further event chain `segments` then at least one sequence of event chain `segments` shall exist from the event chain's `stimulus` to the `response`.]

[constr_4583] Referencing no further event chain `segments`*Status:* DRAFT

[If a `TimingDescriptionEventChain` is not subdivided in further event chain `segments`, then the reference playing the role of `segment` shall reference this `TimingDescriptionEventChain`. In other words, an event chain without any event chain `segments` shall reference itself.]

[constr_4584] Specifying `stimulus` event and `response` event of first and last event chain segment*Status:* DRAFT

[The `stimulus` event of the first event chain segment and the `response` event of the last event chain segment shall reference the `stimulus` and `response` of the parent event chain the event chain segments directly belong to.]

[constr_4585] Specifying `patternLength`*Status:* DRAFT

[The `patternLength` shall be specified such that the following holds: $0 \leq \max(\text{offset}) \leq \text{patternLength}$.]

[constr_4586] Specifying attribute `synchronizationConstraintType`*Status:* DRAFT

[The attribute `synchronizationConstraintType` shall be specified if the `SynchronizationTimingConstraint` is imposed on events.]

[constr_4587] Specifying attribute `synchronizationConstraintType`*Status:* DRAFT

[The attribute `synchronizationConstraintType` shall be specified if the `SynchronizationTimingConstraint` is imposed on event chains.]

[constr_4588] `SynchronizationTimingConstraint` shall either reference events or event chains*Status:* DRAFT

[The `SynchronizationTimingConstraint` shall either reference timing description events or timing description event chains, but not both at the same time.]

[constr_4589] Maximum value of the parameter `minimumInterArrivalTime`*Status:* DRAFT

[The value of the parameter `minimumInterArrivalTime` shall be less than or equal the value of the parameter `period`.]

[constr_4590] Specifying `patternLength`, `patternJitter` and `patternPeriod`*Status:* DRAFT

[The pattern length, pattern jitter and pattern period shall be specified such that the following holds: $\text{patternLength} + \text{patternJitter} < \text{patternPeriod}$.]

[constr_4591] Use only Numericals in `TDEventOccurrenceExpression`*Status:* DRAFT

[The target data prototype of the instance references of `variable` and `argument` shall be `Numerical`.]

[constr_4592] Restricted usage of `AutosarVariableInstance` for Content Filter*Status:* DRAFT

[If a content filter is defined for an atomic event then references to `AutosarVariableInstances` are only allowed if the atomic event is of type `TDEventVariableDataPrototype`. Only if such an atomic event occurs, the value of the variables

can be evaluated. Thus, also the scope of the atomic event shall be the same as the `AutosarVariableInstance`, meaning that they shall point to the same `Variable-DataPrototype`.]

[constr_6902] Existence of `ExecutableTiming.executable` [For each `ExecutableTiming`, the reference to a `Executable` in the role `executable` shall exist at the time when the `Executable Timing Description` is complete.]

[constr_6903] Existence of `ServiceTiming.serviceInstance` [For each `ServiceTiming`, the reference to a `AdaptivePlatformServiceInstance` in the role `serviceInstance` shall exist at the time when the `Service Timing Description` is complete.]

[constr_6904] Existence of `MachineTiming.machine` [For each `MachineTiming`, the reference to a `Machine` in the role `machine` shall exist at the time when the `Machine Timing Description` is complete.]

A Mentioned Class Tables

Class	AbstractCryptoKeySlotToPortPrototypeMapping (abstract)			
Note	This abstract meta-class acts as a base class for crypto key slot mappings. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDeploymentElement, UploadablePackageElement			
Subclasses	CryptoKeySlotToClientPortPrototypeMapping, CryptoKeySlotToPortPrototypeMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
allowPlainTextExport	Boolean	0..1	attr	This attribute describes whether the key slot content is allowed to be exported in plaintext format or not by the application referenced in the role process. Plaintext export is only possible if supported by the cryptographic module and by the CryptoProvider implementation and if the key has been generated/ imported with the keySlot.keySlotContentAllowed Usage.allowedKeyslotUsage set to exportable.
allowPlainTextImport	Boolean	0..1	attr	This attribute describes whether the key slot content is allowed to be imported in plaintext format or not by the application referenced in the role process. Plaintext import is only possible if supported by the cryptographic module and by the CryptoProvider implementation.
keySlot	CryptoKeySlot	0..1	ref	This reference represents the mapped CryptoKeySlot.
portPrototype	RPortPrototype	0..1	iref	This reference represents the mapped PortPrototype. InstanceRef implemented by: RPortPrototypeIn ExecutableInstanceRef
process	Process	0..1	ref	This reference represents the process required as context for the mapping.

Table A.1: AbstractCryptoKeySlotToPortPrototypeMapping

Class	AbstractDolpPortMapping (abstract)			
Note	This meta-class acts as an abstract base class for DoLP-related mappings. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping, DiagnosticSwMapping, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Subclasses	DiagnosticDolpActivationLinePortMapping, DiagnosticDolpEntityIdentificationPortMapping, DiagnosticDolpGroupIdentificationPortMapping, DiagnosticDolpPowerModePortMapping, DiagnosticDolpTrigger VehicleAnnouncementPortMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
pPortPrototypeInExecutable	PPortPrototype	0..1	iref	This identifies the PPortPrototype for which the Abstract DolpPortMapping is applicable. Stereotypes: atpUriDef InstanceRef implemented by: PPortPrototypeIn ExecutableInstanceRef
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atpSplitable Tags: atp.Splitkey=process





Class	AbstractDolpPortMapping (abstract)			
rPortPrototype InExecutable	RPortPrototype	0..1	iref	This identifies the RPortPrototype for which the Abstract DolpPortMapping is applicable. Stereotypes: atpUriDef InstanceRef implemented by: RPortPrototypeInExecutableInstanceRef

Table A.2: AbstractDolpPortMapping

Class	AbstractImplementationDataType (abstract)			
Note	This meta-class represents an abstract base class for different flavors of ImplementationDataType.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, AutosarDataType , CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Subclasses	CplusplusImplementationDataType , ImplementationDataType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.3: AbstractImplementationDataType

Class	AbstractImplementationDataTypeElement (abstract)			
Note	This meta-class represents the ability to act as an abstract base class for specific derived meta-classes that support the modeling of ImplementationDataTypes for a particular language binding.			
Base	ARObject, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable , MultilanguageReferrable, Referrable			
Subclasses	CplusplusImplementationDataTypeElement , ImplementationDataTypeElement			
Aggregated by	AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.4: AbstractImplementationDataTypeElement

Class	AbstractPersistencyRequireComSpec (abstract)			
Note	This meta-class acts as a bas-class of persistency-related ComSpec classes. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, RPortComSpec			
Subclasses	PersistencyDataRequiredComSpec , PersistencyFileRequiredComSpec			
Aggregated by	AbstractRequiredPortPrototype.requiredComSpec , PortPrototypeBlueprint.requiredComSpec			
Attribute	Type	Mult.	Kind	Note
accessMode	PersistencyAccess Enum	0..1	attr	This attribute controls how persistent data can be accessed.

Table A.5: AbstractPersistencyRequireComSpec

Class	AbstractRawDataStreamEthernetCredentials (abstract)			
Note	This meta-class serves as an abstract base class for the configuration of network credentials. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Describable			
Subclasses	RawDataStreamEthernetTcpUdpCredentials , RawDataStreamEthernetUdpCredentials			





Class	AbstractRawDataStreamEthernetCredentials (abstract)			
Attribute	Type	Mult.	Kind	Note
ipV4Address	Ip4AddressString	0..1	attr	This attribute describes the IP V4 address of the remote server.
ipV6Address	Ip6AddressString	0..1	attr	This attribute describes the IP V6 address of the remote server.
udpPort	PositiveInteger	0..1	attr	This attribute represents the configuration of a UDP port number.

Table A.6: AbstractRawDataStreamEthernetCredentials

Class	AbstractServiceInstance (abstract)			
Note	Provided and Consumed Ethernet Service Instances that are available at the ApplicationEndpoint.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Subclasses	ConsumedServiceInstance, DdsCpServiceInstance , ProvidedServiceInstance			
Aggregated by	ServiceInstanceCollectionSet.serviceInstance			
Attribute	Type	Mult.	Kind	Note
capability Record	TagWithOptionalValue	*	aggr	A sequence of records to store arbitrary name/value pairs conveying additional information about the named service. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=capabilityRecord, capabilityRecord.variationPoint.shortLabel vh.latestBindingTime=postBuild
majorVersion	PositiveInteger	0..1	attr	Major Version of the ServiceInterface. Value can be set to a number that represents the Major Version of the service.
method Activation RoutingGroup	PduActivationRouting Group	0..1	aggr	The ServiceDiscovery module is able to activate and deactivate the PDU routing for ClientServerOperations (SOME/IP methods). Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=methodActivationRoutingGroup.shortName, methodActivationRoutingGroup.variationPoint.shortLabel vh.latestBindingTime=postBuild

Table A.7: AbstractServiceInstance

Class	AbstractSignalBasedToSignalTriggeringMapping (abstract)			
Note	This meta-class is the common class for all SignalBased to ISignalTriggering mappings. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Subclasses	SignalBasedEventElementToSignalTriggeringMapping , SignalBasedFieldToSignalTriggeringMapping , SignalBasedFireAndForgetMethodToSignalTriggeringMapping , SignalBasedTriggerToSignalTriggeringMapping			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.8: AbstractSignalBasedToSignalTriggeringMapping

Class	AbstractSuspendToRamMapping (abstract)			
Note	This meta-class acts as an abstract base class for suspend-to-RAM-related mappings. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Subclasses	SuspendToRamHubMapping , SuspendToRamSatelliteMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
module Instantiation	SuspendToRamModule Instantiation	0..1	ref	This reference identifies the applicable suspend-to-RAM module instantiation. Tags: atp.Status=candidate
pPortPrototype InExecutable	PPortPrototype	0..1	iref	This reference identifies the suspend-to-RAM-related port. Stereotypes: atp.UriDef Tags: atp.Status=candidate InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	Process	0..1	ref	This reference identifies the Process in which the Executable referenced in the role pPortPrototypeInExecutable is executed. Tags: atp.Status=candidate

Table A.9: AbstractSuspendToRamMapping

Class	AdaptiveApplicationSwComponentType			
Note	This meta-class represents the ability to support the formal modeling of application software on the AUTOSAR adaptive platform. Consequently, it shall only be used on the AUTOSAR adaptive platform. Tags: atp.recommendedPackage=AdaptiveApplicationSwComponentTypes This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , SwComponentType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
internalBehavior	AdaptiveSwcInternal Behavior	0..1	aggr	This aggregation represents the internal behavior of the AdaptiveApplicationSwComponentType for the AUTOSAR adaptive platform. Stereotypes: atp.Splitable; atp.Variation Tags: atp.Splitkey=internalBehavior.shortName, internalBehavior.variationPoint.shortLabel vh.latestBindingTime=preCompileTime

Table A.10: AdaptiveApplicationSwComponentType

Class	AdaptiveFirewallToPortPrototypeMapping			
Note	This meta-class maps the AdaptiveFirewall moduleInstantiation to the RPortPrototype that is typed by a FirewallModeSwitchInterface. Tags: atp.Status=candidate atp.recommendedPackage=AdaptiveFirewallToPortPrototypeMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	AdaptiveFirewallToPortPrototypeMapping			
firewall	AdaptiveFirewallModule Instantiation	0..1	ref	Reference to the Firewall module Tags: atp.Status=candidate
process	Process	0..1	ref	The referenced Process is supposed to define the Port Prototype typed by a FirewallStateSwitchInterface, referenced by the enclosing mapping class. If this reference does not exist, any Process using the respective API can switch the firewall state. Tags: atp.Status=candidate
rPortPrototype	RPortPrototype	0..1	ref	Reference to RPortPrototype typed by a FirewallMode SwitchInterface Tags: atp.Status=candidate

Table A.11: AdaptiveFirewallToPortPrototypeMapping

Class	AdaptivePlatformServiceInstance (abstract)			
Note	This meta-class represents the ability to describe the existence and configuration of a service instance in an abstract way. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement</i>			
Subclasses	ProvidedApServiceInstance , RequiredApServiceInstance			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
e2eEvent ProtectionProps	End2EndEvent ProtectionProps	*	aggr	This aggregation allows to protect an event or a field notifier that is defined inside of the ServiceInterface that is referenced by the ServiceInstance in the role service Interface.
e2eMethod ProtectionProps	End2EndMethod ProtectionProps	*	aggr	This aggregation allows to protect a method or a field getter or a field setter that is defined inside of the Service Interface that is referenced by the ServiceInstance in the role serviceInterface
secureCom Config	ServiceInterface ElementSecureCom Config	*	aggr	Configuration settings to secure the communication of ServiceInterface elements.
serviceInterface Deployment	ServiceInterface Deployment	0..1	ref	Reference to a ServiceInterfaceDeployment that identifies the ServiceInterface that is represented by the Service Instance.

Table A.12: AdaptivePlatformServiceInstance

Class	AgeConstraint			
Note	Constrains the scope by a minimum and maximum time boundary.			
Base	<i>ARObject, Identifiable, MultilanguageReferrable, Referrable, TimingConstraint, Traceable</i>			
Aggregated by	<i>TimingExtension.timingGuarantee, TimingExtension.timingRequirement</i>			
Attribute	Type	Mult.	Kind	Note
maximum	MultidimensionalTime	0..1	aggr	The received event referenced by scope should not exceed this upper bound.
minimum	MultidimensionalTime	0..1	aggr	The received event referenced by scope should not precede this lower bound.
scope	TimingDescriptionEvent	0..1	ref	TimingDescriptionEvent to be constrained.

Table A.13: AgeConstraint

Class	AliveSupervision			
Note	Defines an AliveSupervision for one checkpoint. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , PhmSupervision , Referrable			
Aggregated by	GlobalSupervision.aliveSupervision			
Attribute	Type	Mult.	Kind	Note
aliveReferenceCycle	TimeValue	0..1	attr	Time period at which the Alive Supervision mechanism compares the amount of received Alive Indications for the SupervisionCheckpoint against the expectedAliveIndications.
checkpoint	SupervisionCheckpoint	0..1	ref	Reference to a checkpoint in the context of Alive Supervision.
expectedAliveIndications	PositiveInteger	0..1	attr	Defines the amount of expected Alive Indications of the SupervisionCheckpoint within the aliveReferenceCycle.
failedReferenceCyclesTolerance	PositiveInteger	0..1	attr	This attribute defines the acceptable amount of alive ReferenceCycles with incorrect/failed AliveSupervision.
maxMargin	PositiveInteger	0..1	attr	Defines the amount of Alive Indications of the SupervisionCheckpoint that are acceptable to be additional to the expectedAliveIndications within the aliveReferenceCycle.
minMargin	PositiveInteger	0..1	attr	Defines the amount of Alive Indications of the SupervisionCheckpoint that are acceptable to be missing to the expectedAliveIndications within the aliveReferenceCycle.
terminatingCheckpoint	SupervisionCheckpoint	0..1	ref	Reference to the SupervisionCheckpoint which is defined as the terminating checkpoint of this AliveSupervision.
terminatingCheckpointTimeoutUntilTermination	TimeValue	0..1	attr	Defines the time a process shall terminate after it has announced its start of termination by reporting terminatingCheckpoint.

Table A.14: AliveSupervision

Class	Allocator			
Note	This meta-class represents the ability to specify an optional custom C++ allocator for a C++ type which may dynamically grow beyond it's initial allocated size during it's lifetime. Any storage principles are defined in the implementation of the allocator itself, which should implement the ISO C++ std::allocator_traits interface. Tags: atp.recommendedPackage=Allocators This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
headerFile	String	0..1	attr	Configuration of the Header File with the custom class declaration
namespace (ordered)	SymbolProps	*	aggr	This aggregation allows for the definition of a namespace of an Allocator.

Table A.15: Allocator

Class	ApApplicationEndpoint			
Note	An application endpoint is the endpoint on an Ecu in terms of application addressing (e.g. UDP or TCP Port). This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			





Class	ApApplicationEndpoint			
Aggregated by	EthernetCommunicationConnector.apApplicationEndpoint			
Attribute	Type	Mult.	Kind	Note
priority	PositiveInteger	0..1	attr	This attribute defines the VLAN frame priority where values from 0 (best effort) to 7 (highest) are allowed.
tpConfiguration	TcpUdpConfig	0..1	aggr	Configuration of the used transport protocol.

Table A.16: ApApplicationEndpoint

Class	ApApplicationError			
Note	This meta-class represents the ability to formally specify the semantics of an application error on the AUTOSAR adaptive platform Tags: atp.recommendedPackage=ApplicationErrors This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
errorCode	Integer	0..1	attr	This attribute has the ability to specify the error code value within the enclosing AdaptivePlatformApplication Error.
errorDomain	ApApplicationErrorDomain	0..1	ref	This reference represents the error domain of the Ap ApplicationError.

Table A.17: ApApplicationError

Class	ApApplicationErrorDomain			
Note	This meta-class represents the ability to define a global error domain for an ApApplicationError. Tags: atp.recommendedPackage=ApplicationErrorDomains This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
namespace (ordered)	SymbolProps	*	aggr	This aggregation defines the namespace of the Ap ApplicationErrorDomain
value	PositiveUnlimitedInteger	0..1	attr	This attribute identifies the error category.

Table A.18: ApApplicationErrorDomain

Class	ApApplicationErrorSet			
Note	This meta-class acts as a reference target that represents an entire collection of ApApplicationErrors. This takes the burden from ClientServerOperations that reference a larger number of ApApplication Errors. Tags: atp.recommendedPackage=ApplicationErrorSets This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
apApplication Error	ApApplicationError	*	ref	This reference represents the collection of ApApplication Error represented by the enclosing ApApplicationErrorSet

Table A.19: ApApplicationErrorSet

Class	ApSomeipTransformationProps			
Note	SOME/IP serialization properties. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i> , <i>TransformationProps</i>			
Aggregated by	TransformationPropsSet.transformationProps			
Attribute	Type	Mult.	Kind	Note
alignment	PositiveInteger	0..1	attr	Defines the padding for alignment purposes that will be added by the SOME/IP transformer after the serialized data of the variable data length data element. The alignment shall be specified in Bits.
byteOrder	ByteOrderEnum	0..1	attr	Specifies the byte order of data in the serialized data stream.
isDynamicLengthFieldSize	Boolean	0..1	attr	This attribute represents the ability to control the setting of the wire type for TLV encoding.
sizeOfArrayLengthField	PositiveInteger	0..1	attr	Configures the SOME/IP serialization for the referenced dataPrototype in case of a variable size Array (Vector), fixed-size Array or an Associative_Map. It describes the size of the length field (in Bytes) that will be put in front of the Array or Associative_Map in the SOME/IP message.
sizeOfStringLengthField	PositiveInteger	0..1	attr	Configures the SOME/IP serialization for the referenced dataPrototype in case of a String. It describes the size of the length field (in Bytes) that will be put in front of the String in the SOME/IP message.
sizeOfStructLengthField	PositiveInteger	0..1	attr	Configures the SOME/IP serialization for the referenced dataPrototype in case of an Struct. It describes the size of the length field (in Bytes) that will be put in front of the Struct in the SOME/IP message.
sizeOfUnionLengthField	PositiveInteger	0..1	attr	Configures the SOME/IP serialization for the referenced dataPrototype in case of a Union. It describes the size of the length field (in Bytes) that will be put in front of the Union in the SOME/IP message.
sizeOfUnionTypeSelectorField	PositiveInteger	0..1	attr	Configures the SOME/IP serialization for the referenced dataPrototype in case of a Union. It describes the size of the type selector field (in Bytes) that will be put in front of the Union in the SOME/IP message.
stringEncoding	BaseTypeEncodingString	0..1	attr	Configures the encoding for SOME/IP serialization for the referenced dataPrototype in case of an String.

Table A.20: ApSomeipTransformationProps

Class	ApmcAbstractValue (abstract)			
Note	This abstract meta-class implements the "value" side of the abstract structure for the machine configuration. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i>			
Subclasses	<i>ApmcContainerElementValue</i> , <i>ApmcContainerValue</i> , <i>ApmcFunctionalClusterValue</i>			
Attribute	Type	Mult.	Kind	Note
definition	ApmcAbstractDefinition	0..1	ref	This reference implements the relation of "value" side to "definition" side in the abstract structure of the machine configuration model. Stereotypes: atpAbstract Tags: atp.Status=candidate

Table A.21: ApmcAbstractValue

Class	ApmcBooleanParamDef			
Note	This meta-class represents a boolean parameter on the "definition" side of the target-configuration. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractDefinition, ApmcConfigurationElementDef, ApmcContainerElementDef, ApmcDefinitionElement , ApmcParameterDef, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	ApmcParamConfContainerDef.element			
Attribute	Type	Mult.	Kind	Note
defaultValue	Boolean	0..1	attr	This attribute represents the definition of the default value for the enclosing parameter. The default value applies if the parameter is instantiated on the "value" side without assigning a dedicated value to it. Tags: atp.Status=candidate

Table A.22: ApmcBooleanParamDef

Class	ApmcContainerElementValue (abstract)			
Note	This abstract meta-class represents an element of a container on the "value" side of the target-configuration. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractValue , ApmcIndexableValue, Identifiable , MultilanguageReferrable, Referrable			
Subclasses	ApmcParameterValue , ApmcReferenceValue			
Aggregated by	ApmcContainerValue.element			
Attribute	Type	Mult.	Kind	Note
definition	ApmcContainerElementDef	0..1	ref	This reference implements the concrete relation of container element configuration on the "value" side to container element configuration on the "definition" side in the abstract structure of the machine configuration model. Tags: atp.Status=candidate

Table A.23: ApmcContainerElementValue

Class	ApmcContainerReferenceDef			
Note	This meta-class represents a reference to another container of the target-configuration. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractDefinition, ApmcConfigurationElementDef, ApmcContainerElementDef, ApmcDefinitionElement , ApmcReferenceDef , Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	ApmcParamConfContainerDef.element			
Attribute	Type	Mult.	Kind	Note
destination	ApmcContainerDef	0..1	ref	This reference identifies the target container. Tags: atp.Status=candidate
isFunctionClusterEndpointRef	Boolean	0..1	attr	This attribute indicates whether the enclosing ApmcContainerReferenceDef identifies endpoint for the interaction with other functional clusters. Tags: atp.Status=candidate

Table A.24: ApmcContainerReferenceDef

Class	ApmcContainerValue			
Note	This meta-class represents a container on the "value" side of the target-configuration. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			





Class	ApmcContainerValue			
Base	ARObject, ApmcAbstractValue , ApmcIndexableValue , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApmcContainerValue.container , ApmcFunctionalClusterValue.container			
Attribute	Type	Mult.	Kind	Note
container	ApmcContainerValue	*	aggr	This aggregation represents the collection of sub-containers of the enclosing container. By using this aggregation arbitrary nested structures of containers can be created. Stereotypes: atpSplitable Tags: atp.Splitkey=container.shortName atp.Status=candidate
definition	ApmcContainerDef	0..1	ref	This reference implements the concrete relation of container configuration on the "value" side to container configuration on the "definition" side in the abstract structure of the machine configuration model.
element	ApmcContainerElementValue	*	aggr	This aggregation represents the collection of elements in the container. Stereotypes: atpSplitable Tags: atp.Splitkey=element.shortName atp.Status=candidate

Table A.25: ApmcContainerValue

Class	ApmcDefinitionElement (abstract)			
Note	This abstract class contributes basic properties to the modeling of classes on the "definition" side of the target-configuration. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Subclasses	ApmcContainerDef , ApmcContainerElementDef , ApmcFunctionalClusterDef			
Attribute	Type	Mult.	Kind	Note
element Creation	ApmcElementCreation Enum	0..1	attr	This attribute gives a hint about how (in terms of the AUTOSAR workflow) the model element comes into existence. Tags: atp.Status=candidate xml.sequenceOffset=10
lowerMultiplicity	PositiveInteger	0..1	attr	This attribute specifies the lower multiplicity of the respective model element. Tags: atp.Status=candidate xml.sequenceOffset=30
relatedTrace Item	Traceable	0..1	ref	This contains a sloppy reference to the formal ID of the element. Stereotypes: atpUriDef Tags: atp.Status=candidate xml.sequenceOffset=20
upperMultiplicity	PositiveInteger	0..1	attr	This attribute specifies the upper multiplicity of the respective model element. Tags: atp.Status=candidate xml.sequenceOffset=40





Class	ApmcDefinitionElement (abstract)			
upperMultiplicity IsInfinite	Boolean	0..1	attr	This attribute indicates (if set to true) that the upper multiplicity is set to "infinite". Tags: atp.Status=candidate xml.sequenceOffset=50

Table A.26: ApmcDefinitionElement

Class	ApmcEnumerationLiteralDef			
Note	This meta-class represents an enumerator (or enumeration literal) on the "definition" side of the target-configuration. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApmcEnumerationParamDef.literal			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.27: ApmcEnumerationLiteralDef

Class	ApmcEnumerationParamDef			
Note	This meta-class represents an enumeration parameter on the "definition" side of the target-configuration. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractDefinition , ApmcConfigurationElementDef , ApmcContainerElementDef , ApmcDefinitionElement , ApmcParameterDef , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApmcParamConfContainerDef.element			
Attribute	Type	Mult.	Kind	Note
defaultValue	Identifier	0..1	attr	This attribute represents the definition of the default value for the enclosing parameter. The default value applies if the parameter is instantiated on the "value" side without assigning a dedicated value to it. Tags: atp.Status=candidate
literal	ApmcEnumerationLiteralDef	*	aggr	This aggregation represents the collection of enumerators that are part of the enumeration. Stereotypes: atp.Splitable Tags: atp.Splitkey=literal.shortName atp.Status=candidate

Table A.28: ApmcEnumerationParamDef

Class	ApmcFunctionalClusterDef			
Note	This class represents the entry point into the configuration of a single functional cluster on the AUTOSAR adaptive platform on the "definition" side. Tags: atp.Status=candidate atp.recommendedPackage=FunctionalClusterDefinitions This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, ApmcAbstractDefinition , ApmcDefinitionElement , AtpBlueprint , AtpBlueprintable , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadablePackageElement			
Aggregated by	ARPackage.element			





Class	ApmcFunctionalClusterDef			
Attribute	Type	Mult.	Kind	Note
container	ApmcContainerDef	*	aggr	This aggregation represents the collection of containers aggregated directly by the functional cluster configuration definition. Stereotypes: atpSplitable Tags: atp.Splitkey=container.shortName atp.Status=candidate

Table A.29: ApmcFunctionalClusterDef

Class	ApmcFunctionalClusterValue			
Note	This class represents the entry point into the configuration of a single functional cluster on the AUTOSAR adaptive platform on the "value" side. Tags: atp.Status=candidate atp.recommendedPackage=FunctionalClusterValues This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, ApmcAbstractValue , CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
container	ApmcContainerValue	*	aggr	This aggregation represents the collection of containers aggregated directly by the functional cluster configuration definition. Stereotypes: atpSplitable Tags: atp.Splitkey=container.shortName atp.Status=candidate
definition	ApmcFunctionalClusterDef	0..1	ref	This reference implements the concrete relation of functional cluster configuration on the "value" side to functional cluster configuration on the "definition" side in the abstract structure of the machine configuration model.

Table A.30: ApmcFunctionalClusterValue

Class	ApmclpV4AddressParamDef			
Note	This meta-class represents an restricted string parameter for the specification of an IP V4 address (notation: 255.255.255.255) on the "definition" side of the target-configuration. Tags: atp.Status=candidate xml.name=APMC-IP-V4-ADDRESS-PARAM-DEF This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractDefinition, ApmcAbstractRestrictedStringParamDef, ApmcConfigurationElementDef, ApmcContainerElementDef, ApmcDefinitionElement , ApmcParameterDef, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	ApmcParamConfContainerDef .element			
Attribute	Type	Mult.	Kind	Note
defaultValue	Ip4AddressString	0..1	attr	This attribute implements the default value of the IP V4 address. Tags: atp.Status=candidate

Table A.31: ApmclpV4AddressParamDef

Class	ApmcIpV4AddressParamValue			
Note	This meta-class represents a restricted textual parameter for the specification of an IP V4 address on the "value" side of the target-configuration. Tags: atp.Status=candidate xml.name=APMC-IP-V4-ADDRESS-PARAM-VALUE This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractRestrictedTextualParamValue, ApmcAbstractValue , ApmcContainerElementValue , ApmcIndexableValue , ApmcParameterValue , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApmcContainerValue.element			
Attribute	Type	Mult.	Kind	Note
value	Ip4AddressString	0..1	attr	This attribute implements the actual value of the IP V4 address. Tags: atp.Status=candidate

Table A.32: ApmcIpV4AddressParamValue

Class	ApmcIpV6AddressParamDef			
Note	This meta-class represents an restricted string parameter for the specification of an IP V4 address (notation: 255.255.255.255) on the "definition" side of the target-configuration. Notation: FFFF:FFFF:FFFF:FFFF:FFFF:FFFF:FFFF:FFFF Alternative notations, short-cuts with duplicate colons like ::, etc. or mixtures using colons and dots, are not allowed. Tags: atp.Status=candidate xml.name=APMC-IP-V6-ADDRESS-PARAM-DEF This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractDefinition, ApmcAbstractRestrictedStringParamDef, ApmcConfigurationElementDef, ApmcContainerElementDef, ApmcDefinitionElement , ApmcParameterDef, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApmcParamConfContainerDef.element			
Attribute	Type	Mult.	Kind	Note
defaultValue	Ip6AddressString	0..1	attr	This attribute implements the default value of the IP V6 address. Tags: atp.Status=candidate

Table A.33: ApmcIpV6AddressParamDef

Class	ApmcIpV6AddressParamValue			
Note	This meta-class represents a restricted textual parameter for the specification of an IP V6 address on the "value" side of the target-configuration. Tags: atp.Status=candidate xml.name=APMC-IP-V6-ADDRESS-PARAM-VALUE This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractRestrictedTextualParamValue, ApmcAbstractValue , ApmcContainerElementValue , ApmcIndexableValue , ApmcParameterValue , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApmcContainerValue.element			
Attribute	Type	Mult.	Kind	Note
value	Ip6AddressString	0..1	attr	This attribute implements the actual value of the IP V6 address. Tags: atp.Status=candidate

Table A.34: ApmcIpV6AddressParamValue

Class	ApmcMacAddressParamDef			
Note	This meta-class represents an restricted string parameter for the specification of a MAC address label on the "definition" side of the target-configuration. Notation: FF:FF:FF:FF:FF:FF Alternative notations, e.g. using dash instead of colon, or another grouping of numbers, is not allowed. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractDefinition, ApmcAbstractRestrictedStringParamDef, ApmcConfigurationElementDef, ApmcContainerElementDef, ApmcDefinitionElement , ApmcParameterDef, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApmcParamConfContainerDef.element			
Attribute	Type	Mult.	Kind	Note
defaultValue	MacAddressString	0..1	attr	This attribute implements the default value of the MAC address. Tags: atp.Status=candidate

Table A.35: ApmcMacAddressParamDef

Class	ApmcMacAddressParamValue			
Note	This meta-class represents a restricted textual parameter for the specification of a MAC address on the "value" side of the target-configuration. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractRestrictedTextualParamValue, ApmcAbstractValue , ApmcContainerElementValue , ApmcIndexableValue , ApmcParameterValue , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApmcContainerValue.element			
Attribute	Type	Mult.	Kind	Note
value	MacAddressString	0..1	attr	This attribute implements the actual value of the MAC address. Tags: atp.Status=candidate

Table A.36: ApmcMacAddressParamValue

Class	ApmcNumericalParamValue			
Note	This meta-class represents a numerical parameter on the "value" side of the target-configuration. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractValue , ApmcContainerElementValue , ApmcIndexableValue , ApmcParameterValue , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApmcContainerValue.element			
Attribute	Type	Mult.	Kind	Note
value	Numerical	0..1	attr	This attribute represents the value of the numerical parameter. Tags: atp.Status=candidate

Table A.37: ApmcNumericalParamValue

Class	ApmcParamConfContainerDef			
Note	This meta-class represents the definition of container (on the "definition" side of the target-configuration) that carries the definition of parameters and references. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractDefinition, ApmcConfigurationElementDef, ApmcContainerDef, ApmcDefinitionElement , Identifiable , MultilanguageReferrable , Referrable			





Class	ApmcParamConfContainerDef			
Aggregated by	ApmcChoiceContainerDef.choice, ApmcFunctionalClusterDef.container , ApmcParamConfContainerDef.container			
Attribute	Type	Mult.	Kind	Note
container	ApmcContainerDef	*	aggr	This aggregation represents the collection of sub-containers of the enclosing container. By using this aggregation arbitrary nested structures of containers can be created. Stereotypes: atp.Splitable Tags: atp.Splitkey=container.shortName atp.Status=candidate
element	ApmcContainerElementDef	*	aggr	This aggregation represents the collection of elements in the container. Stereotypes: atp.Splitable Tags: atp.Splitkey=element.shortName atp.Status=candidate
isFuncClusterEndpoint	Boolean	0..1	attr	This attribute indicates whether the enclosing ApmcParamConfContainerDef represents the configuration of an endpoint for the interaction with other functional clusters. Tags: atp.Status=candidate

Table A.38: ApmcParamConfContainerDef

Class	ApmcReferenceValue (abstract)			
Note	This meta-class represents a reference on the "value" side of the adaptive platform. The concrete nature of the reference is clarified by a subclass. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractValue , ApmcContainerElementValue , ApmcIndexableValue , Identifiable , MultilanguageReferrable , Referrable			
Subclasses	ApmcAbstractInstanceReferenceValue , ApmcAbstractReferenceValue , ApmcContainerReferenceValue			
Aggregated by	ApmcContainerValue.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.39: ApmcReferenceValue

Class	ApmcRevisionLabelParamDef			
Note	This meta-class represents an restricted string parameter for the specification of a revision label on the "definition" side of the target-configuration. <ul style="list-style-type: none"> • supports three integers representing from left to right MajorVersion, MinorVersion, PatchVersion. • may add an application specific suffix separated by one of ".", "_", ";". Legal patterns are for example: <ul style="list-style-type: none"> • 4.0.0 • 4.0.0.1234565 • 4.0.0_vendor specific;13 • 4.0.0;12 Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			





Class	ApmcRevisionLabelParamDef			
Base	ARObject, ApmcAbstractDefinition, ApmcAbstractRestrictedStringParamDef, ApmcConfigurationElementDef, ApmcContainerElementDef, ApmcDefinitionElement , ApmcParameterDef, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	ApmcParamConfContainerDef.element			
Attribute	Type	Mult.	Kind	Note
defaultValue	RevisionLabelString	0..1	attr	This attribute implements the default value of the revision label. Tags: atp.Status=candidate

Table A.40: ApmcRevisionLabelParamDef

Class	ApmcRevisionLabelParamValue			
Note	This meta-class represents a restricted textual parameter for the specification of a revision label on the "value" side of the target-configuration. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractRestrictedTextualParamValue, ApmcAbstractValue , ApmcContainerElementValue , ApmcIndexableValue , ApmcParameterValue , Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	ApmcContainerValue.element			
Attribute	Type	Mult.	Kind	Note
value	RevisionLabelString	0..1	attr	This attribute implements the actual value of the revision label. Tags: atp.Status=candidate

Table A.41: ApmcRevisionLabelParamValue

Class	ApmcStrongRevisionLabelParamDef			
Note	This meta-class represents an restricted string parameter for the specification of a strong revision label on the "definition" side of the target-configuration. This class enforces a pattern which requires three integer numbers separated by a dot, representing from left to right MajorVersion, MinorVersion, PatchVersion and additional labels for pre-release version and build metadata. Legal patterns are for example: 1.0.0-alpha+001 1.0.0+20130313144700 1.0.0-beta+exp.sha.5114f85 Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractDefinition, ApmcAbstractRestrictedStringParamDef, ApmcConfigurationElementDef, ApmcContainerElementDef, ApmcDefinitionElement , ApmcParameterDef, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	ApmcParamConfContainerDef.element			
Attribute	Type	Mult.	Kind	Note
defaultValue	StrongRevisionLabelString	0..1	attr	This attribute implements the default value of the strong revision label. Tags: atp.Status=candidate

Table A.42: ApmcStrongRevisionLabelParamDef

Class	ApmcStrongRevisionLabelParamValue			
Note	This meta-class represents a restricted textual parameter for the specification of a strong revision label on the "value" side of the target-configuration. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			





Class	ApmcStrongRevisionLabelParamValue			
Base	ARObject, ApmcAbstractRestrictedTextualParamValue, ApmcAbstractValue , ApmcContainerElementValue , ApmcIndexableValue , ApmcParameterValue , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApmcContainerValue.element			
Attribute	Type	Mult.	Kind	Note
value	StrongRevisionLabelString	0..1	attr	This attribute implements the actual value of the strong revision label. Tags: atp.Status=candidate

Table A.43: ApmcStrongRevisionLabelParamValue

Class	ApmcTextualParamValue			
Note	This meta-class represents a textual parameter on the "value" side of the target-configuration. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractValue , ApmcContainerElementValue , ApmcIndexableValue , ApmcParameterValue , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApmcContainerValue.element			
Attribute	Type	Mult.	Kind	Note
value	VerbatimString	0..1	attr	This attribute represents the value of the textual parameter. Tags: atp.Status=candidate

Table A.44: ApmcTextualParamValue

Class	ApmcUriParamDef			
Note	This meta-class represents an restricted string parameter for the specification of a Uniform Resource Identifier (URI) label on the "definition" side of the target-configuration. A Uniform Resource Identifier (URI), is a compact string of characters used to identify or name a resource. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractDefinition, ApmcAbstractRestrictedStringParamDef, ApmcConfigurationElementDef, ApmcContainerElementDef, ApmcDefinitionElement , ApmcParameterDef , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApmcParamConfContainerDef.element			
Attribute	Type	Mult.	Kind	Note
defaultValue	UriString	0..1	attr	This attribute implements the default value of the URI. Tags: atp.Status=candidate

Table A.45: ApmcUriParamDef

Class	ApmcUriParamValue			
Note	This meta-class represents a restricted textual parameter for the specification of a URI on the "value" side of the target-configuration. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ApmcAbstractRestrictedTextualParamValue, ApmcAbstractValue , ApmcContainerElementValue , ApmcIndexableValue , ApmcParameterValue , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApmcContainerValue.element			
Attribute	Type	Mult.	Kind	Note
value	UriString	0..1	attr	This attribute implements the actual value of the URI. Tags: atp.Status=candidate

Table A.46: ApmcUriParamValue

Class	ApplicationArrayType			
Note	An application data type which is an array, each element is of the same application data type. Tags: atp.recommendedPackage=ApplicationDataTypes			
Base	ARElement, ARObject, ApplicationCompositeDataType , ApplicationDataType , AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, AutosarDataType , CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dynamicArraySizeProfile	String	0..1	attr	Specifies the profile which the array will follow if it is a variable size array.
element	ApplicationArrayElement	0..1	aggr	This association implements the concept of an array element. That is, in some cases it is necessary to be able to identify single array elements, e.g. as input values for an interpolation routine.

Table A.47: ApplicationArrayType

Class	ApplicationArrayElement			
Note	Describes the properties of the elements of an application array data type.			
Base	ARObject, ApplicationCompositeElementDataPrototype, AtpFeature, AtpPrototype, DataPrototype , Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	ApplicationArrayType.element , AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
arraySizeHandling	ArraySizeHandlingEnum	0..1	attr	The way how the size of the array is handled.
arraySizeSemantics	ArraySizeSemanticsEnum	0..1	attr	This attribute controls how the information about the array size shall be interpreted.
indexDataType	ApplicationPrimitiveDataType	0..1	ref	This reference can be taken to assign a CompuMethod of category TEXTTABLE to the array. The texttable entries associate a textual value to an index number such that the element with that index number is represented by a symbolic name.
maxNumberOfElements	PositiveInteger	0..1	attr	The maximum number of elements that the array can contain. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.48: ApplicationArrayElement

Class	ApplicationAssocMapDataType			
Note	An application data type which is a map and consists of a key and a value Tags: atp.recommendedPackage=ApplicationDataTypes This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, ApplicationCompositeDataType , ApplicationDataType , AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, AutosarDataType , CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
key	ApplicationAssocMapElement	0..1	aggr	Key element of the map that is used to uniquely identify the value of the map.
value	ApplicationAssocMapElement	0..1	aggr	Value element of the map that stores the content associated to a key.

Table A.49: ApplicationAssocMapDataType

Class	ApplicationAssocMapElement			
Note	Describes the properties of the elements of an application map data type. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , <i>ApplicationCompositeElementDataPrototype</i> , <i>AtpFeature</i> , <i>AtpPrototype</i> , DataPrototype , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApplicationAssocMapDataType.key , ApplicationAssocMapDataType.value , <i>AtpClassifier.atpFeature</i>			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.50: ApplicationAssocMapElement

Class	ApplicationAssocMapElementValueSpecification			
Note	This meta-class represents the ability to define the initialization of the elements of an ApplicationAssoc MapDataType. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i>			
Aggregated by	ApplicationAssocMapValueSpecification.mapElementTuple			
Attribute	Type	Mult.	Kind	Note
key	ValueSpecification	0..1	aggr	This aggregation represents the initialization of the key part of an AssociativeElementValueSpecification.
value	ValueSpecification	0..1	aggr	This aggregation represents the initialization of the value part of an AssociativeElementValueSpecification.

Table A.51: ApplicationAssocMapElementValueSpecification

Class	ApplicationAssocMapValueSpecification			
Note	This meta-class represents the ability to define the initialization of an ApplicationAssocMapDataType. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , <i>CompositeValueSpecification</i> , ValueSpecification			
Aggregated by	ApplicationAssocMapElementValueSpecification.key , ApplicationAssocMapElementValueSpecification.value , <i>ArrayValueSpecification.element</i> , <i>CalibrationParameterValue.applInitValue</i> , <i>CalibrationParameterValue.implInitValue</i> , <i>CompositeRuleBasedValueSpecification.argument</i> , <i>ConstantSpecification.valueSpec</i> , <i>CryptoServiceKey.developmentValue</i> , <i>DiagnosticEnvDataCondition.compareValue</i> , DiagnosticEnvDataElementCondition.compareValue , DiagnosticEnvSovdDataCondition.compareValue , <i>FieldSenderComSpec.initValue</i> , <i>ISignal.initValue</i> , <i>ISignal.receptionDefaultValue</i> , <i>ISignal.timeoutSubstitutionValue</i> , <i>NonqueuedReceiverComSpec.initValue</i> , <i>NonqueuedReceiverComSpec.timeoutSubstitutionValue</i> , <i>NonqueuedSenderComSpec.initValue</i> , <i>NvProvideComSpec.ramBlockInitValue</i> , <i>NvProvideComSpec.romBlockInitValue</i> , <i>NvRequireComSpec.initValue</i> , <i>ParameterDataPrototype.initValue</i> , <i>ParameterProvideComSpec.initValue</i> , <i>ParameterRequireComSpec.initValue</i> , PersistencyDataRequiredComSpec.initValue , PersistencyKeyValuePair.initValue , <i>PortDefinedArgumentValue.value</i> , <i>PortPrototypeBlueprintInitValue.value</i> , <i>RecordValueSpecification.field</i> , <i>SomeipEventDeployment.eventReceptionDefaultValue</i> , StateManagementCompareCondition.compareValue , <i>SwDataDefProps.invalidValue</i> , <i>UserDefinedEventDeployment.eventReceptionDefaultValue</i> , <i>VariableDataPrototype.initValue</i>			
Attribute	Type	Mult.	Kind	Note
mapElement Tuple (ordered)	ApplicationAssocMapElementValueSpecification	*	aggr	This aggregation represents the initial values for the elements of the ApplicationAssocMapValueSpecification.

Table A.52: ApplicationAssocMapValueSpecification

Class	ApplicationCompositeDataType (abstract)			
Note	Abstract base class for all application data types composed of other data types.			
Base	ARElement, ARObject, ApplicationDataType , AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, AutosarDataType , CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Subclasses	ApplicationArrayDataType , ApplicationAssocMapDataType , ApplicationRecordDataType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.53: ApplicationCompositeDataType

Class	ApplicationDataType (abstract)			
Note	ApplicationDataType defines a data type from the application point of view. Especially it should be used whenever something "physical" is at stake. An ApplicationDataType represents a set of values as seen in the application model, such as measurement units. It does not consider implementation details such as bit-size, endianness, etc. It should be possible to model the application level aspects of a VFB system by using ApplicationDataTypes only.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, AutosarDataType , CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Subclasses	ApplicationCompositeDataType , ApplicationPrimitiveDataType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.54: ApplicationDataType

Class	ApplicationPrimitiveDataType			
Note	A primitive data type defines a set of allowed values. Tags: atp.recommendedPackage=ApplicationDataTypes			
Base	ARElement, ARObject, ApplicationDataType , AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, AutosarDataType , CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.55: ApplicationPrimitiveDataType

Class	ApplicationRecordDataType			
Note	An application data type which can be decomposed into prototypes of other application data types. Tags: atp.recommendedPackage=ApplicationDataTypes			
Base	ARElement, ARObject, ApplicationCompositeDataType , ApplicationDataType , AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, AutosarDataType , CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	ApplicationRecordDataType			
element (ordered)	ApplicationRecordElement	*	aggr	Specifies an element of a record. The aggregation of ApplicationRecordElement is subject to variability with the purpose to support the conditional existence of elements inside a ApplicationRecordDataType . Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=element.shortName, element.variation Point.shortLabel vh.latestBindingTime=preCompileTime

Table A.56: ApplicationRecordDataType

Class	ApplicationRecordElement			
Note	Describes the properties of one particular element of an application record data type.			
Base	ARObject , ApplicationCompositeElementDataPrototype , AtpFeature , AtpPrototype , DataPrototype , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApplicationRecordDataType.element , AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
isOptional	Boolean	0..1	attr	This attribute represents the ability to declare the enclosing ApplicationRecordElement as optional. This means that, at runtime, the ApplicationRecordElement may or may not have a valid value and shall therefore be ignored. The underlying runtime software provides means to set the ApplicationRecordElement as not valid at the sending end of a communication and determine its validity at the receiving end.

Table A.57: ApplicationRecordElement

Class	ApplicationValueSpecification			
Note	This meta-class represents values for DataPrototypes typed by ApplicationDataTypes (this includes in particular compound primitives). For further details refer to ASAM CDF 2.0. This meta-class corresponds to some extent with SW-INSTANCE in ASAM CDF 2.0.			
Base	ARObject , CompositeRuleBasedValueArgument , ValueSpecification			
Aggregated by	ApplicationAssocMapElementValueSpecification.key , ApplicationAssocMapElementValueSpecification.value , ArrayValueSpecification.element , CalibrationParameterValue.applInitValue , CalibrationParameterValue.implInitValue , CompositeRuleBasedValueSpecification.compoundPrimitiveArgument , ConstantSpecification.valueSpec , CryptoServiceKey.developmentValue , DiagnosticEnvDataCondition.compareValue , DiagnosticEnvDataElementCondition.compareValue , DiagnosticEnvSovdDataCondition.compareValue , FieldSenderComSpec.initValue , ISignal.initValue , ISignal.receptionDefaultValue , ISignal.timeoutSubstitutionValue , NonqueuedReceiverComSpec.initValue , NonqueuedReceiverComSpec.timeoutSubstitutionValue , NonqueuedSenderComSpec.initValue , NvProvideComSpec.ramBlockInitValue , NvProvideComSpec.romBlockInitValue , NvRequireComSpec.initValue , ParameterDataPrototype.initValue , ParameterProvideComSpec.initValue , ParameterRequireComSpec.initValue , PersistenceDataRequiredComSpec.initValue , PersistenceKeyValuePair.initValue , PortDefinedArgumentValue.value , PortPrototypeBlueprintInitValue.value , RecordValueSpecification.field , SomeipEventDeployment.eventReceptionDefaultValue , StateManagementCompareCondition.compareValue , SwDataDefProps.invalidValue , UserDefinedEventDeployment.eventReceptionDefaultValue , VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note





Class	ApplicationValueSpecification			
category	Identifier	0..1	attr	Specifies to which category of ApplicationDataType this ApplicationValueSpecification can be applied (e.g. as an initial value), thus imposing constraints on the structure and semantics of the contained values, see [constr_1006] and [constr_1519].
swAxisCont (ordered)	SwAxisCont	*	aggr	This represents the axis values of a Compound Primitive Data Type (curve or map). The first swAxisCont describes the x-axis, the second swAxisCont describes the y-axis, the third swAxisCont describes the z-axis. In addition to this, the axis can be denoted in swAxisIndex.
swValueCont	SwValueCont	0..1	aggr	This represents the values of a Compound Primitive Data Type.

Table A.58: ApplicationValueSpecification

Class	ArgumentDataPrototype			
Note	An argument of an operation, carries direction and implementation information.			
Base	ARObject, AtpFeature, AtpPrototype, AutosarDataPrototype, DataPrototype, Identifiable, Multilanguage Referrable, Referrable			
Aggregated by	AtpClassifier.atpFeature, ClientServerOperation.argument			
Attribute	Type	Mult.	Kind	Note
direction	ArgumentDirection Enum	0..1	attr	This attribute specifies the direction of the argument.
serverArgument ImplPolicy	ServerArgumentImpl PolicyEnum	0..1	attr	This defines how the argument type of the servers RunnableEntity is implemented. If the attribute is not defined this has the same semantics as if the attribute is set to the value useArgumentType for primitive arguments and structures.

Table A.59: ArgumentDataPrototype

Enumeration	ArgumentDirectionEnum
Note	Use cases: <ul style="list-style-type: none"> Arguments in ClientServerOperation can have different directions that need to be formally indicated because they have an impact on how the function signature looks like eventually. Arguments in BswModuleEntry already determine a function signature, but the direction is used to specify the semantics, especially of pointer arguments.
Aggregated by	ArgumentDataPrototype.direction, DiagnosticSovdAccessArgument.direction, RunnableEntity Argument.direction, SwServiceArg.direction
Literal	Description
in	The argument value is passed to the callee. Tags: atp.EnumerationLiteralIndex=0
inout	The argument value is passed to the callee but also passed back from the callee to the caller. Tags: atp.EnumerationLiteralIndex=1
out	The argument value is passed from the callee to the caller. Tags: atp.EnumerationLiteralIndex=2

Table A.60: ArgumentDirectionEnum

Enumeration	ArraySizeSemanticsEnum
Note	This type controls how the information about the number of elements in an <code>ApplicationArrayDataType</code> is to be interpreted.
Aggregated by	ApplicationArrayElement.arraySizeSemantics , DiagnosticDataElement.arraySizeSemantics , ImplementationDataTypeElement.arraySizeSemantics , SwTextProps.arraySizeSemantics
Literal	Description
fixedSize	This means that the ApplicationArrayDataType will always have a fixed number of elements. Tags: atp.EnumerationLiteralIndex=0
variableSize	This implies that the actual number of elements in the <code>ApplicationArrayDataType</code> might vary at run-time. The value of <code>arraySize</code> represents the maximum number of elements in the array. Tags: atp.EnumerationLiteralIndex=1

Table A.61: ArraySizeSemanticsEnum

Class	ArtifactLocator			
Note	This meta-class has the ability to define the location of an artifact that is represented by a model element, e.g. Executable. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	SoftwareCluster.artifactLocator , SoftwarePackage.artifactLocator			
Attribute	Type	Mult.	Kind	Note
represented ModelElement	Identifiable	0..1	ref	This reference identifies the model element that is represented by the artifact.
uri	String	0..1	attr	This attribute describes the location of the artifact.

Table A.62: ArtifactLocator

Class	AutosarDataPrototype (abstract)			
Note	Base class for prototypical roles of an AutosarDataType .			
Base	ARObject , AtpFeature , AtpPrototype , DataPrototype , Identifiable , MultilanguageReferrable , Referrable			
Subclasses	ArgumentDataPrototype , Field , ParameterDataPrototype , PersistencyDataElement , VariableDataPrototype			
Aggregated by	AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
type	AutosarDataType	0..1	tref	This represents the corresponding data type. Stereotypes: isOfType

Table A.63: AutosarDataPrototype

Class	AutosarDataType (abstract)			
Note	Abstract base class for user defined AUTOSAR data types for software.			
Base	ARElement , ARObject , AtpClassifier , AtpType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	AbstractImplementationDataType , ApplicationDataType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
swDataDef Props	SwDataDefProps	0..1	aggr	The properties of this <code>AutosarDataType</code> . Stereotypes: atp.Splitable Tags: atp.Splitkey=swDataDefProps

Table A.64: AutosarDataType

Class	AutosarOperationArgumentInstance			
Note	This class represents a reference to an argument instance. This way it is possible to reference an argument instance in the occurrence expression formula. The argument instance can target to one of the following arguments: <ul style="list-style-type: none"> a whole argument used in an operation of a PortPrototype with ClientServerInterface an element inside of a composite argument used in an operation of a PortPrototype with ClientServerInterface 			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	TDEventOccurrenceExpression.argument , TimingExtensionResource.timingArgument			
Attribute	Type	Mult.	Kind	Note
operationArgumentInstance	DataPrototype	0..1	iref	This is the reference to the instanceRef definition. InstanceRef implemented by: OperationArgumentInComponentInstanceRef

Table A.65: AutosarOperationArgumentInstance

Class	AutosarVariableInstance			
Note	This class represents a reference to a variable instance within AUTOSAR. This way it is possible to reference a variable instance in the occurrence expression formula. The variable instance can target to one of the following variables: <ul style="list-style-type: none"> a variable provided via a PortPrototype as whole an element inside of a composite variable provided via a PortPrototype 			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	TDEventOccurrenceExpression.variable , TimingExtensionResource.timingVariable			
Attribute	Type	Mult.	Kind	Note
variableInstance	DataPrototype	0..1	iref	This is the reference to the instanceRef definition. InstanceRef implemented by: VariableInComponentInstanceRef

Table A.66: AutosarVariableInstance

Class	BaseType (abstract)			
Note	This abstract meta-class represents the ability to specify a platform dependent base type.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	SwBaseType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
baseTypeDefinition	BaseTypeDefinition	1	aggr	This is the actual definition of the base type. Tags: xml.roleElement=false xml.roleWrapperElement=false xml.sequenceOffset=20 xml.typeElement=false xml.typeWrapperElement=false

Table A.67: BaseType

Class	BaseTypeDirectDefinition			
Note	This BaseType is defined directly (as opposite to a derived BaseType)			
Base	ARObject, BaseTypeDefinition			
Aggregated by	BaseType.baseTypeDefinition			





Class	BaseTypeDirectDefinition			
Attribute	Type	Mult.	Kind	Note
baseTypeEncoding	BaseTypeEncodingString	0..1	attr	This specifies, how an object of the current BaseType is encoded, e.g. in an ECU within a message sequence. Tags: xml.sequenceOffset=90
baseTypeSize	PositiveInteger	0..1	attr	Describes the length of the data type specified in the container in bits. Tags: xml.sequenceOffset=70
byteOrder	ByteOrderEnum	0..1	attr	This attribute specifies the byte order of the base type. Tags: xml.sequenceOffset=110
memAlignment	PositiveInteger	0..1	attr	This attribute describes the alignment of the memory object in bits. E.g. "8" specifies, that the object in question is aligned to a byte while "32" specifies that it is aligned four byte. If the value is set to "0" the meaning shall be interpreted as "unspecified". Tags: xml.sequenceOffset=100
nativeDeclaration	NativeDeclarationString	0..1	attr	This attribute describes the declaration of such a base type in the native programming language, primarily in the Programming language C. This can then be used by a code generator to include the necessary declarations into a header file. For example BaseType with shortName: "MyUnsignedInt" native Declaration: "unsigned short" Results in typedef unsigned short MyUnsignedInt; If the attribute is not defined the referring Implementation DataTypes will not be generated as a typedef by RTE. If a nativeDeclaration type is given it shall fulfill the characteristic given by basetypeEncoding and baseTypeSize. This is required to ensure the consistent handling and interpretation by software components, RTE, COM and MCM systems. Tags: xml.sequenceOffset=120

Table A.68: BaseTypeDirectDefinition

Class	CanXIProps			
Note	This meta-class is used to configure Machine specific CAN XL attributes. Tags: atp.recommendedPackage=CanXIProps This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
canBaudrate	PositiveInteger	0..1	attr	Specifies the data segment CAN 2.0 baud rate of the CAN XL controller in bits/s.
canConfig	CanControllerConfiguration	0..1	aggr	CAN 2.0 configuration parameters for the CAN XL controller.
canFdBaudrate	PositiveInteger	0..1	attr	Specifies the data segment CAN FD baud rate of the CAN XL controller in bits/s.
canFdConfig	CanControllerFdConfiguration	0..1	aggr	CAN FD configuration parameters for the CAN XL controller.
canXIBaudrate	PositiveInteger	0..1	attr	Specifies the data segment CAN XL baud rate of the CAN XL controller in bits/s.





Class	CanXIProps			
canXIConfig	CanControllerXI Configuration	0..1	aggr	CAN XL configuration parameters for the CAN XL controller.
canXIConfig Reqs	CanControllerXI Configuration Requirements	0..1	aggr	CAN XL configuration parameter requirements for the CAN XL controller.

Table A.69: CanXIProps

Class	CheckpointTransition			
Note	Defines one transition between two checkpoints. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	GlobalSupervision.transition			
Attribute	Type	Mult.	Kind	Note
source	SupervisionCheckpoint	0..1	ref	Reference to the source checkpoint for this transition.
target	SupervisionCheckpoint	0..1	ref	Reference to the target checkpoint for this transition.

Table A.70: CheckpointTransition

Class	ClientServerOperation			
Note	An operation declared within the scope of a client/server interface.			
Base	ARObject, AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApplicationInterface.command , AtpClassifier.atpFeature , ClientServerInterface.operation , DiagnosticDataElementInterface.read , DiagnosticDataIdentifierInterface.read , DiagnosticDataIdentifierInterface.write , DiagnosticExtendedDataRecordInterface.provide , DiagnosticRoutineInterface.requestResult , DiagnosticRoutineInterface.start , DiagnosticRoutineInterface.stop , PhmRecoveryActionInterface.recovery , ServiceInterface.method			
Attribute	Type	Mult.	Kind	Note
argument (ordered)	ArgumentDataPrototype	*	aggr	An argument of this ClientServerOperation . Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=argument.shortName, argument.variation Point.shortLabel vh.latestBindingTime=blueprintDerivationTime
fireAndForget	Boolean	0..1	attr	This attribute defines whether this method is a fire&forget method (true) or not (false). This Attribute is only used by the AUTOSAR Adaptive Platform.
possibleApError	ApApplicationError	*	ref	This reference identifies AdaptivePlatformApplication Errors as a possible error raised by the enclosing Client ServerOperation. This Attribute is only used by the AUTOSAR Adaptive Platform.
possibleApError Set	ApApplicationErrorSet	*	ref	This reference represents the ability to refer to an entire group of ApApplicationErrors as one model element instead of having to refer to all the represented Ap ApplicationErrors separately. This Attribute is only used by the AUTOSAR Adaptive Platform.

Table A.71: ClientServerOperation

Class	CmModuleInstantiation			
Note	This meta-class represents the ability to define a definition of a Communication Management instantiation. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AdaptiveModuleInstantiation, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable , MultilanguageReferrable , NonOsModuleInstantiation , Referrable			
Aggregated by	AtpClassifier.atpFeature, Machine.moduleInstantiation			
Attribute	Type	Mult.	Kind	Note
grant	Grant	*	ref	This reference identifies the applicable Grants for this Cm ModuleInstantiation. Stereotypes: atpSplittable Tags: atp.Splitkey=grant atp.Status=candidate
localCom AccessControl Enabled	Boolean	0..1	attr	This switch activates the policy enforcement in Communication Management on local applications. Tags: atp.Status=candidate
remoteAccess ControlEnabled	Boolean	0..1	attr	This switch activates the check of the remote subject. Tags: atp.Status=candidate
secOCIgnore Verification Result	Boolean	0..1	attr	The result of the authentication process (e.g. MAC Verify) is ignored after the first try and the SecOC proceeds like the result was a success. The calculation of the authenticator is still done, only its result will be ignored. <ul style="list-style-type: none"> • true: enabled (verification result is ignored). • false: disabled (verification result is NOT ignored). Tags: atp.Status=candidate

Table A.72: CmModuleInstantiation

Class	ComEventGrant			
Note	This meta-class represents the ability to grant access to a ServiceInterface.event. Tags: atp.Status=candidate atp.recommendedPackage=Grants This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, ComGrant , Grant , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDeploymentElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
design	ComEventGrantDesign	0..1	ref	This reference identifies the ComEventGrantDesign that the enclosing ComEventGrant was created from. Stereotypes: atpUriDef Tags: atp.Status=candidate
service Deployment	ServiceEvent Deployment	0..1	ref	This reference identifies the applicable deployment within the context of an AdaptivePlatformServiceInstance for which the grant applies. Tags: atp.Status=candidate

Table A.73: ComEventGrant

Class	ComEventGrantDesign			
Note	This meta-class represents the ability to define a Grant for a ServiceInterface.event. Tags: atp.Status=candidate atp.recommendedPackage=GrantDesigns This Class is only used by the AUTOSAR Adaptive Platform.			





Class	ComEventGrantDesign			
Base	ARElement, ARObject, CollectableElement, ComGrantDesign , GrantDesign, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
event	VariableDataPrototype	0..1	iref	This reference represents the affected event. Tags: atp.Status=candidate InstanceRef implemented by: EventInExecutableInstanceRef

Table A.74: ComEventGrantDesign

Class	ComFieldGrant			
Note	This meta-class represents the ability to grant access to a ServiceInterface.field. Tags: atp.Status=candidate atp.recommendedPackage=Grants This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, ComGrant , Grant , Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
design	ComFieldGrantDesign	0..1	ref	This reference identifies the ComFieldGrantDesign that the enclosing ComFieldGrant was created from. Stereotypes: atpUriDef Tags: atp.Status=candidate
role	FieldAccessEnum	0..1	attr	This attribute provides the ability to further specify the access to the ServiceInterface.field. Tags: atp.Status=candidate
service Deployment	ServiceFieldDeployment	0..1	ref	This reference identifies the applicable deployment within the context of an AdaptivePlatformServiceInstance for which the grant applies. Tags: atp.Status=candidate

Table A.75: ComFieldGrant

Class	ComFieldGrantDesign			
Note	This meta-class represents the ability to define a Grant for a ServiceInterface.field. Tags: atp.Status=candidate atp.recommendedPackage=GrantDesigns This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, ComGrantDesign , GrantDesign, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
field	Field	0..1	iref	Reference to the affected Field in the context of an Executable. Tags: atp.Status=candidate InstanceRef implemented by: FieldInExecutableInstanceRef





Class	ComFieldGrantDesign			
role	FieldAccessEnum	0..1	attr	This attribute provides the ability to further specify the access to the ServiceInterface.field from a design perspective. Tags: atp.Status=candidate

Table A.76: ComFieldGrantDesign

Class	ComGrant (abstract)			
Note	This meta-class serves as the abstract base class for defining specific ComGrants Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Grant, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDeploymentElement, UploadablePackageElement			
Subclasses	ComEventGrant, ComFieldGrant, ComMethodGrant, ComTriggerGrant			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
remoteSubject	AbstractIamRemoteSubject	*	ref	This optional reference defines the remoteSubject that is allowed to access the defined Object via the Grant. Tags: atp.Status=candidate
serviceInstance	AdaptivePlatformServiceInstance	0..1	ref	This reference identifies the applicable AdaptivePlatformServiceInstance for which the grant applies. Tags: atp.Status=candidate

Table A.77: ComGrant

Class	ComGrantDesign (abstract)			
Note	This meta-class serves as an abstract base class for the description of com grants on design level. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, GrantDesign, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Subclasses	ComEventGrantDesign, ComFieldGrantDesign, ComMethodGrantDesign, ComTriggerGrantDesign			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
remoteSubject	AbstractIamRemoteSubject	*	ref	This optional reference defines the remoteSubject that is allowed to access the defined Object via the Grant. Tags: atp.Status=candidate

Table A.78: ComGrantDesign

Class	ComMethodGrant			
Note	This meta-class represents the ability to grant access to a ServiceInterface.method. Tags: atp.Status=candidate atp.recommendedPackage=Grants This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, ComGrant, Grant, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	ComMethodGrant			
design	ComMethodGrant Design	0..1	ref	This reference identifies the ComMethodGrantDesign that the enclosing ComMethodGrant was created from. Stereotypes: atpUriDef Tags: atp.Status=candidate
service Deployment	ServiceMethod Deployment	0..1	ref	This reference identifies the applicable deployment within the context of an AdaptivePlatformServiceInstance for which the grant applies. Tags: atp.Status=candidate

Table A.79: ComMethodGrant

Class	ComMethodGrantDesign			
Note	This meta-class represents the ability to define a Grant for a ServiceInterface.method. Tags: atp.Status=candidate atp.recommendedPackage=GrantDesigns This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, ComGrantDesign , GrantDesign, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
method	ClientServerOperation	0..1	iref	This reference identifies the corresponding method. Tags: atp.Status=candidate InstanceRef implemented by: RequiredMethodInExecutableInstanceRef

Table A.80: ComMethodGrantDesign

Class	ComOfferServiceGrant			
Note	This meta-class represents the ability to grant the offering of a service. Tags: atp.Status=candidate atp.recommendedPackage=Grants This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Grant , Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
design	ComOfferServiceGrant Design	0..1	ref	This reference identifies the ComOfferServiceGrant Design that the enclosing ComOfferServiceGrant was created from. Stereotypes: atpUriDef Tags: atp.Status=candidate
serviceInstance	AdaptivePlatform ServiceInstance	0..1	ref	This reference identifies the AdaptivePlatformService Instances for which the grant applies. Tags: atp.Status=candidate

Table A.81: ComOfferServiceGrant

Class	ComOfferServiceGrantDesign			
Note	This meta-class represents the ability to define a Grant for offering a service. Tags: atp.Status=candidate atp.recommendedPackage=GrantDesigns This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, GrantDesign, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
providedServicePort	PPortPrototype	0..1	iref	This instanceRef identifies the PPortPrototype on which the service shall be offered. Tags: atp.Status=candidate InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef

Table A.82: ComOfferServiceGrantDesign

Class	ComTriggerGrant			
Note	This meta-class represents the ability to grant access to a ServiceInterface.trigger Tags: atp.Status=candidate atp.recommendedPackage=Grants This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, ComGrant , Grant , Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
design	ComTriggerGrantDesign	0..1	ref	This reference identifies the ComTriggerGrantDesign that the enclosing ComTriggerGrant was created from Stereotypes: atp.UriDef Tags: atp.Status=candidate
serviceDeployment	ServiceEventDeployment	0..1	ref	This reference identifies the applicable deployment within the context of an AdaptivePlatformServiceInstance for which the grant applies. Tags: atp.Status=candidate

Table A.83: ComTriggerGrant

Class	ComTriggerGrantDesign			
Note	This meta-class represents the ability to define a Grant for a ServiceInterface.trigger. Tags: atp.Status=candidate atp.recommendedPackage=GrantDesigns This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, ComGrantDesign , GrantDesign, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
trigger	Trigger	0..1	iref	This reference represents the affected trigger. Tags: atp.Status=candidate InstanceRef implemented by: TriggerInExecutableInstanceRef

Table A.84: ComTriggerGrantDesign

Class	CommConnectorPort (abstract)			
Note	<p>The Ecu communication relationship defines which signals, Pdus and frames are actually received and transmitted by this ECU.</p> <p>For each signal, Pdu or Frame that is transmitted or received and used by the Ecu an association between an ISignalPort, IPduPort or FramePort with the corresponding Triggering shall be created. An ISignalPort shall be created only if the corresponding signal is handled by COM (RTE or Signal Gateway). If a Pdu Gateway ECU only routes the Pdu without being interested in the content only a FramePort and an IPduPort needs to be created.</p>			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Subclasses	FramePort, IPduPort, ISignalPort			
Aggregated by	CommunicationConnector .ecuCommPortInstance			
Attribute	Type	Mult.	Kind	Note
communication Direction	CommunicationDirectionType	0..1	attr	Communication Direction of the Connector Port (input or output Port).

Table A.85: CommConnectorPort

Class	«atpVariation» CommunicationCluster (abstract)			
Note	<p>The CommunicationCluster is the main element to describe the topological connection of communicating ECUs.</p> <p>A cluster describes the ensemble of ECUs, which are linked by a communication medium of arbitrary topology (bus, star, ring, ...). The nodes within the cluster share the same communication protocol, which may be event-triggered, time-triggered or a combination of both.</p> <p>A CommunicationCluster aggregates one or more physical channels.</p> <p>Tags: vh.latestBindingTime=postBuild</p>			
Base	ARElement, ARObject, CollectableElement, FibexElement, Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			
Subclasses	AbstractCanCluster, EthernetCluster, FlexrayCluster, LinCluster, UserDefinedCluster			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
baudrate	PositiveUnlimitedInteger	0..1	attr	Channels speed in bits/s.
physical Channel	PhysicalChannel	*	aggr	<p>This relationship defines which channel element belongs to which cluster. A channel shall be assigned to exactly one cluster, whereas a cluster may have one or more channels.</p> <p>Note: This atpSplittable property has no atp.Splitkey due to atpVariation (PropertySetPattern).</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: vh.latestBindingTime=systemDesignTime</p>
protocolName	String	0..1	attr	The name of the protocol used.
protocolVersion	String	0..1	attr	The version of the protocol used.

Table A.86: CommunicationCluster

Class	CommunicationConnector (abstract)			
Note	<p>The connection between the referencing ECU and the referenced channel via the referenced controller. Connectors are used to describe the bus interfaces of the ECUs and to specify the sending/receiving behavior. Each CommunicationConnector has a reference to exactly one communicationController.</p> <p>Note: Several CommunicationConnectors can be assigned to one PhysicalChannel in the scope of one ECU Instance.</p>			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Subclasses	AbstractCanCommunicationConnector, EthernetCommunicationConnector , FlexrayCommunicationConnector, UserDefinedCommunicationConnector			
Aggregated by	EcuInstance.connector, MachineDesign.communicationConnector			
Attribute	Type	Mult.	Kind	Note





Class	CommunicationConnector (abstract)			
commController	Communication Controller	0..1	ref	Reference to the communication controller. The CommunicationConnector and referenced CommunicationController shall be aggregated by the same ECUInstance. The communicationController can be referenced by several CommunicationConnector elements. This is important for the FlexRay Bus. FlexRay communicates via two physical channels. But only one controller in an ECU is responsible for both channels. Thus, two connectors (for channel A and for channel B) shall reference to the same controller.
createEcuWakeupSource	Boolean	0..1	attr	If this parameter is available and set to true then a channel wakeup source shall be created for the Physical Channel referencing this CommunicationConnector.
explicitWakeupChannel	PhysicalChannel	*	ref	Defines a restriction which PhysicalChannels shall be woken up if this CommunicationConnector is the wakeup source. If not defined, then no restriction applies. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=explicitWakeupChannel.physicalChannel, explicitWakeupChannel.variationPoint.shortLabel vh.latestBindingTime=postBuild
explicitWakeupPnc	PncMappingIdent	*	ref	Defines a restriction which PNCs shall be woken up if this CommunicationConnector is the wakeup source. If not defined, then no restriction applies. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=explicitWakeupPnc.pncMappingIdent, explicitWakeupPnc.variationPoint.shortLabel vh.latestBindingTime=postBuild
pncFilterArrayMask (ordered)	PositiveInteger	*	attr	Bit mask for NM-Pdu Payload used to configure the NM filter mask for the Network Management.

Table A.87: CommunicationConnector

Enumeration	CommunicationDirectionType
Note	Describes the communication direction.
Aggregated by	CommConnectorPort.communicationDirection , IEEE1722TpConnection.communicationDirection , IPSecRule.direction , ISignalIPduGroup.communicationDirection
Literal	Description
in	Reception (Input) Tags: atp.EnumerationLiteralIndex=0
out	Transmission (Output) Tags: atp.EnumerationLiteralIndex=1

Table A.88: CommunicationDirectionType

Class	CompositionSwComponentType
Note	A CompositionSwComponentType aggregates SwComponentPrototypes (that in turn are typed by SwComponentType)s as well as SwConnectors for primarily connecting SwComponentPrototypes among each others and towards the surface of the CompositionSwComponentType. By this means, a hierarchical structures of software-components can be created. Tags: atp.recommendedPackage=SwComponentTypes
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, SwComponentType





Class	CompositionSwComponentType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
component	SwComponent Prototype	*	aggr	The instantiated components that are part of this composition. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=component.shortName, component.variation Point.shortLabel vh.latestBindingTime=postBuild
connector	SwConnector	*	aggr	SwConnectors have the principal ability to establish a connection among PortPrototypes. They can have many roles in the context of a CompositionSwComponentType. Details are refined by subclasses. The aggregation of SwConnectors is subject to variability with the purpose to support variant data flow. The aggregation is marked as atpSplitable in order to allow the extension of the ECU extract with AssemblySwConnectors between ApplicationSwComponentTypes and ServiceSwComponentTypes during the ECU integration. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=connector.shortName, connector.variation Point.shortLabel vh.latestBindingTime=postBuild
constantValue Mapping	ConstantSpecification MappingSet	*	ref	Reference to the ConstantSpecificationMapping to be applied for initValues of PPortComSpecs and RPortComSpec. Stereotypes: atpSplitable Tags: atp.Splitkey=constantValueMapping
dataType Mapping	DataTypeMappingSet	*	ref	Reference to the DataTypeMapping to be applied for the used ApplicationDataTypes in ServiceInterfaces. Stereotypes: atpSplitable Tags: atp.Splitkey=dataTypeMapping
physical Dimension Mapping	PhysicalDimension MappingSet	0..1	ref	This reference identifies the PhysicalDimensionMappingSet that is applicable in the context of the enclosing CompositionSwComponentType. The PhysicalDimensionMappings contained in the PhysicalDimensionMappingSet shall be taken into account for the assessment of the compatibility of PhysicalDimensions in the context of creation of a PortInterfaceMapping in the scope of the CompositionSwComponentType.

Table A.89: CompositionSwComponentType

Class	CompuMethod
Note	This meta-class represents the ability to express the relationship between a physical value and the mathematical representation. Note that this is still independent of the technical implementation in data types. It only specifies the formula how the internal value corresponds to its physical pendant. Tags: atp.recommendedPackage=CompuMethods
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, CollectableElement, Identifiable, Multilanguage Referrable, PackageableElement, Referrable





Class	CompuMethod			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
compuInternalToPhys	Compu	0..1	aggr	This specifies the computation from internal values to physical values. Stereotypes: atpSplitable Tags: atp.Splitkey=compuInternalToPhys xml.sequenceOffset=80
compuPhysToInternal	Compu	0..1	aggr	This represents the computation from physical values to the internal values. Stereotypes: atpSplitable Tags: atp.Splitkey=compuPhysToInternal xml.sequenceOffset=90
displayFormat	DisplayFormatString	0..1	attr	This property specifies, how the physical value shall be displayed e.g. in documents or measurement and calibration tools. Tags: xml.sequenceOffset=20
unit	Unit	0..1	ref	This is the physical unit of the Physical values for which the CompuMethod applies. Tags: xml.sequenceOffset=30

Table A.90: CompuMethod

Class	ConcretePatternEventTriggering			
Note	Describes the behavior of an event that occurs according to a precisely known pattern.			
Base	ARObject, EventTriggeringConstraint, Identifiable , MultilanguageReferrable , Referrable , TimingConstraint , Traceable			
Aggregated by	TimingExtension.timingGuarantee, TimingExtension.timingRequirement			
Attribute	Type	Mult.	Kind	Note
offset	MultidimensionalTime	*	aggr	The offset for each occurrence of the event in the specified time interval. A list of point-in-times in the time interval given by the parameter patternLength at which the event occurs. Tags: xml.name=TIME-VALUE xml.roleElement=true xml.sequenceOffset=10 xml.typeElement=false
patternJitter	MultidimensionalTime	0..1	aggr	The maximum deviation of the time interval's starting point from the beginning of the given period. This parameter is only applicable in conjunction with the parameter patternPeriod .
patternLength	MultidimensionalTime	0..1	aggr	The duration of the time interval within which the event repeatedly occurs. The event occurs at concrete points in time within the given time interval. Tags: xml.sequenceOffset=20
patternPeriod	MultidimensionalTime	0..1	aggr	The time distance between the beginnings of subsequent repetitions of the given concrete pattern.

Table A.91: ConcretePatternEventTriggering

Class	ConstantReference			
Note	Instead of defining this value inline, a constant is referenced.			
Base	ARObject, ValueSpecification			
Aggregated by	ApplicationAssocMapElementValueSpecification.key , ApplicationAssocMapElementValueSpecification.value , ArrayValueSpecification.element , CalibrationParameterValue.applInitValue , CalibrationParameterValue.implInitValue , ConstantSpecification.valueSpec , CryptoServiceKey.developmentValue , DiagnosticEnvDataCondition.compareValue , DiagnosticEnvDataElementCondition.compareValue , DiagnosticEnvSovdDataCondition.compareValue , FieldSenderComSpec.initValue , ISignal.initValue , ISignal.receptionDefaultValue , ISignal.timeoutSubstitutionValue , NonqueuedReceiverComSpec.initValue , NonqueuedReceiverComSpec.timeoutSubstitutionValue , NonqueuedSenderComSpec.initValue , NvProvideComSpec.ramBlockInitValue , NvProvideComSpec.romBlockInitValue , NvRequireComSpec.initValue , ParameterDataPrototype.initValue , ParameterProvideComSpec.initValue , ParameterRequireComSpec.initValue , PersistencyDataRequiredComSpec.initValue , PersistencyKeyValuePair.initValue , PortDefinedArgumentValue.value , PortPrototypeBlueprintInitValue.value , RecordValueSpecification.field , SomeipEventDeployment.eventReceptionDefaultValue , StateManagementCompareCondition.compareValue , SwDataDefProps.invalidValue , UserDefinedEventDeployment.eventReceptionDefaultValue , VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note
constant	ConstantSpecification	0..1	ref	The referenced constant.

Table A.92: ConstantReference

Class	CouplingPort			
Note	A CouplingPort is used to connect a CouplingElement with an EcuInstance or two CouplingElements with each other via a CouplingPortConnection. Optionally, the CouplingPort may also have a reference to a macMulticastGroup and a defaultVLAN.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	CouplingElement.couplingPort, EthernetCommunicationController.couplingPort			
Attribute	Type	Mult.	Kind	Note
connection Negotiation Behavior	EthernetConnection NegotiationEnum	0..1	attr	Specifies the connection negotiation of the CouplingPort.
couplingPort Details	CouplingPortDetails	0..1	aggr	Defines more details of a CouplingPort in case a more specific configuration is required.
couplingPort Role	CouplingPortRoleEnum	0..1	attr	Defines the role this CouplingPort takes in the context of the CouplingElement.
defaultVlan	EthernetPhysical Channel	0..1	ref	<p>The vLanIdentifier of the referenced VLAN is the Default-PVID (port VLAN ID). A Port VLAN ID is a default VLAN ID that is assigned to an access CouplingPort to designate the VLAN segment to which this port is connected. Also, if a CouplingPort has not been configured with any VLAN memberships, the virtual switch's Port VLAN ID (pvid) becomes the default VLAN ID for the ports connection.</p> <p>This identifier/tag is added for incoming untagged messages at the port (ingress tagging). For outgoing messages with this identifier, the tag is removed at the port (egress untagging, depending on the Vlan Membership.sendActivity).</p>
macAddress VlanAssignment	MacAddressVlan Membership	*	aggr	<p>Statically defines the assignment of MAC-Multicast-Addresses, optionally together with VLANs, to this CouplingPort.</p> <p>Stereotypes: atpSplitable; atpVariation</p> <p>Tags: atp.Splitkey=macAddressVlanAssignment.shortName, macAddressVlanAssignment.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
macLayerType	EthernetMacLayerType Enum	0..1	attr	Specifies the mac layer type of the CouplingPort.





Class	CouplingPort			
macSecProps	MacSecProps	*	aggr	Properties to configure MACsec (Media access control security) and the MKA (MACsec Key Agreement) for the CouplingPort (PHY). Tags: atp.Status=candidate
physicalLayerType	EthernetPhysicalLayerTypeEnum	0..1	attr	Specifies the physical layer type of the CouplingPort.
plcaProps	PlcaProps	0..1	aggr	Optional properties for configuration of PLCA (Physical Layer Collision Avoidance) in case 10-BASE-T1S Ethernet is used and PLCA is enabled on the Coupling Port (PHY).
pncMapping	PncMappingIdent	*	ref	Reference to the partial networks this CouplingPort participates in. Stereotypes: atp.Splittable Tags: atp.Splitkey=pncMapping
receiveActivity	EthernetSwitchVlanIngressTagEnum	0..1	attr	Defines the handling of frames at the ingress port.
vlanMembership	VlanMembership	*	aggr	Messages of VLANs that are defined here can be communicated via the CouplingPort.
wakeupSleepOnDatalineConfig	EthernetWakeupSleepOnDatalineConfig	0..1	ref	Optional reference to EthernetWakeupSleepOnDatalineConfig.

Table A.93: CouplingPort

Class	CpplImplementationDataType (abstract)			
Note	This meta-class represents the way to specify a reusable data type definition taken as a the basis for a C++ language binding This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AbstractImplementationDataType , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , AutosarDataType , CollectableElement , CpplImplementationDataTypeContextTarget , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	CustomCpplImplementationDataType , StdCpplImplementationDataType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
arraySize	PositiveInteger	0..1	attr	This attribute can be used to specify the array size if the enclosing CpplImplementationDataType has array semantics. Stereotypes: atp.Variation Tags: vh.latestBindingTime=preCompileTime
headerFile	String	0..1	attr	Configuration of the Header File with the custom class declaration.
namespace (ordered)	SymbolProps	*	aggr	This aggregation allows for the definition an own namespace for the enclosing CpplImplementationDataType.
subElement (ordered)	CpplImplementationDataTypeElement	*	aggr	This represents the collection of sub-elements of the enclosing CpplImplementationDataType
template Argument (ordered)	CppTypeArgument	*	aggr	This aggregation allows for the specification of properties of template arguments
typeEmitter	NameToken	0..1	attr	This attribute can be taken to control how the respective CpplImplementationDataType is contributed to the language binding.
typeReference	CpplImplementationDataType	0..1	ref	This reference shall be defined to define a type reference (a.k.a. typedef).

Table A.94: CpplImplementationDataType

Class	CppImplementationDataTypeElement			
Note	Declares a data object which is locally aggregated. Such an element can only be used within the scope where it is aggregated. A CppImplementationDataTypeElement is used to represent an element of a structure, defining its type. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AbstractImplementationDataTypeElement , AtpClassifier , AtpFeature , AtpStructureElement , CppImplementationDataTypeContextTarget , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	AtpClassifier.atpFeature , CppImplementationDataType.subElement			
Attribute	Type	Mult.	Kind	Note
isOptional	Boolean	0..1	attr	This attribute represents the ability to declare the enclosing CppImplementationDataTypeElement as optional. This means the that, at runtime, the CppImplementationDataTypeElement may or may not have a valid value and shall therefore be ignored. The underlying runtime software provides means to set the CppImplementationDataTypeElement as not valid at the sending end of a communication and determine its validity at the receiving end.
swDataDef Props	SwDataDefProps	0..1	aggr	This aggregation allows for the definition of qualifying properties of the enclosing CppImplementationDataTypeElement. Stereotypes: atpSplitable Tags: atp.Splitkey=swDataDefProps
typeReference	CppImplementationDataTypeElementQualifier	0..1	aggr	This aggregation defines the type of the CppImplementationDataTypeElement and determines whether in C++ the CppImplementationDataTypeElement is defined inside or outside of the enclosing CppImplementationDataType.

Table A.95: CppImplementationDataTypeElement

Class	CppImplementationDataTypeElementQualifier			
Note	This element qualifies the typeReference of the CppImplementationDataTypeElement to the CppImplementationDataType. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	CppImplementationDataTypeElement.typeReference			
Attribute	Type	Mult.	Kind	Note
inplace	Boolean	0..1	attr	This attribute defines whether the member type of the CppImplementationDataTypeElement in C++ is an embedded type element inside of the enclosing struct (true) or whether the type declaration is defined outside of the struct.
typeReference	CppImplementationDataType	0..1	ref	This reference defines a type reference.

Table A.96: CppImplementationDataTypeElementQualifier

Class	CppTemplateArgument			
Note	This meta-class has the ability to define properties for template arguments. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	CppImplementationDataType.templateArgument			
Attribute	Type	Mult.	Kind	Note
allocator	Allocator	0..1	ref	This reference identifies the applicable allocator.





Class	CppTypeArgument			
category	CategoryString	0..1	attr	This attribute shall be used to contribute further clarification regarding the semantics of the enclosing Cpp TemplateArgument.
inplace	Boolean	0..1	attr	This attribute specifies whether the shortName of the referenced templateType is used in the code generation and the type declaration is defined outside of the enclosing CppImplementationDataType (true) or whether the type definition is embedded inside of the enclosing CppImplementationDataType and the shortName is ignored (false).
templateType	CppImplementationDataType	0..1	ref	This reference identifies the data type of the specific template argument required for the language binding.

Table A.97: CppTemplateArgument

Class	CryptoAlgorithmDescription			
Note	This meta-class is used to provide properties of the crypto algorithm. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	CryptoKeySlot.algorithmDescription			
Attribute	Type	Mult.	Kind	Note
cryptoAlgorithmId	String	0..1	attr	This attribute describes the identity of the crypto algorithm.
cryptoKeyType	CryptoKeyTypeEnum	0..1	attr	This attribute describes the identity of the crypto algorithm.

Table A.98: CryptoAlgorithmDescription

Class	CryptoCertificateInterface			
Note	This meta-class provides the ability to define a PortInterface for a CryptoCertificate. Tags: atp.Status=candidate atp.recommendedPackage=CryptoInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, CryptoInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
isPrivate	Boolean	0..1	attr	This attribute controls the possibility to access the content of the CryptoCertificateSlot by Find() interfaces of the X509 Provider. Tags: atp.Status=candidate
writeAccess	Boolean	0..1	attr	This attribute defines whether the application has write-access to the CryptoCertificate (true) or only read-access (false). Tags: atp.Status=candidate

Table A.99: CryptoCertificateInterface

Class	CryptoCertificateToPortPrototypeMapping			
Note	This meta-class represents the ability to define a mapping between a CryptoCertificate on target-configuration level to a given PortPrototype that is typed by a CryptoCertificateInterface. Tags: atp.recommendedPackage=CryptoCertificateToPortPrototypeMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
cryptoCertificate	CryptoCertificate	0..1	ref	This reference represents the mapped cryptoCertificate.
portPrototype	RPortPrototype	0..1	iref	This reference represents the mapped PortPrototype. InstanceRef implemented by: RPortPrototypeInExecutableInstanceRef
process	Process	0..1	ref	This reference represents the process required as context for the mapping.
writeAccess	Boolean	0..1	attr	This attribute defines whether the application has write-access to the CryptoCertificate (true) or only read-access (false).

Table A.100: CryptoCertificateToPortPrototypeMapping

Class	CryptoKeySlotAllowedModification			
Note	This meta-class restricts the allowed modification of a key stored in the key slot. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	AbstractCryptoKeySlotInterface.keySlotAllowedModification, CryptoKeySlot.keySlotAllowedModification			
Attribute	Type	Mult.	Kind	Note
maxNumberOfAllowedUpdates	PositiveInteger	0..1	attr	This attribute describes the maximum updates that are allowed to the slot. Tags: atp.Status=candidate
restrictUpdate	Boolean	0..1	attr	This attribute defines whether restrictions on the number of updates are defined or not. <ul style="list-style-type: none"> false: no restriction is placed on the number of updates. true: restrictions are placed on the number of updates with the attribute maxNumberOfAllowedUpdates. Tags: atp.Status=candidate

Table A.101: CryptoKeySlotAllowedModification

Class	CryptoKeySlotContentAllowedUsage			
Note	This meta-class restricts the allowed usage of a key stored in the key slot. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	AbstractCryptoKeySlotInterface.keySlotContentAllowedUsage, CryptoKeySlot.keySlotContentAllowedUsage			
Attribute	Type	Mult.	Kind	Note
allowedKeyslotUsage	String	0..1	attr	This attribute defines for which operations the KeySlot may be used. Tags: atp.Status=candidate

Table A.102: CryptoKeySlotContentAllowedUsage

Class	CryptoKeySlotDesign			
Note	This meta-class represents a key slot on the design level. This class is used to create a model of the usage of key slots so that owners and users of the key slot can be described, as the basis for consistency checking of the overall design. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	MachineDesign.cryptoKeySlot			
Attribute	Type	Mult.	Kind	Note
algorithm Description	CryptoKeySlotDesignDescription	*	aggr	This aggregation contains the collection of crypto algorithm descriptions that can be used in the context of the enclosing crypto key slot design.
owner	CryptoKeySlotUsageDesign	*	ref	This reference attributes an owner of the enclosing crypto key slot design.
shared	Boolean	0..1	attr	This attribute controls whether the cryptographic key is shared with at least one user.
user	CryptoKeySlotUsageDesign	*	ref	This reference attributes a user of the enclosing crypto key slot design.

Table A.103: CryptoKeySlotDesign

Class	CryptoKeySlotDesignDescription			
Note	This meta-class is used to provide properties of the crypto algorithm on design level. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	CryptoKeySlotDesign.algorithmDescription			
Attribute	Type	Mult.	Kind	Note
cryptoAlgorithm Id	String	0..1	attr	This attribute describes the identity of the crypto algorithm.
cryptoObject Type	String	0..1	attr	This attribute describes the type of the crypto algorithm.

Table A.104: CryptoKeySlotDesignDescription

Class	CryptoKeySlotInterface			
Note	This meta-class provides the ability to define a PortInterface for using and modifying Crypto Key Slots. Tags: atp.Status=candidate atp.recommendedPackage=CryptoInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AbstractCryptoKeySlotInterface, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, CryptoInterface, Identifiable , MultilanguageReferrable , PackageableElement , PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.105: CryptoKeySlotInterface

Class	CryptoKeySlotUsageDesign			
Note	This meta-class represents the concrete usage (on design level) of a cryptographic key. Tags: atp.recommendedPackage=CryptoKeySlotDesigns This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			





Class	CryptoKeySlotUsageDesign			
Aggregated by	CryptoKeySlotUserDesign.keySlotUsage			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.106: CryptoKeySlotUsageDesign

Class	CryptoProviderInterface			
Note	This meta-class provides the ability to define a PortInterface for a CryptoProvider. Tags: atp.Status=candidate atp.recommendedPackage=CryptoInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, CryptoInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.107: CryptoProviderInterface

Class	CryptoProviderToPortPrototypeMapping			
Note	This meta-class represents the ability to define a mapping between a CryptoProvider on deployment level to a given PortPrototype that is typed by a CryptoProviderInterface. Tags: atp.recommendedPackage=CryptoProviderToPortPrototypeMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
cryptoProvider	CryptoProvider	0..1	ref	This reference represents the mapped cryptoProvider.
portPrototype	RPortPrototype	0..1	iref	This reference represents the mapped PortPrototype. InstanceRef implemented by: RPortPrototypeInExecutableInstanceRef
process	Process	0..1	ref	This reference represents the process required as context for the mapping.

Table A.108: CryptoProviderToPortPrototypeMapping

Class	CryptoServiceCertificate			
Note	This meta-class represents the ability to model a cryptographic certificate. Tags: atp.recommendedPackage=CryptoServiceCertificates			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
algorithmFamily	CryptoCertificateAlgorithmFamilyEnum	0..1	attr	This attribute represents a description of the family of crypto algorithm used to generate public key and signature of the cryptographic certificate.
format	CryptoCertificateFormatEnum	0..1	attr	This attribute can be used to provide information about the format used to create the certificate





Class	CryptoServiceCertificate			
maximum Length	PositiveInteger	0..1	attr	This attribute represents the ability to define the maximum length of the certificate in bytes.
nextHigher Certificate	CryptoServiceCertificate	0..1	ref	The reference identifies the next higher certificate in the certificate chain.
serverName Identification	String	0..1	attr	Server Name Indication (SNI) is needed if the IP address hosts multiple servers (on the same port), each of them using a different certificate. If the client sends the SNI to the Server in the client hello, the server looks the SNI up in its certificate list and uses the certificate identified by the SNI.

Table A.109: CryptoServiceCertificate

Class	CustomCpplImplementationDataType			
Note	This meta-class represents the way to specify a data type definition that is taken as the basis for a C++ language binding to a custom implementation that is declared in the configured header file. The Short Name of this CustomCpplImplementationDataType defines the Class-Name of the custom implementation. Tags: atp.recommendedPackage=CpplImplementationDataTypes This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement , ARObject , AbstractImplementationDataType , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , AutosarDataType , CollectableElement , CpplImplementationDataType , CpplImplementationDataTypeContextTarget , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.110: CustomCpplImplementationDataType

Class	DataConstr			
Note	This meta-class represents the ability to specify constraints on data. Tags: atp.recommendedPackage=DataConstrs			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataConstrRule	DataConstrRule	*	aggr	This is one particular rule within the data constraints. Tags: xml.roleElement=true xml.roleWrapperElement=true xml.sequenceOffset=30 xml.typeElement=false xml.typeWrapperElement=false

Table A.111: DataConstr

Class	DataConstrRule			
Note	This meta-class represents the ability to express one specific data constraint rule.			
Base	ARObject			
Aggregated by	DataConstr.dataConstrRule			
Attribute	Type	Mult.	Kind	Note





Class	DataConstrRule			
constrLevel	Integer	0..1	attr	This attribute describes the category of a constraint. One of its functions is in the area of constraint violation, where it can be used from a certain level, to produce error messages. The lower the level, the more stringent the check. Used to distinguish hard or soft limits. Tags: xml.sequenceOffset=20
internalConstrs	InternalConstrs	0..1	aggr	Describes the limitations applicable on the internal domain (as opposed to the physical domain). Tags: xml.sequenceOffset=40
physConstrs	PhysConstrs	0..1	aggr	Describes the limitations applicable on the physical domain (as opposed to the internal domain). Tags: xml.sequenceOffset=30

Table A.112: DataConstrRule

Class	DataPrototype (abstract)			
Note	Base class for prototypical roles of any data type.			
Base	ARObject, AtpFeature, AtpPrototype, Identifiable , MultilanguageReferrable, Referrable			
Subclasses	ApplicationCompositeElementDataPrototype, AutosarDataPrototype			
Aggregated by	AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
swDataDef Props	SwDataDefProps	0..1	aggr	This property allows to specify data definition properties which apply on data prototype level. Stereotypes: atpSplitable Tags: atp.Splitkey=swDataDefProps

Table A.113: DataPrototype

Class	DataPrototypeInPortInterfaceRef			
Note	This class represents a RootDataPrototype that is typed by an ApplicationDataType or Implementation DataType or a DataTypeElement that is aggregated within a composite application data type (record or array).			
Base	ARObject, DataPrototypeReference			
Aggregated by	DataPrototypeTransformationProps.dataPrototypeInPortInterfaceRef, SignalServiceTranslationElement Props.element, TransmissionComSpecProps.onChangeDataPrototype			
Attribute	Type	Mult.	Kind	Note
dataPrototypeIn ServiceInterface	DataPrototype	0..1	iref	This element defines a reference to a DataPrototype in the context of a ServiceInterface. Tags: atp.Status=draft InstanceRef implemented by: DataPrototypeInServiceInterfaceInstanceRef This Attribute is only used by the AUTOSAR Adaptive Platform.

Table A.114: DataPrototypeInPortInterfaceRef

Class	DataPrototypeInServiceInterfaceInstanceRef			
Note	This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , <i>AtpInstanceRef</i> , <i>DataPrototypeInPortInterfaceInstanceRef</i>			
Aggregated by	DataPrototypeInPortInterfaceRef.dataPrototypeInServiceInterface , DataPrototypeInServiceInterfaceRef.dataPrototype , SignalBasedFireAndForgetMethodToSignalTriggeringMapping.dataPrototypeInMethodArgumentInstanceRef			
Attribute	Type	Mult.	Kind	Note
base	ServiceInterface	0..1	ref	Stereotypes: atpDerived
contextData Prototype (ordered)	ApplicationComposite ElementDataPrototype	*	ref	Tags: xml.sequenceOffset=20
rootData Prototype	AutosarDataPrototype	0..1	ref	Tags: xml.sequenceOffset=10
targetData Prototype	DataPrototype	0..1	ref	Tags: xml.sequenceOffset=30

Table A.115: DataPrototypeInServiceInterfaceInstanceRef

Class	DataPrototypeInServiceInterfaceRef			
Note	This meta-class represents the ability to refer to an AUTOSAR DataPrototype in the context of a Service Interface. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i>			
Aggregated by	SignalBasedEventElementToSignalTriggeringMapping.dataPrototypeInServiceInterfaceRef , SignalBasedFieldToSignalTriggeringMapping.dataPrototypeInServiceInterfaceRef , SomeipDataPrototypeTransformationProps.dataPrototype			
Attribute	Type	Mult.	Kind	Note
dataPrototype	DataPrototype	0..1	iref	This element represents the ability to: <ul style="list-style-type: none"> refer to a DataPrototype in the context of a Service Interface. refer to the internal structure of a DataPrototype in which is typed by an ApplicationDatatype the context of a ServiceInterface. InstanceRef implemented by: DataPrototypeInServiceInterfaceInstanceRef
elementInImpl Datatype	PortInterfaceElementIn Implementation DatatypeRef	0..1	aggr	This element represents the ability to refer to the internal structure of an AutosarDataPrototype which is typed by an ImplementationDatatype in the context of a Service Interface.

Table A.116: DataPrototypeInServiceInterfaceRef

Class	DataPrototypeReference (abstract)			
Note	This meta-class provides the ability to reference a DataPrototype.			
Base	<i>ARObject</i>			
Subclasses	DataPrototypeInPortInterfaceRef , ImplementationDataTypeElementInPortInterfaceRef			
Aggregated by	DataPrototypeTransformationProps.dataPrototypeInPortInterfaceRef, SignalServiceTranslationElement Props.element, TransmissionComSpecProps.onChangeDataPrototype			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.117: DataPrototypeReference

Class	DataTypeMap			
Note	This class represents the relationship between ApplicationDataType and its implementing AbstractImplementationDataType .			
Base	ARObject			
Aggregated by	DataTypeMappingSet.dataTypeMap			
Attribute	Type	Mult.	Kind	Note
applicationData Type	ApplicationDataType	0..1	ref	This is the corresponding ApplicationDataType
implementation DataType	AbstractImplementation DataType	0..1	ref	This is the corresponding AbstractImplementationDataType .

Table A.118: DataTypeMap

Class	DataTypeMappingSet			
Note	This class represents a list of mappings between ApplicationDataTypes and ImplementationDataTypes . In addition, it can contain mappings between ImplementationDataTypes and ModeDeclarationGroups . Tags: atp.recommendedPackage=DataTypeMappingSets			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , CollectableElement , Identifiable , Multilanguage Referrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataTypeMap	DataTypeMap	*	aggr	This is one particular association between an ApplicationDataType and its AbstractImplementationDataType .
modeRequest TypeMap	ModeRequestTypeMap	*	aggr	This is one particular association between an ModeDeclarationGroup and its AbstractImplementationDataType .

Table A.119: DataTypeMappingSet

Class	DdsDomainRange			
Note	DDS Domain ID range. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	DdsSecureGovernance.domainId			
Attribute	Type	Mult.	Kind	Note
max	PositiveInteger	0..1	attr	Upper bound of the DdsDomainRange.
min	PositiveInteger	0..1	attr	Lower bound of the DdsDomainRange.

Table A.120: DdsDomainRange

Class	DdsEventDeployment			
Note	DDS configuration settings for an Event. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable , ServiceEventDeployment , ServiceInterface DeploymentElement			
Aggregated by	DdsFieldDeployment.notifier , ServiceInterfaceDeployment.eventDeployment			
Attribute	Type	Mult.	Kind	Note
eventTopic AccessRule	DdsTopicAccessRule	0..1	ref	DDS Security access rule applicable to the DDS Topics used for the service interface event.





Class	DdsEventDeployment			
topicName	String	0..1	attr	Name of the DDS Topic associated with the Event.
transport Protocol	String	*	attr	This attribute defines over which Transport Layer Protocol(s) this event is intended to be sent.

Table A.121: DdsEventDeployment

Class	DdsEventQosProps			
Note	Configuration properties of the Event using DDS as the underlying network binding. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, DdsQosProps			
Aggregated by	DdsProvidedServiceInstance.eventQosProps , DdsRequiredServiceInstance.eventQosProps			
Attribute	Type	Mult.	Kind	Note
event	ServiceEvent Deployment	0..1	ref	Reference to an event that is provided.

Table A.122: DdsEventQosProps

Class	DdsFieldQosProps			
Note	Configuration properties of the Field interaction when using DDS as the underlying network binding. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, DdsQosProps			
Aggregated by	DdsProvidedServiceInstance.fieldNotifierQosProps , DdsRequiredServiceInstance.fieldNotifierQosProps			
Attribute	Type	Mult.	Kind	Note
field	ServiceField Deployment	0..1	ref	Reference to the field.

Table A.123: DdsFieldQosProps

Enumeration	DdsProtectionKindEnum			
Note	Supported cryptographic transformations (extended). This Enumeration is only used by the AUTOSAR Adaptive Platform.			
Aggregated by	DdsSecureGovernance.discoveryProtectionKind , DdsSecureGovernance.livelinessProtectionKind , DdsSecureGovernance.rtpsProtectionKind , DdsTopicAccessRule.dataProtectionKind , DdsTopicAccessRule.metadataProtectionKind			
Literal	Description			
encryptAndSign	encryption and MAC transformations (in that precise order) are applied Tags: atp.EnumerationLiteralIndex=2			
encryptAndSign WithOrigin Authentication	similar to "EncryptAndSign" but with additional authentication codes produced under different secret keys, which prevents receiving peers from impersonating a specific sender Tags: atp.EnumerationLiteralIndex=4			
none	no transformation is applied Tags: atp.EnumerationLiteralIndex=0			
sign	Message Authentication Code (MAC) is applied, no encryption Tags: atp.EnumerationLiteralIndex=1			
signWithOrigin Authentication	similar to "sign" but with additional authentication codes produced under different secret keys, which prevents receiving peers from impersonating a specific sender Tags: atp.EnumerationLiteralIndex=3			

Table A.124: DdsProtectionKindEnum

Class	DdsProvidedServiceInstance			
Note	This meta-class represents the ability to describe the existence and configuration of a provided service instance in a concrete implementation on top of DDS. Tags: atp.recommendedPackage=ServiceInstances This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AdaptivePlatformServiceInstance , CollectableElement , DdsQosProps , DdsServiceInstanceProps , Identifiable , MultilanguageReferrable , PackageableElement , ProvidedApServiceInstance , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
discoveryType	DdsServiceInstanceDiscoveryTypeEnum	0..1	attr	Discovery protocol.
eventQosProps	DdsEventQosProps	*	aggr	List of configuration properties for the Events that are provided by the Service Instance.
fieldNotifierQosProps	DdsFieldQosProps	*	aggr	List of configuration properties for Field notifiers that are provided by the Service Instance.
resourceIdentifierType	DdsServiceInstanceResourceIdentifierTypeEnum	0..1	attr	Type of resource identification scheme.
serviceInstanceId	PositiveInteger	0..1	attr	Identification number that is used by DDS to identify DomainParticipants associated with an instance of the service.

Table A.125: DdsProvidedServiceInstance

Class	DdsQosProps (abstract)			
Note	QoS configuration properties for the DDS entities associated with an event, method, or field provided by or requested from a Service Instance using DDS as the underlying network binding. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Subclasses	DdsEventQosProps , DdsFieldQosProps , DdsServiceInstanceProps			
Attribute	Type	Mult.	Kind	Note
qosProfile	String	0..1	attr	Identifies a group of QoS Policies that apply to the DDS entities associated with the event, method, field, or the service instance.

Table A.126: DdsQosProps

Class	DdsRequiredServiceInstance			
Note	This meta-class represents the ability to describe the existence and configuration of a required service instance in a concrete implementation on top of DDS. Tags: atp.recommendedPackage=ServiceInstances This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AdaptivePlatformServiceInstance , CollectableElement , DdsQosProps , DdsServiceInstanceProps , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , RequiredApServiceInstance , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
blocklistedVersion	DdsServiceVersion	*	aggr	Collection of blocklisted versions.
discoveryType	DdsServiceInstanceDiscoveryTypeEnum	0..1	attr	Discovery protocol.
eventQosProps	DdsEventQosProps	*	aggr	List of configuration properties for the Events that are required by the Service Instance.





Class	DdsRequiredServiceInstance			
fieldNotifierQosProps	DdsFieldQosProps	*	aggr	List of configuration properties for Field notifiers that are required by the Service Instance.
requiredServiceInstancelId	AnyServiceInstancelId	0..1	attr	This attribute represents the ability to describe the required service instance ID.

Table A.127: DdsRequiredServiceInstance

Class	DdsRule			
Note	Configuration of a DDS firewall rule Tags: atp.Status=candidate			
Base	ARObject			
Aggregated by	FirewallRule.ddsRule			
Attribute	Type	Mult.	Kind	Note
appld	PositiveInteger	0..1	attr	Filter for DDSI-RTPS messages in which the appld in the DDSI-RTPS header and the INFO_DST (0x0E) submessage matches. Tags: atp.Status=candidate
hostId	PositiveInteger	0..1	attr	Filter for DDSI-RTPS messages in which the hostId in the DDSI-RTPS header and the INFO_DST (0x0E) submessage matches. Tags: atp.Status=candidate
instancelId	PositiveInteger	0..1	attr	Filter for DDSI-RTPS messages in which the instancelId in the DDSI-RTPS header and the INFO_DST (0x0E) submessage matches. Tags: atp.Status=candidate
majorProtocolVersion	PositiveInteger	0..1	attr	Filter for DDSI-RTPS messages in which the major ProtocolVersion in the DDSI-RTPS header matches. Tags: atp.Status=candidate
minorProtocolVersion	PositiveInteger	0..1	attr	Filter for DDSI-RTPS messages in which the minor ProtocolVersion in the DDSI-RTPS header matches. Tags: atp.Status=candidate
productId	PositiveInteger	0..1	attr	Filter for DDSI-RTPS messages in which the productId in the DDSI-RTPS header matches. Tags: atp.Status=candidate
readerEntityId	PositiveInteger	0..1	attr	Filter for DDSI-RTPS messages in which the readerEntity ID in a DDSI-RTPS submessage matches Tags: atp.Status=candidate
submessageType	PositiveInteger	0..1	attr	Defines the allowed submessage type in the DDSI-RTPS message Tags: atp.Status=candidate
vendorId	PositiveInteger	0..1	attr	Filter for DDSI-RTPS messages in which the vendorId in the DDSI-RTPS header matches. Tags: atp.Status=candidate
writerEntityId	PositiveInteger	0..1	attr	Filter for DDSI-RTPS messages in which the writerEntity ID in a DDSI-RTPS submessage matches Tags: atp.Status=candidate

Table A.128: DdsRule

Class	DdsSecureComProps
Note	Identity and governance information of participants in case of DDS Security. Tags: atp.recommendedPackage=SecureComProps This Class is only used by the AUTOSAR Adaptive Platform.





Class	DdsSecureComProps			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , SecureComProps , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
governance	DdsSecureGovernance	0..1	ref	This attribute defines general DDS Security communication properties applicable to the DDS domain(s) in which the subject operates. Tags: atp.Status=candidate
identity	CryptoCertificate	0..1	ref	This attribute defines the cryptographic identity of the subject.

Table A.129: DdsSecureComProps

Class	DdsSecureGovernance			
Note	Configuration of DDS Security for all applications joining a specific set of DDS Domains. Tags: atp.Status=candidate atp.recommendedPackage=DdsSecureGovernances This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
allowUnauthenticatedParticipants	Boolean	0..1	attr	Defines whether unauthenticated participants can join this domain. Tags: atp.Status=candidate
discoveryProtectionKind	DdsProtectionKindEnum	0..1	attr	Defines the kind of cryptographic transformation to apply in DDS discovery communication. Tags: atp.Status=candidate
domainId	DdsDomainRange	*	aggr	Set of domains to be covered by this property set. Tags: atp.Status=candidate
enableJoinAccessControl	Boolean	0..1	attr	Defines whether access control is to be enforced upon joining this domain. Tags: atp.Status=candidate
identityCertificateAuthority	CryptoCertificate	0..1	ref	Certificate representing the identity certificate authority applicable to the domain(s) specified by domainIds. Tags: atp.Status=candidate
livelinessProtectionKind	DdsProtectionKindEnum	0..1	attr	Defines the kind of cryptographic transformation to apply in DDS liveliness communication. Tags: atp.Status=candidate
permissionCertificateAuthority	CryptoCertificate	0..1	ref	Certificate representing the permissions certificate authority applicable to the domain(s) specified by domainIds. Tags: atp.Status=candidate
rtpsProtectionKind	DdsProtectionKindEnum	0..1	attr	Defines the kind of cryptographic transformation to apply to whole DDS RTPS. Tags: atp.Status=candidate

Table A.130: DdsSecureGovernance

Enumeration	DdsServiceInstanceDiscoveryTypeEnum
Note	Supported discovery schemes for DDS Service Instances. This Enumeration is only used by the AUTOSAR Adaptive Platform.
Aggregated by	DdsProvidedServiceInstance.discoveryType , DdsRequiredServiceInstance.discoveryType
Literal	Description
domainParticipant UserDataQos	The USER_DATA QoS policy is used to advertise and discover available Service Instances hosted by each Domain Participant. Tags: atp.EnumerationLiteralIndex=0
topic	A purpose-specific Topic is used to convey availability of Service Instances and how to bind against them. Tags: atp.EnumerationLiteralIndex=1

Table A.131: DdsServiceInstanceDiscoveryTypeEnum

Class	DdsServiceInstanceProps (abstract)			
Note	Common configuration properties for the DDS entities provided by or requested from a Service Instance using DDS as the underlying network binding. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject , DdsQosProps			
Subclasses	DdsProvidedServiceInstance , DdsRequiredServiceInstance			
Attribute	Type	Mult.	Kind	Note
domainId	Integer	0..1	attr	This attribute identifies the DDS Domain the Service Instance shall join.

Table A.132: DdsServiceInstanceProps

Enumeration	DdsServiceInstanceResourceIdentifierTypeEnum
Note	Supported Resource Identification schemes for DDS Service Instances. This Enumeration is only used by the AUTOSAR Adaptive Platform.
Aggregated by	DdsProvidedServiceInstance.resourceIdentifierType
Literal	Description
instanceId	In-band instance identification fields are used to discriminate samples related to specific Service Instances sharing the same DDS Topics <ul style="list-style-type: none"> Partitions: - Topics: ara.com://services/<InterfaceId>/<Major>.<<Minor>/<TopicName> Tags: atp.EnumerationLiteralIndex=2
partition	The DDS PARTITION QoS policy is used to isolate DDS Topics related to specific Service Instances <ul style="list-style-type: none"> Partitions: ara.com://services/<InterfaceId>/<InstanceId> Topics: ara.com://services/<InterfaceId>/<Major>.<Minor>/<TopicName> Tags: atp.EnumerationLiteralIndex=0
topicPrefix	Unique prefixes are assigned to DDS Topics related to specific Service Instances <ul style="list-style-type: none"> Partitions: - Topics: ara.com://services/<InterfaceId>/<InstanceId>/<TopicName> Tags: atp.EnumerationLiteralIndex=1

Table A.133: DdsServiceInstanceResourceIdentifierTypeEnum

Class	DdsServiceInstanceToMachineMapping
Note	This meta-class allows to map DdsServiceInstances to a CommunicationConnector of a Machine. Tags: atp.recommendedPackage=ServiceInstanceToMachineMappings This Class is only used by the AUTOSAR Adaptive Platform.





Class	DdsServiceInstanceToMachineMapping			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , ServiceInstanceToMachineMapping , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
secureComPropsForDds	DdsSecureComProps	0..1	ref	Reference to SecureComProps applicable to the service instance.

Table A.134: DdsServiceInstanceToMachineMapping

Class	DdsServiceInterfaceDeployment			
Note	DDS configuration settings for a ServiceInterface. Tags: atp.recommendedPackage=ServiceInterfaceDeployments This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , ServiceInterfaceDeployment , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
fieldReplyTopicName	String	0..1	attr	Name of the DDS Reply Topic associated with the Field.
fieldRequestTopicName	String	0..1	attr	Name of the DDS Request Topic associated with the Field.
fieldTopicsAccessRule	DdsTopicAccessRule	0..1	ref	DDS Security access rule applicable to the DDS Topics used for service interface field access methods (Get, Set).
methodReplyTopicName	String	0..1	attr	Name of the DDS Reply Topic associated with the Method.
methodRequestTopicName	String	0..1	attr	Name of the DDS Request Topic associated with the Method.
methodTopicsAccessRule	DdsTopicAccessRule	0..1	ref	DDS Security access rule applicable to the DDS Topics used for service interface methods.
serviceInterfaceId	String	0..1	attr	Unique Identifier that identifies the ServiceInterface in DDS. This Identifier is encoded in the USER_DATA QoS of the DomainParticipant associated with the Service Instance and its value is propagated by DDS Discovery messages.
transportProtocol	String	*	attr	This attribute defines over which Transport Layer Protocol(s) this Method is intended to be sent.

Table A.135: DdsServiceInterfaceDeployment

Class	DdsTopicAccessRule			
Note	DDS Topic access rule definition. Tags: atp.recommendedPackage=DdsTopicAccessRules This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataProtectionKind	DdsProtectionKind Enum	0..1	attr	Defines the data protection policy applicable to metadata related to the DDS Topic(s).





Class	DdsTopicAccessRule			
enableDiscoveryProtection	Boolean	0..1	attr	Defines whether discovery protection mechanisms should apply to the DDS Topic(s).
enableLivelinessProtection	Boolean	0..1	attr	Defines whether liveliness protection mechanisms should apply to the DDS Topic(s).
enableReadAccessControl	Boolean	0..1	attr	Defines whether read access control mechanisms should apply to the DDS Topic(s).
enableWriteAccessControl	Boolean	0..1	attr	Defines whether write access control mechanisms should apply to the DDS Topic(s).
metadataProtectionKind	DdsProtectionKind Enum	0..1	attr	Defines the data protection policy applicable to metadata related to the DDS Topic(s).

Table A.136: DdsTopicAccessRule

Class	DeadlineSupervision			
Note	Defines an DeadlineSupervision for one transition. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable, MultilanguageReferrable, PhmSupervision, Referrable			
Aggregated by	GlobalSupervision.deadlineSupervision			
Attribute	Type	Mult.	Kind	Note
maxDeadline	TimeValue	0..1	attr	Defines the longest time span before which the deadline is considered to be met for transition.
minDeadline	TimeValue	0..1	attr	Defines the shortest time span after which the deadline is considered to be met for transition.
transition	CheckpointTransition	0..1	ref	Reference to the transition in the context of a Deadline Supervision.

Table A.137: DeadlineSupervision

Class	DiagnosticAbstractParameter (abstract)			
Note	This meta-class represents an abstract base class for modeling a diagnostic parameter.			
Base	ARObject			
Subclasses	DiagnosticParameter, DiagnosticParameterElement			
Attribute	Type	Mult.	Kind	Note
bitOffset	PositiveInteger	0..1	attr	This represents the bitOffset of the DiagnosticParameter. The value of the bitOffset shall always be interpreted as relative to the start of the enclosing DiagnosticData Identifier, DiagnosticParameterIdentifier, or Diagnostic RoutineSubfunction. Stereotypes: atpIdentityContributor Tags: atp.Status=candidate
dataElement	DiagnosticDataElement	0..1	aggr	This represents the related dataElement of the Diagnostic Parameter Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dataElement.shortName, dataElement.variationPoint.shortLabel vh.latestBindingTime=postBuild





Class	DiagnosticAbstractParameter (abstract)			
parameterSize	PositiveInteger	0..1	attr	This attribute allows for the specification of the parameter size. This information is relevant if there is a gap between one diagnostic parameter and the following diagnostic parameter (or the tail of the telegram). The unit is bit and the values shall be multiples of 8. Tags: atp.Status=candidate

Table A.138: DiagnosticAbstractParameter

Class	DiagnosticAuthTransmitCertificate			
Note	This meta-class represents the sub-function to transmit a certificate Tags: atp.recommendedPackage=DiagnosticAuthTransmitCertificates			
Base	ARElement, ARObject, CollectableElement, DiagnosticAuthentication , DiagnosticCommonElement, DiagnosticServiceInstance, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
certificateEvaluation	DiagnosticAuthTransmitCertificateEvaluation	*	aggr	This aggregation represents a collection of certificate evaluation configurations.

Table A.139: DiagnosticAuthTransmitCertificate

Class	DiagnosticAuthentication (abstract)			
Note	This meta-class represents the ability to configure the usage of the UDS service Authentication in the Diagnostic extract.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticServiceInstance, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Subclasses	DiagnosticAuthTransmitCertificate , DiagnosticAuthenticationConfiguration, DiagnosticDeAuthentication, DiagnosticProofOfOwnership, DiagnosticVerifyCertificateBidirectional, DiagnosticVerifyCertificateUnidirectional			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
authenticationClass	DiagnosticAuthenticationClass	0..1	ref	This represents the corresponding "class", i.e. this meta-class provides properties that are shared among all instances of applicable sub-classes of DiagnosticServiceInstance. The subclasses that affected by this pattern implement references to the applicable "class"-role that substantiate this abstract reference.

Table A.140: DiagnosticAuthentication

Class	DiagnosticAuthenticationInterface			
Note	This meta-class represents the ability to implement a focused PortInterface for handling the diagnostic service "authentication" on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.141: DiagnosticAuthenticationInterface

Class	DiagnosticAuthenticationPortMapping			
Note	This mapping class identifies the PortPrototype in the application software that handles the client authentication. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnostic Authentication	Diagnostic Authentication	0..1	ref	Reference to the DiagnosticAuthentication that is assigned to a SWC service port.
pPortPrototype InExecutable	PPortPrototype	0..1	iref	This aggregation allows for the usage of the Diagnostic AuthenticationPortMapping on the AUTOSAR adaptive platform. Stereotypes: atpUriDef InstanceRef implemented by: PPortPrototypeIn ExecutableInstanceRef
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atpSplittable Tags: atp.Splitkey=process

Table A.142: DiagnosticAuthenticationPortMapping

Class	DiagnosticClearCondition			
Note	This meta-class describes a clear condition for diagnostic purposes. Tags: atp.recommendedPackage=DiagnosticConditions This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticCondition , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.143: DiagnosticClearCondition

Class	DiagnosticClearConditionPortMapping			
Note	Defines to which SWC service ports the DiagnosticClearCondition is mapped. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
clearCondition	DiagnosticClear Condition	0..1	ref	Reference to the ClearCondition which is mapped to a SWC service port.
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atpSplittable Tags: atp.Splitkey=process





Class	DiagnosticClearConditionPortMapping			
rPortPrototype InExecutable	RPortPrototype	0..1	iref	This aggregation allows for the usage of the Diagnostic ClearConditionMapping on the AUTOSAR adaptive platform. Stereotypes: atpUriDef InstanceRef implemented by: RPortPrototypeInExecutableInstanceRef

Table A.144: DiagnosticClearConditionPortMapping

Class	«atpVariation» DiagnosticCommonProps			
Note	This meta-class aggregates a number of common properties that are shared among a diagnostic extract. Tags: vh.latestBindingTime=codeGenerationTime			
Base	ARObject			
Aggregated by	DiagnosticContributionSet.commonProperties			
Attribute	Type	Mult.	Kind	Note
authentication Timeout	TimeValue	0..1	attr	This attribute defines the time (in seconds) that the authentication state is maintained in default-session if there is no communication from the authenticated client.
debounce AlgorithmProps	DiagnosticDebounce AlgorithmProps	*	aggr	Defines the used debounce algorithms relevant in the context of the enclosing DiagnosticCommonProps. Usually, there is a variety of debouncing algorithms to take into account and therefore the multiplicity of this aggregation is set to 0..*. Note: This atpSplitable property has no atp.Splitkey due to atpVariation (PropertySetPattern). Stereotypes: atpSplitable; atpVariation Tags: vh.latestBindingTime=postBuild
default Endianness	ByteOrderEnum	0..1	attr	Defines the default endianness of the data belonging to a DID or RID which is applicable if the DiagnosticData Element does not define the endianness via the swData DefProps.baseType attribute.
diagnostic Address	SoftwareCluster DiagnosticAddress	*	aggr	"This aggregation represents the collection of diagnostic addresses that apply for the SoftwareClusterDesign. Note: This atpSplitable property has no atp.Splitkey due to atpVariation (PropertySetPattern). Stereotypes: atpSplitable Tags: xml.namePlural=DIAGNOSTIC-ADDRESSES This Attribute is only used by the AUTOSAR Adaptive Platform.
event Combination Reporting Behavior	DiagnosticEvent CombinationReporting BehaviorEnum	0..1	attr	In case of EventCombination on Retrieval, this attribute specifies if a specific order of reporting is to be maintained.
external Authentication	DiagnosticExternal Authentication Identification	*	aggr	This aggregation supports the configuration of the authentication of diagnostic clients. Note: This atpSplitable property has no atp.Splitkey due to atpVariation (PropertySetPattern). Stereotypes: atpSplitable This Attribute is only used by the AUTOSAR Adaptive Platform.
maxNumberOf Request Correctly Received Response Pending	PositiveInteger	0..1	attr	Maximum number of negative responses with response code 0x78 (requestCorrectlyReceived-ResponsePending) allowed per request. DCM will send a negative response with response code 0x10 (generalReject), in case the limit value gets reached. Value 0xFF means that no limit number of NRC 0x78 response apply.





Class	«atpVariation» DiagnosticCommonProps			
occurrenceCounterProcessing	DiagnosticOccurrenceCounterProcessingEnum	0..1	attr	This attribute defines the consideration of the fault confirmation process for the occurrence counter.
resetConfirmedBitOnOverflow	Boolean	0..1	attr	This attribute defines, whether the confirmed bit is reset or not while an event memory entry will be displaced.
resetPendingBitOnOverflow	Boolean	0..1	attr	This attribute defines, whether the pending bit is reset or not while an event memory entry will be displaced. In order to be compliant to ISO 14229-1 [1], this parameter needs to be set to "false".
responseOnAllRequestSids	Boolean	0..1	attr	If set to FALSE the DCM will not respond to diagnostic request that contains a service ID which is in the range from 0x40 to 0x7F or in the range from 0xC0 to 0xFF (Response IDs).
responseOnSecondDeclinedRequest	Boolean	0..1	attr	Defines the reaction upon a second request (ClientB) that can not be processed (e.g. due to priority assessment). TRUE: when the second request (Client B) can not be processed, it shall be answered with NRC21 BusyRepeat Request. FALSE: when the second request (Client B) can not be processed, it shall not be responded.
sovdProperties	DiagnosticSovdProps	1	aggr	This aggregation contains the definition of common properties that are specific for SOVD. This Attribute is only used by the AUTOSAR Adaptive Platform.
typeOfEventCombinationSupported	DiagnosticEventCombinationBehaviorEnum	0..1	attr	Select type of Event Combination support.

Table A.145: DiagnosticCommonProps

Class	DiagnosticConditionInterface			
Note	This meta-class represents the ability to implement a PortInterface to process requests for diagnostic conditions on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.146: DiagnosticConditionInterface

Class	DiagnosticContributionSet			
Note	This meta-class represents a root node of a diagnostic extract. It bundles a given set of diagnostic model elements. The granularity of the DiagnosticContributionSet is arbitrary in order to support the aspect of decentralized configuration, i.e. different contributors can come up with an own DiagnosticContribution Set. Tags: atp.recommendedPackage=DiagnosticContributionSets			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–





Class	DiagnosticContributionSet			
common Properties	DiagnosticCommon Props	0..1	aggr	This attribute represents a collection of diagnostic properties that are shared among the entire DiagnosticContributionSet. Stereotypes: atpSplitable Tags: atp.Splitkey=commonProperties
element	DiagnosticCommon Element	*	ref	This represents a DiagnosticCommonElement considered in the context of the DiagnosticContributionSet Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=element.diagnosticCommonElement, element.variationPoint.shortLabel vh.latestBindingTime=postBuild
serviceTable	DiagnosticServiceTable	*	ref	This represents the collection of DiagnosticServiceTables to be considered in the scope of this DiagnosticContributionSet. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=serviceTable.diagnosticServiceTable, serviceTable.variationPoint.shortLabel vh.latestBindingTime=postBuild

Table A.147: DiagnosticContributionSet

Class	DiagnosticDTCInformationInterface			
Note	This meta-class represents the ability to implement a PortInterface to access the properties of DTCs on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.148: DiagnosticDTCInformationInterface

Class	DiagnosticDataElement			
Note	This meta-class represents the ability to describe a concrete piece of data to be taken into account for diagnostic purposes.			
Base	ARObject, DiagnosticServiceMappingDiagTarget, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	DiagnosticAbstractParameter.dataElement			
Attribute	Type	Mult.	Kind	Note
arraySize Semantics	ArraySizeSemantics Enum	0..1	attr	This attribute controls the meaning of the value of the array size.
maxNumberOf Elements	PositiveInteger	0..1	attr	The existence of this attribute turns the data instance into an array of data. The attribute determines the size of the array in terms of how many elements the array can take.
scalingInfoSize	PositiveInteger	0..1	attr	Size in bytes of scaling information for the DiagnosticDataElement if used with DiagnosticReadScalingDataBy Identifier





Class	DiagnosticDataElement			
swDataDef Props	SwDataDefProps	0..1	aggr	This property allows to specify data definition properties in order to support the definition of e.g. computation formulae and data constraints. Stereotypes: atpSplitable Tags: atp.Splitkey=swDataDefProps

Table A.149: DiagnosticDataElement

Class	DiagnosticDataElementInterface			
Note	This meta-class represents the ability to implement a element-of-DID-focused PortInterface for diagnostics on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticAbstractDataIdentifierInterface, DiagnosticPortInterface, Identifiable, MultilanguageReferrable, PackageableElement, PortInterface, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
read	ClientServerOperation	0..1	aggr	This represents the method to read the content of an element of a diagnostic data identifier.

Table A.150: DiagnosticDataElementInterface

Class	DiagnosticDataIdentifier			
Note	This meta-class represents the ability to model a diagnostic data identifier (DID) that is fully specified regarding the payload at configuration-time. Tags: atp.recommendedPackage=DiagnosticDataIdentifiers			
Base	<i>ARElement, ARObject, CollectableElement, DiagnosticAbstractDataIdentifier, DiagnosticCommonElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataElement	DiagnosticParameter	*	aggr	This is the dataElement associated with the Diagnostic DataIdentifier. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dataElement.bitOffset, dataElement.ident.shortName, dataElement.variation Point.shortLabel vh.latestBindingTime=postBuild
didSize	PositiveInteger	0..1	attr	This attribute indicates the size in bytes of the Diagnostic DataIdentifier.
representsVin	Boolean	0..1	attr	This attributes indicates whether the specific Diagnostic DataIdentifier represents the vehicle identification.
supportInfoByte	DiagnosticSupportInfo Byte	0..1	aggr	This attribute represents the supported information associated with the DiagnosticDataIdentifier.

Table A.151: DiagnosticDataIdentifier

Class	DiagnosticDataIdentifierGenericInterface			
Note	This meta-class represents the ability to implement a generic DID-focused PortInterface for diagnostics on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			





Class	DiagnosticDataIdentifierGenericInterface			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticAbstractDataIdentifierInterface, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.152: DiagnosticDataIdentifierGenericInterface

Class	DiagnosticDataIdentifierInterface			
Note	This meta-class represents the ability to implement a DID-focused PortInterface for diagnostics on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticAbstractDataIdentifierInterface, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
read	ClientServerOperation	0..1	aggr	This represents the method to read the content of a diagnostic data identifier.
write	ClientServerOperation	0..1	aggr	This represents the method to write the contents of a diagnostic data identifier.

Table A.153: DiagnosticDataIdentifierInterface

Class	DiagnosticDataPortMapping			
Note	This meta-class provides the ability to define a diagnostic access to an entire DID. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnosticDataElement	DiagnosticDataElement	0..1	ref	This reference represents the applicable DiagnosticDataElement.
diagnosticDataIdentifier	DiagnosticDataIdentifier	0..1	ref	This reference represents the applicable DiagnosticDataIdentifier.
pPortPrototypeInExecutable	PPortPrototype	0..1	iref	This reference identifies the applicable PPortPrototype from which that data is obtained. The reference has the ability to point into the component hierarchy (under possible consideration of the rootSoftwareComposition). Stereotypes: atp.UriDef InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atp.Splitable Tags: atp.Splitkey=process

Table A.154: DiagnosticDataPortMapping

Class	DiagnosticDoIPActivationLineInterface			
Note	This meta-class represents the ability to implement a PortInterface to implement the DoIPActivationLine on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.155: DiagnosticDoIPActivationLineInterface

Class	DiagnosticDoIPEntityIdentificationInterface			
Note	This meta-class represents the ability to implement a PortInterface to implement the DoIP Entity Identification on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.156: DiagnosticDoIPEntityIdentificationInterface

Class	DiagnosticDoIPGroupIdentificationInterface			
Note	This meta-class represents the ability to implement a PortInterface to implement the DoIP Group Identification on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.157: DiagnosticDoIPGroupIdentificationInterface

Class	DiagnosticDoIPPowerModelInterface			
Note	This meta-class represents the ability to implement a PortInterface to implement the DoIP Power Mode on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.158: DiagnosticDoIPPowerModelInterface

Class	DiagnosticDoIPTriggerVehicleAnnouncementInterface			
Note	This meta-class represents the ability to implement a PortInterface to implement the DoIPTriggerVehicle Announcement on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.159: DiagnosticDoIPTriggerVehicleAnnouncementInterface

Class	DiagnosticDoIPActivationLinePortMapping			
Note	This mapping class identifies the PortPrototype in the application software that handles the DoIP activation line. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AbstractDoIPPortMapping , CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
network Configuration Design	DoIPNetwork ConfigurationDesign	0..1	ref	This reference identifies the applicable DoIPNetwork ConfigurationDesign.

Table A.160: DiagnosticDoIPActivationLinePortMapping

Class	DiagnosticDoIPEntityIdentificationPortMapping			
Note	This mapping class identifies the PortPrototype in the application software that handles the DoIP identity identification. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AbstractDoIPPortMapping , CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.161: DiagnosticDoIPEntityIdentificationPortMapping

Class	DiagnosticDoIPGroupIdentificationPortMapping			
Note	This mapping class identifies the PortPrototype in the application software that handles the DoIP group identification. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AbstractDoIPPortMapping , CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.162: DiagnosticDoIPGroupIdentificationPortMapping

Class	DiagnosticDolpPowerModePortMapping			
Note	This mapping class identifies the PortPrototype in the application software that handles the DoIP power mode. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AbstractDolpPortMapping , CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.163: DiagnosticDolpPowerModePortMapping

Class	DiagnosticDolpTriggerVehicleAnnouncementPortMapping			
Note	This mapping class identifies the PortPrototype in the application software that triggers the DoIP vehicle announcement. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AbstractDolpPortMapping , CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
network Configuration Design	DolpNetwork ConfigurationDesign	0..1	ref	This reference identifies the applicable DolpNetwork ConfigurationDesign.

Table A.164: DiagnosticDolpTriggerVehicleAnnouncementPortMapping

Class	DiagnosticEcuReset			
Note	This represents an instance of the "ECU Reset" diagnostic service. Tags: atp.recommendedPackage=DiagnosticEcuResets			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticServiceInstance, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
customSub Function Number	PositiveInteger	0..1	attr	This attribute shall be used to define a custom sub-function number if none of the standardized values of category shall be used.
ecuResetClass	DiagnosticEcuReset Class	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticEcuReset in the given context.

Table A.165: DiagnosticEcuReset

Class	DiagnosticEnableCondition			
Note	Specification of an enable condition. Tags: atp.recommendedPackage=DiagnosticConditions			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticCondition, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			





Class	DiagnosticEnableCondition			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.166: DiagnosticEnableCondition

Class	DiagnosticEnableConditionPortMapping			
Note	Defines to which SWC service ports the DiagnosticEnableCondition is mapped. Tags: atp.recommendedPackage=DiagnosticPortMappings			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
enableCondition	DiagnosticEnableCondition	0..1	ref	Reference to the EnableCondition which is mapped to a SWC service port.
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atpSplittable Tags: atp.Splitkey=process This Attribute is only used by the AUTOSAR Adaptive Platform.
rPortPrototypeInExecutable	RPortPrototype	0..1	iref	This aggregation allows for the usage of the Diagnostic EnableConditionPortMapping on the AUTOSAR adaptive platform. Stereotypes: atpUriDef InstanceRef implemented by: RPortPrototypeInExecutableInstanceRef This Attribute is only used by the AUTOSAR Adaptive Platform.

Table A.167: DiagnosticEnableConditionPortMapping

Class	DiagnosticEnvDataElementCondition			
Note	This meta-class represents the ability to formulate a diagnostic environment condition based on the value of a data element owned by the application software.			
Base	ARObject, DiagnosticEnvCompareCondition, DiagnosticEnvConditionFormulaPart			
Aggregated by	DiagnosticEnvConditionFormula.part			
Attribute	Type	Mult.	Kind	Note
compareValue	ValueSpecification	0..1	aggr	This aggregation represents the definition of the compare value against which the value taken from the application software shall be compared.
dataPrototype	DataPrototype	0..1	iref	This instanceRef represent the ability to access a data element owned by the application software on the AUTOSAR classic platform. InstanceRef implemented by: DataPrototypeInSystemInstanceRef





Class	DiagnosticEnvDataElementCondition			
pPortPrototype	PPortPrototype	0..1	iref	This instanceRef identifies the PortPrototype from which the relevant information for the environment condition can be obtained. This InstanceRef is only relevant for the adaptive platform. Stereotypes: atpUriDef InstanceRef implemented by: PPortPrototypeIn ExecutableInstanceRef This Attribute is only used by the AUTOSAR Adaptive Platform.
process	ProcessDesign	0..1	ref	This reference identifies the applicable ProcessDesign. This Attribute is only used by the AUTOSAR Adaptive Platform.
swDataDef Props	SwDataDefProps	0..1	aggr	Via this aggregation it is possible to describe the properties of the data that is obtained from the application for the environmental condition. Stereotypes: atpSplitable Tags: atp.Splitkey=swDataDefProps

Table A.168: DiagnosticEnvDataElementCondition

Class	DiagnosticEnvSovdDataCondition			
Note	A DiagnosticEnvSovdDataCondition is an atomic condition that compares the current value of the referenced DiagnosticSovdContentElement with a constant value defined by the ValueSpecification. All compareTypes are supported. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, DiagnosticEnvCompareCondition, DiagnosticEnvConditionFormulaPart			
Aggregated by	DiagnosticEnvConditionFormula.part			
Attribute	Type	Mult.	Kind	Note
compareValue	ValueSpecification	0..1	aggr	This attribute represents a fixed compare value taken to evaluate the compare condition. Tags: atp.Status=candidate
contentElement	DiagnosticSovdContentElement	0..1	ref	This reference represents the related diagnostic SOVD content element. Tags: atp.Status=candidate

Table A.169: DiagnosticEnvSovdDataCondition

Class	DiagnosticEvent			
Note	This element is used to configure DiagnosticEvents. Tags: atp.recommendedPackage=DiagnosticEvents			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, Identifiable , Multilanguage Referrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
associated Event Identification	PositiveInteger	0..1	attr	This attribute represents the identification number that is associated with the enclosing DiagnosticEvent and allows to identify it when placed into a snapshot record or extended data record storage. This value can be reported as internal data element in snapshot records or extended data records.
clearEvent Allowed Behavior	DiagnosticClearEvent AllowedBehaviorEnum	0..1	attr	This attribute defines the resulting UDS status byte for the related event, which shall not be cleared according to the ClearEventAllowed callback





Class	DiagnosticEvent			
confirmation Threshold	PositiveInteger	0..1	attr	<p>This attribute defines the number of operation cycles with a failed result before a confirmed DTC is set to 1. The semantic of this attribute is a by "1" increased value compared to the confirmation threshold of the "trip counter" mentioned in ISO 14229-1 in figure D.4. A value of "1" defines the immediate confirmation of the DTC along with the first reported failed. This is also sometimes called "zero trip DTC". A value of "2" defines a DTC confirmation in the operation cycle after the first occurred failed. A value of "2" is typically used in the US for OBD DTC confirmation.</p> <p>Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild</p>
connected Indicator	DiagnosticConnected Indicator	*	aggr	<p>Event specific description of Indicators.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=connectedIndicator.shortName, connected Indicator.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
prestorage FreezeFrame	Boolean	0..1	attr	<p>This attribute describes whether the Prestorage of Freeze Frames is supported by the assigned event or not.</p> <p>true: Prestorage of FreezeFrames is supported false: Prestorage of FreezeFrames is not supported</p>
prestored FreezeFrame StoredInNvm	Boolean	0..1	attr	<p>If the Event uses a prestored freeze-frame (using the operations PrestoreFreezeFrame and ClearPrestored FreezeFrame of the service interface DiagnosticMonitor) this attribute indicates if the Event requires the data to be stored in non-volatile memory. TRUE = Dem shall store the prestored data in non-volatile memory, FALSE = Data can be lost at shutdown (not stored in Nvm)</p>
recoverableIn SameOperation Cycle	Boolean	0..1	attr	<p>If the attribute is set to true then reporting PASSED will reset the indication of a failed test in the current operation cycle. If the attribute is set to false then reporting PASSED will be ignored and not lead to a reset of the indication of a failed test.</p>

Table A.170: DiagnosticEvent

Class	DiagnosticEventInterface			
Note	<p>This meta-class represents the ability to implement a PortInterface to access the properties of diagnostic events on the adaptive platform.</p> <p>Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.</p>			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.171: DiagnosticEventInterface

Class	DiagnosticEventPortMapping			
Note	Defines to which SWC service ports the DiagnosticEvent is mapped. Tags: atp.recommendedPackage=DiagnosticPortMappings			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnosticEvent	DiagnosticEvent	0..1	ref	Reference to the DiagnosticEvent that is assigned to SWC service ports.
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atp.Splitable Tags: atp.Splitkey=process This Attribute is only used by the AUTOSAR Adaptive Platform.
rPortPrototypeInExecutable	RPortPrototype	0..1	iref	This aggregation allows for the usage of the DiagnosticEventPortMapping on the AUTOSAR adaptive platform. Stereotypes: atp.UriDef InstanceRef implemented by: RPortPrototypeInExecutableInstanceRef This Attribute is only used by the AUTOSAR Adaptive Platform.

Table A.172: DiagnosticEventPortMapping

Class	DiagnosticExtendedDataRecord			
Note	Description of an extended data record. Tags: atp.recommendedPackage=DiagnosticExtendedDataRecords			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
customTrigger	String	0..1	attr	This attribute shall be taken to verbally describe the nature of the custom trigger.
element (ordered)	DiagnosticExtendedDataRecordElement	*	aggr	This aggregation represents the collection of elements of the enclosing Extended Data Record.
recordNumber	PositiveInteger	0..1	attr	This attribute specifies a unique identifier for an extended data record.
trigger	DiagnosticRecordTriggerEnum	0..1	attr	This attribute specifies the primary trigger to allocate an event memory entry.
update	Boolean	0..1	attr	This attribute defines when an extended data record is captured. true: This extended data record is captured every time. false: This extended data record is only captured for new event memory entries.

Table A.173: DiagnosticExtendedDataRecord

Class	DiagnosticExtendedDataRecordClientPortMapping			
Note	This mapping class identifies a PortPrototype in the application software that provides data to an external data record. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			





Class	DiagnosticExtendedDataRecordClientPortMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable.
recordElement	DiagnosticExtendedDataRecordElement	0..1	ref	This reference identifies the mapped element of an extended data record.
rPortPrototypeInExecutable	RPortPrototype	0..1	iref	This reference identifies the applicable RPortPrototype from which that data is obtained. The reference has the ability to point into the component hierarchy (under possible consideration of the rootSoftwareComposition). Stereotypes: atpUriDef InstanceRef implemented by: RPortPrototypeInExecutableInstanceRef

Table A.174: DiagnosticExtendedDataRecordClientPortMapping

Class	DiagnosticExtendedDataRecordElement			
Note	This meta-class represents an element of an extended data record. Such an element represents a primitive data object or a fixed-size array of primitive data objects without further internal structure (no structure allowed).			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	DiagnosticExtendedDataRecord.element			
Attribute	Type	Mult.	Kind	Note
numberOfElements	PositiveInteger	0..1	attr	The existence of this attribute turns the data instance into a fixed-size array of data. The attribute determines the size of the array in terms of how many elements the array shall take. The aggregation of SwDataDefProps (especially with respect to SwBaseType) applies specifically to an element of the array (as a representation of all array elements) instead of the entire array itself!
swDataDefProps	SwDataDefProps	0..1	aggr	This aggregation allows for the specification of various properties for the enclosing element.

Table A.175: DiagnosticExtendedDataRecordElement

Class	DiagnosticExtendedDataRecordInterface			
Note	This meta-class represents the ability to implement a focused PortInterface for providing values to an extended data record from within an application. Tags: atp.recommendedPackage=DiagnosticMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , CollectableElement , DiagnosticPortInterface , Identifiable , MultilanguageReferrable , PackageableElement , PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
provide	ClientServerOperation	0..1	aggr	This represents the method to provide the content of an element of a diagnostic extended data record.

Table A.176: DiagnosticExtendedDataRecordInterface

Class	DiagnosticExternalAuthenticationInterface			
Note	This meta-class represents the ability to implement a focused PortInterface for handling the diagnostic client authentication (i.e. convey the Authentication state to the Diagnostic Server instance of the DM) on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.177: DiagnosticExternalAuthenticationInterface

Class	DiagnosticExternalAuthenticationPortMapping			
Note	This mapping class identifies the PortPrototype in the application software that handles the external authentication. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atp.Splitable Tags: atp.Splitkey=process
rPortPrototype InExecutable	RPortPrototype	0..1	iref	This aggregation allows for the usage of the Diagnostic ClientAuthenticationPortMapping on the AUTOSAR adaptive platform. Stereotypes: atp.UriDef InstanceRef implemented by: RPortPrototypeInExecutableInstanceRef

Table A.178: DiagnosticExternalAuthenticationPortMapping

Class	DiagnosticGenericUdsInterface			
Note	This meta-class represents the ability to implement a generic UDS PortInterface for diagnostics on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.179: DiagnosticGenericUdsInterface

Class	DiagnosticIndicatorInterface			
Note	This meta-class represents the ability to implement a PortInterface to implement indicator functionality on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.180: DiagnosticIndicatorInterface

Class	DiagnosticIndicatorPortMapping			
Note	Defines to which SWC service ports the DiagnosticIndicator is mapped. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
indicator	DiagnosticIndicator	0..1	ref	Reference to the DiagnosticIndicator which is mapped to a SWC service port.
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atp.Splitable Tags: atp.Splitkey=process
rPortPrototype InExecutable	RPortPrototype	0..1	iref	This aggregation allows for the usage of the Diagnostic IndicatorMapping on the AUTOSAR adaptive platform. Stereotypes: atp.UriDef InstanceRef implemented by: RPortPrototypeInExecutableInstanceRef

Table A.181: DiagnosticIndicatorPortMapping

Class	DiagnosticMapping (abstract)			
Note	Abstract element for different kinds of diagnostic mappings.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Subclasses	DiagnosticEdrDataProviderMapping, DiagnosticEventToDebounceAlgorithmMapping, DiagnosticEventToEnableConditionGroupMapping, DiagnosticEventToOperationCycleMapping, DiagnosticEventToSecurityEventMapping, DiagnosticEventToTroubleCodeUdsMapping, DiagnosticFimAliasEventGroupMapping, DiagnosticFimAliasEventMapping, DiagnosticInhibitSourceEventMapping, DiagnosticMasterToSlaveEventMapping, DiagnosticProvidedDataMapping , DiagnosticSecureCodingMapping, DiagnosticSovdConfigContentMapping , DiagnosticSwMapping , DiagnosticTroubleCodeUdsToClearConditionGroupMapping , DiagnosticTroubleCodeUdsToTroubleCodeObdMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.182: DiagnosticMapping

Class	DiagnosticMemoryDestinationPortMapping			
Note	Defines to which SWC service ports the DiagnosticMemoryDestination. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
memory Destination	DiagnosticMemory Destination	0..1	ref	Reference to the MemoryDestination which is mapped to a SWC service port.
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atpSplittable Tags: atp.Splitkey=process
rPortPrototype InExecutable	RPortPrototype	0..1	iref	This aggregation allows for the usage of the Diagnostic MemoryDestinationMapping on the AUTOSAR adaptive platform. Stereotypes: atpUriDef InstanceRef implemented by: RPortPrototypeIn ExecutableInstanceRef

Table A.183: DiagnosticMemoryDestinationPortMapping

Class	DiagnosticMonitorInterface			
Note	This meta-class represents the ability to implement a monitor-focused PortInterface for diagnostics on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.184: DiagnosticMonitorInterface

Class	DiagnosticMonitorPortMapping			
Note	Defines to which SWC service port the Diagnostic Monitor is mapped. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnosticEvent	DiagnosticEvent	0..1	ref	Reference to the DiagnosticEvent that is assigned to SWC service ports.
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atpSplittable Tags: atp.Splitkey=process





Class	DiagnosticMonitorPortMapping			
rPortPrototype InExecutable	RPortPrototype	0..1	iref	This aggregation allows for the usage of the Diagnostic MonitorPortMapping on the AUTOSAR adaptive platform. Stereotypes: atpUriDef InstanceRef implemented by: RPortPrototypeIn ExecutableInstanceRef

Table A.185: DiagnosticMonitorPortMapping

Class	DiagnosticMultipleConditionInterface			
Note	This meta-class represents the ability to implement a condition-focused PortInterface for diagnostics on the adaptive platform. In contrast to the DiagnosticConditionInterface, the DiagnosticMultipleCondition Interface allows for handling more than one condition in the scope of a single PortPrototype. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticMultipleResourceInterface, DiagnosticPortInterface, <i>Identifiable</i> , MultilanguageReferrable, PackageableElement, <i>PortInterface</i> , <i>Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.186: DiagnosticMultipleConditionInterface

Class	DiagnosticMultipleConditionPortMapping			
Note	Defines to which SWC service port that can handle a collection of diagnostic conditions the specific condition is mapped. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, <i>DiagnosticMapping</i> , DiagnosticMultipleResourcePortMapping, <i>DiagnosticSwMapping</i> , <i>Identifiable</i> , MultilanguageReferrable, PackageableElement, <i>Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnostic Condition	DiagnosticCondition	0..1	ref	Reference to the DiagnosticCondition which is mapped to a SWC service port.
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atpSplittable Tags: atp.Splitkey=process
rPortPrototype InExecutable	RPortPrototype	0..1	iref	This aggregation allows for the usage of the Diagnostic ConditionPortMapping on the AUTOSAR adaptive platform. Stereotypes: atpUriDef InstanceRef implemented by: RPortPrototypeIn ExecutableInstanceRef

Table A.187: DiagnosticMultipleConditionPortMapping

Class	DiagnosticMultipleEventInterface			
Note	<p>This meta-class represents the ability to implement a event-focused PortInterface for diagnostics on the adaptive platform. In contrast to the DiagnosticEventInterface, the DiagnosticMultipleMonitorInterface allows for handling more than one event in the scope of a single PortPrototype.</p> <p>Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.</p>			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticMultipleResourceInterface, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.188: DiagnosticMultipleEventInterface

Class	DiagnosticMultipleEventPortMapping			
Note	<p>Defines to which SWC service port that can handle a collection of event status the specific event is mapped.</p> <p>Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.</p>			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticMultipleResourcePortMapping, DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnosticEvent	DiagnosticEvent	0..1	ref	Reference to the DiagnosticEvent that is assigned to a SWC service port.
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atp.Splitable Tags: atp.Splitkey=process
rPortPrototype InExecutable	RPortPrototype	0..1	iref	This aggregation allows for the usage of the Diagnostic MonitorMultipleEventPortMapping on the AUTOSAR adaptive platform. Stereotypes: atp.UriDef InstanceRef implemented by: RPortPrototypeInExecutableInstanceRef

Table A.189: DiagnosticMultipleEventPortMapping

Class	DiagnosticMultipleMonitorInterface			
Note	<p>This meta-class represents the ability to implement a monitor-focused PortInterface for diagnostics on the adaptive platform. In contrast to the DiagnosticMonitorInterface, the DiagnosticMultipleMonitorInterface allows for handling more than one event in the scope of a single PortPrototype.</p> <p>Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.</p>			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticMultipleResourceInterface, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.190: DiagnosticMultipleMonitorInterface

Class	DiagnosticMultipleMonitorPortMapping			
Note	Defines to which SWC service port that can handle a collection of monitors the specific event is mapped Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticMultipleResourcePortMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnosticEvent	DiagnosticEvent	0..1	ref	Reference to the DiagnosticEvent that is assigned to a SWC service port.
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atp.Splitable Tags: atp.Splitkey=process
rPortPrototypeInExecutable	RPortPrototype	0..1	iref	This aggregation allows for the usage of the Diagnostic MonitorMultipleMonitorPortMapping on the AUTOSAR adaptive platform. Stereotypes: atp.UriDef InstanceRef implemented by: RPortPrototypeInExecutableInstanceRef

Table A.191: DiagnosticMultipleMonitorPortMapping

Class	DiagnosticOperationCycle			
Note	Definition of an operation cycle that is the base of the event qualifying and for Dem scheduling. Tags: atp.recommendedPackage=DiagnosticOperationCycles			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
type	DiagnosticOperationCycleTypeEnum	0..1	attr	Operation cycles types for the Dem.

Table A.192: DiagnosticOperationCycle

Class	DiagnosticOperationCycleInterface			
Note	This meta-class represents the ability to implement a PortInterface to process requests for operation cycles on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface , Identifiable , MultilanguageReferrable , PackageableElement , PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.193: DiagnosticOperationCycleInterface

Class	DiagnosticOperationCyclePortMapping			
Note	Defines to which SWC service ports the DiagnosticOperationCycle is mapped. Tags: atp.recommendedPackage=DiagnosticPortMappings			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
operationCycle	DiagnosticOperation Cycle	0..1	ref	Reference to the DiagnosticOperationCycle that is assigned to SWC service ports.
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atp.Splitable Tags: atp.Splitkey=process This Attribute is only used by the AUTOSAR Adaptive Platform.
rPortPrototypeInExecutable	RPortPrototype	0..1	iref	This aggregation allows for the usage of the DiagnosticOperationCyclePortMapping on the AUTOSAR adaptive platform. Stereotypes: atp.UriDef InstanceRef implemented by: RPortPrototypeInExecutableInstanceRef This Attribute is only used by the AUTOSAR Adaptive Platform.

Table A.194: DiagnosticOperationCyclePortMapping

Class	DiagnosticProvidedDataMapping			
Note	This represents the ability to define the nature of a data access for a DiagnosticDataElement based on a data provider that cannot be modeled explicitly. Tags: atp.recommendedPackage=DiagnosticMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataElement	DiagnosticDataElement	0..1	ref	This represents the DiagnosticDataElement to which the internal data is mapped, further qualified by the DiagnosticProvidedDataMapping.dataProvider.
dataProvider	NameToken	0..1	attr	This represents the ability to further specify the data provider.

Table A.195: DiagnosticProvidedDataMapping

Class	DiagnosticRoutineInterface			
Note	This meta-class represents the ability to implement a routine-focused PortInterface for diagnostics on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticAbstractRoutineInterface, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	DiagnosticRoutineInterface			
requestResult	ClientServerOperation	0..1	aggr	This represents the request result method of the diagnostic routine.
start	ClientServerOperation	0..1	aggr	This represents the start method of the diagnostic routine.
stop	ClientServerOperation	0..1	aggr	This represents the stop method of the diagnostic routine.

Table A.196: DiagnosticRoutineInterface

Class	DiagnosticSecurityLevel			
Note	This meta-class represents the ability to define a security level considered for diagnostic purposes. Tags: atp.recommendedPackage=DiagnosticSecurityLevels			
Base	<i>ARElement, ARObject, CollectableElement, DiagnosticCommonElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
accessDataRecordSize	PositiveInteger	0..1	attr	This represents the size of the AccessDataRecord used in GetSeed. Unit:byte.
keySize	PositiveInteger	0..1	attr	This represents the size of the security key. Unit: byte.
numFailedSecurityAccess	PositiveInteger	0..1	attr	This represents the number of failed security accesses after which the delay time is activated.
securityDelayTime	TimeValue	0..1	attr	This represents the delay time after a failed security access. Unit: second.
seedSize	PositiveInteger	0..1	attr	This represents the size of the security seed. Unit: byte.

Table A.197: DiagnosticSecurityLevel

Class	DiagnosticSecurityLevelInterface			
Note	This meta-class represents the ability to implement a security-level-focused PortInterface for diagnostics on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, Identifiable, MultilanguageReferrable, PackageableElement, PortInterface, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.198: DiagnosticSecurityLevelInterface

Class	DiagnosticSecurityLevelPortMapping			
Note	Defines to which SWC service ports the DiagnosticSecurityLevel is mapped. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping, DiagnosticSwMapping, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	DiagnosticSecurityLevelPortMapping			
pPortPrototype InExecutable	PPortPrototype	0..1	iref	This aggregation allows for the usage of the Diagnostic SecurityLevelMapping on the AUTOSAR adaptive platform. Stereotypes: atpUriDef InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atpSplitable Tags: atp.Splitkey=process
securityLevel	DiagnosticSecurityLevel	0..1	ref	Reference to the SecurityLevel which is mapped to a SWC service port.

Table A.199: DiagnosticSecurityLevelPortMapping

Class	DiagnosticServiceGenericMapping			
Note	This meta-class represents the ability to implement a generic generic mapping for select diagnostics services on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnostic ServiceInstance	DiagnosticService Instance	0..1	ref	Reference to the ServiceInstance mapped to a SWC service port.
pPortPrototype InExecutable	PPortPrototype	0..1	iref	This aggregation allows for the usage of the Diagnostic ServiceGenericMapping on the AUTOSAR adaptive platform. Stereotypes: atpUriDef InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atpSplitable Tags: atp.Splitkey=process

Table A.200: DiagnosticServiceGenericMapping

Class	DiagnosticServiceValidationConfiguration			
Note	This meta-class has the ability to configure the order of manufacturer/supplier-checks. Tags: atp.recommendedPackage=DiagnosticValueConfigurations This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	SoftwareClusterDiagnosticDeploymentProps.validationConfiguration			
Attribute	Type	Mult.	Kind	Note
manufacturer ValidationOrder (ordered)	DiagnosticService ValidationMapping	*	ref	This reference defines the order in which validations created by manufacturer are executed.
sovdValidation Order (ordered)	DiagnosticSovdService ValidationPortMapping	*	ref	This reference defines the order in which validations of SOVD requests are executed.





Class	DiagnosticServiceValidationConfiguration			
supplier ValidationOrder (ordered)	DiagnosticServiceValidationMapping	*	ref	This reference defines the order in which validations created by supplier are executed.

Table A.201: DiagnosticServiceValidationConfiguration

Class	DiagnosticServiceValidationInterface			
Note	This meta-class represents the ability to implement a PortInterface to process requests for service validation on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObjct, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.202: DiagnosticServiceValidationInterface

Class	DiagnosticServiceValidationMapping			
Note	This meta-class provides the ability to specify manufacturer/supplier checks to be executed before diagnostic services can be processed. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObjct, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
pPortPrototype InExecutable	PPortPrototype	0..1	iref	This mapping identifies a PortPrototype typed by a DiagnosticValidationInterface in which a manufacturer/supplier-specific check is executed. Stereotypes: atpUriDef InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atpSplitable Tags: atp.Splitkey=process

Table A.203: DiagnosticServiceValidationMapping

Class	DiagnosticSovdAccessArgument			
Note	This meta-class represents a single data element used in the context of reading or writing data using SOVD This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	DiagnosticSovdAccessOperation.argument			
Attribute	Type	Mult.	Kind	Note
contentObject	VariableDataPrototype	0..1	aggr	This aggregation represents the ability to specify further information about the argument.





Class					DiagnosticSovdAccessArgument
direction	ArgumentDirectionEnum	0..1	attr	This attribute specifies the direction of the argument.	
isOptional	Boolean	0..1	attr	This attribute defines whether the enclosing DiagnosticSovdAccessArgument is considered optional in the context of reading or writing data using SOVD.	

Table A.204: DiagnosticSovdAccessArgument

Class					DiagnosticSovdAccessOperation
Note		This meta-class represents a directional access to data for SOVD. This Class is only used by the AUTOSAR Adaptive Platform.			
Base		<i>ARObject</i>			
Aggregated by		DiagnosticSovdContentElementInterface.read , DiagnosticSovdContentElementInterface.write , DiagnosticSovdOperationInterface.readStatus , DiagnosticSovdOperationInterface.start , DiagnosticSovdOperationInterface.terminate			
Attribute		Type	Mult.	Kind	Note
argument	DiagnosticSovdAccessArgument	*	aggr	This role represents a specific data element used for reading or writing with SOVD.	

Table A.205: DiagnosticSovdAccessOperation

Class					DiagnosticSovdArrayContentElement
Note		This meta-class represents the ability to define a DiagnosticSovdCompositeContentElement with array semantics. This Class is only used by the AUTOSAR Adaptive Platform.			
Base		<i>ARObject</i> , <i>DiagnosticAbstractSovdContent</i> , <i>DiagnosticSovdCompositeContentElement</i> , DiagnosticSovdContentElement , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by		DiagnosticSovdArrayContentElement.element , DiagnosticSovdContent.element , DiagnosticSovdRecordContentElement.element			
Attribute		Type	Mult.	Kind	Note
element	DiagnosticSovdContentElement	0..1	aggr	This aggregation represents the specification of the nature of an element of an enclosing DiagnosticSovdArrayContentElement. It is only necessary to aggregate one element because the array semantics requires that all elements of the array have the same nature. Tags: xml.sequenceOffset=100	
maxNumberOfElements	PositiveInteger	0..1	attr	This attribute specifies the maximum number of elements expected in the array. Tags: xml.sequenceOffset=20	
minNumberOfElements	PositiveInteger	0..1	attr	This attribute specifies the minimum number of elements expected in the array. Tags: xml.sequenceOffset=10	

Table A.206: DiagnosticSovdArrayContentElement

Class					DiagnosticSovdAuthorizationInterface
Note		This meta-class is used to type a PPortPrototype for implementing the SOVD authorization. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base		<i>ARElement</i> , <i>ARObject</i> , <i>AtpBlueprint</i> , <i>AtpBlueprintable</i> , <i>AtpClassifier</i> , <i>AtpType</i> , <i>CollectableElement</i> , <i>DiagnosticPortInterface</i> , <i>DiagnosticSovdPortInterface</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>PortInterface</i> , <i>Referrable</i>			





Class	DiagnosticSovdAuthorizationInterface			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.207: DiagnosticSovdAuthorizationInterface

Class	DiagnosticSovdAuthorizationPortMapping			
Note	This mapping class identifies the PortPrototype in the application software that handles the SOVD authorization. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
pPortPrototype InExecutable	PPortPrototype	0..1	iref	This aggregation allows for the usage of the Diagnostic SovdAuthorizationPortMapping on the AUTOSAR adaptive platform. Stereotypes: atp.UriDef InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atp.Splitable Tags: atp.Splitkey=process

Table A.208: DiagnosticSovdAuthorizationPortMapping

Class	DiagnosticSovdBulkData			
Note	This meta-class represents a "Bulk Data" SOVD service instance. Tags: atp.recommendedPackage=DiagnosticSovdServiceInstances This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticSovdServiceInstance, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
bulkData Category	String	0..1	attr	This attribute provides a categorization of the bulk data.

Table A.209: DiagnosticSovdBulkData

Class	DiagnosticSovdBulkDataInterface			
Note	This meta-class is used to type a PPortPrototype for implementing the SOVD bulk data transmission. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, DiagnosticSovdPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.210: DiagnosticSovdBulkDataInterface

Class	DiagnosticSovdBulkDataPortMapping			
Note	This mapping associates a PPortPrototype typed by a DiagnosticSovdBulkDataInterface to the corresponding SOVD service instance that is modeled as DiagnosticSovdBulkData. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
pPortPrototype InExecutable	PPortPrototype	0..1	iref	This aggregation allows for the usage of the DiagnosticSovdBulkDataPortMapping on the AUTOSAR adaptive platform. Stereotypes: atp.UriDef InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atp.Splitable Tags: atp.Splitkey=process
serviceInstance	DiagnosticSovdBulkData	0..1	ref	This reference identifies the applicable diagnostic SOVD service instance.

Table A.211: DiagnosticSovdBulkDataPortMapping

Class	DiagnosticSovdConfigContentMapping			
Note	This mapping associates an SOVD configuration parameter service instance to an SOVD content. Tags: atp.recommendedPackage=DiagnosticMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
content	DiagnosticSovdContent	0..1	ref	This reference identifies the applicable SOVD content.
serviceInstance	DiagnosticSovdConfigurationParameter	0..1	ref	This reference identifies the applicable service instance.

Table A.212: DiagnosticSovdConfigContentMapping

Class	DiagnosticSovdConfiguration (abstract)			
Note	This abstract meta-class represents a "configuration" SOVD service instance. The concrete nature of the service instance is defined by sub-classes. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticSovdServiceInstance , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Subclasses	DiagnosticSovdConfigurationBulkData, DiagnosticSovdConfigurationParameter			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.213: DiagnosticSovdConfiguration

Class	DiagnosticSovdConfigurationInterface			
Note	This meta-class is used to configure a PortInterface for the exchange of configuration content. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, DiagnosticSovdPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.214: DiagnosticSovdConfigurationInterface

Class	DiagnosticSovdConfigurationParameter			
Note	This meta-class represents a "Configuration Parameter" SOVD service instance. Tags: atp.recommendedPackage=DiagnosticSovdServiceInstances This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticSovdConfiguration , DiagnosticSovdServiceInstance , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.215: DiagnosticSovdConfigurationParameter

Class	DiagnosticSovdConfigurationPortMapping			
Note	This mapping associates a PPortPrototype typed by a DiagnosticSovdConfigurationInterface to the corresponding SOVD service instance that is modeled as DiagnosticSovdConfiguration. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
pPortPrototype InExecutable	PPortPrototype	0..1	iref	This aggregation allows for the usage of the DiagnosticSovdConfigurationPortMapping on the AUTOSAR adaptive platform. Stereotypes: atp.UriDef InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atp.Splitable Tags: atp.Splitkey=process
serviceInstance	DiagnosticSovdConfiguration	0..1	ref	This reference identifies the applicable diagnostic SOVD service instance.

Table A.216: DiagnosticSovdConfigurationPortMapping

Class	DiagnosticSovdContent			
Note	This meta-class represents a data packet exchanged between am SOVD Tester and an SOVD server. The semantics is very close to the semantics of a UDS DID, with some extensions. Tags: atp.recommendedPackage=DiagnosticSovdContents This Class is only used by the AUTOSAR Adaptive Platform.			





Class	DiagnosticSovdContent			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , <i>DiagnosticAbstractSovdContent</i> , <i>DiagnosticCommonElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
element	DiagnosticSovdContentElement	*	aggr	This aggregation identifies the collection of elements of the enclosing DiagnosticSovdContent. Stereotypes: atpSplitable Tags: atp.Splitkey=element.shortName

Table A.217: DiagnosticSovdContent

Class	DiagnosticSovdContentElement (abstract)			
Note	This meta-class represents an element of a DiagnosticSovdContent. When compared to the modeling of a UDS DID, this class would correspond to a mixture of DiagnosticParameter and DiagnosticDataElement. The concrete semantics of a DiagnosticSovdContentElement is defined by its subclasses. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , <i>DiagnosticAbstractSovdContent</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Subclasses	<i>DiagnosticSovdCompositeContentElement</i> , <i>DiagnosticSovdPrimitiveContentElement</i>			
Aggregated by	DiagnosticSovdArrayContentElement.element , DiagnosticSovdContent.element , <i>DiagnosticSovdRecordContentElement.element</i>			
Attribute	Type	Mult.	Kind	Note
isOptional	Boolean	0..1	attr	This attribute defines whether the enclosing DiagnosticSovdContentElement is considered optional. Note that array elements cannot be declared optional.

Table A.218: DiagnosticSovdContentElement

Class	DiagnosticSovdContentElementInterface			
Note	This meta-class is used to type a PPortPrototype for reading and/or writing a single data element as part of a bigger data packet using SOVD. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>AtpBlueprint</i> , <i>AtpBlueprintable</i> , <i>AtpClassifier</i> , <i>AtpType</i> , <i>CollectableElement</i> , <i>DiagnosticAbstractSovdContentInterface</i> , <i>DiagnosticPortInterface</i> , <i>DiagnosticSovdPortInterface</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>PortInterface</i> , <i>Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
read	DiagnosticSovdAccessOperation	0..1	aggr	This role represents the read access to content elements in the context of the enclosing DiagnosticSovdContentElementInterface.

Table A.219: DiagnosticSovdContentElementInterface

Class	DiagnosticSovdContentInterface			
Note	This meta-class is used to type a PPortPrototype for reading and/or writing data using SOVD. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>AtpBlueprint</i> , <i>AtpBlueprintable</i> , <i>AtpClassifier</i> , <i>AtpType</i> , <i>CollectableElement</i> , <i>DiagnosticAbstractSovdContentInterface</i> , <i>DiagnosticPortInterface</i> , <i>DiagnosticSovdPortInterface</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>PortInterface</i> , <i>Referrable</i>			





Class	DiagnosticSovdContentInterface			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
read	DiagnosticSovdAccessOperation	0..1	aggr	This role represents the read access to "SOVD data" in the context of the enclosing DiagnosticSovdContentInterface.
write	DiagnosticSovdAccessOperation	0..1	aggr	This role represents the write access to "SOVD data" in the context of the enclosing DiagnosticSovdContentInterface.

Table A.220: DiagnosticSovdContentInterface

Class	DiagnosticSovdContentPortMapping			
Note	This mapping associates a PPortPrototype typed by either a DiagnosticSovdContentInterface or a DiagnosticSovdContentElementInterface to the corresponding SOVD content that is modeled as DiagnosticAbstractSovdContent. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping, DiagnosticSwMapping, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
content	DiagnosticAbstractSovdContent	0..1	ref	This reference identifies the applicable content for the mapping.
pPortPrototypeInExecutable	PPortPrototype	0..1	iref	This aggregation allows for the usage of the DiagnosticSovdContentPortMapping on the AUTOSAR adaptive platform. Stereotypes: atp.UriDef InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable.

Table A.221: DiagnosticSovdContentPortMapping

Class	DiagnosticSovdData			
Note	This meta-class represents a "Data" SOVD service instance. Tags: atp.recommendedPackage=DiagnosticSovdServiceInstances This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticSovdServiceInstance, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
sovdDataCategory	DiagnosticSovdDataCategory	0..1	ref	This reference identifies the SOVD category that applies to the enclosing SOVD data. Tags: atp.Status=candidate
sovdGroup	DiagnosticSovdGroup	*	ref	This reference identifies the collection of SOVD groups in which the enclosing SOVD data is a "member". Tags: atp.Status=candidate
target	DiagnosticSovdContent	0..1	ref	This reference identifies the content that the DiagnosticSovdData service instance is responsible for.

Table A.222: DiagnosticSovdData

Class	DiagnosticSovdDataCategory			
Note	This meta-class represents the primary filter criterion for the access to SOVD data. Tags: atp.Status=candidate atp.recommendedPackage=DiagnosticDataCategorys This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
group	DiagnosticSovdGroup	*	ref	This reference identifies the SOVD groups in which the SOVD category is a "member". Tags: atp.Status=candidate

Table A.223: DiagnosticSovdDataCategory

Class	DiagnosticSovdFaultMemoryAccess			
Note	This meta-class represents the ability to access (read/get and delete) the fault memory. Tags: atp.recommendedPackage=DiagnosticSovdServiceInstances This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticSovdServiceInstance, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.224: DiagnosticSovdFaultMemoryAccess

Class	DiagnosticSovdGroup			
Note	This meta-class represents the secondary filter criterion for the access to SOVD data Tags: atp.Status=candidate atp.recommendedPackage=DiagnosticSovdGroups This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.225: DiagnosticSovdGroup

Class	DiagnosticSovdLog			
Note	This meta-class represents a "Log" SOVD service instance. Tags: atp.recommendedPackage=DiagnosticSovdServiceInstances This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticSovdServiceInstance, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.226: DiagnosticSovdLog

Class	DiagnosticSovdMethod			
Note	A DiagnosticSovdMethod represents a re-usable complex operation (that consists of primitive operations) in the context of the communication of an SOVD server. Tags: atp.recommendedPackage=DiagnosticSovdMethods This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
delete	DiagnosticSovdMethodPrimitive	*	aggr	This represents the "delete" method primitive.
get	DiagnosticSovdMethodPrimitive	*	aggr	This represents the "get" method primitive.
post	DiagnosticSovdMethodPrimitive	*	aggr	This represents the "post" method primitive.
put	DiagnosticSovdMethodPrimitive	*	aggr	This represents the "delete" method primitive.

Table A.227: DiagnosticSovdMethod

Class	DiagnosticSovdMethodPrimitive			
Note	This meta-class represents a primitive operation inside a DiagnosticSovdMethod. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	DiagnosticSovdMethod.delete , DiagnosticSovdMethod.get , DiagnosticSovdMethod.post , DiagnosticSovdMethod.put			
Attribute	Type	Mult.	Kind	Note
access Permission	DiagnosticAccess Permission	0..1	ref	This reference identifies the applicable access permission.

Table A.228: DiagnosticSovdMethodPrimitive

Class	DiagnosticSovdOperation			
Note	This meta-class represents a "Operation" SOVD service instance. Tags: atp.recommendedPackage=DiagnosticSovdServiceInstances This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticSovdServiceInstance , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
proximityProof Required	Boolean	0..1	attr	If true, the execution of the operation requires proof of co-location, and the offline capability description includes the attribute x-sovd-proximity-proof-required in the Path Item object. An SOVD client can use this information to filter operations in advance if a co-location proof cannot be provided. Tags: atp.Status=candidate
readStatus	DiagnosticSovdOperationGetStatus	1	aggr	This aggregation identifies the "read status" operation primitive.
start	DiagnosticSovdOperationStart	0..1	aggr	This aggregation identifies the "start" operation primitive.
terminate	DiagnosticSovdOperationStop	0..1	aggr	This aggregation identifies the "terminate" operation primitive.

Table A.229: DiagnosticSovdOperation

Class	DiagnosticSovdOperationInterface			
Note	This meta-class is used to type a PPortPrototype for implementing the SOVD operation. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, DiagnosticSovdPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
readStatus	DiagnosticSovdAccessOperation	0..1	aggr	This role represents the "readStatus" primitive within an "SOVD operation" in the context of the enclosing DiagnosticSovdOperationInterface. Tags: xml.sequenceOffset=120
start	DiagnosticSovdAccessOperation	0..1	aggr	This role represents the "start" primitive within an "SOVD operation" in the context of the enclosing DiagnosticSovdOperationInterface. Tags: xml.sequenceOffset=100
terminate	DiagnosticSovdAccessOperation	0..1	aggr	This role represents the "terminate" primitive within an "SOVD operation" in the context of the enclosing DiagnosticSovdOperationInterface. Tags: xml.sequenceOffset=110

Table A.230: DiagnosticSovdOperationInterface

Class	DiagnosticSovdOperationPortMapping			
Note	This mapping associates a PPortPrototype typed by a DiagnosticSovdOperationInterface to the corresponding SOVD operation. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
pPortPrototypeInExecutable	PPortPrototype	0..1	iref	This aggregation allows for the usage of the DiagnosticSovdOperationPortMapping on the AUTOSAR adaptive platform. Stereotypes: atp.UriDef InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable.
sovOperation	DiagnosticSovdOperation	0..1	ref	This reference identifies the applicable DiagnosticSovdOperation.

Table A.231: DiagnosticSovdOperationPortMapping

Class	DiagnosticSovdPrimitiveContentElement			
Note	This meta-class represents a primitive leaf element of a DiagnosticSovdContent. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, DiagnosticAbstractSovdContent, DiagnosticSovdContentElement , Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	DiagnosticSovdArrayContentElement.element , DiagnosticSovdContent.element , DiagnosticSovdRecordContentElement.element			
Attribute	Type	Mult.	Kind	Note





Class	DiagnosticSovdPrimitiveContentElement			
swDataDef Props	SwDataDefProps	0..1	aggr	This aggregation represents the applicable data definition properties. Stereotypes: atpSplittable Tags: atp.Splitkey=swDataDefProps xml.sequenceOffset=100
type	DiagnosticSovdPrimitiveContentTypeEnum	0..1	attr	This attribute denotes the type of the primitive content element. Tags: xml.sequenceOffset=10

Table A.232: DiagnosticSovdPrimitiveContentElement

Class	DiagnosticSovdProximityChallengeInterface			
Note	This meta-class is used to type a PPortPrototype for implementing the SOVD proximity challenge. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, DiagnosticSovdPortInterface, Identifiable, MultilanguageReferrable, PackageableElement, PortInterface, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.233: DiagnosticSovdProximityChallengeInterface

Class	DiagnosticSovdProximityChallengePortMapping			
Note	This mapping class identifies the PortPrototype in the application software that handles the SOVD proximity challenge. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping, DiagnosticSwMapping, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
pPortPrototype InExecutable	PPortPrototype	0..1	iref	This aggregation allows for the usage of the Diagnostic SovdProximityChallengePortMapping on the AUTOSAR adaptive platform. Stereotypes: atpUriDef InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atpSplittable Tags: atp.Splitkey=process

Table A.234: DiagnosticSovdProximityChallengePortMapping

Class	DiagnosticSovdServiceValidationInterface			
Note	This meta-class is used to type a PPortPrototype for implementing the SOVD service validation. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			





Class	DiagnosticSovdServiceValidationInterface			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, DiagnosticSovdPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.235: DiagnosticSovdServiceValidationInterface

Class	DiagnosticSovdServiceValidationPortMapping			
Note	This mapping class identifies the PortPrototype in the application software that handles the SOVD service validation. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
pPortPrototype InExecutable	PPortPrototype	0..1	iref	This aggregation allows for the usage of the Diagnostic SovdValidationPortMapping on the AUTOSAR adaptive platform. Stereotypes: atpUriDef InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable.

Table A.236: DiagnosticSovdServiceValidationPortMapping

Class	DiagnosticSovdUpdate			
Note	This meta-class represents a "Update" SOVD service instance. Tags: atp.recommendedPackage=DiagnosticSovdServiceInstances This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticSovdServiceInstance, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.237: DiagnosticSovdUpdate

Class	DiagnosticSovdUpdateInterface			
Note	This meta-class is used to type a PPortPrototype for implementing the SOVD update procedure. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface, DiagnosticSovdPortInterface, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.238: DiagnosticSovdUpdateInterface

Class	DiagnosticSovdUpdatePortMapping			
Note	This mapping associates a PPortPrototype typed by an DiagnosticSovdUpdateInterface with the corresponding SOVD service instance that is modeled as a DiagnosticSovdUpdate. Tags: atp.recommendedPackage=DiagnosticPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
pPortPrototype InExecutable	PPortPrototype	0..1	iref	This aggregation allows for the usage of the DiagnosticSovdUpdatePortMapping on the AUTOSAR adaptive platform. Stereotypes: atp.UriDef InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	ProcessDesign	0..1	ref	Reference to the representation of a Process that is required because the mapping could be different for different Processes referring to a specific Executable. Stereotypes: atp.Splitable Tags: atp.Splitkey=process
serviceInstance	DiagnosticSovdUpdate	0..1	ref	This reference identifies the applicable diagnostic SOVD service instance. Tags: atp.Status=candidate

Table A.239: DiagnosticSovdUpdatePortMapping

Class	DiagnosticSwMapping (abstract)			
Note	This represents the ability to define a mapping between a diagnostic information (at this point there is no way to become more specific about the semantics) to a software-component.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Subclasses	AbstractDolpPortMapping , DiagnosticAuthenticationPortMapping , DiagnosticClearConditionPortMapping , DiagnosticDataPortMapping , DiagnosticEdrSenderPortMapping , DiagnosticEdrServerPortMapping , DiagnosticEnableConditionPortMapping , DiagnosticEventPortMapping , DiagnosticExtendedDataRecordClientPortMapping , DiagnosticExternalAuthenticationPortMapping , DiagnosticFimFunctionMapping , DiagnosticIndicatorPortMapping , DiagnosticMemoryDestinationPortMapping , DiagnosticMonitorPortMapping , DiagnosticMultipleResourcePortMapping , DiagnosticOperationCyclePortMapping , DiagnosticSecurityLevelPortMapping , DiagnosticServiceDataMapping , DiagnosticServiceGenericMapping , DiagnosticServiceSwMapping , DiagnosticServiceValidationMapping , DiagnosticSovdAuthorizationPortMapping , DiagnosticSovdBulkDataPortMapping , DiagnosticSovdConfigurationPortMapping , DiagnosticSovdContentPortMapping , DiagnosticSovdOperationPortMapping , DiagnosticSovdProximityChallengePortMapping , DiagnosticSovdServiceValidationPortMapping , DiagnosticSovdUpdatePortMapping , ISignalPortToDiagnosticEventMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.240: DiagnosticSwMapping

Class	DiagnosticTransmitCertificateInterface			
Note	This meta-class represents the ability to implement the transmit-certificate functionality on application software level. Tags: atp.recommendedPackage=DiagnosticPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DiagnosticPortInterface , Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			





Class	DiagnosticTransmitCertificateInterface			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.241: DiagnosticTransmitCertificateInterface

Class	DiagnosticTroubleCodeUds			
Note	This element is used to describe diagnostic trouble codes (DTCs). Tags: atp.recommendedPackage=DiagnosticTroubleCodes			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticTroubleCode, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
considerPtoStatus	Boolean	0..1	attr	This attribute describes the affection of the event by the Dem PTO handling. true: the event is affected by the Dem PTO handling. false: the event is not affected by the Dem PTO handling. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild
eventReadinessGroup	EventObdReadinessGroup	0..1	aggr	This attribute specifies the Event OBD Readiness group for PID \$01 and PID \$41 computation. This attribute is only applicable for emission-related ECUs. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=eventReadinessGroup.eventObdReadinessGroup, eventReadinessGroup.variationPoint.shortLabel vh.latestBindingTime=postBuild
functionalUnit	PositiveInteger	0..1	attr	This attribute specifies a 1-byte value which identifies the corresponding basic vehicle / system function which reports the DTC. This parameter is necessary for the report of severity information. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild
obdDtcValue3Byte	PositiveInteger	0..1	attr	3 Byte OBD DTC value based on the definition from SAE J2012. The existence of this attribute is only required if separated UDS and OBD DTC values are used for SAE J1979-2. If this attribute does not exist, then UDS DTC values are used with J1979-2. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild
severity	DiagnosticUdsSeverityEnum	0..1	attr	DTC severity according to ISO 14229-1. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild
troubleCodeProps	DiagnosticTroubleCodeProps	0..1	ref	Defined properties associated with the DemDTC. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=troubleCodeProps.diagnosticTroubleCodeProps, troubleCodeProps.variationPoint.shortLabel vh.latestBindingTime=postBuild
udsDtcValue	PositiveInteger	0..1	attr	Unique Diagnostic Trouble Code value for UDS. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild





Class	DiagnosticTroubleCodeUds			
wwhObdDtc Class	DiagnosticWwhObdDtc ClassEnum	0..1	attr	This attribute is used to identify (if applicable) the corresponding severity class of an WWH-OB DTC. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild

Table A.242: DiagnosticTroubleCodeUds

Class	DiagnosticTroubleCodeUdsToClearConditionGroupMapping			
Note	This meta-class provides the ability to map a DiagnosticClearConditionGroup to a collection of Diagnostic TroubleCodeUds. Tags: atp.recommendedPackage=DiagnosticMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping , Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
clearCondition Group	DiagnosticClear ConditionGroup	0..1	ref	This reference identifies the applicable DiagnosticClear ConditionGroup.
troubleCodeUds	DiagnosticTroubleCode Uds	0..1	ref	This reference identifies the DiagnosticTroubleCodeUds that are relevant for the mapping.

Table A.243: DiagnosticTroubleCodeUdsToClearConditionGroupMapping

Class	DltApplication			
Note	This meta-class represents the application from which the log and trace message originates.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	DltEcu.application			
Attribute	Type	Mult.	Kind	Note
application Description	String	0..1	attr	This attribute can be used to describe the applicationId that is used in the log and trace message in more detail.
applicationId	String	0..1	attr	This attribute identifies the SW-C/BSW module in the log and trace message.
context	DltContext	*	ref	Definition of ContextIds for the Application. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=context.dltContext, context.variation Point.shortLabel vh.latestBindingTime=systemDesignTime

Table A.244: DltApplication

Class	DltApplicationToProcessMapping			
Note	This element assigns a DltApplicationId to a Process. Tags: atp.recommendedPackage=DltApplicationToProcessMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dltApplication	DltApplication	0..1	ref	Reference to a DltApplication that defines the application Id
process	Process	0..1	ref	Reference to the process that is assigned to a Log And Trace applicationId.

Table A.245: DltApplicationToProcessMapping

Class	DltContext			
Note	This meta-class represents the Context that groups Log and Trace Messages that are generated by an application. Tags: atp.recommendedPackage=DltContexts			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
contextDescription	String	0..1	attr	This attribute can be used to describe the contextId that is used in the log and trace message in more detail.
contextId	String	0..1	attr	This attribute is used to group log and trace messages produced by an application to distinguish functionality.
dltMessage	DltMessage	*	ref	Group of Log and Trace Messages assigned to the Dlt Context Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dltMessage.dltMessage, dltMessage.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime

Table A.246: DltContext

Class	DltEcu			
Note	This element represents an Ecu or Machine that produces logging and tracing information. Tags: atp.recommendedPackage=DltEcus			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
application	DltApplication	*	aggr	Application on DltEcu that provides log or trace data. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=application.shortName, application.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime
eculd	String	0..1	attr	This attribute defines the name of the ECU for use within the Dlt protocol.

Table A.247: DltEcu

Class	DltLogSink			
Note	The meta-class defines the output sink for DltLogMessages Tags: atp.recommendedPackage=DltLogSinks This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
bufferOutput	Boolean	0..1	attr	This attribute defines whether a buffer is used in case that the output sink is the console.
defaultLogThreshold	LogTraceDefaultLogLevelEnum	0..1	attr	This attribute allows to set a log level Threshold for Log Level filtering.
defaultTraceState	Boolean	0..1	attr	This attributes defines the default trace status.
endpointConfiguration	PlatformModuleEthernetEndpointConfiguration	0..1	ref	Network configuration (Protocol, Port, IP Address) for transmission of dlt messages on a specific VLAN.
logChannelId	String	0..1	attr	This attribute identifies the LogChannel for usage within the Log And Trace protocol.
nonVerboseMode	Boolean	0..1	attr	This attribute defines whether this DltLogSink supports non-Verbose Dlt messages. If disabled only verbose mode messages shall be used.
path	UriString	0..1	attr	This attribute defines the path to the file that is used as output sink.
queueSize	PositiveInteger	0..1	attr	Length of the queue (in which messages can be stored before processing) in the unit "Log message".
segmentationSupported	Boolean	0..1	attr	If enabled, segmentation will be used for DLT messages that are larger than EthernetCommunicationConnector.maximumTransmissionUnit referenced via DltLogSink.endpointConfiguration.

Table A.248: DltLogSink

Class	DltLogSinkToPortPrototypeMapping			
Note	This meta-class maps a PortPrototype to an output sink of a log and trace message. Tags: atp.recommendedPackage=DltLogSinkToPortPrototypeMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dltContext	DltContext	0..1	ref	Assignment of the DltContext that groups log and trace messages that will be transmitted to the DltLogSink.
dltLogSink	DltLogSink	*	ref	Reference to the output sink to which the log or trace message will be transmitted,
dltSessionId	PositiveInteger	0..1	attr	This attribute allows distinguishing log/trace messages from different instances of the same SW-C.
pPortPrototype	PPortPrototype	0..1	iref	Reference to PPortPrototype that is mapped to the DltLog Sink. InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	Process	0..1	ref	This reference represents the process required as context for the mapping.





Class	DltLogSinkToPortPrototypeMapping			
rPortPrototype	RPortPrototype	0..1	iref	Reference to RPortPrototype that is mapped to a DltLog Sink InstanceRef implemented by: RPortPrototypeIn ExecutableInstanceRef

Table A.249: DltLogSinkToPortPrototypeMapping

Enumeration	DolpEidRetrievalEnum
Note	Enumeration with options to retrieve EID. This Enumeration is only used by the AUTOSAR Adaptive Platform.
Aggregated by	DolpNetworkConfiguration.eidRetrieval , DolpNetworkConfigurationDesign.eidRetrieval
Literal	Description
eidUseApi	API DiagnosticDoIPEntityIdentification is used to retrieve eid Tags: atp.EnumerationLiteralIndex=1
eidUseConfigValue	eid is configured manually by DolpInstantiation.eid Tags: atp.EnumerationLiteralIndex=2
eidUseMac	MAC of the network interface is used as eid Tags: atp.EnumerationLiteralIndex=0

Table A.250: DolpEidRetrievalEnum

Class	DolpFunctionalClusterDesign			
Note	This meta-class defines the attributes for the DoIP configuration settings in the MachineDesign. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AbstractFunctionalClusterDesign, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	MachineDesign.functionalClusterDesign			
Attribute	Type	Mult.	Kind	Note
dolpLogical Address	DolpLogicalAddress	0..1	aggr	This aggregation contains information about the DoIP logical address.
dolpProtocol Version	PositiveInteger	0..1	attr	Configures the DoIP protocol version used in the generic DoIP header. The valid range of this parameter is defined by the always latest release of ISO 13400-2 and can be extended with every new release of the ISO document. As example a value of 0x03 defines the ISO 13400-2:2019 release.
eid	PositiveUnlimitedInteger	0..1	attr	Configured EID (Entity ID) used for VehicleIdentification Request.
entityStatusMax ByteFieldUse	Boolean	0..1	attr	This attribute is used to distinguish the optional support of the Max data size element of a diagnostic entity status response.
maxRequest Bytes	PositiveInteger	0..1	attr	Specifies the maximum allowed bytes of a DoIP message request without the DoIP header.
network Interface	DolpNetwork ConfigurationDesign	*	aggr	This element collects DoIP properties that are network interface specific.
request Configuration Design	DolpRequest ConfigurationDesign	*	aggr	Request configuration that is used to determine whether an incoming DiagnosticMessage request needs to be interpreted as PHYSICAL or FUNCTIONAL. Any request with target address not within the configured target address range will be rejected.

Table A.251: DolpFunctionalClusterDesign

Class	DolpInstantiation			
Note	This meta-class defines the attributes for the DoIP configuration on a specific machine. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AdaptiveModuleInstantiation, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable , MultilanguageReferrable, NonOsModuleInstantiation , Referrable			
Aggregated by	AtpClassifier.atpFeature, Machine.moduleInstantiation			
Attribute	Type	Mult.	Kind	Note
dolpDesign	DolpFunctionalClusterDesign	0..1	ref	Reference to the DoIP Design that this DolpInstantiation implements.
gid	PositiveUnlimitedInteger	0..1	attr	Configured GID (Group ID) used for VehicleIdentification Request. If configured, take this value (and set "Further action required" byte to 0x00="No further action required"), if not configured use ServiceInterface Do IPGroupIdentification to retrieve GID and 'further action required' values.
logicalAddress	PositiveInteger	0..1	attr	Describes the logical address of the DoIP entity, which is used for VehicleAnnouncement and RoutingActivation responses.
network Interface	DolpNetworkConfiguration	*	aggr	Network interface specific DoIP properties.
request Configuration	DolpRequestConfiguration	*	aggr	Request configuration that is used to determine whether an incoming DiagnosticMessage request needs to be interpreted as PHYSICAL or FUNCTIONAL. Any request with target address not within the configured target address range will be rejected.

Table A.252: DolpInstantiation

Class	DolpLogicalAddress			
Note	This meta-class describes the DoIP logical address. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	DolpFunctionalClusterDesign.dolpLogicalAddress			
Attribute	Type	Mult.	Kind	Note
logicalAddress	PositiveInteger	0..1	attr	This attribute holds the DoIP logical address.

Table A.253: DolpLogicalAddress

Class	DolpNetworkConfiguration			
Note	This element collects DoIP properties that are network interface specific. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	DolpInstantiation.networkInterface			
Attribute	Type	Mult.	Kind	Note
eidRetrieval	DolpEidRetrievalEnum	0..1	attr	This attribute defines how Dolp Entity Identification is retrieved.
isActivationLine Dependent	Boolean	0..1	attr	This attribute defines whether the network interface <ul style="list-style-type: none"> is started "on-demand" when an activation line is sensed or is always available.





Class	DolpNetworkConfiguration			
maxInitialVehicleAnnouncementTime	TimeValue	0..1	attr	Upper bound for the time to wait in [s] for sending first vehicle announcement message after IP address assignment. Represents parameter A_DoIP_Announce_Wait of ISO 13400-2:2019. The value of this timing shall be determined randomly in the closed interval [0..maxInitialVehicleAnnouncementTime].
maxTesterConnections	PositiveInteger	0..1	attr	Maximum amount of tester connections that shall be maintained at one time before alive check is performed.
networkConfiguration	PlatformModuleEthernetEndpointConfiguration	*	ref	Network configuration (Protocol, Port, IP Address) for transmission of DoIP messages on a specific VLAN.
networkConfigurationDesign	DolpNetworkConfigurationDesign	0..1	ref	Reference to the DoIP network configuration design that this DolpNetworkConfiguration implements.
networkInterfaceId	PositiveInteger	0..1	attr	This attribute defines the identifier for the DoIPInterface.
tcpAliveCheckResponseTimeout	TimeValue	0..1	attr	Timeout in [s] for waiting for a response to an Alive Check request before the connection is considered to be disconnected. Represents parameter T_TCP_AliveCheck of ISO 13400-2:2019.
tcpGeneralInactivityTime	TimeValue	0..1	attr	Timeout in [s] for maximum inactivity of a TCP socket connection before the DoIP module will close the according socket connection. Represents parameter T_TCP_General_Inactivity of ISO 13400-2:2019.
tcpInitialInactivityTime	TimeValue	0..1	attr	Timeout in [s] used for initial inactivity of a connected TCP socket connection directly after socket connection. Represents parameter T_TCP_Initial_Inactivity of ISO 13400-2:2019.
vehicleAnnouncementCount	PositiveInteger	0..1	attr	Number of vehicle announcement messages on IP address assignment. Represents parameter A_DoIP_Announce_Num of ISO 13400-2:2019.
vehicleAnnouncementInterval	TimeValue	0..1	attr	Time to wait in [s] for sending subsequent vehicle announcement messages. Represents parameter A_DoIP_Announce_Interval of ISO 13400-2:2019.
vehicleIdentificationSyncStatus	Boolean	0..1	attr	Defines if the optional VIN/GID synchronization status is used additionally in the vehicle identification/announcement.

Table A.254: DolpNetworkConfiguration

Class	DolpNetworkConfigurationDesign			
Note	This element collects DoIP properties that are network interface specific. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	DolpFunctionalClusterDesign.networkInterface			
Attribute	Type	Mult.	Kind	Note
eidRetrieval	DolpEidRetrievalEnum	0..1	attr	This attribute defines how DoIP Entity Identification is retrieved.
isActivationLineDependent	Boolean	0..1	attr	This attribute defines whether the network interface <ul style="list-style-type: none"> is started "on-demand" when an activation line is sensed or is always available.





Class	DolpNetworkConfigurationDesign			
maxInitialVehicleAnnouncementTime	TimeValue	0..1	attr	Upper bound for the time to wait in [s] for sending first vehicle announcement message after IP address assignment. Represents parameter A_DoIP_Announce_Wait of ISO 13400-2:2019. The value of this timing shall be determined randomly in the closed interval [0..maxInitialVehicleAnnouncementTime].
maxTesterConnections	PositiveInteger	0..1	attr	Maximum amount of tester connections that shall be maintained at one time before alive check is performed.
networkConfiguration	PlatformModuleEthernetEndpointConfiguration	*	ref	Network configuration (Protocol, Port, IP Address) for transmission of DoIP messages on a specific VLAN.
networkInterfaceId	PositiveInteger	0..1	attr	This attribute defines the identifier for the DoIPInterface.
tcpAliveCheckResponseTimeout	TimeValue	0..1	attr	Timeout in [s] for waiting for a response to an Alive Check request before the connection is considered to be disconnected. Represents parameter T_TCP_AliveCheck of ISO 13400-2:2019.
tcpGeneralInactivityTime	TimeValue	0..1	attr	Timeout in [s] for maximum inactivity of a TCP socket connection before the DoIP module will close the according socket connection. Represents parameter T_TCP_General_Inactivity of ISO 13400-2:2019.
tcpInitialInactivityTime	TimeValue	0..1	attr	Timeout in [s] used for initial inactivity of a connected TCP socket connection directly after socket connection. Represents parameter T_TCP_Initial_Inactivity of ISO 13400-2:2019.
tpConnection	GenericTpConnection	*	ref	Reference to a TpConnection that identifies the receiver(s) of a particular communication
vehicleAnnouncementCount	PositiveInteger	0..1	attr	Number of vehicle announcement messages on IP address assignment. Represents parameter A_DoIP_Announce_Num of ISO 13400-2:2019.
vehicleAnnouncementInterval	TimeValue	0..1	attr	Time to wait in [s] for sending subsequent vehicle announcement messages. Represents parameter A_DoIP_Announce_Interval of ISO 13400-2:2019.
vehicleIdentificationSyncStatus	Boolean	0..1	attr	Defines if the optional VIN/GID synchronization status is used additionally in the vehicle identification/announcement.

Table A.255: DolpNetworkConfigurationDesign

Class	DolpRequestConfiguration			
Note	This meta-class specifies a range of target addresses and its interpretation as either physical or functional request. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	DolpInstantiation.requestConfiguration			
Attribute	Type	Mult.	Kind	Note
endAddress	PositiveInteger	0..1	attr	End address for range of target-addresses (including this address).
requestType	RequestTypeEnum	0..1	attr	Determines the type of request.
startAddress	PositiveInteger	0..1	attr	Start address for range of target-addresses (including this address).

Table A.256: DolpRequestConfiguration

Class	E2EProfileCompatibilityProps			
Note	This meta-class collects settings for configuration of the E2E state machine. Tags: atp.recommendedPackage=E2EProfileCompatibilityPropsCollection			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
combinedNoDataInitCount	Boolean	0..1	attr	E2E State machine behavior concerning counting of detected counter errors and missing messages in states NODATA and INIT <ul style="list-style-type: none"> value = 0 (false) or not defined: counting of detected counter errors and missing messages in states NODATA and INIT are counted per state separated (Autosar R23-11 or former behavior) value = 1 (true): counting of detected counter errors and missing messages in states NODATA and INIT are counted in total
transitToInvalidExtended	Boolean	0..1	attr	E2E State machine behavior concerning transition from NODATA/INIT to INVALID value=0 (false): no direct transition from NODATA to INVALID, no transition from INIT to INVALID due to counter-related faults (Autosar R19-11 or former behavior) value=1 (true): direct transition from NODATA to INVALID covered, transition from INIT to INVALID due to counter-related faults covered (state machine extended)

Table A.257: E2EProfileCompatibilityProps

Class	E2EProfileConfiguration			
Note	This element holds E2E profile specific configuration settings. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	E2EProfileConfigurationSet.e2eProfileConfiguration			
Attribute	Type	Mult.	Kind	Note
clearFromValidToInvalid	Boolean	0..1	attr	Clear monitoring window on transition from state Valid to state Invalid.
dataIdMode	DataIdModeEnum	0..1	attr	This attribute describes the inclusion mode that is used to include the implicit Data ID in the one-byte CRC.
e2eProfileCompatibilityProps	E2EProfileCompatibilityProps	0..1	ref	Reference to additional settings for the E2E state machine.
maxDeltaCounter	PositiveInteger	0..1	attr	Maximum allowed difference between two counter values of two consecutively received valid messages. For example, if the receiver gets data with counter 1 and MaxDeltaCounter is 3, then at the next reception the receiver can accept Counters with values 2, 3 or 4.
maxErrorStateInit	PositiveInteger	0..1	attr	Maximal number of checks in which ProfileStatus equal to E2E_P_ERROR was determined, within the last Window Size checks, for the state E2E_SM_INIT.
maxErrorStateInvalid	PositiveInteger	0..1	attr	Maximal number of checks in which ProfileStatus equal to E2E_P_ERROR was determined, within the last Window Size checks, for the state E2E_SM_INVALID.
maxErrorStateValid	PositiveInteger	0..1	attr	Maximal number of checks in which ProfileStatus equal to E2E_P_ERROR was determined, within the last Window Size checks, for the state E2E_SM_VALID.





Class	E2EProfileConfiguration			
minOkStateInit	PositiveInteger	0..1	attr	Minimal number of checks in which ProfileStatus equal to E2E_P_OK was determined, within the last WindowSize checks, for the state E2E_SM_INIT.
minOkStateInvalid	PositiveInteger	0..1	attr	Minimal number of checks in which ProfileStatus equal to E2E_P_OK was determined, within the last WindowSize checks, for the state E2E_SM_INVALID.
minOkStateValid	PositiveInteger	0..1	attr	Minimal number of checks in which ProfileStatus equal to E2E_P_OK was determined, within the last WindowSize checks, for the state E2E_SM_VALID.
profileName	NameToken	0..1	attr	Definition of the E2E profile.
windowSizeInit	PositiveInteger	0..1	attr	Size of the monitoring window of state Init for the E2E state machine.
windowSizeInvalid	PositiveInteger	0..1	attr	Size of the monitoring window of state Invalid for the E2E state machine.
windowSizeValid	PositiveInteger	0..1	attr	Size of the monitoring window of state Valid for the E2E state machine.

Table A.258: E2EProfileConfiguration

Class	End2EndEventProtectionProps			
Note	This element allows to protect an event or a field notifier with an E2E profile. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	AdaptivePlatformServiceInstance.e2eEventProtectionProps			
Attribute	Type	Mult.	Kind	Note
dataId (ordered)	PositiveInteger	*	attr	This represents a unique numerical identifier for the referenced event or field notifier that is included in the CRC calculation. Note: ID is used for protection against masquerading. The details concerning the maximum number of values (this information is specific for each E2E profile) applicable for this attribute are controlled by a semantic constraint that depends on the category of the EndToEnd Protection.
dataLength	PositiveInteger	0..1	attr	Length of payload including E2E header in bits.
dataUpdatePeriod	TimeValue	0..1	attr	This attribute describes the period in which the applications are assumed to process E2E-protected messages. The middleware does not use this attribute at all.
e2eProfileConfiguration	E2EProfileConfiguration	0..1	ref	Reference to E2E profile configuration settings that are valid to protect the referenced event or field notifier.
event	ServiceEventDeployment	0..1	ref	Reference to an event that is protected by the E2E profile.
maxDataLength	PositiveInteger	0..1	attr	Maximum length of payload including E2E header in bits.
minDataLength	PositiveInteger	0..1	attr	Minimum length of payload including E2E header in bits.

Table A.259: End2EndEventProtectionProps

Class	End2EndMethodProtectionProps			
Note	This element allows to protect a method, a field setter or a field getter with an E2E profile. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			





Class	End2EndMethodProtectionProps			
Aggregated by	AdaptivePlatformServiceInstance.e2eMethodProtectionProps			
Attribute	Type	Mult.	Kind	Note
dataId (ordered)	PositiveInteger	*	attr	This represents a numerical identifier that is included in the CRC calculation. This dataId is used for call and response. Note: ID is used for protection against masquerading. The details concerning the maximum number of values (this information is specific for each E2E profile) applicable for this attribute are controlled by a semantic constraint that depends on the category of the EndToEnd Protection.
dataLength	PositiveInteger	0..1	attr	Length of payload including E2E header in bits.
dataUpdate Period	TimeValue	0..1	attr	This attribute describes the period in which the applications are assumed to process E2E-protected messages. The middleware does not use this attribute at all.
e2eProfile Configuration	E2EProfileConfiguration	0..1	ref	Reference to E2E profile configuration settings that are valid to protect the referenced method, field getter or field setter.
maxDataLength	PositiveInteger	0..1	attr	Maximum length of payload including E2E header in bits.
method	ServiceMethod Deployment	0..1	ref	Reference to a method, a field getter or a field setter that is protected by the E2E profile.
minDataLength	PositiveInteger	0..1	attr	Minimum length of payload including E2E header in bits.
sourceId	PositiveInteger	0..1	attr	This represents a unique numerical identifier identifying the source of a certain transmission. In case of C/S communication, this ID uniquely identifies the client. Note: ID is used for protection against masquerading. The details concerning the maximum number of values (this information is specific for each E2E profile) applicable for this attribute are controlled by a semantic constraint that depends on the category of the EndToEnd Protection.

Table A.260: End2EndMethodProtectionProps

Class	EnterExitTimeout			
Note	This meta-class represents the ability to specify a pair of timeouts, one for entering, and one for exiting. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i>			
Aggregated by	Machine.defaultApplicationTimeout , StartupConfig.timeout			
Attribute	Type	Mult.	Kind	Note
enterTimeout Value	TimeValue	0..1	attr	This attribute represents the value of the enter timeout in seconds.
exitTimeout Value	TimeValue	0..1	attr	This attribute represents the value of the exit timeout in seconds.

Table A.261: EnterExitTimeout

Class	EthernetCommunicationConnector			
Note	Ethernet specific attributes to the CommunicationConnector.			
Base	<i>ARObject</i> , CommunicationConnector , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	<i>EcuInstance.connector</i> , MachineDesign.communicationConnector			
Attribute	Type	Mult.	Kind	Note





Class	EthernetCommunicationConnector			
apApplicationEndpoint	ApApplicationEndpoint	*	aggr	Collection of Application Addresses that are used on the CommunicationConnector. This Attribute is only used by the AUTOSAR Adaptive Platform.
canXIProps	CanXIProps	*	ref	If the Ethernet frames handled by this Ethernet CommunicationConnector are tunneled through CAN XL, then this reference shall refer the CanXIProps which contains the specific configuration parameters of the CAN XL controller of the physical CAN XL connection to be used for tunneling. This Attribute is only used by the AUTOSAR Adaptive Platform.
maximumTransmissionUnit	PositiveInteger	0..1	attr	This attribute specifies the maximum transmission unit in bytes.
neighborCacheSize	PositiveInteger	0..1	attr	This attribute specifies the size of neighbor cache or ARP table in units of entries.
pathMtuEnabled	Boolean	0..1	attr	If enabled the IPv4/IPv6 processes incoming ICMP "Packet Too Big" messages and stores a MTU value for each destination address. Tags: atp.Status=obsolete
pathMtuTimeout	TimeValue	0..1	attr	If this value is >0 the IPv4/IPv6 will reset the MTU value stored for each destination after n seconds. Tags: atp.Status=obsolete
unicastNetworkEndpoint	NetworkEndpoint	*	ref	Network Endpoint that defines the IPAddress of the machine. This Attribute is only used by the AUTOSAR Adaptive Platform.

Table A.262: EthernetCommunicationConnector

Class	«atpVariation» EthernetCommunicationController			
Note	Ethernet specific communication port attributes.			
Base	ARObject, CommunicationController, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	EcuInstance.commController, MachineDesign.communicationController			
Attribute	Type	Mult.	Kind	Note
canXIConfig	AbstractCanCommunicationController	0..1	ref	If the Ethernet frames handled by this Ethernet CommunicationController are to be tunneled through CAN XL, then this reference shall refer to the Abstract CanCommunicationController that aggregates the CanControllerXIConfiguration of the physical CAN XL channel to be used for tunneling.
couplingPort	CouplingPort	*	aggr	Optional CouplingPort that can be used to connect the ECU to a CouplingElement (e.g. a switch).
macLayerType	EthernetMacLayerTypeEnum	0..1	attr	Specifies the mac layer type of the ethernet controller.
macUnicastAddress	MacAddressString	0..1	attr	Media Access Control address (MAC address) that uniquely identifies each EthernetCommunicationController in the network.
maximumReceiveBufferLength	Integer	0..1	attr	Determines the maximum receive buffer length (frame length) in bytes.
maximumTransmitBufferLength	Integer	0..1	attr	Determines the maximum transmit buffer length (frame length) in bytes.





Class	«atpVariation» EthernetCommunicationController			
slaveActAs Passive Communication Slave	Boolean	0..1	attr	This attribute specifies if the EcuInstance is acting as a passive communication slave on the connected Physical Channel. This is used for EthernetCommunication Controllers that use Ethernet hardware which supports wake-up and sleep on the network (e.g. Open Alliance TC10 compliant Ethernet hardware).
slaveQualified UnexpectedLink DownTime	TimeValue	0..1	attr	This attribute specifies time when an unexpected link down is evaluated as link down and indicated to the AUTOSAR communication stack.

Table A.263: EthernetCommunicationController

Class	EthernetMacRawDataStreamMapping (abstract)			
Note	This meta-class serves as the abstract bases class for the ability to map a PortPrototype to an Ethernet-Mac-layer based communication. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, RawDataStreamMapping, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Subclasses	IEEE1722RawDataStreamMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
localComm Connector	EthernetCommunication Connector	0..1	ref	This reference represents the CommunicationConnector taken for Mac-based data communication. Tags: atp.Status=candidate
socketOption	String	*	attr	This attribute represents the ability to specify non-formal socket options that might only be valid for specific platforms. AUTOSAR does not define a standardized meaning for the possible values of this attribute. Tags: atp.Status=candidate

Table A.264: EthernetMacRawDataStreamMapping

Class	EthernetPhysicalChannel			
Note	The EthernetPhysicalChannel represents a VLAN or an untagged channel. An untagged channel is modeled as an EthernetPhysicalChannel without an aggregated VLAN.			
Base	ARObject, Identifiable , MultilanguageReferrable, PhysicalChannel, Referrable			
Aggregated by	CommunicationCluster.physicalChannel			
Attribute	Type	Mult.	Kind	Note
network Endpoint	NetworkEndpoint	*	aggr	Collection of NetworkEndpoints that are used in the VLAN. Stereotypes: atp.Splittable Tags: atp.Splitkey=networkEndpoint.shortName
vlan	VlanConfig	0..1	aggr	VLAN Configuration.

Table A.265: EthernetPhysicalChannel

Class	EthernetRawDataStreamLocalEndpointConfig			
Note	This meta-class has the ability to act as a wrapper for the configuration of the remote endpoint in the context of a raw data stream mapping. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			





Class	EthernetRawDataStreamLocalEndpointConfig			
Aggregated by	EthernetRawDataStreamMapping.localEndpointConfig			
Attribute	Type	Mult.	Kind	Note
localCommConnector	EthernetCommunicationConnector	0..1	ref	This attribute represents the CommunicationConnector taken for socket-based data communication.
localTcpPort	ApApplicationEndpoint	0..1	ref	This aggregation represents the configuration of a local TCP port number.
localUdpPort	ApApplicationEndpoint	0..1	ref	This aggregation represents the configuration of a local unicast UDP port number.

Table A.266: EthernetRawDataStreamLocalEndpointConfig

Class	EthernetRawDataStreamMapping (abstract)			
Note	This meta-class serves as the abstract bases class for the ability to map a PortPrototype to a Ethernet-based communication channel. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , Identifiable , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>RawDataStreamMapping</i> , Referrable , <i>UploadableDeploymentElement</i> , <i>UploadablePackageElement</i>			
Subclasses	EthernetRawDataStreamClientMapping, EthernetRawDataStreamServerMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
localEndpointConfig	EthernetRawDataStreamLocalEndpointConfig	0..1	aggr	This aggregation is used to configure the credentials of the endpoint.
socketOption	String	*	attr	This attribute represents the ability to specify non-formal socket options that might only be valid for specific platforms. AUTOSAR does not define a standardized meaning for the possible values of this attribute.
tlsSecureComProps	TlsSecureComProps	0..1	ref	This reference provides the ability to define TLS-related properties for the enclosing SocketRawDataStream Mapping.

Table A.267: EthernetRawDataStreamMapping

Class	EthernetRawDataStreamRemoteClientConfig			
Note	This meta-class has the ability to act as a wrapper for the configuration of the remote server in the context of a raw data stream client mapping. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i>			
Aggregated by	EthernetRawDataStreamServerMapping.remoteClientConfig			
Attribute	Type	Mult.	Kind	Note
multicastCredentials	RawDataStreamEthernetUdpCredentials	0..1	aggr	This aggregation represents the configuration of multicast credentials for communication with a remote raw data stream client.
unicastUdpCredentials	RawDataStreamEthernetUdpCredentials	0..1	aggr	This aggregation represents the configuration of a remote raw data stream client that communicates via unicast over UDP.

Table A.268: EthernetRawDataStreamRemoteClientConfig

Class	EthernetRawDataStreamServerMapping			
Note	This meta-class represents the ability to map a server PortPrototype to a Ethernet-based communication channel. Tags: atp.recommendedPackage=RawDataStreamingMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, EthernetRawDataStreamMapping , Identifiable , MultilanguageReferrable , PackageableElement , RawDataStreamMapping , Referrable , UploadableDeploymentElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
remoteClient Config	EthernetRawDataStreamRemoteClientConfig	0..1	aggr	This aggregation is used to configure the credentials of the remote client.

Table A.269: EthernetRawDataStreamServerMapping

Class	Executable			
Note	This meta-class represents an executable program. Tags: atp.recommendedPackage=Executables This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpClassifier, CollectableElement, Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
implementation Props	Executable ImplementationProps	*	aggr	This aggregation contains the collection of implementation-specific properties necessary to properly build the enclosing Executable.
minimumTimer Granularity	TimeValue	0..1	attr	This attribute describes the minimum timer resolution (TimeValue of one tick) that is required by the Executable.
reporting Behavior	ExecutionStateReportingBehaviorEnum	0..1	attr	this attribute controls the execution state reporting behavior of the enclosing Executable.
rootSw Component Prototype	RootSwComponentPrototype	0..1	aggr	This represents the root SwCompositionPrototype of the Executable. This aggregation is required (in contrast to a direct reference of a SwComponentType) in order to support the definition of instanceRefs in Executable context.
suspendToRam Awareness	SuspendToRam AwarenessEnum	0..1	attr	This attribute describes the type of awareness of the enclosing Executable to suspend-to-RAM functionality. Tags: atp.Status=candidate
version	StrongRevisionLabel String	0..1	attr	Version of the executable.

Table A.270: Executable

Class	ExecutableLoggingImplementationProps			
Note	This meta-class contains configuration relevant for the implementation of an Executable used in the context of the LogAndTraceInstantiation. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Describable, ExecutableImplementationProps			
Aggregated by	Executable.implementationProps			
Attribute	Type	Mult.	Kind	Note





Class	ExecutableLoggingImplementationProps			
usesTimeBaseResource	Boolean	0..1	attr	This attribute indicates that the implementation of the enclosing Executable is required to access resources provided by the synchronized time base functional cluster.

Table A.271: ExecutableLoggingImplementationProps

Class	ExecutableTiming			
Note	This meta-class represents the timing view for one or more executables. Tags: atp.Status=draft atp.recommendedPackage=TimingExtensions This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, TimingExtension			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
executable	Executable	*	ref	This defines the scope of a ExecutableTiming. All corresponding timing descriptions and constraints shall be defined within this scope. Tags: atp.Status=draft

Table A.272: ExecutableTiming

Class	ExecutionDependency			
Note	This element defines a ProcessState in which a dependent process needs to be before the process that aggregates the ExecutionDependency element can be started. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	StateDependentStartupConfig.executionDependency			
Attribute	Type	Mult.	Kind	Note
processState	ModeDeclaration	0..1	iref	This represent the applicable modeDeclaration that represents an ProcessState. InstanceRef implemented by: ModeInProcessInstanceRef

Table A.273: ExecutionDependency

Enumeration	ExecutionStateReportingBehaviorEnum			
Note	This enumeration provides options for controlling of how an Executable reports its execution state to the Execution Management This Enumeration is only used by the AUTOSAR Adaptive Platform.			
Aggregated by	Executable.reportingBehavior			
Literal	Description			
doesNotReportExecutionState	The Executable shall not report its execution state to the Execution Management. Tags: atp.EnumerationLiteralIndex=1			
reportsExecutionState	The Executable shall report its execution state to the Execution Management. Tags: atp.EnumerationLiteralIndex=0			

Table A.274: ExecutionStateReportingBehaviorEnum

Class	Field			
Note	This meta-class represents the ability to define a piece of data that can be accessed with read and/or write semantics. It is also possible to generate a notification if the value of the data changes. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AtpFeature, AtpPrototype, AutosarDataPrototype , DataPrototype , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApplicationInterface.attribute, AtpClassifier.atpFeature, ServiceInterface.field			
Attribute	Type	Mult.	Kind	Note
hasGetter	Boolean	0..1	attr	This attribute controls whether read access is foreseen to this field.
hasNotifier	Boolean	0..1	attr	This attribute controls whether a notification semantics is foreseen to this field.
hasSetter	Boolean	0..1	attr	This attribute controls whether write access is foreseen to this field.

Table A.275: Field

Class	FieldMapping			
Note	Mapping of a Field that is located in a ServiceInterface to ClientServerOperations that represent the getter and setter methods and to a VariableDataPrototype that represents the notifier in the Field. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	InterfaceMapping.fieldMapping			
Attribute	Type	Mult.	Kind	Note
field	Field	0..1	ref	Reference to a field that is located in a ServiceInterface.
getterOperation	ClientServerOperation	0..1	ref	Reference to a ClientServerOperation that represents the getter Method in the Field.
notifierDataElement	VariableDataPrototype	0..1	ref	Reference to a VariableDataPrototype that represents the notifier in the Field.
setterOperation	ClientServerOperation	0..1	ref	Reference to a ClientServerOperation that represents the setter Method in the Field.

Table A.276: FieldMapping

Class	FieldSenderComSpec			
Note	Port specific communication attributes for a Field that is defined in a ServiceInterface. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, PPortComSpec, SenderComSpec			
Aggregated by	AbstractProvidedPortPrototype.providedComSpec, PortPrototypeBlueprint.providedComSpec			
Attribute	Type	Mult.	Kind	Note
initValue	ValueSpecification	0..1	aggr	Initial value for a Field that is set before the Service Interface is offered.

Table A.277: FieldSenderComSpec

Class	FireAndForgetMethodMapping			
Note	Mapping of a Fire&Forget Method that is located in a ServiceInterface to a VariableDataPrototype in a SenderReceiverInterface or to a Trigger in a TriggerInterface. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	InterfaceMapping.fireAndForgetMethodMapping			
Attribute	Type	Mult.	Kind	Note





Class	FireAndForgetMethodMapping			
dataElement	VariableDataPrototype	0..1	ref	Reference to a VariableDataPrototype that is located in a SenderReceiverInterface in case that the Fire&Forget Method is represented by this VariableDataPrototype.
method	ClientServerOperation	0..1	ref	Reference to a Fire&Forget Method that is located in a ServiceInterface.
trigger	Trigger	0..1	ref	Reference to a Trigger that is located in a TriggerInterface in case that the Fire&Forget Method is represented by this Trigger.

Table A.278: FireAndForgetMethodMapping

Class	FirewallRule			
Note	Firewall Rule that defines the control information in individual packets. Tags: atp.Status=candidate atp.recommendedPackage=FirewallRules			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
bucketSize	PositiveInteger	0..1	attr	This attribute defines the capacity of the queue for rate limitation (leaky-bucket Algorithm). Tags: atp.Status=candidate
dataLinkLayerRule	DataLinkLayerRule	0..1	aggr	Configuration of rules on the Data Link Layer Tags: atp.Status=candidate
ddsRule	DdsRule	0..1	aggr	Configuration of firewall rules for DDS. Tags: atp.Status=candidate
dolpRule	DolpRule	0..1	aggr	Configuration of firewall rules for DoIP messages Tags: atp.Status=candidate
networkLayerRule	NetworkLayerRule	0..1	aggr	Configuration of rules on the Network Layer Tags: atp.Status=candidate
payloadBytePatternRule	PayloadBytePatternRule	*	aggr	Configuration of generic firewall rules Tags: atp.Status=candidate
refillAmount	PositiveInteger	0..1	attr	This attribute defines the output rate that describes how many packets leave the queue per second (leaky-bucket Algorithm). Tags: atp.Status=candidate
someipRule	SomeipProtocolRule	0..1	aggr	Configuration of firewall rules for SOME/IP messages Tags: atp.Status=candidate
someipSdRule	SomeipSdRule	0..1	aggr	Configuration of firewall rules for SOME/IP Service Discovery messages Tags: atp.Status=candidate
transportLayerRule	TransportLayerRule	0..1	aggr	Configuration of rules on the Transport Layer Tags: atp.Status=candidate

Table A.279: FirewallRule

Class	FirewallRuleProps			
Note	Firewall rule that is defined by an action that is performed if the referenced pattern matches. Tags: atp.Status=candidate			
Base	<i>ARObject</i>			
Aggregated by	StateDependentFirewall.firewallRuleProps			





Class	FirewallRuleProps			
Attribute	Type	Mult.	Kind	Note
action	FirewallActionEnum	0..1	attr	Action that is performed by the firewall if the matching Rule is fulfilled. Tags: atp.Status=candidate
matchingEgress Rule (ordered)	FirewallRule	*	ref	This element defines an egress rule expression against which the network traffic is matched. Tags: atp.Status=candidate
matching IngressRule (ordered)	FirewallRule	*	ref	This element defines an ingress rule expression against which the network traffic is matched. Tags: atp.Status=candidate

Table A.280: FirewallRuleProps

Class	FirewallStateSwitchInterface			
Note	This meta-class provides the ability to implement a PortInterface for interaction with the Firewall mode. Tags: atp.Status=candidate atp.recommendedPackage=FirewallStateSwitchPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
firewallState Machine	ModeDeclarationGroup Prototype	*	aggr	The state machine of this firewall interface. Tags: atp.Status=candidate

Table A.281: FirewallStateSwitchInterface

Class	FunctionGroupPhmStateReference			
Note	Function Group state dependency. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject , PhmStateReference			
Aggregated by	SupervisionModeCondition.stateReference			
Attribute	Type	Mult.	Kind	Note
functionGroup State	ModeDeclaration	0..1	iref	This represent the applicable functionGroupState. InstanceRef implemented by: FunctionGroupStateIn FunctionGroupSetInstanceRef

Table A.282: FunctionGroupPhmStateReference

Class	FunctionGroupPortMapping			
Note	This class is used to associate a PortPrototype typed by a StateClientInterface with the actual function group to which the state changes communicated over the PortPrototype shall apply. Tags: atp.Status=draft atp.recommendedPackage=FunctionGroupPortMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement , ARObject , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDeploymentElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	FunctionGroupPortMapping			
functionGroup	ModeDeclarationGroupPrototype	0..1	ref	This reference identifies the applicable function group for which the state change shall be executed. Tags: atp.Status=draft
process	Process	0..1	ref	This reference identifies the Process of the state client Tags: atp.Status=draft
rPortPrototypeInExecutable	RPortPrototype	0..1	iref	This reference identifies the applicable PortPrototype for the function group state change. Stereotypes: atpUriDef Tags: atp.Status=draft InstanceRef implemented by: RPortPrototypeInExecutableInstanceRef

Table A.283: FunctionGroupPortMapping

Class	FunctionGroupSet			
Note	This meta-class provides the ability to create arbitrary collections of function groups. Tags: atp.recommendedPackage=FunctionGroupSets This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement , ARObject , AtpClassifier , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
functionGroup	ModeDeclarationGroupPrototype	*	aggr	This aggregation represents the collection of function groups.

Table A.284: FunctionGroupSet

Class	FunctionGroupStateInFunctionGroupSetInstanceRef			
Note	This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject , AtpInstanceRef			
Aggregated by	FunctionGroupPhmStateReference.functionGroupState , NmHandleToFunctionGroupStateMapping.functionGroupState , SecurityEventStateFilter.blockIfStateActiveAp , StateDependentStartupConfig.functionGroupState , StateManagementSetFunctionGroupStateActionItem.setFunctionGroupState			
Attribute	Type	Mult.	Kind	Note
base	FunctionGroupSet	0..1	ref	Stereotypes: atpDerived
contextModeDeclarationGroupPrototype	ModeDeclarationGroupPrototype	0..1	ref	Tags: xml.sequenceOffset=10
targetModeDeclaration	ModeDeclaration	0..1	ref	Tags: xml.sequenceOffset=20

Table A.285: FunctionGroupStateInFunctionGroupSetInstanceRef

Class	FunctionalClusterInteractsWithDiagnosticEventMapping			
Note	This meta-class creates an association between a functional cluster and a diagnostic event that represents the diagnostic management by proxy. The purpose of this mapping is to support the reporting of production errors. Tags: atp.recommendedPackage=FCInteractions This Class is only used by the AUTOSAR Adaptive Platform.			





Class	FunctionalClusterInteractsWithDiagnosticEventMapping			
Base	ARElement, ARObject, CollectableElement, FunctionalClusterInteractsWithFunctionalClusterMapping, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnosticEvent	DiagnosticEvent	*	ref	This reference identifies the collection of diagnostic events that can be reported by the mapped functional cluster.
functional Cluster	AdaptiveModule Instantiation	0..1	ref	This reference identifies the reporting functional cluster.
persistence Deployment	PersistenceDeployment	0..1	ref	This reference identifies the reporting persistence deployment.

Table A.286: FunctionalClusterInteractsWithDiagnosticEventMapping

Class	FunctionalClusterInteractsWithPersistenceDeploymentMapping			
Note	This meta-class represents the ability to define a mapping between any functional cluster modeled as a subclass of NonOsModuleInstantiation and a PersistenceDeployment. Tags: atp.recommendedPackage=FCInteractions This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, FunctionalClusterInteractsWithFunctionalClusterMapping, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
contractVersion	StrongRevisionLabel String	0..1	attr	This attribute represents the contract version that is used to determine whether the Persistence configuration experienced structural changes and is also used for the check for data type compatibility.
functional Cluster	NonOsModule Instantiation	0..1	ref	This reference identifies the client functional cluster that wants to use persistence.
maxNumberOf Files	PositiveInteger	0..1	attr	This attribute represents the definition of an upper bound for the handling of files at run-time in the context of the enclosing FunctionalClusterInteractsWithPersistence DeploymentMapping.
persistence Access	FunctionalCluster PersistenceAccess Enum	0..1	attr	This attribute represents the definition of the persistence access of all kinds of persisted data at run-time in the context of the enclosing FunctionalClusterInteractsWith PersistenceDeploymentMapping.
persistence Deployment	PersistenceDeployment	0..1	ref	This reference identifies the applicable Persistence Deployment.
process	Process	0..1	ref	"This reference identifies the applicable process.

Table A.287: FunctionalClusterInteractsWithPersistenceDeploymentMapping

Class	GenericTpConnection			
Note	A TpConnection that defines a communication between the logical target address of the DoIP Entity and the source address range. Tags: atp.recommendedPackage=GenericTpConnections This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			





Class	GenericTpConnection			
Attribute	Type	Mult.	Kind	Note
priority	PositiveInteger	0..1	attr	This attribute defines the priority for a particular communication connection. For more details see the SWS Diagnostics specification.
sourceAddressRangeEnd	PositiveInteger	0..1	attr	The DoIP source address defines the logical address of the tester that starts the communication. The GenericTpConnection is able to define a source address range (without gaps) with the two attributes sourceAddressRangeStart and sourceAddressRangeEnd. This attribute defines the end of the range.
sourceAddressRangeStart	PositiveInteger	0..1	attr	The DoIP source address defines the logical address of the tester that starts the communication. The GenericTpConnection is able to define a source address range (without gaps) with the two attributes sourceAddressRangeStart and sourceAddressRangeEnd. This attribute defines the start of the range.

Table A.288: GenericTpConnection

Class	GlobalSupervision			
Note	This element defines a collection of AliveSupervisions, DeadlineSupervisions, and LogicalSupervisions in order to provide an aggregated supervision state. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	PlatformHealthManagementContribution.globalSupervision			
Attribute	Type	Mult.	Kind	Note
aliveSupervision	AliveSupervision	*	aggr	Collection of AliveSupervisions in the context of this GlobalSupervision.
deadlineSupervision	DeadlineSupervision	*	aggr	Collection of DeadlineSupervisions in the context of this GlobalSupervision.
expiredSupervisionTolerance	TimeValue	0..1	attr	Defines the acceptable amount of time with EXPIRED supervision status before the GlobalSupervision is considered STOPPED.
logicalSupervision	LogicalSupervision	*	aggr	Collection of LogicalSupervisions in the context of this GlobalSupervision.
noCheckpointSupervision	NoCheckpointSupervision	*	aggr	Definition of No Checkpoint Supervision.
noSupervision	NoSupervision	*	aggr	Collection of NoSupervisions in the context of this GlobalSupervision.
supervisionMode	SupervisionMode	*	aggr	Collection of SupervisionModes in the context of this GlobalSupervision. Stereotypes: atpSplitable Tags: atp.Splitkey=supervisionMode.shortName
transition	CheckpointTransition	*	aggr	Collection of CheckpointTransitions in the context of this GlobalSupervision.

Table A.289: GlobalSupervision

Class	GlobalTimeDomain			
Note	This represents the ability to define a global time domain. Tags: atp.recommendedPackage=GlobalTimeDomains			
Base	ARElement, ARObject, CollectableElement , FibexElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			





Class	GlobalTimeDomain			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
debounceTime	TimeValue	0..1	attr	Defines the minimum amount of time between two time sync messages are transmitted.
domainId	PositiveInteger	0..1	attr	This represents the ID of the GlobalTimeDomain used in the network messages sent on behalf of global time management. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild
gateway	GlobalTimeGateway	*	aggr	A GlobalTimeGateway may exist in the context of a GlobalTimeDomain to actively update the global time information as it is routed from one GlobalTimeDomain to another. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=gateway.shortName, gateway.variationPoint.shortLabel vh.latestBindingTime=postBuild
globalTimeCorrectionProps	GlobalTimeCorrectionProps	0..1	aggr	Defintion of attributes for rate and offset correction.
globalTimeDomainProperty	AbstractGlobalTimeDomainProps	0..1	aggr	Additional properties of the GlobalTimeDomain. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=globalTimeDomainProperty, globalTimeDomainProperty.variationPoint.shortLabel vh.latestBindingTime=postBuild
globalTimeMaster	GlobalTimeMaster	0..1	aggr	This represents the single master of a GlobalTimeDomain. A GlobalTimeDomain may have no GlobalTimeDomain.master, e.g. when it gets its time from a GPS receiver. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=globalTimeMaster.shortName, globalTimeMaster.variationPoint.shortLabel vh.latestBindingTime=postBuild
globalTimeSubDomain	GlobalTimeDomain	*	ref	By this means it is possible to create a hierarchy of sub Domains where one global time domain can declare one or more other global time domains as its subDomains. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=globalTimeSubDomain.globalTimeDomain, globalTimeSubDomain.variationPoint.shortLabel vh.latestBindingTime=postBuild
icvFreshnessValueId	PositiveInteger	0..1	attr	This attribute defines the Id of the Freshness Value for the Integrity Check Value (ICV) calculation and verification.
icvSecureComProps	SecOcSecureComProps	0..1	ref	Reference to a SecureComProps definition to be used for the Integrity Check Value (ICV) calculation and verification. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=icvSecureComProps.secOcSecureComProps, icvSecureComProps.variationPoint.shortLabel vh.latestBindingTime=postBuild
maxProgressionMismatchThreshold	TimeValue	0..1	attr	This attribute defines the maximum allowed difference between local time and fallback time of the time base in seconds.
networkSegmentId	NetworkSegmentIdentification	0..1	aggr	Defines the numerical identification of a GlobalTime sub domain.





Class	GlobalTimeDomain			
pduTriggering	PduTriggering	0..1	ref	This PduTriggering will be taken to transmit the global time information from a GlobalTimeMaster to a the associated GlobalTimeSlaves. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=pduTriggering.pduTriggering, pduTriggering.variationPoint.shortLabel vh.latestBindingTime=postBuild
slave	GlobalTimeSlave	*	aggr	This represents the collections of slaves of the Global TimeDomain. A GlobalTimeDomain may have no Global TimeDomain.slaves, e.g. when it propagates its time directly to sub domains. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=slave.shortName, slave.variationPoint.shortLabel vh.latestBindingTime=postBuild
syncLoss Timeout	TimeValue	0..1	attr	This attribute describes the timeout for the situation that the time synchronization gets lost in the scope of the time domain.

Table A.290: GlobalTimeDomain

Class	Grant (abstract)			
Note	This meta-class serves as the abstract base class for defining specific Grants Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Subclasses	ComGrant , ComOfferServiceGrant			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.291: Grant

Class	HealthChannel (abstract)			
Note	This element defines the source of a health channel. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable			
Subclasses	HealthChannelSupervision			
Aggregated by	PlatformHealthManagementContribution.healthChannel			
Attribute	Type	Mult.	Kind	Note
recovery Notification	RecoveryNotification	*	ref	Defines the RecoveryNotification for this HealthChannel.

Table A.292: HealthChannel

Class	HealthChannelSupervision			
Note	This element defines a health channel representing the status of a PhmSupervision. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, HealthChannel , Identifiable , MultilanguageReferrable, Referrable			





Class	HealthChannelSupervision			
Aggregated by	PlatformHealthManagementContribution.healthChannel			
Attribute	Type	Mult.	Kind	Note
supervision	GlobalSupervision	0..1	ref	Reference to the GlobalSupervision as source for the health channel.

Table A.293: HealthChannelSupervision

Class	IEEE1722AcfBusPartRawDataStreamConsumerMapping			
Note	This meta-class represents the ability to map a consumer PortPrototype to an Ethernet-Mac-layer IEEE1722 ACF based communication for a whole bus (Can or Lin). Tags: atp.Status=candidate atp.recommendedPackage=RawDataStreamingMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement , ARObject , CollectableElement , EthernetMacRawDataStreamMapping , IEEE1722RawDataStreamMapping , Identifiable , MultilanguageReferrable , PackageableElement , RawDataStreamMapping , Referrable , UploadableDeploymentElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
acfBusPart	IEEE1722TpAcfBusPart	*	ref	Reference to the ACF bus parts (Can or Lin frames) which shall be handled by this mapping. Tags: atp.Status=candidate

Table A.294: IEEE1722AcfBusPartRawDataStreamConsumerMapping

Class	IEEE1722AcfBusRawDataStreamConsumerMapping			
Note	This meta-class represents the ability to map a consumer PortPrototype to an Ethernet-Mac-layer IEEE1722 ACF based communication for a whole bus (Can or Lin). Tags: atp.Status=candidate atp.recommendedPackage=RawDataStreamingMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement , ARObject , CollectableElement , EthernetMacRawDataStreamMapping , IEEE1722RawDataStreamMapping , Identifiable , MultilanguageReferrable , PackageableElement , RawDataStreamMapping , Referrable , UploadableDeploymentElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
acfBus	IEEE1722TpAcfBus	*	ref	Reference to the ACF buses which shall be handled by this mapping. Tags: atp.Status=candidate

Table A.295: IEEE1722AcfBusRawDataStreamConsumerMapping

Class	IEEE1722RawDataStreamConsumerMapping			
Note	This meta-class represents the ability to map a consumer PortPrototype to an Ethernet-Mac-layer IEEE1722 based communication. Tags: atp.Status=candidate atp.recommendedPackage=RawDataStreamingMappings This Class is only used by the AUTOSAR Adaptive Platform.			





Class	IEEE1722RawDataStreamConsumerMapping			
Base	ARElement, ARObject, CollectableElement, EthernetMacRawDataStreamMapping , IEEE1722RawDataStreamMapping, Identifiable , MultilanguageReferrable, PackageableElement, RawDataStreamMapping, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
ieee1722Stream	IEEE1722TpConnection	0..1	ref	Reference to the IEEE1722TpConnection. Tags: atp.Status=candidate

Table A.296: IEEE1722RawDataStreamConsumerMapping

Class	IEEE1722RawDataStreamProducerMapping			
Note	This meta-class represents the ability to map a producer PortPrototype to an Ethernet-Mac-layer IEEE1722 based communication. Tags: atp.Status=candidate atp.recommendedPackage=RawDataStreamingMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, EthernetMacRawDataStreamMapping , IEEE1722RawDataStreamMapping, Identifiable , MultilanguageReferrable, PackageableElement, RawDataStreamMapping, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
ieee1722Stream	IEEE1722TpConnection	0..1	ref	Reference to the IEEE1722TpConnection. Tags: atp.Status=candidate

Table A.297: IEEE1722RawDataStreamProducerMapping

Class	IPSecRule			
Note	This element defines an IPsec rule that describes communication traffic that is monitored, protected and filtered.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	IPSecConfig.ipSecRule			
Attribute	Type	Mult.	Kind	Note
direction	CommunicationDirectionType	0..1	attr	This attribute defines the direction in which the traffic is monitored. If this attribute is not set a bidirectional traffic monitoring is assumed.
headerType	IPsecHeaderTypeEnum	0..1	attr	Header type specifying the IPsec security mechanism.
ipProtocol	IPsecIpProtocolEnum	0..1	attr	This attribute defines the relevant IP protocol used in the Security Policy Database (SPD) entry.
localCertificate	CryptoServiceCertificate	*	ref	This reference identifies the applicable certificate used for a local authentication.
localId	String	0..1	attr	This attribute defines how the local participant should be identified for authentication.
localPortRangeEnd	PositiveInteger	0..1	attr	This attribute restricts the traffic monitoring and defines an end value for the local port range. If this attribute is not set then this rule shall be effective for all local ports. Please note that port ranges are currently not supported in the AUTOSAR AP's operating system backend. If AP systems are involved, each IPsec rule may only contain a single port.





Class	IPSecRule			
localPortRangeStart	PositiveInteger	0..1	attr	This attribute restricts the traffic monitoring and defines a start value for the local port range. If this attribute is not set then this rule shall be effective for all local ports. Please note that port ranges are currently not supported in the AUTOSAR AP's operating system backend. If AP systems are involved, each IPsec rule may only contain a single port.
mode	IPsecModeEnum	0..1	attr	This attribute defines the type of the connection.
policy	IPsecPolicyEnum	0..1	attr	An IPsec policy defines the rules that determine which type of IP traffic needs to be secured using IPsec and how that traffic is secured.
preSharedKey	CryptoServiceKey	0..1	ref	This reference identifies the applicable cryptographic key used for authentication.
priority	PositiveInteger	0..1	attr	This attribute defines the priority of the IPSecRule (SPD entry). The processing of entries is based on priority, starting with the highest priority "0".
remoteCertificate	CryptoServiceCertificate	*	ref	This reference identifies the applicable certificate used for a remote authentication.
remoteId	String	0..1	attr	This attribute defines how the remote participant should be identified for authentication.
remoteIp Address	NetworkEndpoint	*	ref	Definition of the remote NetworkEndpoint. With this reference the connection between the local Network Endpoint and the remote NetworkEndpoint is described on which the traffic is monitored.
remotePortRangeEnd	PositiveInteger	0..1	attr	This attribute restricts the traffic monitoring and defines an end value for the remote port range. If this attribute is not set then this rule shall be effective for all local ports. Please note that port ranges are currently not supported in the AUTOSAR AP's operating system backend. If AP systems are involved, each IPsec rule may only contain a single port.
remotePortRangeStart	PositiveInteger	0..1	attr	This attribute restricts the traffic monitoring and defines a start value for the remote port range. If this attribute is not set then this rule shall be effective for all local ports. Please note that port ranges are currently not supported in the AUTOSAR AP's operating system backend. If AP systems are involved, each IPsec rule may only contain a single port.

Table A.298: IPSecRule

Class	ISignal
Note	Signal of the Interaction Layer. The RTE supports a "signal fan-out" where the same System Signal is sent in different SignalIPdus to multiple receivers. To support the RTE "signal fan-out" each SignalIPdu contains ISignals. If the same System Signal is to be mapped into several SignalIPdus there is one ISignal needed for each ISignalToIPduMapping. ISignals describe the Interface between the Precompile configured RTE and the potentially Postbuild configured Com Stack (see ECUC Parameter Mapping). In case of the SystemSignalGroup an ISignal shall be created for each SystemSignal contained in the SystemSignalGroup. Tags: atp.recommendedPackage=ISignals
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , <i>FibexElement</i> , Identifiable , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , Referrable , <i>UploadableDesignElement</i> , <i>UploadablePackageElement</i>
Aggregated by	ARPackage.element





Class	ISignal			
Attribute	Type	Mult.	Kind	Note
dataTransformation	DataTransformation	0..1	ref	Optional reference to a DataTransformation which represents the transformer chain that is used to transform the data that shall be placed inside this ISignal. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dataTransformation.dataTransformation, dataTransformation.variationPoint.shortLabel vh.latestBindingTime=codeGenerationTime
dataTypePolicy	DataTypePolicyEnum	0..1	attr	With the aggregation of SwDataDefProps an ISignal specifies how it is represented on the network. This representation follows a particular policy. Note that this causes some redundancy which is intended and can be used to support flexible development methodology as well as subsequent integrity checks. If the policy "networkRepresentationFromComSpec" is chosen the network representation from the ComSpec that is aggregated by the PortPrototype shall be used. If the "override" policy is chosen the requirements specified in the PortInterface and in the ComSpec are not fulfilled by the networkRepresentationProps. In case the System Description doesn't use a complete Software Component Description (VFB View) the "legacy" policy can be chosen.
initValue	ValueSpecification	0..1	aggr	Optional definition of a ISignal's initValue in case the System Description doesn't use a complete Software Component Description (VFB View). This supports the inclusion of legacy system signals. This value can be used to configure the Signal's "Init Value". If a full DataMapping exist for the SystemSignal this information may be available from a configured Sender ComSpec and ReceiverComSpec. In this case the initvalues in SenderComSpec and/or ReceiverComSpec override this optional value specification. Further restrictions apply from the RTE specification.
iSignalProps	ISignalProps	0..1	aggr	Additional optional ISignal properties that may be stored in different files. Stereotypes: atpSplitable Tags: atp.Splitkey=iSignalProps
iSignalType	ISignalTypeEnum	0..1	attr	This attribute defines whether this iSignal is an array that results in a UINT8_N / UINT8_DYN ComSignalType in the COM configuration or a primitive type.
length	UnlimitedInteger	0..1	attr	Size of the signal in bits. The size needs to be derived from the mapped VariableDataPrototype according to the mapping of primitive DataTypes to BaseTypes as used in the RTE. Indicates maximum size for dynamic length signals. The ISignal length of zero bits is allowed.





Class	ISignal			
network Representation Props	SwDataDefProps	0..1	aggr	<p>Specification of the actual network representation. The usage of SwDataDefProps for this purpose is restricted to the attributes compuMethod and baseType. The optional baseType attributes "memAlignment" and "byteOrder" shall not be used.</p> <p>The attribute "dataTypePolicy" in the SystemTemplate element defines whether this network representation shall be ignored and the information shall be taken over from the network representation of the ComSpec.</p> <p>If "override" is chosen by the system integrator the network representation can violate against the requirements defined in the PortInterface and in the network representation of the ComSpec.</p> <p>In case that the System Description doesn't use a complete Software Component Description (VFB View) this element is used to configure "ComSignalDataInvalid Value" and the Data Semantics.</p> <p>Stereotypes: atp.Splittable Tags: atp.Splitkey=networkRepresentationProps</p>
reception DefaultValue (ordered)	ValueSpecification	*	aggr	<p>Value used to fill data on the receiver side, if less then expected data is received.</p> <p>The value is expected to cover the entire expected ISignal network payload.</p> <p>Tags: atp.Status=obsolete</p>
systemSignal	SystemSignal	0..1	ref	<p>Reference to the System Signal that is supposed to be transmitted in the ISignal.</p>
timeout Substitution Value	ValueSpecification	0..1	aggr	<p>Defines and enables the ComTimeoutSubstitution for this ISignal.</p>
transformation ISignalProps	TransformationISignal Props	*	aggr	<p>A transformer chain consists of an ordered list of transformers. The ISignal specific configuration properties for each transformer are defined in the TransformationISignalProps class. The transformer configuration properties that are common for all ISignals are described in the TransformationTechnology class.</p> <p>Stereotypes: atp.Splittable Tags: atp.Splitkey=transformationISignalProps</p>

Table A.299: ISignal

Class	ISignalGroup			
Note	<p>SignalGroup of the Interaction Layer. The RTE supports a "signal fan-out" where the same System Signal Group is sent in different SignalPdus to multiple receivers.</p> <p>An ISignalGroup refers to a set of ISignals that shall always be kept together. A ISignalGroup represents a COM Signal Group.</p> <p>Therefore it is recommended to put the ISignalGroup in the same Package as ISignals (see atp.recommendedPackage)</p> <p>Tags: atp.recommendedPackage=ISignalGroups</p>			
Base	ARElement, ARObject, CollectableElement, FibexElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	ISignalGroup			
comBasedSignalGroupTransformation	DataTransformation	0..1	ref	Optional reference to a DataTransformation which represents the transformer chain that is used to transform the data that shall be placed inside this ISignalGroup based on the COMBasedTransformer approach. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=comBasedSignalGroupTransformation.dataTransformation, comBasedSignalGroupTransformation.variationPoint.shortLabel vh.latestBindingTime=codeGenerationTime
iSignal	ISignal	*	ref	Reference to a set of ISignals that shall always be kept together.
systemSignalGroup	SystemSignalGroup	0..1	ref	Reference to the SystemSignalGroup that is defined on VFB level and that is supposed to be transmitted in the ISignalGroup.
transformationISignalProps	TransformationISignalProps	*	aggr	A transformer chain consists of an ordered list of transformers. The ISignalGroup specific configuration properties for each transformer are defined in the TransformationISignalProps class. The transformer configuration properties that are common for all ISignalGroups are described in the TransformationTechnology class. Stereotypes: atpSplitable Tags: atp.Splitkey=transformationISignalProps

Table A.300: ISignalGroup

Class	ISignalIPdu			
Note	Represents the IPdus handled by Com. The ISignalIPdu assembled and disassembled in AUTOSAR COM consists of one or more signals. In case no multiplexing is performed this IPdu is routed to/from the Interface Layer. A maximum of one dynamic length signal per IPdu is allowed. Tags: atp.recommendedPackage=Pdus			
Base	<i>ARElement, ARObject, CollectableElement, FibexElement, IPdu, Identifiable, MultilanguageReferrable, PackageableElement, Pdu, Referrable, UploadableDesignElement, UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
iPduTimingSpecification	IPduTiming	0..1	aggr	Timing specification for Com IPdus (Transmission Modes). This information is mandatory for the sender in a System Extract. This information may be omitted on receivers in a System Extract. atpVariation: The timing of a Pdu can vary. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=iPduTimingSpecification, iPduTimingSpecification.variationPoint.shortLabel vh.latestBindingTime=postBuild
iSignalToPduMapping	ISignalToIPduMapping	*	aggr	Definition of SignalToIPduMappings included in the Signal IPdu. atpVariation: The content of a PDU can be variable. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=iSignalToPduMapping.shortName, iSignalToPduMapping.variationPoint.shortLabel vh.latestBindingTime=postBuild





Class	ISignalIPdu			
unusedBitPattern	Integer	0..1	attr	AUTOSAR COM and AUTOSAR IPDUM are filling not used areas of an IPDU with this bit-pattern. This attribute is mandatory to avoid undefined behavior. This byte-pattern will be repeated throughout the IPdu.

Table A.301: ISignalIPdu

Class	ISignalPort			
Note	Connectors reception or send port on the referenced channel referenced by an ISignalTriggering. If different timeouts or DataFilters for ISignals need to be specified several ISignalPorts may be created.			
Base	ARObject, CommConnectorPort , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	CommunicationConnector .ecuCommPortInstance			
Attribute	Type	Mult.	Kind	Note
dataFilter	DataFilter	0..1	aggr	Optional specification of a signal COM filter at the receiver side in case that the System Description doesn't use a complete Software Component Description (VFB View). This supports the inclusion of legacy system signals. If a full DataMapping exist for the SystemSignal this information may be available from a configured ReceiverComSpec. In this case the ReceiverComSpec overrides this optional specification.
ddsQosProfile	DdsCpQosProfile	0..1	ref	Reference to the DDS Qos profile used for this ISignal. Tags: atp.Status=candidate
firstTimeout	TimeValue	0..1	attr	<ul style="list-style-type: none"> ISignalPort with communicationDirection = in: Optional first timeout value in seconds for the reception of the ISignal. ISignalPort with communicationDirection = out: Optional first timeout value in seconds for transmission deadline monitoring.
handleInvalid	HandleInvalidEnum	0..1	attr	This attribute defines how invalidation is applied to the ISignals received in the context of this ISignalPort.
timeout	TimeValue	0..1	attr	<ul style="list-style-type: none"> ISignalPort with communicationDirection = in: Optional timeout value in seconds for the reception of the ISignal. The attribute value is used to configure the Com Timeout in the COM module. The RTE ignores this attribute. The timeout can also be specified with the NonqueuedReceiverComSpec.aliveTimeout attribute. If a full DataMapping exists for the SystemSignal and the value is available in the configured ReceiverComSpec, then the timeout value in the ReceiverComSpec overrides this optional timeout specification during the creation of the Base Ecu Configuration of the COM module. ISignalPort with communicationDirection = out: Optional timeout value in seconds for the transmission of the ISignal. The attribute value is used to configure the ComTimeout in the COM module. The RTE ignores this attribute. The timeout can also be specified with the SenderComSpec.transmissionAcknowledge.timeout attribute. If a full DataMapping exists for the SystemSignal and the value is available in the configured SenderComSpec, then the timeout value in the SenderComSpec overrides this optional timeout specification during the creation of the Base Ecu Configuration of the COM module.





Class	ISignalPort			
				<p>This attribute can be used in the following cases:</p> <ul style="list-style-type: none"> • legacy signal where the System Description doesn't use a complete Software Component Description (VFB View) and where the DataMapping is missing. • bus monitoring use cases in which the DataMapping is ignored.

Table A.302: ISignalPort

Class	ISignalToIPduMapping			
Note	An ISignalToIPduMapping describes the mapping of ISignals to ISignalIPdus and defines the position of the ISignal within an ISignalIPdu.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ISignalIPdu.iSignalToPduMapping , NmPdu.iSignalToIPduMapping			
Attribute	Type	Mult.	Kind	Note
iSignal	ISignal	0..1	ref	Reference to a ISignal that is mapped into the ISignal IPdu. Each ISignal contained in the ISignalGroup shall be mapped into an IPdu by an own ISignalToIPduMapping. The references to the ISignal and to the ISignalGroup in an ISignalToIPduMapping are mutually exclusive.
iSignalGroup	ISignalGroup	0..1	ref	Reference to an ISignalGroup that is mapped into the SignalIPdu. If an ISignalToIPduMapping for an ISignal Group is defined, only the UpdateIndicationBitPosition and the transferProperty is relevant. The startPosition and the packingByteOrder shall be ignored. Each ISignal contained in the ISignalGroup shall be mapped into an IPdu by an own ISignalToIPduMapping. The references to the ISignal and to the ISignalGroup in an ISignalToIPduMapping are mutually exclusive.
packingByteOrder	ByteOrderEnum	0..1	attr	This parameter defines the order of the bytes of the signal and the packing into the SignalIPdu. The byte ordering "Little Endian" (MostSignificantByteLast), "Big Endian" (MostSignificantByteFirst) and "Opaque" can be selected. For opaque data endianness conversion shall be configured to Opaque. The value of this attribute impacts the absolute position of the signal into the SignalIPdu (see the startPosition attribute description). For an ISignalGroup the packingByteOrder is irrelevant and shall be ignored.
startPosition	UnlimitedInteger	0..1	attr	This parameter is necessary to describe the bitposition of a signal within an SignalIPdu. It denotes the least significant bit for "Little Endian" and the most significant bit for "Big Endian" packed signals within the IPdu (see the description of the packingByteOrder attribute). In AUTOSAR the bit counting is always set to "sawtooth" and the bit order is set to "Decreasing". The bit counting in byte 0 starts with bit 0 (least significant bit). The most significant bit in byte 0 is bit 7. Please note that the way the bytes will be actually sent on the bus does not impact this representation: they will always be seen by the software as a byte array. If a mapping for the ISignalGroup is defined, this attribute is irrelevant and shall be ignored.
transferProperty	TransferPropertyEnum	0..1	attr	Defines how the referenced ISignal contributes to the send triggering of the ISignalIPdu.





Class	ISignalToIPduMapping			
updateIndicationBitPosition	UnlimitedInteger	0..1	attr	<p>The UpdateIndicationBit indicates to the receivers that the signal (or the signal group) was updated by the sender. Length is always one bit. The UpdateIndicationBitPosition attribute describes the position of the update bit within the SignalIPdu. For Signals of a ISignalGroup this attribute is irrelevant and shall be ignored.</p> <p>Note that the exact bit position of the updateIndicationBitPosition is linked to the value of the attribute packingByteOrder because the method of finding the bit position is different for the values mostSignificantByteFirst and mostSignificantByteLast. This means that if the value of packingByteOrder is changed while the value of updateIndicationBitPosition remains unchanged the exact bit position of updateIndicationBitPosition within the enclosing ISignalIPdu still undergoes a change.</p> <p>This attribute denotes the least significant bit for "Little Endian" and the most significant bit for "Big Endian" packed signals within the IPdu (see the description of the packingByteOrder attribute). In AUTOSAR the bit counting is always set to "sawtooth" and the bit order is set to "Decreasing". The bit counting in byte 0 starts with bit 0 (least significant bit). The most significant bit in byte 0 is bit 7.</p>

Table A.303: ISignalToIPduMapping

Class	ISignalTriggering			
Note	A ISignalTriggering allows an assignment of ISignals to physical channels.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	PhysicalChannel.iSignalTriggering			
Attribute	Type	Mult.	Kind	Note
iSignal	ISignal	0..1	ref	This reference shall be used if an ISignal is transported on the PhysicalChannel. This reference forms an XOR relationship with the ISignalTriggering-ISignalGroup reference.
iSignalGroup	ISignalGroup	0..1	ref	This reference shall be used if an ISignalGroup is transported on the PhysicalChannel. This reference forms an XOR relationship with the ISignalTriggering-ISignal reference.
iSignalPort	ISignalPort	*	ref	References to the ISignalPort on every ECU of the system which sends and/or receives the ISignal. References for both the sender and the receiver side shall be included when the system is completely defined.

Table A.304: ISignalTriggering

Class	Identifiable (abstract)
Note	Instances of this class can be referred to by their identifier (within the namespace borders). In addition to this, Identifiables are objects which contribute significantly to the overall structure of an AUTOSAR description. In particular, Identifiables might contain Identifiables.
Base	ARObject, MultilanguageReferrable , Referrable





Class	Identifiable (abstract)			
Subclasses	ARPackage, AbstractDolpLogicAddressProps, AbstractEvent, AbstractFunctionalClusterDesign, AbstractImplementationDataTypeElement, AbstractSecurityEventFilter, AbstractSecurityIdsmInstanceFilter, AbstractServiceInstance, AbstractSignalBasedToSignalTriggeringMapping, AdaptiveSwcInternalBehavior, ApApplicationEndpoint, ApmcAbstractDefinition, ApmcConfigurationElementDef, ApmcContainerElementValue, ApmcContainerValue, ApmcEnumerationLiteralDef, ApplicationEndpoint, ApplicationError, AppliedStandard, ArtifactChecksum, ArtifactLocator, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpFeature, AutosarOperationArgumentInstance, AutosarVariableInstance, BuildActionEntity, BuildActionEnvironment, Chapter, CheckpointTransition, ClientIdDefinition, ClientServerOperation, Code, CollectableElement, ComManagementMapping, CommConnectorPort, CommunicationConnector, CommunicationController, Compiler, ConsistencyNeeds, ConsumedEventGroup, CouplingPort, CouplingPortAbstractShaper, CouplingPortStructuralElement, CryptoCertificate, CryptoCertificateGroup, CryptoKeySlot, CryptoKeySlotDesign, CryptoKeySlotUsageDesign, CryptoProvider, CryptoServiceMapping, DataPrototypeGroup, DataPrototypeTransformationPropsIdent, DataTransformation, DdsAbstractServiceInstanceElementCp, DdsCpDomain, DdsCpPartition, DdsCpQosProfile, DdsCpTopic, DdsDomainRange, DependencyOnArtifact, DiagEventDebounceAlgorithm, DiagnosticAbstractSovdContent, DiagnosticAuthTransmitCertificateEvaluation, DiagnosticConnectedIndicator, DiagnosticDataElement, DiagnosticDebounceAlgorithmProps, DiagnosticExtendedDataRecordElement, DiagnosticFunctionInhibitSource, DiagnosticParameterElement, DiagnosticRoutineSubfunction, DiagnosticSovdMethodPrimitive, DltApplication, DltArgument, DltArgumentProps, DltMessage, DolpInterface, DolpLogicAddress, DolpLogicalAddress, DolpNetworkConfigurationDesign, DolpRoutingActivation, E2EProfileConfiguration, End2EndEventProtectionProps, End2EndMethodProtectionProps, EthernetWakeupSleepOnDataLineConfig, EventHandler, EventMapping, ExclusiveArea, ExecutableEntity, ExecutionTime, FMAttributeDef, FMFeatureMapAssertion, FMFeatureMapCondition, FMFeatureMapElement, FMFeatureRelation, FMFeatureRestriction, FMFeatureSelection, FieldMapping, FireAndForgetMethodMapping, FlexrayArTpNode, FlexrayTpPduPool, FrameTriggering, GeneralParameter, GlobalSupervision, GlobalTimeGateway, GlobalTimeMaster, GlobalTimeSlave, HealthChannel, HeapUsage, HwAttributeDef, HwAttributeLiteralDef, HwPin, HwPinGroup, IEEE1722TpAcfBus, IEEE1722TpAcfBusPart, IPSecRule, IPv6ExtHeaderFilterList, ISignalToIPduMapping, ISignalTriggering, IdentCaption, ImpositionTime, InternalTriggeringPoint, Keyword, LifeCycleState, Linker, MacAddressVlanMembership, MacMulticastGroup, MacSecKayParticipant, McDataInstance, MemorySection, MemoryUsage, MethodMapping, ModeDeclaration, ModeDeclarationMapping, ModeSwitchPoint, ModeSwitchSenderComSpecProps, NetworkEndpoint, NmCluster, NmNode, PackageableElement, ParameterAccess, PduActivationRoutingGroup, PduToFrameMapping, PduTriggering, PerInstanceMemory, PersistencyDeploymentElement, PersistencyInterfaceElement, PhmSupervision, PhysicalChannel, PortGroup, PortInterfaceMapping, ProcessToMachineMapping, Processor, ProcessorCore, PskIdentityToKeySlotMapping, QueuedReceiverComSpecProps, ResourceConsumption, ResourceGroup, RootSwClusterDesignComponentPrototype, RootSwComponentPrototype, RootSwCompositionPrototype, RptComponent, RptContainer, RptExecutableEntity, RptExecutableEntityEvent, RptExecutionContext, RptProfile, RptServicePoint, RunnableEntityGroup, SdgAttribute, SdgClass, SecOcJobMapping, SecOcJobRequirement, SecureCommunicationAuthenticationProps, SecureCommunicationDeployment, SecureCommunicationFreshnessProps, SecurityEventContextDataElement, SecurityEventContextProps, ServerComSpecProps, ServiceInterfaceDeploymentElement, ServiceInterfaceElementSecureComConfig, ServiceNeeds, SignalServiceTranslationEventProps, SignalServiceTranslationProps, SocketAddress, SoftwarePackageStep, SomeipEventGroup, SomeipProvidedEventGroup, SomeipTpChannel, StackUsage, StateManagementActionItem, StateManagementActionList, StateManagementStateNotification, StateManagementStateRequest, StaticSocketConnection, StructuredReq, SupervisionCheckpoint, SupervisionMode, SupervisionModeCondition, SwGenericAxisParamType, SwServiceArg, SwcServiceDependency, SystemMapping, TimeBaseResource, TimingClock, TimingClockSyncAccuracy, TimingCondition, TimingConstraint, TimingDescription, TimingExtensionResource, TimingModelInstance, TlsCryptoCipherSuite, TlsCryptoCipherSuiteProps, TlsJobMapping, Topic1, TpAddress, TraceableTable, TraceableText, TracedFailure, TransformationSignalPropsIdent, TransformationProps, TransformationTechnology, Trigger, UcmDescription, UcmRetryStrategy, UcmStep, UriDescription, VariableAccess, VariationPointProxy, VehicleRolloutStep, ViewMap, VlanConfig, WaitPoint			
Attribute	Type	Mult.	Kind	Note
adminData	AdminData	0..1	aggr	This represents the administrative data for the identifiable object. Stereotypes: atpSplitable Tags: atp.Splitkey=adminData xml.sequenceOffset=-40





Class	<i>Identifiable</i> (abstract)			
annotation	Annotation	*	aggr	Possibility to provide additional notes while defining a model element (e.g. the ECU Configuration Parameter Values). These are not intended as documentation but are mere design notes. Tags: xml.sequenceOffset=-25
category	CategoryString	0..1	attr	The category is a keyword that specializes the semantics of the Identifiable. It affects the expected existence of attributes and the applicability of constraints. Tags: xml.sequenceOffset=-50
desc	MultiLanguageOverviewParagraph	0..1	aggr	This represents a general but brief (one paragraph) description what the object in question is about. It is only one paragraph! Desc is intended to be collected into overview tables. This property helps a human reader to identify the object in question. More elaborate documentation, (in particular how the object is built or used) should go to "introduction". Tags: xml.sequenceOffset=-60
introduction	DocumentationBlock	0..1	aggr	This represents more information about how the object in question is built or is used. Therefore it is a DocumentationBlock. Tags: xml.sequenceOffset=-30
uuid	String	0..1	attr	The purpose of this attribute is to provide a globally unique identifier for an instance of a meta-class. The values of this attribute should be globally unique strings prefixed by the type of identifier. For example, to include a DCE UUID as defined by The Open Group, the UUID would be preceded by "DCE:". The values of this attribute may be used to support merging of different AUTOSAR models. The form of the UUID (Universally Unique Identifier) is taken from a standard defined by the Open Group (was Open Software Foundation). This standard is widely used, including by Microsoft for COM (GUIDs) and by many companies for DCE, which is based on CORBA. The method for generating these 128-bit IDs is published in the standard and the effectiveness and uniqueness of the IDs is not in practice disputed. If the id namespace is omitted, DCE is assumed. An example is "DCE:2fac1234-31f8-11b4-a222-08002b34c003". The uuid attribute has no semantic meaning for an AUTOSAR model and there is no requirement for AUTOSAR tools to manage the timestamp. Tags: xml.attribute=true

Table A.305: Identifiable

Class	<i>IdsPlatformInstantiation</i> (abstract)			
Note	This meta-class acts as an abstract base class for platform modules that implement the intrusion detection system. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AdaptiveModuleInstantiation, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable , MultilanguageReferrable , NonOsModuleInstantiation , Referrable			
Subclasses	IdsmModuleInstantiation			
Aggregated by	AtpClassifier.atpFeature, Machine.moduleInstantiation			
Attribute	Type	Mult.	Kind	Note





Class	IdsPlatformInstantiation (abstract)			
idsTimeBase	TimeBaseResource	*	ref	This reference identifies the applicable time base resource. Stereotypes: atpSplittable Tags: atp.Splitkey=idsTimeBase atp.Status=candidate
network Interface	PlatformModule EthernetEndpoint Configuration	*	ref	This association contains the network configuration that shall be applied to an instance of an IDS entity. Tags: atp.Status=candidate

Table A.306: IdsPlatformInstantiation

Class	IdsmContextProviderInterface			
Note	This meta-class provides the ability to define a PortInterface for providing a Context for security events in the context of the intrusion detection system. Tags: atp.recommendedPackage=IdsmPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObjct, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, IdsmAbstractPortInterface, MultilanguageReferrable, PackageableElement, PortInterface, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.307: IdsmContextProviderInterface

Class	IdsmContextProviderMapping			
Note	This meta-class represents the ability to define a mapping between an IdsMInstance and a Process on target-configuration level to a given PortPrototype that is typed by a IdsmContextProviderInterface. Tags: atp.recommendedPackage=IdsmProviderMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObjct, CollectableElement, Identifiable, MultilanguageReferrable, Packageable Element, Referrable, UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
idsPlatform Instantiation	IdsPlatformInstantiation	0..1	ref	This represents the IdsM functional cluster. Tags: atp.Status=candidate
pPortPrototype InExecutable	PPortPrototype	0..1	iref	This reference identifies the mapped PortPrototype in the application software. Stereotypes: atpUriDef InstanceRef implemented by: PPortPrototypeIn ExecutableInstanceRef
process	Process	0..1	ref	This reference identifies the process in which the application runs.

Table A.308: IdsmContextProviderMapping

Class	IdsmModuleInstantiation			
Note	This meta-class defines the attributes for the IdsM configuration on a specific machine. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			





Class	IdsmModuleInstantiation			
Base	ARObject, AdaptiveModuleInstantiation, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable , IdsPlatformInstantiation , MultilanguageReferrable, NonOsModuleInstantiation , Referrable			
Aggregated by	AtpClassifier.atpFeature, Machine.moduleInstantiation			
Attribute	Type	Mult.	Kind	Note
reportable SecurityEvent	SecurityEventMapping	*	ref	Collection of reportable instances of security events. Stereotypes: atpSplitable Tags: atp.Splitkey=reportableSecurityEvent atp.Status=candidate

Table A.309: IdsmModuleInstantiation

Class	IdsmQualifiedEventReceiverInterface			
Note	This meta-class provides the ability to define a PortInterface for receiving qualified security events in the context of the intrusion detection system. Tags: atp.recommendedPackage=IdsmPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable , IdsmAbstractPortInterface, MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.310: IdsmQualifiedEventReceiverInterface

Class	IdsmQualifiedEventReceiverMapping			
Note	This meta-class represents the ability to define a mapping between an IdsM Module Instance and a Process on deployment level to a given PortPrototype that is typed by a IdsmQualifiedEventReceiver Interface. Tags: atp.recommendedPackage=IdsmReceiverMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
idsPlatform Instantiation	IdsPlatformInstantiation	0..1	ref	This represents the IdsM functional cluster. Tags: atp.Status=candidate
process	Process	0..1	ref	This reference identifies the process in which the application runs.
rPortPrototype InExecutable	RPortPrototype	0..1	iref	This reference identifies the mapped RPortPrototype in the application software. Stereotypes: atpUriDef InstanceRef implemented by: RPortPrototypeInExecutableInstanceRef

Table A.311: IdsmQualifiedEventReceiverMapping

Class	IdsmReportingModeProviderInterface			
Note	This meta-class provides the ability to define a PortInterface for setting and getting the reporting mode for security events in the context of the intrusion detection system. Tags: atp.recommendedPackage=IdsmPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			





Class	IdsmReportingModeProviderInterface			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, IdsmAbstractPortInterface, MultilanguageReferrable, PackageableElement, PortInterface, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.312: IdsmReportingModeProviderInterface

Class	IdsmReportingModeProviderMapping			
Note	This meta-class represents the ability to define a mapping between an IdsMInstance and a Process on target-configuration level to a given PortPrototype that is typed by a IdsmReportingModeProvider Interface. Tags: atp.recommendedPackage=IdsmProviderMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
idsPlatform Instantiation	IdsPlatformInstantiation	0..1	ref	This represents the IdsM functional cluster. Tags: atp.Status=candidate
process	Process	0..1	ref	This reference identifies the process in which the application runs
rPortPrototype InExecutable	RPortPrototype	0..1	iref	This reference identifies the mapped RPortPrototype in the application software. Stereotypes: atpUriDef InstanceRef implemented by: RPortPrototypeIn ExecutableInstanceRef

Table A.313: IdsmReportingModeProviderMapping

Class	IdsmTimestampProviderInterface			
Note	This meta-class provides the ability to define a PortInterface for providing a timestamp for security events in the context of the intrusion detection system. Tags: atp.recommendedPackage=IdsmPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, IdsmAbstractPortInterface, MultilanguageReferrable, PackageableElement, PortInterface, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.314: IdsmTimestampProviderInterface

Class	IdsmTimestampProviderMapping			
Note	This meta-class represents the ability to define a mapping between an IdsMInstance and a Process on target-configuration level to a given PortPrototype that is typed by a IdsmTimestampProviderInterface. Tags: atp.recommendedPackage=IdsmProviderMappings This Class is only used by the AUTOSAR Adaptive Platform.			





Class	IdsmTimestampProviderMapping			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
idsPlatform Instantiation	IdsPlatformInstantiation	0..1	ref	This represents the IdsM functional cluster. Tags: atp.Status=candidate
pPortPrototype InExecutable	PPortPrototype	0..1	iref	This reference identifies the mapped PortPrototype in the application software. Stereotypes: atp.UriDef InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	Process	0..1	ref	This reference identifies the process in which the application runs.

Table A.315: IdsmTimestampProviderMapping

Class	ImplementationDataTypeElementInPortInterfaceRef			
Note	This meta-class represents the ability to refer to the internal structure of an AutosarDataPrototype which is typed by an ImplementationDatatype in the context of a PortInterface. In other words, this meta-class shall not be used to model a reference to the AutosarDataPrototype as a target itself, even if the AutosarDataPrototype is typed by an ImplementationDataType and even if that ImplementationDataType represents a composite data type.			
Base	ARObject, DataPrototypeReference			
Aggregated by	DataPrototypeTransformationProps.dataPrototypeInPortInterfaceRef, SignalServiceTranslationElementProps.element, TransmissionComSpecProps.onChangeDataPrototype			
Attribute	Type	Mult.	Kind	Note
context Implementation DataElement (ordered)	AbstractImplementationDataTypeElement	*	ref	This is a context in case there are subelements with explicit types. The reference has to be ordered to properly reflect the nested structure. Tags: xml.sequenceOffset=20
rootData Prototype	AutosarDataPrototype	0..1	ref	This refers to the AutosarDataPrototype which is typed by the ImplementationDatatype. The targetDataPrototype and all defined contextDataPrototypes can be found within this rootDataPrototype. Tags: xml.sequenceOffset=10
target Implementation DataType Element	AbstractImplementationDataTypeElement	0..1	ref	This is a target ImplementationDataTypeElement in case that the rootDataPrototype is composite and the target is a subElement of the rootDataPrototype. Tags: xml.sequenceOffset=30

Table A.316: ImplementationDataTypeElementInPortInterfaceRef

Class	InterfaceMapping			
Note	This meta-class collects the mappings of elements of a single ServiceInterface to PortInterface elements of the AUTOSAR Classic Platform. Tags: atp.recommendedPackage=InterfaceMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
eventMapping	EventMapping	*	aggr	Mapping of a VariableDataPrototype in a SenderReceiver Interface to an Event in a ServiceInterface.





Class	InterfaceMapping			
fieldMapping	FieldMapping	*	aggr	Mapping of a Field in a ServiceInterface to ClientServer Operations that represent the getter and setter methods and to a VariableDataPrototype that represents the notifier in the Field.
fireAndForget MethodMapping	FireAndForgetMethodMapping	*	aggr	Mapping of a Fire&Forget Method that is located in a ServiceInterface to a VariableDataPrototype in a Sender ReceiverInterface or to a Trigger in a TriggerInterface.
methodMapping	MethodMapping	*	aggr	Mapping of a ClientServerOperation in a ClientServer Interface to a Method in a ServiceInterface.

Table A.317: InterfaceMapping

Class	Ipv4Configuration			
Note	Internet Protocol version 4 (IPv4) configuration.			
Base	<i>ARObject</i> , <i>NetworkEndpointAddress</i>			
Aggregated by	NetworkEndpoint.networkEndpointAddress			
Attribute	Type	Mult.	Kind	Note
assignment Priority	PositiveInteger	0..1	attr	Priority of assignment (1 is highest). If a new address from an assignment method with a higher priority is available, it overwrites the IP address previously assigned by an assignment method with a lower priority.
defaultGateway	Ip4AddressString	0..1	attr	IP address of the default gateway.
dnsServer Address	Ip4AddressString	*	attr	IP addresses of preconfigured DNS servers. Tags: xml.namePlural=DNS-SERVER-ADDRESSES
ipAddressKeep Behavior	IpAddressKeepEnum	0..1	attr	Defines the lifetime of a dynamically fetched IP address.
ipv4Address	Ip4AddressString	0..1	attr	IPv4 Address. Notation: 255.255.255.255. The IP Address shall be declared in case the ipv4AddressSource is FIXED and thus no auto-configuration mechanism is used. Stereotypes: atplIdentityContributor
ipv4Address Source	Ipv4AddressSource Enum	0..1	attr	Defines how the node obtains its IP address.
networkMask	Ip4AddressString	0..1	attr	Network mask. Notation 255.255.255.255
ttl	PositiveInteger	0..1	attr	Lifespan of data (0..255). The purpose of the TimeToLive field is to avoid a situation in which an undeliverable datagram keeps circulating on a system.

Table A.318: Ipv4Configuration

Class	Ipv6Configuration			
Note	Internet Protocol version 6 (IPv6) configuration.			
Base	<i>ARObject</i> , <i>NetworkEndpointAddress</i>			
Aggregated by	NetworkEndpoint.networkEndpointAddress			
Attribute	Type	Mult.	Kind	Note
assignment Priority	PositiveInteger	0..1	attr	Priority of assignment (1 is highest). If a new address from an assignment method with a higher priority is available, it overwrites the IP address previously assigned by an assignment method with a lower priority.
defaultRouter	Ip6AddressString	0..1	attr	IP address of the default router.
dnsServer Address	Ip6AddressString	*	attr	IP addresses of pre configured DNS servers. Tags: xml.namePlural=DNS-SERVER-ADDRESSES





Class	Ipv6Configuration			
enableAnycast	Boolean	0..1	attr	This attribute is used to enable anycast addressing (i.e. to one of multiple receivers).
hopCount	PositiveInteger	0..1	attr	The distance between two hosts. The hop count n means that n gateways separate the source host from the destination host (Range 0..255)
ipAddressKeep Behavior	IpAddressKeepEnum	0..1	attr	Defines the lifetime of a dynamically fetched IP address.
ipAddressPrefix Length	PositiveInteger	0..1	attr	IPv6 prefix length defines the part of the IPv6 address that is the network prefix.
ipv6Address	Ip6AddressString	0..1	attr	IPv6 Address. Notation: FFFF:::FFFF. The IP Address shall be declared in case the ipv6AddressSource is FIXED and thus no auto-configuration mechanism is used. Stereotypes: atpIdentityContributor
ipv6Address Source	Ipv6AddressSource Enum	0..1	attr	Defines how the node obtains its IP address.

Table A.319: Ipv6Configuration

Class	LTMessageCollectionToPortPrototypeMapping			
Note	This mapping element assigns a collection of Log or Trace messages to a PortPrototype of an application. Tags: atp.recommendedPackage=LTMessageCollectionToPortPrototypeMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObjct, CollectableElement, Identifiable , MultilanguageReferrable, Packageable Element, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
logAndTrace Message CollectionSet	LogAndTraceMessage CollectionSet	0..1	ref	Reference to a Collection of Log or Trace messages
rPort	RPortPrototype	0..1	iref	Reference to the RPortPrototype to which Log or Trace messages are assigned. InstanceRef implemented by: RPortPrototypeIn ExecutableInstanceRef

Table A.320: LTMessageCollectionToPortPrototypeMapping

Class	LogAndTraceInstantiation			
Note	This meta-class defines the attributes for the Log&Trace configuration on a specific machine. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AdaptiveModuleInstantiation, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable , MultilanguageReferrable, NonOsModuleInstantiation , Referrable			
Aggregated by	AtpClassifier.atpFeature, Machine.moduleInstantiation			
Attribute	Type	Mult.	Kind	Note
dltEcu	DltEcu	0..1	ref	Reference to the Ecu representation in the Log And Trace Extract.
logSink	DltLogSink	*	ref	Reference to output sinks for log or trace messages that are produced on the Machine.
sessionId Support	Boolean	0..1	attr	This attribute defines whether the sessionId is used or not.





Class	LogAndTraceInstantiation			
timeBase Resource	TimeBaseResource	*	ref	This reference is used to describe to which time base the Log and Trace module has access. From the Time Base Resource the Log and Trace module gets the needed information to generate the time stamp.

Table A.321: LogAndTraceInstantiation

Class	LogAndTraceInterface			
Note	This meta-class provides the ability to implement a PortInterface for support of Logging or Tracing. Tags: atp.recommendedPackage=PortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.322: LogAndTraceInterface

Class	LogicalSupervision			
Note	Defines a LogicalSupervision graph consisting of transitions, initial- and final checkpoints. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject , Identifiable , MultilanguageReferrable , PhmSupervision , Referrable			
Aggregated by	GlobalSupervision.logicalSupervision			
Attribute	Type	Mult.	Kind	Note
finalCheckpoint	SupervisionCheckpoint	*	ref	Reference to the final Checkpoint(s) for this Logical Supervision. Tags: xml.sequenceOffset=20
initialCheckpoint	SupervisionCheckpoint	*	ref	Reference to the initial Checkpoint(s) for this Logical Supervision. Tags: xml.sequenceOffset=10
transition	CheckpointTransition	*	ref	Reference to the transitions for this LogicalSupervision. Tags: xml.sequenceOffset=30

Table A.323: LogicalSupervision

Class	Machine			
Note	Machine that represents an Adaptive Autosar Software Stack. Tags: atp.recommendedPackage=Machines This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement , ARObject , AtpClassifier , AtpFeature , AtpStructureElement , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDeploymentElement , UploadablePackageElement			
Aggregated by	ARPackage.element, AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
default Application Timeout	EnterExitTimeout	0..1	aggr	This aggregation defines a default timeout in the context of a given Machine with respect to the launching and termination of applications.





Class	Machine			
environment Variable	TagWithOptionalValue	*	aggr	This aggregation represents the collection of environment variables that shall be added to the environment defined on the level of the enclosing Machine. Stereotypes: atpSplitable Tags: atp.Splitkey=environmentVariable
machineDesign	MachineDesign	0..1	ref	Reference to the MachineDesign this Machine is implementing.
module Instantiation	AdaptiveModule Instantiation	*	aggr	Configuration of Adaptive Autosar module instances that are running on the machine. Stereotypes: atpSplitable Tags: atp.Splitkey=moduleInstantiation.shortName
processor	Processor	*	aggr	This represents the collection of processors owned by the enclosing machine.
secure Communication Deployment	SecureCommunication Deployment	*	aggr	Target-configuration of secure communication protocol configuration settings to crypto module entities. Stereotypes: atpSplitable Tags: atp.Splitkey=secureCommunication Deployment.shortName
trustedPlatform Executable LaunchBehavior	TrustedPlatform ExecutableLaunch BehaviorEnum	0..1	attr	This attribute controls the behavior of how authentication affects the ability to launch for each Executable.

Table A.324: Machine

Class	MachineDesign			
Note	This meta-class represents the ability to define requirements on a Machine in the context of designing a system. Tags: atp.recommendedPackage=MachineDesigns This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, AtpClassifier, AtpFeature, AtpStructureElement, CollectableElement, Fibex Element, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesign Element, UploadablePackageElement</i>			
Aggregated by	ARPackage.element, AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
accessControl	AccessControlEnum	0..1	attr	This attribute defines how the access restriction to the Service Instance is defined.
communication Connector	Communication Connector	*	aggr	This aggregation defines the network connection of the machine. Stereotypes: atpSplitable Tags: atp.Splitkey=communicationConnector.shortName
communication Controller	Communication Controller	*	aggr	CommunicationControllers of the Machine that are used for description of 10-Base-T1S topologies Stereotypes: atpSplitable Tags: atp.Splitkey=communicationController.shortName
cryptoKeySlot	CryptoKeySlotDesign	*	aggr	This aggregation represents the key slots for which a key slot design is created in the context of the enclosing machine design. Stereotypes: atpSplitable Tags: atp.Splitkey=cryptoKeySlot.shortName
ethIpProps	EthIpProps	*	ref	Machine specific IP attributes.
functional ClusterDesign	AbstractFunctional ClusterDesign	*	aggr	Configuration settings for Functional Clusters on the machine design level.
pncPrepare SleepTimer	TimeValue	0..1	attr	Time in seconds the PNC state machine shall wait in PNC_PREPARE_SLEEP.





Class	MachineDesign			
pnResetTimer	TimeValue	0..1	attr	Specifies the runtime of the reset timer in seconds. This reset time is valid for the reset of PN requests.
processor	Processor	*	aggr	This represents the collection of processors owned by the enclosing MachineDesign.
service Discovery Config	ServiceDiscovery Configuration	*	aggr	Set of service discovery configuration settings that are defined on the machine for individual Communication Connectors. Stereotypes: atpSplitable Tags: atp.Splitkey=serviceDiscoveryConfig
tcpIpIcmpProps	EthTcpIpIcmpProps	*	ref	Machine specific ICMP (Internet Control Message Protocol) attributes
tcpIpProps	EthTcpIpProps	*	ref	Machine specific TcpIp Stack attributes.

Table A.325: MachineDesign

Class	MachineTiming			
Note	This meta-class represents the timing view for a machine. Tags: atp.Status=draft atp.recommendedPackage=TimingExtensions This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , Identifiable , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , Referrable , <i>TimingExtension</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
machine	Machine	0..1	ref	This defines the scope of a MachineTiming. All corresponding timing descriptions and constraints shall be defined within this scope. Tags: atp.Status=draft

Table A.326: MachineTiming

Class	ModeDeclaration			
Note	Declaration of one Mode. The name and semantics of a specific mode is not defined in the meta-model.			
Base	<i>ARObject</i> , <i>AtpClassifier</i> , <i>AtpFeature</i> , <i>AtpStructureElement</i> , Identifiable , <i>MultilanguageReferrable</i> , Referrable			
Aggregated by	<i>AtpClassifier</i> .atpFeature, ModeDeclarationGroup.modeDeclaration			
Attribute	Type	Mult.	Kind	Note
value	PositiveInteger	0..1	attr	The RTE shall take the value of this attribute for generating the source code representation of this Mode Declaration.

Table A.327: ModeDeclaration

Class	ModeDeclarationGroup			
Note	A collection of Mode Declarations. Also, the initial mode is explicitly identified. Tags: atp.recommendedPackage=ModeDeclarationGroups			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>AtpBlueprint</i> , <i>AtpBlueprintable</i> , <i>AtpClassifier</i> , <i>AtpType</i> , <i>CollectableElement</i> , Identifiable , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , Referrable , <i>UploadableDesignElement</i> , <i>UploadablePackageElement</i>			
Aggregated by	ARPackage.element			





Class	ModeDeclarationGroup			
Attribute	Type	Mult.	Kind	Note
initialMode	ModeDeclaration	0..1	ref	The initial mode of the ModeDeclarationGroup. This mode is active before any mode switches occurred.
mode Declaration	ModeDeclaration	*	aggr	The ModeDeclarations collected in this ModeDeclaration Group. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=modeDeclaration.shortName, mode Declaration.variationPoint.shortLabel vh.latestBindingTime=blueprintDerivationTime

Table A.328: ModeDeclarationGroup

Class	ModeDeclarationGroupPrototype			
Note	The ModeDeclarationGroupPrototype specifies a set of Modes (ModeDeclarationGroup) which is provided or required in the given context.			
Base	<i>ARObject</i> , <i>AtpFeature</i> , <i>AtpPrototype</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	<i>AtpClassifier.atpFeature</i> , <i>BswModuleDescription.providedModeGroup</i> , <i>BswModuleDescription.requiredModeGroup</i> , <i>FirewallStateSwitchInterface.firewallStateMachine</i> , <i>FunctionGroupSet.functionGroup</i> , <i>ModeSwitchInterface.modeGroup</i> , <i>Process.processStateMachine</i> , <i>StateManagementStateNotification.stateMachine</i>			
Attribute	Type	Mult.	Kind	Note
type	ModeDeclarationGroup	0..1	tref	The "collection of ModeDeclarations" (= ModeDeclaration Group) supported by a component Stereotypes: isOfType

Table A.329: ModeDeclarationGroupPrototype

Class	ModelnProcessInstanceRef			
Note	This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , <i>AtpInstanceRef</i>			
Aggregated by	ExecutionDependency.processState			
Attribute	Type	Mult.	Kind	Note
base	Process	0..1	ref	Stereotypes: atpDerived Tags: xml.sequenceOffset=10
contextMode Declaration GroupPrototype	ModeDeclarationGroupPrototype	0..1	ref	Tags: xml.sequenceOffset=20
targetMode Declaration	ModeDeclaration	0..1	ref	Tags: xml.sequenceOffset=30

Table A.330: ModelnProcessInstanceRef

Class	NetworkEndpoint			
Note	The network endpoint defines the network addressing (e.g. IP-Address or MAC multicast address).			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	EthernetPhysicalChannel.networkEndpoint			
Attribute	Type	Mult.	Kind	Note
fullyQualified DomainName	String	0..1	attr	Defines the fully qualified domain name (FQDN) e.g. some.example.host.





Class	NetworkEndpoint			
ipSecConfig	IPSecConfig	0..1	aggr	Optional IPSec configuration that provides security services for IP packets.
networkEndpointAddress	NetworkEndpointAddress	*	aggr	Definition of a Network Address. Stereotypes: atpSplitable Tags: atp.Splitkey=networkEndpointAddress.ipv4Address, networkEndpointAddress.ipv6Address, networkEndpointAddress.macMulticastGroup xml.namePlural=NETWORK-ENDPOINT-ADDRESSES
priority	PositiveInteger	0..1	attr	Defines the frame priority where values from 0 (best effort) to 7 (highest) are allowed.

Table A.331: NetworkEndpoint

Class	NetworkHandlePortMapping			
Note	This class is used to associate a PortPrototype with a network handle in order to control the network handle from the PortPrototype Tags: atp.recommendedPackage=NetworkHandleMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
networkHandle	NmNetworkHandle	0..1	ref	This reference identifies the applicable network handle.
pPortPrototypeInExecutable	PPortPrototype	0..1	iref	This reference identifies the applicable PortPrototype in the context of an enclosing Executable. Stereotypes: atpUriDef InstanceRef implemented by: PPortPrototypeInExecutableInstanceRef
process	Process	0..1	ref	This reference identifies the process applicable for the state management

Table A.332: NetworkHandlePortMapping

Class	NetworkManagementPortInterface			
Note	This PortInterface shall be used to submit triggers to the state management Tags: atp.recommendedPackage=NetworkManagementInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.333: NetworkManagementPortInterface

Class	NmCluster (abstract)
Note	Set of NM nodes coordinated with use of the NM algorithm.
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable
Subclasses	CanNmCluster, FlexrayNmCluster, UdpNmCluster
Aggregated by	NmConfig.nmCluster





Class	NmCluster (abstract)			
Attribute	Type	Mult.	Kind	Note
communication Cluster	CommunicationCluster	0..1	ref	Association to a CommunicationCluster in the topology description.
nmLightTimeout	TimeValue	0..1	attr	Defines the timeout (in seconds) after COMM_FULL_COMMUNICATION sub-state COMM_FULL_COM_READY_SLEEP is left.
nmNode	NmNode	*	aggr	Collection of NmNodes of the NmCluster. atpVariation: Derived, because NmNode can be variable. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=nmNode.shortName, nmNode.variation Point.shortLabel vh.latestBindingTime=postBuild
nmPnc Participation	Boolean	0..1	attr	Defines whether this NmCluster contributes to the partial network mechanism.
pncCluster VectorLength	PositiveInteger	0..1	attr	Optionally defines the length of the PNC Vector per CommunicationCluster (and VLAN in case of UdpNm). If not defined then System.pncVectorLength applies. Should only make the PNC Vector shorter (or same length as defined in System.pncVectorLength).

Table A.334: NmCluster

Class	NmConfig			
Note	Contains the all configuration elements for AUTOSAR Nm. Tags: atp.recommendedPackage=NmConfigs			
Base	ARElement, ARObject, CollectableElement, FibexElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
nmCluster	NmCluster	*	aggr	Collection of NM Clusters atpVariation: Derived, because cluster can be variable. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=nmCluster.shortName, nmCluster.variation Point.shortLabel vh.latestBindingTime=postBuild

Table A.335: NmConfig

Enumeration	NmHandleMappingDirectionEnum			
Note	This enumeration provides direction values for the mapping of NM handles to function group states. This Enumeration is only used by the AUTOSAR Adaptive Platform.			
Aggregated by	NmHandleToFunctionGroupStateMapping.mappingDirection			
Literal	Description			
functionGroupState ToNmHandle	The purpose of the mapping is to indicate which function group state requires network access. Tags: atp.EnumerationLiteralIndex=0			
nmHandleActiveTo FunctionGroupState	The purpose of the mapping is to indicate that the function group shall be switched to a given state if the network handle becomes active. Tags: atp.EnumerationLiteralIndex=2			





Enumeration	NmHandleMappingDirectionEnum
nmHandleInactiveToFunctionGroupState	The purpose of the mapping is to indicate that the function group shall be switched to a given state if the network handle becomes inactive. Tags: atp.enumerationLiteralIndex=1

Table A.336: NmHandleMappingDirectionEnum

Class	NmHandleToFunctionGroupStateMapping			
Note	This meta-class represents the ability to create a mapping between an NmNetworkHandle and a collection of function group states. This way, the impact of function groups on the network management can be specified. Tags: atp.recommendedPackage=NmHandleToFunctionGroupStateMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
functionGroupState	ModeDeclaration	*	iref	This reference identifies the collection of function group states in the context of the mapping. InstanceRef implemented by: FunctionGroupStateInFunctionGroupSetInstanceRef
mappingDirection	NmHandleMappingDirectionEnum	0..1	attr	This attribute describes the direction of the mapping.
nmHandle	NmNetworkHandle	0..1	ref	This reference identifies the applicable NmNetworkHandle in the context of the mapping.

Table A.337: NmHandleToFunctionGroupStateMapping

Class	NmInteractsWithSmMapping			
Note	This mapping represents an interaction from network management to state management. Tags: atp.Status=draft atp.recommendedPackage=FCInteractions This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, FunctionalClusterInteractsWithFunctionalClusterMapping, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
nmNetworkHandle	NmNetworkHandle	0..1	ref	This reference identifies the network management handle that wants to interact with state management. Tags: atp.Status=draft
stateRequest	StateManagementStateRequest	0..1	ref	This reference identifies the state management state request that is involved in the interaction with the network management. Tags: atp.Status=draft

Table A.338: NmInteractsWithSmMapping

Class	NoCheckpointSupervision
Note	Defines explicitly that NO supervision shall be applied for a set of SupervisionCheckpoints. This Class is only used by the AUTOSAR Adaptive Platform.
Base	ARObject, Identifiable, MultilanguageReferrable, PhmSupervision, Referrable





Class	NoCheckpointSupervision			
Aggregated by	GlobalSupervision.noCheckpointSupervision			
Attribute	Type	Mult.	Kind	Note
checkpoint	SupervisionCheckpoint	*	ref	Reference to the set of SupervisionCheckpoints which shall not be considered for any kind of supervision.

Table A.339: NoCheckpointSupervision

Class	NoSupervision			
Note	Defines explicitly that NO supervision shall be applied for a specific Supervised Entity instance. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , Identifiable , <i>MultilanguageReferrable</i> , PhmSupervision , Referrable			
Aggregated by	GlobalSupervision.noSupervision			
Attribute	Type	Mult.	Kind	Note
process	Process	0..1	ref	Reference to the Process this NoSupervision applies to.
targetPhm Supervised Entity	RPortPrototype	0..1	iref	Instance reference to the RPortPrototype which represents the Supervised Entity instance. Stereotypes: atpUriDef InstanceRef implemented by: RPortPrototypeIn ExecutableInstanceRef

Table A.340: NoSupervision

Class	NonOsModuleInstantiation (abstract)			
Note	This meta-class defines the abstract attributes for the configuration of an adaptive autosar module other than the OS module. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , <i>AdaptiveModuleInstantiation</i> , <i>AtpClassifier</i> , <i>AtpFeature</i> , <i>AtpStructureElement</i> , Identifiable , <i>MultilanguageReferrable</i> , Referrable			
Subclasses	AdaptiveFirewallModuleInstantiation , CmModuleInstantiation , CryptoModuleInstantiation , DolpInstantiation , GenericDiagnosticTransportInstantiation , GenericModuleInstantiation , IdsPlatformInstantiation , LogAndTraceInstantiation , NmInstantiation , SovdModuleInstantiation , StateManagementModuleInstantiation , SuspendToRamModuleInstantiation , TimeSyncModuleInstantiation , UcmModuleInstantiation			
Aggregated by	<i>AtpClassifier.atpFeature</i> , Machine.moduleInstantiation			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.341: NonOsModuleInstantiation

Primitive	Numerical
Note	<p>This primitive specifies a numerical value. It can be denoted in different formats such as Decimal, Octal, Hexadecimal, Float. See the xsd pattern for details.</p> <p>The value can be expressed in octal, hexadecimal, binary representation. Negative numbers can only be expressed in decimal or float notation.</p> <p>Tags:</p> <p>xml.xsd.customType=NUMERICAL-VALUE</p> <p>xml.xsd.pattern=(0[xX][0-9a-fA-F+]) (0[0-7]+) (0[bB][0-1]+) ([+-]?[1-9][0-9]*(\.[0-9+])? [+-]?[0-9](\.[0-9+])?)([eE]([+-]?[0-9+])?) \.[0]INF -INF NaN</p> <p>xml.xsd.type=string</p>

Table A.342: Numerical

Class	OsModuleInstantiation			
Note	This meta-class defines the attributes for the OS configuration on a specific machine. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AdaptiveModuleInstantiation, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	AtpClassifier.atpFeature, Machine.moduleInstantiation			
Attribute	Type	Mult.	Kind	Note
osArtiAdapterLaunchBehavior	OsArtiAdapterLaunchBehaviorEnum	0..1	attr	This attribute controls the startup behavior of the OS/ ARTI Adapter. Tags: atp.Status=candidate
resourceGroup	ResourceGroup	*	aggr	This represents the collection of ResourceGroups owned by the enclosing OsModuleImplementation.
supportedTimerGranularity	TimeValue	0..1	attr	This attribute describes the supported timer granularity (TimeValue of one tick).

Table A.343: OsModuleInstantiation

Class	PPortPrototype			
Note	Component port providing a certain port interface.			
Base	ARObject, AbstractProvidedPortPrototype, AtpBlueprintable, AtpFeature, AtpPrototype, Identifiable , MultilanguageReferrable, PortPrototype , Referrable			
Aggregated by	AtpClassifier.atpFeature, SwComponentType.port			
Attribute	Type	Mult.	Kind	Note
providedInterface	PortInterface	0..1	tref	The interface that this port provides. Stereotypes: isOfType

Table A.344: PPortPrototype

Class	PRPortPrototype			
Note	This kind of PortPrototype can take the role of both a required and a provided PortPrototype.			
Base	ARObject, AbstractProvidedPortPrototype, AbstractRequiredPortPrototype, AtpBlueprintable, AtpFeature, AtpPrototype, Identifiable , MultilanguageReferrable, PortPrototype , Referrable			
Aggregated by	AtpClassifier.atpFeature, SwComponentType.port			
Attribute	Type	Mult.	Kind	Note
providedRequiredInterface	PortInterface	0..1	tref	This represents the PortInterface used to type the PRPortPrototype. Stereotypes: isOfType

Table A.345: PRPortPrototype

Class	PassThroughSwConnector			
Note	This kind of SwConnector can be used inside a CompositionSwComponentType to connect two delegation PortPrototypes.			
Base	ARObject, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable , MultilanguageReferrable, Referrable , SwConnector			
Aggregated by	AtpClassifier.atpFeature, CompositionSwComponentType.connector			
Attribute	Type	Mult.	Kind	Note
providedOuterPort	AbstractProvidedPortPrototype	0..1	ref	This represents the provided outer delegation Port Prototype of the PassThroughSwConnector.
requiredOuterPort	AbstractRequiredPortPrototype	0..1	ref	This represents the required outer delegation Port Prototype of the PassThroughSwConnector.





Class	PassThroughSwConnector			
serviceInterfaceElementMapping	ServiceInterfaceElementMapping	*	ref	Reference to a ServiceInterfaceElementMapping specifying the mapping of unequal named ServiceInterface elements of the two different ServiceInterfaces typing the two PortPrototypes which are referenced by the PassThroughSwConnector. This Attribute is only used by the AUTOSAR Adaptive Platform.

Table A.346: PassThroughSwConnector

Class	PduTriggering			
Note	The PduTriggering describes on which channel the IPdu is transmitted. The Pdu routing by the PduR is only allowed for subclasses of IPdu. Depending on its relation to entities such channels and clusters it can be unambiguously deduced whether a fan-out is handled by the Pdu router or the Bus Interface. If the fan-out is specified between different clusters it shall be handled by the Pdu Router. If the fan-out is specified between different channels of the same cluster it shall be handled by the Bus Interface.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	PhysicalChannel.pduTriggering			
Attribute	Type	Mult.	Kind	Note
iPdu	Pdu	0..1	ref	Reference to the Pdu for which the PduTriggering is defined. One I-Pdu can be triggered on different channels (PduR fan-out). The Pdu routing by the PduR is only allowed for subclasses of IPdu. Nevertheless is the reference to the Pdu element necessary since the PduTriggering element is also used to specify the sending and receiving connections to Ecu Ports.
iPduPort	IPduPort	*	ref	References to the IPduPort on every ECU of the system which sends and/or receives the I-PDU. References for both the sender and the receiver side shall be included when the system is completely defined.
iSignalTriggering	ISignalTriggering	*	ref	This reference provides the relationship to the ISignalTriggerings that are implemented by the PduTriggering. The reference is optional since no ISignalTriggering can be defined for DCM and Multiplexed Pdus. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=iSignalTriggering.iSignalTriggering, iSignalTriggering.variationPoint.shortLabel vh.latestBindingTime=postBuild
secOcCryptoMapping	SecOcCryptoServiceMapping	0..1	ref	This reference identifies the crypto profile applicable to the usage (send, receive) of the also referenced Secured IPdu. Obviously, this reference is only applicable if the PduTriggering also references a SecuredIPdu in the role i Pdu. Tags: atp.Status=obsolete





Class	PduTriggering			
secOcCryptoServiceMapping	SecOcCryptoServiceMapping	0..1	ref	<p>This reference identifies the crypto profile applicable to the usage (send, receive) of the also referenced Secured IPdu.</p> <p>Obviously, this reference is only applicable if the Pdutriggering also references a SecuredIPdu in the role i Pdu.</p> <p>Stereotypes: atpSplitable; atpVariation</p> <p>Tags: atp.Splitkey=secOcCryptoServiceMapping.secOcCryptoServiceMapping, secOcCryptoServiceMapping.variation Point.shortLabel vh.latestBindingTime=postBuild</p>
triggerIPduSendCondition	TriggerIPduSendCondition	*	aggr	<p>Defines the trigger for the Com_TriggerIPDUSend API call. Only if all defined TriggerIPduSendConditions evaluate to true (AND associated) the Com_TriggerIPDUSend API shall be called.</p>

Table A.347: PduTriggering

Class	PeriodicEventTriggering			
Note	<p>Describes the behavior of an event with a strict periodic occurrence pattern, given by period. Additionally, it is possible to soften the strictness of the periodic occurrence behavior by specifying a jitter, so that there can be a deviation from the period up to the size of the jitter.</p>			
Base	AObject, EventTriggeringConstraint, Identifiable , MultilanguageReferrable, Referrable , TimingConstraint, Traceable			
Aggregated by	TimingExtension.timingGuarantee, TimingExtension.timingRequirement			
Attribute	Type	Mult.	Kind	Note
jitter	MultidimensionalTime	0..1	aggr	<p>The maximum deviation of the periodic event occurrence.</p> <p>Tags: xml.sequenceOffset=20</p>
minimumInterArrivalTime	MultidimensionalTime	0..1	aggr	<p>The minimum time distance between subsequent consecutive occurrences of the associated event.</p> <p>If the minimumInterArrivalTime is less than the period minus the jitter, then the minimumInterArrivalTime has no effect on the properties of the constraint.</p> <p>Tags: xml.sequenceOffset=10</p>
period	MultidimensionalTime	0..1	aggr	<p>The periodic distance between subsequent occurrences of the event.</p> <p>Tags: xml.sequenceOffset=30</p>

Table A.348: PeriodicEventTriggering

Class	PersistencyDataElement			
Note	<p>This meta-class represents the ability to formally specify a piece of data that is subject to persistency in the context of the enclosing PersistencyKeyValueStorageInterface.</p> <p>PersistencyDataElement represents also a key-value pair of the deployed PersistencyKeyValueStorage and provides an initial value.</p> <p>This Class is only used by the AUTOSAR Adaptive Platform.</p>			
Base	AObject, AtpFeature, AtpPrototype, AutosarDataPrototype , DataPrototype , Identifiable , MultilanguageReferrable, PersistencyInterfaceElement , Referrable			
Aggregated by	AtpClassifier.atpFeature, PersistencyKeyValueStorageInterface.dataElement			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.349: PersistencyDataElement

Class	PersistenceDataRequiredComSpec			
Note	This meta-class represents the ability to define port-specific attributes for supporting use cases of data persistency on the required side. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AbstractPersistenceRequireComSpec , RPortComSpec			
Aggregated by	AbstractRequiredPortPrototype.requiredComSpec, PortPrototypeBlueprint.requiredComSpec			
Attribute	Type	Mult.	Kind	Note
dataElement	PersistenceDataElement	0..1	ref	This reference represents the PersistenceDataElement for which the PersistenceDataRequiredComSpec applies. Stereotypes: atpIdentityContributor
initValue	ValueSpecification	0..1	aggr	This aggregation represents the definition of an initial value for the PersistenceDataElement referenced by the enclosing PersistenceDataRequiredComSpec

Table A.350: PersistenceDataRequiredComSpec

Class	PersistenceDeployment (abstract)			
Note	This abstract meta-class serves as a base class for concrete classes representing different aspects of persistency. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadableExclusivePackageElement , UploadablePackageElement			
Subclasses	PersistenceFileStorage , PersistenceKeyValueStorage			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
deploymentUri (ordered)	PersistenceDeployment Uri	*	aggr	This aggregation represents the collection of URIs relevant for the enclosing PersistenceDeployment.
maximum AllowedSize	PositiveUnlimitedInteger	0..1	attr	The value of this attribute represents the maximum size (unit: bytes) allowed at target-configuration time for the enclosing PersistenceDeployment.
minimum SustainedSize	PositiveInteger	0..1	attr	The value of this attribute represents the minimum size (unit: bytes) guaranteed at deployment time for the enclosing PersistenceDeployment.
redundancy Handling	PersistenceRedundancyHandling	*	aggr	This aggregation represents the chosen approaches to handle redundancy. Stereotypes: atpSplitable Tags: atp.Splitkey=redundancyHandling
updateStrategy	PersistenceCollection LevelUpdateStrategy Enum	0..1	attr	This attribute shall be used to specify the update strategy of the respective PersistenceDeployment as a whole.
version	StrongRevisionLabel String	0..1	attr	The attribute represents the version of the PersistenceFileStorage or PersistenceKeyValueStorage .

Table A.351: PersistenceDeployment

Class	PersistenceDeploymentElement (abstract)			
Note	This abstract meta-class serves as a base class for concrete classes representing different aspects of elements of a PersistenceDeployment . This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable			
Subclasses	PersistenceFile , PersistenceKeyValuePair			
Attribute	Type	Mult.	Kind	Note





Class	PersistencyDeploymentElement (abstract)			
updateStrategy	PersistencyElementLevelUpdateStrategyEnum	0..1	attr	This attribute can be used to specify the update strategy of the respective PersistencyDeploymentElement.

Table A.352: PersistencyDeploymentElement

Class	PersistencyDeploymentToCryptoKeySlotMapping			
Note	This meta-class represents the ability to define a mapping between the PersistencyDeployment and a CryptoKeySlot. Tags: atp.recommendedPackage=FCInteractions This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement , ARObject , CollectableElement , FunctionalClusterInteractsWithFunctionalClusterMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDeploymentElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
cryptoAlgorithmString	String	0..1	attr	This attribute defines the cryptographic algorithm used for hashing, encryption, decryption, signature/MAC verification, or MAC generation.
cryptoKeySlot	CryptoKeySlot	0..1	ref	This reference represents the mapped CryptoKeySlot.
keySlotUsage	CryptoKeySlotUsageEnum	0..1	attr	This attribute defines the role of the keySlot assignment.
persistencyDeployment	PersistencyDeployment	0..1	ref	This reference represents the mapped PersistencyDeployment.
verificationHash	String	0..1	attr	This attribute defines the hash of the storage used in case of verification.

Table A.353: PersistencyDeploymentToCryptoKeySlotMapping

Enumeration	PersistencyElementLevelUpdateStrategyEnum
Note	This enumeration provides possible values for the update strategy on element level. This Enumeration is only used by the AUTOSAR Adaptive Platform.
Aggregated by	PersistencyDeploymentElement.updateStrategy , PersistencyInterfaceElement.updateStrategy
Literal	Description
delete	The update strategy is to delete the value of the respective data item. Tags: atp.EnumerationLiteralIndex=2
keepExisting	The update strategy is to keep the existing value of the respective data item. Tags: atp.EnumerationLiteralIndex=1
overwrite	The update strategy is to overwrite the respective data item. Tags: atp.EnumerationLiteralIndex=0

Table A.354: PersistencyElementLevelUpdateStrategyEnum

Class	PersistencyFile			
Note	This meta-class represents the model of a file as part of the persistency on deployment level. Tags: atp.recommendedPackage=PersistencyFiles This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject , Identifiable , MultilanguageReferrable , PersistencyDeploymentElement , Referrable			
Aggregated by	PersistencyFileStorage.file			
Attribute	Type	Mult.	Kind	Note





Class	PersistencyFile			
contentUri	UriString	0..1	attr	This attribute represents the URI that identifies the initial content of the PersistencyFile.
fileName	String	0..1	attr	This attribute holds filename part of the storage location for the PersistencyFile, e.g. file on the file system.

Table A.355: PersistencyFile

Class	PersistencyFileElement			
Note	This meta-class has the ability to represent a file at design time such that it is possible to configure the behavior for accessing the represented file at run-time. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , PersistencyInterfaceElement , Referrable			
Aggregated by	PersistencyFileStorageInterface.fileElement			
Attribute	Type	Mult.	Kind	Note
contentUri	UriString	0..1	attr	This attribute represents the URI that identifies the initial content of the PersistencyFile.
fileName	String	0..1	attr	This attribute holds the filename part of the storage location, e.g. file on the file system.

Table A.356: PersistencyFileElement

Class	PersistencyFileRequiredComSpec			
Note	This meta-class represents the ability to define port-specific attributes for supporting use cases of file persistency on the required side. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AbstractPersistencyRequireComSpec , RPortComSpec			
Aggregated by	AbstractRequiredPortPrototype.requiredComSpec , PortPrototypeBlueprint.requiredComSpec			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.357: PersistencyFileRequiredComSpec

Class	PersistencyFileStorage			
Note	This meta-class comes with the ability to define a collection of single files (directory) that creates the deployment-side counterpart to a PortPrototype typed by a PersistencyFileStorageInterface . Tags: atp.recommendedPackage=PersistencyFileStorages This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , PersistencyDeployment , Referrable , UploadableDeploymentElement , UploadableExclusivePackageElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
file	PersistencyFile	*	aggr	This aggregation represents the collection of files aggregated by the PersistencyFileStorage.

Table A.358: PersistencyFileStorage

Class	PersistencyFileStorageInterface			
Note	This meta-class provides the ability to implement a PortInterface for supporting persistency use cases for files. Tags: atp.recommendedPackage=PersistencyFileStorageInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, PersistencyInterface , PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
fileElement	PersistencyFileElement	*	aggr	This aggregation represents the collection of Persistency FileStorages in the context of the enclosing Persistency FileStorageInterface.
maxNumberOf Files	PositiveInteger	0..1	attr	This attribute represents the definition of an upper bound for the handling of files at run-time in the context of the enclosing PersistencyFileStorageInterface.

Table A.359: PersistencyFileStorageInterface

Class	PersistencyInterface (abstract)			
Note	This meta-class provides the abstract ability to define a PortInterface for the support of persistency use cases. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Subclasses	PersistencyFileStorageInterface , PersistencyKeyValueStorageInterface			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
contractVersion	StrongRevisionLabel String	0..1	attr	This attribute represents the contract version that is used to determine whether the Persistency configuration experienced structural changes and is also used for the check for data type compatibility.
minimum SustainedSize	PositiveInteger	0..1	attr	The value of this attribute represents the minimum size (unit: bytes) required at design time for the enclosing PersistencyInterface.
redundancy	PersistencyRedundancy Enum	0..1	attr	This attribute represents a requirement towards the redundancy of storage.
redundancy Handling	PersistencyRedundancy Handling	*	aggr	This aggregation represents the chosen approaches to handle redundancy for the various use cases implemented by subclasses Stereotypes: atp.Splitable Tags: atp.Splitkey=redundancyHandling
updateStrategy	PersistencyCollection LevelUpdateStrategy Enum	0..1	attr	This attribute can be used to specify the update strategy of the respective PersistencyInterface as a whole.

Table A.360: PersistencyInterface

Class	PersistencyInterfaceElement (abstract)			
Note	This meta-class provides the abstract ability to define an element of a PortInterface for the support of persistency use cases. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable			
Subclasses	PersistencyDataElement , PersistencyFileElement			
Attribute	Type	Mult.	Kind	Note





Class	PersistencyInterfaceElement (abstract)			
updateStrategy	PersistencyElementLevelUpdateStrategyEnum	0..1	attr	This attribute can be used to specify the update strategy of the respective PersistencyInterfaceElement.

Table A.361: PersistencyInterfaceElement

Class	PersistencyKeyValueDataTypeMapping			
Note	This meta-class represents the ability to define a mapping between an existing data type in a key-value-storage stored by a previous version to a new data type used on application software level in the current version. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , <i>Describable</i>			
Aggregated by	PersistencyKeyValueStorageInterface.dataTypeMapping			
Attribute	Type	Mult.	Kind	Note
currentDataType	AutosarDataType	0..1	ref	This reference identifies the current data type for an existing key-value-pair in the context of the enclosing PersistencyKeyValueStorageInterface.
previousContractVersion	StrongRevisionLabelString	0..1	attr	This attribute identifies the contract version in which the previousDataType was used.
previousDataType	AutosarDataType	0..1	ref	This reference identifies the previous data type in a key-value-pair existing in the context of the enclosing PersistencyKeyValueStorageInterface.

Table A.362: PersistencyKeyValueDataTypeMapping

Class	PersistencyKeyValuePair			
Note	This meta-class represents the ability to formally model a key-value pair in the context of the target-configuration of persistency. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , Identifiable , <i>MultilanguageReferrable</i> , PersistencyDeploymentElement , <i>Referrable</i>			
Aggregated by	PersistencyKeyValueStorage.keyValuePair			
Attribute	Type	Mult.	Kind	Note
initValue	ValueSpecification	0..1	aggr	This aggregation represents the ability to define an initial value for the value side of the key-value pair. Please note that it does not make sense to configure an initial value if the PersistencyDeploymentElement.updateStrategy is set to the value <code>delete</code> .
valueDataType	AbstractImplementationDataType	0..1	ref	This reference represents the data type applicable for the value of the key-value pair.

Table A.363: PersistencyKeyValuePair

Class	PersistencyKeyValueStorage			
Note	This meta-class represents the ability to model a key-value storage on target-configuration level. Tags: atp.recommendedPackage=PersistencyKeyValueStorages This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, PersistencyDeployment , Referrable , UploadableDeploymentElement, UploadableExclusivePackageElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
keyValuePair	PersistencyKeyValuePair	*	aggr	This aggregation represents the key-value-pairs owned by the enclosing PersistencyKeyValueStorage .

Table A.364: PersistencyKeyValueStorage

Class	PersistencyKeyValueStorageInterface			
Note	This meta-class provides the ability to implement a PortInterface for supporting persistency use cases for data. Tags: atp.recommendedPackage=PersistencyKeyValueStorageInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, PersistencyInterface , PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataElement	PersistencyDataElement	*	aggr	This aggregation represents the collection of PersistencyDataElements in the context of the enclosing PersistencyKeyValueStorageInterface.
dataTypeForSerialization	AbstractImplementationDataType	*	ref	This reference identifies the AbstractImplementationDataTypes that shall be supported for storing in a key-value storage in addition to the types already determined from the aggregation of PersistencyDataElement.
dataTypeMapping	PersistencyKeyValueDataTypeMapping	0..1	aggr	This aggregation provides a collection of replacement rules for data types used in the context of the enclosing PersistencyKeyValueStorageInterface.

Table A.365: PersistencyKeyValueStorageInterface

Class	PersistencyPortPrototypeToDeploymentMapping (abstract)			
Note	This abstract bas class implements the shared functionality of all mapping between a PortPrototype , a Process , and a specific subclass of PersistencyDeployment . This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadableExclusivePackageElement , UploadablePackageElement			
Subclasses	PersistencyPortPrototypeToFileStorageMapping , PersistencyPortPrototypeToKeyValueStorageMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
portPrototype	PortPrototype	0..1	iref	This reference represents the mapped PortPrototype. InstanceRef implemented by: PortPrototypelnExecutableInstanceRef
process	Process	0..1	ref	This reference represents the process required as context for the mapping.

Table A.366: PersistencyPortPrototypeToDeploymentMapping

Class	PersistencyPortPrototypeToFileStorageMapping			
Note	This meta-class represents the ability to define a mapping between a collection of files on deployment level to a given PortPrototype . Tags: atp.recommendedPackage=PersistencyPortPrototypeToFileStorageMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement , ARObject , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , PersistencyPortPrototypeToDeploymentMapping , Referrable , UploadableDeploymentElement , UploadableExclusivePackageElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
fileStorage	PersistencyFileStorage	0..1	ref	This reference represents the mapped file storage.

Table A.367: PersistencyPortPrototypeToFileStorageMapping

Class	PersistencyPortPrototypeToKeyValueStorageMapping			
Note	This meta-class represents the ability to define a mapping between a PortPrototype and a key-value storage. Tags: atp.recommendedPackage=PersistencyPortPrototypeToKeyValueStorageMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement , ARObject , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , PersistencyPortPrototypeToDeploymentMapping , Referrable , UploadableDeploymentElement , UploadableExclusivePackageElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
keyValueStorage	PersistencyKeyValueStorage	0..1	ref	This reference represents the mapped key-value storage.

Table A.368: PersistencyPortPrototypeToKeyValueStorageMapping

Class	PersistencyRedundancyChecksum (abstract)			
Note	Abstract class that defines the common attributes for implementations of redundancy. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject , PersistencyRedundancyHandling			
Subclasses	PersistencyRedundancyCrc , PersistencyRedundancyHash			
Aggregated by	PersistencyDeployment.redundancyHandling , PersistencyInterface.redundancyHandling			
Attribute	Type	Mult.	Kind	Note
algorithmFamily	String	0..1	attr	This attribute identifies the algorithm family that is used to execute the CRC/Hash.
length	PositiveInteger	0..1	attr	This attribute describes the length of the CRC/Hash in the unit bits.

Table A.369: PersistencyRedundancyChecksum

Enumeration	PersistencyRedundancyEnum			
Note	This meta-class provides a way to specify in which way redundancy shall be applied on collection level. This Enumeration is only used by the AUTOSAR Adaptive Platform.			
Aggregated by	PersistencyInterface.redundancy			
Literal	Description			
none	This value represents the requirement that redundancy measures are not applied on persistency storage level. Tags: atp.EnumerationLiteralIndex=1			





Enumeration	PersistencyRedundancyEnum
redundant	This value represents the requirement that redundancy measures are applied on persistency storage level. The nature of the redundant persistent storage is not further qualified and subject to integrator decisions. Tags: atp.EnumerationLiteralIndex=0
redundantPer Element	This value represents the requirement that redundancy measures are applied on key-value level of a key-value storage or on file level of a file storage. The nature of the redundancy used on the persistent storage is not further qualified and subject to integrator decisions. Tags: atp.EnumerationLiteralIndex=2

Table A.370: PersistencyRedundancyEnum

Class	PersistencyRedundancyHandling (abstract)			
Note	This abstract base class represents a formal description of redundancy. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Subclasses	PersistencyRedundancyChecksum , PersistencyRedundancyMOutOfN			
Aggregated by	PersistencyDeployment.redundancyHandling , PersistencyInterface.redundancyHandling			
Attribute	Type	Mult.	Kind	Note
scope	PersistencyRedundancyHandlingScopeEnum	0..1	attr	This attribute controls the scope in which the redundancy handling is applied.

Table A.371: PersistencyRedundancyHandling

Enumeration	PersistencyRedundancyHandlingScopeEnum
Note	This meta-class provides values to control the scope of redundancy measures in the persistency target-configuration. This Enumeration is only used by the AUTOSAR Adaptive Platform.
Aggregated by	PersistencyRedundancyHandling.scope
Literal	Description
persistency Redundancy HandlingScope Element	The redundancy handling shall be applied on element level (key-value pair and file). Tags: atp.EnumerationLiteralIndex=0
persistency Redundancy HandlingScope Storage	The redundancy handling shall be applied on storage (key-value storage and file storage) level. Tags: atp.EnumerationLiteralIndex=1

Table A.372: PersistencyRedundancyHandlingScopeEnum

Class	PersistencyRedundancyMOutOfN			
Note	This meta-class provides the ability to describe redundancy via an "M out of N" approach. In this case N is the number of copies created and M is the minimum number of identical copies to justify a reliable read access to the data. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, PersistencyRedundancyHandling			
Aggregated by	PersistencyDeployment.redundancyHandling , PersistencyInterface.redundancyHandling			
Attribute	Type	Mult.	Kind	Note





Class	PersistencyRedundancyMOutOfN			
m	PositiveInteger	0..1	attr	This attribute represents the "M" coordinate in the "M out of N" scheme.
n	PositiveInteger	0..1	attr	This attribute represents the "N" coordinate in the "M out of N" scheme.

Table A.373: PersistencyRedundancyMOutOfN

Class	PhmCheckpoint			
Note	This meta-class provides the ability to implement a checkpoint for interaction with the Platform Health Management Supervised Entity. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AtpFeature, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	AtpClassifier.atpFeature, PhmSupervisedEntityInterface.checkpoint			
Attribute	Type	Mult.	Kind	Note
checkpointId	PositiveInteger	0..1	attr	Defines the numeric value which is used to indicate the reporting of this Checkpoint to the Phm.

Table A.374: PhmCheckpoint

Class	PhmCheckpointInExecutableInstanceRef			
Note	This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AtpInstanceRef			
Aggregated by	SupervisionCheckpoint.phmCheckpoint			
Attribute	Type	Mult.	Kind	Note
base	Executable	0..1	ref	Stereotypes: atpDerived; atpUriDef Tags: xml.sequenceOffset=10
context Component Prototype (ordered)	SwComponent Prototype	*	ref	Stereotypes: atpUriDef Tags: xml.sequenceOffset=30
contextRootSw Component Prototype	RootSwComponent Prototype	0..1	ref	Stereotypes: atpUriDef Tags: xml.sequenceOffset=20
contextRPort Prototype	RPortPrototype	0..1	ref	Stereotypes: atpUriDef Tags: xml.sequenceOffset=40
targetPhm Checkpoint	PhmCheckpoint	0..1	ref	Stereotypes: atpUriDef Tags: xml.sequenceOffset=50

Table A.375: PhmCheckpointInExecutableInstanceRef

Class	PhmStateReference (abstract)			
Note	Definition of state dependency. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Subclasses	FunctionGroupPhmStateReference			
Aggregated by	SupervisionModeCondition.stateReference			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.376: PhmStateReference

Class	PhmSupervisedEntityInterface			
Note	This meta-class provides the ability to implement a PortInterface for interaction with the Platform Health Management Supervised Entity. Tags: atp.recommendedPackage=PlatformHealthManagementInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, PlatformHealthManagementInterface, PortInterface, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
checkpoint	PhmCheckpoint	*	aggr	Defines the set of checkpoints which can be reported on this supervised entity.

Table A.377: PhmSupervisedEntityInterface

Class	PhmSupervision (abstract)			
Note	Defines explicitly that NO supervision shall be applied for a set of SupervisionCheckpoints. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Subclasses	AliveSupervision, DeadlineSupervision, LogicalSupervision, NoCheckpointSupervision, NoSupervision			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.378: PhmSupervision

Class	PhmSupervisionRecoveryNotificationInterface			
Note	This meta-class represents a PortInterface that can be taken for implementing a PHM Supervision notification. Tags: atp.recommendedPackage=PlatformHealthManagementInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, PhmAbstractRecoveryNotificationInterface, PlatformHealthManagementInterface, PortInterface, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.379: PhmSupervisionRecoveryNotificationInterface

Class	PlatformHealthManagementContribution			
Note	This element defines a contribution to the Platform Health Management. Tags: atp.recommendedPackage=PlatformHealthManagementContributions This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
checkpoint	SupervisionCheckpoint	*	aggr	Collection of checkpoints in the context of a Platform HealthManagementContribution. Stereotypes: atp.Splitable Tags: atp.Splitkey=checkpoint.shortName xml.sequenceOffset=10





Class	PlatformHealthManagementContribution			
global Supervision	GlobalSupervision	*	aggr	Collection of GlobalSupervisions in the context of a PlatformHealthManagementContribution. Stereotypes: atpSplitable Tags: atp.Splitkey=globalSupervision.shortName xml.sequenceOffset=30
healthChannel	HealthChannel	*	aggr	Collection of HealthChannels in the context of a Platform HealthManagementContribution. Stereotypes: atpSplitable Tags: atp.Splitkey=healthChannel.shortName xml.sequenceOffset=40
supervision ModeCondition	SupervisionMode Condition	*	aggr	Collection of SupervisionModeConditions in the context of a PlatformHealthManagementContribution. Stereotypes: atpSplitable Tags: atp.Splitkey=supervisionModeCondition.shortName xml.sequenceOffset=20

Table A.380: PlatformHealthManagementContribution

Class	PlatformModuleEthernetEndpointConfiguration			
Note	This meta-class defines the attributes for the configuration of a port, protocol type and IP address (local address) of the communication on a VLAN. Tags: atp.recommendedPackage=PlatformModuleEndpointConfigurations This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, Packageable Element, PlatformModuleEndpointConfiguration, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
communication Connector	EthernetCommunication Connector	0..1	ref	Reference to the CommunicationConnector (VLAN) for which the network configuration is defined.
remoteConfig	RemoteEndpoint Configuration	*	aggr	Defintion of remote addresses of peers.
secureCom PropsForTcp	SecureComProps	0..1	ref	Reference to communication security configuration settings that are valid for the tcp unicast endpoint (Tcp Port + unicast IP Address) defined by the PlatformModule EthernetEndpointConfiguration.
secureCom PropsForUdp	SecureComProps	0..1	ref	Reference to communication security configuration settings that are valid for the udp unicast endpoint (Udp Port + unicast IP Address) defined by the PlatformModule EthernetEndpointConfiguration.
tcpPort	ApApplicationEndpoint	0..1	ref	This reference allows to configure a tcp port number.
udpPort	ApApplicationEndpoint	0..1	ref	This reference allows to configure a udp port number.

Table A.381: PlatformModuleEthernetEndpointConfiguration

Class	PncMapping
Note	Describes a mapping between one or several Virtual Function Clusters onto Partial Network Clusters. A Virtual Function Cluster is realized by a PortGroup. A Partial Network Cluster is realized by one or more ServiceInstances.
Base	<i>ARObject, Describable</i>
Aggregated by	SystemMapping.pncMapping





Class	PncMapping			
Attribute	Type	Mult.	Kind	Note
ident	PncMappingIdent	0..1	aggr	This adds the ability to become referable to PncMapping.
physical Channel	PhysicalChannel	*	ref	This reference maps the partial network to a communication channel. Stereotypes: atpSplitable Tags: atp.Splitkey=physicalChannel
pncConsumed Provided ServiceInstance Group	ConsumedProvided ServiceInstanceGroup	*	ref	ConsumedProvidedServiceInstanceGroup used in a Partial Network Cluster. This reference is optional, since this could be used for starting and stopping Consumed ProvidedServiceInstanceGroup according the requested partial network, but is not necessarily needed. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=pncConsumedProvidedServiceInstanceGroup.consumedProvidedServiceInstanceGroup, pnc ConsumedProvidedServiceInstanceGroup.variation Point.shortLabel vh.latestBindingTime=postBuild
pncIdentifier	PositiveInteger	0..1	attr	Identifier of the Partial Network Cluster. This number represents the absolute bit position of this Partial Network Cluster in the NM Pdu.
pncWakeup Enable	Boolean	0..1	attr	If this parameter is available and set to true then this PNC will be woken up as soon as a channel wakeup occurs on a channel where this PNC is assigned to. This is ensured by adding this PNC to the corresponding channel wakeup sources during upstream mapping. Tags: atp.Status=obsolete
serviceInstance	AdaptivePlatform ServiceInstance	*	ref	Reference to ServiceInstances that are participating in a Partial Network Cluster. This Attribute is only used by the AUTOSAR Adaptive Platform.
shortLabel	Identifier	0..1	attr	This attribute specifies an identifying shortName for the PncMapping. It shall be unique in the System scope.
vfc	PortGroup	*	iref	Virtual Function Cluster to be mapped onto a Partial Network Cluster. This reference is optional in case that the System Description doesn't use a complete Software Component Description (VFB View). This supports the inclusion of legacy systems. InstanceRef implemented by: PortGroupInSystem InstanceRef

Table A.382: PncMapping

Class	PortInterface (abstract)			
Note	Abstract base class for an interface that is either provided or required by a port of a software component.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Subclasses	AbstractRawDataStreamInterface, AbstractSuspendToRamInterface, AbstractSynchronizedTimeBase Interface, ClientServerInterface, CryptoInterface, DataInterface, DiagnosticPortInterface, FirewallState SwitchInterface , IdsmAbstractPortInterface, LogAndTraceInterface , ModeSwitchInterface, Network ManagementPortInterface , PersistenceInterface , PlatformHealthManagementInterface, ServiceInterface , StateManagementPortInterface, TriggerInterface			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	PortInterface (abstract)			
namespace (ordered)	SymbolProps	*	aggr	This represents the SymbolProps used for the definition of a hierarchical namespace applicable for the generation of code artifacts out of the definition of a ServiceInterface. Stereotypes: atpSplitable Tags: atp.Splitkey=namespace.shortName This Attribute is only used by the AUTOSAR Adaptive Platform.

Table A.383: PortInterface

Class	PortInterfaceToDataTypeMapping			
Note	This meta-class represents the ability to associate a PortInterface with a DataTypeMappingSet. This association is needed for the generation of header files in the scope of a single PortInterface. The association is intentionally made outside the scope of the PortInterface itself because the designers of a PortInterface most likely will not want to add details about the level of ImplementationDataType. Tags: atp.recommendedPackage=PortInterfaceToDataTypeMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataTypeMappingSet	DataTypeMappingSet	*	ref	This represents the reference to the applicable data TypemappingSet Tags: atp.StatusComment=Reserved for adaptive platform
portInterface	PortInterface	0..1	ref	This represents the reference to the applicable Port Interface Tags: atp.StatusComment=Reserved for adaptive platform

Table A.384: PortInterfaceToDataTypeMapping

Class	PortPrototype (abstract)			
Note	Base class for the ports of an AUTOSAR software component. The aggregation of PortPrototypes is subject to variability with the purpose to support the conditional existence of ports.			
Base	ARObject, AtpBlueprintable, AtpFeature, AtpPrototype, Identifiable , MultilanguageReferrable, Referrable			
Subclasses	AbstractProvidedPortPrototype, AbstractRequiredPortPrototype			
Aggregated by	AtpClassifier.atpFeature, SwComponentType.port			
Attribute	Type	Mult.	Kind	Note
clientServerAnnotation	ClientServerAnnotation	*	aggr	Annotation of this PortPrototype with respect to client/server communication.
delegatedPortAnnotation	DelegatedPortAnnotation	0..1	aggr	Annotations on this delegated port.
ioHwAbstractionServerAnnotation	IoHwAbstractionServerAnnotation	*	aggr	Annotations on this IO Hardware Abstraction port.
modePortAnnotation	ModePortAnnotation	*	aggr	Annotations on this mode port.
nvDataPortAnnotation	NvDataPortAnnotation	*	aggr	Annotations on this non volatile data port.
parameterPortAnnotation	ParameterPortAnnotation	*	aggr	Annotations on this parameter port.





Class	PortPrototype (abstract)			
portPrototype Props	PortPrototypeProps	0..1	aggr	This attribute allows for the definition of further qualification of the semantics of a PortPrototype. This Attribute is only used by the AUTOSAR Adaptive Platform.
senderReceiver Annotation	SenderReceiver Annotation	*	aggr	Collection of annotations of this ports sender/receiver communication. Stereotypes: atpSplitable Tags: atp.Splitkey=senderReceiverAnnotation
triggerPort Annotation	TriggerPortAnnotation	*	aggr	Annotations on this trigger port.

Table A.385: PortPrototype

Class	PortPrototypeProps (abstract)			
Note	This meta-class represents the ability to define a further qualification of semantics of sub-classes of Port Prototype. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Subclasses	RPortPrototypeProps			
Aggregated by	PortPrototype.portPrototypeProps			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.386: PortPrototypeProps

Class	Process			
Note	This meta-class provides information required to execute the referenced Executable. Tags: atp.recommendedPackage=Processes This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AbstractExecutionContext, AtpClassifier, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDeploymentElement, Uploadable PackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
design	ProcessDesign	0..1	ref	This reference represents the identification of the design-time representation for the Process that owns the reference.
executable	Executable	*	ref	Reference to executable that is executed in the process. Stereotypes: atpUriDef
functionCluster Affiliation	String	0..1	attr	This attribute specifies which functional cluster the Process is affiliated with.
numberOf RestartAttempts	PositiveInteger	0..1	attr	This attribute defines how often a process shall be restarted if the start fails. numberOfRestartAttempts = "0" OR Attribute not existing, start once numberOfRestartAttempts = "1", start a second time
preMapping	Boolean	0..1	attr	This attribute describes whether the executable is preloaded into the memory.





Class	Process			
processState Machine	ModeDeclarationGroup Prototype	0..1	aggr	Set of Process States that are defined for the process. This attribute is used to support the modeling of execution dependencies that utilize the condition of process state. Please note that the process states may not be modeled arbitrarily at any stage of the AUTOSAR workflow because the supported states are standardized in the context of the SWS Execution Management [3].
stateDependent StartupConfig	StateDependentStartup Config	*	aggr	Applicable startup configurations.

Table A.387: Process

Class	ProcessArgument			
Note	This meta-class has the ability to define command line arguments for processing by the Main function. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	StartupConfig.processArgument			
Attribute	Type	Mult.	Kind	Note
argument	String	0..1	attr	This represents one command-line argument to be processed by the executable software.

Table A.388: ProcessArgument

Class	ProcessDesign			
Note	This meta-class has the ability to stand in for a Process at the time when the Process does not yet exist. But its future existence already needs to be considered during design phase and for that a dedicated model element is required.. Tags: atp.recommendedPackage=ProcessDesigns This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement , ARObject , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
executable	Executable	*	ref	Reference to executable that is executed in the process.

Table A.389: ProcessDesign

Class	ProcessDesignToMachineDesignMapping			
Note	This element is used in the design phase to predefine a mapping of a process to a machine. Such a mapping may be overruled in the target-configuration phase. Tags: atp.recommendedPackage=ProcessDesignToMachineDesignMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement , ARObject , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
machineDesign	MachineDesign	0..1	ref	This reference identifies the MachineDesign in the context of the ProcessDesignToMachineDesignMapping.
processDesign	ProcessDesign	0..1	ref	This reference identifies the ProcessDesign in the context of the ProcessDesignToMachineDesignMapping.





Class	ProcessDesignToMachineDesignMapping			
shallNotRunOn	ProcessorCore	*	ref	This reference indicates a collection of cores onto which the mapped process shall not be executing.
shallRunOn	ProcessorCore	*	ref	This reference indicates a collection of cores onto which the mapped process shall be executing.

Table A.390: ProcessDesignToMachineDesignMapping

Class	ProcessToMachineMapping			
Note	This meta-class has the ability to associate a Process with a Machine. This relation involves the definition of further properties, e.g. timeouts. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ProcessToMachineMappingSet.processToMachineMapping			
Attribute	Type	Mult.	Kind	Note
design	ProcessDesignToMachineDesignMapping	0..1	ref	This reference represents the identification of the design-time representation for the ProcessToMachine Mapping that owns the reference.
machine	Machine	0..1	ref	This reference identifies the Machine in the context of the ProcessToMachineMapping.
nonOsModuleInstantiation	NonOsModuleInstantiation	0..1	ref	This supports the optional case that the process represents a platform module.
persistenceCentralStorageURI	UriString	0..1	attr	This attribute identifies a central place for the mapped Process to store the list of available storages and version information.
process	Process	0..1	ref	This reference identifies the Process in the context of the ProcessToMachineMapping.
shallNotRunOn	ProcessorCore	*	ref	This reference indicates a collection of cores onto which the mapped process shall not be executing.
shallRunOn	ProcessorCore	*	ref	This reference indicates a collection of cores onto which the mapped process shall be executing.

Table A.391: ProcessToMachineMapping

Class	Processor			
Note	This represents a processor for the execution of an AUTOSAR adaptive platform This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	Machine.processor , MachineDesign.processor			
Attribute	Type	Mult.	Kind	Note
core	ProcessorCore	*	aggr	This represents the collection of cores owned by the enclosing processor.

Table A.392: Processor

Class	ProcessorCore			
Note	This meta-class represents the ability to model a processor core for the execution of an AUTOSAR adaptive platform. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	Processor.core			





Class	ProcessorCore			
Attribute	Type	Mult.	Kind	Note
coreId	PositiveInteger	0..1	attr	This attribute represents a numerical value assigned to the specific core. The value can be taken e.g. for use in a bitmask.

Table A.393: ProcessorCore

Class	ProvidedApServiceInstance (abstract)			
Note	This meta-class represents the ability to describe the existence and configuration of a provided service instance in an abstract way. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AdaptivePlatformServiceInstance , CollectableElement, Identifiable , MultilanguageReferrable , PackageableElement, Referrable , UploadableDesignElement, UploadablePackageElement			
Subclasses	DdsProvidedServiceInstance , ProvidedSomeipServiceInstance , ProvidedUserDefinedServiceInstance			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.394: ProvidedApServiceInstance

Class	ProvidedSomeipServiceInstance			
Note	This meta-class represents the ability to describe the existence and configuration of a provided service instance in a concrete implementation on top of SOME/IP. Tags: atp.recommendedPackage=ServiceInstances This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AdaptivePlatformServiceInstance , CollectableElement, Identifiable , MultilanguageReferrable , PackageableElement, ProvidedApServiceInstance , Referrable , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
capability Record (ordered)	TagWithOptionalValue	*	aggr	A sequence of records to store arbitrary name/value pairs conveying additional information about the named service.
eventProps	SomeipEventProps	*	aggr	Configuration settings for individual events that are provided by the ServiceInstance.
loadBalancing Priority	PositiveInteger	0..1	attr	This attribute is used to specify the priority in the load balancing option of SOME/IP that is added to the Offer Service. When a client searches for all service instances of a service, the client shall choose the service instance with highest priority if one is defined.
loadBalancing Weight	PositiveInteger	0..1	attr	This attribute is used to specify the weight in the load balancing option of SOME/IP that is added to the Offer Service. When a client searches for all service instances of a service, the client shall choose the service instance with highest priority if one is defined. If several service instances exist with the highest priority the service instance shall be chosen based on the weights of the service instances.
method ResponseProps	SomeipMethodProps	*	aggr	Configuration settings for individual methods that are provided by the ServiceInstance.





Class	ProvidedSomeipServiceInstance			
priority	PositiveInteger	0..1	attr	This attribute defines the VLAN frame priority for SOME/IP messages that are resulting from this ProvidedSomeip ServiceInstance (Method and Event communication). Values from 0 (best effort) to 7 (highest) are allowed.
providedEvent Group	SomeipProvidedEvent Group	*	aggr	List of EventGroups that are provided by the Service Instance.
sdServerConfig	SomeipSdServer ServiceInstanceConfig	0..1	ref	Server specific configuration settings relevant for the SOME/IP service discovery.
serviceInstance Id	PositiveInteger	0..1	attr	Identification number that is used by SOME/IP service discovery to identify the instance of the service. The value 65535 for service instance id is reserved and should not be used.

Table A.395: ProvidedSomeipServiceInstance

Class	ProvidedUserDefinedServiceInstance			
Note	This meta-class represents the ability to describe the existence and configuration of a provided service instance in a concrete implementation that is not standardized by AUTOSAR. Tags: atp.recommendedPackage=ServiceInstances This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, AdaptivePlatformServiceInstance, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, ProvidedApServiceInstance, Referrable, Uploadable DesignElement, UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.396: ProvidedUserDefinedServiceInstance

Class	RPortPrototype			
Note	Component port requiring a certain port interface.			
Base	<i>ARObject, AbstractRequiredPortPrototype, AtpBlueprintable, AtpFeature, AtpPrototype, Identifiable, MultilanguageReferrable, PortPrototype, Referrable</i>			
Aggregated by	<i>AtpClassifier.atpFeature, SwComponentType.port</i>			
Attribute	Type	Mult.	Kind	Note
required Interface	PortInterface	0..1	tref	The interface that this port requires. Stereotypes: isOfType

Table A.397: RPortPrototype

Class	RPortPrototypeProps			
Note	PortPrototypeProps for a RPort. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject, PortPrototypeProps</i>			
Aggregated by	PortPrototype.portPrototypeProps			
Attribute	Type	Mult.	Kind	Note





Class	RPortPrototypeProps			
searchIntention	SearchIntentionEnum	0..1	attr	This attribute is used to specify the intention of the developer of the enclosing software-component in terms of whether the respective PortPrototype shall be used to search for a specific service instance or all instances of the given service. Please note that the value of this attribute does not create a binding contract. The actual search behavior is defined as part of the service instance manifest.

Table A.398: RPortPrototypeProps

Class	RawDataStreamEthernetTcpUdpCredentials			
Note	This meta-class represents the ability to create a configuration of network credentials for a raw data stream connection over TCP and UDP (inherited from base class). This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AbstractRawDataStreamEthernetCredentials , Describable			
Aggregated by	EthernetRawDataStreamRemoteServerConfig.unicastCredentials			
Attribute	Type	Mult.	Kind	Note
tcpPort	PositiveInteger	0..1	attr	This attribute represents the configuration of a TCP port number.

Table A.399: RawDataStreamEthernetTcpUdpCredentials

Class	RawDataStreamEthernetUdpCredentials			
Note	This meta-class represents the ability to create a configuration of network credentials for a raw data stream connection over UDP. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AbstractRawDataStreamEthernetCredentials , Describable			
Aggregated by	EthernetRawDataStreamRemoteClientConfig.multicastCredentials , EthernetRawDataStreamRemoteClientConfig.unicastUdpCredentials , EthernetRawDataStreamRemoteServerConfig.multicastCredentials			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.400: RawDataStreamEthernetUdpCredentials

Class	RecordValueSpecification			
Note	Specifies the values for a record.			
Base	ARObject, CompositeValueSpecification , ValueSpecification			
Aggregated by	ApplicationAssocMapElementValueSpecification.key , ApplicationAssocMapElementValueSpecification.value , ArrayValueSpecification.element , CalibrationParameterValue.applInitValue , CalibrationParameterValue.implInitValue , CompositeRuleBasedValueSpecification.argument , ConstantSpecification.valueSpec , CryptoServiceKey.developmentValue , DiagnosticEnvDataCondition.compareValue , DiagnosticEnvDataElementCondition.compareValue , DiagnosticEnvSovdDataCondition.compareValue , FieldSenderComSpec.initValue , ISignal.initValue , ISignal.receptionDefaultValue , ISignal.timeoutSubstitutionValue , NonqueuedReceiverComSpec.initValue , NonqueuedReceiverComSpec.timeoutSubstitutionValue , NonqueuedSenderComSpec.initValue , NvProvideComSpec.ramBlockInitValue , NvProvideComSpec.romBlockInitValue , NvRequireComSpec.initValue , ParameterDataPrototype.initValue , ParameterProvideComSpec.initValue , ParameterRequireComSpec.initValue , PersistenceDataRequiredComSpec.initValue , PersistenceKeyValuePair.initValue , PortDefinedArgumentValue.value , PortPrototypeBlueprintInitValue.value , RecordValueSpecification.field , SomeipEventDeployment.eventReceptionDefaultValue , StateManagementCompareCondition.compareValue , SwDataDefProps.invalidValue , UserDefinedEventDeployment.eventReceptionDefaultValue , VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note





Class	RecordValueSpecification			
field (ordered)	ValueSpecification	*	aggr	<p>The value for a single record field. This could also be mapped explicitly to a record element of the data type using the shortName of the ValueSpecification. But this would introduce a relationship to the data type that is too strong. As of now, it is only important that the structure of the data type matches the structure of the Value Specification independently of the shortNames.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=field, field.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>

Table A.401: RecordValueSpecification

Class	RecoveryNotification			
Note	<p>This meta-class represents a PHM action that can trigger a recovery operation inside a piece of State Management software.</p> <p>Tags: atp.recommendedPackage=RecoveryNotifications</p> <p>This Class is only used by the AUTOSAR Adaptive Platform.</p>			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, Packageable Element, Referrable, UploadableDeploymentElement, UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
recovery Notification Timeout	TimeValue	0..1	attr	<p>The maximum acceptable amount of time (in seconds), Platform Health Management waits for an acknowledgement by State Management after sending the notification.</p>

Table A.402: RecoveryNotification

Class	RecoveryNotificationToPPortPrototypeMapping			
Note	<p>This meta-class represents the ability to associate a RecoveryNotification to a PPortPrototype while also being able to identify the respective Process in which the actual recovery executes.</p> <p>Tags: atp.recommendedPackage=RecoveryNotificationMappings</p> <p>This Class is only used by the AUTOSAR Adaptive Platform.</p>			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, Packageable Element, Referrable, UploadableDeploymentElement, UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
process	Process	0..1	ref	<p>Reference to the process which represents the State Management instance that the recovery notification shall be applied to.</p>
recoveryAction	PPortPrototype	0..1	iref	<p>This reference identifies the PortPrototype to be addressed as part of a PHM recovery.</p> <p>InstanceRef implemented by: PPortPrototypeIn ExecutableInstanceRef</p>
recovery Notification	RecoveryNotification	0..1	ref	<p>This reference identifies the applicable Recovery Notification to be mapped.</p>

Table A.403: RecoveryNotificationToPPortPrototypeMapping

Class	ReferenceValueSpecification			
Note	Specifies a reference to a data prototype to be used as an initial value for a pointer in the software.			
Base	<i>ARObject</i> , ValueSpecification			
Aggregated by	ApplicationAssocMapElementValueSpecification.key , ApplicationAssocMapElementValueSpecification.value , ArrayValueSpecification.element , CalibrationParameterValue.applInitValue , CalibrationParameterValue.implInitValue , ConstantSpecification.valueSpec , CryptoServiceKey.developmentValue , DiagnosticEnvDataCondition.compareValue , DiagnosticEnvDataElementCondition.compareValue , DiagnosticEnvSovdDataCondition.compareValue , FieldSenderComSpec.initValue , ISignal.initValue , ISignal.receptionDefaultValue , ISignal.timeoutSubstitutionValue , NonqueuedReceiverComSpec.initValue , NonqueuedReceiverComSpec.timeoutSubstitutionValue , NonqueuedSenderComSpec.initValue , NvProvideComSpec.ramBlockInitValue , NvProvideComSpec.romBlockInitValue , NvRequireComSpec.initValue , ParameterDataPrototype.initValue , ParameterProvideComSpec.initValue , ParameterRequireComSpec.initValue , PersistencyDataRequiredComSpec.initValue , PersistencyKeyValuePair.initValue , PortDefinedArgumentValue.value , PortPrototypeBlueprintInitValue.value , RecordValueSpecification.field , SomeipEventDeployment.eventReceptionDefaultValue , StateManagementCompareCondition.compareValue , SwDataDefProps.invalidValue , UserDefinedEventDeployment.eventReceptionDefaultValue , VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note
referenceValue	DataPrototype	0..1	ref	The referenced data prototype.

Table A.404: ReferenceValueSpecification

Class	Referrable (abstract)			
Note	Instances of this class can be referred to by their identifier (while adhering to namespace borders).			
Base	<i>ARObject</i>			
Subclasses	<i>AtpDefinition</i> , <i>BswDistinguishedPartition</i> , <i>BswModuleCallPoint</i> , <i>BswModuleClientServerEntry</i> , <i>BswVariableAccess</i> , <i>CouplingPortTrafficClassAssignment</i> , <i>CpplImplementationData typeContextTarget</i> , <i>DiagnosticEnvModeElement</i> , <i>EthernetPriorityRegeneration</i> , <i>ExclusiveAreaNestingOrder</i> , <i>HwDescriptionEntity</i> , <i>ImplementationProps</i> , <i>ModeTransition</i> , <i>MultilanguageReferrable</i> , <i>NmNetworkHandle</i> , <i>PncMappingIdent</i> , <i>SingleLanguageReferrable</i> , SoConIPdulIdentifier , SomeipRequiredEventGroup , <i>TpConnectionIdent</i>			
Attribute	Type	Mult.	Kind	Note
shortName	Identifier	1	attr	This specifies an identifying shortName for the object. It needs to be unique within its context and is intended for humans but even more for technical reference. Stereotypes: atpIdentityContributor Tags: xml.enforceMinMultiplicity=true xml.sequenceOffset=-100
shortName Fragment	ShortNameFragment	*	aggr	This specifies how the Referrable.shortName is composed of several shortNameFragments. Tags: xml.sequenceOffset=-90

Table A.405: Referrable

Class	RemoteEndpointConfiguration			
Note	This meta-class is used to define the IP address and port of a peer. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i>			
Aggregated by	PlatformModuleEthernetEndpointConfiguration.remoteConfig			
Attribute	Type	Mult.	Kind	Note
ipv4Address	Ip4AddressString	0..1	attr	remote Unicast or Multicast IPv4 Address
ipv6Address	Ip6AddressString	0..1	attr	remote Unicast or Multicast IPv6 Address
tcpPort	PositiveInteger	0..1	attr	remote tcpPort
udpPort	PositiveInteger	0..1	attr	remote udpPort

Table A.406: RemoteEndpointConfiguration

Class	RequiredApServiceInstance (abstract)			
Note	This meta-class represents the ability to describe the existence and configuration of a required service instance in an abstract way. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AdaptivePlatformServiceInstance , CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDesignElement, UploadablePackageElement			
Subclasses	DdsRequiredServiceInstance , RequiredSomeipServiceInstance , RequiredUserDefinedServiceInstance			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.407: RequiredApServiceInstance

Class	RequiredSomeipServiceInstance			
Note	This meta-class represents the ability to describe the existence and configuration of a required service instance in a concrete implementation on top of SOME/IP. Tags: atp.recommendedPackage=ServiceInstances This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AdaptivePlatformServiceInstance , CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , RequiredApServiceInstance , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
blocklisted Version	SomeipServiceVersion	*	aggr	Collection of blocklisted versions.
capability Record (ordered)	TagWithOptionalValue	*	aggr	A sequence of records to store arbitrary name/value pairs conveying additional information about the named service.
methodRequest Props	SomeipMethodProps	*	aggr	Configuration settings for individual methods that are requested by the ServiceInstance.
requiredEvent Group	SomeipRequiredEvent Group	*	aggr	List of EventGroups that are used by the RequiredService Instance.
requiredMinor Version	AnyVersionString	0..1	attr	This attribute is used to configure for which minor version of the Someip ServiceInterface the Service Discovery will search. Value can be set to a number that represents the Minor Version of the searched service or to ANY.
requiredService InstanceId	AnyServiceInstanceId	0..1	attr	This attribute represents the ability to describe the required service instance ID.
sdClientConfig	SomeipSdClientService InstanceConfig	0..1	ref	Client specific configuration settings relevant for the SOME/IP service discovery.
versionDriven FindBehavior	ServiceVersion AcceptanceKindEnum	0..1	attr	Defines the service discovery find behavior.

Table A.408: RequiredSomeipServiceInstance

Class	RequiredUserDefinedServiceInstance			
Note	This meta-class represents the ability to describe the existence and configuration of a required service instance in a concrete implementation that is not standardized by AUTOSAR. Tags: atp.recommendedPackage=ServiceInstances This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AdaptivePlatformServiceInstance , CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , RequiredApServiceInstance , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			





Class	RequiredUserDefinedServiceInstance			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.409: RequiredUserDefinedServiceInstance

Class	ResourceGroup			
Note	This meta-class represents a resource group that limits the resource usage of a collection of processes. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	OsModuleInstantiation.resourceGroup			
Attribute	Type	Mult.	Kind	Note
cpuUsage	PositiveInteger	0..1	attr	CPU resource limit in percentage of the total CPU capacity on the machine.
memUsage	PositiveInteger	0..1	attr	Memory limit in bytes.

Table A.410: ResourceGroup

Class	RootSwComponentPrototype			
Note	The RootSwCompositionPrototype represents the top-level-composition of software components within an Executable. The contained SwComponentPrototypes are fully specified by their SwComponentTypes (including Port Prototypes, PortInterfaces, VariableDataPrototypes, etc.). This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AtpFeature , AtpPrototype , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	AtpClassifier.atpFeature , Executable.rootSwComponentPrototype			
Attribute	Type	Mult.	Kind	Note
applicationType	SwComponentType	0..1	tref	This SwComponentType acts as the Type of the RootSw ComponentPrototype. Stereotypes: isOfType

Table A.411: RootSwComponentPrototype

Class	SecOcJobRequirement			
Note	Requirements for the cryptographic job that need to be executed.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	SecOcSecureComProps.jobRequirement			
Attribute	Type	Mult.	Kind	Note
secOcJob Semantic	SecOcJobSemantic Enum	0..1	attr	This attribute defines the cryptographic algorithm that needs to be supported.

Table A.412: SecOcJobRequirement

Class	SecOcSecureComProps			
Note	Configuration of AUTOSAR SecOC. Tags: atp.recommendedPackage=SecureComProps			
Base	ARElement, ARObject, CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , SecureComProps , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			





Class	SecOcSecureComProps			
Attribute	Type	Mult.	Kind	Note
authentication	CryptoServicePrimitive	0..1	ref	This reference defines the authentication algorithm used for MAC generation and verification.
authentication BuildAttempts	PositiveInteger	0..1	attr	This attribute defines the additional number of authentication build attempts that are to be carried out when the generation of the authentication information failed for a given message. If zero is set then only one authentication attempt is done.
authentication VerifyAttempts	PositiveInteger	0..1	attr	This attribute defines the additional number of authentication attempts that are to be carried out when the generation of the authentication information failed for a given message. If zero is set then only one authentication attempt is done.
authInfoTx Length	PositiveInteger	0..1	attr	This attribute defines the length in bits of the authentication code to be included in the payload of the authenticated Message.
freshnessValue Length	PositiveInteger	0..1	attr	This attribute defines the complete length in bits of the Freshness Value.
freshnessValue TxLength	PositiveInteger	0..1	attr	This attribute defines the length in bits of the Freshness Value to be included in the payload of the secured message.
jobRequirement	SecOcJobRequirement	*	aggr	Collection of cryptographic job requirements.

Table A.413: SecOcSecureComProps

Class	SecureComProps (abstract)			
Note	This meta-class defines a communication security protocol and its configuration settings.			
Base	ARElement , ARObject , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			
Subclasses	DdsSecureComProps , SecOcSecureComProps , TlsSecureComProps			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.414: SecureComProps

Class	SecuredIPdu			
Note	If useAsCryptographicPdu is not set or set to false this IPdu contains the payload of an Authentic IPdu supplemented by additional Authentication Information (Freshness Counter and an Authenticator). If useAsCryptographicPdu is set to true this IPdu contains the Authenticator for a payload that is transported in a separate message. The separate Authentic IPdu is described by the Pdu that is referenced with the payload reference from this SecuredIPdu. Tags: atp.recommendedPackage=Pdus			
Base	ARElement , ARObject , CollectableElement , FibexElement , IPdu , Identifiable , MultilanguageReferrable , PackageableElement , Pdu , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
authentication Props	SecureCommunication AuthenticationProps	0..1	ref	Reference to authentication properties that are valid for this SecuredIPdu.





Class	SecuredIPdu			
dynamic RuntimeLength Handling	Boolean	0..1	attr	Defines whether the length information for handling this SecuredIPdu with SecuredIPdu.useSecuredPdu Header=noHeader is taken from the configuration or from the actually provided length information during runtime. true: SecuredIPdu length information is taken from the actually provided length information during runtime. false: SecuredIPdu length information is taken from the configuration.
freshnessProps	SecureCommunication FreshnessProps	0..1	ref	Reference to freshness properties that are valid for this SecuredIPdu.
payload	PduTriggering	0..1	ref	Reference to a Pdu that will be protected against unauthorized manipulation and replay attacks.
secure Communication Props	SecureCommunication Props	0..1	aggr	Specific configuration properties for this SecuredIPdu.
useAs Cryptographic IPdu	Boolean	0..1	attr	If this attribute is set to true the SecuredIPdu contains the Authentication Information for an AuthenticIPdu that is transmitted in a separate message. The AuthenticIPdu contains the original payload, i.e. the secured data. If this attribute is set to false this SecuredIPdu contains the payload of an Authentic IPdu supplemented by additional Authentication Information.
useSecuredPdu Header	SecuredPduHeader Enum	0..1	attr	This attribute defines the size of the header which is inserted into the SecuredIPdu. If this attribute is set to anything but noHeader, the SecuredIPdu contains the Secured I-PDU Header to indicate the length of the AuthenticIPdu. The AuthenticIPdu contains the original payload, i.e. the secured data.

Table A.415: SecuredIPdu

Class	SecurityEventMapping			
Note	This meta-class represents a reportable instance of a security event. Tags: atp.Status=candidate atp.recommendedPackage=SecurityEventMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, Packageable Element, Referrable, UploadableDeploymentElement, UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
process	Process	0..1	ref	This reference identifies the process in which context the security event is reported. Tags: atp.Status=candidate
reportingPort Prototype	RPortPrototype	0..1	iref	This instanceRef identifies the PortPrototype over which the security event is reported. Stereotypes: atpUriDef Tags: atp.Status=candidate InstanceRef implemented by: RPortPrototypeIn ExecutableInstanceRef
securityEvent	SecurityEventDefinition	0..1	ref	This reference identifies the corresponding SecurityEvent Definition. Tags: atp.Status=candidate

Table A.416: SecurityEventMapping

Class	SenderComSpec (abstract)			
Note	Communication attributes for a sender port (PPortPrototype typed by ServiceInterface) that are relevant for events and field notifiers.			
Base	ARObject , PPortComSpec			
Subclasses	FieldSenderComSpec , NonqueuedSenderComSpec , QueuedSenderComSpec			
Aggregated by	AbstractProvidedPortPrototype.providedComSpec , PortPrototypeBlueprint.providedComSpec			
Attribute	Type	Mult.	Kind	Note
dataElement	AutosarDataPrototype	0..1	ref	Data element these quality of service attributes apply to. Stereotypes: atpIdentityContributor
senderIntent	SenderIntentEnum	0..1	attr	This attribute represents the expressed intent of the sender. The sender may decide to claim that existing resources of a ServiceInterface are expressly not used by this specific sender. The conceptual background of this claim may be driven by security, safety, etc. Tags: atp.Status=candidate This Attribute is only used by the AUTOSAR Adaptive Platform.
transmission Props	TransmissionComSpec Props	0..1	aggr	This aggregation represents the definition transmission props in the context of the enclosing SenderComSpec .
usesEndToEnd Protection	Boolean	0..1	attr	This indicates whether the corresponding dataElement shall be transmitted using end-to-end protection. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.417: SenderComSpec

Enumeration	SerializationTechnologyEnum
Note	This enumeration allows to choose a Serialization Technology. This Enumeration is only used by the AUTOSAR Adaptive Platform.
Aggregated by	SomeipEventDeployment.serializer
Literal	Description
signalBased	Signal-Based serializer. Tags: atp.EnumerationLiteralIndex=1
someip	SOME/IP Serializer Tags: atp.EnumerationLiteralIndex=0

Table A.418: SerializationTechnologyEnum

Class	ServiceEventDeployment (abstract)			
Note	This abstract meta-class represents the ability to specify a deployment of an Event to a middleware transport layer. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable , ServiceInterfaceDeploymentElement			
Subclasses	DdsEventDeployment , SomeipEventDeployment , UserDefinedEventDeployment			
Aggregated by	ServiceInterfaceDeployment.eventDeployment			
Attribute	Type	Mult.	Kind	Note
event	VariableDataPrototype	0..1	ref	Reference to an Event that is deployed to a middleware transport layer. Stereotypes: atpUriDef
trigger	Trigger	0..1	ref	Reference to a Trigger that is deployed to a middleware transport layer. Stereotypes: atpUriDef

Table A.419: ServiceEventDeployment

Class	ServiceFieldDeployment (abstract)			
Note	This abstract meta-class represents the ability to specify a deployment of a Field to a middleware transport layer. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , ServiceInterfaceDeploymentElement			
Subclasses	DdsFieldDeployment, SomeipFieldDeployment , UserDefinedFieldDeployment			
Aggregated by	ServiceInterfaceDeployment.fieldDeployment			
Attribute	Type	Mult.	Kind	Note
field	Field	0..1	ref	Reference to a Field that is deployed to a middleware transport layer. Stereotypes: atpUriDef

Table A.420: ServiceFieldDeployment

Class	ServiceInstanceToMachineMapping (abstract)			
Note	This meta-class represents the ability to map one or several AdaptivePlatformServiceInstances to a CommunicationConnector of a Machine. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			
Subclasses	DdsServiceInstanceToMachineMapping , SomeipServiceInstanceToMachineMapping , UserDefinedServiceInstanceToMachineMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
communication Connector	CommunicationConnector	0..1	ref	Reference to the Machine to which the ServiceInstance is mapped.
secOcCom PropsFor Multicast	SecOcSecureComProps	*	ref	Reference to communication security configuration settings that are valid for the udp multicast endpoint (Port + Multicast IP Address) defined by the ServiceInstanceToMachineMapping.
secureCom PropsForTcp	SecureComProps	0..1	ref	Reference to communication security configuration settings that are valid for the tcp unicast endpoint (Tcp Port + Unicast IP Address) defined by the ServiceInstanceToMachineMapping.
secureCom PropsForUdp	SecureComProps	0..1	ref	Reference to communication security configuration settings that are valid for the udp unicast endpoint (Udp Port + Unicast IP Address) defined by the ServiceInstanceToMachineMapping.
serviceInstance	AdaptivePlatformServiceInstance	*	ref	Reference to a ServiceInstance that is mapped to the Machine.

Table A.421: ServiceInstanceToMachineMapping

Class	ServiceInstanceToPortPrototypeMapping			
Note	This meta-class represents the ability to assign a transport layer dependent ServiceInstance to a Port Prototype. With this mapping it is possible to define how specific PortPrototypes are represented in the middleware in terms of service configuration. Tags: atp.recommendedPackage=ServiceInstanceToPortPrototypeMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	ServiceInstanceToPortPrototypeMapping			
portPrototype	PortPrototype	0..1	iref	Reference to a specific PortPrototype that represents the ServiceInstance. Stereotypes: atpUriDef InstanceRef implemented by: PortPrototypeInExecutableInstanceRef
process	Process	0..1	ref	Reference to the Process in which the enclosing ServiceInstanceToPortPrototypeMapping is executed. Stereotypes: atpSplitable Tags: atp.Splitkey=process
processDesign	ProcessDesign	0..1	ref	Reference to the ProcessDesign in which the Executable that contains the SoftwareComponent and the referenced PortPrototype is executed. Stereotypes: atpUriDef
serviceInstance	AdaptivePlatformServiceInstance	0..1	ref	Reference to a ServiceInstance that is represented in the Software Component by the mapped group of Port Prototypes.

Table A.422: ServiceInstanceToPortPrototypeMapping

Class	ServiceInstanceToSignalMapping			
Note	This meta-class is defined for a specific ServiceInstance and contains the mappings of elements of a ServiceInterface for which the ServiceInstance is defined to individual ISignalTriggerings. Tags: atp.recommendedPackage=ServiceInstanceToSignalMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
eventElementMapping	SignalBasedEventElementToISignalTriggeringMapping	*	aggr	Mapping of an event or an element inside of the event to an ISignalTriggering.
fieldMapping	SignalBasedFieldToISignalTriggeringMapping	*	aggr	Mapping of a field to ISignalTriggerings.
fireAndForgetMethodMapping	SignalBasedFireAndForgetMethodToISignalTriggeringMapping	*	aggr	Mapping of an ISignalTriggering being part of a fire and forget message to a ClientServerOperation.
serviceInstance	AdaptivePlatformServiceInstance	0..1	ref	Reference to a ServiceInstance from which the corresponding ServiceInterface elements will be transported in the signal-based way over a communication medium.
triggerMapping	SignalBasedTriggerToISignalTriggeringMapping	*	aggr	Mapping of a trigger to an ISignalTriggering.

Table A.423: ServiceInstanceToSignalMapping

Class	ServiceInterface
Note	This represents the ability to define a PortInterface that consists of a heterogeneous collection of methods, events and fields. Tags: atp.recommendedPackage=ServiceInterfaces This Class is only used by the AUTOSAR Adaptive Platform.
Base	<i>ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, PortInterface, Referrable</i>





Class	ServiceInterface			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
event	VariableDataPrototype	*	aggr	This represents the collection of events defined in the context of a ServiceInterface. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=event.shortName, event.variationPoint.shortLabel vh.latestBindingTime=blueprintDerivationTime xml.sequenceOffset=30
field	Field	*	aggr	This represents the collection of fields defined in the context of a ServiceInterface. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=field.shortName, field.variationPoint.shortLabel vh.latestBindingTime=blueprintDerivationTime xml.sequenceOffset=40
majorVersion	PositiveInteger	0..1	attr	Major version of the service contract. Tags: xml.sequenceOffset=10
method	ClientServerOperation	*	aggr	This represents the collection of methods defined in the context of a ServiceInterface. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=method.shortName, method.variationPoint.shortLabel vh.latestBindingTime=blueprintDerivationTime xml.sequenceOffset=50
minorVersion	PositiveInteger	0..1	attr	Minor version of the service contract. Tags: xml.sequenceOffset=20
trigger	Trigger	*	aggr	This represents the collection of triggers defined in the context of a ServiceInterface. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=trigger.shortName, trigger.variationPoint.shortLabel vh.latestBindingTime=blueprintDerivationTime xml.sequenceOffset=60

Table A.424: ServiceInterface

Class	ServiceInterfaceDeployment (abstract)			
Note	Middleware transport layer specific configuration settings for the ServiceInterface and all contained ServiceInterface elements. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement			
Subclasses	DdsServiceInterfaceDeployment, SomeipServiceInterfaceDeployment, UserDefinedServiceInterfaceDeployment			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	<i>ServiceInterfaceDeployment</i> (abstract)			
event Deployment	ServiceEvent Deployment	*	aggr	Middleware transport layer specific configuration settings for an Event that is defined in the ServiceInterface. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=eventDeployment.shortName, event Deployment.variationPoint.shortLabel vh.latestBindingTime=blueprintDerivationTime
fieldDeployment	ServiceField Deployment	*	aggr	Middleware transport layer specific configuration settings for a Field that is defined in the ServiceInterface. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=fieldDeployment.shortName, field Deployment.variationPoint.shortLabel vh.latestBindingTime=blueprintDerivationTime
method Deployment	ServiceMethod Deployment	*	aggr	Middleware transport layer specific configuration settings for a method that is defined in the ServiceInterface. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=methodDeployment.shortName, method Deployment.variationPoint.shortLabel vh.latestBindingTime=blueprintDerivationTime
serviceInterface	ServiceInterface	0..1	ref	Reference to a ServiceInterface that is deployed to a middleware transport layer. Stereotypes: atpUriDef

Table A.425: ServiceInterfaceDeployment

Class	<i>ServiceInterfaceDeploymentElement</i> (abstract)			
Note	This meta-class provides shared attributes for concrete classes used in the context of the definition of the ServiceInterfaceDeployment. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Subclasses	ServiceEventDeployment , ServiceFieldDeployment , ServiceMethodDeployment			
Attribute	Type	Mult.	Kind	Note
minimumSend Interval	TimeValue	0..1	attr	Minimum time between two consecutive transmissions of a service instance element (event, field, trigger or method call). Unit: seconds

Table A.426: ServiceInterfaceDeploymentElement

Class	<i>ServiceInterfaceElementMapping</i> (abstract)			
Note	This abstract meta-class acts as base class for the mapping of specific elements of a ServiceInterface. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	ServiceInterfaceEventMapping , ServiceInterfaceFieldMapping , ServiceInterfaceMethodMapping , ServiceInterfaceTriggerMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.427: ServiceInterfaceElementMapping

Class	ServiceInterfaceElementSecureComConfig			
Note	This element allows to secure the communication of the referenced ServiceInterface element. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	AdaptivePlatformServiceInstance.secureComConfig			
Attribute	Type	Mult.	Kind	Note
dataId	PositiveInteger	0..1	attr	This attribute defines a unique numerical identifier for the referenced ServiceInterface element.
event	ServiceEvent Deployment	0..1	ref	Reference to an event that is protected by a security protocol.
fieldNotifier	ServiceField Deployment	0..1	ref	Reference to a field notifier that is protected by a security protocol.
freshnessValue Id	PositiveInteger	0..1	attr	This attribute defines the Id of the Freshness Value.
getterCall	ServiceField Deployment	0..1	ref	Reference to a field getter call message that is protected by a security protocol.
getterReturn	ServiceField Deployment	0..1	ref	Reference to a field getter return message that is protected by a security protocol.
methodCall	ServiceMethod Deployment	0..1	ref	Reference to a method call message that is protected by a security protocol.
methodReturn	ServiceMethod Deployment	0..1	ref	Reference to a method return message that is protected by a security protocol.
securedRx Verification	Boolean	0..1	attr	This attribute defines whether the ServiceInterface element shall verify its security credentials during reception.
setterCall	ServiceField Deployment	0..1	ref	Reference to a field setter call message that is protected by a security protocol.
setterReturn	ServiceField Deployment	0..1	ref	Reference to a field setter return message that is protected by a security protocol.

Table A.428: ServiceInterfaceElementSecureComConfig

Class	ServiceInterfaceEventMapping			
Note	This meta-class allows to define a mapping between events of ServiceInterfaces that are mapped to each other by the ServiceInterfaceMapping. Tags: atp.recommendedPackage=ServiceInterfaceElementMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement , Identifiable , MultilanguageReferrable , Packageable Element , Referrable , ServiceInterfaceElementMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
sourceEvent	VariableDataPrototype	0..1	ref	Reference to an event that is contained in the source ServiceInterface.
targetEvent	VariableDataPrototype	0..1	ref	Reference to an event that is contained in the composite ServiceInterface.

Table A.429: ServiceInterfaceEventMapping

Class	ServiceInterfaceFieldMapping			
Note	This meta-class allows to define a mapping between fields of ServiceInterfaces that are mapped to each other by the ServiceInterfaceMapping. Tags: atp.recommendedPackage=ServiceInterfaceElementMappings This Class is only used by the AUTOSAR Adaptive Platform.			





Class	ServiceInterfaceFieldMapping			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , ServiceInterfaceElementMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
sourceField	Field	0..1	ref	Reference to a field that is contained in the source ServiceInterface.
targetField	Field	0..1	ref	Reference to a field that is contained in the composite ServiceInterface.

Table A.430: ServiceInterfaceFieldMapping

Class	ServiceInterfaceMapping			
Note	Specifies one ServiceInterfaceMapping that allows to define that a ServiceInterface is composite of several other ServiceInterfaces. Tags: atp.recommendedPackage=ServiceInterfaceMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AtpBlueprint, AtpBlueprintable, Identifiable , MultilanguageReferrable, PortInterfaceMapping , Referrable			
Aggregated by	PortInterfaceMappingSet.portInterfaceMapping			
Attribute	Type	Mult.	Kind	Note
compositeServiceInterface	ServiceInterface	0..1	ref	This represents the composite ServiceInterface.
sourceServiceInterface	ServiceInterface	*	ref	ServiceInterface that is mapped into the composite ServiceInterface.

Table A.431: ServiceInterfaceMapping

Class	ServiceInterfaceMethodMapping			
Note	This meta-class allows to define a mapping between methods of ServiceInterfaces that are mapped to each other by the ServiceInterfaceMapping. Tags: atp.recommendedPackage=ServiceInterfaceElementMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , ServiceInterfaceElementMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
sourceMethod	ClientServerOperation	0..1	ref	Reference to a method that is contained in the source ServiceInterface.
targetMethod	ClientServerOperation	0..1	ref	Reference to a method that is contained in the composite ServiceInterface.

Table A.432: ServiceInterfaceMethodMapping

Class	ServiceInterfaceTriggerMapping			
Note	This meta-class allows to define a mapping between triggers of ServiceInterfaces that are mapped to each other by the ServiceInterfaceMapping. Tags: atp.recommendedPackage=ServiceInterfaceElementMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , ServiceInterfaceElementMapping			
Aggregated by	ARPackage.element			





Class	ServiceInterfaceTriggerMapping			
Attribute	Type	Mult.	Kind	Note
sourceTrigger	Trigger	0..1	ref	Reference to a trigger that is contained in the source ServiceInterface.
targetTrigger	Trigger	0..1	ref	Reference to a trigger that is contained in the target ServiceInterface.

Table A.433: ServiceInterfaceTriggerMapping

Class	ServiceMethodDeployment (abstract)			
Note	This abstract meta-class represents the ability to specify a deployment of a Method to a middleware transport layer. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , ServiceInterfaceDeploymentElement			
Subclasses	SomeipMethodDeployment , UserDefinedMethodDeployment			
Aggregated by	ServiceInterfaceDeployment.methodDeployment			
Attribute	Type	Mult.	Kind	Note
method	ClientServerOperation	0..1	ref	Reference to a method that is deployed to a middleware transport layer. Stereotypes: atpUriDef

Table A.434: ServiceMethodDeployment

Class	ServiceTiming			
Note	This meta-class represents the timing view for one or more service instances. Tags: atp.Status=draft atp.recommendedPackage=TimingExtensions This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , TimingExtension			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
serviceInstance	AdaptivePlatformServiceInstance	*	ref	This defines the scope of a ServiceTiming. All corresponding timing descriptions and constraints shall be defined within this scope. Tags: atp.Status=draft

Table A.435: ServiceTiming

Enumeration	ServiceVersionAcceptanceKindEnum			
Note	Defined the possible acceptance kinds for required service instances.			
Aggregated by	ConsumedServiceInstance.versionDrivenFindBehavior, RequiredSomeipServiceInstance.versionDrivenFindBehavior			
Literal	Description			
exactOrAnyMinorVersion	Search for ANY or specific minor version service instance and select either ALL returned service instances (in case of ANY) or exactly the specific minor version service instances defined in required MinorVersion. Tags: atp.EnumerationLiteralIndex=0			





Enumeration	ServiceVersionAcceptanceKindEnum
minimumMinorVersion	Search for ANY minor version service instance and select only those service instances which have an equal or greater minor version than given in requiredMinorVersion. Tags: atp.EnumerationLiteralIndex=1

Table A.436: ServiceVersionAcceptanceKindEnum

Class	SignalBasedEventElementToSignalTriggeringMapping			
Note	This meta-class defines the mapping of a ServiceInterface event or an element that is defined inside of the event in case that the datatype is composite to an ISignalTriggering. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AbstractSignalBasedToSignalTriggeringMapping , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ServiceInstanceToSignalMapping.eventElementMapping			
Attribute	Type	Mult.	Kind	Note
dataPrototypeInServiceInterfaceRef	DataPrototypeInServiceInterfaceRef	0..1	aggr	Reference to a DataPrototype or to an internal structure of a DataPrototype in the context of a ServiceInterface.
filter	DataFilter	0..1	aggr	Defines an optional filter to be applied during translation.
iSignalTriggering	ISignalTriggering	0..1	ref	Reference to the ISignalTriggering that is used to transport a piece of data of an event that is defined in a ServiceInterface in a signal-based way over a communication channel.
transmissionTrigger	Boolean	0..1	attr	Defines whether the source element triggers the sending of the respective payload.

Table A.437: SignalBasedEventElementToSignalTriggeringMapping

Class	SignalBasedFieldToSignalTriggeringMapping			
Note	This meta-class defines the mapping of a ServiceInterface field to ISignalTriggerings that represent the notifier elements on a signal-based communication channel. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AbstractSignalBasedToSignalTriggeringMapping , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ServiceInstanceToSignalMapping.fieldMapping			
Attribute	Type	Mult.	Kind	Note
dataPrototypeInServiceInterfaceRef	DataPrototypeInServiceInterfaceRef	0..1	aggr	Reference to a DataPrototype or to an internal structure of a DataPrototype in the context of a ServiceInterface.
filter	DataFilter	0..1	aggr	Defines an optional filter to be applied during translation.
notifierSignalTriggering	ISignalTriggering	0..1	ref	Reference to the ISignalTriggering that is used to transport a piece of data of a notifier in a signal-based way over a communication channel.
transmissionTrigger	Boolean	0..1	attr	Defines whether the source notifier element triggers the sending of the respective payload.

Table A.438: SignalBasedFieldToSignalTriggeringMapping

Class	SignalBasedFireAndForgetMethodToSignalTriggeringMapping
Note	This meta-class defines the mapping of a ServiceInterface fire and forget method part to an ISignalTriggering. This Class is only used by the AUTOSAR Adaptive Platform.





Class	SignalBasedFireAndForgetMethodToSignalTriggeringMapping			
Base	ARObject, AbstractSignalBasedToSignalTriggeringMapping , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ServiceInstanceToSignalMapping.fireAndForgetMethodMapping			
Attribute	Type	Mult.	Kind	Note
dataPrototypeInMethodArgumentInstanceRef	DataPrototype	0..1	iref	Instance reference to a (potentially structured) member of a ClientServerOperation. InstanceRef implemented by: DataPrototypeInServiceInterfaceInstanceRef
iSignalTriggering	ISignalTriggering	0..1	ref	Reference to an ISignalTriggering being part of a fire and forget message.

Table A.439: SignalBasedFireAndForgetMethodToSignalTriggeringMapping

Class	SignalBasedTriggerToSignalTriggeringMapping			
Note	This meta-class defines the mapping of a ServiceInterface trigger to an ISignalTriggering. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AbstractSignalBasedToSignalTriggeringMapping , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ServiceInstanceToSignalMapping.triggerMapping			
Attribute	Type	Mult.	Kind	Note
iSignalTriggering	ISignalTriggering	0..1	ref	Reference to the ISignalTriggering that is used to transport the trigger that is defined in a ServiceInterface in a signal-based way over a communication channel.
trigger	Trigger	0..1	ref	Reference to a trigger defined in the context of a Service Interface.

Table A.440: SignalBasedTriggerToSignalTriggeringMapping

Class	SignalServiceTranslationEventProps			
Note	This element allows to define the properties which are applicable for the signal/service translation event.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	SignalServiceTranslationProps.signalServiceTranslationEventProps			
Attribute	Type	Mult.	Kind	Note
safeTranslation	Boolean	0..1	attr	Defined whether the translation shall happen in a safe way.
secureTranslation	Boolean	0..1	attr	Defined whether the translation shall happen in a secure way.
serviceElementMapping	AbstractSignalBasedToISignalTriggeringMapping	*	ref	Reference to the collection of SignalBased to ISignal Triggering mappings the properties apply to. This Attribute is only used by the AUTOSAR Adaptive Platform.

Table A.441: SignalServiceTranslationEventProps

Class	SignalServiceTranslationProps			
Note	This element allows to define the properties which are applicable for the signal/service translation service.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	SignalServiceTranslationPropsSet.signalServiceTranslationProps			
Attribute	Type	Mult.	Kind	Note





Class	SignalServiceTranslationProps			
serviceControl	SignalServiceTranslationControlEnum	0..1	attr	Defines how the service instance control shall behave.
signalServiceTranslationEventProps	SignalServiceTranslationEventProps	*	aggr	Defines properties for a single translated event.

Table A.442: SignalServiceTranslationProps

Class	SmInteractsWithNmMapping			
Note	This mapping represents an interaction from state management to network management. Tags: atp.Status=draft atp.recommendedPackage=FCInteractions This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, CollectableElement, FunctionalClusterInteractsWithFunctionalClusterMapping, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDeploymentElement, UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
actionItem	StateManagementNmActionItem	0..1	ref	This reference identifies the action item with which the state management wants to interact with network management. Tags: atp.Status=draft
nmNetworkHandle	NmNetworkHandle	0..1	ref	This reference identifies the network management handle that is affected by the interaction with the state management. Tags: atp.Status=draft

Table A.443: SmInteractsWithNmMapping

Class	SoConIPduIdentifier			
Note	Identification of Pdu content on a socket connection. This Identifier is required in case that multiple Pdus are transmitted over the same socket connection.			
Base	<i>ARObject, Referrable</i>			
Aggregated by	SocketConnectionIpdulIdentifierSet.iPdulIdentifier			
Attribute	Type	Mult.	Kind	Note
headerId	PositiveInteger	0..1	attr	If multiple Pdus are transmitted over the same connection this headerId can be used to distinguish between the different Pdus. For the constraints on constructing the headerId for SOME/IP also see PRS_SOMEIP_00245.
pduCollectionPduTimeout	TimeValue	0..1	attr	Defines the timeout in seconds the PDU collection shall be transmitted at the latest after this PDU has been put into the buffer.
pduCollectionSemantics	PduCollectionSemanticsEnum	0..1	attr	Specifies if the referenced PduTriggering shall be collected using a queued (i.e. all PDU instances) or last-is-best (i.e. only the last PDU instance) semantics. If this attribute is not present the behavior of "queued" is assumed.
pduCollectionTrigger	PduCollectionTriggerEnum	0..1	attr	Defines whether the referenced Pdu contributes to the triggering of the socket transmission if Pdu collection is enabled for this socket.
pduTriggering	PduTriggering	0..1	ref	Reference to a Pdu that is transmitted over a socket connection.

Table A.444: SoConIPduIdentifier

Class	SoftwareCluster			
Note	<p>This meta-class represents the ability to define an uploadable software-package, i.e. the SoftwareCluster shall contain all software and configuration for a given purpose.</p> <p>Tags: atp.recommendedPackage=SoftwareClusters</p> <p>This Class is only used by the AUTOSAR Adaptive Platform.</p>			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
artifact Checksum	ArtifactChecksum	*	aggr	<p>This aggregation carries the checksums for artifacts contained in the enclosing SoftwareCluster. Please note that the value of these checksums is only applicable at the time of configuration.</p> <p>Stereotypes: atpSplittable</p> <p>Tags: atp.Splitkey=artifactChecksum.shortName</p>
artifactLocator	ArtifactLocator	*	aggr	<p>This aggregation represents the artifact locations that are relevant in the context of the enclosing SoftwareCluster</p>
claimed FunctionGroup	ModeDeclarationGroup Prototype	*	ref	<p>Each SoftwareCluster can reserve the usage of a given functionGroup such that no other SoftwareCluster is allowed to use it</p>
contained ARElement	ARElement	*	ref	<p>This reference represents the collection of model elements that cannot derive from UploadablePackageElement and that contribute to the completeness of the definition of the SoftwareCluster.</p> <p>Stereotypes: atpSplittable</p> <p>Tags: atp.Splitkey=containedARElement</p>
contained Package Element	UploadablePackageElement	*	ref	<p>This reference identifies model elements that are required to complete the manifest content.</p> <p>Stereotypes: atpSplittable</p> <p>Tags: atp.Splitkey=containedPackageElement</p>
contained Process	Process	*	ref	<p>This reference represent the processes contained in the enclosing SoftwareCluster.</p>
design	SoftwareClusterDesign	*	ref	<p>This reference represents the identification of all SoftwareClusterDesigns applicable for the enclosing SoftwareCluster.</p> <p>Stereotypes: atpUriDef</p>
diagnostic Deployment Props	SoftwareCluster DiagnosticDeployment Props	0..1	ref	<p>This reference identifies the applicable SoftwareClusterDiagnosticDeploymentProps that are applicable for the referencing SoftwareCluster.</p>
license	Documentation	*	ref	<p>This attribute allows for the inclusion of the full text of a license of the enclosing SoftwareCluster. In many cases open source licenses require the inclusion of the full license text to any software that is released under the respective license.</p>
module Instantiation	AdaptiveModuleInstantiation	*	ref	<p>This reference identifies AdaptiveModuleInstantiations that need to be included with the SoftwareCluster in order to establish infrastructure required for the installation of the SoftwareCluster.</p> <p>Stereotypes: atpSplittable</p> <p>Tags: atp.Splitkey=moduleInstantiation</p>
releaseNotes	Documentation	0..1	ref	<p>This attribute allows for the explanations of changes since the previous version. The list of changes might require the creation of multiple paragraphs of test.</p>
typeApproval	String	0..1	attr	<p>This attribute carries the homologation information that may be specific for a given country.</p>
vendorId	PositiveInteger	0..1	attr	<p>Vendor ID of this Implementation according to the AUTOSAR vendor list.</p>
vendor Signature	CryptoService Certificate	0..1	ref	<p>This reference identifies the certificate that represents the vendor's signature.</p>





Class	SoftwareCluster			
version	StrongRevisionLabel String	0..1	attr	This attribute can be used to describe a version information for the enclosing SoftwareCluster.

Table A.445: SoftwareCluster

Class	SoftwareClusterDependencyCompareCondition			
Note	This meta-class represents the ability to specify a concrete dependency condition in the context of a SoftwareClusterDependencyFormula. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, SoftwareClusterDependencyFormulaPart			
Aggregated by	SoftwareClusterDependencyFormula.part			
Attribute	Type	Mult.	Kind	Note
compareType	SoftwareClusterDependencyOperator Enum	0..1	attr	This attribute identifies the semantics of the compare operator.
considerBuild Number	Boolean	0..1	attr	If this attribute is set to true then the build number shall be taken into account for the comparison. Build numbers don't have to be consecutive but could be created by some kind of hashing algorithm. In such a case it might make sense to include the build number in a test for equality but it is probably not reasonable to apply e.g. a less-than comparison.
softwareCluster Design	SoftwareClusterDesign	0..1	ref	This reference identifies the SoftwareClusterDesign to which the dependency/conflict applies.
version	StrongRevisionLabel String	0..1	attr	This attribute represents the value of a version against which the comparison shall be executed.

Table A.446: SoftwareClusterDependencyCompareCondition

Class	SoftwareClusterDependencyFormula			
Note	This meta-class represents the ability to define a dependency among SoftwareClusters. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, SoftwareClusterDependencyFormulaPart			
Aggregated by	SoftwareClusterDependencyFormula.part, SoftwareClusterDesign.conflictsTo, SoftwareClusterDesign.dependsOn			
Attribute	Type	Mult.	Kind	Note
operator	SoftwareClusterDependencyLogical OperatorEnum	0..1	attr	This logical operator can be used to relate the results of different SoftwareClusterDependencyParts.
part (ordered)	SoftwareClusterDependencyFormula Part	*	aggr	This aggregation represents the ordered collection of the parts of the SoftwareClusterDependencyFormula.

Table A.447: SoftwareClusterDependencyFormula

Class	SoftwareClusterDesign			
Note	This meta-class represents the ability for the OEM to design the grouping of software uploadable to a specific target Machine. Tags: atp.recommendedPackage=SoftwareClusterDesigns This Class is only used by the AUTOSAR Adaptive Platform.			





Class	SoftwareClusterDesign			
Base	ARElement, ARObject, AtpClassifier, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
conflictsTo	SoftwareClusterDependencyFormula	0..1	aggr	This aggregation handles conflicts. If it yields true then the SoftwareClusterDesign shall not be installed. Stereotypes: atpSplitable Tags: atp.Splitkey=conflictsTo
contained Process	ProcessDesign	*	ref	This reference represent the ProcessDesigns contained in the enclosing SoftwareCluster. Stereotypes: atpSplitable Tags: atp.Splitkey=containedProcess
dependsOn	SoftwareClusterDependencyFormula	0..1	aggr	This aggregation can be taken to identify a dependency for the enclosing SoftwareClusterDesign. Stereotypes: atpSplitable Tags: atp.Splitkey=dependsOn
diagnostic Contribution	DiagnosticContributionSet	*	ref	This reference identifies the corresponding collection of DiagnosticContributionSet. Stereotypes: atpSplitable Tags: atp.Splitkey=diagnosticContribution
dolpLogical Address	DolpLogicalAddress	0..1	ref	This reference identifies the Dolp logical address that shall be used to contact the diagnostic management in the SoftwareCluster derived from the enclosing Software ClusterDesign. Stereotypes: atpSplitable Tags: atp.Splitkey=dolpLogicalAddress
installation Behavior	SoftwareClusterInstallationBehaviorEnum	0..1	attr	This attribute controls the behavior of the SoftwareCluster in terms of installation.
intendedTarget Machine	MachineDesign	*	ref	This reference can be taken to identify the Machine Design for which the final SoftwareCluster shall be developed. Stereotypes: atpUriDef
required ARElement	ARElement	*	ref	This reference represents the collection of ARElements that are required for the completeness of the definition of the SoftwareCluster. Stereotypes: atpSplitable Tags: atp.Splitkey=requiredARElement
requiredDesign Element	UploadableDesign Element	*	ref	This reference points to uploadable design elements that have been identified as relevant in the context of the enclosing SoftwareClusterDesign. Stereotypes: atpSplitable Tags: atp.Splitkey=requiredDesignElement
root Composition	RootSwClusterDesign ComponentPrototype	0..1	aggr	This aggregation represents the design of the software inside the SwClusterDesign terms of the communication endpoints.
version	StrongRevisionLabel String	0..1	attr	This attribute can be used to describe a version information for the enclosing SoftwareClusterDesign.

Table A.448: SoftwareClusterDesign

Class	SoftwareClusterDiagnosticAddress (abstract)
Note	This meta-class represents the ability to define a diagnostic address in an abstract form. Sub-classes are supposed to clarify how the diagnostic address shall be defined according to the applicable addressing scheme (DoIP vs. CAN TP vs. ...). This Class is only used by the AUTOSAR Adaptive Platform.





Class	SoftwareClusterDiagnosticAddress (abstract)			
Base	ARObject			
Subclasses	SoftwareClusterSovdAddress, SoftwareClusterUdsDiagnosticAddress			
Aggregated by	DiagnosticCommonProps.diagnosticAddress			
Attribute	Type	Mult.	Kind	Note
address Semantics	SoftwareCluster DiagnosticAddress SemanticsEnum	0..1	attr	This attribute clarifies whether the address value shall be interpreted as a physical or a functional address.

Table A.449: SoftwareClusterDiagnosticAddress

Enumeration	SoftwareClusterDiagnosticAddressSemanticsEnum
Note	This meta-class defines a list of semantics for the interpretation of diagnostic addresses in the context of a SoftwareCluster. This Enumeration is only used by the AUTOSAR Adaptive Platform.
Aggregated by	SoftwareClusterDiagnosticAddress.addressSemantics
Literal	Description
functionalAddress	This address represents a functional address. Tags: atp.EnumerationLiteralIndex=1
physicalAddress	This address represents a physical address. Tags: atp.EnumerationLiteralIndex=0

Table A.450: SoftwareClusterDiagnosticAddressSemanticsEnum

Class	SoftwareClusterDiagnosticDeploymentProps			
Note	This meta-class acts as the owner of all deployment-related diagnostic properties of a SoftwareCluster. Tags: atp.recommendedPackage=SoftwareClusterDiagnosticProps This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnostic Extract	DiagnosticContribution Set	0..1	ref	This reference identifies the DiagnosticContributionSet that is applicable for the referencing SoftwareCluster.
max Conversations	PositiveInteger	0..1	attr	Maximum number of diagnostic Conversations supported by the Diagnostic Server Instance. This attribute has no relation to the definition of the maximum number of clients in DoIP context, configured by means of DoIPNetworkConfiguration.maxTesterConnections.
powerDown Time	PositiveInteger	0..1	attr	This attribute indicates the minimum time of the stand-by sequence the server will remain in the power-down sequence. The unit is seconds.
validation Configuration	DiagnosticService ValidationConfiguration	0..1	aggr	This aggregation represents the ability to define the order of manufacturer and supplier validations in diagnostic management.

Table A.451: SoftwareClusterDiagnosticDeploymentProps

Enumeration	SoftwareClusterInstallationBehaviorEnum
Note	This enumeration defines possible approaches for the installation behavior of a SoftwareCluster. This Enumeration is only used by the AUTOSAR Adaptive Platform.
Aggregated by	SoftwareClusterDesign.installationBehavior
Literal	Description
canBeRemoved	The enclosing SoftwareCluster can be removed from the target Machine or updated with a newer version. Tags: atp.EnumerationLiteralIndex=0
cannotBeRemoved	The enclosing SoftwareCluster cannot be removed from the target Machine. It can only be updated with a newer version. Tags: atp.EnumerationLiteralIndex=1

Table A.452: SoftwareClusterInstallationBehaviorEnum

Class	SoftwareClusterSovdAddress			
Note	This meta-class represents the ability to define a diagnostic address specifically for the SOVD case. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, SoftwareClusterDiagnosticAddress			
Aggregated by	DiagnosticCommonProps.diagnosticAddress			
Attribute	Type	Mult.	Kind	Note
component Qualifier	String	0..1	attr	This attribute is used to specify the component qualifier for the usage in an SOVD query. Stereotypes: atpIdentityContributor Tags: atp.Status=candidate

Table A.453: SoftwareClusterSovdAddress

Class	SoftwarePackage			
Note	This meta-class represents the ability to formalize the content of a software package. Tags: atp.recommendedPackage=SoftwarePackages This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
actionType	SoftwarePackageActionTypeEnum	0..1	attr	This attribute defines the action to be taken in the step of processing the enclosing SoftwarePackage.
activationAction	SoftwarePackageActivationActionEnum	0..1	attr	This attribute governs the action to be taken after the installation of the SoftwareCluster completed.
artifactLocator	ArtifactLocator	0..1	aggr	This attribute identifies the software package at configuration time, out of the context of an AUTOSAR model.
compressed Software PackageSize	PositiveInteger	0..1	attr	This size represents the size of the compressed Software Package.
deltaPackage Applicable Version	StrongRevisionLabel String	0..1	attr	This attribute identifies the version of the included SoftwareCluster for which the enclosing SoftwarePackage can be used as a delta update
estimated DurationOf Operation	TimeValue	0..1	attr	This attribute provides an estimation about how long the operation of the SoftwarePackage is going to take for its transfer, processing and activation when updated standalone (not within an update campaign)





Class	SoftwarePackage			
minimum SupportedUcm Version	RevisionLabelString	0..1	attr	This attribute identifies the minimum supported version of the UCM for this SoftwarePackage.
packagerId	PositiveInteger	0..1	attr	This attribute identifies Id of the organization that provides the packager generating the SoftwarePackage.
packager Signature	CryptoService Certificate	0..1	ref	This reference identifies the certificate that represents the packager's signature.
primary DownloadUri	UriDescription	0..1	aggr	This attribute represents the description of the primary download location. Stereotypes: atpSplitable Tags: atp.Splitkey=primaryDownloadUri.shortName
purposeOf Update	Documentation	0..1	ref	The referenced Documentation is supposed to provide a description of the purpose of the update.
secondary DownloadUri	UriDescription	*	aggr	This attribute represents the description of the secondary download locations. Stereotypes: atpSplitable Tags: atp.Splitkey=secondaryDownloadUri.shortName
softwareCluster	SoftwareCluster	0..1	ref	This reference identifies the SoftwareCluster that belongs to the SoftwarePackage. The nature of this relation is actually more like an aggregation than a reference. But the relation is still modelled as a reference because two ARElements cannot aggregate each other.
uncompressed SoftwareCluster Size	PositiveInteger	0..1	attr	This attribute gives an indication about the storage that has to be available on the target.

Table A.454: SoftwarePackage

Class	SoftwarePackageStep			
Note	This meta-class represents the configuration of an activation step in the context of software package activation. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	UcmStep.softwarePackageStep			
Attribute	Type	Mult.	Kind	Note
process	SoftwarePackage	0..1	ref	This reference identifies the SoftwarePackage to be processed in the enclosing SoftwarePackageStep.
transfer	SoftwarePackage Storing	*	aggr	This aggregation clarifies the storing of the Software Package.

Table A.455: SoftwarePackageStep

Class	SoftwarePackageStoring			
Note	This meta-class provides the ability to specify whether and where the referenced SoftwarePackage is stored. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	SoftwarePackageStep.transfer			
Attribute	Type	Mult.	Kind	Note
storing	SoftwarePackage StoringEnum	0..1	attr	This attribute clarifies whether and where the referenced SoftwarePackage is stored.
transfer	SoftwarePackage	*	ref	This reference identifies the SoftwarePackage(s) to be transferred in the enclosing SoftwarePackageStep.

Table A.456: SoftwarePackageStoring

Class	SomeipDataPrototypeTransformationProps			
Note	This meta-class represents the ability to define data transformation props specifically for a SOME/IP serialization for a given DataPrototype. Tags: atp.recommendedPackage=SomeipDataPrototypeTransformationPropss This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataPrototype	DataPrototypeInServiceInterfaceRef	*	aggr	Collection of DataPrototypes for which the settings in SomeipDataPrototypeTransformationProps are valid. For reuse reasons the SomeipDataPrototypeTransformationProps is able to aggregate several DataPrototypes.
networkRepresentation	SwDataDefProps	0..1	aggr	Optional specification of the actual network representation for the referenced primitive DataPrototype. If a network representation is provided then the baseType available in the SwDataDefProps shall be used as input for the serialization/deserialization. If the network Representation is not provided then the baseType of the AbstractImplementationDataType shall be used for the serialization/deserialization. Stereotypes: atpSplittable Tags: atp.Splitkey=networkRepresentation
someipTransformationProps	ApSomeipTransformationProps	0..1	ref	This reference represents the ability to define data transformation props specifically for a SOME/IP serialization.

Table A.457: SomeipDataPrototypeTransformationProps

Class	SomeipEventDeployment			
Note	SOME/IP configuration settings for an Event. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable , ServiceEventDeployment , ServiceInterfaceDeploymentElement			
Aggregated by	ServiceInterfaceDeployment.eventDeployment , SomeipFieldDeployment.notifier			
Attribute	Type	Mult.	Kind	Note
burstSize	PositiveInteger	0..1	attr	Specifies the number of segments that shall be transmitted in a burst ignoring separationTime. SeparationTime will then only be applied between bursts. If not configured, SeparationTime will be applied between all frames.
eventId	PositiveInteger	0..1	attr	Unique Identifier within a ServiceInterface that identifies the Event in SOME/IP. This Identifier is sent as part of the Message ID in SOME/IP messages.
eventReceptionDefaultValue	ValueSpecification	0..1	aggr	Value used to fill the Event data on the receiver side, if less data than expected is received. The value is expected to cover the entire expected event network payload. The value specification is supposed to take the order of serialized representation of the data on the network, as opposed to the order of elements in a data type description. Tags: atp.Status=obsolete





Class	SomeipEventDeployment			
maximumSegmentLength	PositiveInteger	0..1	attr	This attribute describes the length in bytes of the SOME/IP segment. This includes 8 bytes for the Request ID, Protocol Version, Interface Version, Message Type and Return Code and 4 additional SOME/IP TP bytes. If this attribute is set to a value and the data length is larger than maximumSegmentLength then the corresponding SOME/IP message will be segmented into smaller parts that are transmitted over the network.
segmentReceptionTimeoutTime	TimeValue	0..1	attr	Timer to monitor the successful reception of segments (in seconds) in SOME/IP.
separationTime	TimeValue	0..1	attr	Sets the duration of the minimum time in seconds SOME/IP shall wait between the transmissions of segments.
serializer	SerializationTechnologyEnum	0..1	attr	Defines which serialization technology shall be used.
transportProtocol	TransportLayerProtocolEnum	0..1	attr	This attribute defines over which Transport Layer Protocol this event is intended to be sent.

Table A.458: SomeipEventDeployment

Class	SomeipEventGroup			
Note	Grouping of events and notification events inside a ServiceInterface in order to allow subscriptions. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , Identifiable , <i>MultilanguageReferrable</i> , Referrable			
Aggregated by	SomeipServiceInterfaceDeployment.eventGroup			
Attribute	Type	Mult.	Kind	Note
event	SomeipEventDeployment	*	ref	Reference to an event that is part of the EventGroup.
eventGroupId	PositiveInteger	0..1	attr	Unique Identifier that identifies the EventGroup in SOME/IP. This Identifier is sent as Eventgroup ID in SOME/IP Service Discovery messages.

Table A.459: SomeipEventGroup

Class	SomeipFieldDeployment			
Note	SOME/IP configuration settings for a Field. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , Identifiable , <i>MultilanguageReferrable</i> , Referrable , ServiceFieldDeployment , ServiceInterfaceDeploymentElement			
Aggregated by	ServiceInterfaceDeployment.fieldDeployment			
Attribute	Type	Mult.	Kind	Note
get	SomeipMethodDeployment	0..1	aggr	This aggregation represents the setting of the get method.
notifier	SomeipEventDeployment	0..1	aggr	This aggregation represents the settings of the notifier.
set	SomeipMethodDeployment	0..1	aggr	This aggregation represents the settings of the set method

Table A.460: SomeipFieldDeployment

Class	SomeipMethodDeployment			
Note	SOME/IP configuration settings for a Method. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , ServiceInterfaceDeploymentElement , ServiceMethodDeployment			
Aggregated by	ServiceInterfaceDeployment.methodDeployment , SomeipFieldDeployment.get , SomeipFieldDeployment.set			
Attribute	Type	Mult.	Kind	Note
burstSize Request	PositiveInteger	0..1	attr	Specifies the number of segments for the Method Call that shall be transmitted in a burst ignoring separation Time. SeparationTime will then only be applied between bursts. If not configured, SeparationTime will be applied between all frames.
burstSize Response	PositiveInteger	0..1	attr	Specifies the number of segments for the Method Response that shall be transmitted in a burst ignoring separationTime. SeparationTime will then only be applied between bursts. If not configured, SeparationTime will be applied between all frames.
maximum SegmentLength Request	PositiveInteger	0..1	attr	This attribute describes the length in bytes of one SOME/IP segment into which the Method Call Message will be divided. This length field includes 8 bytes for the Request ID, Protocol Version, Interface Version, Message Type and Return Code and 4 additional SOME/IP TP bytes. If this attribute is set to a value and the data length is larger than maximumSegmentLengthRequest then the corresponding SOME/IP message will be segmented into smaller parts that are transmitted over the network.
maximum SegmentLength Response	PositiveInteger	0..1	attr	This attribute describes the length in bytes of one SOME/IP segment into which the Method Return Message will be divided. This length field includes 8 bytes for the Request ID, Protocol Version, Interface Version, Message Type and Return Code and 4 additional SOME/IP TP bytes. If this attribute is set to a value and the data length is larger than maximumSegmentLengthResponse then the corresponding SOME/IP message will be segmented into smaller parts that are transmitted over the network.
methodId	PositiveInteger	0..1	attr	Unique Identifier within a ServiceInterface that identifies the Method in SOME/IP. This Identifier is sent as part of the Message ID in SOME/IP messages.
segment Reception TimeoutTime Request	TimeValue	0..1	attr	Timer to monitor the successful reception of segments (in seconds) in SOME/IP for the Method Call.
segment Reception TimeoutTime Response	TimeValue	0..1	attr	Timer to monitor the successful reception of segments (in seconds) in SOME/IP for the Method Response.
separationTime Request	TimeValue	0..1	attr	Sets the duration of the minimum time in seconds SOME/IP shall wait between the transmissions of segments into which the Method Call Message will be divided.
separationTime Response	TimeValue	0..1	attr	Sets the duration of the minimum time in seconds SOME/IP shall wait between the transmissions of segments into which the Method Return Message will be divided.
transport Protocol	TransportLayerProtocol Enum	0..1	attr	This attribute defines over which Transport Layer Protocol this method is intended to be sent.

Table A.461: SomeipMethodDeployment

Class	SomeipProvidedEventGroup			
Note	The meta-class represents the ability to configure ServiceInstance related communication settings on the provided side for each EventGroup separately. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ProvidedSomeipServiceInstance.providedEventGroup			
Attribute	Type	Mult.	Kind	Note
eventGroup	SomeipEventGroup	0..1	ref	Reference to the SomeipEventGroup in the System Manifest for which the ServiceInstance related Event Group settings are valid.
eventMulticast UdpPort	PositiveInteger	0..1	attr	UdpPort configuration that is used for Event communication in the IP-Multicast case. During SOME/IP Service Discovery: Send in the SD-SubscribeEventGroupAck Message to client (answer to SD-SubscribeEventGroup). Event: This is the destination-port where the server sends the multicast event messages if the multicastThreshold is exceeded.
ipv4MulticastIp Address	Ip4AddressString	0..1	attr	Multicast IPv4 Address that is transmitted in the Event GroupSubscribeAck message.
ipv6MulticastIp Address	Ip6AddressString	0..1	attr	Multicast IPv6 Address that is transmitted in the Event GroupSubscribeAck message.
multicast Threshold	PositiveInteger	0..1	attr	Specifies the number of subscribed clients that trigger the server to change the transmission of events to multicast. Example: If configured to 0 only unicast will be used. If configured to 1 the first client will be already served by multicast. If configured to 2 the first client will be served with unicast and as soon as the 2nd client arrives both will be served by multicast. This does not influence the handling of initial events, which are served using unicast only.
sdServerEvent GroupTiming Config	SomeipSdServerEvent GroupTimingConfig	0..1	ref	Server Timing configuration settings that are EventGroup specific.

Table A.462: SomeipProvidedEventGroup

Class	SomeipRemoteMulticastConfig			
Note	This meta-class is used to statically configure the remote peer's multicast address. Tags: atp.Status=candidate atp.recommendedPackage=RemoteMulticastConfigs This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
eventGroup	SomeipEventGroup	*	ref	Reference to the SomeipEventGroups this Someip RemoteMulticastConfig applies to. Tags: atp.Status=candidate
ipv4Address	Ip4AddressString	0..1	attr	This attribute defines the multicast IPv4 address to allow a static service connection between Service Provider and Service Consumers. Tags: atp.Status=candidate





Class	SomeipRemoteMulticastConfig			
ipv6Address	Ip6AddressString	0..1	attr	This attribute defines the multicast IPv6 address to allow a static service connection between Service Provider and Service Consumers. Tags: atp.Status=candidate
udpPort	PositiveInteger	0..1	attr	This attribute defines the udpPort used for the multicast communication. Tags: atp.Status=candidate

Table A.463: SomeipRemoteMulticastConfig

Class	SomeipRemoteUnicastConfig			
Note	This meta-class is used to statically configure the remote peer's unicast address in case that a static service connection is used and only a single remote peer exists. Tags: atp.Status=candidate atp.recommendedPackage=SomeipRemoteUnicastConfigs This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
eventGroup	SomeipEventGroup	*	ref	Reference to the SomeipEventGroups this Someip RemoteUnicastConfig applies to. Tags: atp.Status=candidate
ipv4Address	Ip4AddressString	0..1	attr	This attribute defines the IPv4 address of the remote peer to allow a static service connection between Service Provider and Service Consumer. Tags: atp.Status=candidate
ipv6Address	Ip6AddressString	0..1	attr	This attribute defines the IPv6 address of the remote peer to allow a static service connection between Service Provider and Service Consumer. Tags: atp.Status=candidate
tcpPort	PositiveInteger	0..1	attr	This attribute defines the tcpPort of the remote peer to allow a static service connection between Service Provider and Service Consumer. Tags: atp.Status=candidate
udpPort	PositiveInteger	0..1	attr	This attribute defines the udpPort of the remote peer to allow a static service connection between Service Provider and Service Consumer. Tags: atp.Status=candidate

Table A.464: SomeipRemoteUnicastConfig

Class	SomeipRequiredEventGroup			
Note	The meta-class represents the ability to configure ServiceInstance related communication settings on the required side for each EventGroup separately. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Referrable			
Aggregated by	RequiredSomeipServiceInstance.requiredEventGroup			
Attribute	Type	Mult.	Kind	Note
eventGroup	SomeipEventGroup	0..1	ref	Reference to the SomeipEventGroup in the System Manifest for which the ServiceInstance related Event Group settings are valid.





Class	SomeipRequiredEventGroup			
sdClientEventGroupTimingConfig	SomeipSdClientEventGroupTimingConfig	0..1	ref	Client Timing configuration settings that are EventGroup specific.

Table A.465: SomeipRequiredEventGroup

Class	SomeipServiceDiscovery			
Note	This meta-class represents a specialization of the generic service discovery for the SOME/IP case. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, ServiceDiscoveryConfiguration			
Aggregated by	MachineDesign.serviceDiscoveryConfig			
Attribute	Type	Mult.	Kind	Note
multicastSdIpAddress	NetworkEndpoint	0..1	ref	This reference identifies the multicast IP address used for service discovery.
multicastSecureComProps	SecureComProps	0..1	ref	Reference to a communication security protocol and its configuration settings that will provide communication security for Service Discovery messages that are transmitted using multicast, e.g. FindService message.
someipServiceDiscoveryPort	PositiveInteger	0..1	attr	This attribute represents the port number reserved for service discovery.
unicastSecureComProps	SecureComProps	*	ref	Reference to a communication security protocol and its configuration settings that will provide communication security for Service Discovery messages that are transmitted using unicast, e.g. OfferService as answer to a FindService message.

Table A.466: SomeipServiceDiscovery

Class	SomeipServiceInstanceToMachineMapping			
Note	This meta-class allows to map SomeipServiceInstances to a CommunicationConnector of a Machine. In this step the network configuration (IP Address, Transport Protocol, Port Number) for the ServiceInstance is defined. Tags: atp.recommendedPackage=ServiceInstanceToMachineMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, ServiceInstanceToMachineMapping, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
remoteMulticastConfig	SomeipRemoteMulticastConfig	*	ref	This reference defines a remote multicast Address (IP Address, Port) that is used in a static configuration to setup the communication path between a service provider and service consumer. This reference shall ONLY be used if the remote address is determined from the configuration and not at runtime from the Service Discovery. Tags: atp.Status=candidate
remoteUnicastConfig	SomeipRemoteUnicastConfig	*	ref	In case that a static service connection is used and a single peer exists this element is used to statically configure the remote peer's address. Tags: atp.Status=candidate
tcpPort	ApApplicationEndpoint	0..1	ref	local TcpPort that will be used by the ServiceInstance for the communication.





Class	SomeipServiceInstanceToMachineMapping			
udpCollectionBufferSizeThreshold	PositiveInteger	0..1	attr	Specifies the amount of data in bytes that shall be buffered for data transmission over the udp connection specified by this SomeipServiceInstanceToMachineMapping. If this attribute is set to a value, then the data collection feature is enabled.
udpPort	ApApplicationEndpoint	0..1	ref	local UdpPort that will be used by the ServiceInstance for the communication.

Table A.467: SomeipServiceInstanceToMachineMapping

Class	SomeipServiceInterfaceDeployment			
Note	SOME/IP configuration settings for a ServiceInterface. Tags: atp.recommendedPackage=ServiceInterfaceDeployments This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement , ARObject , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , ServiceInterfaceDeployment , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
eventGroup	SomeipEventGroup	*	aggr	SOME/IP EventGroups that are defined within the SOME/IP ServiceClass.
serviceInterfaceId	PositiveInteger	0..1	attr	Unique Identifier that identifies the ServiceInterface in SOME/IP. This Identifier is sent as Service ID in SOME/IP Service Discovery messages.
serviceInterfaceVersion	SomeipServiceVersion	0..1	aggr	The SOME/IP major and minor Version of the Service.

Table A.468: SomeipServiceInterfaceDeployment

Class	SomeipServiceVersion			
Note	This meta-class represents the ability to describe a version of a SOME/IP Service.			
Base	ARObject			
Aggregated by	ConsumedServiceInstance.blocklistedVersion , RequiredSomeipServiceInstance.blocklistedVersion , SomeipServiceInterfaceDeployment.serviceInterfaceVersion			
Attribute	Type	Mult.	Kind	Note
majorVersion	PositiveInteger	0..1	attr	Major Version of the ServiceInterface. Tags: xml.sequenceOffset=10
minorVersion	PositiveInteger	0..1	attr	Minor Version of the ServiceInterface. Tags: xml.sequenceOffset=20

Table A.469: SomeipServiceVersion

Class	SovdGatewayEthernetCredentials (abstract)			
Note	This meta-class represents the ability to define Ethernet credentials for the purpose of connecting a client to an SOVD gateway. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Subclasses	SovdGatewayLocalEndpointTcpConfig			
Attribute	Type	Mult.	Kind	Note





Class	SovdGatewayEthernetCredentials (abstract)			
ipv4Address	Ip4AddressString	0..1	attr	This attribute represents the IPv4 address for the case that IPv4 is used for communication between the SOVD gateway and a client. Tags: atp.Status=candidate
ipv6Address	Ip6AddressString	0..1	attr	This attribute represents the IPv6 address for the case that IPv6 is used for communication between the SOVD gateway and a client. Tags: atp.Status=candidate
udpPort	PositiveInteger	0..1	attr	This attribute describes the port number of the port used for UDP communication. Tags: atp.Status=candidate

Table A.470: SovdGatewayEthernetCredentials

Class	SovdGatewayLocalEndpointTcpConfig			
Note	This meta-class provides the ability to define the TCP configuration of a local endpoint for external communication of an SOVD gateway. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, SovdGatewayEthernetCredentials			
Aggregated by	SovdGatewayInstantiation.unicastCredentials			
Attribute	Type	Mult.	Kind	Note
tcpPort	PositiveInteger	0..1	attr	This attribute describes the port number of the port used for TCP communication. Tags: atp.Status=candidate

Table A.471: SovdGatewayLocalEndpointTcpConfig

Class	SovdServerInstantiation			
Note	This meta-class represents the configuration of an SOVD server. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AdaptiveModuleInstantiation , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , NonOsModuleInstantiation , Referrable , SovdModuleInstantiation			
Aggregated by	AtpClassifier.atpFeature , Machine.moduleInstantiation			
Attribute	Type	Mult.	Kind	Note
component Qualifier	String	0..1	attr	This attributes described the component qualifier used to compose an SOVD query. Tags: atp.Status=candidate

Table A.472: SovdServerInstantiation

Class	StartupConfig			
Note	This meta-class represents a reusable startup configuration for processes.. Tags: atp.recommendedPackage=StartupConfigs This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDeploymentElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	StartupConfig			
environment Variable	TagWithOptionalValue	*	aggr	This aggregation represents the collection of environment variables that shall be added to the respective Process's environment prior to launch.
permissionTo CreateChild Process	Boolean	0..1	attr	This attribute defines if Process is permitted to create child Processes. When setting this parameter to true two things should be kept in mind: 1) safety and security implication of this configuration, 2) the fact that Process will assume management responsibilities for child Processes (i.e. it will be responsible for terminating Processes that it creates).
process Argument (ordered)	ProcessArgument	*	aggr	This aggregation represents the collection of command-line arguments applicable to the enclosing StartupConfig.
process ExecutionError	ApApplicationError	0..1	ref	this reference is used to identify the applicable execution error. Tags: atp.Status=draft
scheduling Policy	String	0..1	attr	This attribute represents the ability to define the scheduling policy for the initial thread of the application.
scheduling Priority	Integer	0..1	attr	This is the scheduling priority requested by the application itself.
termination Behavior	TerminationBehavior Enum	0..1	attr	This attribute defines the termination behavior of the Process.
timeout	EnterExitTimeout	0..1	aggr	This aggregation can be used to specify the timeouts for launching and terminating the process depending on the StartupConfig.

Table A.473: StartupConfig

Class	StateClientInterface			
Note	This PortInterface is used communicate changes of a function group state towards the Execution Management. Tags: atp.Status=draft atp.recommendedPackage=StateManagementPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, PortInterface, Referrable, State ManagementNotificationInterface, StateManagementPortInterface</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
functionGroup Type	ModeDeclarationGroup	0..1	ref	This reference identifies the ModeDeclarationGroup that shall be used in the API of the StateClientInterface. Tags: atp.Status=draft

Table A.474: StateClientInterface

Class	StateDependentFirewall			
Note	Firewall rules that are defined in a firewall state Tags: atp.Status=candidate atp.recommendedPackage=StateDependentFirewallRules			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, Packageable Element, Referrable, UploadableDesignElement, UploadablePackageElement</i>			
Aggregated by	ARPackage.element			





Class	StateDependentFirewall			
Attribute	Type	Mult.	Kind	Note
defaultAction	FirewallActionEnum	0..1	attr	This attribute defines a defaultAction in case that the VehicleMode is not yet set. Tags: atp.Status=candidate
firewallRule Props (ordered)	FirewallRuleProps	*	aggr	Collection of firewall rules that apply in the vehicle mode Tags: atp.Status=candidate
firewallState	ModeDeclaration	*	iref	Reference to firewall states in which the Firewall is active. If one of the referenced ModeDeclarations is the current firewall state then the firewall rule shall be considered as active. Tags: atp.Status=candidate InstanceRef implemented by: FirewallStateInFirwall StateSwitchInterfaceInstanceRef This Attribute is only used by the AUTOSAR Adaptive Platform.

Table A.475: StateDependentFirewall

Class	StateDependentStartupConfig			
Note	This meta-class defines the startup configuration for the process depending on a collection of machine states. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	Process.stateDependentStartupConfig			
Attribute	Type	Mult.	Kind	Note
execution Dependency	ExecutionDependency	*	aggr	This attribute defines that all processes that are referenced via the ExecutionDependency shall be launched and shall reach a certain ProcessState before the referencing process is started.
functionGroup State	ModeDeclaration	*	iref	This represent the applicable functionGroupMode. InstanceRef implemented by: FunctionGroupStateInFunctionGroupSetInstanceRef
resource Consumption	ResourceConsumption	0..1	aggr	This aggregation provides the ability to define resource consumption boundaries on a per-process-startup-config basis.
resourceGroup	ResourceGroup	0..1	ref	Reference to an applicable resource group.
startupConfig	StartupConfig	0..1	ref	Reference to a reusable startup configuration with startup parameters.

Table A.476: StateDependentStartupConfig

Class	StateManagementActionList			
Note	This meta-class represents the ability to define an action list that is associated with a state of a state machine. Tags: atp.Status=draft This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	StateManagementModuleInstantiation.actionItemList			
Attribute	Type	Mult.	Kind	Note
actionItem (ordered)	StateManagement ActionItem	*	aggr	This represents the collection of action items in the context of the action item list. Tags: atp.Status=draft





Class	StateManagementActionList			
actionList Processing FailedError	ApApplicationError	0..1	ref	This reference identifies the error code for the case that the enclosing action list fails to process successfully. This reference is only relevant for state management agents. Tags: atp.Status=draft
affectedState	ModeDeclaration	0..1	iref	This reference identifies the state for which the referencing action list applies. Tags: atp.Status=draft InstanceRef implemented by: ModeDeclarationInState ManagementStateNotificationInstanceRef
maxActionList Duration	TimeValue	0..1	attr	This attribute defines the maximum duration in which the enclosing StateManagementActionList shall finish execution Tags: atp.Status=draft
maxDuration ExceededError	ApApplicationError	0..1	ref	This reference identifies the ApApplicationError that shall be triggered if the configured maximum duration of the execution of the action item list is exceeded. Tags: atp.Status=draft

Table A.477: StateManagementActionList

Class	StateManagementCompareCondition (abstract)			
Note	StateManagementCompareConditions are atomic conditions. They are based on the idea of a comparison at runtime of some variable data with something constant. The type of the comparison (==, !=, <, <=, ...) is specified in StateManagementCompareCondition.compareType. Tags: atp.Status=draft This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, StateManagementCompareFormulaPart			
Subclasses	StateManagementErrorCompareRule, StateManagementTriggerCompareRule			
Aggregated by	StateManagementCompareFormula.part			
Attribute	Type	Mult.	Kind	Note
compareType	StateManagement CompareEnum	0..1	attr	This attributes represents the concrete type of the comparison. Tags: atp.Status=draft
compareValue	ValueSpecification	0..1	aggr	This aggregation represents the reference value against which the value obtained from request shall be compared to. Tags: atp.Status=draft

Table A.478: StateManagementCompareCondition

Class	StateManagementErrorInterface (abstract)			
Note	The usage of this meta-class for typing a PortPrototype indicates that the PortPrototype is used for the error provision in the context of state management on the AUTOSAR adaptive platform. Tags: atp.Status=draft This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable , State ManagementPortInterface, StateManagementRequestInterface			
Subclasses	StateManagementEmErrorInterface, StateManagementPhmErrorInterface			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.479: StateManagementErrorInterface

Class	StateManagementFunctionGroupSwitchNotificationInterface			
Note	<p>The usage of this meta-class for typing a PortPrototype indicates that the PortPrototype is used for sending out a notification of a function group state change in the context of state management on the AUTOSAR adaptive platform.</p> <p>Tags: atp.Status=draft atp.recommendedPackage=StateManagementPortInterfaces This Class is only used by the AUTOSAR Adaptive Platform.</p>			
Base	<i>ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, PortInterface, Referrable, StateManagementNotificationInterface, StateManagementPortInterface</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
modeGroup	ModeDeclarationGroup	0..1	ref	<p>This reference identifies the ModeDeclarationGroup that defines the individual states that that can be switched to.</p> <p>Tags: atp.Status=draft</p>

Table A.480: StateManagementFunctionGroupSwitchNotificationInterface

Class	StateManagementModuleInstantiation			
Note	<p>This meta-class represents the target-configuration-level configuration of the state management on the AUTOSAR adaptive platform.</p> <p>Tags: atp.Status=draft This Class is only used by the AUTOSAR Adaptive Platform.</p>			
Base	<i>ARObject, AdaptiveModuleInstantiation, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable, MultilanguageReferrable, NonOsModuleInstantiation, Referrable</i>			
Aggregated by	AtpClassifier.atpFeature, Machine.moduleInstantiation			
Attribute	Type	Mult.	Kind	Note
actionItemList	StateManagementActionList	*	aggr	<p>This represents the collection of action item lists defined in the context of the enclosing state management module.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=actionItemList.shortName atp.Status=draft</p>
functionGroupErrorMapping	FunctionGroupErrorMapping	*	aggr	<p>This aggregation contains the collection of FunctionGroupErrorMappings in the context of the enclosing StateManagementModuleInstantiation.</p> <p>Tags: atp.Status=draft</p>
maxActionListDuration	TimeValue	0..1	attr	<p>This attribute defines a global value for the maximum duration in which any enclosed StateManagementActionList shall finish execution. the value in this attribute will be superseded by the definition of attribute maxActionListDuration in the context of a specific StateManagementActionList</p> <p>Tags: atp.Status=draft</p>
notification	StateManagementStateNotification	*	aggr	<p>This aggregation represents the state switch notifications handled by the state manager.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=notification.shortName atp.Status=draft</p>
request	StateManagementStateRequest	*	aggr	<p>This aggregation represents the state requests handled by the state manager.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=request.shortName atp.Status=draft</p>

Table A.481: StateManagementModuleInstantiation

Class	StateManagementRequestError			
Note	This meta-class has the ability to configure the submission of an error to the state management. Tags: atp.Status=draft atp.recommendedPackage=StateManagementRequests This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , StateManagementStateRequest			
Aggregated by	StateManagementModuleInstantiation.request			
Attribute	Type	Mult.	Kind	Note
rule	StateManagementRequestRule	*	aggr	This aggregation represents the collection of rules applicable for the error request. Tags: atp.Status=draft

Table A.482: StateManagementRequestError

Class	StateManagementRequestRule			
Note	This meta-class represents a rule for deciding about a state change. Tags: atp.Status=draft This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	StateManagementRequestError.rule , StateManagementRequestTrigger.rule			
Attribute	Type	Mult.	Kind	Note
formula	StateManagementCompareFormula	0..1	aggr	This aggregation represents the definition of the formula for the StateManagementRequestRule Tags: atp.Status=draft
nextState	ModeDeclaration	0..1	iref	This reference identifies the state to be switched to if the condition is fulfilled. Tags: atp.Status=draft InstanceRef implemented by: ModeDeclarationInStateManagementStateNotificationInstanceRef

Table A.483: StateManagementRequestRule

Class	StateManagementRequestTrigger			
Note	This meta-class has the ability to configure a trigger request to the state management. Tags: atp.Status=draft This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , StateManagementStateRequest			
Aggregated by	StateManagementModuleInstantiation.request			
Attribute	Type	Mult.	Kind	Note
rule	StateManagementRequestRule	*	aggr	This aggregation represents the collection of rules applicable for the trigger request. Tags: atp.Status=draft

Table A.484: StateManagementRequestTrigger

Class	StateManagementSetFunctionGroupStateActionItem			
Note	This meta-class represents a state management action item to set a specific state in a specific function group. Tags: atp.Status=draft This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , StateManagementActionItem			
Aggregated by	StateManagementActionList.actionItem			





Class	StateManagementSetFunctionGroupStateActionItem			
Attribute	Type	Mult.	Kind	Note
rPortPrototype	RPortPrototype	0..1	iref	This reference identifies the PortPrototype over which the function group state switch shall be communicated. Tags: atp.Status=draft InstanceRef implemented by: RPortPrototypeInExecutableInstanceRef
setFunctionGroupState	ModeDeclaration	0..1	iref	This reference identifies the function group step that shall become active after the action step terminates. InstanceRef implemented by: FunctionGroupStateInFunctionGroupSetInstanceRef

Table A.485: StateManagementSetFunctionGroupStateActionItem

Class	StateManagementSleepActionItem			
Note	This action item can be used to universally implement afterrun. One specific use case for afterrun comes up in the context of network management. Tags: atp.Status=draft This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable, StateManagementActionItem			
Aggregated by	StateManagementActionList.actionItem			
Attribute	Type	Mult.	Kind	Note
sleepTime	TimeValue	0..1	attr	This attribute represents the amount of time that the execution of the StateManagementActionItemList is supposed to go to sleep. Tags: atp.Status=draft

Table A.486: StateManagementSleepActionItem

Class	StateManagementStateMachineActionItem			
Note	This meta-class represents a state management action item to start or stop a state machine. Tags: atp.Status=draft This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable, StateManagementActionItem			
Aggregated by	StateManagementActionList.actionItem			
Attribute	Type	Mult.	Kind	Note
overrideInitialState	ModeDeclaration	0..1	iref	The referenced ModeDeclaration shall be considered the initial state of the context ModeDeclarationGroup Prototype and the corresponding reference ModeDeclarationGroup.initialMode shall be ignored. Tags: atp.Status=draft InstanceRef implemented by: ModeDeclarationInStateManagementStateNotificationInstanceRef
startAgent	ModeDeclarationGroupPrototype	0..1	ref	This reference identifies the state machine that shall be started when the enclosing action list item is executed. Tags: atp.Status=draft
startAgentError	ApApplicationError	0..1	ref	This reference identifies the error that shall be raised if the starting of an agent failed. Tags: atp.Status=draft
stopAgent	ModeDeclarationGroupPrototype	0..1	ref	This reference identifies the state machine that shall be stopped when the enclosing action list item is executed. Tags: atp.Status=draft





Class	StateManagementStateMachineActionItem			
stopAgentError	ApApplicationError	0..1	ref	This reference identifies the error that shall be raised if the stopping of an agent failed. Tags: atp.Status=draft

Table A.487: StateManagementStateMachineActionItem

Class	StateManagementStateNotification			
Note	This meta-class represents the ability to formalize state notifications on the AUTOSAR adaptive platform. Tags: atp.Status=draft This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , <i>AtpClassifier</i> , Identifiable , <i>MultilanguageReferrable</i> , Referrable			
Aggregated by	StateManagementModuleInstantiation.notification			
Attribute	Type	Mult.	Kind	Note
notificationPort	PPortPrototype	0..1	iref	This instanceRef identifies the PPortPrototype over which the notification is to be conveyed. Tags: atp.Status=draft InstanceRef implemented by: PPortPrototypeIn ExecutableInstanceRef
stateMachine	ModeDeclarationGroup Prototype	0..1	aggr	This aggregation represents the existence of an actual state machine. Tags: atp.Status=draft

Table A.488: StateManagementStateNotification

Class	StateManagementStateRequest (abstract)			
Note	This abstract class serves as the base class for state requests on the AUTOSAR adaptive platform. Tags: atp.Status=draft This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , Identifiable , <i>MultilanguageReferrable</i> , Referrable			
Subclasses	StateManagementRequestError , StateManagementRequestTrigger			
Aggregated by	StateManagementModuleInstantiation.request			
Attribute	Type	Mult.	Kind	Note
stateRequest Port	RPortPrototype	0..1	iref	This represents the RPortPrototype in the application software that is issuing the request for state change. Tags: atp.Status=draft InstanceRef implemented by: RPortPrototypeIn ExecutableInstanceRef

Table A.489: StateManagementStateRequest

Class	StateManagementSuspendToRamActionItem (abstract)			
Note	This meta-class serves as an abstract base class for all suspend-to-RAM-related subclasses. Tags: atp.Status=draft This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , Identifiable , <i>MultilanguageReferrable</i> , Referrable , <i>StateManagementActionItem</i>			
Subclasses	StateManagementEnterSuspendToRamActionItem, StateManagementEnterSuspendToRamOsAction Item, StateManagementLeaveSuspendToRamActionItem			
Aggregated by	StateManagementActionList.actionItem			
Attribute	Type	Mult.	Kind	Note





Class	StateManagementSuspendToRamActionItem (abstract)			
maxActionItemDuration	TimeValue	0..1	attr	This attribute denotes the amount of time after which the execution of the action item is considered failed. Tags: atp.Status=draft

Table A.490: StateManagementSuspendToRamActionItem

Class	StateManagementTriggerCompareRule			
Note	This meta-class represents the configuration of a compare rule for the processing of a trigger request. Tags: atp.Status=draft This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, StateManagementCompareCondition , StateManagementCompareFormulaPart			
Aggregated by	StateManagementCompareFormula.part			
Attribute	Type	Mult.	Kind	Note
assumedCurrentState	ModeDeclaration	0..1	iref	This reference denotes the assumed current state for the given compare rule for trigger values. Tags: atp.Status=draft InstanceRef implemented by: ModeDeclarationInStateManagementStateNotificationInstanceRef

Table A.491: StateManagementTriggerCompareRule

Class	StateManagementTriggerInterface (abstract)			
Note	The usage of this meta-class for typing a PortPrototype indicates that the PortPrototype is used for the trigger provision in the context of state management on the AUTOSAR adaptive platform. Tags: atp.Status=draft This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , PortInterface , Referrable , StateManagementPortInterface , StateManagementRequestInterface			
Subclasses	StateManagementDiagTriggerInterface			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.492: StateManagementTriggerInterface

Class	StdCpplImplementationDataType			
Note	This meta-class represents the way to specify a data type definition that is taken as the basis for a C++ language binding to a C++ Standard Library feature. Tags: atp.recommendedPackage=CpplImplementationDataTypes This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AbstractImplementationDataType , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , AutosarDataType , CollectableElement , CpplImplementationDataType , CpplImplementationDataTypeContextTarget , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.493: StdCpplImplementationDataType

Class	SupervisionCheckpoint			
Note	This element contains an instance reference to a RPortPrototype representing a checkpoint for Platform Health Management. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	PlatformHealthManagementContribution.checkpoint			
Attribute	Type	Mult.	Kind	Note
checkpointId	PositiveInteger	0..1	attr	Defines the numeric value which is used to identify the reporting of this SupervisionCheckpoint to the Phm.
phmCheckpoint	PhmCheckpoint	0..1	iref	Instance reference to the PhmCheckpoint defined in the context of a PortInterface. Stereotypes: atpUriDef InstanceRef implemented by: PhmCheckpointInExecutableInstanceRef
process	Process	0..1	ref	Reference to the Process this checkpoint shall be monitored.

Table A.494: SupervisionCheckpoint

Class	SupervisionMode			
Note	This element defines a SupervisionMode. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	GlobalSupervision.supervisionMode			
Attribute	Type	Mult.	Kind	Note
active Supervision	PhmSupervision	*	ref	The reference defines which PhmSupervisions shall be active in this specific SupervisionMode.
modeCondition	SupervisionModeCondition	0..1	ref	Reference to SupervisionModeCondition (Condition under which the configuration made under this SupervisionMode are to be applied).

Table A.495: SupervisionMode

Class	SupervisionModeCondition			
Note	This element defines a SupervisionModeCondition in the context of platform health management contribution. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	PlatformHealthManagementContribution.supervisionModeCondition			
Attribute	Type	Mult.	Kind	Note
stateReference	PhmStateReference	*	aggr	Collection of stateReferences.

Table A.496: SupervisionModeCondition

Class	SuspendToRamHubInterface			
Note	This meta-class represents a hub-side PortInterface for the implementation of suspend-to-RAM functionality. Tags: atp.Status=candidate atp.recommendedPackage=SuspendToRamInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			





Class	SuspendToRamHubInterface			
Base	ARElement, ARObject, AbstractSuspendToRamInterface, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.497: SuspendToRamHubInterface

Class	SuspendToRamHubMapping			
Note	This mapping associates a suspend-to-RAM hub with the applicable module instantiation. Tags: atp.Status=candidate atp.recommendedPackage=SuspendToRamMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AbstractSuspendToRamMapping , CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.498: SuspendToRamHubMapping

Class	SuspendToRamModuleInstantiation			
Note	This meta-class represents the ability to define the target-configuration of a suspend-to-RAM module instantiation. Tags: atp.Status=candidate This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AdaptiveModuleInstantiation, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable , MultilanguageReferrable, NonOsModuleInstantiation , Referrable			
Aggregated by	AtpClassifier.atpFeature, Machine.moduleInstantiation			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.499: SuspendToRamModuleInstantiation

Class	SuspendToRamSatelliteInterface			
Note	This meta-class represents a satellite-side PortInterface for the implementation of suspend-to-RAM functionality. Tags: atp.Status=candidate atp.recommendedPackage=SuspendToRamInterfaces This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AbstractSuspendToRamInterface, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.500: SuspendToRamSatelliteInterface

Class	SuspendToRamSatelliteMapping			
Note	This mapping associates a suspend-to-RAM satellite with the applicable module instantiation. Tags: atp.Status=candidate atp.recommendedPackage=SuspendToRamMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, AbstractSuspendToRamMapping , CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.501: SuspendToRamSatelliteMapping

Class	SwBaseType			
Note	This meta-class represents a base type used within ECU software. Tags: atp.recommendedPackage=BaseTypes			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, BaseType , CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.502: SwBaseType

Class	SwComponentPrototype			
Note	Role of a software component within a composition.			
Base	ARObject, AtpFeature, AtpPrototype, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	AtpClassifier.atpFeature, CompositionSwComponentType.component			
Attribute	Type	Mult.	Kind	Note
type	SwComponentType	0..1	tref	Type of the instance. Stereotypes: isOfType

Table A.503: SwComponentPrototype

Class	SwComponentType (abstract)			
Note	Base class for AUTOSAR software components.			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable			
Subclasses	AdaptiveApplicationSwComponentType , AtomicSwComponentType , CompositionSwComponentType , ParameterSwComponentType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	SwComponentType (abstract)			
port	PortPrototype	*	aggr	The PortPrototypes through which this SwComponentType can communicate. The aggregation of PortPrototype is subject to variability with the purpose to support the conditional existence of PortPrototypes . Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=port.shortName, port.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
portGroup	PortGroup	*	aggr	A port group being part of this component. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=portGroup.shortName, portGroup.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
swComponentDocumentation	SwComponentDocumentation	0..1	aggr	This adds a documentation to the SwComponentType. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=swComponentDocumentation, swComponentDocumentation.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=-10

Table A.504: SwComponentType

Class	SwConnector (abstract)			
Note	The base class for connectors between ports. Connectors have to be identifiable to allow references from the system constraint template.			
Base	ARObject, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable , MultilanguageReferrable, Referrable			
Subclasses	AssemblySwConnector, DelegationSwConnector, PassThroughSwConnector			
Aggregated by	AtpClassifier.atpFeature, CompositionSwComponentType.connector			
Attribute	Type	Mult.	Kind	Note
mapping	PortInterfaceMapping	0..1	ref	Reference to a PortInterfaceMapping specifying the mapping of unequal named PortInterface elements of the two different PortInterfaces typing the two PortPrototypes which are referenced by the SwConnector.

Table A.505: SwConnector

Class	«atpVariation» SwDataDefProps			
Note	<p>This class is a collection of properties relevant for data objects under various aspects. One could consider this class as a "pattern of inheritance by aggregation". The properties can be applied to all objects of all classes in which SwDataDefProps is aggregated.</p> <p>Note that not all of the attributes or associated elements are useful all of the time. Hence, the process definition (e.g. expressed with an OCL or a Document Control Instance MSR-DCI) has the task of implementing limitations.</p> <p>SwDataDefProps covers various aspects:</p> <ul style="list-style-type: none"> • Structure of the data element for calibration use cases: is it a single value, a curve, or a map, but also the recordLayouts which specify how such elements are mapped/converted to the DataTypes in the programming language (or in AUTOSAR). This is mainly expressed by properties like swRecordLayout and swCalprmAxisSet • Implementation aspects, mainly expressed by swImplPolicy, swVariableAccessImplPolicy, swAddr Method, swPointerTargetProps, baseType, implementationDataType and additionalNativeTypeQualifier • Access policy for the MCD system, mainly expressed by swCalibrationAccess • Semantics of the data element, mainly expressed by compuMethod and/or unit, dataConstr, invalid Value • Code generation policy provided by swRecordLayout <p>Tags: vh.latestBindingTime=codeGenerationTime</p>			
Base	ARObject			
Aggregated by	AutosarDataType.swDataDefProps , CompositeNetworkRepresentation.networkRepresentation, Cpp ImplementationDataTypeElement.swDataDefProps , DataPrototype.swDataDefProps , DataPrototype TransformationProps.networkRepresentationProps, DiagnosticDataElement.swDataDefProps , Diagnostic EnvDataElementCondition.swDataDefProps , DiagnosticExtendedDataRecordElement.swDataDefProps , DiagnosticSovdPrimitiveContentElement.swDataDefProps , DltArgumentProps.networkRepresentation, FlatInstanceDescriptor.swDataDefProps, ImplementationDataTypeElement.swDataDefProps, InstantiationDataDefProps.swDataDefProps, ISignal.networkRepresentationProps , McDataInstance. resultingProperties, ParameterAccess.swDataDefProps, PerInstanceMemory.swDataDefProps, Receiver ComSpec.networkRepresentation , SecurityEventContextDataElement.networkRepresentation, Sender ComSpec.networkRepresentation , SomeipDataPrototypeTransformationProps.networkRepresentation , SwPointerTargetProps.swDataDefProps , SwServiceArg.swDataDefProps, SwSystemconst.swDataDef Props, SystemSignal.physicalProps			
Attribute	Type	Mult.	Kind	Note
additionalNative TypeQualifier	NativeDeclarationString	0..1	attr	<p>This attribute is used to declare native qualifiers of the programming language which can neither be deduced from the baseType (e.g. because the data object describes a pointer) nor from other more abstract attributes. Examples are qualifiers like "volatile", "strict" or "enum" of the C-language. All such declarations have to be put into one string.</p> <p>Tags: xml.sequenceOffset=235</p>
annotation	Annotation	*	aggr	<p>This aggregation allows to add annotations (yellow pads ...) related to the current data object.</p> <p>Tags: xml.roleElement=true xml.roleWrapperElement=true xml.sequenceOffset=20 xml.typeElement=false xml.typeWrapperElement=false </p>
baseType	SwBaseType	0..1	ref	<p>Base type associated with the containing data object.</p> <p>Tags: xml.sequenceOffset=50</p>
compuMethod	CompuMethod	0..1	ref	<p>Computation method associated with the semantics of this data object.</p> <p>Tags: xml.sequenceOffset=180</p>
dataConstr	DataConstr	0..1	ref	<p>Data constraint for this data object.</p> <p>Tags: xml.sequenceOffset=190</p>
displayFormat	DisplayFormatString	0..1	attr	<p>This property describes how a number is to be rendered e.g. in documents or in a measurement and calibration system.</p> <p>Tags: xml.sequenceOffset=210</p>





Class	«atpVariation» SwDataDefProps			
display Presentation	DisplayPresentation Enum	0..1	attr	This attribute controls the presentation of the related data for measurement and calibration tools.
implementation DataType	AbstractImplementation DataType	0..1	ref	<p>This association denotes the ImplementationDataType of a data declaration via its aggregated SwDataDefProps. It is used whenever a data declaration is not directly referring to a base type. Especially</p> <ul style="list-style-type: none"> • redefinition of an ImplementationDataType via a "typedef" to another ImplementationDatatype • the target type of a pointer (see SwPointerTarget Props), if it does not refer to a base type directly • the data type of an array or record element within an ImplementationDataType, if it does not refer to a base type directly • the data type of an SwServiceArg, if it does not refer to a base type directly <p>Tags: xml.sequenceOffset=215</p>
invalidValue	ValueSpecification	0..1	aggr	<p>Optional value to express invalidity of the actual data element.</p> <p>Tags: xml.sequenceOffset=255</p>
stepSize	Float	0..1	attr	This attribute can be used to define a value which is added to or subtracted from the value of a DataPrototype when using up/down keys while calibrating.
swAddrMethod	SwAddrMethod	0..1	ref	<p>Addressing method related to this data object. Via an association to the same SwAddrMethod it can be specified that several DataPrototypes shall be located in the same memory without already specifying the memory section itself.</p> <p>Tags: xml.sequenceOffset=30</p>
swAlignment	AlignmentType	0..1	attr	<p>The attribute describes the intended typical alignment of the DataPrototype. If the attribute is not defined the alignment is determined by the swBaseType size and the memoryAllocationKeywordPolicy of the referenced Sw AddrMethod.</p> <p>Tags: xml.sequenceOffset=33</p>
swBit Representation	SwBitRepresentation	0..1	aggr	<p>Description of the binary representation in case of a bit variable.</p> <p>Tags: xml.sequenceOffset=60</p>
swCalibration Access	SwCalibrationAccess Enum	0..1	attr	<p>Specifies the read or write access by MCD tools for this data object.</p> <p>Tags: xml.sequenceOffset=70</p>
swCalprmAxis Set	SwCalprmAxisSet	0..1	aggr	<p>This specifies the properties of the axes in case of a curve or map etc. This is mainly applicable to calibration parameters.</p> <p>Tags: xml.sequenceOffset=90</p>
swComparison Variable	SwVariableRefProxy	*	aggr	<p>Variables used for comparison in an MCD process.</p> <p>Tags: xml.sequenceOffset=170 xml.typeElement=false</p>
swData Dependency	SwDataDependency	0..1	aggr	<p>Describes how the value of the data object has to be calculated from the value of another data object (by the MCD system).</p> <p>Tags: xml.sequenceOffset=200</p>





Class	«atpVariation» SwDataDefProps			
swHostVariable	SwVariableRefProxy	0..1	aggr	Contains a reference to a variable which serves as a host-variable for a bit variable. Only applicable to bit objects. Tags: xml.sequenceOffset=220 xml.typeElement=false
swImplPolicy	SwImplPolicyEnum	0..1	attr	Implementation policy for this data object. Tags: xml.sequenceOffset=230
swIntendedResolution	Numerical	0..1	attr	The purpose of this element is to describe the requested quantization of data objects early on in the design process. The resolution ultimately occurs via the conversion formula present (compuMethod), which specifies the transition from the physical world to the standardized world (and vice-versa) (here, "the slope per bit" is present implicitly in the conversion formula). In the case of a development phase without a fixed conversion formula, a pre-specification can occur through swIntendedResolution. The resolution is specified in the physical domain according to the property "unit". Tags: xml.sequenceOffset=240
swInterpolationMethod	Identifier	0..1	attr	This is a keyword identifying the mathematical method to be applied for interpolation. The keyword needs to be related to the interpolation routine which needs to be invoked. Tags: xml.sequenceOffset=250
swIsVirtual	Boolean	0..1	attr	This element distinguishes virtual objects. Virtual objects do not appear in the memory, their derivation is much more dependent on other objects and hence they shall have a swDataDependency . Tags: xml.sequenceOffset=260
swPointerTargetProps	SwPointerTargetProps	0..1	aggr	Specifies that the containing data object is a pointer to another data object. Tags: xml.sequenceOffset=280
swRecordLayout	SwRecordLayout	0..1	ref	Record layout for this data object. Tags: xml.sequenceOffset=290
swRefreshTiming	MultidimensionalTime	0..1	aggr	This element specifies the frequency in which the object involved shall be or is called or calculated. This timing can be collected from the task in which write access processes to the variable run. But this cannot be done by the MCD system. So this attribute can be used in an early phase to express the desired refresh timing and later on to specify the real refresh timing. Tags: xml.sequenceOffset=300
swTextProps	SwTextProps	0..1	aggr	the specific properties if the data object is a text object. Tags: xml.sequenceOffset=120
swValueBlockSize	Numerical	0..1	attr	This represents the size of a Value Block Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.sequenceOffset=80





Class	«atpVariation» SwDataDefProps			
swValueBlockSizeMult (ordered)	Numerical	*	attr	This attribute is used to specify the dimensions of a value block (VAL_BLK) for the case that that value block has more than one dimension. The dimensions given in this attribute are ordered such that the first entry represents the first dimension, the second entry represents the second dimension, and so on. For one-dimensional value blocks the attribute swValueBlockSize shall be used and this attribute shall not exist. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
unit	Unit	0..1	ref	Physical unit associated with the semantics of this data object. This attribute applies if no compuMethod is specified. If both units (this as well as via compuMethod) are specified the units shall be compatible. Tags: xml.sequenceOffset=350
valueAxisDataType	ApplicationPrimitiveDataType	0..1	ref	The referenced ApplicationPrimitiveDataType represents the primitive data type of the value axis within a compound primitive (e.g. curve, map). It supersedes CompuMethod, Unit, and BaseType. Tags: xml.sequenceOffset=355

Table A.506: SwDataDefProps

Class	SwPointerTargetProps			
Note	This element defines, that the data object (which is specified by the aggregating element) contains a reference to another data object or to a function in the CPU code. This corresponds to a pointer in the C-language. The attributes of this element describe the category and the detailed properties of the target which is either a data description or a function signature.			
Base	ARObject			
Aggregated by	SwDataDefProps.swPointerTargetProps			
Attribute	Type	Mult.	Kind	Note
swDataDefProps	SwDataDefProps	0..1	aggr	The properties of the target data type. Tags: xml.sequenceOffset=30
targetCategory	Identifier	0..1	attr	This specifies the category of the target: <ul style="list-style-type: none"> In case of a data pointer, it shall specify the category of the referenced data. In case of a function pointer, it could be used to denote the category of the referenced BswModuleEntry. Tags: xml.sequenceOffset=5

Table A.507: SwPointerTargetProps

Class	SwTextProps			
Note	This meta-class expresses particular properties applicable to strings in variables or calibration parameters.			
Base	ARObject			
Aggregated by	SwDataDefProps.swTextProps			
Attribute	Type	Mult.	Kind	Note





Class	SwTextProps			
arraySize Semantics	ArraySizeSemanticsEnum	0..1	attr	This attribute controls the semantics of the arraysize for the array representing the string in an <code>ImplementationDataType</code> . It is there to support a safe conversion between <code>ApplicationDataType</code> and <code>ImplementationDataType</code> , even for variable length strings as required e.g. for Support of SAE J1939.
baseType	SwBaseType	0..1	ref	This is the base type of one character in the string. In particular this <code>baseType</code> denotes the intended encoding of the characters in the string on level of <code>ApplicationDataType</code> . Tags: xml.sequenceOffset=30
swFillCharacter	Integer	0..1	attr	Filler character for text parameter to pad up to the maximum length <code>swMaxTextSize</code> . The value will be interpreted according to the encoding specified in the associated base type of the data object, e.g. 0x30 (hex) represents the ASCII character zero as filler character and 0 (dec) represents an end of string as filler character. The usage of the fill character depends on the <code>arraySizeSemantics</code> . Tags: xml.sequenceOffset=40
swMaxTextSize	Integer	0..1	attr	Specifies the maximum text size in characters. Note the size in bytes depends on the encoding in the corresponding <code>baseType</code> . Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.sequenceOffset=20

Table A.508: SwTextProps

Class	SynchronizationTimingConstraint
Note	<p>This constraint is used to restrict the timing behavior of different, but correlated events or event chains, with regard to synchronization. Two scenarios are supported:</p> <ul style="list-style-type: none"> If (<code>synchronizationConstraintType==responseSynchronization</code>) <ul style="list-style-type: none"> TimingDescriptionEvents: An arbitrary number of correlated events which play the role of responses shall occur synchronously with respect to a predefined tolerance. TimingDescriptionEventChains: An arbitrary number of correlated event chains with a common stimulus, but different responses, where the responses shall occur synchronously with respect to a predefined tolerance. If (<code>synchronizationConstraintType==stimulusSynchronization</code>) <ul style="list-style-type: none"> TimingDescriptionEvents: An arbitrary number of correlated events which play the role of stimuli shall occur synchronously with respect to a predefined tolerance. TimingDescriptionEventChains: An arbitrary number of correlated event chains with a common response, but different stimuli, where the stimuli shall occur synchronously with respect to a predefined tolerance. <p>In case the constraint is imposed on events the following two scenarios are supported:</p> <ul style="list-style-type: none"> If (<code>eventOccurrenceKind==singleOccurrence</code>): any of the events shall occur only once in the given time interval. If (<code>eventOccurrenceKind==multipleOccurrences</code>): any of the events may occur more than once in the given time interval. In other words multiple occurrences of an event within the given time interval are permitted.
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TimingConstraint , Traceable
Aggregated by	TimingExtension.timingGuarantee , TimingExtension.timingRequirement





Class	SynchronizationTimingConstraint			
Attribute	Type	Mult.	Kind	Note
event OccurrenceKind	EventOccurrenceKind Enum	0..1	attr	Indicates whether the referenced events shall occur only once (single occurrence) or multiple times (multiple occurrences) in the given time interval.
scope	TimingDescriptionEvent Chain	*	ref	The event chains that are in the scope of the constraint. Mutually exclusive to scopeEvent , see ([constr_4522]).
scopeEvent	TimingDescriptionEvent	*	ref	The events that are in the scope of the constraint. Mutually exclusive to scope , see ([constr_4522]).
synchronization ConstraintType	SynchronizationType Enum	0..1	attr	Indicates whether the associated events of the SynchronizationTimingConstraint have a common stimulus or response.
tolerance	MultidimensionalTime	0..1	aggr	The maximum time interval, within which the synchronized events shall occur. The events may occur in any order within this time interval. The time interval starts at the point-in-time when one of the referenced events occurs.

Table A.509: SynchronizationTimingConstraint

Class	SynchronizedTimeBaseConsumer			
Note	This meta-class represents a Synchronized Time Base Consumer. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TimeBaseResource			
Aggregated by	TimeSyncModuleInstantiation.timeBase			
Attribute	Type	Mult.	Kind	Note
networkTime Consumer	GlobalTimeSlave	0..1	ref	This reference defines the GlobalTime Consumer which is synchronized with this Time Base.

Table A.510: SynchronizedTimeBaseConsumer

Class	SynchronizedTimeBaseProvider			
Note	This meta-class represents a Synchronized Time Base Provider. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TimeBaseResource			
Aggregated by	TimeSyncModuleInstantiation.timeBase			
Attribute	Type	Mult.	Kind	Note
networkTime Provider	GlobalTimeMaster	0..1	ref	This reference defines the GlobalTime Provider which is synchronized with this Time Base.
timeSync Correction	TimeSyncCorrection	0..1	aggr	This aggregation defines the attributes used for the correction of time synchronization. Tags: atp.Status=obsolete

Table A.511: SynchronizedTimeBaseProvider

Class	System
Note	The top level element of the System Description. Tags: atp.recommendedPackage=Systems
Base	ARElement, ARObject, AtpClassifier, AtpFeature, AtpStructureElement, CollectableElement, Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement





Class	System			
Aggregated by	ARPackage.element, <i>AtpClassifier.atpFeature</i>			
Attribute	Type	Mult.	Kind	Note
fibexElement	FibexElement	*	ref	Reference to ASAM FIBEX elements specifying Communication and Topology. All Fibex Elements used within a System Description shall be referenced from the System Element. atpVariation: In order to describe a product-line, all Fibex Elements can be optional. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=fibexElement.fibexElement, fibexElement.variationPoint.shortLabel vh.latestBindingTime=postBuild
mapping	SystemMapping	*	aggr	Aggregation of all mapping aspects relevant in the System Description. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=mapping.shortName, mapping.variationPoint.shortLabel vh.latestBindingTime=postBuild
pncVectorLength	PositiveInteger	0..1	attr	Length of the partial networking request release information vector (in bytes).
pncVectorOffset	PositiveInteger	0..1	attr	Absolute offset (with respect to the NM-PDU) of the partial networking request release information vector that is defined in bytes as an index starting with 0.
systemComSpecDefinition	SystemComSpecDefinitionSet	*	ref	Reference to the set of ComSpec definitions that are used for inter-ECU communication in the System.
systemVersion	RevisionLabelString	0..1	attr	Version number of the System Description.

Table A.512: System

Class	SystemMapping			
Note	The system mapping aggregates all mapping aspects that are relevant in the System Description.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	System.mapping			
Attribute	Type	Mult.	Kind	Note
pncMapping	PncMapping	*	aggr	Mappings between Virtual Function Clusters and Partial Network Clusters. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=pncMapping, pncMapping.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime

Table A.513: SystemMapping

Class	TDEventComplex			
Note	This is used to describe complex timing events. The context of a complex timing event either is described informally, e.g. using the documentation block, or is described formally by the associated TDEventOccurrenceExpression.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TimingDescription , TimingDescriptionEvent			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.514: TDEventComplex

Class	TDEventOccurrenceExpression			
Note	This is used to specify a filter on the occurrences of TimingDescriptionEvents by means of a TDEventOccurrenceExpressionFormula. Filter criteria can be variable and argument values, i.e. the timing event only occurs for specific values, as well as the temporal characteristics of the occurrences of arbitrary timing events.			
Base	ARObject			
Aggregated by	TimingDescriptionEvent.occurrenceExpression			
Attribute	Type	Mult.	Kind	Note
argument	AutosarOperationArgumentInstance	*	aggr	An occurrence expression can reference an arbitrary number of OperationArgumentPrototypes in its expression. This association aggregates instance references to OperationArgumentPrototypes which can be referenced in the expression.
formula	TDEventOccurrenceExpressionFormula	0..1	aggr	This is the expression formula which is used to describe the occurrence expression.
mode	TimingModelInstance	*	aggr	An occurrence expression can reference an arbitrary number of TimingModelInstances in its expression. This association aggregates instance references to Mode Declaration which can be referenced in the expression.
variable	AutosarVariableInstance	*	aggr	An occurrence expression can reference an arbitrary number of VariableDataPrototypes in its expression. This association aggregates instance references to Variable DataPrototypes which can be referenced in the expression.

Table A.515: TDEventOccurrenceExpression

Class	TDEventOperation			
Note	A TimingDescriptionEvent triggered by the sending/receiving of a ClientServerOperation in a ClientServerInterface on VFB level.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TDEventVfb , TDEventVfbPort , TimingDescription , TimingDescriptionEvent			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
operation	ClientServerOperation	0..1	ref	The referenced ClientServerOperation from a ClientServerInterface .
tdEventOperationType	TDEventOperationTypeEnum	0..1	attr	The specific type of this timing event.

Table A.516: TDEventOperation

Class	TDEventVariableDataPrototype			
Note	A TimingDescriptionEvent triggered by the sending/receiving of a VariableDataPrototype in a SenderReceiverInterface on VFB level.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TDEventVfb , TDEventVfbPort , TimingDescription , TimingDescriptionEvent			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
dataElement	VariableDataPrototype	0..1	ref	The referenced VariableDataPrototype from a SenderReceiverInterface .
tdEventVariableDataPrototypeType	TDEventVariableDataPrototypeTypeEnum	0..1	attr	The specific type of this timing event.

Table A.517: TDEventVariableDataPrototype

Class	TagWithOptionalValue			
Note	A tagged value is a combination of a tag (key) and a value that gives supplementary information that is attached to a model element. Please note that keys without a value are allowed.			
Base	<i>ARObject</i>			
Aggregated by	AbstractServiceInstance.capabilityRecord , Machine.environmentVariable , ProvidedSomeipServiceInstance.capabilityRecord , RequiredSomeipServiceInstance.capabilityRecord , StartupConfig.environmentVariable			
Attribute	Type	Mult.	Kind	Note
key	String	0..1	attr	Defines a key.
sequenceOffset	Integer	0..1	attr	The sequenceOffset attribute supports the use case where TagWithOptionalValue is aggregated as splittable. If multiple aggregations define the same value of attribute key then the order in which the value collection is merged might be significant. As an example consider the modeling of the \$PATH environment variable by means of a meta class TagWithOptionalValue. The sequenceOffset describes the relative position of each contribution in the concatenated value. The contributions are sorted in increasing integer order.
value	String	0..1	attr	Defines the corresponding value.

Table A.518: TagWithOptionalValue

Enumeration	TerminationBehaviorEnum
Note	This enumeration provides options for controlling of how a Process terminates. This Enumeration is only used by the AUTOSAR Adaptive Platform.
Aggregated by	StartupConfig.terminationBehavior
Literal	Description
processIsNotSelf Terminating	The Process terminates only on request from Execution Management. Tags: atp.EnumerationLiteralIndex=0
processIsSelf Terminating	The Process is allowed to terminate without request from Execution Management. Tags: atp.EnumerationLiteralIndex=1

Table A.519: TerminationBehaviorEnum

Class	TimeBaseProviderToPersistencyMapping			
Note	This meta-class represents the ability to define a mapping between a TimeBaseProvider and a PersistencyDeploymentElement for the purpose of storing and retrieving the time value. Tags: atp.recommendedPackage=FCInteractions This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , <i>FunctionalClusterInteractsWithFunctionalClusterMapping</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , Referrable , <i>UploadableDeploymentElement</i> , <i>UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
cyclicBackup Interval	TimeValue	0..1	attr	Time interval in seconds to store the time base value periodically to persistence.
persistency Deployment Element	PersistencyDeploymentElement	0..1	ref	This reference represents the PersistencyDeploymentElement where the time value shall be stored in and retrieved from.
timeBase Provider	SynchronizedTimeBaseProvider	0..1	ref	This reference represents the mapped TimeBase Provider.

Table A.520: TimeBaseProviderToPersistencyMapping

Class	TimeBaseResource (abstract)			
Note	This meta-class represents the attributes of one Time Base Resource for Time Synchronization. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Subclasses	SynchronizedTimeBaseConsumer , SynchronizedTimeBaseProvider			
Aggregated by	TimeSyncModuleInstantiation.timeBase			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.521: TimeBaseResource

Class	TimeSyncCorrection			
Note	This meta-class represents the attributes used for the correction of time synchronization. Tags: atp.Status=obsolete This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	SynchronizedTimeBaseProvider.timeSyncCorrection			
Attribute	Type	Mult.	Kind	Note
allowProviderRateCorrection	Boolean	0..1	attr	Defines whether the rate correction value of a Time Base can be set by means of the method setRateCorrection(). false: rate correction cannot be set by method setRateCorrection(). true: rate correction can be set by method setRateCorrection().
offsetCorrectionAdaptionInterval	TimeValue	0..1	attr	Defines the interval during which the adaptive rate correction cancels out the rate and time deviation. Unit: seconds.
offsetCorrectionJumpThreshold	TimeValue	0..1	attr	Threshold for the correction method. Deviations below this value will be corrected by a linear reduction over a defined timespan. Values equal and greater than this value will be corrected by immediately setting the correct time and rate in form of a jump. Unit: seconds.
providerRateDeviationMax	PositiveInteger	0..1	attr	This attribute describes the maximum allowed absolute value of the rate deviation value [unit: ppm].
rateCorrectionsPerMeasurementDuration	PositiveInteger	0..1	attr	Number of simultaneous rate measurements to determine the current rate deviation.
rateDeviationMeasurementDuration	TimeValue	0..1	attr	Time span used to calculate the rate deviation. Unit: seconds.

Table A.522: TimeSyncCorrection

Class	TimingDescriptionEvent (abstract)			
Note	A timing event is the abstract representation of a specific system behavior -- that can be observed at runtime -- in the AUTOSAR specification. Timing events are used to define the scope for timing constraints. Depending on the specific scope, the view on the system, and the level of abstraction different types of events are defined. In order to avoid confusion with existing event descriptions in the AUTOSAR templates the timing specific event types use the prefix TD.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TimingDescription			
Subclasses	TDEventCom, TDEventComplex , TDEventServiceInstance , TDEventVfb			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note





Class	TimingDescriptionEvent (abstract)			
clockReference	TimingClock	0..1	ref	Optional reference to a clock that holds the time base for an TD event. Tags: atp.Status=draft
occurrence Expression	TDEventOccurrence Expression	0..1	aggr	The occurrence expression for this event.

Table A.523: TimingDescriptionEvent

Class	TimingDescriptionEventChain			
Note	An event chain describes the causal order for a set of functionally dependent timing events. Each event chain has a well defined stimulus and response, which describe its start and end point. Furthermore, it can be hierarchically decomposed into an arbitrary number of sub-chains, so called <i>event chain segments</i> .			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable , TimingDescription			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
isPipelining Permitted	Boolean	0..1	attr	States whether the scheduled entities in an LET interval shall use pipelined execution or not i.e. "permitted pipelining property" If TRUE, then the scheduled entities must implement pipelining. If FALSE or undefined, no pipelining applies. Tags: atp.Status=draft
response	TimingDescriptionEvent	0..1	ref	The response event representing the point in time where the event chain is terminated. Tags: xml.sequenceOffset=20
segment	TimingDescriptionEvent Chain	*	ref	A composed event chain consists of an arbitrary number of sub-chains. Tags: xml.sequenceOffset=30
stimulus	TimingDescriptionEvent	0..1	ref	The stimulus event representing the point in time where the event chain is activated. Tags: xml.sequenceOffset=10

Table A.524: TimingDescriptionEventChain

Class	TlsCryptoCipherSuite			
Note	This meta-class represents a cipher suite for describing cryptographic operations in the context of establishing a connection of ApplicationEndpoints that is protected by TLS.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	TlsCryptoServiceMapping.tlsCipherSuite, TlsSecureComProps.tlsCipherSuite			
Attribute	Type	Mult.	Kind	Note
authentication	CryptoServicePrimitive	0..1	ref	This reference identifies the crypto service primitive for the generation and verification of MACs.
authentication Key	CryptoServiceKey	0..1	ref	This reference identifies the private key or pre-shared key used for authentication.
certificate	CryptoService Certificate	0..1	ref	This reference identifies the applicable local certificate.
cipherSuiteId	PositiveInteger	0..1	attr	Identification of the CipherSuite according to the IANA assignments list.
cipherSuite ShortLabel	String	0..1	attr	Name of the CipherSuite according to the IANA assignments list.





Class	TlsCryptoCipherSuite			
ellipticCurve	CryptoEllipticCurve Props	*	ref	This references point to the properties of elliptic curves.
encryption	CryptoServicePrimitive	0..1	ref	This reference identifies the crypto service primitive for the execution of encryption.
keyExchange	CryptoServicePrimitive	*	ref	This reference identifies the individual (i.e. per cipher suite) crypto service primitive for the execution of key exchange during the handshake phase.
keyExchange Authentication	CryptoServicePrimitive	*	ref	This reference identifies the crypto service primitives for the generation and verification of signatures during the key exchange algorithm.
priority	PositiveInteger	0..1	attr	This attribute identifies the priority of the cipher suite. Range: 1..65535. Lower values represent higher priorities.
props	TlsCryptoCipherSuite Props	0..1	aggr	The aggregated TlsCryptoCipherSuiteProps provide details for the TLS Cipher Suite.
pskIdentity	TlsPskIdentity	0..1	aggr	Pre-shared key identity shared during the handshake among the communication parties, to establish a TLS connection if the handshake is based on the existence of a pre-shared key.
remote Certificate	CryptoService Certificate	0..1	ref	This reference identifies the applicable remote certificate.
signature Scheme	CryptoSignature Scheme	*	ref	This reference points to the properties of a TLS Signature Scheme.
version	TlsVersionEnum	0..1	attr	This attribute supports the definition of the applicable version of TLS.

Table A.525: TlsCryptoCipherSuite

Class	TlsPskIdentity			
Note	This element is used to describe the pre-shared key shared during the handshake among the communication parties, to establish a TLS connection if the handshake is based on the existence of a pre-shared key.			
Base	ARObject			
Aggregated by	TlsCryptoCipherSuite.pskIdentity			
Attribute	Type	Mult.	Kind	Note
pskIdentity	String	0..1	attr	This attribute provides the key identification.
pskIdentityHint	String	0..1	attr	This attribute provides the identity hint for a pre-shared key.

Table A.526: TlsPskIdentity

Class	TlsSecureComProps			
Note	Configuration of the Transport Layer Security protocol (TLS). Tags: atp.recommendedPackage=SecureComProps This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, Packageable Element, Referrable , SecureComProps , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	TlsSecureComProps			
keyExchange	CryptoServicePrimitive	*	ref	This reference identifies the shared (i.e. applicable for each of the aggregated cipher suites) crypto service primitive for the execution of key exchange during the handshake phase.
tlsCipherSuite	TlsCryptoCipherSuite	*	aggr	Collection of supported cipher suites that are used to negotiate the security settings for a network connection defined by the ServiceInstanceToMachineMapping.

Table A.527: TlsSecureComProps

Class	TlvDataIdDefinition			
Note	This meta-class represents the ability to define the tlvDataId.			
Base	<i>ARObject</i>			
Aggregated by	TlvDataIdDefinitionSet.tlvDataIdDefinition			
Attribute	Type	Mult.	Kind	Note
id	PositiveInteger	0..1	attr	This attribute represents the definition of the value of the TlvDataId Stereotypes: atpIdentityContributor
tlvArgument	ArgumentDataPrototype	0..1	ref	This reference assigns a tlvDataId to a given argument of a ClientServerOperation.
tlvImplementationDataTypeElement	AbstractImplementationDataTypeElement	0..1	ref	This reference associates the definition of a TLV data id with a given AbstractImplementationDataTypeElement.
tlvRecordElement	ApplicationRecordElement	0..1	ref	This reference associates the definition of a TLV data id with a given ApplicationRecordElement.

Table A.528: TlvDataIdDefinition

Class	TlvDataIdDefinitionSet			
Note	This meta-class acts as a container of TlvDataIdDefinitions to be used in a given context Tags: atp.recommendedPackage=TlvDataDefinitionSets			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , Identifiable , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , Referrable , <i>UploadableDesignElement</i> , <i>UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
tlvDataIdDefinition	TlvDataIdDefinition	*	aggr	This aggregation represents the collection of TlvDataIdDefinitions aggregated by the TlvDataIdDefinitionSet Stereotypes: atpSplittable Tags: atp.Splitkey=tlvDataIdDefinition.id

Table A.529: TlvDataIdDefinitionSet

Class	TraceSwitchConfig			
Note	This class maps a DitMessage to a trace switch type. Tags: atp.recommendedPackage=TraceSwitchConfigs This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , Identifiable , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	TraceSwitchConfig			
executable	Executable	0..1	ref	Executable that defines the context of the trace switch.
namespace (ordered)	SymbolProps	*	aggr	This represents the SymbolProps used for the definition of a hierarchical namespace applicable for the generation of code artifacts out of the definition of a TraceSwitchConfig.
traceMessage	DltMessage	0..1	ref	Reference to the DltMessage that has to be routed in the trace switch.
traceSwitch	TraceSwitchEnum	0..1	attr	Defines how the message is routed, either to <ul style="list-style-type: none"> • ARTI trace, • Logger (default), • ARTI trace and logger • None

Table A.530: TraceSwitchConfig

Class	TransformationPropsToServiceInterfaceElementMapping			
Note	This meta-class represents the ability to associate a ServiceInterface element with TransformationProps. The referenced elements of the Service Interface will be serialized according to the settings defined in the TransformationProps. Tags: atp.recommendedPackage=TransformationPropsToServiceInterfaceElementMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement, ARObjct, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
event	VariableDataPrototype	*	ref	This represents the reference to one or several events of one ServiceInterface.
field	Field	*	ref	This represents the reference to one or several fields of one ServiceInterface.
methodCall	ClientServerOperation	*	ref	This represents the reference to one or several method calls of one ServiceInterface.
methodReturn	ClientServerOperation	*	ref	This represents the reference to one or several method return of one ServiceInterface.
tlvDataId Definition	TlvDataIdDefinitionSet	*	ref	This reference identifies the TlvDataIdDefinitions relevant for the enclosing TransformationPropsToServiceInterface Mapping.
transformation Props	TransformationProps	0..1	ref	This represents the reference to the applicable Serialization properties.
trigger	Trigger	*	ref	This represents the reference to one or several triggers of one ServiceInterface.

Table A.531: TransformationPropsToServiceInterfaceElementMapping

Class	TransmissionComSpecProps			
Note	This meta-class defines a set of transmission attributes which the application software is assumed to implement.			
Base	<i>ARObject</i>			
Aggregated by	SenderComSpec.transmissionProps			
Attribute	Type	Mult.	Kind	Note
dataUpdate Period	TimeValue	0..1	attr	This attribute defines the period in which the application is assumed to transmit the respective data.





Class	TransmissionComSpecProps			
minimumSendInterval	TimeValue	0..1	attr	This attribute defines the minimum interval between two consecutive transmissions of the respective data the application is assumed to ensure.
onChangeDataPrototype	DataPrototypeReference	*	aggr	This reference defines which DataPrototypes trigger the onChange transmission of the data. Stereotypes: atpSplitable Tags: atp.Splitkey=onChangeDataPrototype
transmissionMode	TransmissionModeDefinitionEnum	0..1	attr	The attribute defines the mode in which the application is assumed to transmit the respective data.

Table A.532: TransmissionComSpecProps

Enumeration	TransportLayerProtocolEnum
Note	This enumeration allows to choose a TCP/IP transport layer protocol. This Enumeration is only used by the AUTOSAR Adaptive Platform.
Aggregated by	SomeipEventDeployment.transportProtocol , SomeipMethodDeployment.transportProtocol
Literal	Description
tcp	Transmission control protocol Tags: atp.EnumerationLiteralIndex=1
udp	User datagram protocol Tags: atp.EnumerationLiteralIndex=0

Table A.533: TransportLayerProtocolEnum

Class	Trigger			
Note	The Trigger represents a special kind of an event (without data) at which occurrence the Service Consumer shall react in a particular manner.			
Base	ARObject, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	AtpClassifier.atpFeature, BswModuleDescription.releasedTrigger, BswModuleDescription.requiredTrigger, ServiceInterface.trigger , TriggerInterface.trigger			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.534: Trigger

Class	UcmDescription			
Note	This meta-class represents the ability to define an identifier for a given UCM. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	VehiclePackage.ucm			
Attribute	Type	Mult.	Kind	Note
identifier	String	0..1	attr	This attribute represents the unique identification of the UcmIdentifier.
ucmModuleInstantiation	UcmModuleInstantiation	0..1	ref	This reference identifies the applicable UcmModule Instantiation. Stereotypes: atpUriDef

Table A.535: UcmDescription

Class	UcmMasterModuleInstantiation			
Note	This meta-class represents the ability to define the target-configuration of a UCM Master instantiation. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AdaptiveModuleInstantiation, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable , MultilanguageReferrable, NonOsModuleInstantiation , Referrable , UcmModuleInstantiation			
Aggregated by	AtpClassifier.atpFeature, Machine.moduleInstantiation			
Attribute	Type	Mult.	Kind	Note
blockInconsistent	UcmRetryStrategy	0..1	aggr	This attribute defines the retry strategy of the UCM Master for the case that the block is inconsistent.
serviceBusy	UcmRetryStrategy	0..1	aggr	This attribute defines the retry strategy of the UCM Master for the case that the service is busy.
ucmNotAvailableOnTheNetwork	UcmRetryStrategy	0..1	aggr	This attribute defines the retry strategy of the UCM Master for the case that one (or more) UCM is not available on the network.
updateSessionRejected	UcmRetryStrategy	0..1	aggr	This attribute defines the retry strategy of the UcmMaster for the case that the update session is rejected.

Table A.536: UcmMasterModuleInstantiation

Class	UcmModuleInstantiation (abstract)			
Note	This meta-class represents the ability to define the target-configuration of a UCM instantiation. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AdaptiveModuleInstantiation, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable , MultilanguageReferrable, NonOsModuleInstantiation , Referrable			
Subclasses	UcmMasterModuleInstantiation , UcmSubordinateModuleInstantiation			
Aggregated by	AtpClassifier.atpFeature, Machine.moduleInstantiation			
Attribute	Type	Mult.	Kind	Note
identifier	String	0..1	attr	This represents the identification of a UCM.
maxBlockSize	PositiveInteger	0..1	attr	This attribute denotes the maximum block size (unit: bytes) used in the UCM implementation.
version	StrongRevisionLabelString	0..1	attr	This attribute defines the software version of the UCM on this platform. Note that the definition of the version is required if the ability of the SoftwarePackage to require a minimum version of the UCM is utilized.

Table A.537: UcmModuleInstantiation

Class	UcmRetryStrategy			
Note	This meta-class describes the configuration of the retry strategy for a sub-class of UcmModule Implementation. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	UcmMasterModuleInstantiation.blockInconsistent , UcmMasterModuleInstantiation.serviceBusy , UcmMasterModuleInstantiation.ucmNotAvailableOnTheNetwork , UcmMasterModuleInstantiation.updateSessionRejected , UcmSubordinateModuleInstantiation.prepareRollback , UcmSubordinateModuleInstantiation.prepareUpdate , UcmSubordinateModuleInstantiation.verifyUpdate			
Attribute	Type	Mult.	Kind	Note
maximumNumberOfRetries	PositiveInteger	0..1	attr	This attribute defines the maximum number of time the UCM module instantiation shall attempt a retry.
retryIntervalTime	TimeValue	0..1	attr	This attribute defines the time (in seconds) between two retry attempts.

Table A.538: UcmRetryStrategy

Class	UcmStep			
Note	This meta-class represents one rollout step in which software packages are processed on a specific Ucm. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	VehicleRolloutStep.ucmProcessing			
Attribute	Type	Mult.	Kind	Note
software PackageStep (ordered)	SoftwarePackageStep	*	aggr	This aggregation represents the sequence of activities to be carried out in the context of the respective UCM.
ucm	UcmDescription	0..1	ref	This reference identifies the UCM for which the rollout step applies.

Table A.539: UcmStep

Class	UcmSubordinateModuleInstantiation			
Note	This meta-class represents the ability to define the target-configuration of a UCM Subordinate instantiation. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, AdaptiveModuleInstantiation , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , NonOsModuleInstantiation , Referrable , UcmModuleInstantiation			
Aggregated by	AtpClassifier.atpFeature , Machine.moduleInstantiation			
Attribute	Type	Mult.	Kind	Note
maxAvailable Persistency StorageSpace	PositiveInteger	0..1	attr	This attribute names the maximum amount of space available for persistent data handled by the Persistency of installed packages. The UCM needs to figure out from traversing the minimum storage requirement from existing PersistencyDeployments whether specific packages can be installed from the perspective of available storage space. Note that the minimum storage requirement of PersistencyDeployment needs to include space for the handling of the storage, which shall be calculated by the tooling that creates the manifest information inside the package.
prepareRollback	UcmRetryStrategy	0..1	aggr	This attribute identifies the configuration of prepare rollback retries initiated by the Ucm Subordinate.
prepareUpdate	UcmRetryStrategy	0..1	aggr	This attribute identifies the configuration of prepare update retries initiated by the Ucm Subordinate.
verifyUpdate	UcmRetryStrategy	0..1	aggr	This attribute identifies the configuration of verify update retries initiated by the Ucm Subordinate.

Table A.540: UcmSubordinateModuleInstantiation

Class	UdpNmCluster			
Note	Udp specific NmCluster attributes			
Base	ARObject, Identifiable , MultilanguageReferrable , NmCluster , Referrable			
Aggregated by	NmConfig.nmCluster			
Attribute	Type	Mult.	Kind	Note
network Configuration	UdpNmNetwork Configuration	0..1	aggr	Configuration of a UDP port and UDP multicast IP address of the Nm communication on a VLAN. This Attribute is only used by the AUTOSAR Adaptive Platform.
nmCbvPosition	Integer	0..1	attr	Defines the position of the control bit vector within the Nm Pdu (Byte position). If this attribute is not configured, the Control Bit Vector is not used.





Class	UdpNmCluster			
nmImmediateNmCycleTime	TimeValue	0..1	attr	Defines the immediate NmPdu cycle time in seconds which is used for nmImmediateNmTransmissions NmPdu transmissions. This attribute is only valid if nmImmediateNmTransmissions is greater one.
nmImmediateNmTransmissions	PositiveInteger	0..1	attr	Defines the number of immediate NmPdus which shall be transmitted. If the value is zero no immediate NmPdus are transmitted. The cycle time of immediate NmPdus is defined by nmImmediateNmCycleTime.
nmMsgCycleTime	TimeValue	0..1	attr	Period of a NmPdu in seconds. It determines the periodic rate in the periodic transmission mode with bus load reduction and is the basis for transmit scheduling in the periodic transmission mode without bus load reduction.
nmNetworkTimeout	TimeValue	0..1	attr	Network Timeout for NmPdus in seconds. It denotes the time how long the UdpNm shall stay in the Network Mode before transition into Prepare Bus-Sleep Mode shall take place.
nmNidPosition	Integer	0..1	attr	Defines the byte position of the source node identifier within the NmPdu. If this attribute is not configured, the Node Identification is not used.
nmPnHandleMultipleNetworkRequests	Boolean	0..1	attr	Defines if Nm performs an additional transition from Network Mode to Repeat Message State (true) or not (false).
nmRepeatMessageTime	TimeValue	0..1	attr	Timeout for Repeat Message State in seconds. Defines the time how long the NM shall stay in the Repeat Message State.
nmUserDataLength	Integer	0..1	attr	Defines the length in bytes of the user data contained in the Nm message. User data excludes the PNC bit vector. This Attribute is only used by the AUTOSAR Adaptive Platform.
nmUserDataOffset	PositiveInteger	0..1	attr	Specifies the offset (in bytes) of the user data information in the NM message. User data excludes the PNC bit vector. This Attribute is only used by the AUTOSAR Adaptive Platform.
nmWaitBusSleepTime	TimeValue	0..1	attr	Timeout for bus calm down phase in seconds. It denotes the time how long the CanNm shall stay in the Prepare Bus-Sleep Mode before transition into Bus-Sleep Mode shall take place.
vlan	EthernetPhysicalChannel	0..1	ref	Reference to the vlan (represented by the Ethernet PhysicalChannel) this UdpNmCluster shall apply to.

Table A.541: UdpNmCluster

Class	UdpNmNetworkConfiguration			
Note	This meta-class defines the attributes for the configuration of a UDP port and UDP multicast IP address of the Nm communication on a VLAN. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject			
Aggregated by	UdpNmCluster.networkConfiguration			
Attribute	Type	Mult.	Kind	Note
ipv4MulticastIpAddress	Ip4AddressString	0..1	attr	Multicast IPv4 Address to which the message will be transmitted.
ipv6MulticastIpAddress	Ip6AddressString	0..1	attr	Multicast IPv6 Address to which the message will be transmitted





Class	UdpNmNetworkConfiguration			
priority	PositiveInteger	0..1	attr	This attribute defines the VLAN frame priority for messages on the Socket defined by the udpPort and the multicast IP address. Values from 0 (best effort) to 7 (highest) are allowed.
udpPort	PositiveInteger	0..1	attr	This attribute allows to configure a udp port number that is used for reception and transmission of UdpNm messages.

Table A.542: UdpNmNetworkConfiguration

Class	UploadableExclusivePackageElement (abstract)			
Note	This meta-class represents an abstract base class for an uploadable package element that is not supposed to be referenced from a different software cluster. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , UploadableDeploymentElement, UploadablePackageElement			
Subclasses	PersistencyDeployment , PersistencyPortPrototypeToDeploymentMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.543: UploadableExclusivePackageElement

Class	UriDescription			
Note	This meta-class can be used to define a URI. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	SoftwarePackage.primaryDownloadUri , SoftwarePackage.secondaryDownloadUri			
Attribute	Type	Mult.	Kind	Note
uri	String	0..1	attr	This attribute represents the actual URI. There are intentionally no format restrictions for how the URI shall be created.

Table A.544: UriDescription

Class	UserDefinedCommunicationConnector			
Note	This element allows the modeling of arbitrary Communication Connectors.			
Base	ARObject, CommunicationConnector , Identifiable , MultilanguageReferrable, Referrable			
Aggregated by	EcuInstance.connector, MachineDesign.communicationConnector			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.545: UserDefinedCommunicationConnector

Class	UserDefinedEventDeployment			
Note	UserDefined configuration settings for an Event. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable , MultilanguageReferrable, Referrable , ServiceEventDeployment , ServiceInterfaceDeploymentElement			





Class	UserDefinedEventDeployment			
Aggregated by	ServiceInterfaceDeployment.eventDeployment, UserDefinedFieldDeployment.notifier			
Attribute	Type	Mult.	Kind	Note
eventReception DefaultValue	ValueSpecification	0..1	aggr	Value used to fill the Event data on the receiver side, if less data than expected is received. The value is expected to cover the entire expected event network payload. The value specification is supposed to take the order of serialized representation of the data on the network, as opposed to the order of elements in a data type description. Tags: atp.Status=obsolete

Table A.546: UserDefinedEventDeployment

Class	UserDefinedFieldDeployment			
Note	UserDefined configuration settings for a Field. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable, ServiceFieldDeployment, ServiceInterfaceDeploymentElement			
Aggregated by	ServiceInterfaceDeployment.fieldDeployment			
Attribute	Type	Mult.	Kind	Note
get	UserDefinedMethodDeployment	0..1	aggr	This aggregation represents the settings of the get method
notifier	UserDefinedEventDeployment	0..1	aggr	This aggregation represents the settings of the notifier.
set	UserDefinedMethodDeployment	0..1	aggr	This aggregation represents the settings of the set method

Table A.547: UserDefinedFieldDeployment

Class	UserDefinedMethodDeployment			
Note	UserDefined configuration settings for a Method. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable, ServiceInterfaceDeploymentElement, ServiceMethodDeployment			
Aggregated by	ServiceInterfaceDeployment.methodDeployment, UserDefinedFieldDeployment.get, UserDefinedFieldDeployment.set			
Attribute	Type	Mult.	Kind	Note
—	—	—	—	—

Table A.548: UserDefinedMethodDeployment

Class	UserDefinedServiceInstanceToMachineMapping			
Note	This meta-class allows to map UserDefinedServiceInstances to a CommunicationConnector of a Machine. Tags: atp.recommendedPackage=ServiceInstanceToMachineMappings This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, ServiceInstanceToMachineMapping, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			





Class	UserDefinedServiceInstanceToMachineMapping			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.549: UserDefinedServiceInstanceToMachineMapping

Class	UserDefinedServiceInterfaceDeployment			
Note	UserDefined configuration settings for a ServiceInterface. Tags: atp.recommendedPackage=ServiceInterfaceDeployments This Class is only used by the AUTOSAR Adaptive Platform.			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable, PackageableElement, Referrable , ServiceInterfaceDeployment , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.550: UserDefinedServiceInterfaceDeployment

Class	ValueSpecification (abstract)			
Note	Base class for expressions leading to a value which can be used to initialize a data object.			
Base	ARObject			
Subclasses	AbstractRuleBasedValueSpecification, ApplicationValueSpecification , CompositeValueSpecification, ConstantReference , NotAvailableValueSpecification, NumericalValueSpecification, ReferenceValueSpecification , TextValueSpecification			
Aggregated by	ApplicationAssocMapElementValueSpecification.key , ApplicationAssocMapElementValueSpecification.value , ArrayValueSpecification.element, CalibrationParameterValue.applInitValue, CalibrationParameterValue.implInitValue, ConstantSpecification.valueSpec, CryptoServiceKey.developmentValue, DiagnosticEnvDataCondition.compareValue, DiagnosticEnvSovdDataCondition.compareValue , FieldSenderComSpec.initValue, ISignal.initValue, ISignal.receptionDefaultValue, ISignal.timeoutSubstitutionValue, NonqueuedReceiverComSpec.initValue, NonqueuedReceiverComSpec.timeoutSubstitutionValue, NonqueuedSenderComSpec.initValue, NvProvideComSpec.ramBlockInitValue, NvProvideComSpec.romBlockInitValue, NvRequireComSpec.initValue, ParameterDataPrototype.initValue, ParameterProvideComSpec.initValue, ParameterRequireComSpec.initValue, PersistencyDataRequiredComSpec.initValue , PersistencyKeyValuePair.initValue , PortDefinedArgumentValue.value, PortPrototypeBlueprintInitValue.value, RecordValueSpecification.field , SomeipEventDeployment.eventReceptionDefaultValue , StateManagementCompareCondition.compareValue , SwDataDefProps.invalidValue, UserDefinedEventDeployment.eventReceptionDefaultValue, VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note
shortLabel	Identifier	0..1	attr	This can be used to identify particular value specifications for human readers, for example elements of a record type.

Table A.551: ValueSpecification

Class	VariableDataPrototype			
Note	A VariableDataPrototype represents a formalized generic piece of information that is typically mutable by the application software layer. VariableDataPrototype is used in various contexts and the specific context gives the otherwise generic VariableDataPrototype a dedicated semantics.			
Base	ARObject, AtpFeature, AtpPrototype, AutosarDataPrototype , DataPrototype , Identifiable , MultilanguageReferrable, Referrable			





Class	VariableDataPrototype			
Aggregated by	ApplicationInterface.indication, <i>AtpClassifier.atpFeature</i> , BswInternalBehavior.arTypedPerInstanceMemory, BswModuleDescription.providedData, BswModuleDescription.requiredData, BulkNvDataDescriptor.bulkNvBlock, DiagnosticSovdAccessArgument.contentObject , <i>InternalBehavior.staticMemory</i> , NvBlockDescriptor.ramBlock, NvDataInterface.nvData, SenderReceiverInterface.dataElement, ServiceInterface.event , SwcInternalBehavior.arTypedPerInstanceMemory, SwcInternalBehavior.explicitInterRunnableVariable, SwcInternalBehavior.implicitInterRunnableVariable			
Attribute	Type	Mult.	Kind	Note
initValue	ValueSpecification	0..1	aggr	Specifies initial value(s) of the VariableDataPrototype

Table A.552: VariableDataPrototype

Class	VehicleDriverNotification			
Note	This meta-class provides the ability to configure a notification of the vehicle driver with respect to the update of vehicle software. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i>			
Aggregated by	VehiclePackage.driverNotification			
Attribute	Type	Mult.	Kind	Note
approvalRequired	Boolean	0..1	attr	This attribute controls whether approval is required for the driver notification.
notificationState	VehicleDriverNotificationEnum	0..1	attr	This attribute is used to configure the notification state.

Table A.553: VehicleDriverNotification

Class	VehiclePackage			
Note	This meta-class represents the ability to define a vehicle package for executing an update campaign. Tags: atp.recommendedPackage=VehiclePackages This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , Identifiable , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , Referrable , <i>UploadableDeploymentElement</i> , <i>UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
driverNotification	VehicleDriverNotification	*	aggr	This aggregation provides the ability to configure the necessary driver notifications.
estimatedDurationOfCampaign	TimeValue	0..1	attr	This attribute provides an estimation about how long the campaign based on the VehiclePackage is going to take.
maximumDurationOfCampaign	TimeValue	0..1	attr	Maximum time allowed for the campaign to be active until UCM Master automatically cancels the campaign.
minimumSupportedUcmMasterVersion	RevisionLabelString	0..1	attr	This attribute identifies the minimum supported version of the UCM Master for this VehiclePackage.
packagerSignature	CryptoServiceCertificate	0..1	ref	This reference identifies the certificate that represents the packager's signature.
repository	UriString	0..1	attr	This attribute identifies the repository where the Vehicle Package is stored.
rolloutQualification (ordered)	VehicleRolloutStep	*	aggr	This represents the rollout qualification.





Class	VehiclePackage			
ucm	UcmDescription	*	aggr	This aggregation represents the UcmDescriptions to be considered in the context of the VehiclePackage.
ucmMaster Fallback (ordered)	UcmDescription	*	ref	This reference lists the fallback order of Ucms that can take over the master role if the master goes down.
vehicle Description	Documentation	0..1	ref	This reference identifies the vehicle description.

Table A.554: VehiclePackage

Class	VehicleRolloutStep			
Note	This meta-class represents the ability to define a rollout-condition for a vehicle update campaign. This Class is only used by the AUTOSAR Adaptive Platform.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	VehiclePackage.rolloutQualification			
Attribute	Type	Mult.	Kind	Note
safetyCondition	String	*	attr	This attribute represents a list of textual safety conditions (e.g.: close the driver window) that need to be fulfilled before the rollout step can proceed and need to be maintained while the campaign's rolloutQualification is executed.
ucmProcessing	UcmStep	*	aggr	This aggregation collects the UcmProcessingSteps that make up the rollout step.
violatedSafety Condition Behavior	ViolatedSafetyCondition BehaviorEnum	0..1	attr	This attribute provides options for the configuration of the reaction to a violated safety condition.

Table A.555: VehicleRolloutStep

B Change history of AUTOSAR traceable items

Please note that the lists in this chapter also include traceable items that have been removed from the specification in a later version. These items do not appear as hyperlinks in the document.

B.1 Traceable item history of this document according to AUTOSAR Release R25-11

B.1.1 Added Constraints in R25-11

Number	Heading
[constr_10629]	DdsServiceInterfaceDeployment shall cover all applicable elements of the corresponding ServiceInterface
[constr_10630]	PPortPrototype that is typed by a DiagnosticDataIdentifierInterface shall be mapped to a DiagnosticDataIdentifier
[constr_10631]	PPortPrototype that is typed by a DiagnosticDataElementInterface shall be mapped to a DiagnosticDataElement
[constr_10633]	Existence of references StateManagementStateMachineActionItem.overrideInitialState and stopAgent
[constr_10634]	ClientServerOperation aggregated by meta-class DiagnosticDataIdentifierInterface or meta-class DiagnosticDataElementInterface
[constr_10635]	Allowed target type of the reference in the role ApmcRevisionLabelParamValue.definition
[constr_10636]	Allowed target type of the reference in the role ApmcStrongRevisionLabelParamValue.definition
[constr_10637]	Allowed target type of the reference in the role ApmcIPv4AddressParamValue.definition
[constr_10638]	Allowed target type of the reference in the role ApmcIPv6AddressParamValue.definition
[constr_10639]	Allowed target type of the reference in the role ApmcMacAddressParamValue.definition
[constr_10640]	Allowed target type of the reference in the role ApmcUriParamValue.definition
[constr_10641]	Existence of reference in the role StateManagementModuleInstantiation.maxActionListDuration
[constr_10643]	Existence of attributes ApmcDefinitionElement.upperMultiplicity and ApmcDefinitionElement.upperMultiplicityIsInfinite
[constr_10644]	Target of a ApmcReferenceValue where definition.isFuncClusterEndpointRef is set to <code>true</code>
[constr_10648]	Target of the reference in the role DiagnosticDoIpActivationLinePortMapping.networkConfigurationDesign





Number	Heading
[constr_10649]	Existence of reference in the role <code>DiagnosticDoIpActivationLinePortMapping.networkConfigurationDesign</code>
[constr_10650]	Target of the reference in the role <code>DiagnosticDoIpTriggerVehicleAnnouncementPortMapping.networkConfigurationDesign</code>
[constr_10651]	Existence of reference in the role <code>DiagnosticDoIpTriggerVehicleAnnouncementPortMapping.networkConfigurationDesign</code>
[constr_10652]	<code>SystemMappings</code> applicable for a <code>System</code> of category <code>MACHINE_DESIGN_EXTRACT</code>
[constr_10653]	Existence of attribute <code>UriDescription.uri</code>
[constr_10654]	Existence of <code>PersistencyFileRequiredComSpec</code>
[constr_10655]	Allowed range of values for attribute <code>ServiceInterfaceDeploymentElement.minimumSendInterval</code>
[constr_10657]	Multiplicity of reference in the role <code>ProcessDesignToMachineDesignMapping.machineDesign</code>
[constr_10658]	Multiplicity of the reference in the role <code>ProcessToMachineMapping.machine</code>
[constr_10659]	Consistency of references in the roles <code>ProcessDesignToMachineDesignMapping.machineDesign</code> and <code>shallRunOn</code> resp. <code>shallNotRunOn</code>
[constr_10660]	Usage of <code>shallRunOn</code> and <code>shallNotRunOn</code> references
[constr_10661]	Consistency of references <code>shallRunOn</code> and <code>shallNotRunOn</code>
[constr_10662]	Mutual exclusive existence of references <code>shallRunOn</code> and <code>shallNotRunOn</code>
[constr_10663]	Existence of attribute <code>DiagnosticCommonProps.authenticationTimeout</code>
[constr_10666]	Restriction for <code>StateManagementStateMachineActionItem</code>
[constr_10682]	Restriction of the multiplicity of <code>DiagnosticExtendedDataRecordInterface.provide.argument</code>
[constr_10683]	Restriction for the data type of <code>DiagnosticExtendedDataRecordInterface.provide.argument</code>
[constr_10684]	Restriction for the applicability of <code>DiagnosticExtendedDataRecordClientPortMapping</code>
[constr_10685]	Restriction for the reference to an <code>RPortPrototype</code> typed by a <code>DiagnosticExtendedDataRecordInterface</code>
[constr_10686]	Multiplicity of reference in the role <code>DiagnosticExtendedDataRecordClientPortMapping.recordElement</code>
[constr_10690]	Existence of <code>CryptoAlgorithmDescription.cryptoAlgorithmId</code>
[constr_10691]	Existence of <code>CryptoAlgorithmDescription.cryptoKeyType</code>
[constr_10692]	Existence of aggregation in the role <code>DiagnosticSovdOperationInterface.start</code>
[constr_10693]	Existence of reference in the role <code>DiagnosticSovdAccessArgument.contentObject</code>





Number	Heading
[constr_10694]	Restriction for <code>DiagnosticSovdAccessOperation</code> aggregated by a <code>DiagnosticSovdContentInterface</code>
[constr_10695]	Existence of <code>DiagnosticSovdAccessOperation.argument</code> if <code>DiagnosticSovdAccessOperation</code> that is aggregated in the role <code>DiagnosticSovdContentElementInterface.read</code>
[constr_10696]	Target of the reference <code>DiagnosticSovdContentPortMapping.pPortPrototypeInExecutable</code>
[constr_10697]	<code>DiagnosticSovdContentPortMapping</code> maps on the level of SOVD Data
[constr_10698]	<code>DiagnosticSovdContentPortMapping</code> maps on the level of SOVD Data Element
[constr_10699]	Existence of the Reference in the role <code>DiagnosticSovdContentPortMapping.pPortPrototypeInExecutable</code>
[constr_10700]	Existence of the Reference in the role <code>DiagnosticSovdContentPortMapping.content</code>
[constr_10701]	Existence of the Reference in the role <code>DiagnosticSovdContentPortMapping.process</code>
[constr_10702]	Existence of the Reference in the role <code>DiagnosticSovdOperationPortMapping.pPortPrototypeInExecutable</code>
[constr_10703]	Existence of the Reference in the role <code>DiagnosticSovdOperationPortMapping.sovdOperation</code>
[constr_10704]	Existence of the Reference in the role <code>DiagnosticSovdOperationPortMapping.process</code>
[constr_10705]	Restriction regarding references in the roles <code>DiagnosticSovdDataCategory.group</code> and <code>DiagnosticSovdData.sovdGroup</code>
[constr_10706]	Existence of reference in the role <code>DiagnosticSovdData.sovdDataCategory</code>
[constr_10707]	Relation of the values of attributes <code>minNumberOfElements</code> and <code>maxNumberOfElements</code>
[constr_10708]	<code>DiagnosticSovdContentElement</code> aggregated in the role <code>DiagnosticSovdArrayContentElement.element</code> shall not be declared <i>optional</i>
[constr_10711]	Existence of attribute <code>DiagnosticSovdArrayContentElement.maxNumberOfElements</code>
[constr_10712]	Allowed roles within <code>SwDataDefProps</code> in the context of <code>DiagnosticSovdPrimitiveContentElement</code>
[constr_10713]	Target of the reference <code>DiagnosticSovdOperationPortMapping.pPortPrototypeInExecutable</code>
[constr_10714]	<code>PPortPrototype</code> that is typed by a <code>DiagnosticSovdOperationInterface</code> as a mapping target
[constr_10715]	<code>DiagnosticSovdOperation</code> shall not refer to <code>DiagnosticSovdMethod</code>
[constr_10716]	Existence of <code>DiagnosticSovdOperation.start</code>
[constr_10717]	Existence of <code>DiagnosticSovdOperation.proximityProofRequired</code>
[constr_10718]	Existence of <code>DiagnosticEnvSovdDataCondition.compareValue</code>
[constr_10719]	Existence of <code>DiagnosticEnvSovdDataCondition.contentElement</code>





Number	Heading
[constr_10720]	Restriction for the value of <code>StateManagementSuspendToRamActionItem.maxActionItemDuration</code>
[constr_10721]	Target of <code>AbstractSuspendToRamMapping.pPortPrototypeInExecutable</code>
[constr_10722]	Restriction for <code>PPortPrototype</code> that is typed by a <code>SuspendToRamSatelliteInterface</code>
[constr_10723]	Existence of <code>SuspendToRamSatelliteMapping.moduleInstantiation</code>
[constr_10724]	Existence of <code>SuspendToRamSatelliteMapping.pPortPrototypeInExecutable</code>
[constr_10725]	Existence of <code>SuspendToRamSatelliteMapping.process</code>
[constr_10726]	Target of <code>AbstractSuspendToRamMapping.pPortPrototypeInExecutable</code>
[constr_10727]	Restriction for <code>PPortPrototype</code> that is typed by a <code>SuspendToRamHubInterface</code>
[constr_10728]	Restriction for <code>SuspendToRamHubMapping.moduleInstantiation</code>
[constr_10729]	Existence of <code>SuspendToRamHubMapping.moduleInstantiation</code>
[constr_10730]	Existence of <code>SuspendToRamHubMapping.pPortPrototypeInExecutable</code>
[constr_10731]	Existence of <code>SuspendToRamHubMapping.process</code>
[constr_10732]	Existence of attributes <code>DiagnosticExtendedDataRecord.trigger</code> and <code>update</code> on the <i>AUTOSAR adaptive platform</i>
[constr_10733]	Uniqueness of reference from <code>DiagnosticSovdConfigContentMapping</code> to <code>DiagnosticSovdConfigurationParameter</code>
[constr_10734]	Existence of the reference in the role <code>DiagnosticSovdConfigContentMapping.serviceInstance</code>
[constr_10735]	Existence of the reference in the role <code>DiagnosticSovdConfigContentMapping.content</code>
[constr_3795]	No Platform Health Management supervision for non-reporting <code>Executables</code>
[constr_3798]	Applicable attributes for an Ethernet node on the adaptive platform
[constr_3823]	Existence of <code>GlobalSupervision.expiredSupervisionTolerance</code>
[constr_9350]	All Provided Service Instances using the same UDP endpoint shall use the same DTLS SERVER configuration settings
[constr_9351]	All Provided Service Instances using the same TCP endpoint shall use the same TLS SERVER configuration settings
[constr_9352]	Mutual exclusive existence of <code>RemoteEndpointConfiguration.tcpPort</code> and <code>RemoteEndpointConfiguration.udpPort</code>
[constr_9353]	Mutual exclusive existence of <code>RemoteEndpointConfiguration.ipv4Address</code> and <code>RemoteEndpointConfiguration.ipv6Address</code>
[constr_9356]	Upper multiplicity of reference in the role <code>DoIpNetworkConfigurationDesign.networkConfiguration</code>
[constr_9370]	<code>ApSomeipTransformationProps</code> shall be defined at most once for a <code>ServiceInterface</code> element
[constr_9392]	Existence of reference <code>TraceSwitchConfig.traceMessage</code>
[constr_9393]	Existence of attribute <code>TraceSwitchConfig.traceSwitch</code>





Number	Heading
[constr_9394]	Existence of reference TraceSwitchConfig.executable

Table B.1: Added Constraints in R25-11

B.1.2 Changed Constraints in R25-11

Number	Heading
[constr_10029]	ServiceInterfaceDeployment (except DdsServiceInterfaceDeployment) shall cover all elements of the corresponding ServiceInterface
[constr_10037]	Existence of attribute TagWithOptionalValue.sequenceOffset in the context of attribute capabilityRecord owned by ProvidedSomeipServiceInstance , RequiredSomeipServiceInstance , or AbstractServiceInstance
[constr_10154]	Multiplicity of reference in the role ProcessDesignToMachineDesignMapping.processDesign
[constr_10172]	Multiplicity of attribute Processor.core
[constr_10173]	Multiplicity of attribute ProcessorCore.coreId
[constr_10386]	Existence of references StateManagementStateMachineActionItem.startAgent and stopAgent
[constr_10400]	Existence of SovdServerInstantiation.componentQualifier
[constr_10401]	Existence of SovdGatewayLocalEndpointTcpConfig.tcpPort
[constr_10402]	Existence of SovdGatewayEthernetCredentials.ipv4Address vs. SovdGatewayEthernetCredentials.ipv6Address
[constr_10403]	Existence of SovdGatewayEthernetCredentials.udpPort
[constr_10404]	Existence of SoftwareClusterSovdAddress.componentQualifier
[constr_10410]	Value of SoftwareClusterDesign.installationBehavior for a SoftwareClusterDesign of category <code>PLATFORM_CORE</code>
[constr_10442]	Restriction for the applicability of DiagnosticSovdProximityChallengePortMapping
[constr_10443]	Restriction for the applicability of DiagnosticSovdProximityChallengeInterface
[constr_10444]	Existence of DiagnosticSovdProximityChallengePortMapping
[constr_10445]	Existence of the reference in the role DiagnosticSovdProximityChallengePortMapping.pPortPrototypeInExecutable
[constr_10446]	Existence of the reference in the role DiagnosticSovdProximityChallengePortMapping.process
[constr_10447]	Restriction for the applicability of DiagnosticSovdAuthorizationPortMapping
[constr_10448]	Restriction for the applicability of DiagnosticSovdAuthorizationInterface
[constr_10449]	Existence of DiagnosticSovdAuthorizationPortMapping





Number	Heading
[constr_10450]	Existence of the reference in the role DiagnosticSovdAuthorizationPortMapping.pPortPrototypeInExecutable
[constr_10451]	Existence of the reference in the role DiagnosticSovdAuthorizationPortMapping.process
[constr_10452]	Restriction for the applicability of DiagnosticSovdBulkDataPortMapping
[constr_10453]	Restriction for the applicability of DiagnosticSovdBulkDataInterface
[constr_10454]	Uniqueness of reference from DiagnosticSovdBulkDataPortMapping to DiagnosticSovdBulkData
[constr_10455]	Existence of the reference in the role DiagnosticSovdBulkDataPortMapping.serviceInstance
[constr_10456]	Existence of the reference in the role DiagnosticSovdBulkDataPortMapping.pPortPrototypeInExecutable
[constr_10457]	Existence of the reference in the role DiagnosticSovdBulkDataPortMapping.process
[constr_10458]	Restriction for the applicability of DiagnosticSovdUpdatePortMapping
[constr_10459]	Restriction for the applicability of DiagnosticSovdUpdateInterface
[constr_10460]	Uniqueness of reference from DiagnosticSovdUpdatePortMapping to DiagnosticSovdUpdate
[constr_10461]	Existence of the reference in the role DiagnosticSovdUpdatePortMapping.serviceInstance
[constr_10462]	Existence of the reference in the role DiagnosticSovdUpdatePortMapping.pPortPrototypeInExecutable
[constr_10463]	Existence of the reference in the role DiagnosticSovdUpdatePortMapping.process
[constr_10464]	Restriction for the applicability of DiagnosticSovdServiceValidationPortMapping
[constr_10465]	Restriction for the applicability of DiagnosticSovdServiceValidationInterface
[constr_10466]	Existence of the reference in the role DiagnosticSovdServiceValidationPortMapping.pPortPrototypeInExecutable
[constr_10467]	Existence of the reference in the role DiagnosticSovdServiceValidationPortMapping.process
[constr_10468]	Restriction for the applicability of DiagnosticSovdConfigurationPortMapping
[constr_10469]	Restriction for the applicability of DiagnosticSovdConfigurationInterface
[constr_10470]	Uniqueness of reference from DiagnosticSovdConfigurationPortMapping to DiagnosticSovdConfiguration
[constr_10471]	Existence of the reference in the role DiagnosticSovdConfigurationPortMapping.serviceInstance
[constr_10472]	Existence of the reference in the role DiagnosticSovdConfigurationPortMapping.pPortPrototypeInExecutable





Number	Heading
[constr_10473]	Existence of the reference in the role <code>DiagnosticSovdConfigurationPortMapping.process</code>
[constr_10477]	Existence of <code>DiagnosticSovdLog</code>
[constr_10478]	Existence of <code>DiagnosticSovdUpdate</code>
[constr_10479]	Restriction on values of attribute <code>DiagnosticSovdMethodPrimitive.category</code> aggregated in the role <code>put</code> in the context of SOVD Update
[constr_10480]	Restriction on value of attribute <code>DiagnosticSovdMethodPrimitive.category</code> aggregated in the role <code>get</code> in the context of SOVD Update
[constr_10481]	Restriction on values of attribute <code>DiagnosticSovdMethodPrimitive.category</code> aggregated in the role <code>get</code> in the context of SOVD Log
[constr_10482]	Restriction on values of attribute <code>DiagnosticSovdMethodPrimitive.category</code> aggregated in the roles <code>put</code> and <code>delete</code> in the context of SOVD Log
[constr_10483]	Applicable values of <code>baseTypeEncoding</code> in the context of the definition of a <code>DiagnosticDataElement</code>
[constr_10490]	<code>DiagnosticDataElement</code> shall be directly or indirectly the target of a reference owned by a subclass of <code>DiagnosticMapping</code>
[constr_10567]	Existence of <code>DiagnosticSovdMethod.get</code> resp. <code>delete</code> in the context of <code>DiagnosticSovdFaultMemoryAccess</code>
[constr_10612]	Standardized values for attribute <code>CryptoKeySlotDesignDescription.cryptoObjectType</code>
[constr_1507]	<code>PortInterfaceToDataTypeMapping</code> is only applicable to <code>PortInterfaces</code> that contain modeled data types
[constr_1549]	Value of <code>ProcessorCore.coreId</code>
[constr_1693]	Relation of <code>Executable</code> , <code>ProcessDesign</code> , and <code>Process</code>
[constr_1697]	Restriction for <code>ClientServerOperation</code> aggregated by a <code>DiagnosticDataIdentifierInterface</code>
[constr_1785]	Restriction regarding the reference into another <code>SoftwareCluster</code>
[constr_3421]	Fibex elements applicable for a <code>System</code> of <code>category</code> MACHINE_DESIGN_EXTRACT
[constr_3650]	<code>headerId</code> required in case of Arbitrary Message Header
[constr_5239]	Predefined values for <code>CryptoKeySlotContentAllowedUsage.allowedKeyslotUsage</code>
[constr_5291]	Allowed usage of <code>LTMessageCollectionToPortPrototypeMapping.rPort</code>

Table B.2: Changed Constraints in R25-11

B.1.3 Deleted Constraints in R25-11

Number	Heading
[constr_10007]	Existence of <code>ProcessExecutionError.executionError</code>
[constr_10008]	Value of <code>ProcessExecutionError.executionError</code>
[constr_10195]	Multiplicity of attribute <code>DoIpNetworkConfiguration.vehicleIdentificationSyncStatus</code>
[constr_10211]	Multiplicity of the reference in the role <code>CryptoCertificateToCryptoKeySlotMapping.cryptoCertificate</code>
[constr_10474]	Uniqueness of reference from <code>DiagnosticSovdConfigurationDataIdentifierMapping</code> to <code>DiagnosticSovdConfigurationParameter</code>
[constr_10475]	Existence of the reference in the role <code>DiagnosticSovdConfigurationDataIdentifierMapping.serviceInstance</code>
[constr_10476]	Existence of the reference in the role <code>DiagnosticSovdConfigurationDataIdentifierMapping.dataIdentifier</code>
[constr_10488]	Existence of attribute <code>DiagnosticCommonProps.authenticationTimeout</code>
[constr_11000]	<code>SomeipEventDeployment.eventReceptionDefaultValue</code> or <code>UserDefinedEventDeployment.eventReceptionDefaultValue</code> shall not be specified in the physical domain
[constr_3639]	Existence of <code>SupervisionMode.expiredSupervisionTolerance</code>
[constr_5386]	Existence of <code>Executable.traceSwitchConfiguration</code>
[constr_5387]	Existence of reference <code>Executable.traceSwitchConfiguration.traceMessage</code>
[constr_5388]	Existence of attribute <code>Executable.traceSwitchConfiguration.traceSwitch</code>

Table B.3: Deleted Constraints in R25-11

B.2 Traceable item history of this document according to AUTOSAR Release R24-11

B.2.1 Added Constraints in R24-11

Number	Heading
[constr_10517]	Upper multiplicity of reference in the role <code>IdsPlatformInstantiation.idsTimeBase</code>
[constr_10518]	Mutually exclusive existence of <code>FunctionalClusterInteractsWithDiagnosticEventMapping.persistenceDeployment</code> vs. <code>functionalCluster</code>





Number	Heading
[constr_10519]	Existence of reference <code>FunctionalClusterInteractsWithDiagnosticEventMapping.diagnosticEvent</code>
[constr_10526]	<code>DiagnosticAuthenticationPortMapping</code> refers to a <code>PPortPrototype</code> that is typed by a <code>DiagnosticTransmitCertificateInterface</code>
[constr_10528]	Existence of <code>FirewallStateSwitchInterface.firewallStateMachine</code>
[constr_10530]	Each Ucm shall process at least one software package
[constr_10535]	Restriction for attribute <code>SenderComSpec.transmissionProps.onChangeDataPrototype</code>
[constr_10536]	Existence of <code>TransmissionComSpecProps.onChangeDataPrototype.dataPrototypeInServiceInterface.rootDataPrototype</code>
[constr_10537]	Existence of <code>TransmissionComSpecProps.onChangeDataPrototype.rootDataPrototype</code>
[constr_10540]	Arguments of a <code>ClientServerOperation</code> shall be fully covered by <code>SignalBasedFireAndForgetMethodToISignalTriggeringMappings</code>
[constr_10541]	Consistent assignment of <code>ISignalTriggerings</code> to an <code>ISignalGroup</code> for <code>SignalBasedFireAndForgetMethodToISignalTriggeringMapping</code>
[constr_10546]	<code>PortPrototype</code> typed by <code>DiagnosticGenericUdsInterface</code> shall only be referenced by <code>DiagnosticServiceGenericMapping</code>
[constr_10547]	Reference in the role <code>UcmStep.ucm</code> in the context of the enclosing <code>VehicleRolloutStep</code>
[constr_10566]	Allowed values of attribute <code>CppImplementationDataType.swDataDefProps.compuMethod.category</code>
[constr_10567]	Existence of <code>DiagnosticSovdMethod.get</code> resp. <code>delete</code> in the context of <code>DiagnosticSovdFaultMemoryAccess</code>
[constr_10568]	Type of <code>RPortPrototype</code> referenced in the role <code>IdsmReportingModeProviderMapping.rPortPrototypeInExecutable</code>
[constr_10569]	<code>RPortPrototype</code> typed by an <code>IdsmReportingModeProviderInterface</code>
[constr_10570]	Existence of <code>IdsmReportingModeProviderMapping.idsPlatformInstantiation</code>
[constr_10571]	Existence of <code>IdsmReportingModeProviderMapping.rPortPrototypeInExecutable</code>
[constr_10572]	Existence of <code>IdsmReportingModeProviderMapping.process</code>
[constr_10574]	Value of <code>ApApplicationErrorDomain.value</code> shall be unique in the context of a <code>ClientServerOperation</code>
[constr_10576]	Existence of attribute <code>PersistencyDataRequiredComSpec.accessMode</code>
[constr_10578]	Existence of the attribute <code>UcmMasterModuleInstantiation.ucmNotAvailableOnTheNetwork</code>
[constr_10579]	Existence of <code>definition</code>
[constr_10580]	Restriction regarding the value of <code>ApmcDefinitionElement.lowerMultiplicity</code> vs. <code>ApmcDefinitionElement.lowerMultiplicity</code>
[constr_10581]	Existence of reference in the role <code>ApmcFunctionalClusterValue.definition</code>
[constr_10582]	Existence of reference in the role <code>ApmcContainerValue.definition</code>





Number	Heading
[constr_10583]	Existence of reference in the role <code>ApmcContainerElementValue.definition</code>
[constr_10584]	Allowed <code>value</code> for a <code>ApmcNumericalParamValue</code> that implements an boolean-style parameter
[constr_10585]	Allowed <code>value</code> for a <code>ApmcTextualParamValue</code> that implements an enumeration-style parameter
[constr_10586]	Restriction for the applicability of <code>DiagnosticDoIpGroupIdentificationPortMapping</code>
[constr_10587]	Restriction for the applicability of <code>DiagnosticDoIPGroupIdentificationInterface</code>
[constr_10588]	Existence of <code>DiagnosticDoIpGroupIdentificationPortMapping.pPortPrototypeInExecutable</code>
[constr_10589]	Existence of <code>DiagnosticDoIpGroupIdentificationPortMapping.process</code>
[constr_10590]	Restriction for the applicability of <code>DiagnosticDoIpActivationLinePortMapping</code>
[constr_10591]	Restriction for the applicability of <code>DiagnosticDoIPActivationLineInterface</code>
[constr_10592]	Existence of <code>DiagnosticDoIpActivationLinePortMapping.pPortPrototypeInExecutable</code>
[constr_10593]	Existence of <code>DiagnosticDoIpActivationLinePortMapping.process</code>
[constr_10594]	Restriction for the applicability of <code>DiagnosticDoIpTriggerVehicleAnnouncementPortMapping</code>
[constr_10595]	Restriction for the applicability of <code>DiagnosticDoIPTriggerVehicleAnnouncementInterface</code>
[constr_10596]	Existence of <code>DiagnosticDoIpTriggerVehicleAnnouncementPortMapping.rPortPrototypeInExecutable</code>
[constr_10597]	Existence of <code>DiagnosticDoIpTriggerVehicleAnnouncementPortMapping.process</code>
[constr_10598]	Restriction for the applicability of <code>DiagnosticDoIpEntityIdentificationPortMapping</code>
[constr_10599]	Restriction for the applicability of <code>DiagnosticDoIPEntityIdentificationInterface</code>
[constr_10600]	Existence of <code>DiagnosticDoIpEntityIdentificationPortMapping.pPortPrototypeInExecutable</code>
[constr_10601]	Existence of <code>DiagnosticDoIpEntityIdentificationPortMapping.process</code>
[constr_10602]	Restriction for the applicability of <code>DiagnosticDoIpPowerModePortMapping</code>
[constr_10603]	Restriction for the applicability of <code>DiagnosticDoIPPowerModeInterface</code>
[constr_10604]	Existence of <code>DiagnosticDoIpPowerModePortMapping.pPortPrototypeInExecutable</code>
[constr_10605]	Existence of <code>DiagnosticDoIpPowerModePortMapping.process</code>
[constr_10609]	Existence of references in the role <code>AbstractDoIpPortMapping.rPortPrototypeInExecutable</code> and <code>AbstractDoIpPortMapping.pPortPrototypeInExecutable</code>
[constr_10611]	Existence of attribute <code>DoIpLogicalAddress.logicalAddress</code>





Number	Heading
[constr_10612]	Standardized values for attribute <code>CryptoKeySlotDesign.cryptoObjectType</code>
[constr_10613]	<code>CryptoKeySlotDesign</code> where attribute <code>shared</code> is set to <code>false</code>
[constr_10614]	Existence of attribute <code>CryptoKeySlotDesign.shared</code>
[constr_10616]	Existence of the reference in the role <code>StateClientInterface.functionGroupType</code>
[constr_10617]	Existence of the reference in the role <code>FunctionGroupPortMapping.functionGroup</code>
[constr_10618]	Existence of the reference in the role <code>FunctionGroupPortMapping.process</code>
[constr_10619]	Existence of the reference in the role <code>FunctionGroupPortMapping.rPortPrototypeInExecutable</code>
[constr_10620]	Reference to function group from <code>FunctionGroupPortMapping</code>
[constr_10621]	Same <code>ModeDeclarationGroup</code> for <code>StateClientInterface</code> and <code>FunctionGroupPortMapping.functionGroup</code>
[constr_10622]	Existence of <code>FunctionGroupPortMapping</code> depending on the role <code>rPortPrototypeInExecutable</code> and <code>process</code>
[constr_10623]	Type of <code>RPortPrototype</code> referenced in the role <code>IdsmQualifiedEventReceiverMapping.rPortPrototypeInExecutable</code>
[constr_10624]	<code>RPortPrototype</code> typed by an <code>IdsmQualifiedEventReceiverInterface</code>
[constr_10625]	Existence of <code>IdsmQualifiedEventReceiverMapping.idsPlatformInstantiation</code>
[constr_10626]	Existence of <code>IdsmQualifiedEventReceiverMapping.rPortPrototypeInExecutable</code>
[constr_10627]	Existence of <code>IdsmQualifiedEventReceiverMapping.process</code>
[constr_10628]	Allowed range of attribute <code>TimeSyncCorrection.providerRateDeviationMax</code>
[constr_3772]	Range of <code>ApApplicationError.errorCode</code> for interoperability with the AUTOSAR classic platform
[constr_3773]	Uniqueness of <code>ApApplicationError.errorCode</code> for interoperability with the AUTOSAR classic platform
[constr_3774]	Existence of <code>EthernetMacRawDataStreamMapping.localCommConnector</code>
[constr_3775]	Existence of <code>IEEE1722RawDataStreamConsumerMapping.ieee1722Stream</code>
[constr_3776]	Existence of <code>IEEE1722RawDataStreamProducerMapping.ieee1722Stream</code>
[constr_3777]	Existence of <code>IEEE1722AcfBusRawDataStreamConsumerMapping.acfBus</code>
[constr_3778]	Existence of <code>IEEE1722AcfBusPartRawDataStreamConsumerMapping.acfBusPart</code>
[constr_9322]	<code>ApmcFunctionalClusterDef</code> category restriction
[constr_9323]	Restriction of <code>DoIpFunctionalClusterDesign</code> on a <code>MachineDesign</code>
[constr_9324]	Allowed <code>PlatformModuleEthernetEndpointConfiguration.communicationConnector</code> references
[constr_9325]	<code>DoIpFunctionalClusterDesign.doIpLogicalAddress.logicalAddress</code> shall be within the physical address boundaries defined by <code>DoIpRequestConfiguration</code>
[constr_9327]	SOME/IP segment reception monitoring allowed for udp <code>SomeIpEventDeployments</code>





Number	Heading
[constr_9328]	Reception Monitoring of SOME/IP segments is allowed for udp SomeIpMethodDeployments
[constr_9329]	Allowed PlatformModuleEthernetEndpointConfiguration.tcpPort and PlatformModuleEthernetEndpointConfiguration.udpPort references
[constr_9334]	Supported value range for attribute GenericTpConnection.sourceAddressRangeStart
[constr_9335]	Supported value range for attribute GenericTpConnection.sourceAddressRangeEnd
[constr_9336]	DoIpNetworkConfigurationDesign shall reference a GenericTpConnection
[constr_9337]	Same priority for overlapping address ranges in the context of the same MachineDesign
[constr_9338]	GenericTpConnection.sourceAddressRangeStart shall be less or equal of GenericTpConnection.sourceAddressRangeEnd
[constr_9344]	Supported value range for attribute DoIpFunctionalClusterDesign.doIpProtocolVersion

Table B.4: Added Constraints in R24-11

B.2.2 Changed Constraints in R24-11

Number	Heading
[constr_10002]	Only one mapping per PortPrototype
[constr_10003]	Restriction for the existence of DiagnosticDataPortMapping.diagnosticDataIdentifier vs. DiagnosticDataPortMapping.diagnosticDataElement
[constr_10007]	Existence of ProcessExecutionError.executionError
[constr_10008]	Value of ProcessExecutionError.executionError
[constr_10023]	Mandatory content of any functionGroup
[constr_10029]	ServiceInterfaceDeployment shall cover all elements of the corresponding ServiceInterface
[constr_10030]	Existence of DiagnosticDataIdentifierInterface.read
[constr_10031]	Existence of DiagnosticRoutineInterface.start
[constr_10035]	Completeness of the PersistencyDeployment.version
[constr_10037]	Existence of attribute TagWithOptionalValue.sequenceOffset in the context of attribute capabilityRecord owned by ProvidedSomeIpServiceInstance , RequiredSomeIpServiceInstance , SdServerConfig , SdClientConfig , or AbstractServiceInstance
[constr_10046]	Value of PersistencyRedundancyMOutOfN.n
[constr_10047]	Restriction for the applicability of DiagnosticMonitorPortMapping
[constr_10048]	Existence of reference from DiagnosticMonitorPortMapping to DiagnosticEvent





Number	Heading
[constr_10049]	Restriction for the applicability of DiagnosticEventPortMapping
[constr_10050]	Restriction for the applicability of DiagnosticOperationCyclePortMapping
[constr_10051]	Existence of reference from DiagnosticOperationCyclePortMapping to DiagnosticOperationCycle
[constr_10052]	Restriction for the applicability of DiagnosticEnableConditionPortMapping
[constr_10053]	Existence of reference from DiagnosticEnableConditionPortMapping to DiagnosticEnableCondition
[constr_10054]	Restriction for the applicability of DiagnosticClearConditionPortMapping
[constr_10055]	Existence of reference from DiagnosticClearConditionPortMapping to DiagnosticClearCondition
[constr_10056]	Restriction for the applicability of DiagnosticIndicatorPortMapping
[constr_10057]	Restriction for the applicability of DiagnosticMemoryDestinationPortMapping
[constr_10058]	Restriction for the applicability of DiagnosticSecurityLevelPortMapping
[constr_10059]	Existence of reference from DiagnosticSecurityLevelPortMapping to DiagnosticSecurityLevel
[constr_10060]	PortInterface of PPortPrototype referenced by DiagnosticDataPortMapping
[constr_10061]	Mapping to DiagnosticDataIdentifierInterface , DiagnosticDataElementInterface , or DiagnosticDataIdentifierGenericInterface
[constr_10063]	Possible values for DiagnosticServiceValidationMapping.category
[constr_10064]	Existence of DiagnosticServiceValidationMapping.pPortPrototypeInExecutable
[constr_10065]	Validity of DiagnosticServiceValidationConfiguration.manufacturerValidationOrder
[constr_10066]	Validity of DiagnosticServiceValidationConfiguration.supplierValidationOrder
[constr_10069]	Existence of SoftwareClusterDiagnosticDeploymentProps.powerDownTime
[constr_10070]	Value of RequiredSomeipServiceInstance.requiredServiceInstanceId
[constr_10076]	Existence of RawDataStreamEthernetUdpCredentials.udpPort
[constr_10077]	Existence of ipV4Address and ipV6Address within AbstractRawDataStreamEthernetCredentials
[constr_10078]	Existence of RawDataStreamEthernetTcpUdpCredentials.tcpPort and udpPort
[constr_10079]	Existence of EthernetRawDataStreamMapping.localTcpPort and localUdpPort
[constr_10080]	Existence of initial values for PersistencyFileElement
[constr_10081]	Existence of initial values in the definition of PersistencyDataRequiredComSpec
[constr_10082]	Existence of initial values for PersistencyFile
[constr_10083]	Existence of initial values for PersistencyKeyValuePair





Number	Heading
[constr_10086]	Existence of unicastUdpCredentials and multicastCredentials in the context of a EthernetRawDataStreamServerMapping
[constr_10090]	Existence of ProcessToMachineMapping.persistencyCentralStorageURI
[constr_10092]	Restriction for the applicability of DiagnosticAuthenticationPortMapping
[constr_10093]	Existence of reference from DiagnosticAuthenticationPortMapping to DiagnosticAuthentication
[constr_10094]	Restriction for the applicability of DiagnosticExternalAuthenticationPortMapping
[constr_10098]	Relation of MachineDesign.pnResetTimer and UdpNmCluster.nmMsgCycleTime
[constr_10101]	Attribute NmHandleToFunctionGroupStateMapping.mappingDirection is set to nmHandleActiveToFunctionGroupState or nmHandleInactiveToFunctionGroupState
[constr_10102]	Existence of initial values for PersistencyKeyValuePair
[constr_10103]	Existence of initial values for PersistencyFile
[constr_10105]	Existence of UcmRetryStrategy.maximumNumberOfRetries
[constr_10106]	Existence of UcmRetryStrategy.retryIntervalTime
[constr_10107]	Existence of the attribute UcmMasterModuleInstantiation.blockInconsistent
[constr_10108]	Existence of the attribute UcmMasterModuleInstantiation.serviceBusy
[constr_10109]	Existence of the attribute UcmMasterModuleInstantiation.updateSessionRejected
[constr_10110]	Existence of UcmSubordinateModuleInstantiation on a Machine
[constr_10113]	Restriction for the existence of ExecutableLoggingImplementationProps
[constr_10114]	Existence of attributes of DiagnosticEnvDataElementCondition if the reference in the role pPortPrototype exists
[constr_10124]	Multiplicity of attribute ApplicationAssocMapDataType.key
[constr_10125]	Multiplicity of attribute ApplicationAssocMapDataType.value
[constr_10126]	Multiplicity of attribute ApplicationAssocMapElementValueSpecification.key
[constr_10127]	Multiplicity of attribute ApplicationAssocMapElementValueSpecification.value
[constr_10128]	Multiplicity of attribute CppImplementationDataTypeElementQualifier.typeReference
[constr_10129]	Multiplicity of attribute Field.hasGetter
[constr_10130]	Multiplicity of attribute Field.hasSetter
[constr_10131]	Multiplicity of attribute Field.hasNotifier
[constr_10132]	Multiplicity of attribute ApApplicationError.errorCode
[constr_10133]	Multiplicity of attribute ApApplicationErrorDomain.value
[constr_10134]	Multiplicity of reference in the role PortInterfaceToDataTypeMapping.dataTypeMappingSet
[constr_10135]	Multiplicity of reference in the role PortInterfaceToDataTypeMapping.portInterface





Number	Heading
[constr_10136]	Multiplicity of reference in the role ServiceInterfaceMapping.compositeServiceInterface
[constr_10137]	Multiplicity of reference in the role ServiceInterfaceMapping.sourceServiceInterface
[constr_10138]	Multiplicity of reference in the role ServiceInterfaceEventMapping.sourceEvent
[constr_10139]	Multiplicity of reference in the role ServiceInterfaceEventMapping.targetEvent
[constr_10140]	Multiplicity of reference in the role ServiceInterfaceFieldMapping.sourceField
[constr_10141]	Multiplicity of reference in the role ServiceInterfaceFieldMapping.targetField
[constr_10142]	Multiplicity of reference in the role ServiceInterfaceMethodMapping.sourceMethod
[constr_10143]	Multiplicity of reference in the role ServiceInterfaceMethodMapping.targetMethod
[constr_10144]	Multiplicity of reference in the role PersistencyRedundancyChecksum.algorithmFamily
[constr_10145]	Multiplicity of reference in the role PersistencyRedundancyChecksum.length
[constr_10146]	Multiplicity of reference in the role PersistencyRedundancyMOutOfN.m
[constr_10147]	Multiplicity of reference in the role PersistencyRedundancyMOutOfN.n
[constr_10148]	Multiplicity of reference in the role PersistencyFileElement.contentUri
[constr_10149]	Multiplicity of reference in the role PersistencyFileElement.fileName
[constr_10151]	Multiplicity of reference in the role PhmCheckpoint.checkpointId
[constr_10152]	Multiplicity of reference in the role FieldSenderComSpec.initValue
[constr_10154]	Multiplicity of reference in the role ProcessDesignToMachineDesignMapping.processDesign
[constr_10162]	Multiplicity of reference in the role DiagnosticClearConditionPortMapping.clearCondition
[constr_10163]	Multiplicity of reference in the role DiagnosticIndicatorPortMapping.indicator
[constr_10164]	Multiplicity of reference in the role DiagnosticMemoryDestinationPortMapping.memoryDestination
[constr_10165]	Multiplicity of reference in the role DiagnosticDataPortMapping.process
[constr_10166]	Multiplicity of attribute DiagnosticProvidedDataMapping.dataProvider
[constr_10167]	Multiplicity of attribute SomeipServiceDiscovery.someipServiceDiscoveryPort
[constr_10169]	Multiplicity of reference in the role Machine.machineDesign
[constr_10170]	Multiplicity of attribute Machine.trustedPlatformExecutableLaunchBehavior
[constr_10171]	Multiplicity of attribute Machine.processor
[constr_10172]	Multiplicity of attribute Processor.core
[constr_10173]	Multiplicity of attribute ProcessorCore.coreId





Number	Heading
[constr_10174]	Multiplicity of the reference in the role ProcessToMachineMapping.process
[constr_10175]	Multiplicity of attribute StateDependentStartupConfig.resourceGroup
[constr_10176]	Multiplicity of attribute StateDependentStartupConfig.startupConfig
[constr_10177]	Multiplicity of attribute PersistencyDeployment.updateStrategy
[constr_10178]	Multiplicity of the reference in the role PersistencyPortPrototypeToDeploymentMapping.process
[constr_10179]	Multiplicity of attribute PersistencyKeyValuePair.valueDataType
[constr_10180]	Multiplicity of the reference in the role PersistencyPortPrototypeToKeyValueStorageMapping.keyValueStorage
[constr_10182]	Multiplicity of the reference in the role PersistencyPortPrototypeToFileStorageMapping.fileStorage
[constr_10183]	Multiplicity of attribute PersistencyFile.fileName
[constr_10184]	Multiplicity of the reference in the role SynchronizedTimeBaseConsumer.networkTimeConsumer
[constr_10185]	Multiplicity of the reference in the role SynchronizedTimeBaseProvider.networkTimeProvider
[constr_10186]	Multiplicity of attribute DoIpFunctionalClusterDesign.entityStatusMaxByteFieldUse
[constr_10188]	Multiplicity of attribute DoIpInstantiation.logicalAddress
[constr_10189]	Multiplicity of attribute DoIpFunctionalClusterDesign.maxRequestBytes
[constr_10191]	Multiplicity of attribute DoIpNetworkConfiguration.isActivationLineDependent
[constr_10192]	Multiplicity of attribute DoIpNetworkConfiguration.maxInitialVehicleAnnouncementTime
[constr_10193]	Multiplicity of attribute DoIpNetworkConfiguration.maxTesterConnections
[constr_10194]	Multiplicity of attribute DoIpNetworkConfiguration.networkInterfaceId
[constr_10195]	Multiplicity of attribute DoIpNetworkConfiguration.vehicleIdentificationSyncStatus
[constr_10197]	Multiplicity of attribute DoIpRequestConfiguration.endAddress
[constr_10198]	Multiplicity of attribute DoIpRequestConfiguration.requestType
[constr_10199]	Multiplicity of attribute DoIpRequestConfiguration.startAddress
[constr_10200]	Multiplicity of attribute UcmModuleInstantiation.identifier
[constr_10207]	Multiplicity of the reference in the role CryptoProviderToPortPrototypeMapping.cryptoProvider
[constr_10208]	Multiplicity of the reference in the role CryptoProviderToPortPrototypeMapping.process
[constr_10209]	Existence of the reference in the role AbstractCryptoKeySlotToPortPrototypeMapping.keySlot
[constr_10210]	Existence of the reference in the role AbstractCryptoKeySlotToPortPrototypeMapping.process
[constr_10211]	Multiplicity of the reference in the role CryptoCertificateToCryptoKeySlotMapping.cryptoCertificate





Number	Heading
[constr_10212]	Multiplicity of attribute SomeipServiceInterfaceDeployment.serviceInterfaceId
[constr_10213]	Multiplicity of attribute SomeipServiceInterfaceDeployment.serviceInterfaceVersion
[constr_10214]	Multiplicity of attribute SomeipEventGroup.eventGroupId
[constr_10215]	Multiplicity of attribute SomeipEventDeployment.eventId
[constr_10216]	Multiplicity of attribute SomeipEventDeployment.transportProtocol
[constr_10217]	Multiplicity of the attribute DdsServiceInterfaceDeployment.serviceInterfaceId
[constr_10218]	Multiplicity of reference in the role ProvidedSomeipServiceInstance.sdServerConfig
[constr_10219]	Multiplicity of attribute ProvidedSomeipServiceInstance.serviceInstanceId
[constr_10220]	Multiplicity of attribute SomeipProvidedEventGroup.multicastThreshold
[constr_10221]	Multiplicity of reference in the role RequiredSomeipServiceInstance.sdClientConfig
[constr_10222]	Multiplicity of the reference in the role SomeipRequiredEventGroup.sdClientEventGroupTimingConfig
[constr_10223]	Multiplicity of attribute DdsServiceInstanceProps.domainId
[constr_10224]	Multiplicity of reference in the role DdsEventQosProps.event
[constr_10225]	Multiplicity of reference in the role DdsFieldQosProps.field
[constr_10226]	Multiplicity of attribute E2EProfileConfiguration.profileName
[constr_10227]	Multiplicity of attribute SecOcJobRequirement.secOcJobSemantic
[constr_10230]	Multiplicity of attribute SignalServiceTranslationEventProps.safeTranslation
[constr_10231]	Multiplicity of attribute SignalServiceTranslationEventProps.secureTranslation
[constr_10232]	Multiplicity of reference in the role PersistencyDeploymentToCryptoKeySlotMapping.persistencyDeployment
[constr_10233]	Multiplicity of the reference in the role SoftwareCluster.vendorSignature
[constr_10234]	Multiplicity of attribute SoftwareCluster.version
[constr_10235]	Multiplicity of attribute SoftwareCluster.vendorId
[constr_10236]	Multiplicity of attribute SoftwareClusterDiagnosticAddress.addressSemantics
[constr_10237]	Multiplicity of attribute SoftwareClusterDependencyCompareCondition.compareType
[constr_10240]	Multiplicity of attribute SoftwarePackage.actionType
[constr_10242]	Multiplicity of attribute SoftwarePackage.minimumSupportedUcmVersion
[constr_10243]	Multiplicity of attribute SoftwarePackage.packagerId
[constr_10244]	Multiplicity of reference in the role SoftwarePackage.packagerSignature
[constr_10245]	Multiplicity of reference in the role SoftwarePackage.softwareCluster





Number	Heading
[constr_10246]	Multiplicity of attribute <code>SoftwarePackage.uncompressedSoftwareClusterSize</code>
[constr_10247]	Multiplicity of reference in the role <code>VehiclePackage.packagerSignature</code>
[constr_10248]	Multiplicity of reference in the role <code>UcmDescription.identifier</code>
[constr_10249]	Multiplicity of reference in the role <code>VehicleDriverNotification.approvalRequired</code>
[constr_10250]	Multiplicity of reference in the role <code>VehicleDriverNotification.notificationState</code>
[constr_10251]	Multiplicity of the reference in the role <code>ServiceFieldDeployment.field</code>
[constr_10253]	Multiplicity of attribute <code>SoftwareClusterDependencyCompareCondition.considerBuildNumber</code>
[constr_10254]	Multiplicity of attribute <code>SoftwareClusterDependencyCompareCondition.version</code>
[constr_10255]	Multiplicity of attribute <code>SignalServiceTranslationProps.serviceControl</code>
[constr_10256]	Multiplicity of reference in the role <code>SoftwarePackageStoring.storing</code>
[constr_10365]	Existence of <code>PersistencyDeployment.deploymentUri</code>
[constr_10366]	Possible multiplicities of <code>PersistencyDeployment.deploymentUri</code>
[constr_10367]	Condition for the multiplicity of attribute <code>PersistencyDeployment.deploymentUri</code>
[constr_10374]	Existence of the attribute <code>UcmSubordinateModuleInstantiation.verifyUpdate</code>
[constr_10375]	Existence of the attribute <code>UcmSubordinateModuleInstantiation.prepareUpdate</code>
[constr_10376]	Existence of the attribute <code>UcmSubordinateModuleInstantiation.prepareRollback</code>
[constr_10377]	Completeness of the modeling of <code>PersistencyKeyValueDataTypeMapping</code>
[constr_10378]	<code>PersistencyKeyValueDataTypeMapping</code> references <code>AbstractImplementationDataType</code> in the role <code>currentDataType</code>
[constr_10379]	<code>PersistencyKeyValueDataTypeMapping</code> references <code>ApplicationDataType</code> in the role <code>currentDataType</code>
[constr_10380]	Target of <code>ArtifactLocator.representedModelElement</code>
[constr_10381]	Existence of attribute <code>ArtifactLocator.uri</code>
[constr_10382]	Existence of attribute <code>ArtifactLocator.representedModelElement</code>
[constr_10399]	Allowed interval of the "index" field according to the initialization rule for data object typed by a <code>CppImplementationDataType</code> of category <code>VARIANT</code>
[constr_10411]	Existence of <code>ExecutionDependency</code> and references to <code>Function Group States</code>
[constr_10416]	Aggregation of optional <code>templateArgument</code> that defines an <code>Allocator</code> for a <code>VECTOR</code>
[constr_10417]	Existence of attributes of <code>CppImplementationDataTypes</code> depending on the <code>category</code>
[constr_10420]	Restriction for the existence of initial values for <code>PersistencyDataElement</code>
[constr_10425]	Existence of initial values for <code>PersistencyDataElement</code>





Number	Heading
[constr_10426]	Multiplicity of attribute PersistencyDeploymentElement.updateStrategy
[constr_10427]	Multiplicity of attribute PersistencyInterfaceElement.updateStrategy
[constr_10428]	Existence of attribute UcmModuleInstantiation.identifier in subclasses
[constr_10429]	Existence of attribute VehicleRolloutStep.violatedSafetyConditionBehavior
[constr_10430]	Existence of attribute Machine.defaultApplicationTimeout
[constr_10431]	Existence of attribute Machine.defaultApplicationTimeout.enterTimeoutValue
[constr_10432]	Existence of attribute Machine.defaultApplicationTimeout.exitTimeoutValue
[constr_10436]	Restriction for the applicability of DiagnosticMultipleMonitorPortMapping
[constr_10437]	Restriction for the applicability of DiagnosticMultipleEventPortMapping
[constr_10438]	Restriction for the applicability of DiagnosticMultipleConditionPortMapping
[constr_10441]	Restriction for NetworkHandlePortMapping.pPortPrototypeInExecutable
[constr_10483]	Applicable values of baseTypeEncoding in the context of the definition of a DiagnosticDataElement
[constr_10484]	Existence of FunctionalClusterInteractsWithPersistencyDeploymentMapping.contractVersion
[constr_10485]	Existence of PersistencyInterface.contractVersion
[constr_10486]	Existence of PersistencyKeyValueDataTypeMapping.previousContractVersion
[constr_10487]	Only one physical address per DiagnosticCommonProps
[constr_10488]	Existence of attribute DiagnosticCommonProps.authenticationTimeout
[constr_10490]	DiagnosticDataElement shall be directly or indirectly the target of a reference owned by a subclass of DiagnosticMapping
[constr_10491]	Type of PPortPrototype referenced in the role IdsmTimestampProviderMapping.pPortPrototypeInExecutable
[constr_10492]	PPortPrototype typed by a IdsmTimestampProviderInterface
[constr_10493]	Existence of IdsmTimestampProviderMapping.idsPlatformInstantiation
[constr_10494]	Existence of IdsmTimestampProviderMapping.pPortPrototypeInExecutable
[constr_10495]	Existence of IdsmTimestampProviderMapping.process
[constr_10496]	Type of PPortPrototype referenced in the role IdsmContextProviderMapping.pPortPrototypeInExecutable
[constr_10497]	PPortPrototype typed by a IdsmContextProviderInterface
[constr_10499]	Existence of IdsmContextProviderMapping.pPortPrototypeInExecutable
[constr_10500]	Existence of IdsmContextProviderMapping.process
[constr_10501]	Access to time stamps for <i>Intrusion Detection System Management</i>





Number	Heading
[constr_10508]	Existence of the attribute <code>UcmSubordinateModuleInstantiation.maxAvailablePersistencyStorageSpace</code>
[constr_10509]	Existence of attribute <code>PersistencyDeployment.maximumAllowedSize</code>
[constr_10510]	Existence of attribute <code>PersistencyDeployment.minimumSustainedSize</code>
[constr_10511]	Reference <code>StateManagementStateRequest.stateRequestPort</code> shall not exist if <code>StateManagementStateRequest</code> is referenced from <code>NmInteractsWithSmMapping</code>
[constr_11000]	<code>SomeipEventDeployment.eventReceptionDefaultValue</code> or <code>UserDefinedEventDeployment.eventReceptionDefaultValue</code> shall not be specified in the physical domain
[constr_1473]	No support for <code>PRPortPrototype</code>
[constr_1478]	<code>SwDataDefProps</code> applicable to <code>ApplicationDataTypes</code> exclusive to the <i>AUTOSAR adaptive platform</i>
[constr_1482]	Mapping of service interfaces vs. mapping of service interface elements
[constr_1483]	Applicability of a <code>ServiceInterface</code>
[constr_1488]	Initialization of a <code>DataPrototype</code> typed by an <code>ApplicationAssocMapDataType</code>
[constr_1489]	Uniqueness of <code>ApplicationAssocMapValueSpecification.mapElementTuple.key</code>
[constr_1490]	Allowed value for <code>Executable.category</code> if <code>ProcessToMachineMapping</code> references a <code>NonOsModuleInstantiation</code>
[constr_1492]	<code>SwComponentType</code> referenced in the role <code>Executable.rootSwComponentPrototype.applicationType</code>
[constr_1494]	Initial value for <code>event</code>
[constr_1507]	<code>PortInterfaceToDataTypeMapping</code> is only applicable to <code>ServiceInterface</code> or <code>PersistencyKeyValueStorageInterface</code>
[constr_1536]	Definition of <code>SoftwareCluster</code> applies for a single <code>Machine</code>
[constr_1549]	Value of <code>ProcessorCore.coreId</code>
[constr_1550]	Reference from <code>Process</code> to <code>ProcessDesign</code>
[constr_1551]	Existence of <code>DataPrototypeInServiceInterfaceRef.dataPrototype</code> vs. <code>DataPrototypeInServiceInterfaceRef.elementInImplDatatype</code>
[constr_1553]	Restriction for <code>ProcessToMachineMapping</code>
[constr_1554]	Restriction regarding attribute <code>PersistencyKeyValuePair.initValue</code>
[constr_1555]	Restriction applicable for <code>PersistencyPortPrototypeToKeyValueStorageMapping.portPrototype</code>
[constr_1556]	Restriction applicable for <code>PersistencyPortPrototypeToFileStorageMapping.portPrototype</code>
[constr_1560]	Usage of <code>SoftwareClusterDesign.requiredARElement</code>
[constr_1566]	Usage of <code>SoftwareCluster.containedARElement</code>
[constr_1570]	Restriction for <code>UserDefinedServiceInterfaceDeployment</code> of <code>category SERVICE_INTERFACE_DEPLOYMENT_IPC</code>
[constr_1571]	<code>CppImplementationDataType</code> is limited





Number	Heading
[constr_1576]	Existence of <code>CppTemplateArgument.templateType</code> vs. <code>CppTemplateArgument allocator</code>
[constr_1578]	Applicable data categories
[constr_1579]	<code>SwDataDefProps</code> applicable to <code>CppImplementationDataTypes</code> exclusive to the <i>AUTOSAR adaptive platform</i>
[constr_1581]	Value of <code>fileElement.fileName</code>
[constr_1582]	<code>PersistencyKeyValuePair.valueDataType</code> shall match to <code>AbstractImplementationDataType</code> for the corresponding <code>PersistencyDataElement</code>
[constr_1589]	Value of <code>file.fileName</code>
[constr_1593]	Completeness of the existence of a set of <code>TlvDataIdDefinition.tlvArguments</code>
[constr_1594]	Consistent assignment of TLV data ids to <code>ApplicationRecordDataType</code>
[constr_1595]	Consistent assignment of TLV data ids to <code>CppImplementationDataType</code> or <code>CppImplementationDataTypeElement</code>
[constr_1596]	Scope of the uniqueness of the value of <code>TlvDataIdDefinition.id</code> for references to <code>ArgumentDataPrototype</code>
[constr_1597]	Scope of the uniqueness of the value of <code>TlvDataIdDefinition.id</code> for references to <code>ApplicationRecordElement</code>
[constr_1598]	Scope of the uniqueness of the value of <code>TlvDataIdDefinition.id</code> for references to <code>CppImplementationDataTypeElement</code>
[constr_1599]	<code>TlvDataIdDefinition</code> referencing <code>ArgumentDataPrototype</code>
[constr_1600]	<code>TlvDataIdDefinition</code> referencing <code>ApplicationRecordElement</code>
[constr_1601]	<code>TlvDataIdDefinition</code> referencing <code>CppImplementationDataTypeElement</code>
[constr_1603]	Completeness of the existence of a set of <code>TlvDataIdDefinition.tlvRecordElements</code>
[constr_1604]	Completeness of the existence of a set of <code>TlvDataIdDefinition.tlvImplementationDataTypeElements</code>
[constr_1605]	Standardized values of attribute <code>Executable.category</code>
[constr_1606]	<code>Processes</code> with mutual <code>ExecutionDependency</code> s
[constr_1613]	File name of matching pairs of <code>PersistencyFileElement</code> and <code>PersistencyFile</code>
[constr_1618]	Ability to shut down
[constr_1619]	Ability to restart
[constr_1625]	Existence of reference <code>ApApplicationError.errorDomain</code>
[constr_1628]	Definition of static length field sizes in case of TLV usage
[constr_1629]	Identical sizes of length fields in case of TLV usage
[constr_1630]	No definition of length field sizes on <code>DataPrototype</code> level in case of TLV usage
[constr_1658]	Number of <code>DiagnosticTroubleCodeUdsToClearConditionGroupMapping</code> elements per <code>DiagnosticTroubleCodeUds</code>
[constr_1659]	Restriction for the usage of <code>CppImplementationDataTypeElementQualifier.inplace</code>





Number	Heading
[constr_1660]	Restriction for the usage of <code>CppTemplateArgument.inplace</code>
[constr_1661]	Multiplicity of <code>OsModuleInstantiation.resourceGroup</code>
[constr_1664]	Unique <code>ApApplicationError.shortName</code>
[constr_1665]	Unique <code>ApApplicationError.errorCode</code>
[constr_1666]	References from <code>PersistencyPortPrototypeToKeyValueStorageMapping</code> to <code>PersistencyKeyValueStorage</code>
[constr_1667]	References from <code>PersistencyPortPrototypeToFileStorageMapping</code> to <code>PersistencyFileStorage</code>
[constr_1668]	Allowed combinations of <code>PersistencyRedundancyChecksum.length</code> and <code>algorithmFamily</code>
[constr_1673]	Existence of attributes <code>hasGetter</code> , <code>hasSetter</code> , and <code>hasNotifier</code>
[constr_1675]	Existence of attribute <code>ApSomeipTransformationProps.stringEncoding</code>
[constr_1676]	Consistency of references <code>shallRunOn</code> and <code>shallNotRunOn</code>
[constr_1677]	Mutual exclusive existence of references <code>shallRunOn</code> and <code>shallNotRunOn</code>
[constr_1678]	Allowed values for attribute <code>ApSomeipTransformationProps.stringEncoding</code>
[constr_1688]	<code>StateDependentStartupConfig</code> shall only refer to Function Group States of the same Function Group
[constr_1689]	Modeling of a startup dependency between different <code>Processes</code>
[constr_1691]	<code>UcmModuleInstantiation.identifier</code> shall be unique
[constr_1692]	Value of <code>schedulingPriority</code>
[constr_1693]	Relation of <code>Executable</code> , <code>ProcessDesign</code> , and <code>Process</code>
[constr_1695]	Semantics of a <code>Grant</code> depends on the existence of <code>CmModuleInstantiation</code>
[constr_1696]	<code>ClientServerOperation</code> aggregated by <code>DiagnosticRoutineInterface</code>
[constr_1697]	Restriction for <code>ClientServerOperation</code> aggregated by a <code>DiagnosticDataIdentifierInterface</code> or <code>DiagnosticDataElementInterface</code>
[constr_1708]	Combination of <code>CppImplementationDataTypeElement.isOptional</code> and <code>CppImplementationDataTypeElementQualifier.inplace</code>
[constr_1710]	Consistency of values of attributes <code>PersistencyInterface.redundancy</code> and <code>PersistencyRedundancyHandling.scope</code>
[constr_1723]	<code>ProvidedSomeipServiceInstance</code> shall be unique in respect of <code>serviceInstanceId</code> , <code>serviceInterfaceId</code> and <code>majorVersion</code> on a VLAN
[constr_1727]	Qualified combinations of <code>PortPrototypes</code> and <code>PhmSupervisedEntityInterface</code> on application software level
[constr_1729]	Qualified combinations of <code>PortPrototypes</code> and <code>PhmSupervisionRecoveryNotificationInterface</code> on State Management software level
[constr_1731]	Value of <code>UcmDescription.identifier</code> in the scope of a <code>VehiclePackage</code>
[constr_1736]	Multiplicity of reference <code>LogicalSupervision.initialCheckpoint</code>
[constr_1737]	Multiplicity of reference <code>LogicalSupervision.finalCheckpoint</code>
[constr_1740]	Multiplicity of reference <code>LogicalSupervision.transition</code>





Number	Heading
[constr_1742]	Multiplicity of reference SupervisionCheckpoint.phmCheckpoint
[constr_1743]	CppImplementationDataType.headerFile vs. CppImplementationDataType.typeEmitter
[constr_1746]	Mutual exclusive existence of PersistencyInterface.redundancy and PersistencyInterface.redundancyHandling
[constr_1747]	Completeness of the SoftwareCluster.version
[constr_1748]	Existence of references TlvDataIdDefinition.tlvArgument , TlvDataIdDefinition.tlvRecordElement , and TlvDataIdDefinition.tlvImplementationDataTypeElement
[constr_1751]	Value of PersistencyRedundancyMOutOfN.m
[constr_1764]	Counterpart of PhmCheckpoint
[constr_1769]	Existence of ProcessArgument.argument
[constr_1770]	Value of ProvidedSomeipServiceInstance.serviceInstanceId
[constr_1784]	Restriction for the reference to UploadableExclusivePackageElement
[constr_1785]	Restriction regarding the reference into another SoftwareCluster
[constr_1786]	Restriction to use functionGroup in terms of SoftwareCluster
[constr_1787]	Restricted use of Function Groups in the context of a SoftwareCluster
[constr_1788]	Restriction to SoftwareCluster of category PLATFORM_CORE
[constr_3287]	Mandatory information of a ProvidedSomeipServiceInstance
[constr_3288]	IP configuration restriction for unicastNetworkEndpoints
[constr_3290]	Transport Protocol attributes defined for a ProvidedSomeipServiceInstance
[constr_3300]	Allowed ServiceMethodDeployment.method references
[constr_3301]	Allowed ServiceEventDeployment.event references
[constr_3302]	Allowed ServiceFieldDeployment.field references
[constr_3304]	Value of attribute SomeipEventGroup.eventGroupId shall be unique
[constr_3305]	Value of attribute SomeipEventDeployment.eventId shall be unique
[constr_3306]	Value of attribute methodId shall be unique per SomeipServiceInterfaceDeployment
[constr_3308]	SomeipEventDeployment.transportProtocol setting to tcp and the impact on ProvidedSomeipServiceInstances
[constr_3309]	SomeipMethodDeployment.transportProtocol setting to udp and the impact on ProvidedSomeipServiceInstances
[constr_3310]	SomeipMethodDeployment.transportProtocol setting to tcp and the impact on ProvidedSomeipServiceInstances
[constr_3320]	Aggregation of CommunicationConnector by MachineDesign
[constr_3349]	Usage of ApplicationAssocMapDataType is limited
[constr_3351]	SOME/IP segmentation allowed for udp SomeipEventDeployments
[constr_3352]	SOME/IP segmentation allowed for udp SomeipMethodDeployments
[constr_3353]	Restriction in usage of ApSomeipTransformationProps.sizeOfArrayLengthField





Number	Heading
[constr_3354]	Restriction in usage of ApSomeipTransformationProps.sizeOfStructLengthField
[constr_3355]	Restriction in usage of ApSomeipTransformationProps.sizeOfUnionLengthField
[constr_3356]	Restriction in usage of ApSomeipTransformationProps.alignment
[constr_3357]	Restriction in usage of ApSomeipTransformationProps.sizeOfUnionTypeSelectorField
[constr_3359]	RPortPrototypeProps are related only to RPortPrototypes
[constr_3361]	Selective definition of serialization settings
[constr_3362]	SomeipEventDeployments aggregated by a SomeipFieldDeployment
[constr_3363]	SomeipMethodDeployments aggregated by a SomeipFieldDeployment
[constr_3367]	FieldMapping.notifierDataElement reference
[constr_3368]	FieldMapping.getterOperation reference
[constr_3369]	FieldMapping.setterOperation reference
[constr_3370]	InterfaceMapping shall map all elements of a single ServiceInterface
[constr_3371]	Mutually exclusive existence of FireAndForgetMethodMapping.dataElement reference and FireAndForgetMethodMapping.trigger reference
[constr_3372]	Restriction in usage of ApSomeipTransformationProps.sizeOfStringLengthField
[constr_3374]	method with attribute fireAndForget set to true shall not have any inout or out arguments
[constr_3375]	method with attribute fireAndForget set to true shall not reference an ApApplicationError
[constr_3376]	FireAndForgetMethodMapping shall reference only fire and forget methods
[constr_3391]	ServiceInterfaceElementSecureComConfig references to ServiceInterfaceDeployment elements
[constr_3392]	ServiceInterfaceElementSecureComConfig.dataId and ServiceInterfaceElementSecureComConfig.freshnessValueId are mandatory in case of SecOC communication
[constr_3393]	Usage of shallRunOn and shallNotRunOn references
[constr_3395]	TransformationPropsToServiceInterfaceElementMapping is restricted to one single ServiceInterface
[constr_3396]	Number of Process.stateDependentStartupConfig that refer to the same functionGroupState
[constr_3408]	Value range of SomeipEventDeployment.eventId
[constr_3409]	Value range of SomeipMethodDeployment.methodId
[constr_3410]	Value range of SomeipServiceInterfaceDeployment.serviceInterfaceId
[constr_3413]	StateDependentStartupConfig of a Process is mapped to exactly one ResourceGroup
[constr_3414]	Allowed usage of PlatformModuleEthernetEndpointConfiguration attributes that are allowed to be used to configure the network communication in the different platform modules





Number	Heading
[constr_3415]	Value range of <code>ProvidedSomeipServiceInstance.loadBalancingPriority</code>
[constr_3416]	Value range of <code>ProvidedSomeipServiceInstance.loadBalancingWeight</code>
[constr_3417]	<code>UserDefinedEventDeployments</code> aggregated by a <code>UserDefinedFieldDeployment</code>
[constr_3418]	<code>UserDefinedMethodDeployments</code> aggregated by a <code>UserDefinedFieldDeployment</code>
[constr_3419]	Allowed usage of <code>UdpNmNetworkConfiguration</code> attributes
[constr_3421]	Fibex elements applicable for a <code>System</code> of category <code>MACHINE_DESIGN_EXTRACT</code>
[constr_3423]	<code>StateDependentStartupConfig</code> of a <code>Process</code> shall reference a <code>functionGroupState</code>
[constr_3424]	<code>StateDependentStartupConfig</code> shall never reference the <code>functionGroupState Off</code>
[constr_3425]	Restriction of <code>DoIpInstantiations</code> on a <code>Machine</code>
[constr_3429]	No allocator usage for <code>CppImplementationDataTypes</code> of category <code>VARIANT</code>
[constr_3433]	Aggregation of <code>templateArguments</code> for an <code>ARRAY</code>
[constr_3434]	Aggregation of <code>templateArguments</code> for a <code>VECTOR</code>
[constr_3443]	Specification of a namespace for a <code>StdCppImplementationDataType</code>
[constr_3446]	<code>CppTemplateArgument</code> with <code>allocator</code> reference and the <code>inplace</code> flag
[constr_3447]	<code>ApSomeipTransformationProps.sizeOfArrayLengthField</code> that equals 0
[constr_3462]	<code>CppTemplateArgument.templateType</code> reference to <code>StdCppImplementationDataType</code> of category <code>STRUCTURE</code> and the <code>inplace</code> flag
[constr_3485]	UDP endpoint using DTLS SERVER role can only serve provided service instances
[constr_3486]	TCP endpoint using TLS SERVER role can only serve provided service instances
[constr_3487]	TCP endpoint can only serve provided or required service instances exclusively
[constr_3492]	<code>DoIpInstantiation.logicalAddress</code> shall be defined as member in the <code>DoIpRequestConfiguration</code>
[constr_3493]	Applicable attributes for standardized E2E Profiles
[constr_3495]	Supported value range for attribute <code>DoIpFunctionalClusterDesign.eid</code>
[constr_3496]	Supported value range for attribute <code>DoIpInstantiation.gid</code>
[constr_3497]	Supported value range for attribute <code>DoIpFunctionalClusterDesign.maxRequestBytes</code>
[constr_3498]	Supported value range for attribute <code>DoIpInstantiation.logicalAddress</code>
[constr_3499]	Supported value range for attribute <code>DoIpRequestConfiguration.startAddress</code>
[constr_3528]	Value range of <code>DdsServiceInstanceProps.domainId</code>
[constr_3529]	Value range of <code>DdsProvidedServiceInstance.serviceInstanceId</code>
[constr_3530]	Mandatory definition of <code>checkpointId</code>
[constr_3538]	Only one <code>ServiceInstanceToMachineMapping</code> per technology and <code>CommunicationConnector</code>





Number	Heading
[constr_3539]	Only one AliveSupervision per SupervisionCheckpoint
[constr_3540]	SupervisionCheckpoint in supervision graph
[constr_3541]	qosProfile mandatory for DdsProvidedServiceInstance
[constr_3542]	qosProfile mandatory for DdsRequiredServiceInstance
[constr_3554]	E2E protection configuration check
[constr_3557]	Mandatory majorVersion at SomeipServiceInterfaceDeployment.serviceInterfaceVersion
[constr_3558]	RequiredSomeipServiceInstance.blocklistedVersion is restricted to the usage of minorVersion
[constr_3561]	minimumMinorVersion and RequiredSomeipServiceInstance.requiredMinorVersion value
[constr_3563]	Mandatory topic name values
[constr_3564]	Consistency between DDS Service Interface Deployment and Provided DDS Service Instance
[constr_3565]	Consistency between DDS Service Interface Deployment and Required DDS Service Instance
[constr_3568]	No support for cross PlatformHealthManagementContribution references
[constr_3569]	Applicability of attribute invalidValue on CppImplementationDataType of category TYPE_REFERENCE
[constr_3612]	Multiplicity of references recoveryNotification , recoveryAction , and process at RecoveryNotificationToPPortPrototypeMapping
[constr_3613]	Reference to a PhmSupervisionRecoveryNotificationInterface in the context of a HealthChannelSupervision
[constr_3619]	Mandatory references of TimeBaseProviderToPersistencyMapping
[constr_3623]	SupervisionCheckpoints in the context of a GlobalSupervision
[constr_3624]	At least one Supervision defined in the context of a GlobalSupervision
[constr_3625]	DeadlineSupervision referencing CheckpointTransition in the context of a GlobalSupervision
[constr_3626]	LogicalSupervision referencing CheckpointTransition in the context of a GlobalSupervision
[constr_3627]	Existence of SupervisionModeCondition.stateReference
[constr_3628]	Reference to Function Group State from a SupervisionModeCondition
[constr_3629]	Identical Function Group in the scope of a GlobalSupervision
[constr_3630]	GlobalSupervision and Process relation
[constr_3631]	Global supervision restricted to one Function Group
[constr_3632]	Supervision of a Supervised Entity Instance in the scope of a Function Group State
[constr_3633]	Mandatory attributes of AliveSupervision
[constr_3634]	Multiplicity of CheckpointTransition.source and CheckpointTransition.target
[constr_3635]	Mandatory attributes of DeadlineSupervision
[constr_3639]	Existence of SupervisionMode.expiredSupervisionTolerance





Number	Heading
[constr_3640]	Existence of SupervisionMode.modeCondition
[constr_3641]	Allowed combinations of ServiceInterfaceDeployment , AdaptivePlatformServiceInstance , ServiceInstanceToMachineMapping
[constr_3642]	Restriction of aggregation of PortPrototypeProps to the Adaptive Platform
[constr_3645]	discoveryType mandatory for DdsProvidedServiceInstance
[constr_3646]	resourceIdentifierType mandatory for DdsProvidedServiceInstance
[constr_3647]	resourceIdentifierType value for USER_DATA QoS-based discovery
[constr_3648]	discoveryType mandatory for DdsRequiredServiceInstance
[constr_3649]	Consistent SupervisionCheckpoint.process reference
[constr_3674]	Existence of NoSupervision.targetPhmSupervisedEntity
[constr_3675]	Existence of NoSupervision.process
[constr_3676]	Exclusive usage of NoSupervision
[constr_3677]	ComGrants referencing DDS Service Instances
[constr_3680]	Existence of attributes for DdsTopicAccessRule
[constr_3681]	Supported values of DdsTopicAccessRule.dataProtectionKind
[constr_3682]	Values of DdsDomainRange.min and DdsDomainRange.max
[constr_3683]	Attributes referencing DdsTopicAccessRule
[constr_3684]	Mutual exclusivity of Secure Communication Properties
[constr_3690]	DdsServiceInterfaceDeployment.serviceInterfaceId value shall not conflict with topic-based service discovery
[constr_3691]	Existence of ServiceInterfaceElementSecureComConfig.securedRxVerification
[constr_3693]	EthernetCommunicationConnector.category is set to CAN_XL
[constr_3694]	Existence of canXlConfig vs. canXlConfigReqs
[constr_3709]	AliveSupervision.terminatingCheckpoint required for self terminating Processes
[constr_3710]	Process referenced by AliveSupervision.terminatingCheckpoint
[constr_3711]	AliveSupervision.terminatingCheckpointTimeoutUntilTermination
[constr_3712]	Exclusive usage of NoCheckpointSupervision
[constr_3715]	Reference in the role SomeipEventGroup.event
[constr_3721]	Upper multiplicity of reference in the role EthernetCommunicationConnector.unicastNetworkEndpoint
[constr_3722]	Upper multiplicity of reference in the role EthernetCommunicationConnector.canXlProps
[constr_3723]	Upper multiplicity of reference in the role MachineDesign.tcpIpProps
[constr_3724]	Upper multiplicity of reference in the role MachineDesign.tcpIpIcmpProps
[constr_3725]	Upper multiplicity of reference in the role MachineDesign.ethIpProps
[constr_3727]	Upper multiplicity of reference in the role SoftwareClusterDesign.intendedTargetMachine





Number	Heading
[constr_3729]	Upper multiplicity of reference in the role <code>LogAndTraceInstantiation.timeBaseResource</code>
[constr_3730]	Upper multiplicity of reference in the role <code>HealthChannel.recoveryNotification</code>
[constr_3731]	Upper multiplicity of reference in the role <code>ProcessDesign.executable</code>
[constr_3732]	Upper multiplicity of reference in the role <code>Process.executable</code>
[constr_3734]	Upper multiplicity of reference in the role <code>DoIpNetworkConfiguration.networkConfiguration</code>
[constr_5000]	Supported value range for attribute <code>DoIpRequestConfiguration.endAddress</code>
[constr_5004]	Mapping of a <code>Process</code> to a <code>Machine</code> is mandatory in the Execution Manifest
[constr_5033]	Compatibility of data types with <code>category VALUE</code>
[constr_5034]	Compatibility of data types with <code>category BOOLEAN</code>
[constr_5035]	Compatibility of data types with <code>category STRING</code>
[constr_5036]	Compatibility of data types with <code>category ARRAY</code>
[constr_5037]	Compatibility of data types with <code>category ARRAY</code> with <code>variableSize</code>
[constr_5038]	Compatibility of data types with <code>category ARRAY</code> with <code>fixedSize</code>
[constr_5039]	Compatibility of data types with <code>category STRUCTURE</code>
[constr_5040]	Compatibility of <code>ApplicationRecordDataType</code> and <code>CppImplementationDataType</code> that both represent an Optional Element Structure
[constr_5041]	Compatibility of data types with <code>category ASSOCIATIVE_MAP</code>
[constr_5042]	No data type mapping for <code>CppImplementationDataType</code> of <code>category VARIANT</code>
[constr_5043]	Forbidden mappings to <code>CppImplementationDataType</code>
[constr_5044]	<code>DataTypeMap</code> for composite data types
[constr_5045]	Only one <code>SomeipServiceDiscovery</code> configuration per VLAN is allowed
[constr_5047]	Supported values of <code>TlsSecureComProps.category</code>
[constr_5048]	Existence of <code>TlsCryptoCipherSuite.certificate</code> and <code>TlsCryptoCipherSuite.pskIdentity</code> in the <code>server</code> role
[constr_5052]	<code>ProvidedSomeipServiceInstances</code> of the same <code>serviceInterface</code> on one Machine
[constr_5056]	Restriction of sub-class of <code>CompositionSwComponentType.connector</code>
[constr_5057]	<code>PassThroughSwConnector</code> and <code>ServiceInterfaceMapping</code>
[constr_5102]	Usage of remote port ranges in <code>IPSecRule</code> is not allowed
[constr_5103]	Usage of local port ranges in <code>IPSecRule</code> is not allowed
[constr_5115]	Search for a specific SOME/IP ServiceInstance and for all SOME/IP Service Instances over the same <code>RPortPrototype</code>
[constr_5155]	<code>SomeipServiceInstanceToMachineMapping</code> only supports a single Address Family
[constr_5156]	<code>SomeipEventDeployment.transportProtocol</code> setting to <code>udp</code> and the impact on <code>ProvidedSomeipServiceInstances</code>





Number	Heading
[constr_5161]	RequiredSomeipServiceInstance that is mapped by a SomeipServiceInstanceToMachineMapping without a configured tcpPort and udpPort
[constr_5227]	Mandatory elements of UdpNmCluster
[constr_5228]	Partial Networking timing constraint
[constr_5230]	Attribute E2EProfileCompatibilityProps.transitToInvalidExtended shall exist for each E2EProfileConfiguration
[constr_5241]	Restriction applicable for AbstractCryptoKeySlotToPortPrototypeMapping.portPrototype
[constr_5250]	Protection of AdaptivePlatformServiceInstances of the same ServiceInterfaceDeployment
[constr_5260]	UDP endpoint using DTLS CLIENT role can only serve required service instances
[constr_5261]	TCP endpoint using TLS CLIENT role can only serve required service instances
[constr_5275]	Existence of LogAndTraceInstantiation.dltEcu
[constr_5276]	Existence of LogAndTraceInstantiation.logSink
[constr_5277]	Applicable values of DltLogSink.category vs. DltLogSink attributes
[constr_5278]	DltLogSink with category DLT_LOGSINK_REMOTE is only allowed to be referenced by DltLogSinkToPortPrototypeMapping
[constr_5279]	DltLogSink with category DLT_LOGSINK_DLT is only allowed to be referenced by LogAndTraceInstantiation
[constr_5281]	Existence of DltLogSink.defaultTraceState
[constr_5282]	Existence of DltLogSinkToPortPrototypeMapping.process
[constr_5283]	Existence of DltLogSinkToPortPrototypeMapping.dltLogSink
[constr_5284]	Existence of DltLogSinkToPortPrototypeMapping.dltContext
[constr_5285]	Existence of PortPrototype references in DltLogSinkToPortPrototypeMapping
[constr_5286]	Restriction applicable for DltLogSinkToPortPrototypeMapping.rPortPrototype
[constr_5287]	Restriction applicable for DltLogSinkToPortPrototypeMapping.pPortPrototype
[constr_5288]	Existence of process reference in DltApplicationToProcessMapping
[constr_5289]	Existence of dltApplication reference in DltApplicationToProcessMapping
[constr_5290]	PPortPrototype is not allowed to be typed by LogAndTraceInterface
[constr_5291]	Allowed usage of LTMessageCollectionToPortPrototypeMapping.rPortPrototype
[constr_5292]	Assigned dltSessionId shall be consistent for the same PortPrototype
[constr_5316]	Allowed ServiceEventDeployment.trigger references
[constr_5317]	ServiceEventDeployment not allowed to reference an event and a trigger at the same time
[constr_5324]	MachineDesign.communicationController aggregation restriction
[constr_5332]	Mandatory multicast endpoint in case of multicastThreshold different from 0





Number	Heading
[constr_5333]	No multicast in case of TCP
[constr_5338]	<code>ProvidedSomeipServiceInstance</code> shall offer all <code>SomeipEventGroups</code> for subscription
[constr_5339]	<code>SomeipEventGroups</code> of a <code>SomeipServiceInterfaceDeployment</code> shall be referenced at most once from a <code>RequiredSomeipServiceInstance</code> that instantiates the <code>SomeipServiceInterfaceDeployment</code>
[constr_5343]	Usage of <code>DoIpNetworkConfiguration.eidRetrieval</code>
[constr_5347]	Supported value range for attribute <code>SecOcSecureComProps.authenticationVerifyAttempts</code>
[constr_5348]	Mandatory <code>initialMode</code> in <code>ModeDeclarationGroup</code> that is referenced by <code>StateDependentFirewall</code>
[constr_5349]	Mandatory <code>defaultAction</code> in <code>StateDependentFirewall</code>
[constr_5350]	Mandatory <code>action</code> in <code>FirewallRuleProps</code>
[constr_5351]	<code>FirewallRule</code> is allowed to aggregate at most one protocol subelement
[constr_5352]	<code>DdsRule.submessageType</code> value restriction
[constr_5353]	<code>DdsRule.readerEntityId</code> and <code>DdsRule.writerEntityId</code> value restriction
[constr_5358]	<code>AdaptiveFirewallToPortPrototypeMapping.rPortPrototype</code> restriction
[constr_5368]	Multiplicity of the reference in the role <code>ComTriggerGrant.serviceDeployment</code>
[constr_5372]	SecureComProps for a <code>PlatformModuleEthernetEndpointConfiguration</code> that contains a UDP configuration
[constr_5373]	SecureComProps for a <code>PlatformModuleEthernetEndpointConfiguration</code> that contains a TCP configuration
[constr_5381]	Modeling of Security Event reports by <code>FunctionalCluster</code> shall not be done via <code>ProcessToMachineMapping</code>
[constr_5386]	Existence of <code>Executable.traceSwitchConfiguration</code>
[constr_5387]	Existence of reference <code>Executable.traceSwitchConfiguration.traceMessage</code>
[constr_5388]	Existence of attribute <code>Executable.traceSwitchConfiguration.traceSwitch</code>
[constr_5392]	Assignment of the same <code>event</code> to several <code>SomeipEventGroups</code> is forbidden in case one of the <code>SomeipEventGroups</code> has the <code>multicastThreshold</code> set to a value greater than 0
[constr_6815]	Existence of <code>CppTemplateArgument.templateType</code> for <code>CppImplementationDataType</code> of category <code>STRING</code>
[constr_6905]	<code>CppTemplateArgument allocator</code>

Table B.5: Changed Constraints in R24-11

B.2.3 Deleted Constraints in R24-11

Number	Heading
[constr_10022]	
[constr_10062]	
[constr_10150]	
[constr_10153]	
[constr_10187]	
[constr_10190]	
[constr_10241]	
[constr_1690]	
[constr_1728]	
[constr_3532]	
[constr_3614]	
[constr_3719]	

Table B.6: Deleted Constraints in R24-11