

Document Title	Requirements on ECU Resource Template
Document Owner	AUTOSAR
Document Responsibility	AUTOSAR
Document Identification No	252
Document Classification	Auxiliary

Document Status	Final
Part of AUTOSAR Release	4.2.2

Document Change History		
Release	Changed by	Description
	AUTOSAR	
4.2.2	Release	Layout update.
	Management	, ,
	AUTOSAR	
4.2.1	Release	Layout update.
	Management	
	AUTOSAR	
4.1.2	Release	Layout update.
	Management	
4.1.1	AUTOSAR	
4.1.1	Administration	Layout update.
0.1.4	AUTOSAR	
3.1.4	Administration	Initial release



Disclaimer

This specification and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the specification.

The material contained in this specification is protected by copyright and other types of Intellectual Property Rights. The commercial exploitation of the material contained in this specification requires a license to such Intellectual Property Rights.

This specification may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the specification may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The AUTOSAR specifications have been developed for automotive applications only. They have neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

Advice for users

AUTOSAR specifications may contain exemplary items (exemplary reference models, "use cases", and/or references to exemplary technical solutions, devices, processes or software).

Any such exemplary items are contained in the specifications for illustration purposes only, and they themselves are not part of the AUTOSAR Standard. Neither their presence in such specifications, nor any later documentation of AUTOSAR conformance of products actually implementing such exemplary items, imply that intellectual property rights covering such exemplary items are licensed under the same rules as applicable to the AUTOSAR Standard.



Table of Contents

1	Scope of this Document			
	1.1	Document Convention	6	
2	Rela	Related Documentation 7		
	2.1 2.2	Input Documents	7 7	
3	Req	uirements Tracing	8	
4	Req	uirements	9	
	4.1	General Requirements	9	
		ware elements [RS_ECUR_00004] Describe generic hardware	9 9 10	
		[RS_ECUR_00014] Timing properties of hardware	10	
		[RS_ECUR_00015] Describe variability of the hardware	10	
		[RS_ECUR_00017] Documentation Support	11	
	4.0	[RS_ECUR_00018] Support hardware descriptions from several sources	11 11	
	4.2	Requirements to describe dedicated hardware	11	
		[RS_ECUR_00008] Available memory	12	
		[RS_ECUR_00009] Available communication means	12	
		[RS_ECUR_00010] Available IO HW-Peripherals	13	
		[RS_ECUR_00016] IO-HW-Abstraction specification	13	
		[RS_ECUR_00011] Available sensors and actuators	14	
	4.3	Requirements on the ECU Resource template development	14	
		[RS_ECUR_00012] Development according to the AUTOSAR Generic		
		Structure Template document	14	
		[RS_ECUR_00013] Transformation of ECU Resource template model-		
		ing according to the AUTOSAR Model Persistence Rules for XML	15	
5	Cha	nge History	16	
	5.1	Change History for AUTOSAR 4.0.1 against 3.1.5	16	
	5.2	Change History for AUTOSAR 4.0.2 against 4.0.1	16	
	5.3	Change History for AUTOSAR 4.0.3 against 4.0.2	16	
	5.4	Change History for AUTOSAR 4.1.1 against 4.0.3	16	
	5.5	Change History for AUTOSAR 4.1.2 against 4.1.1	16	
	5.6	Change History for AUTOSAR 4.2.1 against 4.1.2	16	
	5.7	Change History for AUTOSAR 4.2.2 against 4.2.1	16	



Bibliography

- [1] Specification of ECU Resource Template AUTOSAR TPS ECUResourceTemplate
- [2] Requirements on ECU Configuration AUTOSAR_RS_ECUConfiguration
- [3] System Template AUTOSAR_TPS_SystemTemplate
- [4] Main Requirements AUTOSAR_RS_Main
- [5] Methodology AUTOSAR_TR_Methodology
- [6] Glossary
 AUTOSAR_TR_Glossary
- [7] Generic Structure Template
 AUTOSAR TPS GenericStructureTemplate
- [8] Model Persistence Rules for XML AUTOSAR_TR_XMLPersistenceRules
- [9] Requirements on Timing Extensions AUTOSAR RS TimingExtensions
- [10] Requirements on AUTOSAR Features AUTOSAR_RS_Features



1 Scope of this Document

This document collects the requirements on the ECU Resource Template (EcuR).

The main goal of the EcuR is to provide the scheme for the ECU Resource Description. The ECU Resource Description [1] holds information about the hardware components used to build an AUTOSAR system.

The context of EcuR does enclose

- Processing units
- Memory segments
- IO and communication peripherals
- Micro-controllers
- Ecu electronics
- Sensor and actuators (internal in the Ecu housing but also externally connected to the Ecu)

One usage of the EcuR is to support the system design by providing information about the available hardware resources and their connections.

- Available micro-controller / processor cores on each ECU
- Available memory on each ECU
- Available bus communication interfaces on each ECU

Another usage is the support of the ECU Configuration [2] by providing detailed information about the hardware and their connections.

- How the Ecu electronics is connected to the micro-controller peripherals
- Which micro-controller core has access to which memory and peripherals



1.1 Document Convention

The representation of requirements in AUTOSAR documents follows the table specified in [TPS_STDT_00078], see Standardization Template [3], chapter Support for Traceability.

The verbal forms for the expression of obligation specified in [TPS_STDT_00053] shall be used to indicate requirements, see Standardization Template [3], chapter Support for Traceability.



2 Related Documentation

2.1 Input Documents

The following input documents have been used in the development of these requirements:

- AUTOSAR Main Requirements [4]
- AUTOSAR Methodology [5]
- AUTOSAR Glossary [6]
- AUTOSAR Generic Structure Template [7]
- AUTOSAR Model Persistence Rules for XML [8]
- AUTOSAR Requirements on Timing Extensions [9]

2.2 Specification Documents

The requirements collected in this document will be satisfied by the Specification of the ECU Resource Template [1] document.



3 Requirements Tracing

The following table references the features specified in [10] and links to the fulfillments of these.

Feature	Description	Satisfied by
[RS_Main_00011]	No description	[RS_ECUR_00006]
[RS_Main_00130]	No description	[RS_ECUR_00016]
[RS_Main_00160]	No description	[RS_ECUR_00016]
[RS_Main_00310]	No description	[RS_ECUR_00018]
[RS_Main_00360]	No description	[RS_ECUR_00015]
[RS_TIMEX_00001]	Timing properties	[RS_ECUR_00014]



4 Requirements

4.1 General Requirements

[RS_ECUR_00005] Support configuration of Basic Software

Туре:	valid	
Description:	The ECU Resource template shall provide means to describe hardware properties which are supporting the configuration of the AUTOSAR Basic Software.	
Rationale:	Some ECU Configuration Parameter values can be derived from the ECU Resource description of the configured hardware.	
Use Case:	The maximum number of ADC channels is determined by the available hardware and can therefore be derived from the ECU Resource description.	
Dependencies:	Dependencies: -	
Supporting Material:	-	

]()

[RS_ECUR_00003] Describe characteristic properties of specific hardware elements \lceil

Туре:	valid	
Description:	The ECU Resource template shall provide means to describe the common and characteristic properties of hardware elements based on their kind.	
Rationale:	Due to the diversity in hardware kinds a dedicated description of the properties per hardware kind is needed.	
Use Case:	Description of the guaranteed number of erase cycles for EEPROM.	
Dependencies:	[RS_ECUR_00004]	
Supporting Material:	_	

10

[RS_ECUR_00004] Describe generic hardware

Туре:	valid
Description:	The ECU Resource template shall provide means to describe hardware elements of any kind.
Rationale:	Some hardware elements can already be described using dedicated means of the ECU Resource template ([RS_ECUR_00003]) – however there are hardware elements which have not been considered in the development of the ECU Resource template. For such hardware generic description mechanisms shall be available.
Use Case: Special ASIC hardware can not be described with dedicated description but only with generic attributes.	
Dependencies: [RS_ECUR_00003]	
Supporting Material:	-



[RS_ECUR_00006] Describe connections between hardware elements [

Туре:	valid	
Description:	The ECU Resource template shall provide means to describe in an abstracted way how the individual hardware elements – in an ECU and on the outside of the ECU – are connected.	
Rationale:	The way how the individual hardware elements are connected to each other is essential for the configuration of the ECU.	
Use Case:	 In a dual-core micro-controller some memory segments can only be accessed by one core. With the dedicated description of the individual cores and their connections to the memory segments the accessibility can be described. A Can-Transceiver needs several DIO ports for the control. With a description of the connection between the DIO ports and the transceiver the association is formally defined. 	
Dependencies:	-	
Supporting Material:	_	

](RS_Main_00011)

[RS_ECUR_00014] Timing properties of hardware [

Туре:	valid	
Description:	The ECU Resource template shall provide means to describe the timing properties for hardware I/O, e.g. the latency introduced by a digital I/O hardware port.	
Rationale:	Hardware I/O can introduce an additional significant latency, which must be taken into account for the analysis and validation of a system's timing behavior.	
Use Case:	Analysis and validation of timing behavior.	
Dependencies:	-	
Supporting Material:	_	

(RS_TIMEX_00001)

[RS_ECUR_00015] Describe variability of the hardware

Туре:	valid	
Description:	It shall be possible to describe the variability the actual hardware provides.	
Rationale:	Most hardware is highly configurable, however there are restrictions and constraints on how the configuration can happen.	
Use Case:	A pin of a controller can be either configured to be ADC or DIO. When the choice is done the other pins of that group are implicitly connected to the same peripheral.	
Dependencies:	-	
Supporting Material:	_	



](RS_Main_00360)

[RS_ECUR_00017] Documentation Support [

Туре:	valid	
Description:	The ECU Resource template shall provide means to add documentation to the hardware elements.	
Rationale:	To provide additional documentation about ECUs and peripherals, including elaborate text, figures and tables.	
Use Case:	Provide schematic figures on the ECU Electronics.	
Dependencies:	_	
Supporting Material:	-	

]()

[RS_ECUR_00018] Support hardware descriptions from several sources [

Туре:	valid
Description:	The ECU Resource template shall provide means to combine the hardware descriptions from several sources.
Rationale:	The different partners in AUTOSAR supplying hardware can contribute their hardware descriptions. The hardware integrator can utilize the individual hardware descriptions to deliver the complete hardware description.
Use Case:	The microcontroller vendor provides an ECU Resource Description for the microcontroller. The ECU vendor creates an ECU Resource Description for the ECU and uses the ECU Resource Description for the microcontroller from the microcontroller vendor.
Dependencies:	-
Supporting Material:	-

(RS_Main_00310)

4.2 Requirements to describe dedicated hardware

[RS_ECUR_00007] Processing Unit specification [

Type:	valid
Description:	The ECU Resource template shall provide dedicated means to describe a processing unit. A processing unit shall be defined as the core of the micro controller / processor.
Rationale:	The number of processing units is essential for the design of a System and ECU.



Use Case:	 In order to map the context of software execution to cores the individual cores need to be known. In a dual-core micro-controller some memory segments can only be accessed by one core. With the dedicated description of the individual cores the access to these memory segments can be described.
Dependencies:	_
Supporting Material:	_

[RS_ECUR_00008] Available memory [

Туре:	valid
Description:	The ECU Resource template shall provide dedicated means to describe memory segments. This includes all possible memory kinds like RAM, ROM, EEPROM, Flash, etc.
Rationale:	The amount of memory segments and their attributes is essential for the design of a System and ECU.
Use Case:	 The available memory amount is require to be able to allocate software to the different ECUs in the system and check whether the software will fit from a memory point of view. During the linker run the software's memory needs are mapped onto the physical available hardware memory. In order to support this activity the memory segments shall be described for each ECU. In a multi-core micro-controller some memory segments can only be accessed by one core. With the dedicated description of the individual cores the access to these memory segments can be described.
Dependencies:	-
Supporting Material:	_

]()

[RS_ECUR_00009] Available communication means \lceil

Type:	valid
Description:	The ECU Resource template shall provide dedicated means to describe communication hardware.
Rationale:	The communication of the ECU is essential and shall be described in a coordinated way together with the System Description and the ECU Configuration.



Use Case:	 Describe the network ports used for the System Description and the communication design between ECUs. Describe network ports which are not part of the System Description (local network ports to access intelligent sensors/actuators).
Dependencies:	_
Supporting Material:	_

[RS_ECUR_00010] Available IO HW-Peripherals [

Type:	valid
Description:	The ECU Resource template shall provide dedicated means to describe IO-HW-Peripherals.
Rationale:	The different IO-HW-Peripherals require dedicated means to describe their attributes from a hardware point of view. The different IO-HW-Peripherals require dedicated means to describe their connectivity in the micro controller and to the outside.
Use Case:	 ADC channel 5 is available on pin 87 of the micro controller. Variant Handling: If the micro controller is configured to have ADC channel 7 on pin 53, DIO can not use the pins 50-57 for its purposes.
Dependencies:	[RS_ECUR_00015]
Supporting Material:	_

]()

[RS_ECUR_00016] IO-HW-Abstraction specification [

Type:	valid
Description:	The ECU Resource template shall provide the abstract connection information between the hardware sensor / actuator and the IO-HW peripheral using the IO-HW-Abstraction layer.
Rationale:	For the configuration of the IO-HW-Peripherals it is essential to know which sensors / actuators are connected and how the IO-HW-Abstraction will access the corresponding IO-HW-Peripherals.

13 of 16



Use Case:	 Speed sensor is connected via complex electronics to the IO-Port of the ADC channel 7, micro-controller pin 53. The behavior of the complex electronics will not be described; however the connection itself shall be specified. Thus allowing the implementer of the IO-HW-Abstraction software to get the proper connection information. Transceiver electronics is connected to the Can-Bus, has a connection to the Can Communication Controller, connection to the DIO channel 8 (pin 47) in order to enable the communication and a connection to the DIO channel 5 (pin 87) in order to initiate wake-up.
Dependencies:	-
Supporting Material:	-

](RS_Main_00130, RS_Main_00160)

[RS_ECUR_00011] Available sensors and actuators

Type:	valid
Description:	The ECU Resource template shall provide dedicated means to describe sensors and actuators.
Rationale:	Allow to establish the relationship between Sensor/Actuator Software Components and the actual hardware elements.
Use Case:	 Describe the wheel speed sensor hardware and the corresponding Sensor Software Component. Describe the window lifter motor and the corresponding Actuator Software Component.
Dependencies:	-
Supporting Material:	[RS_Main_00160] AUTOSAR shall provide means to describe interfaces of the entire system [4]

10

4.3 Requirements on the ECU Resource template development

[RS_ECUR_00012] Development according to the AUTOSAR Generic Structure Template document \lceil

Туре:	valid
Description:	The UML representation of the ECU Resource template SHALL be developed according to the AUTOSAR Generic Structure Template.
Rationale:	The experience and tools already available for the AUTOSAR Metamodeling shall be reused.



Use Case:	The ECU Resource template is similar to other templates already done with the AUTOSAR Metamodeling Guide.
Dependencies:	_
Supporting Material:	AUTOSAR Generic Structure Template [7]

[RS_ECUR_00013] Transformation of ECU Resource template modeling according to the AUTOSAR Model Persistence Rules for XML \lceil

Туре:	valid
Description:	The XML representation for the ECU Resource template shall be derived from its UML representation according to the AUTOSAR Model Persistence Rules for XML.
Rationale:	The experience and tools already available for the AUTOSAR Modeling shall be reused.
Use Case:	The ECU Resource template is similar to other templates already done with the AUTOSAR Metamodeling Guide.
Dependencies:	-
Supporting Material:	Model Persistence Rules for XML [8]

]()



5 Change History

5.1 Change History for AUTOSAR 4.0.1 against 3.1.5

This document is new in AUTOSAR R4.0.1.

5.2 Change History for AUTOSAR 4.0.2 against 4.0.1

_

5.3 Change History for AUTOSAR 4.0.3 against 4.0.2

-

5.4 Change History for AUTOSAR 4.1.1 against 4.0.3

-

5.5 Change History for AUTOSAR 4.1.2 against 4.1.1

_

5.6 Change History for AUTOSAR 4.2.1 against 4.1.2

-

5.7 Change History for AUTOSAR 4.2.2 against 4.2.1

-