


	Requirements on Communication
Document Owner	AUTOSAR
Document Responsibility	AUTOSAR
<b>Document Identification No</b>	002
<b>Document Classification</b>	Auxiliary

Document Status	Final
Part of AUTOSAR Release	4.2.1

	Document Change History		
Release	Changed by	Change Description	
4.2.1	AUTOSAR Release Management	<ul> <li>added support for Large Data COM</li> <li>added support for Sender/ Receiver Serialization</li> <li>updated to support CAN FD</li> </ul>	
4.1.3	AUTOSAR Release Management	editorial changes	
4.1.1	AUTOSAR Administration	<ul><li>Formal updates</li><li>Updates with respect to the requirement tracing</li></ul>	
4.0.3	AUTOSAR Administration	<ul> <li>several minor changes and bug-fixes</li> <li>clarification and minor extensions of transmission mode usage and activation</li> <li>clarification and extension of transfer properties</li> <li>added retry mechanism for failed transmission requests</li> </ul>	
3.1.5	AUTOSAR Administration	<ul> <li>Added support for large data types</li> <li>Added support for communication protection</li> <li>Revised mode management interface</li> <li>Legal disclaimer revised</li> </ul>	
3.1.1	AUTOSAR Administration	Legal disclaimer revised	
3.0.1	AUTOSAR Administration	<ul><li>Document meta information extended</li><li>Small layout adaptations made</li></ul>	
2.1.15	AUTOSAR Administration	<ul> <li>updated signal group definition</li> <li>"Advice for users" revised</li> <li>"Revision Information" added</li> <li>Legal disclaimer revised</li> </ul>	
2.0	AUTOSAR Administration	<ul> <li>Requirements for Transmission Modes changed,</li> <li>nearly all requirements slightly changed</li> </ul>	
1.0	AUTOSAR Administration	Initial release	







#### **Disclaimer**

This specification and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the specification.

The material contained in this specification is protected by copyright and other types of Intellectual Property Rights. The commercial exploitation of the material contained in this specification requires a license to such Intellectual Property Rights.

This specification may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only.

For any other purpose, no part of the specification may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The AUTOSAR specifications have been developed for automotive applications only. They have neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

#### **Advice for users**

AUTOSAR specifications may contain exemplary items (exemplary reference models, "use cases", and/or references to exemplary technical solutions, devices, processes or software).

Any such exemplary items are contained in the specifications for illustration purposes only, and they themselves are not part of the AUTOSAR Standard. Neither their presence in such specifications, nor any later documentation of AUTOSAR conformance of products actually implementing such exemplary items, imply that intellectual property rights covering such exemplary items are licensed under the same rules as applicable to the AUTOSAR Standard.



### **Table of Contents**

1	Scope of Document	. 7
2	Acronyms and Abbreviations	. 8
3	Conventions to be used	. 9
	3.1 Requirement structure	. 9
4	Functional Overview	10
5	Requirement Specification	11
	5.1 Functional requirements applicable for AUTOSAR COM and	
	LargeDataCOM	
	5.1.1 Configuration	11
	configured by using XML as configuration language	11
	5.1.1.2 [SRS_Com_00177] AUTOSAR COM and LargeDataCOM shall support multiple configuration stages	11
	5.1.1.3 [SRS_Com_02067] AUTOSAR COM and LargeDataCOM shall	
	define rules for checking the consistency of configuration data	
	layer (PDU-Router)	
	5.1.2.1 [SRS_Com_02043] AUTOSAR COM and LargeDataCOM shall	40
	provide a receive indication function	12
	provide a transmit confirmation function	12
	5.1.2.3 [SRS_Com_02045] AUTOSAR COM and LargeDataCOM shall provide a function to request the transmit buffer data for lower layer triggered	ı
	transmission	13
	5.1.3 Support of Large Data Types	13
	5.1.3.1 [SRS_Com_02091] AUTOSAR COM and LargeDataCOM shall not support splitting of large signals into different I-PDUs	
	5.1.3.2 [SRS_Com_02094] Dynamic length signals must be of type UINT8[i	
	14	
	5.1.3.3 [SRS_Com_02095] AUTOSAR COM and LargeDataCOM shall use the TP to fragment and reassemble large signals	
	5.1.3.4 [SRS_Com_02097] AUTOSAR COM and LargeDataCOM shall	
	support dynamical signals with a static maximum length	
	5.2 AUTOSAR COM specific functional requirements	
	5.2.1.1 [SRS_Com_02037] AUTOSAR COM module shall be based on the	
	functionality and APIs of OSEK COM 3.0.3	15
	5.2.1.2 [SRS_Com_02078] The AUTOSAR COM module shall support endianness conversion	15
	5.2.1.3 [SRS_Com_02086] The AUTOSAR COM module shall support sign	1-
	extension	
	5.2.2.1 [SRS_Com_02042] The AUTOSAR COM module shall fill unused	10
	areas/ bits within an I-PDU with a configurable value	
	5.2.3 Signal and I-PDU Transmission	16



	5.2.3.1 [SRS_Com_02083] The AUTOSAR COM module shall support
	multiple transmission modes
	5.2.3.2 [SRS_Com_02082] The AUTOSAR COM module shall support
	defining two different transmission modes for each I-PDU
	5.2.3.3 [SRS_Com_02084] The AUTOSAR COM module shall support a
	configurable signal data based selection mechanism of the two transmission
	modes 17
	5.2.3.4 [SRS_Com_02113] AUTOSAR COM shall support signal data based
	transmission modes for configured serialized data
	5.2.3.5 [SRS_Com_02080] The AUTOSAR COM module shall cancel
	outstanding repetitions in case of a new send request
	5.2.3.6 [SRS_Com_02046] The AUTOSAR COM module shall support
	immediate and deferred signal based notification to the RTE
	5.2.3.7 [SRS_Com_02089] The AUTOSAR COM module shall provide two
	configurable options to handle signal timeouts
5.	2.4 Signal invalidation
-	5.2.4.1 [SRS_Com_02077] The AUTOSAR COM module shall support
	invalidation of signals at sender side
	5.2.4.2 [SRS_Com_02079] The AUTOSAR COM module shall support an
	optional notification when receiving invalidated data
	5.2.4.3 [SRS_Com_02087] The AUTOSAR COM module shall support an
	optional substitution of received invalidated data
	5.2.4.4 [SRS_Com_02088] The AUTOSAR COM module shall support
	substituting the last received value by the init value in case of a signal timeout
	20
5.	2.5 I-PDU Groups and Mode Changes
	5.2.5.1 [SRS_Com_02090] The AUTOSAR COM module shall define a data-
	structure allowing efficiently starting and stopping of I-PDU groups 20
	5.2.5.2 [SRS_Com_00218] The AUTOSAR COM module shall support
	starting and stopping multiple I-PDU groups during runtime
	5.2.5.3 [SRS_Com_00192] The AUTOSAR COM module shall support
	enabling and disabling reception deadline monitoring of I-PDU groups 21
5.	2.6 Packing signals into I-PDUs
	5.2.6.1 [SRS_Com_02041] The AUTOSAR module shall handle complex
	data types as a consistent set of data22
	5.2.6.2 [SRS_Com_02112] AUTOSAR COM shall provide a uint8-array
	based API for signal groups22
5.	2.7 Interface between the AUTOSAR COM module and the lower layer
(F	PDU-Router)
	5.2.7.1 [SRS_Com_02107] The AUTOSAR COM module shall cancel
	transmission requests in case of expired transmissions
5.	2.8 Support of Large Data Types
	5.2.8.1 [SRS_Com_02092] The AUTOSAR COM module shall support at
	most one dynamic length signal per I-PDU23
	5.2.8.2 [SRS_Com_02093] Dynamic length signal must be placed last in I-
	PDU 23
	5.2.8.3 [SRS_Com_02096] The AUTOSAR COM module shall not support
	fragmentation towards the RTE
	5.2.8.4 [SRS_Com_02098] The AUTOSAR COM module shall distinct
	normal and large signals via its configuration 24



	5.2.9 Signal status information	24
	5.2.9.1 [SRS_Com_02030] The AUTOSAR COM module shall support to	
	detect if a received signal or signal group was updated by the sender	24
	5.2.9.2 [SRS_Com_02058] The AUTOSAR COM module shall support	
	deadline monitoring for updated signals/signal groups on receiver side	25
	5.2.10 I-PDU Counter	
	5.2.10.1 [SRS_Com_02099] The AUTOSAR COM module shall provide a	
	mechanism to detect out of sequence received I-PDUs	25
	5.2.10.2 [SRS_Com_02100] The AUTOSAR COM module shall support	
	configuring the properties of the I-PDU Counter	
	5.2.10.3 [SRS_Com_02101] The AUTOSAR COM module shall support the	
	incrementing and checking of the I-PDU Counter	
	5.2.10.4 [SRS_Com_02102] The AUTOSAR COM module shall support the	
	detection of out of sequence I-PDUs	
	5.2.11 I-PDU replication	26
	5.2.11.1 [SRS_Com_02103] The AUTOSAR COM module shall provide a	
	mechanism to detect corrupted received I-PDUs and to recover from this	27
	failure mode	
	5.2.11.2 [SRS_Com_02104] The AUTOSAR COM module shall support the	
	configuration of I-PDU replication mechanism	
	transmission and reception of replicated I-PDUs	
	5.2.11.4 [SRS_Com_02106] The AUTOSAR COM module shall support the	
	detection of failures when receiving replicated I-PDUs	
	5.3 AUTOSAR LargeDataCOM specific functional requirements	
	5.3.1 [SRS_Com_02108] Support of Large Data COM	
	5.3.2 [SRS_Com_02109] Large Data COM shall support Transport Protoco	
	like communication	
	5.3.3 [SRS_Com_02110] Large Data COM shall support Interface-like	
	communication	29
	5.3.4 [SRS_Com_02111] Large Data COM shall support Transmission	
	Triggered by lower layer	29
	5.4 Non-Functional Requirements (Qualities)	29
6	References	30
	6.1 Deliverables of AUTOSAR	30
	6.2 OSEK	
	6.3 ISO	
	6.4 HIS	



### 1 Scope of Document

The following specification is to define the functional and non-functional requirements on the modules AUTOSAR COM and LargeDataCOM.

This Software Requirement Specification (SRS) of AUTOSAR COM is based on the OSEK<sup>1</sup> COM 3.0.3 specification [DOC\_OSEK\_COM] and only defines add-ons to this OSEK specification or different behavior.

The location of the AUTOSAR COM and LargeDataCOM modules within the whole AUTOSAR ECU SW Architecture is defined in [DOC\_LAYER].

The focus of this document is to specify:

- the behavior of the AUTOSAR COM and LargeDataCOM
- the interfaces of the AUTOSAR COM and LargeDataCOM
- · the input of the generator and its configuration input
- the rules to check the consistency of the configuration input

#### The focus is NOT to specify:

 The editor and the rule checker for the input of the AUTOSAR COM and LargeDataCOM modules implementation. However the rule checker must use the rules for the configuration in/out defined by [DOC\_SWS\_COM] and [DOC\_SWS\_LDCOM].

#### **Constraints**

First scope for specification of requirements on basic software modules is systems which are not safety relevant. For this reason safety requirements are assigned to medium priority.

\_

<sup>&</sup>lt;sup>1</sup> OSEK is a registered trademark of Siemens AG.



### 2 Acronyms and Abbreviations

AUTOSAR data	See 6.1, section 6.4
type	
I-PDU	Interaction Layer Protocol Data Unit (assembled and disassembled in AUTOSAR
	COM), consists of one or more signals (see below and [DOC_LAYER]).
I-PDU group	An I-PDU Group is an arbitrary collection of I-PDUs in COM
LOM	Listen Only Mode
L-PDU	Data Link Layer Protocol Data Unit (assembled and disassembled in AUTOSAR
	Hardware Abstraction layer, see [DOC_LAYER]).
signal	A signal in the AUTOSAR COM context is equal to a message in OSEK COM.
	An AUTOSAR signal is carried by one or more signals in COM. The transformation
	from an AUTOSAR signal to a signal in COM is carried out by the RTE. Typically
	the transformation preserves the syntax of the data. However, in the case of
	complex data types the transformation may change the syntax of the signal.
	Therefore a signal in AUTOSAR COM is not always the same as an AUTOSAR signal.
signal group	A signal group refers to a set of signals that must always be kept together in a common I-PDU.
	A Signal group is used to guarantee the consistent transfer of AUTOSAR
	composite data types.
	A signal group has the following properties:
	A signal can belong to at most one signal group
	<ul> <li>A signal group can not belong to more than exactly one I-PDU</li> </ul>
	Signal groups do not overlap each other within an I-PDU
	<ul> <li>Signal groups are a contiguous set of signals which belong to this group,</li> </ul>
	however it is possible to have unused bits ("holes") within a group.
	<ul> <li>Signal groups may contain no signals ("may be empty").</li> </ul>
	The grouping of signals to signal groups is assumed to be provided as an input for the COM generation process.



#### 3 Conventions to be used

- The representation of requirements in AUTOSAR documents follows the table specified in [TPS\_STDT\_00078].
- In requirements, the following specific semantics shall be used (based on the Internet Engineering Task Force IETF).

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as:

- SHALL: This word means that the definition is an absolute requirement of the specification.
- SHALL NOT: This phrase means that the definition is an absolute prohibition of the specification.
- MUST: This word means that the definition is an absolute requirement of the specification due to legal issues.
- MUST NOT: This phrase means that the definition is an absolute prohibition of the specification due to legal constraints.
- SHOULD: This word, or the adjective "RECOMMENDED", mean that there may exist valid reasons in particular circumstances to ignore a particular item, but the full implications must be understood and carefully weighed before choosing a different course.
- SHOULD NOT: This phrase, or the phrase "NOT RECOMMENDED" mean that there may exist valid reasons in particular circumstances when the particular behavior is acceptable or even useful, but the full implications should be understood and the case carefully weighed before implementing any behavior described with this label.
- MAY: This word, or the adjective "OPTIONAL", means that an item is truly optional. One vendor may choose to include the item because a particular marketplace requires it or because the vendor feels that it enhances the product while another vendor may omit the same item. An implementation, which does not include a particular option, MUST be prepared to interoperate with another implementation, which does include the option, though perhaps with reduced functionality. In the same vein an implementation, which does include a particular option, MUST be prepared to interoperate with another implementation, which does not include the option (except, of course, for the feature the option provides.)

### 3.1 Requirement structure

The requirement structure is defined in TPS\_StdT\_00077



#### 4 Functional Overview

The AUTOSAR COM and LargeDataCom are located between RTE and the PDU Router.

#### Main-Features of AUTOSAR COM are:

- provision of signal oriented data interface for the RTE
- communication transmission control (start/stop of I-PDU groups)
- sending of signals according to transmission type as specified in the VFB specification
- guarantee of minimum distances between transmission requests
- monitoring of receive signals (signals timeout)
- · monitoring of transmit confirmations
- filter mechanisms for incoming signals
- different notification mechanisms
- provision of initialization-values and update-Indications
- endianness conversion + sign extension
- packing and unpacking of AUTOSAR signals to I-PDUs to be transmitted
- supporting large and dynamical length data types
- supporting I-PDU counter and replication mechanisms

#### Main-Features of AUTOSAR LargeDataCOM are:

- provision of dedicated signal oriented data interface for the RTE
- support of large and dynamic signals
- supports just one signal per I-PDU
- supports just opaque byte arrays
- support of IF- and TP-communication



### 5 Requirement Specification

# 5.1 Functional requirements applicable for AUTOSAR COM and LargeDataCOM

#### 5.1.1 Configuration

The chapter Configuration deals with the configurable parameters/ functionalities of the AUTOSAR COM and LargeDataCOM.

This chapter deals only with general configuration requirements, the requirements for configuration of a single feature are defined within the requirement of the feature itself.

# 5.1.1.1 [SRS\_Com\_02040] AUTOSAR COM and LargeDataCOM shall be configured by using XML as configuration language

Type:	Valid
Description:	AUTOSAR COM and LargeDataCOM shall be configured by using XML as configuration language as defined by ECU Configuration Template. It is up to the [DOC_SWS_COM] and [DOC_SWS_LDCOM] to define the configuration parameters themselves.
Rationale:	Having a unique configuration language within AUTOSAR.
Use Case:	Configuration of AUTOSAR COM and LargeDataCOM
Dependencies:	
Supporting Material:	[DOC_ECUC]

(RS\_BRF\_01616,RS\_BRF\_01544)

# 5.1.1.2 [SRS\_Com\_00177] AUTOSAR COM and LargeDataCOM shall support multiple configuration stages

Туре:	valid
Description:	AUTOSAR COM and LargeDataCOM shall allow the configuration of communication at the following different stages:  • Pre-Compile-Time • Link Time • Post-build-Time • Load-able Configuration • Multiple configuration sets  The configuration parameters must be organized in a way to be able to be changed in all the different stages, e.g. one OEM might select to configure pre-compile time while another will configure post-build time.  The concrete set of parameters which are configurable in which state shall be defined in [DOC_SWS_COM].
Rationale:	Guarantee flexibility of using the AUTOSAR COM and LargeDataCOM.
Use Case:	It must be possible to configure the handled bus frames after compile- or build-time, particularly for future concepts running at BMW (reuse an ECU within another vehicle product line with different and incompatible communication layouts).
Dependencies:	
Supporting Material:	



| (RS\_BRF\_01544,RS\_BRF\_01120)

# 5.1.1.3 [SRS\_Com\_02067] AUTOSAR COM and LargeDataCOM shall define rules for checking the consistency of configuration data

Туре:	valid
Description:	A set of rules needs to be specified that enable the Configuration Editor to reject inconsistent configurations or configurations that cannot be implemented.  These rules shall be defined in the SWS and shall be implemented by the Configuration Editor.
Rationale:	Needed to make sure that the generator only works with correct configuration files.
Use Case:	The configuration must not contain overlapping signals within one I-PDU. The period of I-PDUs must not be negative.
Dependencies:	
Supporting Material:	

J (RS\_BRF\_01544)

# 5.1.2 Interface between AUTOSAR COM and LargeDataCOM and the lower layer (PDU-Router)

OSEK COM leaves the interface between COM and the lower layers undefined. In AUTOSAR the only lower layer that COM and LargeDataCOM interfaces to is the PDU Router. The interfaces refer to the definitions in [DOC\_COM\_TYPES]. The requirements are derived from [DOC\_COM\_TYPES].

### 5.1.2.1 [SRS\_Com\_02043] AUTOSAR COM and LargeDataCOM shall provide a receive indication function

Type:	Valid
Description:	AUTOSAR COM and LargeDataCOM shall provide a function that is called by the lower layer (PDU-Router) after an I-PDU has been received. The name of the function has to be Com_RxIndication for COM and LdCom_RxIndication for LargeDataCOM.
Rationale:	Basic functionality of a communication layer
Use Case:	Receiving a PDU by the lower layer
Dependencies:	
Supporting Material:	[DOC_COM_TYPES]

| (RS\_BRF\_01056,RS\_BRF\_01544)

### 5.1.2.2 [SRS\_Com\_02044] AUTOSAR COM and LargeDataCOM shall provide a transmit confirmation function

ſ



Туре:	valid
Description:	AUTOSAR COM and LargeDataCOM shall provide a function that is called by the lower layer (PDU-Router) after an I-PDU has been transmitted on the network.  The name of the function has to be Com_TxConfirmation for COM and LdCom_TxConfirmation for LargeDataCom.
Rationale:	Basic functionality of a communication layer
Use Case:	Transmitting a PDU on the network.
Dependencies:	
Supporting Material:	[DOC_COM_TYPES]

(RS\_BRF\_01544, RS\_BRF\_01072)

# 5.1.2.3 [SRS\_Com\_02045] AUTOSAR COM and LargeDataCOM shall provide a function to request the transmit buffer data for lower layer triggered transmission

Type:	Valid	
Description:	AUTOSAR COM and LargeDataCOM shall provide a function that is called by the lower layer (PDU-Router) when an I-PDU shall be transmitted. Within this function, AUTOSAR COM and LargeDataCOM shall copy the contents of its I-PDU transmit buffer to the L-PDU buffer given by the calling layer. The name of the function has to be Com_TriggerTransmit for COM and LdCom_TriggerTransmit for LargeDataCOM.	
Rationale:	Basic functionality of a communication layer	
Use Case:	This function is used e.g. by the LIN Master for sending out a LIN frame. In this case, the trigger transmit can be initiated by the Master schedule table it self or a received LIN header. This function is also used by the FlexRay Interface for requesting PDUs to be sent in the static part (synchronous to the FlexRay global time).	
Dependencies:		
Supporting Material:	[DOC_COM_TYPES]	

| (RS\_BRF\_01544)

#### 5.1.3 Support of Large Data Types

AUTOSAR COM and LargeDataCOM shall support signals larger than the N-PDUs of the underlying busses. For these large signals also a dynamic length shall be supported. The requirements of this chapter define the support of these data types.

## 5.1.3.1 [SRS\_Com\_02091] AUTOSAR COM and LargeDataCOM shall not support splitting of large signals into different I-PDUs

Туре:	Valid		
Description:	Large signals supported by AUTOSAR COM and LargeDataCOM shall never be split into different I-PDUs, but it shall be supported that an I-PDU can be split into different N-PDUs		
Rationale:	The I-PDU shall be transported by the TP. The TP will work on N-PDU level, and therefore can fragment the I-DPU into a number of N-PDUs		
Use Case:	There is no use-case to have fragmentation on I-PDU level.		
Dependencies:	SRS_Com_02092, SRS_Com_02093		
Supporting Material:			

| (RS\_BRF\_01648, RS\_BRF\_01568, RS\_BRF\_01544)



### 5.1.3.2 [SRS\_Com\_02094] Dynamic length signals must be of type UINT8[n]

Туре:	Valid	
Description:	AUTOSAR COM and LargeDataCOM shall only support dynamic length signals of type UINT8[n].	
Rationale:	It would be possible to also add support for bit length dynamical length signals, but this will introduce unnecessary complexity	
Use Case:	This restriction is made because actually there is no strong use-case that requires non byte-array data for large signals.	
Dependencies:	SRS_Com_02091, SRS_Com_02092, SRS_Com_02093	
Supporting Material:	[DOC_OSEK_GLOS]	

(RS\_BRF\_01648,RS\_BRF\_01544)

# 5.1.3.3 [SRS\_Com\_02095] AUTOSAR COM and LargeDataCOM shall use the TP to fragment and reassemble large signals

	3 3		
Type:	Valid		
Description:	All large signals must be transported using the TP. Note that large signals does not mean "normal signals" (e.g. UINT8[n] type).		
	Therefore AUTOSAR COM and LargeDataCOM shall route all large signals via the PduR to the underlying TPs using the PduR's TP-APIs.		
	Note: Signals with static length and equal or less length than 8 bytes are transported in L-PDUs on CAN and LIN. In case of CAN FD this range is extended up to 64 bytes. On FlexRay this is valid for signals with length equal to or less than 254 bytes. Also dynamic length signals may be transported without TP as long as the maximum length does not exceed the bus specific limits.		
Rationale:	There is no need to reinvent fragmentation since the existing TP modules already supports this.		
Use Case:	For CAN TP it is no problem to have multiple users (DCM and COM) of the TP.  On LIN TP there will be a problem sharing the TP since all TP communication is done through two specific (specified by LIN) frames. A workaround may be to use a specific NAD to differ between diagnostic communication and normal signal communication (containing large signal dynamic length signal).		
	For FlexRay TP it is no problem to have multiple users (DCM and COM) of the TP.		
Dependencies:	SRS_Com_02096		
Supporting Material:			

| (RS\_BRF\_01648,RS\_BRF\_01544)

# 5.1.3.4 [SRS\_Com\_02097] AUTOSAR COM and LargeDataCOM shall support dynamical signals with a static maximum length

Type:	Valid	
Description:	The maximum length of this type of signal must be set in the configuration	
Rationale:	If not given all dynamic length signals can only be considered to be maximum length supported by the used TP and therefore buffers cannot be handled efficient.	
Use Case:	If LIN is used and if not maximum length is given, it must be assumed that	



	the dynamical length signal is 4095 bytes.	
Dependencies:	SRS_Com_02098	
Supporting Material:		

| (RS\_BRF\_01648,RS\_BRF\_01544)

#### 5.2 AUTOSAR COM specific functional requirements

#### 5.2.1 General requirements

# 5.2.1.1 [SRS\_Com\_02037] AUTOSAR COM module shall be based on the functionality and APIs of OSEK COM 3.0.3

Туре:	Valid		
Description:	The AUTOSAR COM module shall be based on the functionality and APIs specified in OSEK COM 3.0.3. Specifications not done there, respectively specifications of functionality different from that specified in the above mentioned document shall be defined in the AUTOSAR COM SRS and SWS specifications.  Features of OSEK COM 3.0.3 which are not provided by the AUTOSAR COM module shall be defined in [DOC_SWS_COM].		
Rationale:	This SRS is only an add-on to OSEK COM 3.0.3 as an existing standard.		
Use Case:			
Dependencies:			
Supporting Material:	[DOC_OSEK_GLOS], [DOC_OSEK_COM]		

(RS\_BRF\_01544)

## 5.2.1.2 [SRS\_Com\_02078] The AUTOSAR COM module shall support endianness conversion

Туре:	Valid		
Description:	The AUTOSAR COM module shall support endianness conversion for the following data types defined in [DOC_SWS_RTE] Table "C/C++ mapping from primitive" AUTOSAR data-types" uint16 uint32 sint16 sint32 float32 float64		
Rationale:	ensure end to end data consistency		
Use Case:			
Dependencies:			
Supporting Material:	[DOC_TPS_SWC] (Chapter 6.1), [DOC_SWS_RTE] (Chapter 6.1)		

J (RS\_BRF\_01624)

## 5.2.1.3 [SRS\_Com\_02086] The AUTOSAR COM module shall support sign-extension

Type:	Valid	
Description:	Sign-Extension means, to map negative values of signed signals correctly, if the bit-size of the signal in an I-PDU received and the bit-size of the signal used in the interface of the receiving software component differ from each other. In this case, the size of the signal received shall be extended to the size of the receiver interface.	



	The AUTOSAR COM module shall support Sign-Extension for the following data types defined in [DOC_SWS_RTE] Table "C/C++ mapping from primitive": sint8 sint16 sint32	
Rationale:	ensure end to end data consistency	
Use Case:		
Dependencies:		
Supporting Material:	[DOC_TPS_SWC] (Chapter 6.1), [DOC_SWS_RTE] (Chapter 6.1)	

(RS\_BRF\_01624)

#### 5.2.2 Initialization

# 5.2.2.1 [SRS\_Com\_02042] The AUTOSAR COM module shall fill unused areas/bits within an I-PDU with a configurable value

Type:	Valid		
Description:	The AUTOSAR COM module shall fill unused areas/ bits within an I-PDU with a configurable value (e.g. 0xFF). This value shall be configurable per I-PDU.		
Rationale:	Limit impact of a wrong configuration, if a not used area of an I-PDU is wrongly assigned to a signal this can be detected by the application SW component.		
Use Case:	For error detection purposes, all data values must be filled with a defined value.		
Dependencies:			
Supporting Material:			

] (RS\_BRF\_01616,RS\_BRF\_01544)

#### 5.2.3 Signal and I-PDU Transmission

This chapter deals with the add-ons to the OSEK COM specification related to signal and I-PDU transmission.

## 5.2.3.1 [SRS\_Com\_02083] The AUTOSAR COM module shall support multiple transmission modes

Туре:	Valid	Valid	
Description:	the following tabula	OM module shall provide the transmission modes given in ar for each I-PDU. It shows the transmission modes ort description of those transmission modes.	
	Transmission Modes	Description	
	Periodic	Transmissions occur indefinitely with a fixed period between them.	
	Direct / n-times	Event driven transmission with n-1 repetitions	
	Mixed	Periodic transmission with direct/n-times transmissions in between	
	None	No transmission	
Rationale:	These modes are	These modes are commonly used by all existing automotive bus systems.	
Use Case:			



Dependencies:	[SRS_Com_02082], [SRS_Com_02084], [SRS_Com_02080]
	Transmission modes "periodic", "mixed" are the same as already defined in [DOC_OSEK_COM]. See also Use Cases in [DOC_OSEK_GLOS].

(RS\_BRF\_01592,RS\_BRF\_01544)

## 5.2.3.2 [SRS\_Com\_02082] The AUTOSAR COM module shall support defining two different transmission modes for each I-PDU

Type:	Valid
Description:	The AUTOSAR COM module shall provide the possibility to define two different transmission modes for each I-PDU. This shall also include the situation where only the parameters of a transmission mode are changed, e.g. different cycle times.  It shall be possible to switch between both Transmission Modes during runtime.
Rationale:	This is commonly used by many existing automotive bus systems.
Use Case:	
Dependencies:	SRS_Com_02083, SRS_Com_02084, SRS_Com_02080
Supporting Material:	

[(RS\_BRF\_01544, RS\_BRF\_01592)

# 5.2.3.3 [SRS\_Com\_02084] The AUTOSAR COM module shall support a configurable signal data based selection mechanism of the two transmission modes

Туре:	Valid
Description:	To select one of the two transmission modes, the AUTOSAR COM module shall provide the possibility to attach a condition to each signal within an I-PDU separately. The possibilities to define those conditions shall be the same as defined in [DOC_OSEK_COM] reception filter algorithms (see [DOC_OSEK_GLOS], Section 2.2.2).  If all conditions defined for signals within one specific I-PDU evaluate to TRUE, one transmission mode shall be used for this I-PDU. In all other cases, the other transmission mode shall be used.
	The conditions shall be evaluated immediately every time a related signal or signal group is sent by RTE and the new transmission request shall be sent using the new transmission mode already.
Rationale:	These modes are commonly used by many existing automotive bus systems.
Use Case:	
Dependencies:	SRS_Com_02082, SRS_Com_02083, SRS_Com_02080
Supporting Material:	

| (RS\_BRF\_01592, RS\_BRF\_01544)

# 5.2.3.4 [SRS\_Com\_02113] AUTOSAR COM shall support signal data based transmission modes for configured serialized data

Type:	valid
Description:	The functionality of signal data based selection mechanism of the two transmission modes (see SRS_Com_02084) shall also be available when the data is provided via the uint8-array based API (see SRS_Com_02112).



Rationale:	When the serialization of the data is done outside of the Com module and the uint8-array representation is passed to Com the transmission modes need to be selected as well.
Use Case:	Usage of transformer with Com-based serialization and Com Interaction to enable the communication with a fixed communication matrix.
Dependencies:	SRS_Com_02082, SRS_Com_02083, SRS_Com_02084, SRS_Com_02112
Supporting Material:	

J (RS\_BRF\_01544, RS\_BRF\_01560, RS\_BRF\_01592, RS\_BRF\_01632)

# 5.2.3.5 [SRS\_Com\_02080] The AUTOSAR COM module shall cancel outstanding repetitions in case of a new send request

Туре:	Valid
Description:	A new send request called while existing repetitions are in progress shall cancel those outstanding repetitions and the transmission shall be started with the new signal/signal group.
Rationale:	These modes are commonly used by many existing automotive bus systems.
Use Case:	
Dependencies:	SRS_Com_02082, SRS_Com_02083, SRS_Com_02084
Supporting Material:	

(RS\_BRF\_01544)

# 5.2.3.6 [SRS\_Com\_02046] The AUTOSAR COM module shall support immediate and deferred signal based notification to the RTE

Type:	Valid
Description:	It shall be configurable whether the signal based notification to the RTE is done either immediately within the I-PDU RxIndication/ TxConfirmation made by the PduRouter or is deferred to the COM main function context.
Rationale:	To allow unpacking of signals in interrupt and polled modes
Use Case:	Unpacking of signals out of an I-PDU
Dependencies:	
Supporting Material:	UML diagram:
	- Polling Mode only in Com (R3b-R1a-R1a) and
	- Interrupt mode (R1b-R1a-R1a)
	(For decryption of the codes in brackets refer to UML Model)

J (RS\_BRF\_01544)

# 5.2.3.7 [SRS\_Com\_02089] The AUTOSAR COM module shall provide two configurable options to handle signal timeouts

Type:	Valid
Description:	Receiver-side the AUTOSAR COM module shall provide two (configurable) options if a signal timeout is detected  • Indication to the RTE → AUTOSAR Software Component can use "spare values"  • No indication to the RTE
Rationale:	The RTE shall have the opportunity to notify its environment about timeouts or the application shall be provided with a default value to avoid using outdated values.
Use Case:	see rationale
Dependencies:	



Supporting Material:
----------------------

(RS\_BRF\_01600)

#### 5.2.4 Signal invalidation

# 5.2.4.1 [SRS\_Com\_02077] The AUTOSAR COM module shall support invalidation of signals at sender side

Type:	Valid
Description:	It shall be possible for the sender side RTE to indicate that it is not able to provide a valid value (e.g. sensor is faulty).  This shall be done by writing a per signal configurable invalid value (outside of the range of the valid values) into the I-PDU which is handled like a valid value in the further processing.  Therefore a special API shall be provided on the sender side AUTOSAR COM module.
Rationale:	The AUTOSAR Software Component shall have (via the RTE) the opportunity to notify its environment about reduced functionality (e.g. sensor is faulty)
Use Case:	See rationale, Starting a fail-safe routine if a sensor is broken.
Dependencies:	SRS_Com_02079
Supporting Material:	

(RS\_BRF\_01544)

# 5.2.4.2 [SRS\_Com\_02079] The AUTOSAR COM module shall support an optional notification when receiving invalidated data

Туре:	Valid
Description:	Receiver-side the AUTOSAR COM module shall provide two (configurable) options if a sender indicates that it is not able to provide a valid value  • Indication to the RTE → AUTOSAR Software Component can use "spare values"  • No indication to the RTE
Rationale:	The RTE shall have the opportunity to notify its environment about reduced functionality (e.g. sensor is faulty)
Use Case:	See rationale, Starting a fail-safe routine if a sensor is broken.
Dependencies:	SRS_Com_02077, SRS_Com_02087
Supporting Material:	

| (RS\_BRF\_01544)

# 5.2.4.3 [SRS\_Com\_02087] The AUTOSAR COM module shall support an optional substitution of received invalidated data

.	
Туре:	Valid
Description:	In case a signal is invalidated on sender-side and the receiver-side is configured in that way, that no indication is given to the upper layer, the AUTOSAR COM module shall substitute the invalid value by the init value. Whether this substitution takes place shall be configurable.
Rationale:	It shall be possible to provide the application with a configurable value in case the signal value received is invalid and no indication is given up to the upper layer.
Use Case:	See rationale



Dependencies:	SRS_Com_02077, SRS_Com_02079
Supporting Material:	

| (RS\_BRF\_01544)

# 5.2.4.4 [SRS\_Com\_02088] The AUTOSAR COM module shall support substituting the last received value by the init value in case of a signal timeout

Type:	Valid
Description:	In case a signal timeout is configured in that way, that no indication is given to the upper layer, the AUTOSAR COM module shall substitute the last received value by the init value. Whether this substitution takes place shall be configurable.
Rationale:	It shall be possible to provide the application with a configurable value in case of a signal timeout and no indication is given up to the upper layer.
Use Case:	see rationale
Dependencies:	
Supporting Material:	

J (RS\_BRF\_01600)

г

#### 5.2.5 I-PDU Groups and Mode Changes

This chapter collects the requirements for the definition and starting/ stopping of I-PDU groups.

#### 5.2.5.1 [SRS\_Com\_02090] The AUTOSAR COM module shall define a datastructure allowing efficiently starting and stopping of I-PDU groups

_	
Туре:	Valid
Description:	The AUTOSAR COM module shall define a data-structure that allows efficiently
	<ul> <li>starting and stopping of transmission and reception of multiple I-PDU groups</li> </ul>
	enabling or disabling the reception deadline monitoring of multiple     I-PDU groups
	The maximum number of I-PDU groups within one ECU shall be compile time configurable.
	Conceptually and per configuration it shall be allowed that one I-PDU group contains arbitrary other I-PDU groups.
Rationale:	To allow efficient mode changes, especially with respect to the AMM/ VMM concept, it is required to change the state of multiple I-PDU groups within one function call to the AUTOSAR COM module.
	The arbitrary nesting of I-PDU groups is no problem, since this can be
	resolved by the configuration tool, thus that each I-PDU only has to store an I-PDU group vector that declares to which I-PDU group it belongs.
Use Case:	AMM/ VMM
Dependencies:	SRS_Com_00218, SRS_Com_00192
Supporting Material:	

J (RS\_BRF\_01544)



# 5.2.5.2 [SRS\_Com\_00218] The AUTOSAR COM module shall support starting and stopping multiple I-PDU groups during runtime

_[	
Type:	Valid
Description:	The AUTOSAR COM module shall be able to start and to stop sending and receiving for multiple I-PDU groups during runtime.
	The corresponding API to this service shall take an I-PDU group vector reflecting the new state as input parameter.
	The minimum delay time and deadline monitoring shall be respected for started groups of I-PDUs. It shall be parameter driver if the corresponding timers of the I-PDUs shall be reset or not.
	After a reset of the AUTOSAR COM module (normally reset of the ECU) all I-PDUs are stopped per default.
Rationale:	OSEK COM can only start/ stop communication (StartCOM and StopCOM services) as a whole. Such a limitation is too restrictive.
Use Case:	Such configurable groups of I-PDUs provide for example the possibility to disable the transmission of all I-PDUs on a single channel, and enable only their reception (Silent Mode).  Such configurable groups of I-PDUs provide for example the possibility to start/ stop communication per logical channel of a single channel (e.g. FlexRay applications).  Start sending and receiving on the body domain (e.g. use of the radio and
	multi-function screen), while powertrain is not still powered on.  Stop the transmission of I-PDUs but not the reception when bus load is too high.  This feature is also needed for Bus Off handling.
Dependencies:	SRS_Com_00192, SRS_Com_02090
Supporting Material:	
1/DO DDE 04544)	

| (RS\_BRF\_01544)

Г

# 5.2.5.3 [SRS\_Com\_00192] The AUTOSAR COM module shall support enabling and disabling reception deadline monitoring of I-PDU groups

Type:	Valid
Description:	The AUTOSAR COM module shall provide the functionality to enable and disable reception deadline monitoring for multiple configurable I-PDU groups.
	The corresponding API to this service shall take an I-PDU group vector reflecting the new state as input parameter.
	After a reset of the AUTOSAR COM module (normally reset of the ECU), the configured state (enabled/ disabled) shall be active.
Rationale:	This is needed to suppress wrong error handling in Listen Only Mode (LOM, see use case). It is assumed that at least a second ECU on the same channel is also in LOM and does not provide the expected signals to the first one.
Use Case:	For the LOM the transmission of all I-PDU groups is switched off, reception (maybe of only one I-PDU group) is still active but without supervision of the reception timeouts (reception deadline monitoring).  For example all ECUs on one channel (e.g. on CAN network) are in LOM, so there are no more periodic send signals on this channel, but the ECU has to be able to receive changes of the ECU state management.
Dependencies:	SRS_Com_00218, SRS_Com_02090



Supporting Material:	

(RS\_BRF\_01544)

#### 5.2.6 Packing signals into I-PDUs

## 5.2.6.1 [SRS\_Com\_02041] The AUTOSAR module shall handle complex data types as a consistent set of data

Type:	Valid
Description:	It is required by AUTOSAR to handle complex data types as a consistent set of data. Therefore, it is necessary to pass the data elements from the RTE to the AUTOSAR COM module consistently.
Rationale:	AUTOSAR provides complex data types; those have to be sent and received atomically via RTE, COM, etc.
Use Case:	Complex AUTOSAR data types, data consistency of signal groups.
Dependencies:	
Supporting Material:	For guarantee data consistency of complex AUTOSAR data types, signal groups are introduced. For definition of signal group see [DOC_TR_GLOS].

[(RS\_BRF\_01632,RS\_BRF\_01544)

# 5.2.6.2 [SRS\_Com\_02112] AUTOSAR COM shall provide a uint8-array based API for signal groups

Type:	valid
Description:	AUTOSAR COM shall provide an API to pass the serialized uint8-array representation of a signal group to COM.
Rationale:	The AUTOSAR transformer chain provides means to serialize composite data into a uint8-array representation. This serialized uint8-array shall be passed as one entity to COM.
Use Case:	Usage of transformer with Com-based serialization and Com Interaction to enable the communication with a fixed communication matrix.
Dependencies:	SRS_Com_02082, SRS_Com_02083, SRS_Com_02084, SRS_Com_02113
Supporting Material:	

(RS\_BRF\_01632, RS\_BRF\_01544, RS\_BRF\_01560)

# 5.2.7 Interface between the AUTOSAR COM module and the lower layer (PDU-Router)

OSEK COM leaves the interface between COM and the lower layers undefined. In AUTOSAR the only lower layer that AUTOSAR COM module interfaces is the PDU Router. The interfaces refer to the definitions in [DOC\_COM\_TYPES]. The requirements are derived from [DOC\_COM\_TYPES].

# 5.2.7.1 [SRS\_Com\_02107] The AUTOSAR COM module shall cancel transmission requests in case of expired transmissions

Type:	Valid
Description:	The AUTOSAR COM module shall cancel the transmission request of an I-PDU in case a violation of the transmission deadline monitoring of an I-PDU is detected.
Rationale:	Needed to free buffers in the FlexRay interface.
Use Case:	Cancellation of outdated I-PDU



Dependencies:	RS_BRF_00303 see [DOC_RS_Features]
Supporting Material:	

| (RS\_BRF\_01544)

#### 5.2.8 Support of Large Data Types

The AUTOSAR COM module shall support signals larger than the N-PDUs of the underlying busses. For these large signals also a dynamic length shall be supported. The requirements of this chapter define the support of these data types.

# 5.2.8.1 [SRS\_Com\_02092] The AUTOSAR COM module shall support at most one dynamic length signal per I-PDU

Туре:	Valid
Description:	At most one dynamic length signal shall be supported per I-PDU.
Rationale:	If only one signal per I-PDU is allowed then the dynamical length does not have to be coded into the I-PDU. The receiver will calculate the length of the signal from the length of the IPDU. This is the same approach as in [DOC_OSEK_GLOS].
Use Case:	Sending textual messages e.g. SMS.
Dependencies:	SRS_Com_02091, SRS_Com_02093
Supporting Material:	[DOC_OSEK_GLOS]

| (RS\_BRF\_01648,RS\_BRF\_01544)

#### 5.2.8.2 [SRS\_Com\_02093] Dynamic length signal must be placed last in I-PDU

Type:	Valid
Description:	The dynamic length signal must be placed last in the dynamic length I-PDU. This is the same approach as in [DOC_OSEK_GLOS].  All other signals and update-bits must be packed in front of the dynamical length signal.
Rationale:	Placing the signal last in the frame removes the need of coding the dynamical length into the IPDU. The receiving COM can directly derive the length of the dynamic length signal from the length of the IPDU  Signal groups may still be used to contain (one) dynamic length signal and other signals.
Use Case:	see Rationale
Dependencies:	SRS_Com_02091, SRS_Com_02092
Supporting Material:	[DOC_OSEK_GLOS]

(RS\_BRF\_01648,RS\_BRF\_01544)

# 5.2.8.3 [SRS\_Com\_02096] The AUTOSAR COM module shall not support fragmentation towards the RTE

Type:	Valid
Description:	The AUTOSAR COM module will always send and receive a complete signal (no fragmentation supported above TP).  The COM/RTE/application will always receive/transmit complete large
	signals and dynamic length signals. Modules above TP are not involved in the fragmentation process.



Rationale:	Fragmentation should be hidden in the BSW architecture and should not be put to the application
Use Case:	It was discussed to have fragmentation for transmit/receive on application level to be able to find a more efficient implementation. This was however not approved since it would make the port-concept complex and bus-aware (it is not required for intra-ECU communication)
Dependencies:	SRS_Com_02095
Supporting Material:	

(RS\_BRF\_01648,RS\_BRF\_01544)

# 5.2.8.4 [SRS\_Com\_02098] The AUTOSAR COM module shall distinct normal and large signals via its configuration

Type:	Valid
Description:	There must be a configuration parameter that states if the signal has dynamic length or predefined length (i.e. a "normal" signal or a large signal)
Rationale:	There is no use-case where a fixed length signal becomes a dynamic length signal in run-time
Use Case:	see Rationale
Dependencies:	SRS_Com_02097
Supporting Material:	

(RS\_BRF\_01648,RS\_BRF\_01544)

#### 5.2.9 Signal status information

# 5.2.9.1 [SRS\_Com\_02030] The AUTOSAR COM module shall support to detect if a received signal or signal group was updated by the sender

Туре:	Valid
Description:	It shall be possible for the receiver to identify and indicate to the upper layer if a signal/ signal group has been up dated by the sender. Whether this feature is provided shall be configurable per signal.
Rationale:	When multiple signals /signal groups are placed in the same I-PDU, and that I-PDU is sent more frequently than a signal/ signal group is update, the update bit provides a mechanism to detect only those signals/ signal groups that have changed values.
Use Case:	-
Dependencies:	SRS_Com_02058
Supporting Material:	Implementation proposal: An update bit is optionally attached to a signal/ signal group and can only be attached at configuration time.  When COM is started all up date bits in all I-PDUs are cleared.  In the sending ECU, when a signal/ signal group is sent by the application, the update bit is set automatically by COM as part of the SendMessage() call.  In the sending ECU, once the call to the lower layers to transmit the ECU has completed, all update bits in the recently sent I-PDU are cleared.  In the receiving ECU, when an I-PDU is received, a signal/signal group with an associated update bit is only processed by COM if its update bit is set.  Therefore filtering and informing the RTE etc. will only take place if the update bit is set.  In the receiving ECU, for a signal/signal group with an update bit, the reception deadline monitor for that signal/signal group (if configured) is only



reset if the update bit is set. Update bits do not have to reside in the I-PDU in a fixed relationship to the signal/signal group with which they are associated. The update bits could reside anywhere in the I-PDU subject to the same restrictions as any other
signal/signal group.

(RS\_BRF\_01544)

# 5.2.9.2 [SRS\_Com\_02058] The AUTOSAR COM module shall support deadline monitoring for updated signals/signal groups on receiver side

Туре:	valid
Description:	The AUTOSAR COM module shall monitor on receiver-side, if an updated value for a specific signal/signal group has been received within a configurable, signal/signal group specific deadline, i.e. the AUTOSAR COM module shall check, whether the sender-side upper layers have explicitly sent the signal/signal group.  If a deadline violation of a specific signal/signal group is detected, the AUTOSAR COM module shall notify the upper receiving layers (the SWC via the RTE) about that fact. This information given to the upper receiving layers shall be signal/signal group specific.  The AUTOSAR COM module shall not do any substitution of signal/signal group values. If upper layers read signals/signal groups that have violated their deadline, the AUTOSAR COM module shall return the last value received.
Rationale:	Due to latency times of communication systems or interrupts data might be not received in a pre-defined time (e.g. jitter of period to big, older than max age).
Use Case:	Detect delays in communication system to make sure the application works on up-to-date data.
Dependencies:	SRS_Com_02030
Supporting Material:	If no update bits are used, the AUTOSAR COM module provides the deadline monitoring defined in [DOC_OSEK_COM] (Section 2.5.1). Here, deadline monitoring is done on the reception of I-PDUs but deadline violations are notified per signal to the upper layer.

(RS\_BRF\_01544)

#### 5.2.10 I-PDU Counter

# 5.2.10.1 [SRS\_Com\_02099] The AUTOSAR COM module shall provide a mechanism to detect out of sequence received I-PDUs

Type:	Valid
Description:	The AUTOSAR COM module shall provide a mechanism to detect out of sequence received I-PDUs. This mechanism shall be a configurable option of the AUTOSAR COM module.
Rationale:	Out of sequence I-PDUs is a communication failure mode which is not already covered by existing mechanisms.
Use Case:	Detection of communication failure modes is needed for safety-related applications.  The order I-PDUs are sent is important e.g. ordered information that logically is one unit but does not have to, or cannot, be transferred atomically.
Dependencies:	
Supporting Material:	-

| (RS\_BRF\_01544)



# 5.2.10.2 [SRS\_Com\_02100] The AUTOSAR COM module shall support configuring the properties of the I-PDU Counter

Type:	valid
Description:	<ul> <li>It shall be possible to configure:</li> <li>If I-PDU Counter mechanism is enabled or not</li> <li>The I-PDUs to include I-PDU Counter,</li> <li>The properties of the included I-PDU Counter (number of bits and position in I-PDU)</li> </ul>
Rationale:	Configuration is needed so that the mechanism can be adapted to the I-PDU content and characteristics of the physical link.
Use Case:	Configuration of communication of safety related information when including I-PDU Counter.
Dependencies:	
Supporting Material:	

(RS\_BRF\_01544)

# 5.2.10.3 [SRS\_Com\_02101] The AUTOSAR COM module shall support the incrementing and checking of the I-PDU Counter

Type:	valid
Description:	The I-PDU Counter shall be a counter that is stored in the I-PDU and incremented at each I-PDU transmission. The I-PDU Counter mechanism shall perform a check for correct I-PDU Counter of received I-PDUs. The I-PDU Counter shall be set up by the I-PDU transmitter and checked by the I-PDU receiver.
Rationale:	Including an I-PDU Counter in an I-PDU makes it possible to keep track of received I-PDUS i.e. that they arrive in the expected order and are not repeated. This will improve error detection capability.
Use Case:	Normal operation for communication of safety related information when including I-PDU Counter.
Dependencies:	
Supporting Material:	

(RS\_BRF\_01544)

# 5.2.10.4 [SRS\_Com\_02102] The AUTOSAR COM module shall support the detection of out of sequence I-PDUs

Туре:	valid
Description:	Detected out of sequence I-PDUs shall be discarded.
Rationale:	The I-PDU Counter shall be able to detect the following failure modes related to communication (where one I-PDU is related to one frame):  one repeated I-PDU one spurious I-PDU
Use Case:	Error handling for communication of safety related information when including I-PDU Counter.
Dependencies:	
Supporting Material:	

J (RS\_BRF\_01544)

#### 5.2.11 I-PDU replication



# 5.2.11.1 [SRS\_Com\_02103] The AUTOSAR COM module shall provide a mechanism to detect corrupted received I-PDUs and to recover from this failure mode

Type:	Valid
Description:	The AUTOSAR COM module shall provide a mechanism to detect corrupted received I-PDUs and to recover from this failure mode. This mechanism shall be a configurable option of the AUTOSAR COM module.
Rationale:	Corrupted and repeated I-PDUs are communication failure modes which are not already covered by existing mechanisms.
Use Case:	Detection of communication failure modes is needed for safety-related applications. It is important not to repeat an I-PDU e.g. an event in I-PDU causing a state transition.
Dependencies:	
Supporting Material:	

(RS\_BRF\_01544)

Γ

Γ

# 5.2.11.2 [SRS\_Com\_02104] The AUTOSAR COM module shall support the configuration of I-PDU replication mechanism

<u>-                                    </u>	
Туре:	Valid
Description:	<ul> <li>It shall be possible to configure:</li> <li>If I-PDU Replication mechanism is enabled or not</li> <li>The I-PDUs to replicate,</li> <li>The number of replicas per I-PDU</li> <li>The voting properties (K out of N)</li> <li>The properties of the included I-PDU counter (number of bits and position in I-PDU)</li> <li>Details about the supported replication mechanisms, that is the supported K and N shall be defined in [DOC_SWS_COM].</li> </ul>
Rationale:	Configuration is needed per I-PDU so that the mechanism can be adapted to the I-PDU content, I-PDU period and characteristics of the physical link.
Use Case:	Communication of safety related information where existing communication does not provide adequate integrity.
Dependencies:	
Supporting Material:	

J (RS\_BRF\_01544)

# 5.2.11.3 [SRS\_Com\_02105] The AUTOSAR COM module shall support transmission and reception of replicated I-PDUs

_	
Туре:	Valid
Description:	The I-PDU Replication mechanism shall, on the transmitting side, replicate a set of I-PDUs, which are statically defined to be replicated, into several (N) I-PDU instances with different I-PDU IDs and communicate them on the bus.
	The I-PDU Replication mechanism shall, on the receiving side, receive replicated I-PDU instances, evaluate and reconstruct the original I-PDU using voting.



	The I-PDU Replication mechanism shall include an I-PDU counter mechanism and use it to synchronize the voting and to detect repeated, spurious and missing replicas.
Rationale:	The I-PDU Replication mechanism is needed in order to support that periodic safety related signals can be packed into an I-PDU and communicated with increased protection against communication errors.
Use Case:	Communication of safety related information where existing communication does not provide adequate integrity.
Dependencies:	
Supporting Material:	

(RS\_BRF\_01544)

# 5.2.11.4 [SRS\_Com\_02106] The AUTOSAR COM module shall support the detection of failures when receiving replicated I-PDUs

_	
Type:	Valid
Description:	The I-PDU Replication shall be able to detect the following failure modes related to communication (where one I-PDU is related to one frame):
	loss of all I-PDUs with a specific ID
	one repeated I-PDU
	one spurious I-PDU
	one corrupted I-PDU
	Detected errors shall be corrected if possible e.g. using voting.
Rationale:	The I-PDU Replication is required as a complement to existing mechanisms in order to detect and if possible recover from a set of failure modes.
Use Case:	Communication of safety related information where existing communication do not provide adequate integrity.
Dependencies:	
Supporting Material:	

| (RS\_BRF\_01544)

### 5.3 AUTOSAR LargeDataCOM specific functional requirements

#### 5.3.1 [SRS\_Com\_02108] Support of Large Data COM

<u>. l</u>	
Type:	Valid
Description:	In addition to AUTOSAR COM Module AUTOSAR shall offer a Module called Large Data COM (LargeDataCOM). LargeDataCOM shall provide support of a reduced set of features targeting communication of large and dynamic data in a mainly event oriented way.  It shall be possible to omit either one of the COM and LargeDataCOM modules if not needed.
Rationale:	Efficiently support large and dynamic data.
Use Case:	Communication of data produced by serializers/ transformers like for example Some/IP.
Dependencies:	
Supporting Material:	

J(RS\_BRF\_01649)

# 5.3.2 [SRS\_Com\_02109] Large Data COM shall support Transport Protocol-like communication



Type:	Valid
Description:	Large Data COM shall support reception/ transmission via TP-APIs
Rationale:	Support of communication via transport protocols.
Use Case:	Efficient communication via e.g. FrTp. Efficient communication of very large data not fitting in an Ethernet frame using TCP.
Dependencies:	
Supporting Material:	

] (RS\_BRF\_01649)

Γ

## 5.3.3 [SRS\_Com\_02110] Large Data COM shall support Interface-like communication

Туре:	Valid
Description:	Large Data COM shall support reception/ transmission via If-APIs
Rationale:	Support of communication without transport protocols.
Use Case:	Efficient communication of long signals, still fitting into one frame of the according target bus. For example a 500 byte signal via SoAd.
Dependencies:	
Supporting Material:	

(RS\_BRF\_01649)

# 5.3.4 [SRS\_Com\_02111] Large Data COM shall support Transmission Triggered by lower layer

Type:	Valid
Description:	Large Data COM shall support Transmission being Triggered by lower layer
Rationale:	Support of TriggerTransmit API.
Use Case:	Provide current signal data to a new subscriber without waiting for the next transmission request of the application
Dependencies:	
Supporting Material:	

| (RS\_BRF\_01649)

### 5.4 Non-Functional Requirements (Qualities)

None



#### 6 References

#### 6.1 Deliverables of AUTOSAR

#### [DOC LAYER]

Layered Sofware Architecture AUTOSAR\_EXP\_LayeredSoftwareArchitecture.pdf

#### [DOC\_COM\_TYPES]

Specification of Communication Stack Types AUTOSAR\_SWS\_CommunicationStackTypes.pdf

#### [DOC\_VFB]

Specification of the Virtual Functional Bus AUTOSAR\_EXP\_VFB.pdf

#### [DOC\_ECUC]

Specification of ECU Configuration AUTOSAR\_TPS\_ECUConfiguration.pdf

#### [DOC\_SWS\_RTE]

Specification of RTE Software AUTOSAR\_SWS\_RTE.pdf

#### [DOC\_SWS\_COM]

Specification of Communication AUTOSAR\_SWS\_COM.pdf

#### [DOC\_SWS\_LDCOM]

Specification of Large Data COM AUTOSAR\_SWS\_LargeDataCOM.pdf

#### [DOC\_TR\_GLOS]

Glossary

AUTOSAR\_TR\_Glossary.pdf

#### [DOC\_TPS\_SWC]

Software Component Template

AUTOSAR\_TPS\_SoftwareComponentTemplate.pdf

#### [DOC RS Features]

Requirements on AUTOSAR Features AUTOSAR\_RS\_Features.pdf

#### [TPS\_STDT]

Standardization Template AUTOSAR\_TPS\_StandardizationTemplate.pdf



#### **6.2 OSEK**

[DOC\_OSEK\_GLOS]
Glossary OSEK/VDX Communication Version 3.0.3 July 20, 2004

[DOC\_OSEK\_COM]
OSEK/VDX Communication Version 3.0.3 July 20, 2004

#### 6.3 ISO

No references at the moment

#### 6.4 HIS

[DOC\_HIS]

Requirements for Protected Applications under OSEK, Version 1, 25.09.2002