

Document Title	Requirements on Module XCP
Document Owner	AUTOSAR
Document Responsibility	AUTOSAR
Document Identification No	429
Document Classification	Auxiliary
Document Status	Final
Part of AUTOSAR Release	4.2.2

Document Change History		
Release	Changed by	Change Description
4.2.2	AUTOSAR Release Management	Editorial changes
4.2.1	AUTOSAR Release Management	 Removing the limitation "Flash Programming for ECU development purposes" Editorial changes
4.1.2	AUTOSAR Release Management	Editorial changes
4.1.1	AUTOSAR Administration	 Link SRS requirements to new feature documents formal updates to TPS_standardizationTemplate (TPS_STDT_00078)
4.0.3	AUTOSAR Administration	 Added support for deactivation of transmission capabilities
3.1.5	AUTOSAR Administration	Initial Release



Disclaimer

This specification and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the specification.

The material contained in this specification is protected by copyright and other types of Intellectual Property Rights. The commercial exploitation of the material contained in this specification requires a license to such Intellectual Property Rights.

This specification may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the specification may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The AUTOSAR specifications have been developed for automotive applications only. They have neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

Advice for users

AUTOSAR specifications may contain exemplary items (exemplary reference models, "use cases", and/or references to exemplary technical solutions, devices, processes or software).

Any such exemplary items are contained in the specifications for illustration purposes only, and they themselves are not part of the AUTOSAR Standard. Neither their presence in such specifications, nor any later documentation of AUTOSAR conformance of products actually implementing such exemplary items, imply that intellectual property rights covering such exemplary items are licensed under the same rules as applicable to the AUTOSAR Standard.



Table of Contents

1	Scope	of Document	4
2		ntions to be used	
3	Function	onal Overview	6
4	Requir	ements Specification	7
		unctional Requirements	
	4.1.1	General	7
	4.1.2	Features	9
	4.1.3	Initialisation	12
		Normal Operation	
		Shutdown Operation	
	4.1.6	Fault Operation	13
5	Refere	nces	14



1 Scope of Document

This document defines general rules and formats for requirements specification within AUTOSAR. It shall be used as a basis for each requirements document.

The AUTOSAR Requirements on XCP specifies the XCP feature-set, which shall be supported by the AUTOSAR XCP Software Specification document.

A detailed list can be found on Chapter 4.2 "Functional Requirements".



2 Conventions to be used

- The representation of requirements in AUTOSAR documents follows the table specified in [1].
- In requirements, the following specific semantics shall be used (based on the Internet Engineering Task Force IETF).

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as:

- SHALL: This word means that the definition is an absolute requirement of the specification.
- SHALL NOT: This phrase means that the definition is an absolute prohibition of the specification.
- MUST: This word means that the definition is an absolute requirement of the specification due to legal issues.
- MUST NOT: This phrase means that the definition is an absolute prohibition of the specification due to legal constraints.
- SHOULD: This word, or the adjective "RECOMMENDED", mean that
 there may exist valid reasons in particular circumstances to ignore a
 particular item, but the full implications must be understood and
 carefully weighed before choosing a different course.
- SHOULD NOT: This phrase, or the phrase "NOT RECOMMENDED" mean that there may exist valid reasons in particular circumstances when the particular behavior is acceptable or even useful, but the full implications should be understood and the case carefully weighed before implementing any behavior described with this label.
- MAY: This word, or the adjective "OPTIONAL", means that an item is truly optional. One vendor may choose to include the item because a particular marketplace requires it or because the vendor feels that it enhances the product while another vendor may omit the same item. An implementation, which does not include a particular option, MUST be prepared to interoperate with another implementation, which does include the option, though perhaps with reduced functionality. In the same vein an implementation, which does include a particular option, MUST be prepared to interoperate with another implementation, which does not include the option (except, of course, for the feature the option provides.)



3 Functional Overview

XCP is an ASAM standard for calibration purpose of an ECU. This protocol provides the following functionality:

XCP provides the following basic features:

- Synchronous data acquisition
- Synchronous data stimulation
- Online memory calibration (read / write access)
- Calibration data page initialization and switching
- Flash Programming for ECU development purposes
- Various transportation layers (CAN, Ethernet (TCP/IP, UDP), USB,...)
- Block communication mode
- Interleaved communication mode
- Dynamic data transfer configuration
- Timestamped data transfer
- Synchronization of data transfer
- Priorization of data transfer
- Atomic bit modification
- Bitwise data stimulation

XCP improves the following features compared to CCP 2.1:

- compatibility and specification
- efficiency and throughput
- power-up data transfer
- data page freezing
- auto configuration
- flash programming.

XCP was designed according to the following principles:

- Minimal Slave resource consumption (RAM, ROM, runtime)
- Efficient communication
- Simple Slave implementation



4 Requirements Specification

4.1 Functional Requirements

4.1.1 General

4.1.1.1 [SRS_Xcp_29001] The AUTOSAR XCP module shall be located above the bus interfaces / Socket Adaptor

Type: valid Description: Within the AUTOSAR layered architecture, the AUTOSAR XCP module shall be located above the bus specific interfaces (CAN, FlexRay) and for Ethernet on top of the Socket Adaptor. Rationale: Due to performance reason, the AUTOSAR XCP is located as low as possible within the layered architecture. Use Case: Dependencies: Supporting Material: BSW Layered Software Architecture	[
be located above the bus specific interfaces (CAN, FlexRay) and for Ethernet on top of the Socket Adaptor. Rationale: Due to performance reason, the AUTOSAR XCP is located as low as possible within the layered architecture. Use Case: Dependencies:	Type:	valid
possible within the layered architecture. Use Case: Dependencies:	Description:	be located above the bus specific interfaces (CAN, FlexRay) and for
Dependencies:	Rationale:	
	Use Case:	
Supporting Material: RSW Lavered Software Architecture	Dependencies:	
Dow Layered Conward Alemeeture	Supporting Material:	BSW Layered Software Architecture

[(RS_BRF_01016,RS_BRF_01656)

4.1.1.2 [SRS_Xcp_29002] The AUTOSAR XCP shall make use of the data transmit- and receive APIs of the Bus Interfaces

1	
Type:	Valid
Description:	For sending and transmission of XCP Messages, the corresponding APIs provided by the bus specific interfaces shall be used
Rationale:	Usage of available APIs
Use Case:	Transmit and receive XCP Messages
Dependencies:	
Supporting Material:	SWS FlexRay Interface, SWS CAN Interface, SWS Socket Adaptor

[(RS_BRF_01656,RS_BRF_02264)

4.1.1.3 [SRS_Xcp_29003] The AUTOSAR XCP messages shall be identified by unique PDU-IDs

Type:	valid
Description:	Unique PDU-IDs have to be assigned to the the XCP messages by configuration
	¥
Rationale:	PDU-IDs are used by the Bus Interfaces to route the PDUs to the assigned target AUTOSAR modules (PDUR, NM, TP, XCP, CDD)
Use Case:	Routing / Scheduling
Dependencies:	
Supporting Material:	BSW Layered Software Architecture

(RS_BRF_01656,RS_BRF_01024)

4.1.1.4 [SRS_Xcp_29004] The XCP Specification Version 1.1 shall be used



Type:	Valid
Description:	The XCP Specification Version 1.1 shall be used for implementation
Rationale:	XCP Specification Version 1.1 is the latest Version available for AUTOSAR
	at this time
Use Case:	Calibration purpose
Dependencies:	
Supporting Material:	http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin=

J(RS_BRF_01656)

4.1.1.5 [SRS_Xcp_29005] XCP on CAN shall be supported

<u> </u>	
Type:	valid
Description:	XCP on CAN shall be supported as described within the ASAM "XCP Transport Layer on CAN" specification
Rationale:	It shall be possible to exchange XCP data using the CAN communications bus
Use Case:	Calibration/Stimulation purpose
Dependencies:	
Supporting Material:	http://www.asam.net/doc_int/getfile/getfile.php?id=239&memberlogin=

(RS_BRF_01656,RS_BRF_01704)

4.1.1.6 [SRS_Xcp_29006] XCP on FlexRay shall be supported

Valid
XCP on FlexRay shall be supported as described within the ASAM "XCP
Transport Layer on FlexRay" specification
It shall be possible to exchange XCP data using the FlexRay
communications bus
Calibration/Stimulation purpose
http://www.asam.net/doc_int/getfile/getfile.php?id=376&memberlogin=

J(RS_BRF_01656,RS_BRF_01752)

4.1.1.7 [SRS_Xcp_29007] XCP on Ethernet shall be supported

<u>. l</u>	
Type:	Valid
Description:	XCP on Ethernet shall be supported as described within the ASAM "XCP Transport Layer on Ethernet" specification, using TCP/IP and/or UDP
Rationale:	It shall be possible to exchange XCP data using the Ethernet communications bus
Use Case:	Calibration/Stimulation purpose
Dependencies:	
Supporting Material:	http://www.asam.net/doc_int/getfile/getfile.php?id=240&memberlogin=

[(RS_BRF_01656,RS_BRF_01776)



4.1.2 Features

г

г

4.1.2.1 [SRS_Xcp_29008] The code generator of the XCP Module shall generate the A2L IF_DATA section

Type:	Valid
Description:	The code generator of the XCP Module shall generate the A2L IF_DATA section, based on the configuration of XCP.
Rationale:	The configuration information of the XCP Slave (AUTOSAR XCP Module) should also be used for the configuration of the XCP Master.
Use Case:	Ensure consistency of XCP Master and XCP Slave configuration.
Dependencies:	
Supporting Material:	http://www.asam.net/doc_int/getfile/getfile.php?id=240&memberlogin=

(RS_BRF_01656, RS_BRF_02264)

4.1.2.2 [SRS_Xcp_29009] The slave shall transfer the contents of the elements defined in each ODT of the DAQ-list to the master

Type:	Valid
Description:	The slave has to transfer the contents of the elements defined in each ODT of the DAQ-list to the master.
Rationale:	-
Use Case:	Calibration purpose
Dependencies:	
Supporting Material:	http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin=

(RS_BRF_01656, RS_BRF_02264)

4.1.2.3 [SRS_Xcp_29010] Synchronous Data Stimulation shall be the inverse mode of Synchronous Data Acquisition

Type:	Valid
Description:	Synchronous Data Stimulation is the inverse mode of Synchronous Data Acquisition. The master has to transfer the contents of the elements defined in each ODT of the DAQ-list to the slave.
Rationale:	-
Use Case:	Stimulation purpose
Dependencies:	
Supporting Material:	http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin=

(RS_BRF_01656, RS_BRF_02264)

4.1.2.4 [SRS_Xcp_29011] Multiple direct successive packets without acknowledge shall be sent / received

Type:	Valid
Description:	Multiple direct successive packets without acknowledge can be sent / received
Rationale:	Speed up memory uploads and downloads
Use Case:	Stimulation/Calibration purpose
Dependencies:	
Supporting Material:	http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin=



(RS_BRF_01656, RS_BRF_02264)

4.1.2.5 [SRS_Xcp_29012] The XCP master shall already send the next request before having received the response on the previous request

_[
Type:	Valid
Description:	The XCP master may already send the next request before having received
	the response on the previous request.
Rationale:	Speed up data transfer
Use Case:	Stimulation/Calibration purpose
Dependencies:	
Supporting Material:	http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin=

(RS_BRF_01656, RS_BRF_02264)

4.1.2.6 [SRS_Xcp_29013] It shall be possible to configure the DAQ Lists dynamically

Type:	Valid
Description:	It shall be possible to configure the DAQ Lists dynamically
Rationale:	Allow flexibility for selection of different data/signal values to be transmitted
Use Case:	Stimulation/Calibration purpose
Dependencies:	
Supporting Material:	http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin=

(RS_BRF_01656, RS_BRF_02264)

4.1.2.7 [SRS_Xcp_29014] It shall be possible to transmit a timestamp within the XCP packet

Type:	Valid
Description:	It shall be possible to transmit a timestamp within the XCP packet
Rationale:	Timing information of the XCP packets are important for the XCP master to be able to reorder the received XCP packets if necessary
Use Case:	Reordering received XCP packets
Dependencies:	
Supporting Material:	http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin=

(RS BRF 01656, RS BRF 02264)

4.1.2.8 [SRS_Xcp_29015] It shall be possible to bypass data by making use of Synchronous Data Acquisition and Synchronous Data Stimulation simultaneously

Туре:	Valid
Description:	It shall be possible to bypass data by making use of Synchronous Data
	Acquisition and Synchronous Data Stimulation simultaneously.
Rationale:	Including additional calculation / manipulation of data
Use Case:	Calibration / Stimulation purpose
Dependencies:	Support of Synchronous Data Acquisition and Synchronous Data
	Stimulation, interaction with AUTSAR RTE required



Supporting Material:	http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin=
	SWS RTE

(RS_BRF_01656, RS_BRF_02264)

4.1.2.9 [SRS_Xcp_29016] The feature "Seed&Key" shall be used for protection handling purpose

Type:	Valid
Description:	The feature "Seed&Key" is used for protection handling purpose.
Rationale:	Secure access to the XCP slave's memory
Use Case:	The need for information hiding is different, depending on the project phase
Dependencies:	
Supporting Material:	http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin=

(RS_BRF_01656, RS_BRF_02264)

4.1.2.10 [SRS_Xcp_29018] Page switching shall be supported

Type:	Valid
Description:	The master can request the slave to answer the current active PAGE. The XCP slave shall be able to switch to another page if this is requested by the XCP master at any point in time.
Rationale:	
Use Case:	Data Page switching is required for high end ECUs because of the huge amount of different data/variables to be transmitted via XCP
Dependencies:	
Supporting Material:	http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin=

(RS_BRF_01656, RS_BRF_02264)

4.1.2.11 [SRS_Xcp_29019] DAQ configuration storing with power-up data transfer (RESUME mode) shall be supported

ſ

Type:	Valid
Description:	The XCP master requests the XCP slave to set the RESUME bit of selected DAQ lists. After power-up, the slave has to restore the DAQ lists and indicate the RESUME mode to the XCP master autonomously.
Rationale:	The purpose of the resume mode is to enable automatic data transfer (DAQ, STIM) directly after the power up of the XCP slave
Use Case:	Calibration data are immediately needed after power-up of an ECU for optimization purpose (e.g. optimization of engine start behaviour).
Dependencies:	
Supporting Material:	http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin=

|(RS_BRF_01656, RS_BRF_02264)



4.1.2.12 [SRS_Xcp_29021] The XCP shall provide a feature to enable and disable communication on specific channel

Type:	Valid
Description:	The XCP shall provide a feature to enable and disable communication on specific channel (TX capabilities)
Rationale:	
Use Case:	Allowing only requested channel communication in order to use bandwidth effectively
Dependencies:	
Supporting Material:	

(RS_BRF_01656, RS_BRF_02264)

4.1.2.13 [SRS_Xcp_29020] Flash Programming for ECU development purposes

1	
Type:	Valid
Description:	XCP shall support flash programming as described within the ASAM "XCP Protocol Layer Specification".
Rationale:	Speeding up ECU development purposes through enabling programming feature.
Use Case:	
Dependencies:	
Supporting Material:	ASAM_XCP_Part2-Protocol-Layer-Specification_V1-1-0.pdf

(RS_BRF_01656, RS_BRF_02264)

4.1.3 Initialisation

4.1.3.1 [SRS_Xcp_29017] The AUTOSAR XCP module shall implement an interface for initialization.

1	
Type:	Valid
Description:	The AUTOSAR XCP module implements an interface for initialization.
	This service shall initialize all global variables of the module.
Rationale:	Basic functionality.
Use Case:	Set the AUTOSAR XCP module into a defined state
Dependencies:	
Supporting Material:	

I(RS_BRF_01656, RS_BRF_02264,RS_BRF_01136)

4.1.4 Normal Operation

The AUTOSAR XCP module shall operate as described within the ASAM XCP Specification Version 1.1. Please refer to

http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin=



4.1.5 Shutdown Operation

The AUTOSAR XCP module shall operate as described within the ASAM XCP Specification Version 1.1. Please refer to <a href="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php."http://www.asam.net/doc_int/getfile.php.

The continue of t

4.1.6 Fault Operation

The AUTOSAR XCP module shall operate as described within the ASAM XCP Specification Version 1.1. Please refer to <a href="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php?id=238&memberlogin="http://www.asam.net/doc_int/getfile.php."http://www.asam.net/doc_int/getfile.php.

The control of the



5 References

[1] Software Standardization Template AUTOSAR_TPS_StandardizationTemplate.pdf