

Document Title	Specification of Communication Stack Types	
Document Owner	AUTOSAR	
Document Responsibility	AUTOSAR	
Document Identification No	050	
Document Classification	Standard	

Document Status	Final
Part of AUTOSAR Release	4.2.2

Document Change History		
Release Changed by Change Description		
4.2.2	AUTOSAR Release Management	Editorial Changes
4.2.1	AUTOSAR Release Management	MetaData information is added in PduInfoType
4.1.3	AUTOSAR Release Management	Added support for Pretended network data type
4.1.2	AUTOSAR Release Management	 Removed the published information Editorial changes Removed chapter(s) on change documentation
4.1.1	AUTOSAR Administration	 Added support for Partial network data type Revised Notification type and RetryInfo type Additional input (SWS_BSW_General) added for SWS_CommunicationStackTypes
4.0.3	AUTOSAR Administration	 ComStack Artifacts have been generated from BSW Model Update of SWS document for new traceability mechanism
3.1.5	AUTOSAR Administration	 Add TPParameterType and Enumeration value TP_NORETRY in RetryInfoType ComStack_Types.h divided into ComStack_Types.h and ComStack_Cfg.h PduIdType and PduLengthType defined in ComStack_Cfg.h file



	Document Change History			
Release	Changed by	Change Description		
3.1.4	AUTOSAR Administration	 Typo errors are corrected throughout the document General return codes for NotifResultType has been added to support Tp_ChangeParameterRequest TpDataStateType and RetryInfoType has been added to store the Tp buffer status information Common Published information has been updated Legal disclaimer revised 		
3.1.1	AUTOSAR Administration	Legal disclaimer revised		
2.1.16	AUTOSAR Administration	 Chapter numbers in chapter 8.1 corrected New data type NetworkHandleType created according item COMTYPE026 established Syntax correction in PduInfoType Document meta information extended Small layout adaptations made 		
2.1.15	AUTOSAR Administration	 "Advice for users" revised "Revision Information" added Changed "sender" to "receiver" at NTFRSLT_E_WFT_OVRN 		
2.1.2	AUTOSAR Administration	 NTFRSLT_E_TIMEOUT_Bs changed NTFRSLT_E_TIMEOUT_BS NTFRSLT_E_TIMEOUT_Cr changed to NTFRSLT_E_TIMEOUT_CR Definitions according to compiler abstraction added Legal disclaimer revised 		
2.1.1	AUTOSAR Administration	Initial release (The V1.0.0 was only as Pre- Release available within Release 1.0)		



Disclaimer

This specification and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the specification.

The material contained in this specification is protected by copyright and other types of Intellectual Property Rights. The commercial exploitation of the material contained in this specification requires a license to such Intellectual Property Rights.

This specification may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the specification may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The AUTOSAR specifications have been developed for automotive applications only. They have neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

Advice for users

AUTOSAR specifications may contain exemplary items (exemplary reference models, "use cases", and/or references to exemplary technical solutions, devices, processes or software).

Any such exemplary items are contained in the specifications for illustration purposes only, and they themselves are not part of the AUTOSAR Standard. Neither their presence in such specifications, nor any later documentation of AUTOSAR conformance of products actually implementing such exemplary items, imply that intellectual property rights covering such exemplary items are licensed under the same rules as applicable to the AUTOSAR Standard.



Table of Contents

1	Introduction and functional overview	5
2	Acronyms and abbreviations	6
3	Related documentation 3.1 Input documents 3.2 Related standards and norms 3.3 Related specification	7 7
4	Constraints and assumptions	9 9
5	Software Architecture 5.1 Dependencies to other modules 5.2 File structure	10
6	Requirements traceability	11
7	Functional specification	
8	API specification 8.1 Type definitions 8.1.1 PduldType 8.1.2 PduLengthType 8.1.3 PdulnfoType 8.1.4 PNCHandleType 8.1.5 TPParameterType 8.1.6 BufReq_ReturnType 8.1.7 BusTrcvErrorType 8.1.8 TpDataStateType 8.1.9 RetryInfoType 8.1.10 NetworkHandleType 8.1.11 IcomConfigIdType 8.1.12 IcomSwitch_ErrorType 8.1.12 Function definitions	19 19 20 21 21 22 23 23 23 23
9	Sequence diagrams	26
1(Configuration specification	
1 -	Not applicable requirements	28



1 Introduction and functional overview

This document specifies the AUTOSAR communication stack type header file. It contains all types that are used across several modules of the communication stack of the basic software and all types of all basic software modules that are platform and compiler independent.

It is strongly recommended that those communication stack type files are unique within the AUTOSAR community to guarantee unique types and to avoid type changes when changing from supplier A to B.



2 Acronyms and abbreviations

Acronyms and abbreviations that have a local scope are not contained in the

AUTOSAR glossary. These must appear in a local glossary.

Acronym:	Description:		
API	Application Programming Interface		
DCM	Diagnostic Communication Manager		
I-PDU	Interaction Layer PDU. In AUTOSAR the Interaction Layer is		
	equivalent to the Communication Services Layer.		
L-PDU	Data Link Layer PDU. In AUTOSAR the Data Link Layer is		
	equivalent to the Communication Hardware Abstraction and		
	Microcontroller Abstraction Layer.		
N-PDU	Network Layer PDU. In AUTOSAR the Network Layer is equivalent		
	to the Transport Protocol.		
OSEK/VDX	In May 1993 OSEK has been founded as a joint project in the		
	German automotive industry aiming at an industry standard for an		
	open-ended architecture for distributed control units in vehicles.		
	OSEK is an abbreviation for the German term "Offene Systeme und		
	deren Schnittstellen für die Elektronik im Kraftfahrzeug" (English:		
	Open Systems and the Corresponding Interfaces for Automotive		
	Electronics). Initial project partners were BMW, Bosch,		
	DaimlerChrysler, Opel, Siemens, VW and the IIIT of the University of		
	Karlsruhe as co-ordinator. The French car manufacturers PSA and		
	Renault joined OSEK in 1994 introducing their VDX-approach		
	(Vehicle Distributed eXecutive) which is a similar project within the		
	French automotive industry. At the first workshop on October 1995		
	the OSEK/VDX group presented the results of the harmonised		
	specification between OSEK and VDX. After the 2nd international OSEK/VDX Workshop in October 1997 the 2nd versions of the		
	specifications were published.		
PDU	Protocol Data Unit		
SDU	Service Data Unit - Payload of PDU		
TP	Transport Protocol		
11	Hallsport Flotocol		

Abbreviation:	Description:
Com	Communication
EcuC	ECU Configuration
e.g.	[lat.] exempli gratia = [eng.] for example
i.e.	[lat.] it est = [eng.] that is



3 Related documentation

3.1 Input documents

[GeneralSRS] General Requirements on Basic Software Modules AUTOSAR_SRS_BSWGeneral.pdf

[SRSSPAL] General Requirements on SPAL AUTOSAR SRS SPALGeneral.pdf

[StdTypes] Specification of Standard Types AUTOSAR SWS StandardTypes.pdf

[PltfTypes] Specification of Platform Types AUTOSAR SWS PlatformTypes.pdf

[CompTypes] Specification of Compiler Abstraction AUTOSAR_SWS_CompilerAbstraction.pdf

[CANTP] Specification of CAN Transport Layer AUTOSAR_SWS_CANTransportLayer.pdf

[FlexRayTP] Specification of FlexRay Transport Layer AUTOSAR_SWS_FlexRayTransportLayer.pdf

[CANTRCV] Specification of CAN Transceiver Driver AUTOSAR SWS CANTransceiverDriver.pdf

[FRTRCV] Specification of FlexRay Transceiver Driver AUTOSAR_SWS_FlexRayTransceiverDriver.pdf

[BSMDT]Basic Software Module Description Template, AUTOSAR_TPS_BSWModuleDescriptionTemplate.pdf

[BSWModule]List of Basic Software Modules AUTOSAR_TR_BSWModuleList

[BSWGeneral]General Specification of Basic Software Modules AUTOSAR_SWS_BSWGeneral.pdf

3.2 Related standards and norms

[CProgLang] ISO/IEC 9899:1990 Programming Language – C [ISONM] ISO/IEC 15765-2; 2003 Diagnostics on Controller Area Networks (CAN) – Network layer services



3.3 Related specification

AUTOSAR provides a General Specification on Basic Software modules (→ chapter 3.1) (SWS BSW General), which is also valid for Communication Stack Types.

Thus, the specification SWS BSW General shall be considered as additional and required specification for Communication Stack Types.



4 Constraints and assumptions

4.1 Limitations

No limitations.

4.2 Applicability to car domains

No limitations.

4.3 Applicability to safety related environments

No restrictions, because the subject of this specification is a header file specifying types. It does not include or implement any functionality.



5 Software Architecture

5.1 Dependencies to other modules

The communication stack type header file defines communication types based on the platform types [PltfTypes] (Platform_Types.h) and Compiler (Compiler.h) header file [CompTypes]. To prevent multiple includes of header files, the communication stack header file includes the standard types header file [StdTypes] which already includes both other files.

5.2 File structure

[SWS_COMTYPE_00001] [The include file structure shall be as follows:




Figure 1: Include File Structure

ComStack_Types.h shall include Std_Types.h and ComStack_Cfg.h Communication related basic software modules shall include ComStack_Types.h Communication related basic software modules shall not include Std_Types.h directly.] (SRS_BSW_00384)



6 Requirements traceability

Requirement	Description	Satisfied by
-	-	SWS_COMTYPE_00003
-	-	SWS_COMTYPE_00004
-	-	SWS_COMTYPE_00005
-	-	SWS_COMTYPE_00006
-	-	SWS_COMTYPE_00007
-	-	SWS_COMTYPE_00008
-	-	SWS_COMTYPE_00010
-	-	SWS_COMTYPE_00011
-	-	SWS_COMTYPE_00012
-	-	SWS_COMTYPE_00014
-	-	SWS_COMTYPE_00015
-	-	SWS_COMTYPE_00016
-	-	SWS_COMTYPE_00017
-	-	SWS_COMTYPE_00020
-	-	SWS_COMTYPE_00021
-	-	SWS_COMTYPE_00022
-	-	SWS_COMTYPE_00027
-	-	SWS_COMTYPE_00029
-	-	SWS_COMTYPE_00030
-	-	SWS_COMTYPE_00031
-	-	SWS_COMTYPE_00036
-	-	SWS_COMTYPE_00037
-	-	SWS_COMTYPE_00038
BSW00324	-	SWS_COMTYPE_00035
BSW00420	-	SWS_COMTYPE_00035
BSW00421	-	SWS_COMTYPE_00035
BSW00431	-	SWS_COMTYPE_00035
BSW00434	-	SWS_COMTYPE_00035
SRS_BSW_00005	Modules of the $\hat{A}\mu C$ Abstraction Layer (MCAL) may not have hard coded horizontal interfaces	SWS_COMTYPE_00035
SRS_BSW_00006	The source code of software modules above the µC Abstraction Layer (MCAL) shall not be processor and compiler dependent.	SWS_COMTYPE_00035
SRS_BSW_00007	All Basic SW Modules written in C language shall conform to the MISRA C 2004 Standard.	SWS_COMTYPE_00035
SRS_BSW_00009	All Basic SW Modules shall be documented according	SWS_COMTYPE_00035



	to a common standard.	
SDS BSW 00010		
	The memory consumption of all Basic SW Modules shall be documented for a defined configuration for all supported platforms.	SWS_COMTYPE_00035
	The Basic Software Module shall be able to initialize variables and hardware in a separate initialization function	SWS_COMTYPE_00035
	All modules of the AUTOSAR Basic Software shall strictly separate configuration from implementation	SWS_COMTYPE_00035
	All modules of the AUTOSAR Basic Software shall support a tool based configuration	SWS_COMTYPE_00035
	Configuration files of AUTOSAR Basic SW module shall be readable for human beings	SWS_COMTYPE_00035
r	The AUTOSAR Basic Software shall provide a microcontroller abstraction layer which provides a standardized interface to higher software layers	SWS_COMTYPE_00035
	The AUTOSAR Basic Software shall provide a hardware abstraction layer	SWS_COMTYPE_00035
k	The Implementation of interrupt service routines shall be done by the Operating System, complex drivers or modules	SWS_COMTYPE_00035
	All AUTOSAR Basic Software Modules shall provide configuration rules and constraints to enable plausibility checks	SWS_COMTYPE_00035
	SW components shall be tested by a function defined in a common API in the Basis-SW	SWS_COMTYPE_00035
	The AUTOSAR SW Components shall provide information about their dependency from faults, signal qualities, driver demands	SWS_COMTYPE_00035
r	Optional functionality of a Basic-SW component that is not required in the ECU shall be configurable at precompile-time	SWS_COMTYPE_00035
	The scheduling strategy that is built inside the Basic Software Modules shall be compatible with the strategy used in the system	SWS_COMTYPE_00035
	All AUTOSAR Basic Software Modules shall be identified by an unambiguous name	SWS_COMTYPE_00035
	All AUTOSAR Basic Software Modules shall only import the necessary information	SWS_COMTYPE_00035
	All AUTOSAR Basic Software Modules shall only export information needed by other modules	SWS_COMTYPE_00035
	All AUTOSAR Basic Software Modules shall use the following data types instead of native C data types	SWS_COMTYPE_00035
	AUTOSAR Basic Software Modules shall be compiler and platform independent	SWS_COMTYPE_00035
SRS_BSW_00307	Global variables naming convention	SWS_COMTYPE_00035
	AUTOSAR Basic Software Modules shall not define global data in their header files, but in the C file	SWS_COMTYPE_00035



SRS_BSW_00309	All AUTOSAR Basic Software Modules shall indicate all global data with read-only purposes by explicitly assigning the const keyword	SWS_COMTYPE_00035
SRS_BSW_00310	API naming convention	SWS_COMTYPE_00035
SRS_BSW_00312	Shared code shall be reentrant	SWS_COMTYPE_00035
SRS_BSW_00314	All internal driver modules shall separate the interrupt frame definition from the service routine	SWS_COMTYPE_00035
SRS_BSW_00321	The version numbers of AUTOSAR Basic Software Modules shall be enumerated according specific rules	SWS_COMTYPE_00035
SRS_BSW_00323	All AUTOSAR Basic Software Modules shall check passed API parameters for validity	SWS_COMTYPE_00035
SRS_BSW_00325	The runtime of interrupt service routines and functions that are running in interrupt context shall be kept short	SWS_COMTYPE_00035
SRS_BSW_00326	-	SWS_COMTYPE_00035
SRS_BSW_00327	Error values naming convention	SWS_COMTYPE_00035
SRS_BSW_00328	All AUTOSAR Basic Software Modules shall avoid the duplication of code	SWS_COMTYPE_00035
SRS_BSW_00329	-	SWS_COMTYPE_00035
SRS_BSW_00330	It shall be allowed to use macros instead of functions where source code is used and runtime is critical	SWS_COMTYPE_00035
SRS_BSW_00331	All Basic Software Modules shall strictly separate error and status information	SWS_COMTYPE_00035
SRS_BSW_00333	For each callback function it shall be specified if it is called from interrupt context or not	SWS_COMTYPE_00035
SRS_BSW_00334	All Basic Software Modules shall provide an XML file that contains the meta data	SWS_COMTYPE_00035
SRS_BSW_00335	Status values naming convention	SWS_COMTYPE_00035
SRS_BSW_00336	Basic SW module shall be able to shutdown	SWS_COMTYPE_00035
SRS_BSW_00337	Classification of development errors	SWS_COMTYPE_00035
SRS_BSW_00338	-	SWS_COMTYPE_00035
SRS_BSW_00339	Reporting of production relevant error status	SWS_COMTYPE_00035
SRS_BSW_00341	Module documentation shall contains all needed informations	SWS_COMTYPE_00035
SRS_BSW_00342	It shall be possible to create an AUTOSAR ECU out of modules provided as source code and modules provided as object code, even mixed	SWS_COMTYPE_00035
SRS_BSW_00343	The unit of time for specification and configuration of Basic SW modules shall be preferably in physical time unit	SWS_COMTYPE_00035
SRS_BSW_00344	BSW Modules shall support link-time configuration	SWS_COMTYPE_00035
SRS_BSW_00345	BSW Modules shall support pre-compile configuration	SWS_COMTYPE_00035
SRS_BSW_00346	All AUTOSAR Basic Software Modules shall provide at least a basic set of module files	SWS_COMTYPE_00035
SRS_BSW_00347	A Naming seperation of different instances of BSW drivers shall be in place	SWS_COMTYPE_00035



SRS_BSW_00348	All AUTOSAR standard types and constants shall be placed and organized in a standard type header file	SWS_COMTYPE_00035
SRS_BSW_00350	All AUTOSAR Basic Software Modules shall apply a specific naming rule for enabling/disabling the detection and reporting of development errors	SWS_COMTYPE_00035
SRS_BSW_00353	All integer type definitions of target and compiler specific scope shall be placed and organized in a single type header	SWS_COMTYPE_00035
SRS_BSW_00355	-	SWS_COMTYPE_00035
SRS_BSW_00357	For success/failure of an API call a standard return type shall be defined	SWS_COMTYPE_00035
SRS_BSW_00358	The return type of init() functions implemented by AUTOSAR Basic Software Modules shall be void	SWS_COMTYPE_00035
SRS_BSW_00359	All AUTOSAR Basic Software Modules callback functions shall avoid return types other than void if possible	SWS_COMTYPE_00035
SRS_BSW_00360	AUTOSAR Basic Software Modules callback functions are allowed to have parameters	SWS_COMTYPE_00035
SRS_BSW_00361	All mappings of not standardized keywords of compiler specific scope shall be placed and organized in a compiler specific type and keyword header	SWS_COMTYPE_00035
SRS_BSW_00369	All AUTOSAR Basic Software Modules shall not return specific development error codes via the API	SWS_COMTYPE_00035
SRS_BSW_00370	-	SWS_COMTYPE_00035
SRS_BSW_00371	The passing of function pointers as API parameter is forbidden for all AUTOSAR Basic Software Modules	SWS_COMTYPE_00035
SRS_BSW_00373	The main processing function of each AUTOSAR Basic Software Module shall be named according the defined convention	SWS_COMTYPE_00035
SRS_BSW_00374	All Basic Software Modules shall provide a readable module vendor identification	SWS_COMTYPE_00035
SRS_BSW_00375	Basic Software Modules shall report wake-up reasons	SWS_COMTYPE_00035
SRS_BSW_00376	-	SWS_COMTYPE_00035
SRS_BSW_00377	A Basic Software Module can return a module specific types	SWS_COMTYPE_00035
SRS_BSW_00378	AUTOSAR shall provide a boolean type	SWS_COMTYPE_00035
SRS_BSW_00379	All software modules shall provide a module identifier in the header file and in the module XML description file.	SWS_COMTYPE_00035
SRS_BSW_00380	Configuration parameters being stored in memory shall be placed into separate c-files	SWS_COMTYPE_00035
SRS_BSW_00381	The pre-compile time parameters shall be placed into a separate configuration header file	SWS_COMTYPE_00035
SRS_BSW_00383	The Basic Software Module specifications shall specify which other configuration files from other modules they use at least in the description	SWS_COMTYPE_00035
SRS_BSW_00384	The Basic Software Module specifications shall specify at least in the description which other modules they	SWS_COMTYPE_00001



	Г.	
	require	
SRS_BSW_00385	List possible error notifications	SWS_COMTYPE_00035
SRS_BSW_00386	The BSW shall specify the configuration for detecting an error	SWS_COMTYPE_00035
SRS_BSW_00387	-	SWS_COMTYPE_00035
SRS_BSW_00388	Containers shall be used to group configuration parameters that are defined for the same object	SWS_COMTYPE_00035
SRS_BSW_00389	Containers shall have names	SWS_COMTYPE_00035
SRS_BSW_00390	Parameter content shall be unique within the module	SWS_COMTYPE_00035
SRS_BSW_00391	-	SWS_COMTYPE_00035
SRS_BSW_00392	Parameters shall have a type	SWS_COMTYPE_00035
SRS_BSW_00393	Parameters shall have a range	SWS_COMTYPE_00035
SRS_BSW_00394	The Basic Software Module specifications shall specify the scope of the configuration parameters	SWS_COMTYPE_00035
SRS_BSW_00395	The Basic Software Module specifications shall list all configuration parameter dependencies	SWS_COMTYPE_00035
SRS_BSW_00396	The Basic Software Module specifications shall specify the supported configuration classes for changing values and multiplicities for each parameter/container	SWS_COMTYPE_00035
SRS_BSW_00397	The configuration parameters in pre-compile time are fixed before compilation starts	SWS_COMTYPE_00035
SRS_BSW_00398	The link-time configuration is achieved on object code basis in the stage after compiling and before linking	SWS_COMTYPE_00035
SRS_BSW_00399	Parameter-sets shall be located in a separate segment and shall be loaded after the code	SWS_COMTYPE_00035
SRS_BSW_00400	Parameter shall be selected from multiple sets of parameters after code has been loaded and started	SWS_COMTYPE_00035
SRS_BSW_00401	Documentation of multiple instances of configuration parameters shall be available	SWS_COMTYPE_00035
SRS_BSW_00404	BSW Modules shall support post-build configuration	SWS_COMTYPE_00035
SRS_BSW_00405	BSW Modules shall support multiple configuration sets	SWS_COMTYPE_00035
SRS_BSW_00406	A static status variable denoting if a BSW module is initialized shall be initialized with value 0 before any APIs of the BSW module is called	SWS_COMTYPE_00035
SRS_BSW_00407	Each BSW module shall provide a function to read out the version information of a dedicated module implementation	SWS_COMTYPE_00035
SRS_BSW_00408	All AUTOSAR Basic Software Modules configuration parameters shall be named according to a specific naming rule	SWS_COMTYPE_00035
SRS_BSW_00409	All production code error ID symbols are defined by the Dem module and shall be retrieved by the other BSW modules from Dem configuration	SWS_COMTYPE_00035
SRS_BSW_00410	Compiler switches shall have defined values	SWS_COMTYPE_00035
SRS_BSW_00411	All AUTOSAR Basic Software Modules shall apply a naming rule for enabling/disabling the existence of the	SWS_COMTYPE_00035





	API	
SRS_BSW_00412	References to c-configuration parameters shall be placed into a separate h-file	SWS_COMTYPE_00035
SRS_BSW_00414	Init functions shall have a pointer to a configuration structure as single parameter	SWS_COMTYPE_00035
SRS_BSW_00415	Interfaces which are provided exclusively for one module shall be separated into a dedicated header file	SWS_COMTYPE_00035
SRS_BSW_00416	The sequence of modules to be initialized shall be configurable	SWS_COMTYPE_00035
SRS_BSW_00417	Software which is not part of the SW-C shall report error events only after the DEM is fully operational.	SWS_COMTYPE_00035
SRS_BSW_00422	Pre-de-bouncing of error status information is done within the DEM	SWS_COMTYPE_00035
SRS_BSW_00423	BSW modules with AUTOSAR interfaces shall be describable with the means of the SW-C Template	SWS_COMTYPE_00035
SRS_BSW_00424	BSW module main processing functions shall not be allowed to enter a wait state	SWS_COMTYPE_00035
SRS_BSW_00425	The BSW module description template shall provide means to model the defined trigger conditions of schedulable objects	SWS_COMTYPE_00035
SRS_BSW_00426	BSW Modules shall ensure data consistency of data which is shared between BSW modules	SWS_COMTYPE_00035
SRS_BSW_00427	ISR functions shall be defined and documented in the BSW module description template	SWS_COMTYPE_00035
SRS_BSW_00428	A BSW module shall state if its main processing function(s) has to be executed in a specific order or sequence	SWS_COMTYPE_00035
SRS_BSW_00429	BSW modules shall be only allowed to use OS objects and/or related OS services	SWS_COMTYPE_00035
SRS_BSW_00432	Modules should have separate main processing functions for read/receive and write/transmit data path	SWS_COMTYPE_00035
SRS_BSW_00433	Main processing functions are only allowed to be called from task bodies provided by the BSW Scheduler	SWS_COMTYPE_00035



7 Functional specification

7.1 General issues

[SWS_COMTYPE_00003] [The file name of the communication stack type header file shall be 'ComStack_Types.h' and configuration header file shall be 'ComStack_Cfg.h'.] ()

[SWS_COMTYPE_00004] [It is not allowed to add any project or supplier specific extension to this file. Any extension invalidates the AUTOSAR conformity.] ()

[SWS_COMTYPE_00015] [Because many of the communication stack type are depending on the appropriate ECU, this file shall be generated dependent on the specific ECU configuration for each ECU independently. | ()

[SWS_COMTYPE_00016] [The communication stack type header files shall be protected against multiple inclusion:

```
ComStack_Types.h
```

```
#ifndef COMSTACK_TYPES_H
#define COMSTACK_TYPES_H
..
/*
   * Contents of file
   */
..
#endif /* COMSTACK_TYPES_H */

ComStack_Cfg.h
#ifndef COMSTACK_CFG_H
#define COMSTACK_CFG_H
..
/*
   * Contents of file
   */
..
#endif /* COMSTACK_CFG_H */
J()
```

[SWS_COMTYPE_00029] [ComStack_Cfg.h shall be generated by the generator to generate the type definition of the PduldType and PduLengthType from the EcuC Virtual Layer based on the configuration e.g. typedef uint8 PduldType if number of PDUs are less than 256. | ()



[SWS_COMTYPE_00030] [The value of PduIdType and PduLengthType shall be derived from the 'PduIdTypeEnum' and 'PduLengthTypeEnum' of the EcuCPduCollection container respectively.] ()



8 API specification

8.1 Type definitions

8.1.1 PduldType

[SWS_COMTYPE_00005][

Name:	PduIdType
Туре:	uint8, uint16
Range:	7- Zero-based integer number The size of this global type depends on the maximum number of PDUs used within one software module. This parameter shall be generated by the generator tool depending on the value configured in EcuC virtual layer. This parameter shall be generated in ComStack_Cfg.h file Example If "'no'" software module deals with more PDUs that 256, this type can be set to uint8. If at least one software module handles more than 256 PDUs, this type must globally be set to uint16.
Description:	This type is used within the entire AUTOSAR Com Stack except for bus drivers.

1 ()

[SWS_COMTYPE_00006][Variables of this type serve as a unique identifier of a PDU within a software module or a set thereof, and also for interaction of two software modules where the Pduld of the corresponding target module is being used for referencing.

1 ()

[SWS_COMTYPE_00007][In order to be able to perform table-indexing within a software module, variables of this type shall be zero-based and consecutive. There might be several ranges of Pdulds in a module, one for each type of operation performed within that module (e.g. sending and receiving).] ()

[SWS_COMTYPE_00014] Pduldmax, the maximum number of a Pduld range, is the number -1 of PDUs dealt with in the corresponding type of operation within that module.

] ()

8.1.2 PduLengthType

[SWS COMTYPE 00008][

Name:	PduLengthType
Type:	uint8, uint16, uint32
Range:	0 <pdulengthmax>Zero-based integer number</pdulengthmax>
	The size of this global type depends on the maximun



	length of PDUs to be sent by an ECU. This parameter shall be generated by the generator tool depending on the value configured in EcuC virtual layer. This parameter shall be generated in ComStack_Cfg.h file Example : If no segmentation is used the length depends on the maximum payload size of a frame of the underlying communication system (for FlexRay maximum size is 255, therefore uint8). If segmentation is used it depends on the maximum length of a segmented N-PDU (in general uint16 is used)
•	This type shall be used within the entire AUTOSAR Com Stack of an ECU except for bus drivers.

] ()

[SWS_COMTYPE_00010] Variables of this type serve as length information of a PDU. The length information is provided in number of bytes.

] ()

[SWS_COMTYPE_00017] PduLengthmax, the maximum length of a Pdu, is the length of the largest (possibly segmented) PDU to be sent by the ECU.

] ()

8.1.3 PduInfoType

[SWS_COMTYPE_00011][

Name:	PduInfoType	PduInfoType				
Туре:	Structure	Structure				
Element:	uint8*	SduDataPtr	Pointer to the SDU (i.e. payload data) of the PDU. Depending on the global parameter MetaDataLength, additional bytes containing MetaData (e.g. the CAN ID) are appended after the payload data. The type of this pointer depends on the memory model being used at compile time.			
	PduLengthType	SduLength	Length of the SDU in bytes, including MetaData.			
Description:	Variables of this type shall be used to store the basic information about a PDU of any type, namely a pointer variable pointing to its SDU (payload), and the corresponding length of the SDU in bytes.					

] ()

8.1.4 PNCHandleType

[SWS_COMTYPE_00036][

Name:	PNCHandleType			
Type:	uint8			
Description:	Used to store the identifier of a partial network cluster.			

| ()



8.1.5 TPParameterType

[SWS_COMTYPE_00031][

Name:	TPParameterT	TPParameterType		
Type:	Enumeration	Enumeration		
Range:	TP_STMIN	0x00: Separation Time		
	TP_BS	0x01: Block Size		
	TP_BC	0x02: The Band width control parameter used in FlexRay transport protocol module.		
Description:	Specify the para	Specify the parameter to which the value has to be changed (BS or STmin).		

] ()

8.1.6 BufReq_ReturnType

[SWS_COMTYPE_00012][

Name:	BufReq_ReturnType		
Туре:	Enumeration		
Range:	BUFREQ_OK	Buffer request accomplished successful. This status shall have the value 0.	
	BUFREQ_E_NOT_OK	Buffer request not successful. Buffer cannot be accessed. This status shall have the value 1.	
	BUFREQ_E_BUSY	Temporarily no buffer available. It's up the requester to retry request for a certain time. This status shall have the value 2.	
	BUFREQ_E_OVFL	No Buffer of the required length can be provided. This status shall have the value 3.	
Description:	Variables of this type	shall be used to store the result of a buffer request.	

] ()

8.1.7 BusTrcvErrorType

[SWS_COMTYPE_00020][

Name:	BusTrcvErrorTy	BusTrcvErrorType		
Туре:	uint8	uint8		
Range:	0x00 - 0x1E		General return codes. A detailed specification is listed below.	
	0x1F - 0x3C	-	Error notification: Error notification codes specific for the communication system CAN. For a detailed definition please refer to the AUTOSAR specification of CAN Transceiver Driver [CANTRCV].	
	0x3D - 0x5A		Error notification: Error notification codes specific for the communication system LIN. A detailed definition is still open, because currently there is not AUTOSAR specification of Lin Interface.	
	0x5B - 0x78		Error notification: Error notification codes specific for the communication system FlexRay.	



			For a detailed definition please refer to the AUTOSAR specification of FlexRay Transceiver Driver [FRTRCV].
	> 0x78		Currently values in this range are invalid. In future it might be possible that further return codes are specified for other communication systems.
	BUSTRCV_OK	0x00	
	BUSTRCV_E_ERRO	R0x01	
Description:	Variables of this t transceiver.	ype sh	all be used to return the bus status evaluated by a

1 ()

Return code specification:

[SWS_COMTYPE_00021][General Codes

[
Return code	Value	Description			
BUSTRCV OK	0x00	There is no bus transceiver error seen by the			
_		driver or transceiver does not support the			
		detection of bus errors.			
BUSTRCV E ERROR	0x01	Bus transceiver detected an unclassified			
		error.			
	0x02-0x1E	Reserved values for future usage.			

| ()

[SWS_COMTYPE_00022] [The Communication System dependent Return codes shall be named as follows:

BUSTRCV_E_<Communication System Abbreviation>_<Error Code Name>.

Communication System Abbreviation:

CAN: for Controller area network
LIN: for Local Interconnect Network

FR: for FlexRay

Error Code Name: self explaining name of error return code.

Example for a CAN specific return value:

BUSTRCV_E_CAN_SINGLE: CAN bus transceiver has detected that the fault tolerant bus is in single wire model ().

8.1.8 TpDataStateType

[SWS_COMTYPE_00027][

Name:	TpDataStateType		
Туре:	Enumeration		
Range:		0x00: TP_DATACONF indicates that all data, that have been copied so far, are confirmed and can be removed from the TP buffer. Data copied by this API call are excluded and will be confirmed later.	
		0x01: TP_DATARETRY indicates that this API call shall copy already copied data in order to recover from an error. In this case TxTpDataCnt specifies the offset of the first byte to be copied by the API call.	
	<u> </u>	0x02: TP_CONFPENDING indicates that the previously copied data must remain in the TP.	
Description:	Variables of this type shall be used to store the state of TP buffer.		



] ()

8.1.9 RetryInfoType

[SWS_COMTYPE_00037][

Name:	RetryInfoType				
Type:	Structure				
Element:	TpDataStateType	TpDataState	The enum type to be used to store the state of Tp buffer.		
	PduLengthType	TxTpDataCnt	Offset from the current position which identifies the number of bytes to be retransmitted.		
Description:	Variables of this type shall be used to store the information about Tp buffer handling.				

] ()

8.1.10 NetworkHandleType

[SWS_COMTYPE_00038][

Name:	NetworkHandleType		
Type:	uint8		
Range:	0255		Zero-based integer number
_	Variables of the type NetworkHandleType shall be used to store the identifier of a communication channel.		

] ()

8.1.11 IcomConfigldType

[SWS_COMTYPE_00039]

Name:	IcomConfigIdType
Туре:	uint8
Description:	IcomConfigIdType defines the configuration ID. An ID of 0 is the default configuration. An ID greater than 0 shall identify a configuration for Pretended Networking. There is more than 1 configuration possible.

] ()

8.1.12 IcomSwitch_ErrorType

[SWS_COMTYPE_00040]

Name:	<pre>IcomSwitch_ErrorType</pre>
Туре:	Enumeration
Range:	ICOM_SWITCH_E_OK The activation of Pretended Networking was successful.
	ICOM_SWITCH_E_FAILED The activation of Pretended Networking was not
	successful.
Description:	IcomSwitch_ErrorType defines the errors which can occur when activating or
	deactivating Pretended Networking.



] ()



8.2 Function definitions

Not applicable.



9 Sequence diagrams

Not applicable.



10 Configuration specification

10.1 Published parameters

For details refer to the chapter 10.3 "Published Information" in SWS_BSWGeneral.



11 Not applicable requirements

applicable to [SWS COMTYPE 00035] These requirements are not specification. (SRS_BSW_00344, SRS_BSW_00404, SRS_BSW_00405, SRS_BSW_00345, SRS BSW 00159, SRS BSW 00167, SRS BSW 00171, SRS_BSW_00170, SRS_BSW_00380, SRS_BSW_00381, SRS_BSW_00412, SRS BSW 00388. SRS_BSW_00389, SRS BSW 00383. SRS BSW 00387. SRS BSW 00390, SRS BSW 00391, SRS BSW 00392, SRS BSW 00393, SRS BSW 00394, SRS BSW 00395. SRS BSW 00396. SRS_BSW_00397, SRS BSW 00399, SRS BSW 00400, SRS BSW 00398, SRS BSW 00375, SRS BSW 00101. SRS BSW 00416. SRS BSW 00406. SRS BSW 00168. SRS BSW 00407, SRS BSW 00423, SRS BSW 00424, SRS BSW 00425, SRS_BSW_00426, SRS BSW 00426, SRS_BSW_00427, SRS BSW 00428, SRS BSW_00429, BSW00431, SRS_BSW_00432, SRS_BSW_00433, BSW00434, SRS BSW 00336, SRS BSW 00337, SRS BSW 00338, SRS BSW 00369, SRS_BSW_00339, BSW00421, SRS_BSW_00422, BSW00420, SRS_BSW_00417, SRS_BSW_00323, SRS_BSW_00409, SRS BSW 00385, SRS_BSW_00386, SRS BSW 00161, SRS BSW 00162, BSW00324, SRS BSW 00005, SRS_BSW_00415, SRS_BSW_00164, SRS_BSW_00325, SRS_BSW_00326, SRS BSW 00342, SRS BSW 00343, SRS BSW 00160, SRS BSW 00007, SRS_BSW_00300, SRS_BSW_00347, SRS_BSW_00307, SRS_BSW_00310, SRS BSW 00350. SRS BSW 00373. SRS BSW 00327. SRS BSW 00335. SRS BSW 00410. SRS BSW 00408. SRS BSW 00411, SRS BSW 00346, SRS_BSW_00314, SRS_BSW_00370, SRS_BSW_00348, SRS_BSW_00158, SRS BSW 00353, SRS BSW 00361, SRS BSW 00301, SRS_BSW_00302, SRS_BSW_00328, SRS BSW 00312, SRS_BSW_00006, SRS_BSW_00357, SRS BSW 00355, SRS BSW 00377, SRS BSW 00304, SRS BSW 00378, SRS_BSW_00306, SRS_BSW_00308, SRS_BSW_00309, SRS_BSW_00371, SRS_BSW_00358, SRS_BSW_00414, SRS_BSW_00376, SRS_BSW_00359, SRS BSW 00360, SRS BSW 00329, SRS BSW 00330, SRS BSW 00331, SRS_BSW_00009, SRS_BSW_00010, SRS_BSW_00401, SRS BSW 00172. SRS BSW 00374, SRS BSW 00379, SRS BSW 00333, SRS BSW 00321, SRS BSW 00341, SRS BSW 00334)