

Document Title	Specification of Time Synchronization over FlexRay
Document Owner	AUTOSAR
Document Responsibility	AUTOSAR
Document Identification No	675
Document Classification	Standard
Document Status	Final
Part of AUTOSAR Release	4.2.2

Document Change History		
Release	Changed by	Change Description
4.2.2	AUTOSAR Release Management	<ul style="list-style-type: none">• Error code FRTSYN_E_INVALID_PDU_SDU_ID replaced by FRTSYN_E_INVALID_PDUID• FlexRay communication state handling simplified (FrIIf_GetPOCStatus replaced by FrIIf_GetState)
4.2.1	AUTOSAR Release Management	<ul style="list-style-type: none">• Initial Release

Disclaimer

This specification and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the specification.

The material contained in this specification is protected by copyright and other types of Intellectual Property Rights. The commercial exploitation of the material contained in this specification requires a license to such Intellectual Property Rights.

This specification may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the specification may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The AUTOSAR specifications have been developed for automotive applications only. They have neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

Advice for users

AUTOSAR specifications may contain exemplary items (exemplary reference models, "use cases", and/or references to exemplary technical solutions, devices, processes or software).

Any such exemplary items are contained in the specifications for illustration purposes only, and they themselves are not part of the AUTOSAR Standard. Neither their presence in such specifications, nor any later documentation of AUTOSAR conformance of products actually implementing such exemplary items, imply that intellectual property rights covering such exemplary items are licensed under the same rules as applicable to the AUTOSAR Standard.

Table of Contents

1	Introduction and functional overview	5
2	Acronyms, Abbreviations, and Definitions	7
3	Related documentation.....	8
3.1	Input documents.....	8
3.2	Related specification	8
4	Constraints and assumptions	9
4.1	Limitations	9
4.2	Applicability to car domains	9
5	Dependencies to other modules	10
5.1	File structure.....	12
5.1.1	Code file structure.....	12
5.1.2	Header file structure.....	12
6	Requirements traceability	14
7	Functional specification	16
7.1	Overview	16
7.2	Module Handling	16
7.2.1	Initialization	16
7.2.2	Flexray Interface	17
7.3	Message Format.....	17
7.3.1	SYNC message	18
7.3.2	OFS message	19
7.4	Acting as Time Master.....	20
7.4.1	SYNC message processing	21
7.4.2	OFS message processing.....	21
7.4.3	Transmission mode.....	22
7.4.4	Calculation and Assembling of Time Synchronization Messages on FlexRay	22
7.5	Acting as Time Slave.....	24
7.5.1	SYNC message processing	24
7.5.2	OFS message processing.....	25
7.5.3	Validation and Disassembling of Time Synchronization Messages on FlexRay	26
7.6	Error Classification	29
7.7	Error Detection	29
7.8	Error Notification.....	29
8	API specification	30
8.1	API.....	30
8.1.1	Imported types	30
8.1.2	Type definitions.....	30
8.1.3	Function definitions	31

8.1.4	Call-back notifications	32
8.1.5	Scheduled functions.....	34
8.1.6	Expected Interfaces	36
9	Sequence diagrams	37
9.1	StbM_GetCurrentTime <Master FR SYNC>.....	37
9.2	StbM_BusSetGlobalTime <Slave FR SYNC>	38
10	Configuration specification.....	39
10.1	How to read this chapter	39
10.2	Containers and configuration parameters	40
10.2.1	Variants	40
10.2.2	FrTSyn.....	40
10.2.3	FrTSynGeneral	41
10.2.4	FrTSynGlobalTimeSyncDataIDList	42
10.2.5	FrTSynGlobalTimeSyncDataIDListElement	44
10.2.6	FrTSynGlobalTimeOfsDataIDList	45
10.2.7	FrTSynGlobalTimeOfsDataIDListElement	46
10.2.8	FrTSynGlobalTimeDomain	47
10.2.9	FrTSynGlobalTimeMaster.....	49
10.2.10	FrTSynGlobalTimeMasterPdu	50
10.2.11	FrTSynGlobalTimeSlave.....	51
10.2.12	FrTSynGlobalTimeSlavePdu	53
10.3	Published Information.....	55

1 Introduction and functional overview

The FrTSyn module handles the distribution of time information over FlexRay busses.

The FlexRay mechanism is much simpler than the mechanism for CAN since it is based on the fact, that FlexRay nodes are synchronized to each other, otherwise no messages can be transmitted on FlexRay.

Both, Time Master and Time Slaves have the same view on the FlexRay global time. It is therefore just necessary to define the same point in (FlexRay) time and to transmit the time information, which will be valid at that point in (FlexRay) time.

Although this same point in (FlexRay) time could be in theory any FlexRay macrotick within a FlexRay cycle. The start of a FlexRay cycle simplifies this mechanism. In addition, the mechanism does not just use any cycle start but uses the cycle start of the subsequent cycle with cycle counter value 0, i.e. the Time Master transmits time information located in the future.

On FlexRay only one synchronization message is needed.

The Time Master uses its current FlexRay time, i.e. macrotick counter and cycle counter, and the current time, which shall be distributed and calculates the resulting time at the start of the next cycle 0. Once this resulting time has been calculated, it is neither very time critical, when exactly the FlexRay frame is transmitted, nor when it is received and processed.

Every Time Slave receiving the transmitted time information will use it in combination with the current FlexRay macrotick counter and cycle counter to determine the actual master time and set its slave time.

The following Figure shows the time synchronization mechanism on FlexRay.




Figure 1: FlexRay time synchronization mechanism

2 Acronyms, Abbreviations, and Definitions

This section lists module local Abbreviations and Definitions. For a complete set of Synchronized Time Base related Abbreviations and Definitions refer to the corresponding chapter in [3].

Abbreviation / Acronym:	Description
(G)TD	(Global) Time Domain
(G)TM	(Global)Time Master
<Bus>TSyn	A bus specific Time Synchronization Provider module
CRC	Cyclic Redundancy Checksum
DEM	Diagnostic Event Manager
DET	Development Error Tracer
FR	Flexray
FUP message	Time adjustment message (Follow-Up)
OFNS message	Offset adjustment message
OFS message	Offset synchronization message
StbM	Synchronized Time-Base Manager
SYNC message	Time synchronization message
TG	Time Gateway
TS	Time Slave
TSD	Time Sub-domain

3 Related documentation

3.1 Input documents

- [1] AUTOSAR Layered Software Architecture
AUTOSAR_EXP_LayeredSoftwareArchitecture.pdf
- [2] AUTOSAR General Specification of Basic Software Modules
AUTOSAR_SWS_BSWGeneral.pdf
- [3] AUTOSAR Synchronized Time Base Manager
AUTOSAR_SWS_SynchronizedTimeBaseManager.pdf
- [4] AUTOSAR Specification of CRC Routines
AUTOSAR_SWS_CRCLibrary.pdf

3.2 Related specification

AUTOSAR provides a General Specification on Basic Software (SWS BSW General [2]) which is also valid for FrTSyn.

Thus, the General Specification on Basic Software (SWS BSW General) shall be considered additionally and as required specification for FrTSyn.

4 Constraints and assumptions

4.1 Limitations

Time Master and Time Slaves shall work with a Time Base reference clock with a worst-case accuracy of 10µs.

4.2 Applicability to car domains

Systems requiring a common Time Base to ECUs independent to which bus system the ECU is connected.

5 Dependencies to other modules

The Time Synchronization over FlexRay (FrTSyn) has interfaces towards the Synchronized Time Base Manager (StbM), the FlexRay Interface (Frlf) and the Development Error Tracer (DET).




Figure 2: Module dependencies of the FrTSyn module

- StbM – Get and set the current time value

- FrIf – Receiving and transmitting messages
- BswM – Coordination of network access (via `FrTSyn_SetTransmissionMode()`)
- DET – Reporting of development errors

5.1 File structure

5.1.1 Code file structure

For details, refer to the section 5.1.6 "Code file structure" of the SWS BSW General [2].

5.1.2 Header file structure

Besides the files defined in section 5.1.7 "Header file structure" of the SWS BSW General [2], the Time Synchronization over FlexRay needs to include the files defined below.

[SWS_FrTSyn_00002]

[The implementation header files shall include `ComStack_Types.h`.

] (SRS_BSW_00301, SRS_BSW_00456)

The following picture shows the include hierarchy of the Time Synchronization over FlexRay.




Figure 3: File structure of FrTSyn

6 Requirements traceability

Requirement	Description	Satisfied by
SRS_BSW_00301	All AUTOSAR Basic Software Modules shall only import the necessary information	SWS_FrTSyn_00002
SRS_BSW_00323	All AUTOSAR Basic Software Modules shall check passed API parameters for validity	SWS_FrTSyn_00058, SWS_FrTSyn_00067, SWS_FrTSyn_00070
SRS_BSW_00337	Classification of development errors	SWS_FrTSyn_00004, SWS_FrTSyn_00067, SWS_FrTSyn_00070, SWS_FrTSyn_00073
SRS_BSW_00385	List possible error notifications	SWS_FrTSyn_00059
SRS_BSW_00396	The Basic Software Module specifications shall specify the supported configuration classes for changing values and multiplicities for each parameter/container	SWS_FrTSyn_00076
SRS_BSW_00456	- A Header file shall be defined in order to harmonize BSW Modules	SWS_FrTSyn_00002
SRS_StbM_20017	The StbM shall initialize the local time base if configured as Time Slave	SWS_FrTSyn_00003, SWS_FrTSyn_00005
SRS_StbM_20018	The StbM shall initialize the local time base with 0 at startup if configured as Time Slave	SWS_FrTSyn_00003, SWS_FrTSyn_00005
SRS_StbM_20019	The StbM shall initialize the global time base with a configurable startup value if configured as Time Master	SWS_FrTSyn_00003, SWS_FrTSyn_00005
SRS_StbM_20035	The CAN TimeSync module shall support a protocol for precise time measurement and synchronization over CAN	SWS_FrTSyn_00074
SRS_StbM_20038	The CAN TimeSync configuration shall allow the CanTSyn to support different roles for a time base	SWS_FrTSyn_00077
SRS_StbM_20039	The FlexRay TimeSync module shall trigger time base synchronization transmission	SWS_FrTSyn_00018, SWS_FrTSyn_00019, SWS_FrTSyn_00023, SWS_FrTSyn_00026, SWS_FrTSyn_00027
SRS_StbM_20040	The FlexRay TimeSync module shall provide a time base after reception of a valid protocol information	SWS_FrTSyn_00041, SWS_FrTSyn_00045, SWS_FrTSyn_00078
SRS_StbM_20041	The FlexRay TimeSync module shall support means to protect the time synchronization	SWS_FrTSyn_00006, SWS_FrTSyn_00014, SWS_FrTSyn_00015, SWS_FrTSyn_00016, SWS_FrTSyn_00017, SWS_FrTSyn_00021,

	protocol	SWS_FrTSyn_00025, SWS_FrTSyn_00030, SWS_FrTSyn_00031, SWS_FrTSyn_00032, SWS_FrTSyn_00033, SWS_FrTSyn_00034, SWS_FrTSyn_00035, SWS_FrTSyn_00036, SWS_FrTSyn_00078
SRS_StbM_20042	The FlexRay TimeSync Module shall detect and handle timeout and integrity errors in the time synchronization protocol	SWS_FrTSyn_00015, SWS_FrTSyn_00017, SWS_FrTSyn_00038, SWS_FrTSyn_00041, SWS_FrTSyn_00042, SWS_FrTSyn_00045, SWS_FrTSyn_00048, SWS_FrTSyn_00049, SWS_FrTSyn_00050, SWS_FrTSyn_00051, SWS_FrTSyn_00052, SWS_FrTSyn_00053, SWS_FrTSyn_00054, SWS_FrTSyn_00055, SWS_FrTSyn_00057, SWS_FrTSyn_00058
SRS_StbM_20043	The FlexRay TimeSync module shall support a protocol for precise time measurement and synchronization over FlexRay	SWS_FrTSyn_00007, SWS_FrTSyn_00008, SWS_FrTSyn_00009, SWS_FrTSyn_00010, SWS_FrTSyn_00014, SWS_FrTSyn_00015, SWS_FrTSyn_00016, SWS_FrTSyn_00017, SWS_FrTSyn_00018, SWS_FrTSyn_00019, SWS_FrTSyn_00020, SWS_FrTSyn_00021, SWS_FrTSyn_00022, SWS_FrTSyn_00023, SWS_FrTSyn_00024, SWS_FrTSyn_00025, SWS_FrTSyn_00026, SWS_FrTSyn_00027, SWS_FrTSyn_00028, SWS_FrTSyn_00029, SWS_FrTSyn_00030, SWS_FrTSyn_00031, SWS_FrTSyn_00032, SWS_FrTSyn_00033, SWS_FrTSyn_00034, SWS_FrTSyn_00035, SWS_FrTSyn_00036, SWS_FrTSyn_00037, SWS_FrTSyn_00038, SWS_FrTSyn_00039, SWS_FrTSyn_00040, SWS_FrTSyn_00041, SWS_FrTSyn_00042, SWS_FrTSyn_00043, SWS_FrTSyn_00044, SWS_FrTSyn_00045, SWS_FrTSyn_00046, SWS_FrTSyn_00047, SWS_FrTSyn_00048, SWS_FrTSyn_00049, SWS_FrTSyn_00050, SWS_FrTSyn_00051, SWS_FrTSyn_00052, SWS_FrTSyn_00053, SWS_FrTSyn_00054, SWS_FrTSyn_00055, SWS_FrTSyn_00056, SWS_FrTSyn_00057, SWS_FrTSyn_00060, SWS_FrTSyn_00061, SWS_FrTSyn_00062, SWS_FrTSyn_00063, SWS_FrTSyn_00064, SWS_FrTSyn_00065, SWS_FrTSyn_00066, SWS_FrTSyn_00068, SWS_FrTSyn_00069, SWS_FrTSyn_00071, SWS_FrTSyn_00072, SWS_FrTSyn_00075
SRS_StbM_20044	The FlexRay TimeSync module shall use the time measurement and synchronization protocol to transmit and receive an offset value	SWS_FrTSyn_00022, SWS_FrTSyn_00023, SWS_FrTSyn_00025, SWS_FrTSyn_00042, SWS_FrTSyn_00043, SWS_FrTSyn_00044, SWS_FrTSyn_00047, SWS_FrTSyn_00049
SRS_StbM_20045	The FlexRay TimeSync module shall support user specific data within the time measurement and synchronization protocol	SWS_FrTSyn_00008, SWS_FrTSyn_00010, SWS_FrTSyn_00011, SWS_FrTSyn_00012, SWS_FrTSyn_00013

7 Functional specification

This chapter defines the behavior of the Time Synchronization over FlexRay. The API of the module is defined in chapter 8, while the configuration is defined in chapter 10.

7.1 Overview

The Time Synchronization over FlexRay is responsible to ensure the collection and distribution of synchronized time information across the FlexRay network. It interacts with the StbM and provides all FlexRay specific functions to the StbM. Time synchronization principles and common wording is described in [3].

7.2 Module Handling

This section contains description of auxiliary functionality of the Time Synchronization over FlexRay.

7.2.1 Initialization

The Time Synchronization over FlexRay is initialized via `FrTSyn_Init()`. Except for `FrTSyn_GetVersionInfo()` and `FrTSyn_Init()`, the API functions of the Time Synchronization over FlexRay may only be called when the module has been properly initialized.

[SWS_FrTSyn_00003]

[A call to `FrTSyn_Init()` initializes all internal variables and sets the Time Synchronization over FlexRay to the initialized state.]

](SRS_StbM_20017, SRS_StbM_20018, SRS_StbM_20019)

[SWS_FrTSyn_00004]

[When DET reporting is enabled (see `FrTSynDevErrorDetect`), the Time Synchronization over FlexRay shall call `Det_ReportError` with the error code `FRTSYN_E_NOT_INITIALIZED` when any API other than `FrTSyn_GetVersionInfo()` or `FrTSyn_Init()` is called in uninitialized state.]

](SRS_BSW_00337)

[SWS_FrTSyn_00005]

[When `FrTSyn_Init()` is called in initialized state, the Time Synchronization over FlexRay shall re-initialize its internal variables.]

](SRS_StbM_20017, SRS_StbM_20018, SRS_StbM_20019)

[SWS_FrTSyn_00006]

[Sequence Counter (SC) shall be initialized with 0.]

](SRS_StbM_20041)

7.2.2 Flexray Interface

[SWS_FrTSyn_00078]

[The FrTSyn module shall call Fr_GetGlobalTime() only if FrIf_GetState() returns FRIF_STATE_ONLINE. This is to ensure that Fr_GetGlobalTime returns valid time information, i.e. that the Flexray communication controller is synchronous to the Flexray global time.] (SRS_StbM_20040, SRS_StbM_20041)

7.3 Message Format

SYNC and OFS messages are assigned to a dedicated SLOT ID of the Static Segment.

SYNC and OFS messages share the same FR PDU by using a multiplexed signal group. The Multiplexer is located at Byte 0, named as "Type".

The usage of *CRC* is optional. To ensure a great variability between several time observing units, the configuration decides of how to handle *CRC* secured time stamp messages if the receiver does not support the *CRC* calculation. It means, it might be possible, that a receiver is just using the given Time Base value, without evaluating the *CRC*.

[SWS_FrTSyn_00007]

[The byte order for time synchronization message time stamp signals is "Big Endian".](SRS_StbM_20043)

[SWS_FrTSyn_00008]

[The byte order for time synchronization message User Data bytes is "Opaque".](SRS_StbM_20043, SRS_StbM_20045)

[SWS_FrTSyn_00009]

[The PayloadLength is 16.](SRS_StbM_20043)

[SWS_FrTSyn_00010]

[Each time synchronization message contains User Data according to the given message format.](SRS_StbM_20043, SRS_StbM_20045)

[SWS_FrTSyn_00011]

[User Data shall be read from the current incoming message consistently.](SRS_StbM_20045)

[SWS_FrTSyn_00012]

[User Data shall be written to the next outgoing message consistently.](SRS_StbM_20045)

[SWS_FrTSyn_00013]

[User Data shall be mapped to the `StbM_UserDataType`, whereas the byte number given in the message and by the `StbM_UserDataType` shall match (User Byte 0 mapped to `StbM_UserDataType.userByte0` etc.). Afterwards `StbM_UserDataType.userDataLength` shall be set accordingly.
](SRS_StbM_20045)

7.3.1 SYNC message

[SWS_FrTSyn_00014]

[SYNC not CRC secured message format:

Byte 0: *Type* = 0x10
Byte 1: User Byte 2, default: 0
Byte 2: *D* = Time Domain 0 to 15 (Bit 7 to Bit 4)
 SC = Sequence Counter (Bit 3 to Bit 0)
Byte 3: *FCNT* = FlexRay Cycle Counter from 0 to 63 (Bit 7 to Bit 2)
 SGW (Bit 1)
 SyncToGTM = 0
 SyncToSubDomain = 1
 reserved (Bit 0), default: 0
Byte 4: User Byte 0, default: 0
Byte 5: User Byte 1, default: 0
Byte 6-11: *SyncTimeSec* = 48 Bit time stamp in seconds
Byte 12-15: *SyncTimeNSec* = 32 Bit time stamp in nanoseconds
](SRS_StbM_20041, SRS_StbM_20043)

[SWS_FrTSyn_00015]

[SYNC CRC secured message format:

Byte 0: *Type* = 0x20
Byte 1: *CRC*
Byte 2: *D* = Time Domain 0 to 15 (Bit 7 to Bit 4)
 SC = Sequence Counter (Bit 3 to Bit 0)
Byte 3: *FCNT* = FlexRay Cycle Counter from 0 to 63 (Bit 7 to Bit 2)
 SGW (Bit 1)
 SyncToGTM = 0
 SyncToSubDomain = 1
 reserved (Bit 0), default: 0
Byte 4: User Byte 0, default: 0
Byte 5: User Byte 1, default: 0
Byte 6-11: *SyncTimeSec* = 48 Bit time stamp in seconds
Byte 12-15: *SyncTimeNSec* = 32 Bit time stamp in nanoseconds
](SRS_StbM_20041, SRS_StbM_20042, SRS_StbM_20043)

7.3.2 OFS message

Offset messages are multiplexed with the SYNC message (using the same PDU, etc.).

[SWS_FrTSyn_00016]

[OFS not CRC secured message format:

Byte 0: Type = 0x30

Byte 1: User Byte 3, default: 0

Byte 2: D = Time Domain 16 to 31 (Bit 7 to Bit 4)

SC = Sequence Counter (Bit 3 to Bit 0)

Byte 3: User Byte 0, default: 0

Byte 4: User Byte 1, default: 0

Byte 5: User Byte 2, default: 0

Byte 6-11: OfsTimeSec = 48 Bit offset time stamp in seconds

Byte 12-15: OfsTimeNSec = 32 Bit offset time stamp in nanoseconds

] (SRS_StbM_20041, SRS_StbM_20043)

[SWS_FrTSyn_00017]

[OFS CRC secured message format:

Byte 0: Type = 0x40

Byte 1: CRC

Byte 2: D = Time Domain 16 to 31 (Bit 7 to Bit 4)

SC = Sequence Counter (Bit 3 to Bit 0)

Byte 3: User Byte 0, default: 0

Byte 4: User Byte 1, default: 0

Byte 5: User Byte 2, default: 0

Byte 6-11: OfsTimeSec = 48 Bit offset time stamp in seconds

Byte 12-15: OfsTimeNSec = 32 Bit offset time stamp in nanoseconds

] (SRS_StbM_20041, SRS_StbM_20042, SRS_StbM_20043)

7.4 Acting as Time Master

A Time Master is an entity which is the master for a certain Time Base and which propagates this Time Base to a set of Time Slaves within a certain segment of a communication network, being a source for this Time Base.

If a Time Master is also the owner of the Global Time Base, the Time Base from which all further Time Bases derived, then it is the Global Time Master. A Time Gateway typically consists of one Time Master port which is connected to one or more Time Slaves. When mapping time entities to real ECUs it has to be noted, that an ECU could be Time Master (or even Global Time Master) for one Time Base and Time Slave for another Time Base.




Figure 4: Terminology Example

[SWS_FrTSyn_00024]

[The FrTSyn module shall transmit in one FlexRay cycle either SYNC or OFS message.

] (SRS_StbM_20043)

7.4.1 SYNC message processing

[SWS_FrTSyn_00018]

[A synchronization message sequence consists of a SYNC message per Time Domain transmitted once per FlexRay cycle.

] (SRS_StbM_20039, SRS_StbM_20043)

[SWS_FrTSyn_00019]

[For each configured Time Master (`FrTSynGlobalTimeMaster`) the FrTSyn module shall periodically transmit a SYNC messages with the cycle `FrTSynGlobalTimeTxPeriod` (**ECUC_FrTSyn_00014** :) including the time stamp that will be valid at the next FlexRay cycle 0 (see Figure 5: Master FR SYNC).

] (SRS_StbM_20039, SRS_StbM_20043)

[SWS_FrTSyn_00021]

[Depending on `FrTSynGlobalTimeTxCrcSecured` the SYNC message shall be of type:

<code>FrTSynGlobalTimeTxCrcSecured</code>	SYNC
<code>CRC_NOT_SUPPORTED</code>	0x10 SYNC not CRC secured message
<code>CRC_SUPPORTED</code>	0x20 SYNC CRC secured message

] (SRS_StbM_20041, SRS_StbM_20043)

7.4.2 OFS message processing

[SWS_FrTSyn_00022]

[An offset message sequence consists of an OFS message per Time Domain transmitted once per FlexRay cycle.

] (SRS_StbM_20043, SRS_StbM_20044)

[SWS_FrTSyn_00023]

[For each configured Time Master (`FrTSynGlobalTimeMaster`) the FrTSyn module shall periodically transmit a OFS messages with the cycle `FrTSynGlobalTimeTxPeriod` (**ECUC_FrTSyn_00014** :) including the offset time stamp.

] (SRS_StbM_20039, SRS_StbM_20043, SRS_StbM_20044)

[SWS_FrTSyn_00025]

[Depending on `FrTSynGlobalTimeTxCrcSecured` the OFS message shall be of type:

<code>FrTSynGlobalTimeTxCrcSecured</code>	OFS
<code>CRC_NOT_SUPPORTED</code>	0x30 OFS not CRC secured message
<code>CRC_SUPPORTED</code>	0x40 OFS CRC secured message

] (SRS_StbM_20041, SRS_StbM_20043, SRS_StbM_20044)

7.4.3 Transmission mode

[SWS_FrTSyn_00026]

If `FrTSyn_SetTransmissionMode(Controller, Mode)` is called and parameter `Mode` equals `FRTSYN_TX_OFF`, all transmit request from FrTSyn shall be omitted on this FlexRay channel.

](SRS_StbM_20039, SRS_StbM_20043)

[SWS_FrTSyn_00027]

If `FrTSyn_SetTransmissionMode(Controller, Mode)` is called and parameter `Mode` equals `FRTSYN_TX_ON`, all transmit request from FrTSyn on this FlexRay channel shall be able to be transmitted.

](SRS_StbM_20039, SRS_StbM_20043)

7.4.4 Calculation and Assembling of Time Synchronization Messages on FlexRay

This chapter describes the workflow, how the items of a time synchronization message will be calculated (1st step) and how the message will be assembled (2nd step).

7.4.4.1 Global Time Calculation

[SWS_FrTSyn_00028]

The transmitter of a Synchronized Time Base (Time Master) shall perform the following steps to distribute the Synchronized Time Base:

1. Get `currentCycle` and `currentMacroticks` from FlexRay driver
2. Retrieve current Synchronized Time Base as T_{SYNC} via
`StbM_GetCurrentTime()`
3. Calculate the time stamp (in future) of the start of the next FlexRay cycle, where the subsequent SYNC message will sent with
$$T0 = T_{SYNC} + (\text{MacroticksPerCycle} * (64 - \text{currentCycle}) - \text{currentMacroticks}) * \text{MacrotickDuration}$$
4. Calculate `SyncTimeSec` (second portion of $T0$) and `SyncTimeNSec` (nanosecond portion of $T0$)

](SRS_StbM_20043)

Note: `MacroticksPerCycle` and `MacrotickDuration` are given statically by configuration.

[SWS_FrTSyn_00029]

[The transmitter of an Offset Time Base (Time Master) shall perform the following steps to distribute the Offset Time Base:

1. Get second portion of the Offset Time Base and write to *OfsTimeSec*
2. Get nanosecond portion of the Offset Time and write to *OfsTimeNSec*

](SRS_StbM_20043)

Note: The Offset Time Base has not been time stamped.

7.4.4.2 SGW Calculation

[SWS_FrTSyn_00020]

[The SGW value (Time Gateway synchronization status) shall be retrieved from the time base synchronization status. If the `SYNC_TO_GATEWAY` bit within `timeBaseStatus` is not set the SGW value shall be *SyncToGTM*. Otherwise the SGW value shall be set to *SyncToSubDomain*.

](SRS_StbM_20043)

7.4.4.3 Sequence Counter Calculation

[SWS_FrTSyn_00030]

[A Sequence Counter (SC) of 4bit is representing numbers from 0 to 15 per Time Domain. The Sequence Counter is independent between SYNC and OFS messages and shall be incremented by 1 continuously on every transmission request of a SYNC or OFS message. It wraps around at 15 to 0 again.

](SRS_StbM_20041, SRS_StbM_20043)

7.4.4.4 CRC Calculation

[SWS_FrTSyn_00031]

[The function `Crc_CalculateCRC8H2F()` as defined in [4] shall be used to calculate the CRC if configured.

](SRS_StbM_20041, SRS_StbM_20043)

[SWS_FrTSyn_00032]

[The CRC start value shall be 0xFF.

](SRS_StbM_20041, SRS_StbM_20043)

[SWS_FrTSyn_00033]

[The CRC final XOR-value shall be 0xFF.

](SRS_StbM_20041, SRS_StbM_20043)

[SWS_FrTSyn_00034]

[The CRC polynomial shall be 0x2F.

](SRS_StbM_20041, SRS_StbM_20043)

[SWS_FrTSyn_00035]

[The `DataID` will be calculated as `DataID = DataIDList[SC]`, whereat `DataIDList` is given by configuration for each message *Type*.]

](SRS_StbM_20041, SRS_StbM_20043)

A specific `DataID` out of a predefined `DataIDList` ensures the identification of data elements of time synchronization messages.

[SWS_FrTSyn_00036]

[The `CRC` will be calculated over time synchronization message *Byte 2 to Byte 15* and `DataID`.]

](SRS_StbM_20041, SRS_StbM_20043)

7.4.4.5 Message Assembling

[SWS_FrTSyn_00037]

[For each transmission of a time synchronization message the FrTSyn module shall assemble the message like follows:

1. Calculate `SC`
2. Calculate `FCNT`
3. Calculate `SGW`
4. Copy all data to the appropriate position within the related message
5. Calculate `CRC` (configuration dependent)

](SRS_StbM_20043)

7.5 Acting as Time Slave

A Time Slave is an entity, which is the recipient for a certain Time Base within a certain segment of a communication network, being a consumer for this Time Base.

7.5.1 SYNC message processing

[SWS_FrTSyn_00038]

[The FrTSyn shall only accept SYNC message with *Type* equal to `0x20` and a correct `CRC` value if `FrTSynRxCrcValidated` is configured to `CRC_VALIDATED`. All other messages shall be ignored.]

](SRS_StbM_20042, SRS_StbM_20043)

[SWS_FrTSyn_00039]

[The FrTSyn shall only accept SYNC message with *Type* equal to `0x10` if `FrTSynRxCrcValidated` is configured to `CRC_NOT_VALIDATED`. All other messages shall be ignored.]

](SRS_StbM_20043)

[SWS_FrTSyn_00040]

[The FrTSyn shall only accept SYNC message with *Type* equal to `0x10` or `0x20` if `FrTSynRxCrcValidated` is configured to `CRC_IGNORED`. All other messages shall be ignored.] (SRS_StbM_20043)

[SWS_FrTSyn_00041]

[For valid SYNC messages a new Global Time value shall be calculated and forwarded to the StbM module via `StbM_BusSetGlobalTime()` (see Figure 6: Slave FR SYNC).]

] (SRS_StbM_20040, SRS_StbM_20042, SRS_StbM_20043)

7.5.2 OFS message processing

[SWS_FrTSyn_00042]

[The FrTSyn shall only accept OFS message with *Type* equal to `0x40` and a correct CRC value if `FrTSynRxCrcValidated` is configured to `CRC_VALIDATED`. All other messages shall be ignored.]

] (SRS_StbM_20042, SRS_StbM_20043, SRS_StbM_20044)

[SWS_FrTSyn_00043]

[The FrTSyn shall only accept OFS message with *Type* equal to `0x30` if `FrTSynRxCrcValidated` is configured to `CRC_NOT_VALIDATED`. All other messages shall be ignored.]

] (SRS_StbM_20043, SRS_StbM_20044)

[SWS_FrTSyn_00044]

[The FrTSyn shall only accept OFS message with *Type* equal to `0x30` or `0x40` if `FrTSynRxCrcValidated` is configured to `CRC_IGNORED`. All other messages shall be ignored.]

] (SRS_StbM_20043, SRS_StbM_20044)

[SWS_FrTSyn_00045]

[For valid OFS messages a new offset time value shall be calculated (according to **[SWS_FrTSyn_00047]**) and forwarded to the StbM module via `StbM_SetOffset()`.]

] (SRS_StbM_20040, SRS_StbM_20042, SRS_StbM_20043)

7.5.3 Validation and Disassembling of Time Synchronization Messages on FlexRay

This chapter describes the workflow, how the items of a time synchronization message will be validated (1st step) and how the message will be disassembled (2nd step).

7.5.3.1 Global Time Calculation

[SWS_FrTSyn_00046]

[The receiver of a Synchronized Time Base (Time Slave) shall perform the following steps to assemble the Synchronized Time Base:

1. On SYNC message RX indication store received time stamp T0 (*SyncTimeSec*, *SyncTimeNSec*)
2. Get *currentCycle* and *currentMacroticks* from FlexRay driver
3. Calculate T1 to update the Time Slaves Local Time Base as:
$$T1 = T0 + (((\text{MacroticksPerCycle} * \text{currentCycle}) + \text{currentMacroticks}) * \text{MacrotickDuration})$$
4. If the *currentCycle* has passed the retrieved *FCNT* from the transmitter side then the previously calculated T1 must be adjusted by the maximum of the cycle counter to:
$$T1 = T1 - (\text{MacroticksPerCycle} * 64 * \text{MacrotickDuration})$$

J(SRS_StbM_20043)

Note: *MacroticksPerCycle* and *MacrotickDuration* are given statically by configuration.

[SWS_FrTSyn_00047]

[The receiver of an Offset Time Base (Time Slave) shall perform the following steps to assemble the Offset Time Base:

1. Get second portion of the Offset Time Base out of *OfsTimeSec*
2. Get nanosecond portion of the Offset Time out of *OfsTimeNSec*

J(SRS_StbM_20043, SRS_StbM_20044)

Note: The Offset Time Base has not been time stamped.

7.5.3.2 Sequence Counter Validation

[SWS_FrTSyn_00048]

[The Sequence Counter Jump Width between two SYNC resp. two OFS messages must be always smaller or equal to `FrTSynGlobalTimeSequenceCounterJumpWidth`. The value 0 is not allowed.

](SRS_StbM_20042, SRS_StbM_20043)

[SWS_FrTSyn_00049]

[Due to an asynchronous startup of Time Slaves compared to the Time Master the 1st Sequence Counter of the 1st received SYNC and OFS message per Time Domain shall not be checked against the defined Sequence Counter Jump Width.

](SRS_StbM_20042, SRS_StbM_20043, SRS_StbM_20044)

7.5.3.3 CRC Validation

[SWS_FrTSyn_00050]

[The function `Crc_CalculateCRC8H2F()` as defined in [4] shall be used to validate the CRC if configured.

](SRS_StbM_20042, SRS_StbM_20043)

[SWS_FrTSyn_00051]

[The CRC start value shall be 0xFF.

](SRS_StbM_20042, SRS_StbM_20043)

[SWS_FrTSyn_00052]

[The CRC final XOR-value shall be 0xFF.

](SRS_StbM_20042, SRS_StbM_20043)

[SWS_FrTSyn_00053]

[The CRC polynomial shall be 0x2F.

](SRS_StbM_20042, SRS_StbM_20043)

[SWS_FrTSyn_00054]

[The `DataID` will be calculated as `DataID = DataIDList[SC]`, whereat `DataIDList` is given by configuration for each message `Type`.

](SRS_StbM_20042, SRS_StbM_20043)

A specific `DataID` out of a predefined `DataIDList` ensures the identification of data elements of time synchronization messages.

[SWS_FrTSyn_00055]

[The CRC will be calculated over time synchronization message `Byte 2` to `Byte 15` and `DataID`.

](SRS_StbM_20042, SRS_StbM_20043)

7.5.3.4 Message Disassembling

[SWS_FrTSyn_00056]

[For each received time synchronization message the FrTSyn module shall validate the message like follows (all conditions must match):

1. Type matches depending on the `FrTSynRxCrcValidated` parameter.
2. SC matches to the expected value.
3. D matches to the defined Time Domain range for each Type
4. D matches to one of the configured Time Domains
5. Time stamp matches the defined range of `StbM_TimeStampType.nanoseconds`.
6. CRC (including `DataID`) matches depending on the `FrTSynRxCrcValidated` parameter.

] (SRS_StbM_20043)

[SWS_FrTSyn_00057]

[For each received time synchronization message the FrTSyn module shall disassemble the message after successful validation [SWS_FrTSyn_00056].

] (SRS_StbM_20042, SRS_StbM_20043)

7.6 Error Classification

This chapter lists and classifies all errors that can be detected by this software module. Each error is classified to relevance (development / production) and the related error code (unique label for the error). For development errors this table also specifies the unique values, which correspond to the error codes.

[SWS_FrTSyn_00058]

[On errors and exceptions, the FrTSyn module shall not modify its current module state but shall simply report the error event.
](SRS_StbM_20042, SRS_BSW_00323)

[SWS_FrTSyn_00059]

[FrTSyn shall use following errors:

Type or error	Relevance	Related error code	Value [hex]
API service called with wrong PDU or SDU.	Development	FRTSYN_E_INVALID_PDUID	0x01
API service used in un-initialized state	Development	FRTSYN_E_NOT_INITIALIZED	0x20
A pointer is invalid	Development	FRTSYN_E_NULL_POINTER	0x21

](SRS_BSW_00385)

7.7 Error Detection

The detection of development errors is configurable (see section 10.2, FrTSynDevErrorDetect).

7.8 Error Notification

The module ID 163 of FrTSyn, which is used as a parameter in the Det_ReportError() call, is exported via the macro definition FRTSYN_MODULE_ID in FrTSyn.h.

8 API specification

8.1 API

8.1.1 Imported types

In this section all types included from the following files are listed:

[SWS_FrTSyn_00060]

Module	Imported Type
ComStack_Types	PduldType
	PdulInfoType
Frlf	Frlf_StateType
StbM	StbM_SynchronizedTimeBaseType
	StbM_TimeStampType
	StbM_UserDataType
Std_Types	Std_ReturnType
	Std_VersionInfoType

] (SRS_StbM_20043)

8.1.2 Type definitions

8.1.2.1 FrTSyn_ConfigType

[SWS_FrTSyn_00061]

Name:	FrTSyn_ConfigType		
Type:	Structure		
Element:	void	implementation specific	--
Description:	<p>This is the base type for the configuration of the Time Synchronization over FlexRay.</p> <p>A pointer to an instance of this structure will be used in the initialization of the Time Synchronization over FlexRay.</p> <p>The content of this structure is defined in chapter 10 Configuration specification.</p>		

] (SRS_StbM_20043)

8.1.2.2 FrTSyn_TransmissionModeType

[SWS_FrTSyn_00062]

Name:	FrTSyn_TransmissionModeType	
Type:	Enumeration	
Range:	FRTSYN_TX_OFF	Transmission Disabled
	FRTSYN_TX_ON	Transmission Enabled
Description:	Handles the enabling and disabling of the transmission mode	

] (SRS_StbM_20043)

8.1.3 Function definitions

8.1.3.1 FrTSyn_Init

[SWS_FrTSyn_00063]

Service name:	FrTSyn_Init	
Syntax:	<pre>void FrTSyn_Init(const FrTSyn_ConfigType* configPtr)</pre>	
Service ID[hex]:	0x01	
Sync/Async:	Synchronous	
Reentrancy:	Non Reentrant	
Parameters (in):	configPtr	Pointer to selected configuration structure
Parameters (inout):	None	
Parameters (out):	None	
Return value:	None	
Description:	This function initializes the Time Synchronization over FlexRay.	

] (SRS_StbM_20043)

See section 7.2.1 for details.

8.1.3.2 FrTSyn_GetVersionInfo

[SWS_FrTSyn_00064]

Service name:	FrTSyn_GetVersionInfo
Syntax:	void FrTSyn_GetVersionInfo(Std_VersionInfoType* versioninfo)
Service ID[hex]:	0x02
Sync/Async:	Synchronous
Reentrancy:	Non Reentrant
Parameters (in):	versioninfo Pointer to where to store the version information of this module.
Parameters (inout):	None
Parameters (out):	None
Return value:	None
Description:	Returns the version information of this module.

J(SRS_StbM_20043)

8.1.3.3 FrTSyn_SetTransmissionMode

[SWS_FrTSyn_00065]

Service name:	FrTSyn_SetTransmissionMode				
Syntax:	void FrTSyn_SetTransmissionMode(uint8 CtrlIdx, FrTSyn_TransmissionModeType Mode)				
Service ID[hex]:	0x03				
Sync/Async:	Synchronous				
Reentrancy:	Non Reentrant				
Parameters (in):	<table> <tr> <td>CtrlIdx</td> <td> Index of the FlexRay channel</td> </tr> <tr> <td>Mode</td> <td> FRTSYN_TX_OFF FRTSYN_TX_ON</td> </tr> </table>	CtrlIdx	Index of the FlexRay channel	Mode	FRTSYN_TX_OFF FRTSYN_TX_ON
CtrlIdx	Index of the FlexRay channel				
Mode	FRTSYN_TX_OFF FRTSYN_TX_ON				
Parameters (inout):	None				
Parameters (out):	None				
Return value:	None				
Description:	This API is used to turn on and off the TX capabilities of the FrTSyn.				

J(SRS_StbM_20043)

8.1.4 Call-back notifications

This is a list of functions provided for other modules. The function prototypes of the callback functions shall be provided in the file *FrTSyn_Cbk.h*.

8.1.4.1 FrTSyn_RxIndication

[SWS_FrTSyn_00066]

Service name:	FrTSyn_RxIndication
Syntax:	void FrTSyn_RxIndication(PduIdType RxPduId, const PduInfoType* PduInfoPtr)
Service ID[hex]:	0x42
Sync/Async:	Synchronous
Reentrancy:	Reentrant for different Pdulds. Non reentrant for the same Pduld.
Parameters (in):	RxPduId ID of the received I-PDU. PduInfoPtr Contains the length (SduLength) of the received I-PDU and a pointer to a buffer (SduDataPtr) containing the I-PDU.
Parameters (inout):	None
Parameters (out):	None
Return value:	None
Description:	Indication of a received I-PDU from a lower layer communication interface module.

] (SRS_StbM_20043)

Note: The callback function `FrTSyn_RxIndication` called by the FR Interface and implemented by the FrTSyn module. It is called in case of a receive indication event of the FR Driver.

[SWS_FrTSyn_00067]

[The callback function `FrTSyn_RxIndication()` shall inform the DET, if development error detection is enabled (`FRTSYN_DEV_ERROR_DETECT` is set to TRUE) and if function call has failed because of the following reasons:

- Invalid PDU ID (`FRTSYN_E_INVALID_PDUID`)
- FrTSyn was not initialized (`FRTSYN_E_NOT_INITIALIZED`)
- `PduInfoPtr` or `SduDataPtr` equals `NULL_PTR` (`FRTSYN_E_NULL_POINTER`)

] (SRS_BSW_00323, SRS_BSW_00337)

[SWS_FrTSyn_00068]

[Caveats of `FrTSyn_RxIndication()`:

- The FrTSyn module is initialized correctly.

] (SRS_StbM_20043)

8.1.4.2 FrTSyn_TriggerTransmit

[SWS_FrTSyn_00069]

Service name:	FrTSyn_TriggerTransmit	
Syntax:	<pre>Std_ReturnType FrTSyn_TriggerTransmit(PduIdType TxPduId, PduInfoType* PduInfoPtr)</pre>	
Service ID[hex]:	0x41	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant for different Pdulds. Non reentrant for the same Pduld.	
Parameters (in):	TxPduld	ID of the SDU that is requested to be transmitted.
Parameters (inout):	PduInfoPtr	Contains a pointer to a buffer (SduDataPtr) to where the SDU data shall be copied, and the available buffer size in SduLength. On return, the service will indicate the length of the copied SDU data in SduLength.
Parameters (out):	None	
Return value:	Std_ReturnType	E_OK: SDU has been copied and SduLength indicates the number of copied bytes. E_NOT_OK: No SDU data has been copied. PduInfoPtr must not be used since it may contain a NULL pointer or point to invalid data.
Description:	Within this API, the upper layer module (called module) shall check whether the available data fits into the buffer size reported by PduInfoPtr->SduLength. If it fits, it shall copy its data into the buffer provided by PduInfoPtr->SduDataPtr and update the length of the actual copied data in PduInfoPtr->SduLength. If not, it returns E_NOT_OK without changing PduInfoPtr.	

] (SRS_StbM_20043)

Note: The function `FrTSyn_TriggerTransmit()` might be called by the FrTSyn module's environment in an interrupt context.

[SWS_FrTSyn_00070]

The callback function `FrTSyn_TriggerTransmit()` shall inform the DET, if development error detection is enabled (`FRTSYN_DEV_ERROR_DETECT` is set to TRUE) and if function call has failed because of the following reasons:

- Invalid PDU ID (`FRTSYN_E_INVALID_PDUID`)
- FrTSyn was not initialized (`FRTSYN_E_NOT_INITIALIZED`)
- PduInfoPtr or SduDataPtr equals NULL_PTR (`FRTSYN_E_NULL_POINTER`)

] (SRS_BSW_00323, SRS_BSW_00337)

8.1.5 Scheduled functions

These functions are directly called by Basic Software Scheduler. The following functions shall have no return value and no parameters. All functions shall be non-reentrant.

8.1.5.1 FrTSyn_MainFunction

[SWS_FrTSyn_00071]

Service name:	FrTSyn_MainFunction
Syntax:	void FrTSyn_MainFunction(void)
Service ID[hex]:	0x04
Sync/Async:	Synchronous
Reentrancy:	Non Reentrant
Parameters (in):	None
Parameters (inout):	None
Parameters (out):	None
Return value:	None
Description:	Main function for cyclic call / resp. SYNC transmission

] (SRS_StbM_20043)

[SWS_FrTSyn_00072]

[The frequency of invocations of `FrTSyn_MainFunction()` is determined by the configuration parameter `FRTSYNMainFunctionPeriod`.

] (SRS_StbM_20043)

[SWS_FrTSyn_00073]

[The scheduled function `FrTSyn_MainFunction()` shall inform the DET, if development error detection is enabled (`FRTSYN_DEV_ERROR_DETECT` is set to TRUE) and if function call has failed because of the following reasons:

- The FrTSyn module was not initialized (`FRTSYN_E_NOT_INITIALIZED`).

] (SRS_BSW_00337)

8.1.6 Expected Interfaces

In this section, all interfaces required by other modules are listed.

8.1.6.1 Mandatory Interfaces

This section defines all interfaces that are required to fulfill a mandatory functionality of the module.

[SWS_FrTSyn_00074]

<i>API function</i>	<i>Description</i>
FrIf_GetGlobalTime	Wraps the FlexRay Driver API function Fr_GetGlobalTime().
FrIf_GetMacrotickDuration	Retrieves the Duration of a Macrotick in ns
FrIf_GetMacroticksPerCycle	Retrieves the amount of Macroticks per Cycle
FrIf_GetState	Get current FrIf state.

] (SRS_StbM_20035)

] (SRS_StbM_20043)

8.1.6.2 Optional Interfaces

This section defines all interfaces that are required to fulfill an optional functionality of the module.

[SWS_FrTSyn_00075]

<i>API function</i>	<i>Description</i>
Crc_CalculateCRC8H2F	This service makes a CRC8 calculation with the Polynomial 0x2F on Crc_Length
Det_ReportError	Service to report development errors.
FrIf_Transmit	Requests the sending of a PDU.
StbM_BusSetGlobalTime	Allows the Timebase Provider Modules to forward a new Global Time to the StbM, which has been received from different busses.
StbM_GetCurrentTime	Returns a time value (Local Time Base derived from Global Time Base) in standard format.
StbM_GetOffset	Allows the Timebase Provider Modules to get the currentoffset time.
StbM_SetOffset	Allows the Customers and the Timebase Provider Modules to set the offset time that has to be valid for the system.

] (SRS_StbM_20043)

9 Sequence diagrams

9.1 StbM_GetCurrentTime <Master FR SYNC>




Figure 5: Master FR SYNC

9.2 StbM_BusSetGlobalTime <Slave FR SYNC>




Figure 6: Slave FR SYNC

10 Configuration specification

In general, this chapter defines configuration parameters and their clustering into containers. In order to support the specification section 10.1 describes fundamentals. It also specifies a template (table) you shall use for the parameter specification. We intend to leave section 10.1 in the specification to guarantee comprehension.

Section 10.2 specifies the structure (containers) and the parameters of the Time Synchronization over FlexRay.

Section 10.3 specifies published information of the Time Synchronization over FlexRay.

10.1 How to read this chapter

For details, refer to the chapter 10.1 “Introduction to configuration specification” in *SWS_BSWGeneral*.

10.2 Containers and configuration parameters

The following sections summarize all configuration parameters of the Time Synchronization over FlexRay. The detailed meaning of the parameters is described in chapters 7 and 8.

10.2.1 Variants

[SWS_FrTSyn_00076]

[The Time Synchronization over FlexRay shall support the configuration variants VARIANT-PRE-COMPILE, VARIANT-LINK-TIME, and VARIANT-POST-BUILD.
](SRS_BSW_00396)


[SWS_FrTSyn_00077]

[The Time Synchronization over FlexRay shall support the configuration for Time Master, Time Slave and Time Gateway.
](SRS_StbM_20038)

10.2.2 FrTSyn

SWS Item	ECUC_FrTSyn_00001 :	
Module Name	FrTSyn	
Module Description	This represents the specific configuration variant for the TSyn on Flexray.	
Post-Build Variant Support	true	

Included Containers		
Container Name	Multiplicity	Scope / Dependency
FrTSynGeneral	1	This container holds the general parameters of the Flexray-specific Synchronized Time-base Manager
FrTSynGlobalTimeDomain	1..*	This represents the existence of a global time domain on Flexray. The FrTSyn module can administrate several global time domains at the same time that in itself form a hierarchy of domains and sub-domains. If the FrTSyn exists it is assumed that at least one global time domain exists.



10.2.3 FrTSynGeneral

SWS Item	ECUC_FrTSyn_00003 :
Container Name	FrTSynGeneral
Description	This container holds the general parameters of the Flexray-specific Synchronized Time-base Manager
Configuration Parameters	

SWS Item	ECUC_FrTSyn_00002 :
Name	FrTSynDevErrorDetect
Description	Switches the Default Error Tracer (Det) detection and notification ON or OFF.

	<ul style="list-style-type: none"> • true: enabled (ON). • false: disabled (OFF). 		
Multiplicity	1		
Type	EcucBooleanParamDef		
Default value	--		
Post-Build Variant Value	false		
Value Configuration Class	<i>Pre-compile time</i>	X	All Variants
	<i>Link time</i>	--	
	<i>Post-build time</i>	--	
Scope / Dependency	scope: local		

SWS Item	ECUC_FrTSyn_00016 :		
Name	FrTSynMainFunctionPeriod		
Description	Schedule period of the main function FrTSyn_MainFunction. Unit: [s].		
Multiplicity	1		
Type	EcucFloatParamDef		
Range	0 .. INF		
Default value	--		
Post-Build Variant Value	false		
Value Configuration Class	<i>Pre-compile time</i>	X	All Variants
	<i>Link time</i>	--	
	<i>Post-build time</i>	--	
Scope / Dependency	scope: local		

SWS Item	ECUC_FrTSyn_00019 :		
Name	FrTSynVersionInfo		
Description	Activate/Deactivate the version information API (FrTSyn_GetVersionInfo). True: version information API activated False: version information API deactivated.		
Multiplicity	1		
Type	EcucBooleanParamDef		
Default value	--		
Post-Build Variant Value	false		
Value Configuration Class	<i>Pre-compile time</i>	X	All Variants
	<i>Link time</i>	--	
	<i>Post-build time</i>	--	
Scope / Dependency	scope: local		


Included Containers			
Container Name	Multiplicity	Scope / Dependency	
FrTSynGlobalTimeOfsDataIDList	1	The DataIDList for OFS messages ensures the identification of data elements due to CRC calculation process.	
FrTSynGlobalTimeSyncDataIDList	1	The DataIDList for SYNC messages ensures the identification of data elements due to CRC calculation process.	

10.2.4 FrTSynGlobalTimeSyncDataIDList

SWS Item	ECUC_FrTSyn_00023 :		
Container Name	FrTSynGlobalTimeSyncDataIDList		

Description	The DataIDList for SYNC messages ensures the identification of data elements due to CRC calculation process.	
Configuration Parameters		

Included Containers		
Container Name	Multiplicity	Scope / Dependency
FrTSynGlobalTimeSyncDataIDListElement	16	Element of the DataIDList for SYNC messages ensures the identification of data elements due to CRC calculation process.



10.2.5 FrTSynGlobalTimeSyncDataIDListElement

SWS Item	ECUC_FrTSyn_00025 :
Container Name	FrTSynGlobalTimeSyncDataIDListElement
Description	Element of the DataIDList for SYNC messages ensures the identification of data elements due to CRC calculation process.
Configuration Parameters	

SWS Item	ECUC_FrTSyn_00026 :		
Name	FrTSynGlobalTimeSyncDataIDListIndex		
Description	Index of the DataIDList for SYNC messages ensures the identification of data elements due to CRC calculation process.		
Multiplicity	1		
Type	EcucIntegerParamDef		
Range	0 .. 15		
Default value	--		
Post-Build Variant Value	false		
Value Configuration Class	Pre-compile time	X	All Variants
	Link time	--	
	Post-build time	--	
Scope / Dependency	scope: local		


SWS Item	ECUC_FrTSyn_00027 :		
Name	FrTSynGlobalTimeSyncDataIDListValue		
Description	Value of the DataIDList for SYNC messages ensures the identification of data elements due to CRC calculation process.		
Multiplicity	1		
Type	EcucIntegerParamDef		
Range	0 .. 255		
Default value	--		
Post-Build Variant Value	false		
Value Configuration Class	Pre-compile time	X	All Variants
	Link time	--	
	Post-build time	--	
Scope / Dependency	scope: local		

No Included Containers

10.2.6 FrTSynGlobalTimeOfsDataIDList

SWS Item	ECUC_FrTSyn_00024 :		
Container Name	FrTSynGlobalTimeOfsDataIDList		
Description	The DataIDList for OFS messages ensures the identification of data elements due to CRC calculation process.		
Configuration Parameters			

Included Containers			
Container Name	Multiplicity	Scope / Dependency	
FrTSynGlobalTimeOfsDataIDListElement	16	Element of the DataIDList for OFS messages ensures the identification of data elements due to CRC calculation process.	



10.2.7 FrTSynGlobalTimeOfsDataIDListElement

SWS Item	ECUC_FrTSyn_00028 :
Container Name	FrTSynGlobalTimeOfsDataIDListElement
Description	Element of the DataIDList for OFS messages ensures the identification of data elements due to CRC calculation process.
Configuration Parameters	

SWS Item	ECUC_FrTSyn_00029 :		
Name	FrTSynGlobalTimeOfsDataIDListIndex		
Description	Index of the DataIDList for OFS messages ensures the identification of data elements due to CRC calculation process.		
Multiplicity	1		
Type	EcucIntegerParamDef		
Range	0 .. 15		
Default value	--		
Post-Build Variant Value	false		
Value Configuration Class	Pre-compile time	X	All Variants
	Link time	--	
	Post-build time	--	
Scope / Dependency	scope: local		

SWS Item	ECUC_FrTSyn_00030 :		
Name	FrTSynGlobalTimeOfsDataIDListValue		
Description	Value of the DataIDList for OFS messages ensures the identification of data elements due to CRC calculation process.		
Multiplicity	1		
Type	EcucIntegerParamDef		
Range	0 .. 255		
Default value	--		
Post-Build Variant Value	false		
Value Configuration Class	Pre-compile time	X	All Variants
	Link time	--	
	Post-build time	--	
Scope / Dependency	scope: local		

No Included Containers

10.2.8 FrTSynGlobalTimeDomain

SWS Item	ECUC_FrTSyn_00004 :		
Container Name	FrTSynGlobalTimeDomain		
Description	This represents the existence of a global time domain on Flexray. The FrTSyn module can administrate several global time domains at the same time that in itself form a hierarchy of domains and sub-domains. If the FrTSyn exists it is assumed that at least one global time domain exists.		
Configuration Parameters			


SWS Item	ECUC_FrTSyn_00005 :		
Name	FrTSynGlobalTimeDomainId		
Description	The global time domain ID.		
Multiplicity	1		
Type	EcucIntegerParamDef		
Range	0 .. 31		
Default value	--		
Post-Build Variant Value	false		
Value Configuration Class	Pre-compile time	X	All Variants
	Link time	--	
	Post-build time	--	

Scope / Dependency	scope: local
---------------------------	--------------

SWS Item	ECUC_FrTSyn_00022 :
Name	FrTSynGlobalTimeSequenceCounterJumpWidth
Description	The SequenceCounterJumpWidth specifies the maximum allowed gap of the Sequence Counter between two SYNC resp. two OFS messages.
Multiplicity	1
Type	EcucIntegerParamDef
Range	1 .. 15
Default value	--
Post-Build Variant Value	false
Scope / Dependency	scope: local

SWS Item	ECUC_FrTSyn_00018 :									
Name	FrTSynSynchronizedTimeBaseRef									
Description	Mandatory reference to the required synchronized time-base.									
Multiplicity	1									
Type	Symbolic name reference to [StbMSynchronizedTimeBase]									
Post-Build Variant Value	false									
Value Configuration Class	<table border="1"> <tr> <td>Pre-compile time</td> <td>X</td> <td>All Variants</td> </tr> <tr> <td>Link time</td> <td>--</td> <td></td> </tr> <tr> <td>Post-build time</td> <td>--</td> <td></td> </tr> </table>	Pre-compile time	X	All Variants	Link time	--		Post-build time	--	
Pre-compile time	X	All Variants								
Link time	--									
Post-build time	--									
Scope / Dependency	scope: local									

Included Containers		
Container Name	Multiplicity	Scope / Dependency
FrTSynGlobalTimeMaster	0..1	Configuration of the global time master. Each global time domain is required to have exactly one global time master. This master may or may not exist on the configured ECU.
FrTSynGlobalTimeSlave	0..1	This represents the time slave for the enclosing global time domain.



10.2.9 FrTSynGlobalTimeMaster


SWS Item	ECUC_FrTSyn_00006 :
Container Name	FrTSynGlobalTimeMaster
Description	Configuration of the global time master. Each global time domain is required to have exactly one global time master. This master may or may not exist on the configured ECU.
Configuration Parameters	

SWS Item	ECUC_FrTSyn_00013 :
Name	FrTSynGlobalTimeTxCrcSecured
Description	This represents the configuration of whether or not CRC is supported.
Multiplicity	1
Type	EcucEnumerationParamDef
Range	CRC_NOT_SUPPORTED CRC_SUPPORTED
	This represents a configuration where CRC is not supported. This represents a configuration where CRC is supported.
Post-Build Variant Value	false
Value Configuration Class	Pre-compile time X All Variants Link time -- Post-build time --
Scope / Dependency	scope: local

SWS Item	ECUC_FrTSyn_00014 :
Name	FrTSynGlobalTimeTxPeriod
Description	This represents the TX period. Unit: seconds
Multiplicity	1
Type	EcucFloatParamDef

Range	0 .. INF	
Default value	--	
Post-Build Variant Value	false	
Value Configuration Class	Pre-compile time	X All Variants
	Link time	--
	Post-build time	--
Scope / Dependency	scope: local	

Included Containers		
Container Name	Multiplicity	Scope / Dependency
FrTSynGlobalTimeMasterPdu	1	This container carries all properties required to configure the PDU sent by the global time master for the given global time domain.



10.2.10 FrTSynGlobalTimeMasterPdu

SWS Item	ECUC_FrTSyn_00008 :
-----------------	----------------------------

Container Name	FrTSynGlobalTimeMasterPdu
Description	This container carries all properties required to configure the PDU sent by the global time master for the given global time domain.
Configuration Parameters	

SWS Item	ECUC_FrTSyn_00007 :		
Name	FrTSynGlobalTimeMasterConfirmationHandleId		
Description	This represents the handle ID of the PDU that contains the global time information.		
Multiplicity	1		
Type	EcucIntegerParamDef (Symbolic Name generated for this parameter)		
Range	0 .. 65535		
Default value	--		
Post-Build Variant Value	false		
Value Configuration Class	Pre-compile time	X	All Variants
	Link time	--	
	Post-build time	--	
Scope / Dependency	scope: local		

SWS Item	ECUC_FrTSyn_00020 :		
Name	FrTSynGlobalTimePduRef		
Description	This represents the reference to the Pdu taken to transmit the global time information. The global time master of a global time domain acts as the sender of the Pdu while all the time slaves are supposed to receive the Pdu.		
Multiplicity	1		
Type	Reference to [Pdu]		
Post-Build Variant Value	true		
Value Configuration Class	Pre-compile time	X	VARIANT-PRE-COMPIL
	Link time	--	
	Post-build time	X	VARIANT-POST-BUILD
Scope / Dependency	scope: local		

No Included Containers


10.2.11 FrTSynGlobalTimeSlave

SWS Item	ECUC_FrTSyn_00010 :		
Container Name	FrTSynGlobalTimeSlave		
Description	This represents the time slave for the enclosing global time domain.		
Configuration Parameters			

SWS Item	ECUC_FrTSyn_00017 :		
Name	FrTSynRxCrcValidated		
Description	This parameter controls whether or not CRC validation shall be supported.		
Multiplicity	1		
Type	EcucEnumerationParamDef		
Range	CRC_IGNORED	The FrTSyn accepts time synchronization messages with all Types. The CRC will be ignored.	
	CRC_NOT_VALIDATED	The FrTSyn accepts time	

		synchronization messages with Type equal to 0x10, 0x30 without validating the CRC. All other time synchronization messages are ignored.
	CRC_VALIDATED	The FrTSyn accepts time synchronization messages with Type equal to 0x20, 0x40 with a correct CRC value. All other time synchronization messages are ignored.
Post-Build Variant Value	false	
Value Configuration Class	Pre-compile time	X All Variants
	Link time	--
	Post-build time	--
Scope / Dependency	scope: local	

Included Containers			
Container Name	Multiplicity	Scope / Dependency	
FrTSynGlobalTimeSlavePdu	1	This container carries all properties required to configure the PDU received by the time slave for the given global time domain.	




10.2.12 FrTSynGlobalTimeSlavePdu

SWS Item	ECUC_FrTSyn_00012 :
Container Name	FrTSynGlobalTimeSlavePdu
Description	This container carries all properties required to configure the PDU received by the time slave for the given global time domain.
Configuration Parameters	

SWS Item	ECUC_FrTSyn_00011 :									
Name	FrTSynGlobalTimeSlaveHandleId									
Description	This represents the handle ID of the PDU that contains the global time information.									
Multiplicity	1									
Type	EcucIntegerParamDef (Symbolic Name generated for this parameter)									
Range	0 .. 65535									
Default value	--									
Post-Build Variant Value	false									
Value Configuration Class	<table border="1"> <tr> <td>Pre-compile time</td> <td>X</td> <td>All Variants</td> </tr> <tr> <td>Link time</td> <td>--</td> <td></td> </tr> <tr> <td>Post-build time</td> <td>--</td> <td></td> </tr> </table>	Pre-compile time	X	All Variants	Link time	--		Post-build time	--	
Pre-compile time	X	All Variants								
Link time	--									
Post-build time	--									
Scope / Dependency	scope: local									

SWS Item	ECUC_FrTSyn_00021 :		
Name	FrTSynGlobalTimePduRef		
Description	This represents the reference to the Pdu taken to transmit the global time information. The global time master of a global time domain acts as the sender of the Pdu while all the time slaves are supposed to receive the Pdu.		
Multiplicity	1		
Type	Reference to [Pdu]		
Post-Build Variant Value	true		
Value Configuration Class	Pre-compile time	X	VARIANT-PRE-COMPILE
	Link time	--	
	Post-build time	X	VARIANT-POST-BUILD
Scope / Dependency	scope: local		

No Included Containers


10.3 Published Information

For details, refer to the chapter 10.3 “Published Information” in *SWS_BSWGeneral*.